

GENL #172 8 SEPT 82

000191

NO. 172 (1982)
SEPTEMBER 8, 1982

DIMAC RESOURCE CORP.

82M / 13E
Tungsten

082M 136

Hole No.	Zone	Interval		Width		Tungsten WO3 %	
DDH-82-1	Lower	3 ft. 6 in.	to 10 ft. 10 in.	7 ft. 4 in.		3.22%	
		21	10	28	4	6 6	1.05
		32	1	34	6	2 5	1.08
		39	2	43	-	3 10	3.51
		45	-	47	2	2 2	3.96
		49	6	51	9	2 3	1.77
	Upper	107 ft. 10 in.	110 ft. 1 in.	2 ft. 3 in.			2.09%
		110	9	111	6	9 -	1.34
		125	11	131	4	5 6	3.97
		131	4	134	10	3 6	1.00
		140	5	141	4	11 -	1.30
		148	-	151	-	3 -	0.069
DDH-82-2	Lower	12 ft. - in.	12 ft. 8 in.	8 ft. - in.			1.32%
		13	3	14	3	1 -	8.14
		22	3	28	3	6 -	2.50
		29	9	35	3	5 6	3.07
		48	1	48	6	- 5	1.72
		52	1	55	9	3 8	1.57
		61	8	63	5	1 9	3.18
		66	10	69	9	2 11	1.65
		76	3	79	1	2 10	3.61
	Upper	153	3	154	11	1 8	1.62
		167	11	169	-	1 1	1.22%

M. McClaren, director of Dimac Resource Corp., has reported that the diamond drilling program on the ~~Silence Lake~~ tungsten mine 80 miles north of Kamloops, B.C. which started in mid-July has been completed. A total of 1,561 feet in eight holes was drilled. Prior to the drilling program unmined ore reserves were estimated at 10,555 tons. The drilling program did not establish the presence of additional ore reserves, however, additional potential still exists along strike. In addition, two further

geologically favourable areas remain to be drill tested. Dimac is negotiating with a major mining company to arrange for further exploration work on the property which may include additional diamond drilling. Diamond drill holes 82-1 and 82-2 intersected the lower portions of the known mineralized zones at the back of the presently established pit.

The tungsten concentrating plant is operating at a rate of 100 to 120 tons per day.