

W.A. No.

NAME SILVER GIANT

SUBJECT REPORTS

82KJED018-07
PROPERTY FILE
003741

NOTES ON THE GIANT VEIN DEVELOPMENTS. # Tunnel, with Assays.

These notes are more particularly, in connection with the physical conditions on the #6 Tunnel, which is vertically below the level of #5 Tunnel 108' at their respective entrances.

The vein is contained between two slate belts, and its strike on the Hanging wall is N 45.43'W, and its dip on the average 53 degrees to the S.W. Attention however is called to the reverse dip, on the East side of the tunnel, and at the contact with the slates, at which point the latter dip 88 degrees to the N.E, meeting the dip of the vein, at a point 3 feet vertically above the floor, and apparently at this place, proving to be the master dip. I will take up this matter later on. The slates are blocky and different to those on the Footwall, the latter being the dog-tooth black slates, and between these and the main ore-body, there is 12 feet of the same blocky slate, and I am inclined to believe that the Fissure - the nearest one shown on the map is probably the real Footwall.. The strike of the slates on the Hanging wall is N 79.17E, and their dip 72 degrees SE. The vein then cuts the slates at an obtuse angle of 55 degrees horizontally, and 19 degrees vertically. Whether it cuts through the enclosing slates below the present level, has yet to be proved. I am inclined to believe that the reverse dip has been caused by a local thrust of the Fault C D shown on the plan attached to these notes.

This Fault is a very large one and is responsible for lots of trouble but has a great deal to do with the large amount of fissuring, which I will call attention to later. Just where this fault is seen in the tunnel, the gouge and crushed material is 30" thick, but this has increased to 4', at a point 14' N.W., showing it to be a very large fault.

The course of the slates on the F.W. is different to that of those on the H.W. being N 76.30W, whilst that of the Fissure mentioned as being the likely F.W. is N60.43W, which latter is more like that of the H.W.

VEIN. The general structure appears to be that of a fissured mineral zone, as along its width we find several well defined Fissures, one of which appears to have the merit of having more to do with the

PROPERTY FILE

mineral occurrences than any of the others. I will first mention the positions of these fissures, so as to have some record of them, for future use probably.

The first one is that which forms the Hanging wall. This is a distinct fissure, cutting the slates as it does.

The second fissure, is the water fissure, 30 feet in, from the H.W. When struck a flood of water broke loose, and has been running ever since. It also dislocated the source of supply for the Power house, since this had been taken from the #5 tunnel level, but which now vanished, showing some underground connection between the two tunnels, in the vein system, and along which the water had been running. Work had to be stopped and a new source of water found, owing to this occurrence.

The third Fissure is a flattish one, which starts just where the East Drift is, and on the right side going in. It dips 46 degrees to the S.W, but joins the 4th Fissure in the roof, at the point in the F.W. of the East Drift, so that this latter is driven along a double line of fissuring.

Fourth Fissure. This strikes a general course of SE and dips 75 degrees to the S.W. Its course is rather winding however, but nevertheless it is a very strong one. Between the two fissures is crushed slate, gouge and some ore, and we get some good Bornite ore, in stringers, with no commercial ore in quantity.

The width between these two fissures is only 7 feet measured along the foot of the crosscut, but as mentioned, they unite in the roof.

The fifth Fissure is the one I think may be the F.W, as next to it, the blocky slates are in strong evidence. for 12 feet, and as on the H.W. we have the same character of blocky slate, I think that perhaps I may be justified in calling this fissure the Footwall.

I do not often quote matter from test books, but happening to have one with me, I find such a good description of such a vein as is here, that I venture to quote same. The book is called "Pocket Manual of Mining" by Messrs. Chewett and Canniff, see page 4 under Geology. 1897 Issue.

"Many deposits show evidence of being a series of parallel
"fissures close together, produced by compression. (crushed
"zones). The metalliferous fluids are supposed to have flowed
"along these fissures, attacking the country rock on each side,

"dissolving the rock and replacing it gradually with the metal sulphides (this has been termed metasomatic replacement) The gold bearing iron and copper sulphides of the Trail Creek district give strong indications that they are of this character. This will explain the irregular width of many of the veins, and gradual fading away of the mineral into the country rock. Veins are often faulted by another fissure cutting across it and breaking its continuity. In four cases out of five the continuation will be found by assuming the narrow based body has slipped down the faulting plane."

The gangue appears to be Barytes, mostly white as to color, and very heavy. It is Barium Sulphate and generally speaking the ore occurrences are associated with this mineral. I note also limestone and quartz in the vein. The latter is very hard and appears to be an innovation, as I have not noticed its appearance in such quantity in the Upper levels. Slate also is associated in the gangue and the principal fissure mentioned is in this material, which is crushed and has considerable gouge.

I may also call attention to a feature noticed when sampling viz the vein structure has ribs of gangue laid in a Northerly direction - Magnetic North- I have shown this at point C in the tunnel, dipping 65 degrees N.W. The strike of the lenses is similar, also to the strike of Fault A, which latter has been cut by the workings from the West Drift. The same ribbed structure is seen in the ore in the West Drift, and also in the East Drift.

The width of the vein is a variable one depending just where to figure the Footwall to be. One reason for taking the width as being that contained between the two slate belts, is that ore has been found in the right hand corner of the main tunnel at the face, same being contained between the god-tooth slates and the blocky slates. My opinion is that ore may be found anywhere, since the low grade mineral zone may extend further N.E. But for the present vein system, I think the real Footwall is the line of Fissuring which I have marked as being the possible footwall, and the ore found beyond is a chance lens.

If we take the two slates belts as being on either wall, the width between them at the narrowest part is 79 feet, but it will be noticed that the width increases very fast, the further East one goes.

This width is 82'6 if the fissure mentioned is taken as the footwall, and it lines up better with the strike of the H.W. than the strike of the slates do.

I may mention another occurrence, which may have some bearing on the genesis or birth of the vein viz on the inner side of the H.W is 4 ft. of whitish rock, which is called a dike locally, then 4 ft of blocky slate, then 1 ft. similar rock, then 13 ft blocky slate, then Barytes. The rock however appears to be a siliceous limestone however and may have no bearing or significance on the vein at all, but it is next the H.W and I mention same. Another feature is the reverse dip of the slates on the H.W in one corner, where it is 88 degrees to the N.E. The vein dips in its correct position to a point about 3 ft vertically above the floor of the tunnel, when it meets this reverse dip mentioned, I think however, as noted already, that this results from a local thrust and that Fault C D is responsible for this, as well as the fissuring in the vein, and Fault A for the later fissuring forming the strike of the lenses, and the mineral solutions found entrance by the fissures, and entered the cracks and breaks formed by the movement of Fault A.

ORE. This is Galena, Chalcopyrite, Bornite and Iron Pyrite contained in lenses as shown on the tracing plan, and the length of these lenses apparently is contained and prescribed as being that between the Water Fissure and the F.W. Fissure. The importance then of these fissures being located properly, and being understood, is then evident, and it is only by observance of such phenomena as these that success in mining a proposition, such as this, may be achieved, provided the mineral is of proper grade and value.

There is hardly any ore seen up to a point 51 feet in from the H.W and although the gangue is favorable to ore, it is not until this point is reached that ore showed up. Occasionally in this 51 ft distance a little ore might be seen, but no body.

From the 51' point ore was found in the tunnel, with one break on the right side, and with two breaks or blanks on the left, as far as the F.W.

DEVELOPMENT. Number 6 Tunnel was driven, until the vein was struck at 942.75 ft, and extended until it reached the black dog tooth slates at 1048.75 feet. At a point 60 feet from the H.W a drift both East and West was started and the latter having reached the objective was stopped. It was driven 40 feet and a crosscut to the N.W driven for 19 feet, when the downward continuation of the fault found on #5 level, was encountered.

As I had previously surveyed the position of this fault, and calculated its probable position on #6 level, and got it almost exactly where figured, it appears as if this fault, is a factor to be reckoned with. It is unfortunate that it has come just where it is, for it makes the mine lop-sided, since at present it has only one side, viz the East to develop. Another bad feature is that it is an expensive business to undertake to find the vein, to the West of this fault, since it is quite a gamble. My opinion is that it may be found to the North, and on the West of the fault, and a diamond drill hole will be the cheapest way to locate the vein. When found its length on the strike, before it is again cut off by fault C D, will be only about 75 feet, so that when found and this short distance developed, diamond drilling will again have to be done to find it the second time. This is therefore why it is an expensive business when faults intervene.

On the East side of the tunnel, the vein is followed along the Fissure and the ore continues for 17' when it cuts out on the right side going in. The main body of ore stops at 8' however. A fault then appears cutting out the vein and limestone fills the drift with Barytes on the left side. The contact between the barytes and the limestone is being followed at present.

I should state that the ore on the west side cuts out in 7 feet.

SAMPLING AND ASSAYS. The vein was sampled very thoroughly in the following manner. Channels 4 inches wide were cut horizontally across the vein every five feet at two places viz each about 1 to 1.5 ft from the roof and floor and each sample is from a width of 5 feet, except in two instances mentioned on the map. Wherever the vein was apparently barren of values, as in the blocky slates, it was not sampled, but every foot on each side of the main tunnel, in the vein was sampled. When the samples were brought to day-light and examined carefully, and little or no ore seen, they were thrown out. Samples from 50 lbs up were taken by hammer and moil and brought down by successive quarterings, and then the resultant sample put through the rock crusher and again brought down until from 1 to 2 lbs were left, and these sent for assay.

The vein up to 51 feet was found to be almost destitute of ore although isolated appearances of ore, were occasionally seen and their positions

noted, but there was no ore found, up to the point named, that was worth sampling and assaying, although as stated every foot was sampled.

East side of main tunnel. From 51' to 76' horizontally or which distance amounts to 17' at right angles to the dip of the vein, ore was found. Then a barren distance of 20'6 taken up by Barytes and Blocky Slates. At 96'6 to 104'6 galena ore was found on the floor of the tunnel, or in its right hand corner, and to extend up from the floor about 18" high. This ore is of better grade than the bulk of the samples taken, but it does not extend to the West side of the tunnel, and if we take the strike of this lens as being that of the others, then it appears to have a very short life. Its width appears to be 5 ft at right angles to the strike of the lens.

West side of main tunnel. Ore was found from 51' to 56', then a space of 10' was found to be almost barren of ore, then ore from 66' to 88'6 making 27'6 in all.

AVERAGE VALUES OF ORE.

In the following calculations I have not figured in the values of the lens found in the right hand corner of the main crosscut, for it does not extend to the East Drift, and is certainly bound to be cut off by the black slates. I have however placed the assays and width of all samples in the map.

The average width of ore sampled is 26 feet and although this width is greater than the combined width of the lenses, I have to take it in order to figure the average values.

This 26 feet represents only 24.4% of the vein taking 79' as its width. The list of assays seen on the plan, and figured out into their foot units gives the following averages.

| | Ozs silver | % lead | % copper |
|-----------------------|------------|--------|----------|
| East side Tunnel. 25' | 1.3 | 5.38 | .84 |
| West side tunnel 27.5 | 0.94 | 3.08 | .54 |

The two sides then average for a width of 26.25 feet the following

| Ozd silver | % lead | % copper |
|------------|--------|----------|
| 1.11 | 4.17 | .68 |

In these calculations I have not taken into account the three roof samples, which are lower than the majority of the samples, except

Perhaps in copper, but in order to find the copper content over its apparent width of 6 ft at right angles to the strike of the lenses, I have used them along with the three samples on each side, and get the following for the copper and other values.

| Oz s silver | % lead | % copper |
|------------------------|--------|----------|
| 1.32 | 1.87 | 1. |

In the width of the larger lens and which is 10 feet only, there is 6 feet of it assaying these figures.

ESTIMATED TONNAGE.

In order to give an idea of the tonnage probably in sight between the two tunnels viz #5 and 6, I have figured the following dimensions for the two lenses taken.

| | | | |
|--|-----------|-------|------------|
| West Lens. Length 20' x 2 ft in width. | 100 backs | 4000 | dubic feet |
| Central Lens. Length 40' x 10' | do | 40000 | do |
| | | ----- | |
| Total cubic feet | | 44000 | |

Since the percentage of galena or rather lead is so small, 10 cubic feet will be about right to take for a ton of ore and this then results in there being possible to be mined from these lenses 4,400 tons of ore.

I have taken 100 feet as the depth for easy figuring, but 94.5 ft is the correct depth immediately over the present workings, owing to the sharper grade of #6 tunnel over that of #5. On the other hand the lenses have a dip which will make the difference about right.

CONCLUSIONS

The grade of the ore is very low as a general thing and much too low for even successful milling, and unless better grade ore can be found in quantity by development work, I would be afraid to recommend you to consider a mill for the present.

The figures of tonnage submitted for the ore found to date, are not very re-assuring either, and hopes for the future have to be based on the work being pushed on the East side, where already we have been in waste for more than 20 feet.

Usually when one drives on ore in a vein, he expects it to continue for some reasonable distance. Here on the other hand it cuts out almost as soon as found.

I trust that the findings here will not cause you to discontinue work, for there is still a chance. Diamond drilling might be of use, but the

holes will have to be intelligently placed in a lens formation of this sort.

The only chance is the mining gamble of finding better grade ore Easterly

Yours faithfully,

"J.L.PARKER"

Mining Engineer.

The Giant Mine,
Spillimachene B.C.
November 11 1929.

Report by J.L. Parker
Nov. 11/1929
on Golden Giant Mine

ALEXIS MARTIN
Barrister & Solicitor
227-8 Pemberton Bldg.
Victoria, B.C.

The Giant Mine
Galena Post Office.
September 5th. 1930.

A.B. Trites, Esq.
President Pacific Mines, Ltd.
Vancouver, B.C.

Dear Sir:-

Diamond Drill Hole #22

In case anyone should be going down in time to catch the train going in to Golden, I am getting this ready.


The enclosed sketch shows the position of the Lens at Drill Hole 14, and its continuance if it kept its route.

At a point, however, viz. at 271 ft. we got the change from the slates and at 275 ft. the regular "shut out quartz" and this AM am down to the 300 ft. point in Drill Hole, ie, drill hole is down 300 ft.

I think that there is no earthly chance of finding any ore in this formation but will drill to around 350 ft. so as to give every chance and may drill deeper, but am afraid the engine will not stand for it. Anyway the situation is hopeless.

The line of shut out takes us to where we get it in D.D. Hole No. 16 and it apexes here - then descends to where we got it in Hole 17.

Sectional Elevation




This quartz then apexes as shown and descends on two sides and shuts out the ore.

We have tried it so often but only Holes 14 and 16 penetrated to any depth.

These are the points in Drill-Holes where we got the quartz and as they were all at steep angles, this will give you some idea of the relative depths.

"J.L.Parker"

The above is a copy of a letter sent to Mr. Trites just as was written by me and shows very clearly how the quartz - the barren quartz - shuts out the ore formation.



COPY

82K/16W
82K/NE-18

REPORT ON MINING OPERATIONS-GIANT MINE B.C.

Following up my report of November 11th, 1929, the following work has been done since that date.

600 ft Level

Drift East - driven 55 feet,
North East Crosscut driven 85 feet.

This gives 35 feet of low grade ore at right angles to the strike.

The following drill stations were made:

| | |
|------------------|------------------------|
| Drill Station #1 | 16' x 3' x 20' height |
| " #2 | 15' x 15' x 8' |
| " #3 | 10' x 6' |
| " #4 | 10' x 10' x 16' height |
| " #5 | 8' x 8' x 16' " |

Diamond Drilling 4101 feet

RESULTS

The ore on the East drift cut out at 8 ft. on the left side going in and 17 ft. on the right hand side, when a fault occurred and the altered limestone came in and continued for the length of the drift. The N.E. crosscut was then started and driven for 85 ft. to the F.W. At 16 ft, the barytes came in and from here to the face we had ore more or less all the way until the turn to the left was made, as shown on the tracing. This length of 45 ft., however, is longer than the true width of the ore, owing to its slanting angle & 35 ft. is its true width. The ore assayed a little less than 4% Lead for this width.

DIAMOND DRILL

Starting in this year a Contract was let to Boyle Brothers to do 1,000 ft. of drilling as a minimum, with a slightly reduced rate if 2000 ft. were done and at a further slight reduction if 3000 ft. were done and it was never contemplated that the 3000 ft. would be exceeded, but owing to getting such unfavourable results, work was carried over the 4000 ft. point in the hope that better results might be obtained. These hopes, were however, disappointing as the following synopsis will show:

Since 10 Diamond Drill holes had been drilled at a previous period, the first hole of 1930 is called No. 11 on 600 ft. level, Drill Station No. 1.

No. 11 Diamond Drill Hole

| | |
|---|----------------------------|
| Vertical angle - 26 degrees 55' N 72.53 E | Distance drilled 285 ft. |
| #503 Sample of Core 202' - 205' - 3 ft. | 2.98 oz. silver 11.8% Lead |
| #504 Sample of Sludge 200 - 205' | 1.82 " " 5.1% " |

PROPERTY FILE

No. 12 Diamond Drill Hole

- 23 degrees - 15' N 68 48 E from D. Station No. 2 - 600' level.
Distance drilled 142 ft.

| | | | |
|-------------|--------------------------|----------------|------------|
| Sample #508 | Core 48'6 - 51' - 2' -6" | .86 oz. silver | 3.7% Lead. |
| " #509 | " 80'9 - 84' - 3' -3" | 1.40 " " | 3.3% " |

No. 13 Diamond Drill Hole

From Drill Station No. 2

| Sample # | | | | <u>Oz. Silver</u> | <u>% Lead</u> |
|----------|--------------|---|------|-------------------|---------------|
| 510 | 23.6 to 25' | - | 1.6" | .76 | 16.8% |
| " # 511 | 29 to 34 | - | 5.0 | .80 | 12.2% |
| " 512 | 35 to 37.3 | - | 2.3 | .88 | 8.7 |
| " 513 | 39.9 to 40.6 | - | .9 | 1.02 | 12.2 |
| " 514 | 51.3 to 51.9 | - | .6 | 1.04 | 12.6 |
| " 515 | 57.0 to 60 | - | 3.0 | 52 | 10.4 |

From 23'6 - 60' - ore zone width 36' - 6".

As there is ore to the width of 13 ft. in 6 widths of ore and the intervening spaces not ore bearing, it will be necessary to work the whole width and the value works out to :-

.27 oz. silver
4.13% Lead for a width of 36' - 6"

No. 14 Diamond Drill Hole

From Drill Station No. 1

N. 45 31E - 44 degrees 27'
West of Main Tunnel on 600 ft. level Drilled to the 700 ft. level.

| | | | <u>Length 158 ft.</u> | <u>Oz. Silver</u> | <u>% Lead</u> |
|------------|----------|-----------|-----------------------|-------------------|--------------------|
| Sample 516 | 125' - 6 | 126' - 6" | - 1.0 | 1.28 | 7.7 |
| 517 | 137' | 139 | - 2.0 | 2.48 | 2.8) Average for |
| 518 | 139' | 144 | - 5.0 | 3.66 | 8.6) 12 ft.) |
| 519 | 144' | 148 | - 4.0 | 1.04 | 6.3) 2.33 oz. sil. |
| 520 | 148' | 149 | - 1.0 | .6 | 3.3) 6.42% Lead |

No. 15 Diamond Drill Hole

From Drill Station, No. 1

N. 75 56E - 39 degrees 07'

| | | | | |
|------------|-------------------------------|-------------|-----|-------|
| Sample 522 | 108.6 - 110 | - 1.6 | .8 | 15.8% |
| 523 | 141 | 143.6 - 2.6 | .5 | 1.1% |
| 524 | Composite sample 45-50) Gold | | | |
| | 50-55) Trace . | | .05 | |
| | 55-60) | | | |

This hole proved disappointing. Length 257'0"

No. 16 Diamond Drill Hole (Original 5A)

N. 66 23 E - 57 degrees 33' Reached 200' deeper than the 600 ft. level and up against the "Nose".

| Sample # | | | | | <u>Oz. Silver</u> | <u>% Lead</u> |
|----------|--------|----------|------------|------|-------------------|---------------|
| 525 | 115 | - 120 | - 5.0 | } | .52 | 5.7 |
| 526 | 120 | - 125 | - 5.0 | | 0.4 | 8.2 |
| 527 | 125 | - 127 | - 2.0 | | .24 | 2.9 |
| 528 | 155 | - 156 | - not sent | | - | - |
| 529 | 159 | - 160 | - 1.0 | 1.6 | 6.4 | |
| 530 | 162 | - 165 | - 3.0 | 3.7 | 12.0 | |
| 531 | 173'9" | - 175'3" | - 1.6 | 1.3 | 21.1 | |
| 536 | 179 | - 183 | - 4.0 | 3.6 | 17.2 | |
| 539 | 184 | - 187 | - 3.0 | 3.0 | 11.4 | |
| 540 | 187 | - 188.6 | - 1.6 | 1.4 | 9.8 | |
| 525 | 115 | - 120 | - 5.0 | 0.2 | 3.7 Sludge | |
| 526 | 120 | - 125 | - 5.0 | 0.32 | 7.2 Sludge | |
| 527 | 125 | - 127 | - 2.0 | .24 | 2.9 | |

Figuring the above we get:-

| | | | | <u>Oz. Silver</u> | <u>% Lead</u> |
|-------|---|-------|------------------|-------------------|---------------|
| 115 | - | 127 | - 12 ft. average | .42 | 6.27 |
| 159 | - | 165 | - 6 ft. " | 2.10 | 7.06 |
| 173'9 | - | 188'6 | - 14.9 " | 1.61 | 9.00 |

Practical working width 159' to 188'6 - 29'6" - 1.23 oz. silver 5.93% lead
and 12.0 .42 " 6.27% "

There is no Diamond Drill Hole No. 17

No. 18 Diamond Drill Hole

N. 74 10 E - 10 degrees 53'

Started from N.E. Crosscut 600 ft. level at Bend Length 140 ft.
Reached F.W. at 130 ft.

| | | | | | <u>oz. silver</u> | <u>% Lead</u> |
|-----|-------|---------|----------------------------|--|-------------------|---------------|
| 541 | 37'3 | - 39.0 | -1.9 Galena & Barytes | | 4.22 | 8.2 |
| 542 | 41.6 | - 42.6 | -1.0 " " | | 2.46 | 4.5 |
| 543 | 55.9 | - 61.9 | -6.0 " " | | 1.18 | 15.9 |
| 544 | 63 | - 64.9 | -1.9 " " | | 9.96 | 26.6 |
| 545 | 110 | - 116 | -6.0 Qtz. Barytes & Galena | | 1.2 | 5.8 |
| 546 | 76 | - 79 | -3 Galena Qtz. etc. | | 1.2 | 2.9 |
| 547 | 81 | - 81'6 | - .6 " & Barytes | | 2.66 | 6.8 |
| 548 | 83 | - 85 | -2. " " | | 0.10 | 2.3 |
| 549 | 105'6 | - 108 | -2.6 " " Qtz. | | 0.30 | 1.8 |
| 550 | 117 | - 119'6 | -2.6 " Barytes & Qtz. | | 1.00 | 8.00 |

The above widths of ore with their intervening barren widths, work out as follows:-

37.3 to 64.9 - 27.6 working width 1.25 5.23

The rest of the widths with assays mentioned are a negligible factor.

No. 19 Diamond Drill Hole

From corner N.E. Crosscut 600' level.

Course S. 80 degrees 54 E. - 10 degrees 38'
Length 192 ft.

This is in quartz all the distance and has been a severe disappointment. We first drilled 101 ft. and later resumed drilling in hopes of finding the quartz out out but this did not occur.

No. 20 Diamond Drill Hole

From Station Number 3

Course S. 7 - 51 E - 21 degrees Length 115 ft.

This is in quartz all the distance and has been a very severe disappointment.

No. 21 Diamond Drill Hole

There is no hole No. 21 as this was not drilled although conjectured to be drilled, but owing to Diamond Drill 19 & 20 being so disappointing it would have been a waste of money.

No. 22 Diamond Drill Hole

Course N. 56 degrees 42' ^{North} E. - 79 degrees 47'

From Drill Station No. 1. Length of hole - 329 ft.

This proved to be the best hole in the lot but the ore has very little length in the strike. It is up against the "Nose"

| | | | | | | oz. silver | % Lead |
|-----|-------|---|--------|------------------------|-----|----------------------|----------------|
| 551 | 129'6 | - | 131'6 | - | 2.0 | Galena Qtz & Barytes | 1.84 21.3 |
| 552 | 133 | , | 133 | - | 5.0 | " " " | 0;7 11.9 |
| 553 | 138 | - | 141 | - | 3.0 | " " " | 0.7 5.9 |
| 554 | 141 | - | 143 | - | 2.0 | " " " | 1.8 7.1 |
| 555 | 143 | - | 144 | - | 1.0 | " & Barytes | 7.36 23.0 |
| 556 | 146 | - | 151 | - | 5.0 | " " | 5.4 25.9 |
| 557 | 157'8 | - | 160'4 | - | 2.8 | " " | 2.96 14.5 |
| 558 | 160'4 | - | 162'6 | - | 2.2 | " " | 1.68 12.2 |
| 559 | 165 | - | 167 | - | 2.0 | Qtz. and Galena | 1.62 2.8 |
| 560 | 167 | - | 168'8 | - | 1.8 | " " | 1.24 7.7 |
| 561 | 180'5 | - | 187'9 | - | 7.4 | Galena & Barytes | 1.2 0.9 |
| 562 | 205 | - | 208 | - | 3.0 | " " | 1.12 2.9 |
| 563 | 208 | - | 213 | - | 5.0 | " " | 2.16 4.6 |
| 564 | 213 | - | 216 | - | 3.0 | " " | 0.92 2.5 |
| 565 | 216 | - | 219'6 | - | 3.6 | " " | 0.5 0.7 |
| 569 | 219'6 | - | 224' | - | 4.6 | " " | 1.4 4.0 Est. |
| 571 | 226 | - | 228 | - | 2.0 | " " & Qtz. | not assayed 3% |
| 572 | 228 | - | 231 | - | 3.0 | " " " | " " 1% |
| 573 | 232'6 | - | 236 | - | 3.6 | " " " | " " 1% |
| 566 | 316'0 | - | 316'6) | Sample of the ore only | | 2.6 | 40.2 |
| | 317'6 | - | 318'0) | or the two 6" streaks | | | |
| 567 | 322'6 | - | 325'0 | - | 2.6 | | 6.1 19.4 |
| 568 | 325 | - | 327'0 | - | 2.0 | | 1.4 4.8 |

| | | | | <u>SLUDGE SAMPLES</u> | | <u>Oz. Silver</u> | <u>%Lead</u> |
|-----|-----|---|-----|-----------------------|-----|-------------------|--------------|
| 628 | 315 | - | 320 | - | 5.0 | 2.0 | 34% |
| 629 | 320 | - | 325 | - | 5.0 | 5.0 | 24.5 |
| 630 | 325 | - | 329 | - | 4.0 | 2.69 | 9.6 |

Later figures a width of 10 ft. 3.25 oz. silver
23.6% Lead.

A summary of the practical working figures for the width of ore passed through is for H.W. ore.

129'6 to 168'8 - 39.2 on line of hole
- 32'0 at right angles to the dip of the lens.
Assaying 1.15 oz silver - 8.1% Lead.

F.W. Ore

| | | | |
|-----------------------|------|---|-------|
| 10 ft. sludge samples | 3.24 | - | 23.6% |
| core " | 3.75 | - | 17.8% |

These two ore bodies are separated by 145 ft. on line of hole and 130 ft. at right angles.

No. 24 Diamond Drill Hole
(There was no 23 hole drilled)
Drill Station No. 1.

Depth of Hole 240' 0".

Hole No. 24 is a vertical hole from 600 ft. level downwards. We got 11'6" of very low grade ore here - 157' to 168'6"

We got through slate at 135 ft. and got Barytes. We should not have had the latter until 137 ft. but a fault has occurred which figures to be the "Nose Fault"

From 135 to 170'6 proved to be ore formation and S #574 - 166 to 168 - 2' - 4.9% Lead. quartz came in at 173 and at 175, the silicified Limestone. The hole was continued to 240' in the same formation. This hole was a disappointment.

No. 25 Diamond Drill Hole

This hole along with No. 26 was drilled and D.D. Station No. 4 in the hopes of proving the ore to widen out on the strike line but proved disappointing in this respect.

Course S.29 - 43W - 66° 58'

| | | | | | | | |
|------------|-------|---|-------|---|-----|------------------|--------------|
| Sample 575 | 12.0 | - | 14.6 | - | 2.6 | Galena & Barytes | 20.4 |
| 576 | 17.0 | - | 18.6 | - | 1.6 | " " | 8.6 |
| 577 | 50.5 | - | 55.0 | - | 4.5 | " " | 12.6 |
| 578 | 63.5 | - | 65.0 | - | 1.5 | " " | 14.4) |
| 579 | 65 | - | 67.5 | - | 2.5 | " " | 33.6) |
| 580 | 69 | - | 73.0 | - | 4.0 | " " | 12.5) |
| 581 | 78 | - | 83.0 | - | 5.0 | " " | 19.1) |
| 582 | 83 | - | 86.6 | - | 3.6 | " " | 5.6) |
| 583 | 86.6 | - | 90.0 | - | 3.6 | Galena & Quartz | 11.8) 53'6 |
| 584 | 90 | - | 94.6 | - | 4.6 | " Barytes | 11.9) almost |
| 585 | 94.6 | - | 99 | - | 4.6 | " " | 24.2) on lin |
| 586 | 99 | - | 104 | - | 5.0 | " " Qtz. | 27.8) dip |
| 587 | 105 | - | 105'6 | - | 0.6 | " " | 6.9) 37.0 |
| 588 | 120'8 | - | 122 | - | 1.4 | " " | 38.6) waste |
| 589 | 122 | - | 125 | - | 3.0 | " " | 22.4) 90'6" |
| 590 | 126'6 | - | 128 | - | 1.6 | " " | 11.7) from |
| 591 | 135 | - | 138 | - | 3.0 | " " little slate | 7.5) 63'6"- |
| 592 | 138 | - | 139'8 | - | 1.8 | " Quartz | 4.2) 154' |
| 593 | 144'3 | - | 145'9 | - | 1.6 | " " | 5.4) is 90' |
| 594 | 147 | - | 150 | - | 3.0 | " " | 10.4) 6" of |
| 595 | 150 | - | 154 | - | 4.0 | " " | 5.8) which |

53'6" is ore & 37' waste. Ore only was assayed. This 53'6 - 18' at right angles to dip of Lens.

At 181 ft. we reached the silicified line and finished the hole at 192 ft. A practical summary of the working widths and values from the above.

On slope of hole 63'6 to 154.0 - 90' 6 - 9.96% lead.

This 90'6 is equivalent to 30 ft. at right angles to dip of lens.

This ore cutting out as it does at 154' and the ore formation being replaced at 181 ft. by the silicified lime, presents no encouraging features for future prospects.

No. 26 Diamond Drill Hole

S. 29 degrees 43 W - 57 degrees 14'

Started from Drill Station No. 4.

What ore was drilled here gave out at 147 ft. the quartz or silicified lime taking the place of the ore formation.

| | | | | | | |
|-----|-------|----|-------|------|-------|----------------------|
| 596 | 38' | to | 43'6" | 5'6" | 3.2% | Galena Qtz & Barytes |
| 597 | 53'9 | | 60 | 1.3 | 0.5% | " & Barytes |
| 598 | 60 | | 67'6 | 7.6 | 14.0% | " " |
| 599 | 137'6 | | 140 | 2.6 | 1.4 | " " |
| 600 | 140 | | 145 | 5.0 | 4.9 | " " |
| 601 | 145 | | 147 | 2.0 | 7.5 | " " |

This hole was drilled to 353 ft. in hopes that we might get through the barren quartz zone but we did not succeed and quit.

The ore assayed is the same ore shoot as the former hole drilled in and is really skimming along the top of the Lens. For the true width at right angles to the dip it is necessary to divide the widths assayed by three.

No. 27 Diamond Drill Hole

From Station No. 4.

- 46 degrees 30'

Direction of hole Southerly towards the vertical hole No. 24.

This hole is on the top of the same Lens of ore as D.D. Hole No. 26 was on. The object was to locate the same ore as was found by No. 24 and then to follow this down as far as possible. We reached the low grade ore at 206 ft. and went through it at 216'6" and got some Galena and quartz at the points mentioned.

Depth of Hole 247'6"

We reached the barren quartz at 239 ft. and quit it at 247'6". No assays were made from the sampling since no object was to be gained by further assaying the top part of the Lens.

No. 28 Diamond Drill Hole

This is a horizontal hole from Drill Station No. 2 Westerly. This was drilled to prove the ground West of the Nose or Fault.

Length 165 feet.

This proved that there was no ore here but I believe we passed across the width of ground that tallies with the position the ore body should have been, had the ore solution worked westerly.

No. 29 Diamond Drill Hole

This is a second Horizontal Hole Westerly from Drill Station No. 1 - 235 ft. long. At 147 ft. to 152 ft. got some white quartz with a little Galena and a very little Chalcopyrite. We reached the F.W. slate at 232 ft. and stopped hole at 235. ft.

No. 30 Diamond Drill Hole

Started this from N.E. Crosscut 600 ft. level N. 81 06 E - 11⁰ 25'
Length of Hole 157 feet.

This hole practically proves the same ground as D.D. Hole 18 but reaches a little further Easterly so that assaying was not done except for the new ground.

| | | | | | | <u>% Lead</u> |
|-----|--------|--------|---|------|------------------------|---------------|
| 724 | 105'9" | 109'6" | - | 3'9" | Galena & Barytes | 4.4 |
| 727 | 109.6 | 112.4 | - | 2.10 | " Quartz | 9.1 |
| 728 | 113.4 | 119.8 | - | 6.4 | " Barytes | 5.0 |
| 729 | 121.0 | 125 | - | 4.0 | " " | 4.0 |
| 730 | 125 | 130 | - | 5.0 | " Quartz | 11.1 |
| 731 | 142'6 | 144 | - | 1.6 | " Slate, Iron Sulphide | 13.2 |
| 732 | 144'0 | 145'6 | - | 1.6 | " " | 12.2 |

Practically 24'3 - assaying 6% Lead (105'9 to 150')

No. 31 Diamond Drill Hole

From N.E. Crosscut - N. 86 degrees 15 E - 11 degrees 25'

This hole was drilled so as to reach still further Easterly than the previous Hole. It passed through the same ore zone as the other two holes.

738 133'6 133'6 - 5' Galena not assayed about 3% Lead.
739 132'9 133'3 - 6" " & Slate
Got the slate at 196'6 and stopped at 197'

No. 32 Diamond Drill Hole

Drilled N. 44⁰ .06 ft E, at a vertical angle of 68⁰ 22'

From Main Tunnel made No. 5 Drill Station. This is at a point 250 ft. S.W. from D.D. Hole No. 1.

Drilled 350 ft. Got no satisfaction at all except to find that there was no Lens of ore or ore formation between the two walls of slate. We passed through Slate and Limestone Shale and quartz and reached the Footwall and quit.

ORE ZONE

The ore zone has proved to be a very narrow one following the Footwall and paralleling this from 35' to 40' southerly is the "Hanging wall of the channel" and which is a quartz or silicified lime, and which is a barren formation. Between the F.W. slate and this quartz is the ore channel containing Lenses of Galena in a gangue of Barytes, and also in some few instances the gangue is quartz.

The course of this ore zone is easterly and dips southerly at an angle of 78 degrees from the horizontal. The length is 180 ft. and as the Lenses strike a course of S.E. the length of the Lenses averages 45 ft. as a maximum. On the west end of this ore zone is what has been aptly termed a "Nose" and which I have classified as a Fault. No ore outside of this narrow channel has been found.

The property therefore cannot be classed as being a big mine.

RESULT

The final results are disappointing since the ore is too low grade for profitable extraction. According to my analysis of the ore from top to bottom of the property the following figures appear to be the value 1.62 oz. silver, 7.825% Lead - and which are higher than the ore proved by the Diamond Drill. These latter values are 1.22 oz. Silver, 7.51% Lead. Neither figures are profitable as the following figures would indicate London price of Lead \$15.15s per ton of 2240 lbs.

Silver .53¢ per ounce.

This equals \$3.42 per 100 lbs. of lead. The Consolidated Mining & Smelting Co. deducts from this price \$1.25 per 100 lbs. for marketing and refining, leaving \$2.17 per 100 lbs. of lead. Basing our calculations on as near a 60% Lead concentrate as possible, we have to concentrate 8 tons of crude ore into one ton of concentrates, and I have figures on two different sized concentrators. The smaller concentrator would seem to be more in keeping with the size of the ore body.

Taking the higher value of the ore viz. 1.62 ounces silver -
 7.825% Lead we get 7.825% less loss 5% - 7.434 x 8 - 59.472%
 Lead Concentrate
 59.472 less 1.25% Smelter deduction - 58.22% - 1164.4 lbs. Lead
 less 20 lbs - 1144.4 @ 2.17 - \$24.83
 1.627 ounces silver less 5% loss - 1.546 oz. x 8 -
 12.368 ounces and 95% paid for - 11.751 ounces 3.87
 Value of 1 ton concentrates \$28.70
500 tons Concentrator 150 ton Concentrator

Less Cost

| | | | |
|-------------------------------------|-------------|-------------------------------|-------------|
| Mining 8 tons @ 2.50 per ton..... | \$20.00 | Mining 8 tons @ 3.50..... | \$28.00 |
| Concentrating 8 tons @ 1.50..... | 12.00 | Concentrating 8 tons @ 1.50.. | 12.00 |
| Freighting to Spillimachene 1 ton.. | 1.00 | Freighting to Spillimachene.. | 1.00 |
| Railway transportation to Trail 1 T | 3.00 | Railway Transportation to Tr. | 3.00 |
| Smelting base rate 8.00 allowance | <u>4.00</u> | Smelting base rate 8.00 with | |
| | \$40.00 | payments for ingredients.... | <u>4.00</u> |
| | | | \$48.00 |

LOSS per ton of concentrates 11.30

\$19.30

The proposition is therefore a losing venture.

AMOUNT EXPENDED

The expenditure this year has been \$15,000 - which is 50% greater than was promised the Vendors last year. Altogether \$100,000 has been spent on the property since the bond was taken.

I wish to go on record as stating that Mr. A. B. Trites has acceded to my requests at all times for further drill holes to be drilled and when I had drilled as far and as often as seemed essential, I called him in to decide whether to drill more holes or not, and more holes were drilled, until it was evident that we could expect no further results than continued disappointment.

Had we stopped drilling when Hole No. 22 was drilled and not drilled holes from No. 24 on, it might have been possible to have got a mining company to do what has since been done, but having now exhausted all apparent chances, there is little hope of being able to lease or bond the property.

When Mr. Trites asked my opinion last Winter as to whether he should or should not carry on, I advised him as a Mining Engineer that the Giant property was not a payable property at the prices then prevailing. Prices have since this time declined sharply and \$15,000 more money has been expended.

The Giant, therefore, as a mining venture of promise is far worse today than at that time.

There is only the possibility of metal prices advancing sufficiently high to allow a profit, but even if these advance, consideration has to be given to the large and necessary expenditure before concentration of the minerals can be made, as this means a sum of \$350,000 for Concentrator, Plant, Equipment, road and water power, buildings for work people and the various necessary utilities.

There is nothing today to encourage anyone but a born gambler to take the chance, and everything to discourage anyone to do this. Will metal prices rise soon?

In 1902-1904 when General Manager of the North Star Mine at Kimberley, lead prices were between £10 and £11 per ton in London but Silver was much higher.

We had, however, a Bounty granted us by the Dominion Government equivalent to 1s per lb. I believe, so that we managed to get along but I am drawing attention to the low price of lead then, to show that there is nothing to assist one in arriving at the conclusion about future prices.

My experience in metal mining shows me very clearly that these prices are very changeable and often very sudden.

Further contrasts of Lead and Silver are as under:-

| | |
|-------------|----------------------------|
| Silver 1902 | .49¢ per oz. |
| Silver 1904 | .53 " " |
| Lead 1904 | .3.88¢ per lb New York |
| Lead 1902 | £10 to £11 per ton London. |

I consider that the whole proposition is a very precarious undertaking.

"J.L.Parker"

Mining Engineer.

607-8 Pacific Building, Vancouver,
B.C.

P.S.

Enclosed find copy of letter under date of Sept. 5th, 1940 to Mr. Trites with sectional elevation showing how the Drill Holes kept running up against the barren quartz and silicified lime formation.

82K/16W
82K/16E-18

April 30, 1942.

E.J. Scovil, Esq.,
GOLDEN, B.C.

Dear Sir:

Thank you for your letter of the 27th. The tracings and prints which you kindly lent me are being mailed to you today.

- (2B) Blue Print, Brunton Survey, 1923, R.J. White.
- (3B) Blue Print, Golden Giant Sections, R.J. White 12/23.
- (7B) Blue Print, Sept. 10/30, J.L. Parker, "Plan of Giant Workings showing D.D. Holes."
- (6B) Tracing, J.L. Parker, showing Drill Holes.
- (#5) Tracing, J.L. Parker, Plan showing Ore shoots. White Print, Giant Group.

Engineering and Mining Journal under date "April 1, 1942" gives under "Metallic Ores,"

"Manganese Ore, (foreign) C.I.F. U.S. Parks, long ton unit of Mn

| | |
|-------------|-----|
| 50 per cent | 66¢ |
| 48 per cent | 65¢ |
| 46 per cent | 64¢ |

"Manganese Ore, domestic,
48 per cent, f.o.b. mines 75¢."

These quotations work out to about 3 cents U.S. per pound of contained manganese in foreign ores.

Manganese ores for smelting usually contain manganese as oxide. The furnace slags contain a good deal of manganese and as the quantity of slag formed is greater with low grade than with high grade ore, furnace recovery of manganese from low grade ore is poor. You will note that the lowest grade ore quoted is 46 per cent.

PROPERTY FILE

-2-E.J.Scovil, Esq., April 30/42.

Some manganese is being recovered electrolytically in the United States. Rhodochrosite, the manganese carbonate, is acceptable for the electrolytic process. Recent information indicates that carbonate ore acceptable in the electrolytic plants may contain less manganese than is required in ore which is to be smelted.

The analysis which you quote is below the grade which is apt to be saleable, but if the manganese mineral is the carbonate, and if higher grade sections could be found, it might be of some interest, providing mining costs and transportation charges are low.

Yours very truly,

H. Sargent,
Mining Engineer.

HS/LEC

Western Mineral Survey District
RECEIVED VANCOUVER
REC'D APR 28/42
Ans'd

Golden B.C., April 27th. 1942.

Mr. H. Sargent.

Resident Mining Engineer.

304. Federal Bldg. Vancouver B.C.,

Dear Sir.

Golden Giant Mines Ltd.,
and "Giant" etc.

Thanks for your reg'd letter of the 25th. inst. with
enclos as stated,

Note the Drawings and prints will be mailed
as soon as possible.

Yours truly,

E. J. Scovil.

Note the hunt for Manganese---

Here is an analysis---

| | | |
|--|----------|----------------|
| Insoluble mineral matter.. | (11.50%) | 11.50 per cent |
| Oxide of Iron, equivalent to metallic iron | | 24.10 per cent |
| Oxid of Manganese, equivalent to Metallic Manganese | | 13.62 per cent |
| Phosphorus | | .032 per cent |
| Sulphur | | .090 per cent. |

Is this of any interest ?

DEPARTMENT OF MINES



OFFICE OF THE MINING ENGINEER
304 FEDERAL BUILDING
325 GRANVILLE STREET
VANCOUVER

20/42

Golden B.L.
Apr 16 '42

The Secretary,
Office of the Mining Engineer
304 Federal Bldg.,
Vancouver.

Dear Sir or Mlle: -

Herewith are some typewritten reports which I have on loan and which are to be returned to the owners as soon as possible. They are confidential and must be made available to no one but myself. Please arrange to copy them in the following order,

- marked 7(A) ① Report by J.L. Parker Nov 11, 1929, on Golden Giant Mine
" 8(A) ② Report on Mining operations Giant Mine B.L.
④ A ③ Golden Giant Mines Ltd,
Report by Rosh & White etc.

Omitted → ④ Western Exploration Co. Ltd, March 1942
summary, de Carlo, Etc.

Thanking you
H. Sargent
Mining Engineer.

P.S. I expect to be back in Vancouver about
Wednesday Apr 22nd.

Material obtained from E S Scott Apr 17 '42

4 (A) Golden Giant Mines Ltd.

Report by Rich J. White - 1923

7 (A) Report by J L Parker, Nov. 11/1929
on Golden Giant Mine

8 (A) Report by J L Parker re Giant Mines
November 1930

2 copy of letter J L P. to A B Tr. Co.

Sept 5/30

(2 B) Blue Print

Brenton Surrey 1923 R J White.

(3 B)

" "

Golden Giant sections R J White 12/23

(#7 B)

" "

Sept 10 '30 J L Parker.

Plan of Giant whg. showing DD Holes

(#6 B) Tracing

R J Parker showing Drill Holes

5 " R J Parker Plan showing Ore shafts

White Print Giant Group

April 25, 1942.

REGISTERED MAIL

E.J. Scovil, Esq.,
GOLDEN, B.C.

Dear Sir:

Herewith are reports which you kindly
lent me:-

| | |
|-----------|--|
| Marked 4A | Golden Giant Mines Ltd., by Rush J. White. |
| 7A | Report by J.L. Parker, Nov. 11, 1929, on Golden Giant Mine. |
| 8A | Report of J.L. Parker re "Giant Mines," November 1930, and copy of letter J.L.Parker to A.B. Trites, September 5, 1930. |

The drawings and prints will be mailed to you
as soon as possible. Thanking you,

Yours very truly,

H. Sargent,
Mining Engineer.

HS/LEC
Encls.

82K/16W
82K/NE-18

Golden B.C.,
May 1st. 1942.

Western Mineral Survey District
RESIDENT ENGINEER

Rec'd. MAY 5

Ans'd. _____

H. Sargent. Esq.,

Mining Engineer.

Dept. of Mines of B.C.,

304 Federal Bldg.

Vancouver, B.C.,

Dear Sir.

Giant Reports and Plans - returned

Thanks for your letter of the 30th. ult., and for the information therein re Manganese and that if the Manganese mineral is a carbonate, and if a higher grade sections could be found, it might be of interest providing mining costs and charges low. I think it is a carbonate.

and under separate cover the maps, etc. as detailed in your letter.

Yours truly,

E. J. Scovil
E. J. Scovil.

PROPERTY FILE

Grant Golden M.D.

The claims, - Mudgett - L 6659; Dewart - L 6658; Adair - L 6660;
Grant - L 1103; Grant Fr. - L 6657; Brothschel - L 136,
Grant N° 2 Fr. - L 6661. Hidden Treasure - L 1108
Torand. Fraction L 1111; Simcoe - L 1110.

All of which have been crown-granted, and understood
to be owned by several estates represented by E J
Scovell at Golden.

Reserves Above #5 level per Hurcell

43 301 tons @ $\begin{matrix} \text{Ag} & \text{Pb} & \text{Zn} \\ 1.7\% & 10.75\% & 0.4\% \end{matrix}$

between #5 & #6 per St Parker

440 tons 1.4% Ag, 4.1% Pb.

From drill holes below #6 level Parker found lenses
a few feet wide assaying up to 26% lead, and
averaging such lenses with under-lying waste gives
lenses 12 to 25' wide running 1.2% Ag, 7.5% Pb.

The location of the property is generally favorable,
and the width of ore is generally good, but
it appears that the lead-bearing mineralization
is confined to lenses within the wide barite
zone. The estimate of reserves above N° 5 level
may be high if it should turn out that the
mineralization here consists of several ^{smaller}, rather
than a single large lens.

The amount of barite with little or no lead mineralization
seems to be much greater than the
lead-bearing lenses. The investment required
to bring the small tonnage of probable &
possible lead ore into production, is not
warranted by the amount of ore. If barite
from the deposit could be marketed in quantity
and at a price which would cover the expenses,
by a product lead could probably be produced.
At any rate moving and milling the lead ore
could not be undertaken unless the substantial
quantity of barite which will have to be mined.

is added with, at the margins Ω and
between lead bearing lenses, and as
the major constituent of the actual lead-
bearing lenses, can be marketed at a price
which will yield some return over the cost of
preparing same for and shipping to the market

Grant - Golden MD
Pri G. M. Co.
Report by H. A. Kussell & Wallace Idaho
Submitted to Fred. Burbidge, Genl Mgr
Federal Mining & Smelting Co. Wallace Idaho
September 1927.

N.B. Copy of report. maps omitted.

Summary.

Mine situated $7\frac{3}{4}$ mi by road from Spillmachene.
Ore deposit is an irregular lode or chimney in a wedge
of limestone between slates.

Development 6 tunnels a raise, 10 ad holes,
which indicate ore body 140' long by 11.25' wide.

Probable reserves are

43,300 tons. Au. Tr, Ag 1.72 Pb 10.75% Zn 0.4%

Fully developed the ore body might contain 100,000 tons.
Gangue is barite limestone & Qtz.

Good recoveries are indicated by flotation tests.

With London lead at \$22, the ore would yield \$4.34/ton.

Costs are estimated @ \$4⁵⁰ to \$5⁵⁰ per ton.

Price asked for property \$160,000. Its equipment would cost 100,000 to 150,000.




Purchase not recommended.

All showings are on the Grant & Rothchild claims.
The country below the mine slopes 300' in 4000' toward
Spillmachene River, offering no lower site for an adit.

Structure

Deposit occurs in siliceous dolomitic limestone (often but
for lower Upper Cambrian). This lime is overlain by
Goldsier slates & limestone (lower Ordovician) underlain
by lower Cambrian & Beltian, Dog tooth series
consisting of sericitic slates interbedded with narrow
members of argillaceous limestone & sandstone.





This reference scale bar has been added to the original image. It will scale at the same rate as the image, therefore it can be used as a reference for the original size.



82K/16W
82K/NE-18

April 1st, 1948.

R. J. Macnachie, Esq.,
Associate Mining Engineer,
Parliament Buildings,
Victoria, B. C.

Dear Roy:

Herewith is material from your Nelson files, re Giant Property, Golden M. D., which you handed me some time ago.

Congratulations and best regards to you and Margaret.

Yours very truly,

Mining Engineer.

PROPERTY FILE

HS/CHG

See also plan M.M. 1927, Page 26 v
" " report re drilling M.M. 1930, Page 232

Excerpt from a letter addressed to B. T. O'Grady, January
 17th, 1931 from A. B. Trites per J. L. Parker,
 Mining Engineer.


| | | | | |
|-----|----|-------------------|---------------------|-----------|
| No. | 11 | 285' | -26.55 | N 72.53 E |
| | 12 | 142' | -23.15 | N 68.48 E |
| | 13 | 81' | -31.00 | N 45.37 E |
| | 14 | 158' | -44.27 | N 45.31 E |
| | 15 | 257' | -39.07 | N 76.56 E |
| | 16 | 248' | -57.33 | N 66.23 E |
| | 17 | Not drilled ----- | | |
| | 18 | 140' | -10.58 | N 74.10 E |
| | 19 | 192' | -10.30 | S 80.54 E |
| | 20 | 115' | -21.0 | S 7.51 E |
| | 21 | Not drilled ----- | | |
| | 22 | 347' | -79.47 | N 56.42 E |
| | 23 | Not drilled ----- | | |
| | 24 | 240' | Vertical | |
| | 25 | 192' | -66.58 | S 29.43 W |
| | 26 | 353' | -57.14 | S 29.43 W |
| | 27 | 247'6 | -46.30 | Southerly |
| | 28 | 156' | Horizontal Westerly | |
| | 29 | 235' | " " | |
| | 30 | 157' | -11.25 | N 81.06 E |
| | 31 | 197' | -11.25 | N 86.15 E |
| | 32 | 350' | -68.22 | N 44.06 E |
| | | <u>4101.6</u> | | |

Re Grant See MM. 1923
 27
 28
 29
 30

Plan. 1927 P 262
 Note re drilling 1930 P 232.

Excerpt from a letter addressed to B. T. O'Grady, January
17th, 1931 from A. B. Trites per J. L. Parker,
Mining Engineer.

| | | | | |
|-----|----|-------------------|---------------------|-----------|
| No. | 11 | 285' | -26.55 | N 72.53 E |
| | 12 | 142' | -23.15 | N 68.48 E |
| | 13 | 81' | -31.00 | N 45.37 E |
| | 14 | 158' | -44.27 | N 45.31 E |
| | 15 | 257' | -39.07 | N 76.56 E |
| | 16 | 248' | -57.33 | N 66.23 E |
| | 17 | Not drilled ----- | | |
| | 18 | 140' | -10.58 | N 74.10 E |
| | 19 | 192' | -10.30 | S 80.54 E |
| | 20 | 115' | -21.0 | S 7.51 E |
| | 21 | Not drilled ----- | | |
| | 22 | 347' | -79.47 | N 56.42 E |
| | 23 | Not drilled ----- | | |
| | 24 | 240' | Vertical | |
| | 25 | 192' | -66.58 | S 29.43 W |
| | 26 | 353' | -57.14 | S 29.43 W |
| | 27 | 247'6 | -46.50 | Southerly |
| | 28 | 156' | Horizontal Westerly | |
| | 29 | 235' | " " | |
| | 30 | 157' | -11.25 | N 91.06 E |
| | 31 | 197' | -11.25 | N 86.15 E |
| | 32 | 350' | -68.22 | N 44.06 E |
| | | <u>4101.6</u> | | |




CROSS SECTION ROTHCHILD TUNNELS

1" = 40'

June 27
A.E.R.

- Surface Wash █
- Schist █
- Limestone █
- Ore █



3400

3500

3600

3700

Rothchild Tunnel No 6

Rothchild Tunnel No 4

surface wash
schist

CONTACT
Limestone

Face, June 6th '27

Beyond this line chances slim

82K/16W
82K/NE-18

GOLDEN GIANT MINES LTD.

Spillimacheen, East Kootenay, B.C.

Report by
Rush J. White,
Mining Engineer,
Wallace, Idaho.

PROPERTY FILE

COPY

RUSH J. WHITE
Mining Engineer
WALLACE, IDAHO.

March 6, 1924.

Mr. James P. Farnham,
57 West 47th Street,
New York City, New York.

Dear Sir:-

Herewith is my report on the Giant property, consisting of mining claims owned by you, and under option to you from the Golden Giant Mines, Ltd.

A brief summary of the report follows. There are four maps with it which should be consulted for a full understanding of the situation.

The property was examined late in the fall of 1923. It consists of some two hundred acres of mineral land and about sixty-five acres of non-mineral land on the Spillimacheen River in the East Kootenay District of British Columbia. It is seven miles from the Kootenay Central Branch of the Canadian Pacific at Spillimacheen Station, and can be reached from that point by automobile.

The valuable minerals are galena, with a little silver, in a barite gangue. It is thought if the tonnage of lead ore develops as hoped that ground barytes can be made as a by-product of lead concentration, at a cost that will compete in the Canadian market.

The vein outcrops as a massive barite and lime cliff for some 400 feet along the top of a low ridge. It is at least 15 feet thick for this distance, and in two places where it is opened is 25 and 35 feet thick. Small outcrops occur at irregular intervals for a mile to the Southeast. Samples along the ore body in the main outcrops over an average width of 11.5 feet carried from 6.4% to 15.4% lead and averages 9.4% lead and 1.3 oz. silver. An individual sample from a small outcrop several hundred feet away carried 23.5% lead and 3 oz. silver over 7 feet wide. Seventeen feet of ore in a tunnel crosscutting the vein under the main outcrop carried 14.5% lead with 1.6 oz. of silver, and the lowest tunnel, under the westerly extremity of the showing, has 2'9" of ore in the face, which carries 16.1% lead, 7.5 ozs. silver and 10.5% zinc. This tunnel and another one at the west end of the ore are the only places where zinc is

found. Two samples of barite of about 100 pounds each, one from the surface, one from underground, carried respectively 95.5% and 92.2% $BaSO_4$. Two other samples taken at random from among the lead samples carried 38.1% and 27.0% $BaSO_4$. These probably represent an approximate average of the barite content of the lead bearing part of the vein. The whole deposit will run higher.

It will cost \$12,000 to \$14,000 to diamond drill the deposit to determine if it is of sufficient size and quality to warrant further exploration. The present development gives some idea of conditions, and offers much encouragement, but it is not conclusive.

Assuming the results of such work are satisfactory, it is estimated that \$400,000 will buy the property, equip it with a 150-ton concentrating mill, 750 KW generating plant on the Spillimacheen River, and the necessary mine plant to produce on a basis of 150 tons in 24 hours. This would not provide a barytes plant. The cost of such a plant would depend on the characteristics of the ore as determined in a preliminary test run, and its feasibility would depend on the quality of material that can be produced, as indicated by such a run, and on the market that develops. The cost should not be very heavy, as much of the material will be partly ground for the concentration process.

Lead ore shipments will be to the Trail plant of the Consolidated Mining & Smelting Co. of Canada, Ltd.

It is estimated that 10% lead ore at present prices will pay 7% interest on \$400,000 capital, 10% amortization on \$290,000 cost of plant, plus a 20% profit. If the lead values should prove to be as good as in the main tunnel crosscut, it will pay more than 50% profit per annum. At the average of 1923 prices 10% ore will about pay interest and amortization, but no profit, while 14% ore will pay 20% profit. These figures do not include any return from barytes.

The price of the property is \$63,000, plus a small interest in any company or syndicate that may be formed. The \$63,000 is the exact price of the Golden Giant option. The interest retained is the price of the Farnham holdings.

Payments are to be made as follows:

| | |
|----------------|----------|
| April 15, 1925 | \$5,000 |
| April 15, 1926 | 13,000 |
| 15, 1927 | 15,000 |
| 15, 1928 | 30,000 |
| | <hr/> |
| | \$63,000 |

Fifteen per cent royalty will be deducted from the net return on all ore and mineral sold, the proceeds to apply on purchase payments. Work is to be started not later than June 15, 1924, and is to average not less than \$300 per month. Any equipment placed on the property may be removed if the option is dropped.

It should be noted that the only expense necessary before a knowledge of the possibilities is available is the cost of drilling and experimental work, estimated at \$12,000 for drilling, and probably not over \$5,000 for experimental work.

In calling this property to the attention of any prospective buyer, you should not fail to mention that the writer of this report is interested in the option with you.

Yours very truly,

Rush J. White.

RJW:M

THE GOLDEN GIANT MINES, LTD
EAST KOOTENAY DISTRICT
BRITISH COLUMBIA

REPORT BY RUSH J. WHITE, MINING ENGINEER
Wallace, Idaho

Location

This mining property is on the east side of the Spillimacheen River Valley about one-half mile from the water. The claims occupy the point of a side ridge where it flattens out into the valley floor. They are seven miles northwesterly from Spillimacheen Station on the Kootenay Central branch of the Canadian Pacific Railway, and are reached by a fairly good road from that station.

The Kootenay Central leaves the main line at Golden, B.C., which is at the western foot of the Canadian Rockies, at the eastern foot of the Selkirks and at the first or east crossing of the Columbia River. The branch runs southerly up the Columbia, past its source, and down the Kootenai River to a junction with the Crowsnest branch of the C.P.R. (See general map).

Spillimacheen Station is on the east bank of the Columbia opposite the mouth of the river of the same name and some forty miles above Golden. It may be reached from Spokane over the Spokane International Railway, via Cranbrook and Fort Steele, or from the East or West over the C.P.R. main line. There are two trains a week each way on the Kootenay Central, leaving Cranbrook Mondays and Thursdays, and leaving Golden Tuesdays and Fridays. A stop is made overnight at Ivermere on Lake Windermere, on both the up and down trips.

PROPERTY

The GIANT crown granted mining claim and a tract of non-mineral land nearby are under option to Mr. Farnham from the GOLDEN GIANT MINES, LTD. The Rothschild crown granted claim, and the Midget, Dwarf, Giant No. 2 and Giant Fraction Locations are owned by him (See claim map).

The total area of mineral land owned and under option is about 207 acres, and of non-mineral land about 65 acres.

The Rothschild is one of the old 600x1500 foot claims that carry extralateral rights. All the others, except the Giant Fraction, are 1500 feet square, and carry the mineral within their boundaries only.

Negotiations are under way with the various owners of the Toronto and Simcoe, the Hidden Treasure, and the Mountain locations looking to the acquirement of these claims. The first two are old 600x1500 foot claims. The others are 1500 feet square. They cover the mineralized ground for 3000 feet southeast of the Giant claim.

BUILDINGS AND EQUIPMENT

Buildings on the property at this time are a small mill building of rather light construction, about 1000 feet south of the principal outcrop, a log bunk and cook house, 15x40 feet, and a log assay office, 15x20 feet. Another log cabin 15x20 feet is just off the property, but near the assay office and cook house. It probably belongs to other parties. There are rough housing accommodations for 15 to 20 men on the ground at this time. There is a 6 hole range, somewhat in need of repair, and a few cooking utensils. New springs, mattresses and bedding are required.

In the assay office is an old style Becker Bros. gold balance, an Ainsworth analytical balance, and a 700# platform scale. The balances are in bad shape, from standing a long time without attention, and from probable handling by rough hands. They can be repaired; perhaps a careful man could put them in shape on the ground. All the weights have disappeared. There is a small gasoline assay furnace taking a 2 $\frac{1}{2}$ x4 $\frac{1}{2}$ x8 inch muffle, with pressure tank and burner. There is a little glassware, and a few other odds and ends.

In the mill are a 7x10 Blake and a 7x10 Dodge Crushers; a 36" sorting belt 15 feet long, belt bad, equipment O.K.; a pair of 10x16 inch rolls; a 4x6 foot ball mill with screen discharge (new); an 8 foot Callow cone (new); 2 dry concentrating tables; a little boiler and a blacksmith shop on the bottom floor, and a hand laboratory crusher and bucking board on one of the upper floors. There are five floors in the mill. The two upper floors with the crushing and sorting plant are 16 feet wide. The rest of the mill is 26 feet wide.

A surface tramway about 1000 feet long runs from a log bin below the No. 1 open cut to the mill. The track can be put in good shape with a little work. The trestle to the mill at the lower end must be replaced. There are two cars

in good condition on it. The 5/8 cable is nearly new, but will have to be replaced on account of rust.

There are some 2000 to 2500 feet of two inch black pipe in good condition scattered over the ground.

WAGON ROAD

The road from Spillimacheen is across the more or less swampy bottom land of the Columbia for two miles. Just before it starts up the hill on the west side of the valley it crosses the Spillimacheen river where it emerges onto the flat from between the walls of a box canyon. The next mile or so is pretty steep, and is not adapted to heavy hauling, but the rest of the road to the mine is nearly level, with local ups and downs, but with a good foundations. This stretch runs along the gravel and slide rock close to the foot of the mountain.

If any work is done at the property the Government will cooperate to help rebuild the road on a good grade, and to eliminate the local irregularities. The cost to the property of its share of such work is included in the \$400,000 estimate. It should not amount to more than \$10,000.

POWER PLANT

It is proposed to build a hydro-electric power plant of 750 KW capacity. The location that suggests itself after a hurried reconnaissance is at the mouth of the box canyon of the Spillimacheen, just above the wagon road crossing. See photograph. At water level it is 75 to 80 feet between the canyon walls. The location is admirable for a dam and a large plant, but for the present it is thought a wood or steel pipe line through the canyon for about a mile will be cheaper and will answer the purpose. This opinion may be changed after a survey and careful estimate. The cost of plant and transmission line is estimated at \$80,000.

TITLE

The option guarantees to transfer the property of the Golden Giant Mines, Ltd. free and clear of all incumbrance except taxes, rates, and assessments charged against the property after June 15, 1924. The Land Registry Office at Nelson, B.C. furnishes the information that the only incumbrance now against the property is a mortgage held by Alexis Martin. Mr. Martin is Secretary of The Golden Giant Mines, Ltd. and as such signed the option, so that as far as Mr. Farnham is concerned the property is clear.

Certificate of Incumbrance No. 7908, dated January 4, 1924, from the Land Registry Office shows the title of the Rothschild Mineral Claim to rest in Mr. Farnham without incumbrance. Locations of the other claims were property made, recorded, and transferred to Mr. Farnham late in 1923.

PRICE AND TERMS

The option price to Mr. Farnham of the Golden Giant property is \$63,000, to be paid as follows:

| | Mining claim | Land |
|---------------|--------------|---------|
| July 15, 1925 | \$5,000 | |
| " 15, 1926 | 10,000 | \$3,000 |
| " 15, 1927 | 15,000 | |
| " 15, 1928 | 30,000 | |
| Total | \$60,000 | \$3,000 |

Work on the property must begin on or before June 15, 1924. Expenditures must be at the average rate of at least \$300 per month. If more than \$1,800 is spent in any six months period the excess may be carried forward to apply on required expenditures in the next period.

A royalty of 15% of the net return from all shipments of ore to the smelter, or barytes or other material to market is to be paid and will apply on the installment of the purchase price due next after any such royalty is paid.

If the option is not exercised all the plant and machinery installed by the optionee may be removed. The optionee is to pay all taxes and assessments charged against the property after June 15, 1924.

It is proposed to consolidate the Giant and Farnham properties into one group, and to reoption the whole at the price of the Giant option, retaining an interest in any Company or association that may be formed to work the property. Dates of payment will be three months ahead of those specified as above in the original Giant option to allow Mr. Farnham to re-finance in the event of failure of the new optionee to meet its terms. Thus the new optionee will come into control of all the property at the cost only of meeting the obligations of the Giant option, while Mr. Farnham will receive an interest as the price of his property and pay for his efforts.

If the effort to get title to the Hidden Treasure, the Toronto and Simcoe, and the Mountain location is successful, either before or after a new option is given, these claims will be added to the group without extra cost.

THE DEPOSIT

The ore deposit is a vein of barite with lime inclusions, carrying galena and silver. It strikes N. 60° W. and dips 70° to the Southwest. The outcrop forms the top and point of a low ridge running Northwesterly from the main divide. The hanging wall is exposed from the apex down the side of the hill for 50 to 200 feet. The apex is exposed for 400 feet along the ridge. The minimum width of the vein appears to be about 15 feet. In two large cuts it is exposed to widths of 25 to 35 feet. The galena is not regularly distributed but is found in bands and ribbons parallel with the strike and dip, sometimes with nearly pure barite, sometimes with lime between.

Along the hill to the Southeast a good many small barite exposures are found for a mile or more. Some of them carry lead, some do not. It is difficult to determine whether they are remnants of the vein, or whether they are detached occurrences. They indicate, at any rate, that mineral is not entirely confined to the area carrying the large exposure. There is a good chance that ore may be continuous over a larger area than that covered by the main outcrop.

It should be noted that the only occurrence of zinc in all the workings and exposures in the two tunnels, Nos. 2 and 3. The assay sheets show appreciable quantities here.

The barite, except where it is impregnated with lead, or contaminated with lime inclusions, is quite pure, as indicated by samples No.s 25 and 29, which carry 92.2% and 95.5% BaSO₄ respectively. It occurs in seams of this purity one to two feet wide. In other seams and bands it carries disseminated lead in the pure barite, while in others it surrounds inclusions of lime rock, and both barite and lime may or may not be impregnated with galena. The larger part of the lead content is in the barite, rather than in the lime.

EXPLORATION

Development to date consists of a number of shallow open cuts across the apex of the vein; a large open cut, No. 1, on the outcrop a short distance above the Northwest end of the vein and a smaller cut, No. 2, 60 or 70 feet Southeast of No. 1.

Tunnel No. 1 is a crosscut driven Northeasterly. It encounters the vein 70 feet from the portal, but is contin-

ued into the footwall to a total length of 260 feet. (See Plan and Sec. "A-A") No. 2 tunnel is at the same elevation as No. 1. The portal is 240 feet northwest of the portal of No. 1. It is 90 feet long and shows the vein at the face at what appears to be its northwest extremity. It penetrates the barite for 9 feet, but does not go through it. No. 3 tunnel is driven under No. 2 68 feet below it, from a point 230 feet southwest of the portal of No. 2. This tunnel shows what seems to be the northwest extremity of the vein at a point 80 feet northwest of the exposure in No. 2. The vein in No. 3 is $12\frac{1}{2}$ feet thick and carries good values.

A tunnel, No. 4 on the map, was started some 500 feet southeast of the portal of No. 1 to crosscut under a large detached outcrop. It was not driven far enough to cut the vein, but is beginning to show a little mineralization at the face. (See Section "B-B").

Some tunnels and open cuts have been made on the Hidden Treasure Claim and on the Mountain Claim. The tunnels on the Hidden Treasure show quite a bit of copper with the barytes. The tunnel and cuts on the Mountain Claim show barytes with a little lead.

SAMPLING

A list of the samples taken, with their assay value, follows. (Page 10). These are shown on the plan map, which should be referred to in this connection. Where numbers were omitted the sample was laid out but not taken for one reason or another.

This sampling was made, not to determine the tonnage and average value of the ore exposed, because the conditions do not allow of such a sampling, but to learn if ore of commercial grade occurs at all and if its distribution seems to warrant further development. It will be noted that in a general way the values underground are richer in lead than those on the surface. This seems to be apparent both in the tunnels and in the larger open cuts.

The sampling indicates a possibility of developing ore of 10% grade or better. It is believed that further exploration is warranted, particularly in view of the liberal terms of the option and the present price of lead.

ASSAY VALUES

| Sample Number | Width feet | Silver oz. | lead % | | |
|---------------|------------|------------|--------|---|--|
| 2 | 12.0 | 0.6 | 2.1 |) | |
| 4# | 5.0 | 1.8 | 15.4 |) | No. 1 open cut |
| 5 | 5.0 | 0.2 | 0.5 |) | |
| 6 | | 0.4 | 5.8 |) | Waste from No. 2 open cut |
| | | | |) | BaSO ₄ |
| 8# | 5.5 | 1.5 | 9.3 |) | 38.1 |
| 9# | 7.0 | 1.4 | 7.0 |) | No. 2 open cut |
| 10 | 6.0 | 1.2 | 2.7 |) | |
| 11 | 12.0 | 0.6 | 7.3 |) | |
| 12 | 24.0 | 0.6 | 3.1 |) | Surface along outcrop |
| 13# | 5.5 | 0.9 | 6.4 |) | Average 15.6 feet wide |
| 14# | 5.0 | 2.7 | 7.6 |) | 0.95 oz silver, 6.98% lead. |
| 15# | 12.0 | 1.2 | 10.2 |) | |
| 16# | 15.0 | 0.9 | 6.8 |) | |
| 17# | 14.0 | 1.0 | 12.6 |) | |
| | | | |) | % zinc |
| 18 | 6.0 | 1.2 | 12.8 |) | none |
| 19 | 11.0 | 1.8 | 15.4 |) | none |
| 20 | 2.0 | 3.2 | 13.4 |) | West side No. 1 tunnel 17 ft. |
| 21 | 5.5 | 0.8 | 4.0 |) | Wide avg. 1.59 silver 14.48 lead |
| 22 | 3.0 | 1.5 | 10.1 |) | Partial width east side No. 1 |
| 23 | 7.0 | 3.0 | 22.5 |) | Open cut at Sta.30 above No. |
| 24 | 6.3 | 0.3 | 0.6 |) | 4 tunnel |
| | | | |) | 2nd outcrop above No. 4 tunnel |
| | | | |) | No. 2 tunnel next footwall only |
| | | | |) | BaSO ₄ |
| 25 | | | |) | 92.2 |
| | | | |) | No. 2 tunnel hanging side of 24. |
| | | | |) | % zinc |
| 26 | 2.8 | 7.5 | 16.5 |) | 10.5 |
| 27 | 3.4 | 1.9 | 7.8 |) | 17.6 |
| 28 | 9.0 | 0.8 | 1.6 |) | 6.8 |
| | | | |) | BaSO ₄ |
| 29 | | | |) | 95.5 |
| | | | |) | Barite sample sorted from face No. 1 open cut. |

By referring to the plan map it will be seen that samples 4, 8-9, 13-14, 15, 16, and 17 represent the richer part of the vein along the hanging side on the surface. These samples average 11.5 feet wide, 1.27 oz. silver and 9.44% lead.

PROPOSED DEVELOPMENT

About 80,000 tons of ore can be measured up now. This is insufficient to warrant building a mill and plant, but it is sufficient to justify an exploration campaign to be undertaken with the hope of finding enough more ore to justify such construction.

Exploration can be carried on best by diamond drilling. The plan would be to put down a few holes first to determine the extension and probable grade of the vein below the present exposure, and to the southeast. If this proves satisfactory it will be in order to do some systematic drilling to determine the grade with some exactness. The preliminary drilling campaign should cost not to exceed \$12,000.00. If it is unsuccessful that will be the extent of the investment. If it is successful the cost of further work will depend entirely on the size of ore body found.

PLANT

Assuming the development, as sketched above, has shown a tonnage of commercial ore, it will be in order to build a plant for its treatment. This should be preceded by careful experimental work which will show just what machinery will give the best results on this particular ore. The size of the mill and plant will depend on the tonnage available. If we are very fortunate, a plant of some size may be advisable, because, of course, the larger the plant the less the cost per ton. It is thought that a capacity of 150 tons is the smallest that will be economical, so the following figures have been made for a plant of that size.

The following will be necessary: a hydro-electric power plant on the Spillimacheen River, at the foot of a box canyon about five miles from the property, to generate 750 K.W; a mill of 150 tons capacity in 24 hours; a compressor plant blacksmith and machine shop and boarding and dwelling houses, office, assay office, etc.

The cost of such a plant is estimated at \$290,000, as follows:

| | |
|--|---------------|
| Hydro-electric plant, with transmission line, transformers, etc. | \$ 80,000 |
| 150 ton mill | 150,000 |
| Compressor and mine plant | <u>60,000</u> |
| Total | \$290,000 |

This estimate was made by using the conventional figures.

of \$100 per KW for power plant capacity, and \$1000 per ton for mill capacity. It was checked over in some detail to see if the resulting figures would fit local conditions. These check figures gave similar results, so it is believed they are as close as can be reached without making surveys and detailed estimates.

CAPITAL COSTS AND CHARGES

These are estimated as follows:

| | |
|---------------------------|------------------|
| Preliminary Exploration | \$12,000 |
| " Development and testing | 28,000 |
| Plant, as above | 290,000 |
| Property, as per option | 63,000 |
| | <u>\$393,000</u> |

say \$400,000

Fixed annual charges would be:

| | |
|-----------------------------|---------------|
| Interest on \$400,000 @ 7% | \$28,000 |
| Amortization 290,000 @ 10% | <u>29,000</u> |
| Total fixed charge per year | \$57,000 |

OPERATING COSTS

These have been figured on the basis of labor to be employed, and assuming that the labor charge would be 40% of the milling cost, and 65% of the mining cost. Mining includes development. It is thought that a shrinkage system, or rill stoping with back filling will be the most efficient and cheapest way to take the ore out, and costs are made on the assumption that one or the other of these schemes will be used, and that the cost for either one will be about the same.

| | |
|--|--------------------|
| Mining, including development, mechanical, etc., | per ton \$1,805 |
| Milling | .97 |
| Superintendence, engineering and overhead | <u>.40</u> |
| Total | \$3.175 |

For details of these costs see page at back of report.

Hauling concentrates to the railroad will cost \$4.00 per ton of material handled.

MILLING

It is believed that ordinary gravity concentration, with regrinding and flotation of fine middlings and tails, will give a good extraction. Recoveries are figured at 85% for lead, and 75% for silver. It is assumed that a 50% concentrate will be made carrying 5.04 oz. silver. With these assumptions, ratios of concentration will be as follows for different grades of mine run ore.

| | | |
|-------|------------------------|------|
| 10.0% | ratio of concentration | 5.86 |
| 14.0% | " " " | 4.2 |

No attempt has been made to make any figures for the value of the barite in the ore. It is thought from an inspection that a clean barytes product can be cut from the table tails, or possibly even made on the jigs. If this proves to be true, the addition of fine grinding equipment will be all that is necessary to size the material to marketable condition.

Some experimental work was done on Giant ore at McGill University in 1907. The results show that a saving of better than 75% in a 58% concentrate can be made by gravity. Since then there have been many improvements in gravity concentration, and flotation has been developed, so that estimate of 85% recovery for lead is not unreasonable.

SMELTING

The Trail plant of the Consolidated Mining & Smelting Co. of Canada, Ltd. is the logical place to treat the ore. It might be possible to ship to the Bunker Hill, or even to East Helena, but our information now is that freight rates make it prohibitive.

Ore will be handled under their schedule "F", which provides, in brief, as follows:

SILVER: 95% will be paid for at the New York quotation for foreign silver converted into Canadian funds, at par, but with allowance for U.S. exchange. Minimum deduction 0.5 oz.

LEAD: The contents will be determined by wet assay, and $1\frac{1}{4}$ units will be deducted to arrive at dry lead assay. 90% of the lead, as determined by the dry assay will be paid for, provided that the minimum deduction from the dry assay shall not be less than 1 unit, or 20 pounds per dry ton of ore. The price shall be London spot quotation converted into Canadian funds at Bank of Montreal's price for sterling exchange, less $1\frac{1}{4}$ cents per pound for refining and marketing, or it may be paid for under a pooling arrangement the smelter has worked out.

SMELTING charge is \$8.00 per dry ton.

ZINC penalty, 25¢ per unit for all zinc contained.

SILICA AND LIME premium, 7¢ per unit, provided that the smelting charge shall not be reduced more than \$4.00 per ton by the above additions and deductions.

SULPHUR penalty, over 2% 30¢ per unit per dry ton.

The freight from Spillimacheen to the smelter is \$3.00 per ton. With 5% moisture it will be \$3.16 per ton of dry ore. This figure has been used in the calculations, as covering about an average moisture content.

METAL PRICES

It is believed that average metal prices over a period of prewar years mean little as establishing a probable future price for lead. It is believed rather that the increased consumption of lead, without a corresponding increase in the supply in reserve must hold the price at a relatively high level. No one seems to be in position to determine what this price will be, but it seems reasonable to think that the average will not be lower than the average of the 1923 price, and may with equal reason hold at an even higher figure.

The price of silver requires no comment.

In order that an estimate of the possibilities may be intelligently made, two sets of figures are presented on page 15, the first showing the values of two grades of ore at the average of 1923 metal prices, the second showing values for the same grades of ore as of Feb. 19, 1924.

The Bank of Montreal's quotations for sterling exchange are not available so New York quotations have been used, but with no allowance for Canadian exchange, for either lead or silver. It is believed this method given an approximate value for the ore within smaller limits of error than that which applies to the mill recovery, the grade of ore, or other assumed factors.

Prices given for lead are the London quotation for lead in pounds sterling per ton of 2240 pounds. Silver prices are New York quotations in cents per ounce.

| | Lead | Silver |
|------------------------|--------|--------|
| Average price for 1923 | 27.147 | 64.87 |
| Feb. 19, 1924 | 35.00 | 64.25 |

CALCULATION OF PROFITS AT DIFFERENT METAL PRICES AND FOR DIFFERENT GRADES
OF ORE

| Grade of ore | | net value per ton at mill bin | cost per ton | operating profit per ton | operating profit per year 52,500 tons. | fixed charges | net profit per year | % profit on \$400,000 investment |
|------------------------------|-----------|-------------------------------------|--------------------|--------------------------------|---|------------------|------------------------------|--|
| silver oz | lead % | | | | | | | |
| AVERAGE OF 1923 metal prices | | | | | | | | |
| 1.2 | 10.0 | \$4,198 | \$3.20 | \$1.00 | \$52,500 | \$57,000 | | |
| 1.6 | 14.0 | 5.878 | 3.20 | 2.68 | 140,700 | 57,000 | \$83,700 | 20.925 |
| Feb. 19, 1924 metal prices | | | | | | | | |
| 1.2 | 10.0 | \$5.929 | \$3.20 | \$2.73 | \$143,325 | \$57,000 | \$86,325 | 21.58 |
| 1.6 | 14.0 | 8.30 | 3.20 | 5.10 | 267,750 | 57,000 | 220,750 | 55.19 |

No details are given of the computations to arrive at net smelter returns or the value per ton mined at the mill bins. If one is curious they can easily be worked out from the data given above.

Details for calculating operating cost will be found on a separate sheet at the back of this report.

CONCLUSION

From the above it will be realized that there is a nice chance to make a profitable mine; providing development works out satisfactorily and lead prices stay about as at present. It is not a sure thing, but is a much better speculation than the ordinary prospect; in most cases the chances of success are perhaps 1 in 100, while in this case they are 1 in 3 or 5. Under the remarkably easy terms of the option, where one can prove or disprove a mine for \$12,000, it is really very attractive.

The writer of this report is interested with Mr. Farnham in the option.

RUSH J. WHITE,

Mining Engineer.

| | Number of men | | total men | Wages | | total labor cost | labor cost per ton | labor % total cost | total cost per day | cost per ton |
|--------------------|---------------|----------|-----------|--------|---------|------------------|--------------------|--------------------|--------------------|--------------|
| | 1 shift | 2 shifts | | shift | total | | | | | |
| MINE | | | | | | | | | | |
| breaking ore | 3 | | 3 | \$5.00 | \$15.00 | | | | | |
| " filling | 2 | | 2 | 5.00 | 10.00 | | | | | |
| timbering rills | 4 | | 4 | 5.25 | 21.00 | | | | | |
| rill raises | 4 | | 4 | 5.00 | 21.00 | | | | | |
| development | 4 | | 4 | 5.00 | 20.00 | | | | | |
| tramming | 2 | | 2 | 5.00 | 10.00 | | | | | |
| raise hoists | 2 | | 2 | 5.50 | 11.00 | | | | | |
| pipe & track | 1 | | 1 | 5.00 | 5.00 | | | | | |
| foreman | 1 | | 1 | 10.00 | 10.00 | | | | | |
| | | | 23 | | 123.50 | | | | | |
| MECHANICAL | | | | | | | | | | |
| blacksmith | 1 | | 1 | 6.00 | 6.00 | | | | | |
| helper | 1 | | 1 | 5.00 | 5.00 | | | | | |
| steel sharpener | 1 | | 1 | 6.00 | 6.00 | | | | | |
| machinist | 2 | | 2 | 6.00 | 12.00 | | | | | |
| | 1 | 1 | 2 | 5.50 | 11.00 | | | | | |
| | 1 | | 1 | 8.00 | 8.00 | | | | | |
| | | | 8 | 4.50 | 48.00 | | | | | |
| TRAMWAY | 1 | | 1 | 4.50 | 4.50 | \$176.00 | \$1,173 | 65 | \$270.77 | \$1.805 |
| MILL | | | | | | | | | | |
| crusher | 1 | 3 | 1 | 4.50 | 4.50 | | | | | |
| rolls, tube, mills | | 1 | 3 | 4.50 | 13.50 | | | | | |
| jigs, tables, etc. | | 1 | 3 | 4.50 | 13.50 | | | | | |
| flotation | | 1 | 3 | 4.50 | 13.50 | | | | | |
| repair | 1 | | 1 | 5.00 | 5.00 | | | | | |
| foreman | 1 | | 1 | 8.00 | 8.00 | 658.00 | 0.386 | 40 | 145.00 | 0.97 |
| OVERHEAD | | | | | | | | | | |
| Mgs. & Supt. | 1 | | 1 | 20.00 | 20.00 | | | | | |
| Assayer | 1 | | 1 | 7.00 | 7.00 | | | | | |
| Engineer | 1 | | 1 | 8.00 | 8.00 | | | | | |
| helper | 1 | | 1 | 5.50 | 5.50 | | | | | |
| office | 2 | | 2 avg | 7.00 | 14.00 | 54.60 | 0.363 | 90 | 60.55 | 0.40 |
| Total | | | 50 | | | \$288.50 | 1.922 | | \$476.32 | \$3.175 |

@ 150 tons/day

GOLDEN GIANT MINES
LIMITED

REPORT

by
RUSH J. WHITE

Alexis Martin,
Barrister & Solicitor
205-6 Pemberton Bldg.
VICTORIA, B.C.

82K/16W
82K/NE-18

R E P O R T
on the
G I A N T M I N E
Golden Mining Division, B.C.

September, 1927

PROPERTY FILE

Submitted to
Mr. Frederick Burbidge, General Manager
Federal Mining and Smelting Company
Wallace, Idaho

BY
H.A. Kursell
Wallace, Idaho.

I N D E X

| | |
|-----------------------------------|--------|
| LOCATION and ACCESSIBILITY | Page 1 |
| PROPERTY, TITLES and OPTIONS | 1 |
| TERMS | 2 |
| CLIMATE | 2 |
| TOPOGRAPHY | 3 |
| ORE OCCURRENCE and NATURE OF ORE | 4 |
| ORE RESERVES | 8 |
| Probable Ore | 9 |
| Prospective Ore | 9 |
| METALLURGY | 10 |
| FINANCIAL RETURNS | 10 |
| CONCLUSIONS | 11 |

LIST OF MAPS

| | | |
|----|--|-----------------------|
| 1. | Sketch of Spillimachene Mountain | Scale 1 in. = 2 miles |
| 2. | Giant mine - Geological map | " 1 in. = 300 ft. |
| 3. | Plan of Giant Mine | " 1 in. = 40 ft. |
| 4. | Assay Plan of Giant Mine | " 1 in. = 40 ft. |
| 5. | Section through Diamond Drill Holes 3 & 6 | " 1 in. = 40 ft. |
| 6. | " " " " " 7 & 8 | " 1 in. = 40 ft. |
| 7. | " " " " " 4 & 5 | " 1 in. = 40 ft. |
| 8. | Blueprint of Claim Map | " 1 in. = 200 ft. |
| 9. | Assay Plan of Giant Mine made by A.W.Davis May 31, 1927 | " 1 in. = 20 ft. |

SUMMARY

The Giant Mine is situated $7\frac{3}{4}$ miles northwest of Spillimachene station on a branch line of the Canadian Pacific Railroad, in the Golden Mining Division of British Columbia.

The ore deposit is an irregular lode or chimney occurring in a wedge of limestone between slates.

Development consists of 6 tunnels, a raise, and 10 diamond drill holes, which indicate an orebody 140 feet long and 11.25 feet wide.

Probable ore reserves, on the strength of present development, are estimated at 43,300 tons, assaying on an average:

Tr. Au, 1.7 ozs. Ag, 10.75% Pb, 0.4% Zn.

Fully developed the Giant orebody might show a total of 100,000 tons or thereabout.

The gangue is barite, limestone, and quartz. The ore is well amenable to flotation and good recoveries are indicated by tests.

With London lead at £22 this ore would net \$4.34 per ton smelter returns.

Working costs, with reference to the small size of the deposit, are estimated at \$4.50 to \$5.00 per ton. Hence the Giant ore shows no profit.

The price of the property is \$160,000 in deferred payments. Its equipment would call for \$100,000 to \$150,000.

The Giant is not considered an attractive mining proposition and its purchase is not recommended.

LOCATION AND ACCESSIBILITY

The Giant Mine lies on the left bank of the Spillimachene River, approximately 5 miles from the Spillimachene station on a branch line of the Canadian Pacific Railroad. The elevation is 3500 feet.

The property is to be reached from Spillimachene (Elev. 2610) by automobile following a narrow road of $7\frac{3}{4}$ miles. The present road is on the left bank of the river and has several excessively steep grades, but by building a bridge across the narrow Spillimachene canyon, about $1\frac{1}{2}$ miles below the camp, and leading the road along the right bank of the river, it could be shortened to about 6 miles and all undue grades avoided. Mr. A.W. Davis estimates the construction of such a road to cost about \$30,000, to which the Government of British Columbia might contribute \$15,000.

The road is open for automobile traffic from about April 15th to November 15th, horse-drawn sleighs being used the rest of the year. Freight from railroad to mine costs \$2.50 per ton by truck, \$8.00 or more per ton by sleigh. The snowfall in this part of British Columbia is slight, seldom exceeding 3-4 feet. during the season. No difficulties are anticipated after building a new road to keep it open for automobile traffic all the year round.

PROPERTY, TITLES and OPTIONS

The property is covered by the Crown granted Giant and Rothschild claims which cover all the showings on the ground. In addition, the Simcoe and Toronto claims to the Southeast have been optioned by the Pacific Mines Ltd., and a number of claims (9?) have been staked by them to the west and south, forming a well rounded holding which covers the possible extensions of the ore deposit. A map showing the relative position of the claims will be submitted supplementary to this report.

A strip of land half a mile wide and extending southward to the Spillimachene river is homesteaded as farm and belongs to the Giant claims.

The Giant option to Mr. A.B. Trites (Pacific Mines Ltd.) of Vancouver, B.C., calls for the following payments:-

| | | | |
|-------------------|---------------|--------|----------|
| November 16, 1927 | \$ 5,000 | (paid) | |
| " 16, 1928 | 20,000 | | |
| " 16, 1930 | <u>50,000</u> | | \$75,000 |

The option on the Farnham-Rothschild claim:-

| | | | |
|-----------|--------------|--|--------|
| July 1927 | 1,000 | | |
| " 1928 | 4,000 | | |
| " 1929 | 6,000 | | |
| " 1930 | <u>9,000</u> | | 20,000 |

| | | | |
|---------------------------------|--------------|--------|-------|
| The Simcoe and Toronto claims:- | 800 | (paid) | |
| Balance due | <u>6,200</u> | | 7,000 |

No money is asked for the claims staked by the Pacific Mines Ltd.

Summarizing the above, we find:-

| | | | |
|----------------------------------|----------|---------------|---------|
| Payments made on the options | | \$6,800 | |
| " due in the second half of 1928 | | 25,000 | |
| " due July 1929 | 7,000 to | 8,000 | |
| " " " 1930 | | <u>62,200</u> | 102,000 |

Mr. Trites has spent on the development of the property up to August 1, 1927, \$58,000, which brings the total price of the property to \$160,000.

TERMS

Mr. Trites proposes that the Federal Mining & Smelting Co. refund the money spent by him on the property to date; take an assignment on the options; and, after return of all the money invested by it plus 5% interest, divide further profits with him at the rate of 75% to the Federal Mining & Smelting Co., and 25% to Mr. Trites.

CLIMATE

The Giant Mine lies in what is known as the Columbia Valley dry belt, with an annual average precipitation of only 12 inches. The climate is pleasant, though cold in winter.

TOPOGRAPHY

The camp and the workings lie on the southwest slope of an isolated mountain range between the Columbia and Spillimachene rivers. The country below the mine slopes gently towards the Spillimachene river (300 ft. drop in 4000 ft.), offering no favorable tunnel sites. Above the Giant workings, the mountain slopes are precipitous.

GEOLOGY (See sketches 1 and 2)

The deposit occurs in a bed of silicious dolomitic limestone classed by the G.S. of Canada as Ottertail, i.e. lower Upper Cambrian. This lime is overlain by Goodsir slates and limestone - Lower Ordovician, underlain by Lower Cambrian and the Beltian Dogtooth series consisting of sercitic slates interbedded with narrow members of impure limestone and sandstone.

Structurally the mountain range between the Columbia and Spillimachene rivers, known as Spillimachene and Jubilee mountains, forms a syncline the axis of which strikes $N50^{\circ}W$. The northeastern wing of this syncline dips gently (20° to 50°) towards the SW; the southwestern wing in the area of the Giant has a reversed dip, pitching steeply (85° to 90°) towards the SW. The axis of the syncline is gently inclined ($30^{\circ}?$) towards NW. Sketch No. 1 illustrates the conditions.

An overthrust fault striking $N35^{\circ}-40^{\circ}W$ and dipping on an average $45^{\circ}SW$ cuts the southwestern wing of the syncline with an upthrow on the south side. As a result of this fault, members of the Dogtooth formation cut off and overlie the Ottertail limestone in the horizon of the workings. They are found farther west in contact with the Ordovician Goodsir slates.

The folded Ottertail lime and the above described overthrust fault intersect at an angle of about 15° , with a line of intersection raking steeply northwest. The Giant orebody lies in the wedge formed by this intersection the best mineralization occurring nearest to that point. The wedge

widens

out towards the SE, and mineralization diminishes and becomes more irregular in this direction. It follows on the whole the fault contact.

A proper understanding of the structural geology of this area is of paramount importance in order to venture an opinion on the prospects of the Giant Mine. Should the Ottertail limestone beds in the area of the deposit assume a dip to the northeast a short distance below the present workings, they would be pitching away from the fault and the chances for further ore at depth as far as a suitable horizon for ore deposition is concerned, would be fair. Should, on the other hand, the Ottertail limestone continue in depth with a southwesterly dip, as exposed at surface, it would be cut off entirely to the northwest by the fault, as this is noticeable now on No. 3 Tunnel level. In the latter case the chances for an orebody of any size would be small.

The distance between the outcrops of the Ottertail limestone on the two wings of the syncline in the area of the workings is 6000 feet. Available observations are too few to establish with certainty the strike and dip of the axis of the syncline, which would make the construction of a reliable profile through the structure possible. Hence the problem as to what happens to the Ottertail limestone at depth below the workings remains obscure.

ORE OCCURRENCE and NATURE OF ORE

Lodes of more or less impure barite occur in the Ottertail limestone mainly near its contact with the overlying Goodsir slates. On the northwestern wing of the syncline such barite lodes can be traced intermittently for a distance of 12 miles, according to Dr. C. S. Evans of the G. S. of Canada.

At the Giant a large body of impure barite occurs as replacement in the dolomitic Ottertail limestone. Its outcrop is shown on map No. 2. This barite is partly mineralized carrying argentiferous galena, pyrite, and small quantities of sphalerite which are believed to have been deposited after the

barite. The ore has no distinct walls, occurring irregularly disseminated though following on the whole certain indistinct zones of shattering.

The Giant orebody may best be described as a lode or chimney, striking N45°W, dipping 45°SW, and pitching about 60°NW.

The ore consists of dense to medium crystalline argentiferous galena (1 oz. Ag; 6.3% Pb), with a little sphalerite and some iron pyrites. Gold is present only in traces. The gangue minerals are baryte, silicious dolomitic limestone, calcite, and quartz.

ORE SHOWINGS

The development workings comprise 6 tunnels and 10 diamond drill holes, shown on Map No. 3.

Tunnel No. 5 is the main tunnel. 85 feet of drifting on the ore has been done from it and a raise, 210 feet long, in ore connects it with Tunnel #3.

The crop of the deposit is exposed for a distance of 320 ft. in the open cut or glory hole shown on map No. 3. Attention is called to the fact that such mining operations as existed here in former years centered on its extreme west end.

(east?)

Farther west of the main crop several islands of more or less mineralized barite have withstood erosion on the steep hill slope, as shown on Map No.2. Under one of them, Tunnels No. 4 and No. 6 were driven on the Rothchild claim.

Tunnel No. 6 disclosed near its face only a few bunches of barite carrying specks of galena. It was stopped in Ottertail limestone formation without reaching the Goodsir slates.

The mineralization follows only in a very general way the fault contact delimitating the Ottertail limestone to the southwest. Particularly to the southeast mineralization is found in many places 50 to 100 ft. away from the contact in the limestone. This makes it difficult to state positively whether

or not

Tunnel No. 6 has penetrated far enough into the Ottertail limestone to disprove the continuation of the ore in this direction. It is likely, considering the evidence furnished by Tunnel No. 1 and Diamond Drill Holes 1,2,3,6, and 10.

Tunnel No. 4 but 6.1 ft. of low grade ore near its face, two channel samples of which assay over -

5.0 ft. - Tr. Au, 0.55 ozs. Ag, 2.9% Pb Tr. Zn.

Tunnel No. 1 penetrated the entire Ottertail series exposing some ore near the fault contact. This ore shows exceedingly irregular and bunched occurrence. In the lower part of the west wall of the Tunnel, a sample of good ore might be obtained over a width of 15 ft. Near the back only 2.8 ft. could be sampled, assaying:

Tr. Au., 0.9 ozs. Ag, 4.95% Pb, Tr. Zn.

In the east wall of this Tunnel there are several bunches of ore and a lead which might be considered the continuation of the ore in the west wall. It assays over a width of -

3.5 ft. Tr. Au, 0.8 ozs. Ag, 6.10% Pb Tr. Zn.

The good samples obtained by several engineers in Tunnel No. 1 were taken near the floor on the west side. They are in no way representative of the ore occurrence here.

Diamond Drill Holes Nos. 1,2, and 10 found no ore, establishing only the continuation of the ore bearing formation and showing at best slightly mineralized barite.

Diamond Drill Holes No. 3 and 6 found low grade ore of narrow width.

The cumulative evidence of all the development workings described so far discounts in my opinion the continuation of ore to the southeast quite thoroughly.

Ore at the Giant is confined to a small shoot or chimney developed by Tunnels No. 5,3 and 2, by the Glory Hole, and by D.D.Holes Nos. 4,5,8 &9.

Diamond Drill Hole No. 7 cut the tail end of the Ottertail lime, 3 ft. wide, between Dogtooth and Goodsir slates. It found no ore and disproves a continuation of ore on No. 5 Tunnel level to the northwest.

The ore exposed on No. 5 Tunnel level is shown on the annexed assay map No. 4. It is 26.9 ft. wide where pierced by the Tunnel. 65 ft. to the east it is 10.5 ft. wide.

Good ore is exposed in the face northwest of the tunnel, and 10 ft. of it were cut in Diamond Drill Hole No. 8, 25 ft. NW of Tunnel No. 5.

Allowing for a continuation of the orebody for 15 ft. to the NW of Diamond Drill Hole No. 8, and 30 ft. to the SE of the East Crosscut, - a length of ore shoot of 140 ft. is obtained, with an estimated average width of 13.1 ft. arrived at as follows:

| | |
|---|------------|
| Average width of ore in D.D. Hole No. 8 | 10.0 ft. |
| " " " " Tunnel No. 5 | 26.9 |
| " " " " East Crosscut | 10.5 |
| " " " " 30 ft. SE of East Crosscut | 5.0 |
| | <hr/> |
| | 52.4 ft. = |
| | 13.1 ft. |

The average metal content of the ore on No. 5 Tunnel level is, according to my sampling:

1.4 ozs. Ag. 12.0% Pb. 0.3% Zn

On the Intermediate Level the orebody is 16.5 ft. wide and assays:

1.8 ozs. Ag. 9.35% Pb 0.1% Zn

The raise exposes only a part of the orebody. For the first 180 ft. it assays over a width of 4.9 ft.

3.3 ozs Ag. 12.0% Pb --Zn

The upper part of the Raise gets out of the ore on the rake of the shoot, there being only a narrow seam of limestone left here between the hanging and footwall slates.

Tunnel No. 3 was driven because of the misconception that the orebody followed the contact of the Goodsir slates and Ottertail limestone, instead of the fault contact of the latter with the Dogtooth slates. It shows ore only

near its face abutting on the footwall Goodsir slates and does not penetrate the total width of the ore. This ore assays over-

7.0 ft. Tr. Au 2.9 ozs. Ag 8.10% Pb 4.6% Zn

Diamond Drill Hole No. 4 which cuts under this showing at a depth of 65 ft. on the dip found mineralized rock assaying 1.75 ozs. Ag. and 1.9% Pb between 141 and 169 ft., according to the records of Mr. A.W. Davis. An examination of the drill core shows, however, that between 140 and 142 ft. 2 ft. of good ore was cut estimated to assay 10% Pb or better.

Diamond Drill Hole No. 5 struck 8 ft. of good ore between 153 and 161 ft. assaying:

| | | |
|---------------|----------|---------|
| 13.5 ozs. Ag. | 34.9% Pb | 0.1% Zn |
|---------------|----------|---------|

and between 174 and 178 ft., 4 ft. of ore assaying:

| | | |
|------------|----------|---------|
| 4.7 ozs Ag | 33.4% Pb | 0.1% Zn |
|------------|----------|---------|

From 161 to 174 and from 178 to 256 ft. it shows low grade mineralized lode material.

Tunnel No. 2 was driven 67 ft. above Tunnel No. 3 along the contact of the Goodsir slate and Ottertail limestone. It cut, like Tunnel No. 3, the tail end of the ore shoot abutting on the footwall slate. On the contact, ore rich in sphalerite was found. A 20-foot winze was put down here, which is now inaccessible, and a carload lot of 35% zinc ore is said to have been shipped from this place.

The old open cut stope lies above Tunnel No. 2. Higher up the hill, the outcrop is found in the cliff where it has been sampled for 320 ft. on the pitch of the deposit, assaying over an indicated average width of 10.3 ft.

| | | |
|-------------|----------|---------|
| 1.3 ozs Ag. | 10.0% Pb | 0.3% Zn |
|-------------|----------|---------|

This sampling does not mean a great deal as the ore deposit in the western part under the crop has been eroded.

ORE RESERVES

Taking into account the lack of definite walls, the irregular character of the occurrence, and the maladroit development in the upper tunnels, it is difficult to estimate ore reserves in this deposit with any degree of accuracy.

Probable Ore

By properly weighing the results obtained in the workings from Tunnels No. 5, No. 3, and No. 2, in the Open Cut and crop, and in Diamond Drill Holes 4, 5, 8, and 9, - I estimate a length of ore shoot of 140 ft., an average width of 11.25 feet, and a height of ore shoot above Tunnel No. 5 level of 240 feet to Tunnel No. 3 and of 380 feet to the open cut.

Classing the ore for 180 ft. above and 40 ft. below the No. 5 Tunnel level as probable Ore, and allowing 8 cub. ft. of ore in place to the ton, (50%-60% BaSO₄) - I obtain -

$$\frac{140 \times 11.25 \times 220}{8} = 43,300 \text{ tons of Probable Ore}$$

assaying on an average: 1.7 ozs. Ag. 10.75% Pb 0.4% Zn.

Prospective Ore

1 ft. of lode on the dip, according to the above calculation, should contain - $\frac{140 \times 11.25 \times 1}{8}$ --- 200 tons of ore.

An extension of the orebody upwards to the open cut for 200 feet, and for some distance below the limits of Probable Ore may be considered Prospective.

One may therefore expect that if completely developed the Giant orebody may contain 100,000 tons of ore or thereabout.

The average assay value of my sampling, which by necessity was less thorough than that of Mr. A.W. Davis as shown on his assay plan, checks fairly well with his results: 10.75% Pb as against his 11% Pb. We disagree on tonnage, mainly because he allows 6 cub. ft. of ore in place to the ton as compared with my 8 cub. ft., secondly, because he bases his estimate of width on that shown in Tunnel No. 5, the East Crosscut, and in the Intermediate Level, measured horizontally and not at right angles to the dip, and disregarding all other evidence; finally, because he classes as "probable" a large part of the ore which I consider "prospective."

METALLURGY

No metallurgical tests on the Giant ore have been made at the Wallace Testing Plant because results obtained by the Consolidated Mining & Smelting Co. and by the Department of Mines in Ottawa show that this ore responds easily to flotation.

Tests made by the Consolidated Mining & Smelting Co. in October 1926 on heads assaying -

Tr. Au. 2.2 ozs. Ag. 10.8% Pb 1.9% Zn 1.3% Fe 4.1% S 59.1% SiO₂ 1.1% CaO gives 21.8% Pb concentrates by weight, assaying -

9.4 ozs Ag 46.3% Pb 7.6% Zn 7.6% Fe 12.2% S 4.8% SiO₂ - CaO

No mention is made of BaSO₄ which evidently forms the balance. The extraction is calculated at 86.8% of the silver, 94.2% lead and 84.3% zinc.

The amount of zinc in the sample tested is considerably above the average indicated by my sampling.

Flotation tests made in the laboratories of the Department of Mines in Ottawa show similar good extraction. The grade of the concentrates, however, is at best 55 percent lead.

FINANCIAL RETURNS

Assuming that a 60 percent concentrate can be made maintaining the same high grade of extraction and using as heads the average grade of the ore as ascertained by my sampling, the Giant ore would yield:

| | | | |
|----------------|--------------|--------------|--------------|
| Assay of Heads | 1.7 ozs Ag | 10.75% Pb | 0.4% Zn |
| In 100 tons | 170 ozs Ag | 1075 Pb | 40 Zn |
| Recoveries | <u>86.8%</u> | <u>94.2%</u> | <u>84.3%</u> |
| | 148 | 1015 | 33.7 |

Pb. Concts. $\frac{1015}{60} \approx$ 16.9 tons conct. 50% Pb 12.2 ozs Ag 1.6% Zn

Value of Pb. Conct. Lead @ £22 London, shipped to Trail Smelter

| | | | | |
|----------------------------------|---------------|-----------------------|---|--------------|
| 60 - 1.25 = 58.75 | 1175 lbs | <u>217</u> | | |
| | 88 " | <u>1250</u> | | |
| | <u>1087</u> " | @3.524 | = | \$38.31 |
| Ag. 12.2 ozs. @ 54¢ x 95 | | | | 6.25 |
| | | | | <u>44.57</u> |
| Treatment | | | | 10.78 |
| Base | \$8.00 | | | <u>33.79</u> |
| Zn 1.6% @ 20¢ | .32 | Freight 2.50 + 5.60 - | | 8.10 |
| S. max. | 2.00 | Net per ton | | <u>25.69</u> |
| Moisture 8% @ 10¢ | .80 | | | |
| | <u>11.12</u> | | | |
| CaO + SiO ₂ 4.8% @ 7¢ | .34 | | | |
| | <u>10.78</u> | | | |

Realizable value per 100 tons - 16.9 tons @ \$25.69 = \$434.16

or per ton - \$4.34

The Giant would justify work on a small scale only, at best 100 tons per day or thereabout, and there are no indications that sufficient ore could be developed to justify large scale operations. Total production costs of mine and mill are estimated at \$4.50 to \$5.00 per ton.

CONCLUSIONS

With London lead at £ 22, the Giant ore would net no profit, and lead is lower still today.

The price of the property is \$160,000 and its equipment would require at least \$100,000, possibly \$150,000.

Freight rates quoted from Spillimachene to East Helena are \$10.80½ as compared with \$5.60 to Trail. Hence the financial outcome would hardly be improved by importing the concentrates into the United States.

At present low metal prices the Giant is not an attractive mining proposition and the purchase of this property is not recommended.

In view of the above it has not been considered necessary to enlarge here upon the details of local costs, economic and mining conditions, which would have been pertinent to this report had the outcome been more favorable.

Wallace, Idaho
October 7, 1927.

Respectfully submitted
(Signed) H.A.Kursell.