

THE DOWA MINING CO., LTD. (JAPAN)

010344

PROPERTY SHEBA COPPER MINES LTD.

HOLE No. S-71-12

DIP TEST		
Footage	Angle	
	Reading	Corrected
No Test		

Hole No. S-71-12 Sheet No. \_\_\_\_\_  
 Section \_\_\_\_\_  
 Date Begun August 4, 1971  
 Date Finished August 10, 1971

Lat. L 8 N  
 Dep. 58 W  
 Bearing -90  
 Elev. Collar 4980 A.S.L.

Total Depth 0-748'  
 Logged By. L.W. Saleken  
 Claim JAY #104 Fr.  
 Core Size B.Q.W.L.

DEPTH	DESCRIPTION	SAMPLE No.	FOOTAGE	WIDTH OF SAMPLE	o/o					
					Cu	Mo	MoS <sub>2</sub> (Cal)	Au	oz/T	Ag
0-33	Overburden-glacial till									
33-748	M.g. granodiorite; Propylitic alt.;									
	f.g. diorite dykes; Mineralization assoc. with								No Assay	
	flaky sericite shear zones & Fr									
33-36	Strong sericite-clay alt. ep-ch strong in mafics	1901	33-40	7	<0.01	0.002	0.003			
	& Fr, weathered									
36-60	Weak propylitic; weathered, ca on Fr									
41-43	Fault, strong sericite-clay alt.									
45.5-46.5	Shattered, Fr @ -60°, strong sericite-clay alt.									
60-86	Weathered, strong clay alt, ca-zeol common	1904	60-70	10	<0.01	0.001	0.001			
	in Fr, Iron staining mod.									
68	Fault									
73	Fault									
78	Fault									
84-85	Fault, blocky									
86-111	Unaltered	1907	90-100	10	<0.01	0.001	0.002			













