DIAMOND DRILL RECORD

010404

HOLE NO: 72-1

PROPERTY: Chetamat Exploration Ltd.

LOCATION: 112+00 E

GRID: 315°

DIP: -44°40'

LENGTH: 500 ft.

ELEVATION: 4100' BSL ± 50'

CLAIM NO: Rugs "8 & Chet "4 Fr.

STARTED: Feb 25th 1972

CORE SIZE: BQ

DATE LOGGED: Mar 15, 16/72 Mar 20/72

EDITION: —

COMPLETED: March 29th 1972

DIP TESTS: 200' - 42°
500' - 42 3/4°

LOGGED BY: Jay D. Murphy

PURPOSE: Test I.P. Anomaly

FOOTAGE from	FOOTAGE to	DESCRIPTION	SAMPLE NO.	FOOTAGE from	FOOTAGE to	LENGTH
0.0'	85.0	Casing - Hole NQ 2.5"				
85.0	168.6	Conglomerate: Cobbles Variety, Local, mod. grey green, med. grained, massive, poorly sorted, except for slight elongation of fragments and pockets between cobbles near surface, estimated composition: 80% Fragments (hornblende) as and grained black or ragged, 10% commonly pebbles, 10% light grey green plagioclase & K-feldspar, ~20% Qtz as embedded subrounded fragments, minor biotite ± Py, some calcareous cobbles, occasional flash of Py, magnetic; discontinuous common to the contact of the cobbles, core strength broken up "blocky" due to numerous disc. fractures @ 25-55° to core axis, 85.0'-2" gauge, slip altitude not determined. 91.0-60.0': 5.0' lost or ground core. 97.0'-8" ch Bentonite w. Malachite alt @ 45°, associated Mag. 120-11.0 - 2.5' lost or ground core. 129.0-5" gauge well defined @ 60°. 167.5-170 - slightly "crumbly" section with some development of gouge, Silica partly Carbonaceous, minor disseminated carbonate & Chrysotile veins, magnetic above last 2'				

CANADIAN SUPERIOR EXPLORATION LIMITED

DIAMOND DRILL RECORD

HOLE NO: 72-1.

PAGE NO: 3

FOOTAGE from	FOOTAGE to	DESCRIPTION	SAMPLE NO:	FOOTAGE from	FOOTAGE to	LENGTH
162.2	218.3	GREENSTONE (Cont'd) :				
		206.0 - 216.5 - Fault zone, strongly fractured & broken with abundant gouge developed, 6" lost core from 6-10" plastic gouge.				
		215.6 - 10" crushed fault breccia consisting of pervasive rock fragments in matrix of gouge & rock flour (?)				
		203.4 - 215.0: dyke or remnant of Gowchaa; Variety granodiorite, contacts indeterminate due to faulting.				
218.3	232.0	218.3 - 232.0 - dyke of Mitchell Brook; similar to previous dyke but finer grained w. higher mafic content, top cht. sharp but irregular, probably faulted, lower cht. indeterminate due to strong development of fault gouge over final 12".				
232.0	500.0	GRANODIORITE: Chotawisy Variety; similar to previous section,				
		241.2 - well developed slip w. gouge @ 40-45°				
		242.0 - 6" crushed section w. gouge				
		255.3 - 2.6" dyke Mitchell Brook, contacts sharp, unchilled @ 45-50°, top cht. offset along slip @ 30°, L-H,				
		270.0 - 276.0 - 12" lost core				
		276.0 - 288.0 - 24" lost core				

CANADIAN SUPERIOR EXPLORATION LIMITED

DIAMOND DRILL RECORD

HOLE NO: 72-1

PAGE NO: 2

FOOTAGE from	FOOTAGE to	DESCRIPTION	SAMPLE NO:	FOOTAGE from	FOOTAGE to	LENGTH	Cu	MoS_2
85.0	163.0	GRANODIORITE: (cont'd)						
		Core recovery 85.0 to 100.0' = 80%						
		100.0-100.0 - sand pebble dyke.						
		107.7 - dia @ 45° to c.a.						
		132.9 - well developed slip @ 45°						
		152.1 - " " " " "	226	152.0	162.0	10.0	0.01	0.004
		153.1 - slip @ 30° to c.a. with Pyrite & Chalcopyrite.	227	162.0	163.0	1.0	0.21	0.004
163.0	229.0	GRANODIORITE: Chalcopyrite Muscovite porphyritic altered pinkish grey, med. grained equigranular, uniform, massive, plag. feldspar fractured & chalky in parts, amphiboles frequently altered to chlorite & magnetite. Considerable evidence of recent slip & fractures with frequent development of 'gouge' resulting in 'blocky' core and only fair recovery.	228	163.0	173.0	10.0	0.02	0.004
		Estimated composition:						
		Hornblende - 15%						
		Biotite 5%						
		Quartz 10-15%						
		K feldspar 10-15%						
		Plag feldspar 50-55%						
		Magnetite 1-2%						
		170.5-175.0 - 10" lost core.						
		185.0-187.0 - 6" " "						
		125.0 - 12" section strongly broken up & bleached, chloritic 'gouge' abundant						
		Recovery 100' to 200' = 86%						
		204.1 - 1/2" gouge along slip @ 55°, epidote developed over 1" along lower contact.						

CANADIAN SUPERIOR EXPLORATION LIMITED

DIAMOND DRILL RECORD

HOLE NO: 72-1

PAGE NO: 4

FOOTAGE from	FOOTAGE to	DESCRIPTION	SAMPLE NO:	FOOTAGE from	FOOTAGE to	LENGTH
232.0	500.0	GRANODIORITE - (cont'd)				
		284.5 - 80° section of 'gouge' & fault breccia, altitude open 45°,				
		292.0 - 302.0 - Fault Zone - core strongly fractured, brecciated, mylonitized, final 2° open breccia & 'gouge', altitude core 60°				
		Recovery 200' to 300' = 89%				
		~~302.0~~ - 22° strongly developed breccia & 'gouge'				
		329.5 - 6" 'gouge'				
		342.0 - 12" 'gouge'				
		332.0 - 337.5 - entire section is 'blocky' soft, brecciated, mylonitized with strong movement @ 50° mainly with many subsidiary fractures & slips at various angles to core, final 18° consists entirely of plastic 'gouge' with rock fragments, from final footage rock appears normal, hard and relatively unaltered with little evidence of movements, minor fracturing @ 45-50°				
		Recovery 300' to 400' = 89%				
		418.0 - 422.0 = 3.5' ground core				
		462 - 36" section fractured & 'blocky'				
		470.0 - 478.0 - fractured, 'blocky', some 'gouge' developed				
		Recovery 400' to 500' = 96%				
	500.0	END OF HOLE				