

— Quesnel Mining Division —  
CARIBOO DIST.



Traverse  
 Main Side of Quesnel River

Sta.	Bearing	Dist.
1	5.19 10 W	5.0
2	7.46 58 W	46.2
3	7.75 28 W	75.2
4	4.82 44 W	50.7
5	7.79 23 W	37.9
6	5.86 28 W	248.8
7	5.07 13 W	38.5
8	5.80 47 W	412.4
9	5.81 36 W	34.0
10	5.78 59 W	334.7
11	5.24 83 W	46.0
12	5.47 40 W	194.0
13	5.19 34 W	17.2 W
14	4.03 34 W	228.0
15	4.83 4 W	22.8
16	7.72 49 W	175.5
17	9.71 3 W	67.0
18	8.81 17 W	344.7
19	5.79 35 W	204.0
20	5.80 13 W	203.2
21	5.73 50 W	80.2
22	5.81 32 W	189.0
23	5.81 3 W	213.4
24	5.81 3 W	213.4

To Line

Sta.	Bearing	Distance
1	7.73 50 W	46.7
2	7.23 22 W	340.3
3	7.33 47 W	474.8
4	7.52 54 W	343.3
5	7.74 47 W	3.8
6	7.89 15 W	192.2
7	8.08 27 W	46.9
8	7.81 32 W	240.0
9	7.48 28 W	57.5
10	7.19 18 E	5.0

0 1 2  
 inches

0 1 2 3 4 5  
 centimetres

This reference scale bar has been added to the original image. It will scale at the same rate as the image, therefore it can be used as a reference for the original size.

Note:-  
 Black Circles indicate Posts.  
 Heavy lines shown are run on the ground.  
 Dotted lines not run.  
 Foot Numbers are shown.

Scale:- 400 feet = 1 inch

Edward D. Frost - d.l.s.

013680