

#### LONGITUDINAL

BLOCK	WIDTH x LENGTH x STRIKE	M <sup>3</sup>	TONS	Au opt	Ag opt	Au oz	Ag oz
67	19.9 x 45 x 60	53,730	174,378	0.217	3.27	37,840	570,216
68	28.8 x 50 x 60	86,400	280,407	0.035	0.98	9,814	274,799
69	7.0 x 50 x 60	21,000	68,154	0.091	0.32	6,202	21,809
<b>TOTAL</b>		<b>522,939</b>	<b>0.103</b>	<b>1.66</b>	<b>53,856</b>	<b>866,824</b>	

#### SECTIONAL

BLOCK	AREA x STRIKE	M <sup>3</sup>	TONS	Au opt	Ag opt	Au oz	Ag oz
67	1825 x 60	109,500	355,377	0.134	2.22	47,621	788,937
68	1425 x 60	85,500	277,486	0.035	0.98	9,712	271,936
69	575 x 60	34,500	111,968	0.091	0.32	10,189	35,830
<b>TOTAL</b>		<b>744,831</b>	<b>0.091</b>	<b>1.47</b>	<b>67,522</b>	<b>1,096,703</b>	


Notes: 1. Longitudinal calculations are based on high grade sections reported. Sectional calculations incorporate contiguous intervals grading 0.05 oz/ton gold equivalent.

2. Both methods use 0.308 cubic metres per ton.

3. Dip extension and strike distance are determined equidistant from nearest drill hole or 25metres for both methods.

Figure 1  
SCHEMATIC OF LONGITUDINAL VS SECTIONAL  
ORE RESERVE CALCULATIONS

20831



This reference scale bar  
has been added to the  
original drawing with  
the intent that it will  
be used as a reference for the  
original size.