

SUMMARY OF INTERSECTIONS 675144

*midway/
Silvertip*

DDH	Inclination	Azimuth	FROM-TO (ft)	LENGTH (ft)	ZINC %	LEAD %	ZINC-LEAD %	SILVER oz/ton	DDH	Inclination	Azimuth	FROM-TO (ft)	LENGTH (ft)	ZINC %	LEAD %	ZINC-LEAD %	SILVER oz/ton
81-1	-70°	328°	404.0- 410.0	6.0	4.96	2.90	7.86	3.52	84-53	-90°	0°	196.9- 214.9	18.0	15.31	8.83	24.14	12.13
81-3	-70°	300°	373.1- 381.1	8.0	5.24	11.80	17.04	16.18	84-54	-90°	0°	262.8- 273.0	10.2	10.82	12.30	23.12	19.54
82-7	-70°	270°	633.6- 650.0	16.4	4.85	3.07	7.92	11.05	84-55	-80°	270°	426.2- 436.4	10.2	10.97	2.89	13.86	4.37
82-8	-70°	270°	671.3- 700.5	29.2	15.80	10.58	26.38	20.15	84-57	-90°	0°	339.9- 369.8	29.9	11.36	12.95	24.31	17.40
			740.3- 746.3	6.0	7.32	9.40	16.72	15.96	84-59	-80°	270°	580.2- 588.2	8.0	19.16	1.85	21.01	3.97
82-10	-70°	270°	805.8- 813.3	7.5	6.30	0.86	7.16	4.55	84-60	-90°	0°	351.2- 392.7	41.5	9.23	15.34	24.57	21.30
			823.2- 841.9	18.7*	5.95	7.95	13.90	11.30	84-61	-90°	0°	220.8- 231.0	10.2	7.53	7.88	15.41	7.53
82-11	-80°	270°	1037.1-1046.0	8.9	15.54	7.80	23.24	17.40	84-62	-90°	0°	245.1- 253.9	8.8	5.66	3.83	9.49	9.25
82-12	-70°	270°	935.0- 941.0	6.0	6.22	6.46	12.68	11.03	84-63	-80°	270°	457.9- 465.9	8.0	8.70	0.76	9.46	3.49
82-16	-80°	270°	1257.9-1281.8	23.9	18.96	5.63	24.59	9.52				510.0- 518.0	8.0	9.52	2.06	11.58	2.79
82-17	-80°	270°	1582.5-1588.5	6.0	17.61	1.47	19.08	11.36	84-66	-80°	270°	642.8- 648.8	6.0	5.74	1.96	7.70	3.94
82-18	-80°	270°	1015.8-1024.0	8.2	7.40	2.38	9.78	4.75	84-67	-80°	270°	769.9- 775.9	6.0	5.99	1.25	7.24	4.83
83-21	-70°	270°	761.0- 774.6	13.6	7.45	5.90	13.35	8.13	84-69	-90°	0°	367.5- 375.0	7.5	6.94	2.02	8.96	3.43
			861.9- 876.8	14.9	14.07	17.44	31.51	25.15				382.2- 391.4	9.2	11.35	6.04	17.39	15.15
83-24	-70°	270°	667.8- 673.9	6.1	3.49	4.71	8.20	8.36	84-73	-90°	0°	135.2- 145.7	10.5	12.49	4.69	17.18	6.54
			687.7- 693.6	5.9	6.80	4.60	11.40	7.31	84-77	-80°	270°	738.2- 778.2	40.0	12.47	10.11	22.58	15.66
83-26	-80°	270°	1853.6-1860.2	6.6	32.31	0.04	32.35	0.34				975.1- 983.6	8.5	9.32	14.52	23.84	20.75
83-29	-80°	270°	212.9- 223.4	10.5	14.92	11.43	26.35	18.10	84-78	-90°	0°	89.9- 106.6	16.7	7.21	10.30	17.51	10.71
83-30	-80°	270°	898.9- 904.8	5.9	7.31	0.20	7.51	3.49	84-81	-80°	270°	706.2- 714.2	8.0	5.51	17.46	22.97	31.89
83-31	-80°	270°	1545.0-1548.9	3.9	3.55	4.20	7.75	5.05	84-82	-80°	270°	752.6- 760.6	8.0	13.48	3.00	16.48	9.31
83-40	-80°	270°	1043.0-1049.7	6.7	6.60	4.34	10.94	10.10	84-84	-80°	270°	1023.3-1061.7	38.4	15.93	8.07	24.00	14.28
			1450.8-1456.7	5.9	0.47	13.14	13.61	18.58	84-89	-80°	270°	782.2- 788.3	6.1	8.24	1.01	9.25	5.82
83-43	-80°	270°	64.6- 77.7	13.1	1.35	10.15	11.50	14.10	84-91	-90°	0°	1259.6-1285.8	26.2	12.34	6.94	19.28	16.80
83-44	-80°	270°	433.2- 439.1	5.9	7.18	1.60	8.78	3.66	84-95	-90°	0°	1293.9-1301.1	7.2	4.39	4.62	9.01	10.06
83-50	-80°	270°	208.0- 217.2	9.2	11.05	0.23	11.28	0.39	84-97	-90°	0°	1017.1-1056.1	39.0	7.07	10.15	17.22	15.80

*Assay based on 9.5 feet of core recovered

Regional Resources Ltd.

1980 - 1055 West Hastings Street, Guinness Tower, Vancouver, B.C. V6E 2E9
Telephone: (604) 669-3398

NEWS

For Release:

November 28, 1984

Contact:

J. W. Stollery

(604) 669-3398

MIDWAY PROPERTY - SILVER, LEAD, ZINC

Underground - Tonnage and Grade - Budget

Initial work to provide underground access to the Silver Creek North deposit began on October 12. To date 525 feet of 15' x 14' decline has been completed. The underground program will continue throughout the winter.

A revised mineral inventory reflecting results to date has been calculated as follows:

	<u>Short Tons</u>	<u>oz/ton Silver</u>	<u>% Lead</u>	<u>% Zinc</u>	<u>% Lead + Zinc</u>
Discovery	3,813,307	10.84	5.40	13.34	18.74
Silver Creek	2,847,920	13.04	8.45	9.98	18.43
	<u>6,661,227</u>	<u>11.78</u>	<u>6.70</u>	<u>11.90</u>	<u>18.60</u>

The Silver Creek deposit includes two high grade cores - North defined by drill holes 29, 53, 54, 57 and 60 - South defined by drill holes 77, 84, 91 and 97.

	<u>Short Tons</u>	<u>oz/ton Silver</u>	<u>% Lead</u>	<u>% Zinc</u>	<u>% Lead + Zinc</u>
Silver Creek North	796,242	19.70	13.96	11.69	25.65
Silver Creek South	670,650	19.00	11.47	13.03	24.50
	<u>1,466,892</u>	<u>19.38</u>	<u>12.82</u>	<u>12.30</u>	<u>25.12</u>


Both the Discovery and Silver Creek deposits remain open to further expansion.

The 1984 budget has been increased to \$6.2 million.

The Midway property is 51% owned and managed by Regional with Canamax Resources Inc. and Procan Exploration Company together holding a 49% interest.

Regional is listed on the Toronto and Vancouver Stock Exchanges under the symbol RGL.

REGIONAL RESOURCES LTD.



By: John W. Stollery, President

The Vancouver Stock Exchange has neither approved nor disapproved the information contained herein.