

Eaglehead Update

6

October 7th, 1980

Diamond drill assay results from two additional holes have now been received.

Results are as follows:

<u>Hole No.</u>	<u>Intersection</u>	<u>Footage</u>	<u>% Copper</u>	<u>% Molybdenum</u>
43	168.0-216.5	58.5	0.95	0.003
44	56.0- 76.0	20.0	0.21	0.002
44	76.0-166.0	90.0	0.80	0.006
44	166.0-191.0	25.0	0.16	0.001
44	191.0-210.5	19.5	0.07	0.001

Additionally, in Hole 44 the section from 210.5' to 274.0' has been sampled but assays are not yet available.

Hole 43 was drilled 1500' northwest of the previously defined "Camp Zone". Hole 44, 6000' to the southeast, explored an extension of the "Bornite Zone" some 400' from Hole #40 drilled earlier in the season.

Three additional holes have been completed and drilling operations are being continued until freeze-up. Assay results will be issued as they become available.

The mineralized zone is represented on the section printed on the back of this Update.



H. S. Aikins
President

NUSPAR RESOURCES LTD.

One of a series of Progress Reports on the 1980 Exploration
Program at Eaglehead Lake, British Columbia

Prepared and issued by NUSPAR RESOURCES LTD.
305-535 Thurlow St., Vancouver, B. C. V6E 3L2

SURFACE

OVERBURDEN (Gravel and clay)

DDH 40

0.07 % Cu

68.0
(83.0 ft)

0.93 % Cu
0.003 % Mo
0.19 oz Ag

215.0 (2.5 ft)
229.0 (13.0 ft)
230.0

0.10 % Cu
463.0 (100.0 ft)

0.46 % Cu
0.023 % Mo

(246.0 ft)

0.40 % Copper

809.0

DDH 42

14 % Cu
83.0 (21.5 ft)
104.5

0.50 % Cu
0.002 % Mo (229.5 ft)

2.00 % Cu
0.069 % Mo
420.5 (7.5 ft)
428.0

0.74 % Cu
0.02 % Mo
0.10 oz Ag

(84.5 ft)

0.40 % Copper

725.0

WASTE ROCK
(above potential ore)

MINERALIZED ROCK
(potential ore grade)

WASTE
(within zone)

EAGLEHEAD PROJECT
Bornite Zone

SECTION 96

Scale: 0 100 Feet

LEGEND

- Minor Copper
- Above 0.4 % Copper

650 Feet Below Surface

IDEALIZED DIAGRAM TO ILLUSTRATE
POSSIBLE OPEN PIT OUTLINE