

800424

AGASSIZ - WEAVER PROJECT
SENECA DEPOSIT

HOLE NO.	FOOTAGE	THICKNESS (FEET)	OZ/TON		PERCENT		
			GOLD	SILVER	COPPER	LEAD	ZINC
1	ore zone absent						
2	ore zone absent						
3	lost hole, abandoned in fault zone						
4	148.0-154.5	6.5	.016	1.11	0.19	0.07	1.33
5	401.0-406.3	4.8	.010	0.70	0.66	0.06	1.67
6	398.4-402.6	4.2	.203	4.21	5.11	0.04	17.70
7	188.0-193.0						
	198.0-224.0	31.0	.037	0.87	0.61	0.10	3.65
	206.5-211.0	4.5	.108	2.35	2.40	0.80	11.55
	218.0-224.0	6.0	.053	2.04	0.22	0.13	4.80
8	78.0-81.0	3.0	.042	0.51	0.16	0.06	1.22
9	147.0-168.4	21.4	.029	0.77	0.77	0.05	3.46
	147.0-148.0	1.0	.316	4.94	0.80	0.11	31.85
	164.4-168.4	4.0	.040	1.70	3.53	0.13	4.80
10	106.2-112.4	6.2	.042	1.27	0.60	0.10	3.45
	133.2-150.6	16.4	.051	2.69	1.38	0.22	5.05
	156.5-167.0	10.5	.016	1.51	0.40	0.18	3.12
	133.2-138.8	5.6	.102	4.58	1.08	0.41	11.10
	144.7-148.6	3.9	.050	4.27	4.40	0.28	4.50
11	251.9-270.0	18.1	.049	1.58	0.71	0.09	5.03
	288.0-296.0	8.0	.014	0.28	1.84	0.01	0.44
	260.0-270.0	10.0	.071	2.14	1.48	0.10	4.54
12	Lost hole, abandoned in fault zone						
13	331.7-333.6	1.9	.086	1.89	1.56	0.28	9.70
14	Holes 14 & 15 drilled very low grade mineralization in the Vent						
15	area consisting of veinlets & stringers of pyrite and quartz.						
16	Thick sulphide zone, very low grade						
17	74.0-75.9	1.9	.012	0.82	1.22	0.04	1.60
18	346.0-364.0	18.0	.012	0.68	1.19	0.36	2.87
	378.0-385.5	7.5	.007	0.30	0.14	0.09	2.25

AGASSIZ - WEAVER PROJECT

SENECA DEPOSIT

HOLE NO.	FOOTAGE	THICKNESS (FEET)	OZ/TON		PERCENT		ZINC
			GOLD	SILVER	COPPER	LEAD	
1	ore zone absent						
2	ore zone absent						
3	lost hole, abandoned in fault zone						
4	148.0-154.5	6.5	.016	1.11	0.19	0.07	1.33
5	401.0-406.3	4.8	.010	0.70	0.66	0.06	1.67
6	398.4-402.6	4.2	.203	4.21	5.11	0.04	17.70
7	188.0-193.0	36.0	.032	0.75	0.53	0.09	3.14
	198.0-224.0	31.0	.037	0.87	0.61	0.10	3.65
	206.5-211.0	4.5	.108	2.35	2.40	0.80	11.55
	218.0-224.0	6.0	.053	2.04	0.22	0.13	4.80
8	78.0-81.0	3.0	.042	0.51	0.16	0.06	1.22
9	147.0-168.4	21.4	.029	0.77	0.77	0.05	3.46
	147.0-148.0	1.0	.316	4.94	0.80	0.11	31.85
	164.4-168.4	4.0	.040	1.70	3.53	0.13	4.80
10	106.2-112.4	33.8	.030	1.77	0.79	0.16	3.42
	133.2-150.6	6.2	.042	1.27	0.60	0.10	3.45
	156.5-167.0	16.4	.051	2.69	1.38	0.22	5.05
	133.2-138.8	10.5	.016	1.51	0.40	0.18	3.12
	144.7-148.6	5.6	.102	4.58	1.08	0.41	11.10
11	251.9-270.0	3.9	.050	4.27	4.40	0.28	4.50
	251.9-270.0	18.1	.049	1.58	0.71	0.09	5.03
	288.0-296.0	8.0	.014	0.28	1.84	0.01	0.44
	260.0-270.0	10.0	.071	2.14	1.48	0.10	4.54

8 holes.

16.0

.038 1.27 0.79 0.10 3.82
 @ \$4000 @ \$8.10 @ 62¢ @ 25¢ @ 47¢
 15.20 10.29 9.80 0.50 35.91
 = \$71.69 Area.

no dilution, 100% Recovery.

