## An Investigation of

## THE RECOVERY OF LEAD AND ZINC

from Rea Gold Silver Zone

submitted by

825131

## CORPORATION FALCONBRIDGE COPPER

Progress Report No. I

Project No. L.R. 3277

NOTE:

This report refers to the samples as received.

The practice of this company in issuing reports of this nature is to require the recipient not to publish the report or any part thereof without the written consent of Lakefield Research.

LAKEFIELD RESEARCH A Division of Falconbridge Limited February 23, 1987

# TABLE OF CONTENTS

	Page No.
INTRODUCTION	3
SUMMARY	4.9
I. Head Analysis	4
2. Flotation RGA Sample	5
3. Flotation RGA Sample	6
4. Flotation of Composite Sample	8
CONCLUSIONS AND DISCUSSIONS	10
SAMPLE PREPARATION	11
DETAILS OF TESTS	12 - 28

#### INTRODUCTION

In a letter dated January 23, 1987, Mr. A.J. Davidson of Corporation Falconbridge Copper requested some preliminary metallurgical testing on two Rea Gold Zone samples. The objective was to recover lead and silver into lead concentrate and zinc into a zinc concentrate or all three into a bulk sulphide concentrate.

LAKEFIELD RESEARCH

R.S. Salter

General Manager

W.T. Yen, Ph.D.

Senior Project Engineer

Experimental Work by: C.W. Payne

## SUMMARY

## 1. Head Sample

below:

The head assays of the two samples as received are shown in Table No. 1.

Table No. 1 - Head Sample Assays

	<u>RGA</u>	RGB
Pb (%)	54.9	3.39
Zn (%)	6.54	6.05
Cu (%)	3.21	1.63
Fe(%)	1.61	4.30
S(%)	14.4	8.65
Au (g/t)	4.22	0.98
Ag (g/t)	4649	649
Specific Gravity	5.25	3.07

The average calculated head assays obtained from the testwork are shown

	RGA	RGB	Composite
Pb(%)	55.1	3.13	18.1
Zn(%)	6.85	6.00	5.92
Cu(%)	3.26	1.59	2.15
Au (g/t)	4.47	1.07	2.10
Ag (g/t)	4875	660	1901

#### 2. Flotation of RGA Sample

A one kilogram sample was ground with soda ash and the zinc depressant Na<sub>2</sub>SO<sub>3</sub>, followed by lead flotation using the collector cyanamid AX 343 and AF 3477. The lead rougher tailing was then conditioned with lime and copper sulphate, followed by zinc flotation.

The results of Test No. 1 in Table No. 2 show that most of the metals, including Pb, Zn, Cu, Au and Ag, were collected into the lead rougher concentrate. Little metal was left for the zinc circuit. The lead rougher concentrate assayed 62.5% Pb and 5445 g/t Ag for a recovery of 94.5% of the lead, 95.3% of the silver and 90% ~ 94% of the other metals. The lead-zinc bulk concentrate prepared by blending the lead rougher and zinc rougher concentrate assayed 60.2% Pb and 5331 g/t Ag for a recovery of 98.5% of the lead and 99.2% of the silver and 97% ~ 99% of the other metals.

In Test No. 5, one rougher or cleaner bulk concentrate was obtained. The grade of the concentrate was similar to that of Test No. 1 but with a lower metals recovery. The excess amount of NaCN used may have caused the slightly lower recoveries.

Table No. 2 - Flotation Results for the RGA Sample

Tes No.	t Product	Wt %	Cu	As Pb	says, % Zn	%, g/t   Au	Ag	Cu	% Pb	Distribu   Zn	ition   Au	Ag
1	Pb Cl.Conc. Pb Ro.Conc. Zn Cl.Conc. Zn Ro.Conc. Pb-Zn Bulk Conc. Zn Ro. Tail	77.22 83.74 4.04 6.91 90.65 9.35	3.86 3.72 2.45 2.24 3.60 0.37	63.8 62.5 35.8 32.1 60.2 9.12	7.93 7.71 8.55 6.17 7.60 0.67	4.72 4.82 5.34 4.80 4.82 1.12	5668 5445 2920 2740 5331 460	90.3 94.3 3.0 4.7 99.0 1.0	88.9 94.5 2.6 4.0 98.5 1.5	88.1 92.9 5.0 6.2 99.1 0.9	81.3 90.2 4.8 7.4 97.6 2.4	89.8 95.3 2.4 3.9 99.2 0.8
<del></del>	Head (Calc.)	100.0	3.30	55.4	6.95	4.47	4875	100.0	100.0	100.0	100.0	100.0
5	Cleaner Conc. Bulk Conc. Bulk Tail	81.10 90.18 9.82	2.73 3.50 0.64	62.6 59.4 13.0	7.86 7.36 1.16	- - -	1	93.8 98.0 2.0	92.5 97.7 2.3	94.4 98.3 1.7		G G
	Head (Calc.)	100.0	3.22	54.9	6.75	-	•	100.0	100.0	100.0	9	

#### 3. Flotation of RGB Sample

The flotation procedure as tested on the RGA sample discussed in the previous section was also used for the TGB sample. The results for Test No. 2 as shown in Table No. 3 indicate that most of the valuable metals, including Cu, Pb, Zn, Au and Ag, reported to the lead rougher concentrate. Zinc depression was not very effective in the lead circuit. After three stages of cleaning the lead grade was only upgraded from 13.9% to 16.8%. This low grade lead concentrate was due primarily to contamination by other valuable metals, such as copper, gold and silver. In Test No. 6, sodium cyanide was tried to depress the other metals. The grade of the lead cleaner concentrate improved to 30.6%.

In Tests No. 4 and No. 7 as shown in Table No. 4, the separation of the copper from the lead in the lead cleaner concentrate was attempted. A copper concentrate of 30.2% Cu was produced and the lead concentrate was upgraded frofm 27.1% Pb to 32.9% Pb. There is a possibility to further upgrade the lead concentrate. There was excess depressant in Test Noi. 7 which not only depressed the lead but also the coper in the Cu-Pb separation circuit.

The zinc flotation has shown some promise. In Test No. 2, the zinc concentrate was upgraded from 19.8% Zn to 48.5% Zn. In Test No. 6, the zinc was upgraded from 10.1% to 47.1%. There was little zinc lost in the zinc cleaner stages.

In Test No. 7, the fineness of the grind was increased both in the primary and the regrinding stages. The zinc dropped in the lead first cleaner concentrate and was reported to the zuinc circuit. The zinc flotation was significantly improved. The zinc cleaner concentrate assayed 60.2% Zn and recovered 67.1% of the total zinc. Only 3.4% of the zinc was lost in the zinc cleaner stages.

# Summary - Continued

Table No. 3 - Flotation Result for the RGB Sample

Test		Wt		As	savs, %.	g/t		% Distribution					
No.	Product	%	Си	Pb	Zn	Au	Ag	Cu	Pb	Zn	Au	Ag	
	Pb Cl.Conc. Pb Ro.Conc. Zn Cl.Conc. Zn Ro.Conc. Pb-Zn Bulk Conc. Zn Ro.Tail	9.16 21.33 4.82 12.14 33.47 66.53	16.2 7.43 0.18 0.27 4.83 0.049	2.26 1.68 9.45	19.8 18.2	7.95 4.22 0.71 0.60 2.91 0.14	6443 2984 97.1 123 1946 12.7	96.0 0.5 2.0 98.0	46.8 90.0 3.3 6.1 96.1 3.9	24.8 60.2 38.2 39.3 95.5 0.5	68.2 84.4 3.2 6.9 91.3 8.7	89.4 96.4 0.7 2.3 98.7 1.3	
	Head (Calc.)	100.0	1.65	3.29	6.12	1.07	660	100.0	100.0	100.0	100.0	100.0	
	Pb Cl.Conc. Pb Ro.Conc. Zn Cl.Conc. Zn Ro.Conc. Pb-Zn Bulk Conc. Zn Ro.Tail	7.01 19.96 3.18 15.57 35.53 64.47	12.7 7.36 1.61 0.49 4.35 0.046	14.0 3.65 1.29 8.45	10.1			56.5 93.3 3.2 4.8 98.1 1.9	68.9 89.9 3.7 6.4 96.3 3.7	18.0 72.0 26.1 27.5 99.5 0.5	-		
	Head (Calc.)	100.0	1.57	3.12	5.74	-	8	100.0	100.0	100.0	0	5	

Table No. 4 - Flotation Result with Cu-Pb Separation on the RGB Sample

Test	Product	Weight		says %, g/t		% Distribution				
No.		%	Cu	Pb	Zn	Cu	Pb	Zn		
4	Cu Cl.Conc. Pb Cl.Conc. Cu-Pb Ro.Conc. Zn Cl.Conc. Zn Ro.Conc. Bulk Ro.Conc. Zn Ro.Tail	1.35 5.56 18.61 5.00 8.79 27.40 72.60	30.2 6.58 8.22 0.36 0.35 5.69 0.044	9.38 32.9 15.5 0.84 0.89 10.8 0.18	7.22 14.8 13.9 59.5 38.9 21.9 0.13	25.6 23.0 96.1 1.1 1.9 98.0 2.0	4.1 59.3 93.2 1.4 2.6 95.8 4.2	1.6 13.5 42.5 48.7 56.0 98.5 1.5		
	Head (Calc.)	100.0	1.59	3.08	6.10	100.0	100.0	100.0		
7	Cu Cl.Conc. Pb Cl.Conc. Cu-Pb Ro.Conc. Zn Cl.Conc. Zn Ro.Conc. Bulk Ro.Conc. Zn Ro.Tail	1.36 5.56 13.81 6.74 23.87 37.68 62.32	14.2 10.4 10.2 0.49 0.49 4.05 0.053	28.2 23.6 20.1 0.72 0.61 7.76 0.13	9.49 12.9 12.5 -60.2 17.9 15.9 0.095	12.4 37.1 90.4 2.1 7.5 97.9 2.1	12.8 43.6 92.5 1.6 4.8 97.3 2.7	2.1 11.9 28.6 67.1 70.5 99.1 0.9		
	Head (Calc.)	100.0	1.56	3.01	6.05	100.0	100.0	100.0		

## 4. Flotation of the Composite Sample

The composite sample, composed from the RGA and RGB samples in the ratio of 3 to 7, was tested for the standard lead-zinc flotation as described in the previous section. The results of Test No. 3 as shown in Table No. 5 indicate that the flotation characteristics of the composite sample were similar to the RGA sample. Most of the metals, including Cu, Pb, Zn, Au and Ag, were collected into the lead concentrate. The lead rougher concentrate assayed 51.2% combined lead and zinc with a recovery of 95.3% of the lead and 96.8% of the zinc, was an acceptable bulk concentrate. The lead rougher concentrate also assayed 4.29 g/t Au, 4096 g/t Ag for recoveries of 91.7% of the gold and 96.8% of the silver. Insufficient metal was left for reasonable zinc flotation.

Table No. 5 - Flotation Results for the Composite Sample (Test No. 3)

Product	Wt %	Pb	As:   Zn	says, %   Cu	6, g/t   Au	Ag	Pb	% j Zn	Distribu Cu	ution Au	Ag
Pb Cl.Conc. Pb Ro.Conc. Zn Cl.Conc. Zn Ro.Conc. Pb-Zn Bulk Conc. Zn Ro.Tail	20.67 44.99 6.29 20.61 65.60 34.40	42.2 38.4 2.54 1.81 26.9 1.40	12.3 12.8 1.87 0.68 8.96 0.13	3.21	7.23 4.29 0.60 0.40 3.07 0.27	7892 4096 283 169 2862 68.2	48.2 95.3 0.9 2.1 97.4 2.6	42.9 96.8 2.0 2.4 99.2 0.8	87.5 96.3 0.9 2.0 98.3 1.7	71.0 91.7 1.8 3.9 95.6 4.4	85.6 96.8 1.0 1.9 98.7 1.3
Head (Calc.)	100.0	18.1	5.92	2.15	2.10	1901	100.0	100.0	100.0	100.0	100.0

#### CONCLUSIONS AND DISCUSSION

Both the RGA and composite samples were high grade in lead. It was easier to produce a bulk concentrate product at high recovery than separate concentrates. The bulk concentrate from RGA sample assayed 60.2% Pb, 7.6% Zn, 3.6% Cu, 4.82 g/t Au and 5331 g/t Ag and represented a recovery of more than 97% of all metals. The bulk concentrate from the composite sample assayed 38.4% Pb, 12.8% Zn, 4.59% Cu, 4.29 g/t Au and 4096 g/t Ag for a recovery of more than 95% for lead, zinc, copper and silver and 91.7% for gold.

The RGB sample assayed lower grade and an acceptable bulk concentrate could not be produced. Copper, lead and zinc concentrate products were produced however. The copper-lead flotastion was not easy and more testwork is required. The silver minerals reported to the copper lead concentrate at a high recovery. When the zinc is depressed effectively in the lead circuit and reported to the zinc circuit, an acceptable zinc concentrate should be easily obtained at a reasonable recovery.

## SAMPLE PREPARATION

A five kilogram sample of RGA and a four kilogram sample of RGB were received at Lakefield on January 26, 1987. Each sample was crushed separately to minus 10 mesh. Head samples and test charges were prepared for the testwork.

Purpose:

To perform a preliminary test on Sample RGA to investigate the recovery of lead and zinc.

Procedure:

Feed:

1000 grams minus 10 mesh sample RGA

Grind:

10 minutes at 60% solids in the lab rod mill

:		Reager	ıts Add		Ti						
Stage .	Na <sub>2</sub> CO <sub>3</sub>	Na <sub>2</sub> SO <sub>3</sub>	AX 343	МІВС	Ca(OH) <sub>2</sub>	CuSO <sub>4</sub>	A3477	Grind	Cond.	Froth	pН
Grind Pb Rougher	500 500	1000	30	10	-	-	10	10	- 1	- 3	8.0 9.5
Condition	- - -	- - -	20 10 -	5 - -	- 1250		10 5 -	- - -	1 1 5	3 3 -	- - -
Zn Rougher	- - -	-	40	5	- - -	800 - 400	20	- -	5 1 3	2	11.5
Aeration	-	- - -	70 - -	-	50	500	20 - - M	-	1 - 10	1 - -	9.0 10.5 -
Zn Rougher (Cont'd) Tailing Regrind Zn Rougher (Cont'd)	- - -	-	20 - 10	-	- - 500	- 200	2030 20 10 5 5	5	1 1 - 1	3 - - 1	- - 10.2
	-	-	50	-	<b></b>	-	-	-	1	Î	-

Test No. 1 - Continued

		Reagen	its Add	Ti							
Stage	Na <sub>2</sub> CO <sub>3</sub>	Na <sub>2</sub> SO <sub>3</sub>	AX 343	3477	MIBC	Ca(OH) <sub>2</sub>	M 2030	Grind	Cond.	Froth	pН
Pb 1st Cleaner	125 - -	250 - -	10 20 5	10 5	5 10 5	- - -	- - -	- - -	2 1 1	1 2 2	8.5 - -
Pb 2nd Cleaner	125	250	10 5	5 5	5 5	-	- -	- -	2 1	3 2	8.3
Zn Cleaner	-	-	-	-	-	400 -	- 5	- - -	2 1	2	11.7

# Metallurgical Results

	Product	Wt %	Pb	A: Zn	ssays, Cu	%, g/t   Au	Ag	Pb	%   Zn	Distribu Cu	ition Au	Ag
1. 2. 3. 4. 5.	PbCleaner Conc. Pb 2nd Cl.Tail Pb 1st Cl.Tail Zn Cleaner Conc. Zn Cleaner Tail. Zn Rougher Tail	77.22 2.16 4.36 4.04 2.87 9.35	63.8 53.8 44.7 35.8 26.8 9.12	7.93 5.95 4.74 8.55 2.83 0.67	3.86 2.12 1.94 2.45 1.94 0.37	4.71 6.69 5.82 5.34 4.04 1.12	5668 4497 3881 2920 2486 460	88.9 2.1 3.5 2.6 1.4 1.5	88.1 1.8 3.0 5.0 1.2 0.9	90.3 1.4 2.6 3.0 1.7 1.0	81.3 3.2 5.7 4.8 2.6 2.4	89.8 2.0 3.5 2.4 1.5 0.8
	Head (Calc.)	100.0	55.4	6.95	3.30	4.47	4875.5	100.0	100.0	100.0	100.0	100.0

# Calculated Grades and Recoveries

Products 1 and 2 Products 1 to 3 Products 4 and 5 Products 1 to 5	79.38 83.74 6.91 90.65	63.5 62.5 32.1 60.2	7.71	3.81 3.72 2.24 3.60	4.76 4.82 4.80 4.82	5636 5545 2740 5331		92.9 6.2	91.7 94.3 4.7 99.0	90.2 7.4	91.8 95.3 3.9 99.2
--	---------------------------------	------------------------------	------	------------------------------	------------------------------	------------------------------	--	-------------	-----------------------------	-------------	-----------------------------

Test No. 1 - Continued

# Screen Analysis

Mesh Size (Tyler)	% R Individual	etained Cumulative	% Passing Cumulative
+ 150 200 270 400 - 400	.2 1.9 9.4 12.5 76.0	.2 2.1 11.5 24.0 100.0	99.8 97.9 88.5 76.0
Total	100.0	-	-

Purpose:

To perform a preliminary test on Sample RGB to investigate the recovery of lead and zinc.

Procedure:

Feed:

1000 grams minus 10 mesh sample RGB

Grind:

10 minutes at 60% solids in the lab rod mill

		Reagei	ats Add	led, gram	ıs per tı	nne		Ti	me, min	utes	
Stage	Na <sub>2</sub> CO <sub>3</sub>	Na <sub>2</sub> SO <sub>3</sub>	AX 343	A 3477	MIBC	Ca(OH) <sub>2</sub>	CuSO <sub>4</sub>	Grind	Cond.	Froth	рН
Grind Pb Rougher	500 - -	1000	- 10 5	10 5	5	-	-	10	- 1 1	3 2	9.4 -
Condition	-	-	- !	-	-	1000	000	-	5 5	-	
Zn Rougher	-	-	10 5	- 5	5 -	-	800 - -	-	1 1	2 1	11.4
Pb 1st Cleaner Pb 2nd Cleaner Pb 3rd Cleaner	250 250 250	500 250 250	-	2.5	2.5 2.5 2.5	-	-	-	2 2 2	3 2 1/2 2	9.6 9.6 -
Zn 1st Cleaner Zn 2nd Cleaner Zn 3rd Cleaner	- - - -	-		5 -	DF 1012 - 5 5 5	300 - 250 250	-		2 1 2 2	2 1 2 2	11.6 11.7 11.8

TEST NO. 2	F	ROJECT	NO. 3	277			
	-						
	WT.	A	SSAY,			% DIST	
PRODUCT	•/			7N	CII	20	7N
1 PB CL CONC	9.16	16.20	16.80	16.60	89.90	46.79	24.83
2 PB 3RD CL TAIL	i.90	1.94	13.90	19.80	2.23	11.49	6.14
3 PB 2ND CL TAIL	3.92	1.07	ເຂ.້ወຍ	20.30	2.54	14.30	13.00
4 PB 1ST CL TAIL	6.35	0.36	8.93	15.60	1.38	17.35	16.17
5 ZN CL CONC	4.82	Ø.18	2.26	48.50	<b>0.</b> 53	3.31	38.21
6 ZN GRD CL TAIL .	0.28	0.39	3.63	4.36	0.07	0.31	0.20
	0.85						
8 ZN 1ST CL TAIL	6.19	0.29	1.04	0.53	1.09	1.96	0.54
9 ZN RO TAIL	66.53	0.05	0.19	0.05	1.98	3.84	0.43
10							
11							
12							
HEAD,CALC			3.29	6.12	100.00	100.00	100.00
•							
CALC. GRADES & RECOVERIES							
1 + 2	11.06	13.75	17.33	17.15	92.13	58.28	30.97
1 - 3 ·	14.97	10.43	15.94	17.97	94.67	72.58	43.97
1 - 4	21.32	7.43	13.87	17.27	96.05	89.93	60.14
5 + 6	5.11	0.19	2.34	46.04	0.53	3.63	38.41
5 - 7	5.96	0.24	2.35	33.89	Ø.88	4.27	38.84
5 <b>-</b> 8 <sub>.</sub>	12.15	0.27	1.68	19.83	1.97	6.23	39.37
1 - 8	33.47	4.83	9.45	18.20	98.02	96.16	99.51

Test No. 2 - Continued

## Metallurgical Results

	Product	Wt %	Pb	A Zn	ssays, ' Cu	%, g/t Au	Ag	Pb	% Zn	Distribi Cu	ution Au	Ag
1. 2. 3. 4. 5. 6. 7. 8. 9.	Pb Cleaner Conc. Pb 3rd Cl.Tail Pb 2nd Cl.Tail Pb 1st Cl.Tail Zn Cleaner Conc. Zn 3rd Cl.Tail Zn 2nd Cl.Tail Zn 1st Cl.Tail Zn Rougher Tail	9.16 1.90 3.92 6.35 4.82 0.28 0.85 6.19 66.53	16.8 19.9 12.0 8.99 2.26 3.63 2.46 1.04 0.19	19.8 20.3 15.6 48.5 4.36 3.06 0.53	16.2 1.94 1.07 0.36 0.18 0.39 0.56 0.29 0.049	7.95 2.37 1.48 1.10 0.71 1.39 0.88 0.44 0.14	6443 783 459 212 97.1 196 251 123 12.7	46.8 11.5 14.3 17.4 3.3 0.3 0.6 1.9 3.9	24.8 6.2 13.0 16.2 38.2 0.2 0.4 0.5 0.5	89.9 2.2 2.5 1.4 0.5 0.1 0.3 1.1 2.0	4.2 5.4	89.4 2.3 2.7 2.0 0.7 0.1 0.3 1.2 1.3
-	Head (Calc.)	100.0	3.29	6.12	1.65	1.07	660	100.0	100.0	100.0	100.0	100.0

# Calculated Grades and Recoveries

			1								
Products 1 and 2	11.06	17.3 17	7.1  1	3.7	6.99	5471	58.3	31.0	92.1	72.4	91.7
Products 1 to 3	14.98	15.9 18	8.0 1	0.4	5.55	4159	72.6	44.0	94.6	77.8	94.4
Products 1 to 4	21.33	13.9 17	7.3	7.43	4.22	2984	90.0	60.2	96.0	84.4	96.4
Products 5 and 6	5.10	2.34 46	6.1	0.19	0.75	102.5	3.6	38.4	0.6	3.6	0.8
Products 5 to 7	5.95	2.35 33	3.9	0.24	0.77	123.7	4.2	38.8	0.9	4.3	1.1
Products 5 to 8	12.14	1.68 19	9.8	0.27	0.60	123.4	6.1	39.3	2.0	6.9	2.3
Products 1 to 8	33.47	9.45 18	8.2	4.83	2.91	1946	96.1	95.5	98.0	91.3	98.7
		1									

# Screen Analysis

Mesh Size		tained	% Passing
(Tyler)	Individual	Cumulative	Cumulative
+ 100 150	.2	.2	99.8
200 270	2.4 13.8 14.8	2.6 16.4 31.2	97.4 83.6 68.8
400 - 400	10.0 58.8	41.2 100.0	58.8 -
Total	100.0	-	-

Purpose:

To investigate the flotation of lead and zinc from a 7:3 mixture of samples RGB and RGA.

Procedure:

Feed:

300 g RGA + 700 g RGB minus 10 mesh sample

Grind:

10 minutes at 60% solids in the lab rod mill

		Reager	its Add	ed, gran	as per to	onne		Ti	me, minu	ites	
Stage	Na <sub>2</sub> CO <sub>3</sub>	Na <sub>2</sub> SO <sub>3</sub>	AX 343	A 3477	МІВС	Ca(OH) <sub>2</sub>	CuSO <sub>4</sub>	Grind	Cond.	Froth	рН
Grind Pb Rougher Condition	500 - - - -	1000	10 5 5	10 5 5	5 5 - -	1250		10 - - - -	1 1 1 5	2 2 2	9.3
Zn Rougher  Aeration Zn Rougher(Cont'd)  Pb 1st Cleaner  Pb 2nd Cleaner  Pb 3rd Cleaner	250 250 250	250 250 125	20 10		5 5 5 5	- - 250 - - - - -	800 - 500 - - - -	M 2030 10 10 20	5 1 10 1 2 1 1 1	2 2 1 2 3 2 2 3	11.0 - 10.5 - 9.5 - 9.7 - 9.9
Zn Cleaner	-	-	-	-	-	350	-	-	2	•	11.8

Test No. 3 - Continued

# Metallurgical Results

	Product	Wt %	Pb	A: Zn	ssays, ' Cu	%, g/t   Au	Ag	Pb	% Zn	Distribu Cu	ition   Au	Ag
1. 2. 3. 4. 5. 6. 7.	Pb Cleaner Conc. Pb 3rd Cl.Tail Pb 2nd Cl.Tail Pb 1st Cl.Tail Zn Cleaner Conc. Zn Cleaner Tail Zn Rougher Tail	20.67 4.78 9.42 10.12 6.29 14.32 34.40	42.2 52.0 46.5 16.5 2.54 1.49 1.40	0.16	9.08 1.16 0.61 0.74 0.32 0.16 0.11	7.23 2.46 1.51 1.73 0.60 0.31 0.27	7892 1388 779 711 283 119 68.2	48.2 13.7 24.2 9.2 0.9 1.2 2.6	42.9 10.8 24.0 19.1 2.0 0.4 0.8	87.5 2.6 2.7 3.5 0.9 1.1 1.7	71.0 5.6 6.8 8.3 1.8 2.1 4.4	85.6 3.5 3.9 3.8 1.0 0.9 1.3
	Head (Calc.)	100.0	18.1	5.92	2.15	2.10	1901	100.0	100.0	100.0	100.0	100.0

# Calculated Grades and Recoveries

Products 1 and 2	25.45		12.5	7.59	6.33	6670	61.9	53.7	90.1	76.6	89.1
Products 1 to 3	34.87		13.2	5.71	5.03	5079	86.1	77.7	92.8	83.4	93.0
Products 1 to 4 Products 5 and 6 Products 1 to 6	44.99 20.61 65.60	38.4 1.81 26.9		4.59 0.21 3.21	4.29 0.40 3.07	4096 169 2862	95.3 2.1 97.4	96.8 2.4 99.2	96.3 2.0 98.3	91.7 3.9 95.6	96.8 1.9 98.7

# Screen Analysis

Mesh Size (Tyler)	% Re	etained   Cumulative	% Passing Cumulative
+ 150 200 270 400 - 400	1.5 9.3 16.0 10.7 62.5	1.5 10.8 26.8 37.5 100.0	98.5 89.2 73.2 62.5
Total	100.0	-	-

Purpose:

To repeat Test No. 2 (Sample RGB) but replace  $Na_2SO_3$  with

ZnSO<sub>4</sub>/NaCN mixture and regrind the lead rougher concentrate.

Procedure:

Feed:

1000 grams minus 10 mesh sample RGB

Grind:

10 minutes at 60% solids in the lab rod mill

		Reage	nts Adde	ed, gran	is per to	nne		Ti	ne, minu	ites	
Stage	Na <sub>2</sub> CO <sub>3</sub>	ZnSO <sub>4</sub> NaCN	AX 343	A 3477	МІВС	Ca(OH) <sub>2</sub>	CuSO <sub>4</sub>	Grind	Cond.	Froth	pН
Primary Grind Pb Rougher  Condition  Zn Rougher  Pb Conc.Regrind(PM) Pb 1st Cleaner	500 - - - - - - - 250	1000	10 5 - 10 5	10 5 - - 5	5 - - 5 - 5	1000	- - - 800 - - -	10	1 1 5 5 1 1	3 2 - 2 1	9.7
Pb 2nd Cleaner	-	200	5 -	-	5	-	- -	-	1 2	2 3	- 9.5
Cu-Pb Separation	SO <sub>2</sub>	XD31									
Condition Cu Rougher Cu Cleaner	150	250	1 1 1	- 5 - 5	- 5 - - 5	- - - -	- - - -		5 5 1 3 1	2	4.0 - 4.0 -
Zn 1st Cleaner Zn 2nd Cleaner Zn 3rd Cleaner	-	-	-	5	5 5 5	300 250 200	- - -	- - -	1 1 2 2	1 1 2 2	11.7

Test No. 4 - Continued

TEST NO. 4		ROJECT	NO. 3	8277			
PRODUCT	₩Т. %	£	SSAY, PB		ີເນື	½ DIST	ZN
3 CU-PB SEPT TAIL 4 PB 2ND CL TAIL 5 PB 1ST CL TAIL 6 ZN CL CONC 7 ZN 3RD CL TAIL 8 ZN 2ND CL TAIL 9 ZN 1ST CL TAIL 10 ZN RO TAIL	5.56 1.61 7.35 5.00 0.63 0.55	19.50 6.58 7.55 2.82 0.36 0.51 0.37 0.28	\$2.30 10.70 3.28 0.84 1.12 1.02 0.83	8.70 14.80 16.40 15.20 59.50 30.40 8.34 7.52	24.96 23.01 8.61 13.90 1.13 0.22 0.13 0.45	8.34 1.36 0.25 0.18 0.74	2.91 13.50 4.88 19.55 48.74 3.38 0.75 3.16
11 12 HEAD,CALC	100.00	1.59	3.89	 6.10	 100.00	199.99	100.00
CALC. GRADES & RECOVERIES			-12-				
1 + 2 1 - 3 1 - 4 1 - 5 6 + 7 6 - 8 6 - 9 1 - 9	10.76 18.61 5.68 6.22 8.79	13,08 12.15 8.21	24.34 15.46 0.87 0.89 0.89	12.27 12.97 13.91 56.02 51.83	73.56 82.16 96.07 1.35 1.46 1.93	84.90 93.24 1.61	18.00 22.88 42.42 52.12 52.87 56.03

Purpose:

To perform a test on sample RGA, to investigate the effect of floating a bulk concentrate.

Procedure:

As indicated below.

Feed:

1000 grams minus 10 mesh sample RGA.

Grind:

10 minutes at 60% solids in the lab rod mill

	R	eagents A	dded, gran	Tin					
Stage	Na <sub>2</sub> CO <sub>3</sub>	A343	A3477	MIBC	NaCN	Grind	Cond.	Froth	рН
Primary Grind Bulk Flotation	1000 500 - -	- 50 20 10	20 5 5	- 10 - -	-	10 - -	1 1	3 3 3	7.5 8.9 -
Bulk Conc.Regrind Pb 1st Cleaner	250 250 -	10 20 10	- - -	- 10 5 5	250 - - - -	20	- 1 1	- 2 2 2	9.0
Pb 2nd Cleaner	- -	- 5	-	- 5	250 -		2	3 2	8.8

Test No. 5 - Continued

# Metallurgical Results

Product	Weight %	Cu	Assays %	Zn	% Distribution Cu   Pb   Zn				
<ol> <li>Pb Cleaner Conc.</li> <li>Pb 2nd Cl.Tail</li> <li>Pb 1st Cl.Tail</li> <li>Bulk Flot.Tail</li> </ol>	81.10 2.89 6.19 9.82	3.73 1.80 1.35 0.64	62.6 39.9 27.0 13.0	7.86 4.23 2.31 1.16	93.8 1.6 2.6 2.0	92.5 2.1 3.1 2.3	94.4 1.8 2.1 1.7		
Head (Calc.)	100.0	3.22	54.9	6.75	100.0	100.0	100.0		

# Calculated Grades and Recoveries

Products 1 and 2	83.99	3.66	61.8	7.73	95.4	94.6	96.2
Products 1 to 3	90.18	3.50	59.4	7.36	98.0	97.7	98.3

## Test\_No. 6

Purpose:

To perform a test on sample RGB, using NaCN in the primary grind and Pb cleaners and regrinding the Zn rougher Conc. prior to cleaning

Procedure:

Feed:

1000 grams minus 10 mesh sample RGB.

Grind:

10 minutes at 60% solids in the lab rod mill

		Reage	Tiı								
Stage -	Na <sub>2</sub> CO <sub>3</sub>	Na <sub>2</sub> SO <sub>3</sub>	NaCN	AX 343	A 3477	MIBC	M 2030	Grind	Cond.	Froth	рН
Primary Grind Pb Rsougher	500 - -	1000 - -	250 - -	10 5	10 5	5		10 - -	- 1 1	3 2	9.8
Pb Conc.Regrind Pb 1st Cleaner Pb 2nd Cleaner Pb 3rd Cleaner	250 - - 100 50	500 - - - -	200 - - 100 50	5 5 - -	- 5 - -	-	- - - -	10 - - - -	1 1 2 2	2 2 3 2	9.7 9.9 -
	Ca(OH) <sub>2</sub>	CuSO <sub>4</sub>									
Pb Ro.Tail. Cond.	1000	800	-	-	-	-	-	-	5 5		11.5
Zn Rougher	-	-	- -	10 5	- 5	5	-	-	1 1	2	-
Zn Conc. Regrind Zn 1st Cleaner Zn 2nd Cleaner Zn 3rd Cleaner	500 500 500	100 - - -	- - -	-		5 - 5	10 - - -	10 - - -	1 2 2	3 2 2	11.6 11.9 12.0

Test No. 6 - Continued

TEST NO. 6	P -	ROJECT	NO.					
PRODUCT		WT. AS				% DIST		
2 PB 3RD CL TAIL 3 PB 2ND CL TAIL 4 PB 1ST CL TAIL 5 ZN CL CONC 6 ZN 3RD CL TAIL 7 ZN 2ND CL TAIL 8 ZN 1ST CL TAIL	1.58 10.13 3.18 0.17 0.98 11.24 64.47	7.86 5.14 3.94 1.61 1.12 0.57 0.16	17.40 10.60 2.68 3.65 3.67 1.96 0.53	24.70 24.50 23.80 47.10 11.70 2.63 0.30	6.19 5.14 25.35 3.25 0.12 0.35 1.14	0.61	5.33 6.72 42.01 25.10 0.35 0.46 0.53	
HEAD, CALC  CALC. GRADES & RECOVERIES	199.99	1.57	3.12	5.74	100.00	100.00	100.00	
1 - 3	4.33 15.57	10.88 7.36 1.58 1.36 0.49	25.73 14.03 3.65 3.27 1.29	45.28 35.63 10.14	67.89 93.25 3.38 3.73 4.87	75.76 81.11 89.82 3.93 4.54 6.45 96.28	30.01 72.02 26.45 26.91 27.50	

Purpose:

To repeat Test No. 4, but with finer primary grind and finer regrind. Combine lead rougher and 1st cleaner tailings for zinc feed.

Procedure:

Feed:

1000 grams minus 10 mesh sample RGB.

Grind:

15 minutes at 65% solids in the lab rod mill

	Reagents Added, grams per tonne							Tiı			
Stage	Na <sub>2</sub> CO <sub>3</sub>	<u>ZnSO4</u> NaCN	AX 343	A 3477	MIBC -	SO <sub>2</sub>	XD31	Grind	Cond.	Froth	рН
Primary Grind Pb Rougher	500 - -	1000 - -	10 5	- 10 5	10 5	-		15	- 1 1	3 2	9.7 -
Pb Conc. Regrind Pb 1st Cleaner Pb 2nd Cleaner	250 - - -	500 - - 250	5 5	5 5 5 5	5 5	- - -	- - -	20 - - -	1 1 2	3 2 2	9.6 - 9.8
Pb 3rd Cleaner	- -	200	5 -	-	5 -	-	-	- -	1 2	2 -	- 9.9
Cu-Pb Separation											
Condition	-	-	-	-	-	550	- 200	-	5 5	-	-
Cu Rougher	_ 	-	-	.5 .5	5	-	- ;	-	1 1	1	4.0 -
Cu Cl.Conditioner		-	-	-	-	50	- - 50	-	3	 T	4.0
Cu Cleaner	-	-	-	5	5	-	-	-	1	1.5	

Test No. 7 - Continued

		Reagents	Tir	Time, minutes					
Stage	Ca(OH) <sub>2</sub>	CuSO <sub>4</sub>	AX 343	A 3477	MIBC	Grind	Cond.	Froth	рΗ
Zn Circuit (Combine	ed Pb rougher	and 1st Cle	aner Tailir	ngs)					
Condition	1000	800	-	-	-	-	3 5	-	110
Zn Rougher	- -	-	10 5	10 5	- -	-	1	2	11.9
Zn 1st Cleaner	400	-	_	-	-	-	2	2	12.0
Zn 2nd Cleaner Zn 3rd Cleaner	250 250	-	-	5 - -	- - 5	-	1 2 2	1 2 1.5	12.2

Test No. 7 - Continued

TEST NO. 7	F	ROJECT					
	-						
	WT.	A	ISSAY,			% DIST	
PRODUCT	WТ. %	CU	PB	ZN	cu	PS	ZN
							THE REP CHE COM ME
1 CU CL CONC	1.36	14.20	28.20	9 49	12 32	12.75	2.13
	2.93					29.03	
3 CU-PB-SEPT TAIL							
	1.86						
	2.10						
E ZN CL CONC	6.74	0.49	0.72	60.20	2.12	1.62	67.06
7 ZN SRD CL TAIL	0.78						
8 ZN 2ND CL TAIL							
9 ZN 1ST CL TAIL	13.44	0.22	0.31	0.35	1.90	1.39	0.78
10 ZN RO TAIL	62.33	0.05	0.13	0.10	2.12	2.70	ଡ.୨୫
11							•
12							
HEAD, CALC							400 00
nend, calc	100.00	1.56	3.01	6.05	100.00	100.00	168.69
•							
CALC. GRADES & RECOVERIES							
•							
	4.29			9.91	37.18	41.78	7.01
	9.84	11.76	25.08	11.60	74.26	85.41	18.85
1 - 4	11.70	11.23	23.02	12.18	84.30	89.62	23.55
1 - 5		10.20					
6 + 7		0.71					
	10.43					3.48	
6 - 9		0.49					
i - 9	37.67	4.05	7.76	15.92	97.88	97,30	SS.02

Lakefield Research A Division of Falconbridge Limited Lakefield, Ontario

February 25th, 1987