

Mt. Sicker
827691
092B/13

IFR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-75 C1N

INDEX FILE : 75C1N.IND

DATA FILE : 75C1N.DAT

LINE NO. : 751

Station	Receive Mode	Dipole	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
200	2	1	61.7	52.7	47.1	43.0	34.4	26.3	21.6	17.2	13.5	11.1	31.3	4.	2020.
		2	52.4	44.1	39.4	35.8	28.6	21.7	17.8	14.2	11.2	9.2	41.1	0.	3530.
		3	38.7	32.0	28.3	25.4	19.8	14.7	11.8	9.3	7.2	5.8	100.5	-14.	9670.
190	2	1	59.1	50.2	44.9	40.8	33.0	25.1	20.6	16.4	12.9	10.7	34.3	1.	2520.
		2	48.0	40.1	35.8	32.5	26.0	19.6	16.1	12.8	10.0	8.2	44.7	1.	4640.
		3	34.7	28.1	24.6	22.1	17.3	12.6	10.2	7.9	6.0	4.9	106.8	-5.	20600.
180	2	1	51.1	43.2	38.3	35.0	27.9	21.1	17.3	13.8	10.8	8.9	43.1	0.	3600.
		2	50.7	42.4	37.4	34.2	27.1	20.4	16.6	13.2	10.4	8.5	41.0	6.	5450.
		3	33.8	27.9	24.3	22.0	17.2	12.7	10.2	8.0	6.2	5.0	135.9	-21.	1550000.
165	2	1	48.5	40.7	36.2	32.8	26.1	19.6	16.0	12.7	9.9	8.2	46.8	8.	5440.
		2	32.8	26.7	23.4	20.9	16.2	11.9	9.4	7.3	5.6	4.5	52.9	-2.	13700.
		3	38.8	32.1	28.4	25.6	20.1	15.0	12.1	9.5	7.3	6.0	130.2	-11.	16500.
150	2	1	40.0	33.2	28.9	26.1	20.4	15.0	12.1	9.5	7.3	5.9	46.8	10.	8880.
		2	29.0	23.6	20.4	18.6	14.4	10.6	8.6	6.6	5.0	4.0	68.4	-10.	1380000.
		3	44.7	37.1	32.7	29.8	23.5	17.5	14.2	11.2	8.7	7.0	91.0	-18.	6030.
135	2	1	29.5	23.9	20.9	18.6	14.4	10.4	8.6	6.4	4.9	3.9	72.1	3.	53300.
		2	36.7	30.5	27.0	24.5	19.5	14.6	11.9	9.4	7.3	6.0	67.4	-15.	17300.
		3	54.9	45.7	40.5	36.6	29.0	21.6	17.5	13.8	10.7	8.7	41.8	-34.	1880.
120	2	1	37.5	30.9	27.4	24.9	19.6	14.7	11.9	9.4	7.3	6.0	72.7	-17.	28200.
		2	43.0	35.7	31.5	28.5	22.4	16.6	13.3	10.3	7.9	6.4	43.9	8.	5680.
		3	77.1	64.8	57.8	52.7	42.3	32.2	26.5	21.2	16.7	13.8	30.0	-103.	1050.
115	2	1	38.1	31.9	28.1	25.6	20.2	15.2	12.3	9.8	7.7	6.3	67.0	0.	17300.
		2	49.7	41.4	36.8	33.4	26.3	19.6	15.8	12.4	9.5	7.6	35.1	-14.	3990.
		3	84.4	71.2	63.6	58.0	46.6	35.5	29.2	23.4	18.5	15.3	28.6	-43.	932.

Index: 75CIN.IND

Data : 75CIN.DAT

105	2	1	44.3	36.9	32.5	29.3	23.2	17.3	14.0	11.0	8.5	6.9	51.4	4.	7770.
		2	64.6	54.4	48.3	43.8	35.2	26.7	21.8	17.4	13.8	11.4	9.2	-38.	796.
		3	83.1	70.3	62.7	57.2	46.2	35.1	28.9	23.1	18.2	15.1	32.2	-18.	919.
100	2	1	45.8	38.0	33.4	30.3	23.8	17.6	14.1	11.0	8.5	6.8	42.3	2.	5330.
		2	73.9	62.3	55.7	50.7	40.9	31.1	25.5	20.4	16.1	13.2	7.1	-76.	570.
		3	79.7	67.3	60.0	54.9	44.1	33.6	27.6	22.0	17.4	14.3	35.8	24.	983.
95	2	1	47.9	39.8	35.0	31.7	24.8	18.4	14.8	11.6	8.9	7.2	32.5	5.	3580.
		2	92.3	78.1	69.8	63.9	51.5	39.5	32.5	26.3	20.9	17.1	5.0	-66.	368.
		3	76.0	64.2	57.1	52.4	42.1	32.1	26.3	21.0	16.5	13.7	38.7	44.	1040.
85	2	1	65.4	54.8	48.7	44.0	35.2	26.5	21.7	17.3	13.5	10.8	8.9	-58.	796.
		2	74.2	62.7	55.9	50.9	40.8	30.9	25.3	20.2	15.9	13.1	18.5	36.	1190.
70	2	1	75.4	63.7	56.6	51.7	41.4	31.5	25.8	20.7	16.3	13.4	13.3	57.	890.
		2	93.2	79.5	71.0	65.0	52.4	40.1	33.1	26.5	20.9	17.3	17.2	-30.	976.
60	2	1	79.4	68.0	60.2	55.1	44.2	33.8	27.7	22.2	17.6	14.6	23.7	-88.	1460.
		2	74.5	63.8	56.7	51.8	41.7	31.9	26.2	21.0	16.4	13.5	14.0	124.	716.
55	2	1	86.1	72.9	65.0	59.5	47.8	36.5	30.0	24.1	19.0	15.7	22.4	-11.	1280.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-75 C1E

INDEX FILE : 75C1E.IND

DATA FILE : 75C1E.DAT

LINE NO. : 752

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
200	2	1	41.2	34.9	30.6	28.1	22.3	16.6	13.5	10.6	8.2	6.7	27.6	5.	1760.
		2	31.8	26.4	23.5	21.2	16.6	12.4	9.9	7.7	6.0	4.8	26.7	-1.	1720.
		3	53.4	44.8	39.2	35.6	27.7	20.5	16.3	12.8	10.0	8.0	24.2	-14.	819.
190	2	1	41.3	34.4	30.6	27.9	22.0	16.5	13.4	10.5	8.1	6.6	29.5	1.	1690.
		2	28.8	23.8	21.1	19.1	15.0	11.0	8.8	6.8	5.2	4.2	33.0	2.	1920.
		3	-884.4	-784.5	-725.4	-676.1	-554.5	-411.6	-335.8	*****	-202.1	-164.9	-1.1	-8.	33.
180	2	1	31.5	26.3	23.0	20.8	16.3	12.1	9.7	7.5	5.8	4.7	31.5	0.	1790.
		2	31.0	26.1	22.9	20.8	16.4	12.2	9.8	7.7	5.8	4.7	34.9	6.	2030.
		3	-25.5	-21.4	-18.9	-17.3	-13.3	-10.0	-8.0	-6.3	-5.0	-4.1	-34.4	-22.	1090.
165	2	1	32.5	26.8	23.9	21.3	16.9	12.5	10.1	7.9	6.0	4.9	39.1	9.	2200.
		2	-549.6	-449.0	-405.0	-354.5	-277.1	-198.8	-157.7	*****	-88.6	-70.8	-7	-4.	40.
		3	5.8	5.7	4.8	5.0	4.1	3.2	2.6	2.1	1.7	1.4	-50.1	-11.	1680.
150	2	1	45.3	36.8	32.2	29.1	22.6	16.5	13.2	10.2	7.7	6.2	12.5	10.	726.
		2	-30.2	-25.5	-22.3	-20.5	-16.2	-12.1	-9.8	-7.8	-6.0	-4.9	-19.3	-10.	1200.
		3	5.1	5.3	5.4	5.3	4.8	4.3	3.9	3.3	2.9	2.6	-32.0	-18.	1180.
135	2	1	-27.0	-22.5	-19.9	-18.1	-14.5	-10.8	-8.7	-6.9	-5.3	-4.2	18.1	4.	1090.
		2	-18.6	-14.8	-12.7	-11.3	-8.7	-6.1	-4.8	-3.7	-2.9	-2.4	22.2	-14.	1470.
		3	272.5	230.4	205.3	187.6	151.1	115.2	94.6	75.8	59.6	48.8	-5.2	-34.	221.
120	2	1	-17.5	-14.7	-12.2	-11.2	-8.6	-6.1	-4.9	-3.7	-2.8	-2.3	23.3	-15.	1510.
		2	34.4	29.8	27.0	24.7	20.2	15.7	12.9	10.3	8.1	6.6	22.3	6.	1650.
		3	49.7	42.2	37.9	34.9	28.2	21.7	18.0	14.5	11.5	9.6	-81.4	-101.	4160.
115	2	1	-14.3	-11.9	-9.9	-9.6	-6.9	-4.9	-3.9	-3.0	-2.3	-1.8	21.9	1.	1450.
		2	36.4	32.0	29.1	26.3	22.0	17.2	14.2	11.4	8.8	7.1	16.0	-14.	1220.
		3	52.7	44.6	40.2	37.1	30.0	23.1	19.1	15.4	12.3	10.2	-85.1	-43.	4660.

Index: 75C1E.IND

Data : 75C1E.DAT

105	2	1	36.9	32.1	29.2	27.2	22.1	17.4	14.4	11.6	9.2	7.6	24.3	4.	1700.
		2	110.4	93.8	83.9	76.5	61.4	46.5	38.0	30.3	23.7	19.4	-10.9	-38.	895.
		3	54.1	46.1	41.2	37.7	30.5	23.4	19.3	15.5	12.3	10.2	-87.5	-17.	5690.
100	2	1	39.5	33.8	30.7	28.7	23.3	18.1	15.1	12.2	9.6	7.9	19.8	3.	1420.
		2	89.5	76.2	68.2	62.4	50.3	38.4	31.6	25.2	19.8	16.3	-22.2	-75.	1930.
		3	52.4	44.2	39.9	36.5	29.5	22.6	18.7	15.0	11.9	9.8	-86.1	25.	6190.
95	2	1	29.0	25.3	22.6	21.3	17.4	13.5	11.1	8.8	6.8	5.4	13.3	5.	999.
		2	87.6	74.3	66.8	61.2	49.4	37.8	31.1	24.8	19.6	16.2	-27.0	-65.	2500.
		3	50.5	42.4	38.1	34.8	28.1	21.5	17.8	14.2	11.2	9.3	-89.5	37.	7300.
85	2	1	103.2	88.6	79.3	72.4	58.5	44.0	36.1	28.3	22.0	17.9	11.6	-57.	956.
		2	39.3	33.7	30.1	27.7	22.5	17.2	14.3	11.5	9.2	7.7	56.6	35.	6060.
70	2	1	51.3	43.6	39.1	35.5	28.7	22.0	18.2	14.6	11.6	9.6	47.6	57.	4730.
		2	57.7	49.3	44.4	40.7	33.0	25.4	21.0	16.9	13.3	11.0	44.1	-31.	6300.
60	2	1	38.4	33.2	29.7	27.3	22.4	17.5	14.6	11.9	9.5	8.0	63.3	-85.	7370.
		2	79.0	66.8	59.1	53.7	42.8	32.2	26.1	20.6	16.0	13.0	27.8	122.	5210.
55	2	1	40.5	34.3	30.6	28.3	22.8	17.6	14.6	11.7	9.3	7.7	57.0	-11.	7310.

IFR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-75 C1S

INDEX FILE : 75C1S.IND

DATA FILE : 75C1S.DAT

LINE NO. : 753

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
200	2	1	42.7	36.1	32.3	29.3	23.5	17.4	14.3	11.1	8.6	7.0	6.7	6.	601.
		2	38.6	32.2	28.9	25.5	20.5	15.4	12.7	10.1	7.8	6.4	7.7	-1.	629.
		3	25.2	20.4	18.4	15.8	12.6	9.1	7.4	5.7	4.3	3.5	20.7	-15.	747.
190	2	1	44.2	37.0	32.8	29.7	23.9	17.9	14.8	11.5	9.1	7.3	6.8	2.	600.
		2	33.8	27.5	24.4	21.8	17.4	12.8	10.4	8.3	6.4	5.2	8.2	1.	659.
		3	22.8	17.9	15.8	14.1	11.1	8.0	6.3	4.8	3.7	2.9	22.5	-8.	784.
180	2	1	36.9	31.0	27.1	24.8	19.7	14.4	11.8	9.0	6.9	5.6	7.9	-1.	641.
		2	34.5	28.5	25.2	22.8	18.3	13.7	10.9	8.7	6.9	5.8	7.7	8.	566.
		3	22.0	18.1	15.8	14.1	11.3	8.2	6.6	5.2	4.1	3.4	28.8	-24.	930.
165	2	1	32.6	27.8	24.3	22.2	17.2	12.8	10.5	8.4	6.4	5.4	8.6	10.	663.
		2	21.8	18.0	15.9	14.7	10.9	8.2	6.6	5.1	3.9	3.2	11.4	-5.	783.
		3	26.0	21.9	19.5	18.0	13.6	10.2	8.4	6.5	5.1	4.2	27.0	-11.	848.
150	2	1	25.7	21.9	19.0	16.6	13.3	9.8	8.2	6.5	5.2	4.3	9.7	9.	685.
		2	18.2	15.2	13.5	11.4	9.4	7.0	5.8	4.5	3.4	2.7	14.2	-10.	929.
		3	35.2	30.0	26.8	23.6	19.4	14.8	12.3	9.9	7.9	6.8	20.3	-19.	590.
135	2	1	19.6	15.3	13.4	13.0	9.5	6.7	5.7	4.3	3.4	2.8	15.4	3.	1010.
		2	24.8	20.3	18.3	17.5	13.4	9.9	8.3	6.5	5.3	4.3	13.7	-14.	818.
		3	52.7	44.2	39.7	36.8	29.0	21.7	17.8	13.9	10.7	8.7	13.0	-34.	358.
120	2	1	24.1	20.5	18.2	15.6	12.8	9.5	7.5	6.0	4.6	3.7	14.7	-14.	894.
		2	33.1	28.5	25.4	22.2	18.0	13.4	10.7	8.5	6.5	5.3	9.7	6.	566.
		3	53.8	46.3	41.7	38.2	31.0	23.8	19.7	15.9	12.5	10.4	18.9	-101.	504.
115	2	1	26.4	22.5	19.1	17.9	13.7	10.5	8.4	6.6	4.9	3.9	13.6	1.	848.
		2	40.1	34.2	30.0	27.2	21.4	15.9	12.7	10.0	7.6	5.9	8.4	-15.	492.
		3	58.4	50.2	45.1	41.6	33.8	25.9	21.4	17.2	13.6	11.3	19.0	-44.	513.

Index: 75C1S.IND

Data : 75C1S.DAT

105	2	1	31.1	26.7	23.5	21.7	17.2	12.7	10.0	7.7	5.9	4.6	10.7	4.	614.
		2	61.9	53.1	47.5	43.5	35.0	26.5	21.5	17.1	13.4	10.7	4.3	-38.	241.
		3	47.7	41.3	37.2	34.0	27.8	21.3	17.5	14.1	11.1	9.2	23.7	-18.	622.
100	2	1	40.8	34.5	30.6	27.2	21.5	15.7	12.6	9.6	7.2	5.8	10.6	3.	632.
		2	77.1	65.9	59.7	54.0	43.9	33.7	27.6	22.0	17.2	14.2	5.7	-74.	320.
		3	54.0	46.3	41.8	37.9	30.8	23.6	19.4	15.5	12.2	10.0	30.7	23.	826.
95	2	1	38.5	32.6	28.0	24.7	20.3	14.9	12.1	9.4	7.4	6.1	7.8	6.	458.
		2	76.6	65.7	59.4	54.2	43.8	33.5	27.5	22.0	17.1	14.0	4.7	-66.	260.
		3	36.6	31.3	28.5	25.9	21.1	16.1	13.3	10.6	8.4	6.9	28.1	34.	746.
85	2	1	61.4	52.3	46.4	42.2	33.6	24.9	20.0	15.7	12.1	10.1	4.3	-56.	244.
		2	47.6	41.1	36.9	33.8	27.5	21.2	17.5	14.1	11.1	9.1	12.3	33.	656.
70	2	1	51.4	43.7	38.8	35.8	28.7	22.1	18.5	15.0	12.1	10.2	9.7	59.	535.
		2	54.2	47.3	42.5	39.5	32.1	24.7	20.3	16.0	12.4	9.9	12.3	-32.	643.
60	2	1	51.7	44.7	40.1	36.6	29.9	23.1	19.1	15.4	12.3	10.3	14.5	-80.	781.
		2	27.7	24.4	21.9	20.0	16.3	12.4	10.2	8.1	6.3	5.2	12.6	120.	665.
55	2	1	53.6	45.9	41.3	37.7	30.7	23.6	19.6	15.8	12.9	11.0	14.2	-11.	750.

IFR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-75 C1W

INDEX FILE : 75C1W.IND

DATA FILE : 75C1W.DAT

LINE NO. : 754

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
200	2	1	47.8	40.0	35.5	32.2	25.6	19.3	15.8	12.5	9.7	8.0	80.7	6.	1850.
		2	45.1	37.4	33.1	30.0	23.9	17.9	14.6	11.5	9.0	7.4	94.2	-2.	2070.
		3	30.7	25.1	22.0	19.9	15.6	11.5	9.3	7.2	5.6	4.5	318.2	-16.	3400.
190	2	1	49.5	41.7	37.0	33.7	26.8	20.2	16.5	13.1	10.3	8.5	84.8	1.	1900.
		2	39.4	32.9	29.1	26.4	20.9	15.6	12.7	10.1	7.8	6.4	102.8	1.	2210.
		3	28.1	23.0	20.1	18.2	14.3	10.5	8.5	6.6	5.1	4.1	385.8	-12.	4140.
180	2	1	42.6	35.6	31.8	28.8	22.8	17.2	13.9	11.1	8.6	7.1	96.8	-1.	2130.
		2	38.4	31.5	28.0	25.3	19.9	14.8	12.0	9.4	7.3	5.9	90.8	7.	1940.
		3	28.6	23.6	20.9	18.8	14.8	11.0	8.9	7.0	5.4	4.4	499.4	-25.	5440.
165	2	1	36.7	30.8	27.2	24.4	19.4	14.4	11.7	9.3	7.2	5.9	102.1	9.	2200.
		2	29.0	23.8	20.9	18.8	14.8	10.9	8.8	6.9	5.3	4.2	190.3	-6.	4060.
		3	35.1	29.4	26.0	23.6	18.8	14.0	11.4	9.0	7.0	5.7	476.2	-14.	5380.
150	2	1	32.2	26.7	23.5	21.2	16.6	12.2	9.8	7.7	5.8	4.7	148.2	7.	3150.
		2	26.4	19.9	17.3	15.8	12.3	9.1	7.4	5.7	4.3	3.5	248.1	-12.	5380.
		3	44.0	37.0	32.8	29.9	23.9	18.0	14.7	11.7	9.1	7.4	350.7	-21.	4220.
135	2	1	26.3	21.5	18.8	17.1	13.2	9.8	7.8	6.1	4.7	3.8	269.7	2.	5890.
		2	31.2	26.1	23.3	21.3	17.0	12.9	10.6	8.4	6.5	5.4	233.0	-16.	5290.
		3	58.9	49.7	44.3	40.4	32.3	24.4	19.9	15.8	12.4	10.1	189.1	-35.	2560.
120	2	1	31.0	25.7	23.0	20.8	16.6	12.5	10.2	8.1	6.3	5.2	250.4	-15.	5630.
		2	47.9	40.2	36.0	32.7	26.2	19.7	16.1	12.7	9.9	8.0	175.8	4.	4290.
		3	76.0	64.0	57.2	52.0	41.7	31.6	25.9	20.6	16.1	13.2	122.1	-102.	1930.
115	2	1	33.2	28.0	24.7	22.6	17.9	13.6	11.1	8.8	6.9	5.6	230.0	0.	5290.
		2	53.4	45.2	40.1	36.6	29.2	22.1	18.0	14.2	11.1	9.0	148.5	-16.	3760.
		3	81.2	68.7	61.2	56.0	44.7	34.0	27.7	22.1	17.3	14.2	111.5	-45.	1890.

Index: 75CIW.IND

Data : 75CIW.DAT

105	2	1	45.7	38.9	34.5	31.5	25.1	19.0	15.5	12.4	9.6	7.9	191.2	3.	4550.
		2	64.8	55.3	49.4	45.0	36.2	27.6	22.7	18.2	14.3	11.9	53.0	-39.	1440.
		3	61.8	52.5	46.6	42.5	34.1	25.9	21.2	16.9	13.2	10.8	133.5	-19.	2690.
100	2	1	50.2	42.2	37.5	34.1	27.2	20.5	16.6	13.1	10.2	8.3	170.0	2.	4180.
		2	70.4	60.0	53.7	49.3	39.8	30.5	25.1	20.1	15.8	13.0	36.7	-74.	1040.
		3	53.2	44.7	39.8	36.3	28.9	21.9	17.9	14.2	11.1	9.1	144.6	22.	3220.
95	2	1	52.1	43.8	39.0	35.3	28.2	21.2	17.3	13.7	10.6	8.7	135.8	5.	3450.
		2	84.5	72.2	64.8	59.2	48.0	36.8	30.3	24.3	19.2	15.9	31.9	-66.	964.
		3	43.7	36.6	32.6	29.6	23.5	17.7	14.4	11.5	8.9	7.3	147.1	32.	3710.
85	2	1	66.5	56.0	50.0	45.6	36.6	27.8	22.8	18.2	14.3	11.8	52.0	-55.	1420.
		2	75.9	64.3	57.4	52.4	41.9	31.7	25.9	20.6	16.0	13.1	71.6	33.	2450.
70	2	1	77.6	65.7	58.7	53.8	43.2	32.8	26.9	21.5	17.0	14.1	59.9	59.	1920.
		2	61.6	51.9	46.3	42.3	33.8	25.6	21.0	16.6	13.0	10.7	62.5	-32.	2800.
60	2	1	78.6	66.3	59.0	53.7	42.8	32.3	26.3	20.8	16.2	13.2	79.4	-78.	2940.
		2	17.2	14.3	12.8	11.5	9.3	7.1	5.8	4.7	3.7	3.1	67.7	119.	3950.
55	2	1	75.6	63.4	56.5	51.5	41.1	31.0	25.4	20.1	15.8	13.0	75.2	-11.	3050.

IFR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-76 C1N

INDEX FILE : 76C1N.IND

DATA FILE : 76C1N.DAT

LINE NO. : 761

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
180	2	1	64.1	53.5	47.4	43.0	34.0	25.5	20.6	16.2	12.6	10.3	39.8	-19.	2020.
		2	83.9	71.6	64.3	59.0	47.8	36.8	30.4	24.4	19.4	16.0	44.9	-96.	3250.
		3	58.1	48.8	43.6	39.8	31.8	24.2	19.8	15.8	12.5	10.3	115.7	150.	21400.
175	2	1	70.6	60.0	53.4	48.5	39.1	29.7	24.3	19.4	15.1	12.5	35.6	7.	1970.
		2	87.5	74.8	67.0	61.3	49.8	38.2	31.5	25.3	20.0	16.6	40.5	-7.	3480.
		3	55.8	47.1	41.8	37.9	30.5	23.1	19.0	15.3	12.0	10.0	110.5	35.	85700.
170	2	1	81.1	69.6	62.4	57.2	46.4	35.6	29.4	23.8	18.9	15.7	32.1	-65.	1920.
		2	74.4	63.4	56.9	52.0	42.0	32.2	26.6	21.3	16.8	13.9	55.9	113.	5630.
		3	55.7	46.9	41.7	37.8	30.1	22.6	18.4	14.7	11.5	9.4	101.7	-13.	39200.
160	2	1	81.7	69.8	62.8	57.5	46.5	35.7	29.5	23.7	18.7	15.4	44.2	-12.	3310.
		2	60.1	50.9	45.6	41.6	33.5	25.7	21.1	17.0	13.4	11.1	61.4	107.	9700.
		3	59.8	50.1	44.6	40.5	32.1	24.1	19.6	15.6	12.2	9.9	97.3	-14.	9680.
150	2	1	73.5	62.8	56.1	51.7	41.8	32.0	26.5	21.2	16.8	13.9	58.7	65.	5900.
		2	48.9	41.3	36.6	33.7	26.7	20.1	16.4	13.0	10.1	8.3	56.8	-7.	22200.
		3	64.8	54.2	47.8	43.5	34.4	25.8	21.0	16.6	13.0	10.6	109.5	-10.	6230.
145	2	1	69.9	59.4	53.1	48.6	39.3	30.0	24.8	19.9	15.7	13.1	60.0	65.	7300.
		2	50.0	41.9	37.3	33.9	27.0	20.3	16.6	13.2	10.3	8.5	58.7	-14.	91200.
		3	63.8	53.1	46.8	42.3	33.5	24.9	20.3	16.0	12.5	10.2	115.5	-50.	5170.
135	2	1	52.4	44.5	39.3	35.8	28.8	21.8	17.9	14.3	11.2	9.3	59.8	24.	13300.
		2	58.5	49.5	43.8	39.8	31.8	24.0	19.6	15.5	12.1	10.0	46.8	-9.	14400.
		3	66.4	55.3	48.4	43.7	34.4	25.5	20.6	16.3	12.6	10.3	123.5	-119.	4240.
125	2	1	50.6	42.5	37.7	34.3	27.3	20.6	16.8	13.4	10.5	8.6	57.3	14.	88400.
		2	70.6	59.6	53.2	48.5	38.7	29.3	24.0	19.0	14.9	12.3	37.8	-7.	5310.
		3	62.4	51.3	45.1	40.6	31.7	23.3	18.8	14.8	11.4	9.3	120.4	-8.	3470.

Index: 76C1N.IND

Data : 76C1N.DAT

110	2	1	64.6	54.4	48.5	44.2	35.0	26.5	21.7	17.3	13.5	11.2	41.8	12.	8330.
		2	62.2	51.6	45.5	41.3	32.3	24.1	19.5	15.4	11.9	9.8	69.1	-10.	5650.
		3	56.3	46.0	40.3	36.4	28.2	20.8	16.8	13.2	10.2	8.3	99.1	19.	2400.
105	2	1	70.8	59.7	52.9	48.4	38.4	29.1	23.9	18.9	14.8	12.3	38.8	15.	5570.
		2	62.9	52.0	45.4	41.3	32.2	23.8	19.3	15.0	11.6	9.4	76.6	-16.	5560.
		3	50.6	40.9	35.4	32.2	24.8	18.3	14.8	11.6	8.9	7.4	100.8	38.	2250.
95	2	1	67.5	56.5	50.1	45.2	35.8	26.8	21.8	17.2	13.3	10.9	59.9	11.	5630.
		2	66.0	54.1	47.4	42.5	33.2	24.4	19.6	15.4	11.8	9.6	67.0	-27.	3910.
		3	219.6	67.7	29.2	19.2	15.9	13.7	11.6	9.3	7.3	6.0	106.9	13.	2060.
83	2	1	65.0	53.7	46.9	42.4	33.2	24.5	19.7	15.6	12.0	9.8	73.2	-3.	5000.
		2	51.0	42.7	37.4	33.9	26.5	19.5	15.6	12.3	9.4	7.7	46.3	12.	2260.
75	2	1	64.9	53.4	46.4	41.9	32.6	24.0	19.4	15.2	11.7	9.5	67.3	-16.	3910.
		2	42.7	35.3	30.8	28.2	21.9	16.2	13.2	10.4	7.9	6.5	42.3	14.	1870.
65	2	1	54.5	44.6	39.2	35.3	27.6	19.8	15.6	11.7	8.6	6.6	47.4	-56.	2370.
		2	45.1	36.2	31.9	28.9	22.2	16.4	13.2	10.5	8.4	7.0	58.1	107.	2380.
50	2	1	39.5	32.1	28.2	25.4	19.9	14.7	11.9	9.3	7.1	5.9	50.1	33.	2130.

IFR-11 DATA SUMMARY

SURVEY : MT. SICKER - DRIP MTS-76 C1E

INDEX FILE : 76C1E.IND

DATA FILE : 76C1E.DAT

LINE NO. : 762

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
180	2	1	43.9	36.1	31.7	28.3	21.9	15.9	12.6	9.7	7.4	5.8	71.2	-18.	2920.
		2	64.2	54.4	48.6	44.3	35.6	27.1	22.2	17.7	13.9	11.5	110.0	-97.	4480.
		3	28.6	22.6	19.6	17.2	12.9	9.0	7.0	5.2	3.9	3.0	325.5	151.	7010.
175	2	1	60.0	50.8	45.1	41.1	32.8	24.7	20.1	15.9	12.4	10.2	88.8	7.	3670.
		2	62.3	52.6	46.7	42.7	34.1	25.8	21.1	16.8	13.1	10.8	97.2	-8.	4030.
		3	25.9	20.4	17.3	15.3	11.3	7.7	5.9	4.3	3.1	2.3	312.6	34.	6890.
170	2	1	65.4	55.0	48.8	44.4	35.0	26.0	20.8	16.1	12.2	9.7	77.5	-66.	3170.
		2	50.2	41.9	37.3	34.0	27.1	20.6	17.0	13.7	10.8	9.1	134.6	115.	5530.
		3	24.6	19.0	16.1	14.1	10.3	6.9	5.2	3.8	2.6	2.0	279.7	-16.	6210.
160	2	1	61.9	52.2	46.5	42.4	33.9	25.6	20.9	16.6	12.9	10.6	111.0	-421.	4520.
		2	27.2	21.9	19.0	16.9	13.0	9.3	7.3	5.5	4.1	3.2	158.8	105.	6650.
		3	21.9	16.3	13.6	11.7	8.2	5.2	3.8	2.6	1.8	1.2	199.9	-14.	4650.
150	2	1	48.7	40.7	35.9	32.5	25.7	19.2	15.6	12.3	9.5	7.8	138.9	65.	5700.
		2	18.6	14.6	12.2	10.4	7.6	4.9	3.6	2.5	1.6	1.1	166.1	-6.	7110.
		3	-11.5	-12.9	-12.9	-13.1	-12.2	-10.6	-9.3	-7.8	-6.5	-5.5	102.4	-11.	2510.
145	2	1	39.5	32.4	28.3	25.6	20.0	14.6	11.7	9.1	7.0	5.6	148.6	66.	6160.
		2	22.3	17.3	14.6	12.8	9.2	6.1	4.6	3.2	2.2	1.6	175.9	-13.	7620.
		3	-161.6	-142.3	-130.0	-120.2	-98.8	-76.8	-63.6	-51.1	-40.4	-33.4	32.5	-49.	828.
140	2	1	26.1	21.0	18.0	15.8	12.0	8.5	6.6	5.0	3.6	2.8	162.1	88.	6780.
		2	28.3	22.2	18.8	16.4	12.1	8.2	6.3	4.6	3.2	2.5	166.1	-3.	7340.
		3	259.1	258.7	258.8	258.8	259.0	259.1	247.1	209.4	175.1	151.9	-8.3	-47.	219.
135	2	1	19.4	15.3	12.8	11.2	8.0	5.4	4.0	2.9	2.0	1.4	166.5	25.	7020.
		2	32.4	25.8	21.9	19.3	14.4	10.0	7.7	5.7	4.2	3.3	135.6	-9.	6100.
		3	285.1	243.1	217.8	199.0	159.3	120.4	98.2	77.7	60.5	49.3	-30.2	-119.	837.

Index: 76C1E.IND

Data : 76C1E.DAT

125	2	1	24.8	19.6	16.5	14.3	10.4	7.0	5.2	3.8	2.6	1.9	177.1	14.	7750.
		2	19.5	14.8	12.2	10.3	7.3	4.8	3.6	2.6	1.8	1.4	61.6	-6.	2950.
		3	82.8	68.7	60.6	54.8	42.9	31.5	25.3	19.6	15.1	12.1	-97.6	-8.	3030.
110	2	1	30.1	23.2	19.5	17.0	12.4	8.4	6.4	4.7	3.4	2.6	95.0	13.	4430.
		2	207.6	177.2	158.7	145.3	116.7	88.7	72.6	57.8	45.1	37.1	-28.1	-8.	1490.
		3	16.7	12.7	10.6	9.2	6.4	4.1	2.9	2.0	1.2	.8	-177.2	18.	6800.
105	2	1	11.0	7.0	4.9	3.7	1.8	.5	.0	-.1	-.3	-.3	49.5	16.	2370.
		2	167.9	142.2	126.7	115.3	92.0	69.5	56.7	44.8	35.0	28.6	-48.0	-14.	2660.
		3	7.3	4.4	3.1	2.5	1.0	.1	-.2	-.5	-.6	-.7	-255.7	37.	10700.
100	2	1	-60.0	-57.2	-54.6	-51.6	-44.5	-36.0	-30.4	-24.7	-20.1	-16.6	20.5	13.	994.
		2	229.2	194.5	173.3	157.6	125.5	94.3	76.6	60.4	47.1	38.3	-34.2	-8.	1950.
		3	183.6	45.2	2.7	-9.0	-8.0	-3.1	-1.8	-1.4	-1.1	-1.0	-338.1	-5.	15500.
90	2	1	161.9	139.3	125.1	114.3	92.1	69.9	57.3	45.6	35.6	29.4	38.9	-5.	2020.
		2	48.2	38.8	33.2	29.0	21.3	14.4	10.9	7.9	5.4	4.1	49.0	1.	3160.
83	2	1	234.3	202.5	182.0	166.9	134.7	102.8	84.2	67.0	52.6	43.1	36.3	-2.	2010.
		2	-9.1	-8.4	-8.2	-7.9	-7.6	-7.0	-6.4	-5.6	-4.8	-4.3	94.5	13.	6740.
75	2	1	109.0	90.8	79.6	71.8	56.1	41.2	32.8	25.4	19.4	15.5	49.4	-16.	2990.
		2	1.8	1.4	.5	.9	.3	-.1	-.3	-.4	-.5	-.5	102.7	14.	8380.
65	2	1	.4	-.6	-1.6	-2.1	-2.7	-3.0	-3.0	-2.8	-2.6	-2.3	83.2	-55.	5750.
		2	7.0	5.3	4.2	3.4	2.3	1.2	.7	.3	.0	-.1	202.9	110.	20900.
50	2	1	1.6	1.2	.8	.8	.2	.0	-.2	-.3	-.3	-.4	154.7	35.	13900.

IFR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-76 C1S

INDEX FILE : 76C1S.IND

DATA FILE : 76C1S.DAT

LINE NO. : 763

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
180	2	1	57.7	48.9	43.6	39.9	31.4	24.1	20.1	15.9	13.1	11.3	9.8	-18.	799.
		2	66.6	57.6	52.0	48.1	39.3	30.3	24.6	19.8	15.1	11.8	8.8	-96.	661.
		3	50.5	43.2	38.7	35.5	28.5	21.9	18.1	14.4	11.4	9.5	24.3	152.	792.
175	2	1	62.0	52.4	46.9	43.4	34.9	27.1	22.1	18.1	14.5	11.9	9.4	7.	751.
		2	71.9	60.8	54.7	50.7	40.7	31.2	25.6	20.3	15.9	13.0	7.9	-8.	576.
		3	50.1	41.7	37.4	34.6	27.5	21.1	17.3	13.9	11.0	9.0	25.1	34.	808.
170	2	1	67.0	57.4	51.7	47.4	38.3	29.3	24.2	19.5	15.5	12.8	8.3	-65.	618.
		2	63.5	54.2	49.0	44.8	36.5	28.3	23.4	19.1	15.1	12.6	11.5	115.	792.
		3	49.7	42.0	37.6	34.0	27.2	20.6	16.8	13.4	10.5	8.6	25.4	-15.	762.
160	2	1	64.4	55.7	49.8	45.9	37.3	28.9	23.8	19.0	15.1	12.5	9.1	-10.	650.
		2	51.2	43.8	39.1	35.9	29.0	22.3	18.4	14.9	11.9	9.9	13.4	105.	858.
		3	50.4	42.4	37.7	34.2	27.3	20.6	16.8	13.3	10.4	8.5	28.4	-15.	822.
150	2	1	61.5	52.8	47.7	43.8	35.9	28.2	23.3	18.8	15.2	12.6	12.0	65.	792.
		2	44.3	37.6	33.7	31.1	24.9	18.9	15.5	12.4	9.6	8.0	12.7	-5.	792.
		3	47.6	39.5	35.1	31.7	25.1	18.8	15.1	11.9	9.2	7.5	36.0	-14.	1020.
145	2	1	57.5	49.1	44.2	40.5	32.8	25.1	20.8	16.7	13.3	10.8	12.8	68.	843.
		2	45.6	38.6	34.6	31.5	25.3	19.2	15.9	12.6	10.0	8.1	13.1	-11.	808.
		3	44.0	36.3	31.8	28.8	22.6	16.7	13.5	10.5	8.2	6.5	40.8	-55.	1120.
135	2	1	45.4	38.4	35.0	31.6	25.4	19.8	16.4	13.0	10.2	8.5	13.6	24.	873.
		2	52.9	44.8	40.6	36.6	29.4	22.6	18.7	14.8	11.6	9.4	12.1	-7.	717.
		3	45.1	37.0	33.0	29.2	22.8	16.7	13.7	10.7	8.2	6.6	45.5	-122.	1210.
125	2	1	45.8	38.4	34.8	31.5	25.4	19.3	15.6	12.7	10.0	8.2	12.8	14.	777.
		2	54.6	45.9	41.0	37.1	29.7	22.4	18.2	14.6	11.4	9.3	14.1	-6.	807.
		3	42.0	34.5	30.2	26.9	21.1	15.4	12.2	9.6	7.3	5.8	45.3	-11.	1180.

Index: 76C1S.IND

Data : 76C1S.DAT

110	2	1	52.9	45.5	40.2	42.6	29.0	21.9	17.9	14.3	11.1	9.2	13.5	14.	763.
		2	39.3	32.9	28.7	25.6	20.0	14.6	11.8	9.3	7.0	5.7	24.2	-10.	1310.
		3	39.9	33.7	29.8	26.7	21.2	15.8	12.8	10.2	7.8	6.5	46.2	18.	1160.
105	2	1	54.4	45.2	40.6	36.7	29.2	21.9	17.8	14.1	11.0	9.0	14.7	16.	836.
		2	39.7	31.9	28.5	25.4	19.9	14.6	11.7	9.2	7.2	5.9	27.2	-15.	1450.
		3	37.8	31.3	28.3	25.6	20.4	15.4	12.4	9.8	7.7	6.2	51.8	37.	1290.
100	2	1	51.8	43.5	38.9	35.2	27.8	21.0	17.1	13.5	10.5	8.7	18.3	13.	991.
		2	38.6	31.5	27.7	24.5	18.8	13.6	10.9	8.5	6.4	5.1	27.2	-9.	1380.
		3	317.8	125.8	51.2	22.6	10.2	11.2	10.5	8.9	7.2	5.9	52.9	-7.	1260.
90	2	1	38.2	31.2	27.6	24.8	19.2	14.2	11.6	8.9	6.9	5.5	25.8	-4.	1340.
		2	50.8	41.5	36.6	32.7	25.6	18.8	15.3	11.8	9.1	7.3	21.7	2.	1060.
83	2	1	39.2	32.1	27.6	24.7	19.1	13.8	11.2	8.8	6.5	5.5	27.0	-1.	1390.
		2	38.6	33.1	29.5	26.7	21.3	15.8	12.9	10.2	7.8	6.5	21.0	13.	1010.
75	2	1	45.4	35.7	31.0	28.2	21.5	16.1	12.9	9.9	7.6	6.2	26.0	-15.	1310.
		2	31.9	27.3	24.6	22.9	18.1	14.1	11.5	9.0	7.1	5.8	22.0	15.	1050.
65	2	1	40.6	33.2	29.7	26.5	21.1	15.8	12.5	9.8	7.7	6.1	21.3	-54.	1040.
		2	34.7	29.8	27.3	24.9	20.4	15.8	12.9	10.3	8.1	6.6	34.8	110.	1630.
50	2	1	30.2	26.4	24.1	21.9	18.2	14.1	12.1	10.3	8.6	7.2	28.3	36.	1340.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-76 C1W

INDEX FILE : 76C1W.IND

DATA FILE : 76C1W.DAT

LINE NO. : 764

Station	Receive Mode	Dipole	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
180	2	1	72.3	61.4	54.6	50.1	40.5	30.8	25.4	20.3	15.9	13.1	24.5	-19.	2070.
		2	61.2	52.4	46.6	43.1	34.9	26.8	22.3	18.0	14.1	12.0	11.0	-95.	887.
		3	93.5	80.6	72.4	67.0	54.9	42.6	35.7	29.1	23.2	19.6	21.5	151.	954.
175	2	1	66.2	56.5	50.4	46.7	37.6	28.8	23.7	19.0	15.1	12.6	19.5	8.	1560.
		2	77.7	65.9	58.5	54.1	43.2	32.9	27.1	21.5	16.8	13.2	8.8	-7.	716.
		3	90.1	77.4	69.5	64.6	52.5	40.9	34.1	27.8	22.5	18.9	24.6	33.	1050.
170	2	1	66.4	56.8	50.9	46.6	37.8	29.0	23.9	19.2	15.1	12.5	16.5	-64.	1300.
		2	75.9	64.8	58.3	53.2	43.2	33.1	27.6	22.3	17.9	14.9	13.3	114.	1060.
		3	82.2	70.1	63.0	57.6	46.8	35.9	29.8	24.0	19.0	15.7	30.1	-15.	1300.
160	2	1	58.1	49.9	44.6	40.4	32.9	25.2	20.7	16.4	13.2	10.7	11.0	-10.	887.
		2	86.8	75.6	67.2	61.3	50.5	39.2	32.6	26.2	21.2	17.7	13.8	104.	1120.
		3	63.8	54.0	47.9	43.5	35.0	26.6	21.7	17.2	13.6	11.1	47.6	-15.	2180.
150	2	1	71.2	61.0	54.6	50.3	40.7	31.4	26.0	21.0	16.6	13.9	13.4	65.	1060.
		2	101.0	87.0	78.3	72.4	59.0	45.9	38.3	31.1	24.9	20.9	11.1	-4.	928.
		3	50.9	42.4	37.4	34.0	26.9	20.2	16.4	12.9	10.0	8.2	78.3	-15.	3800.
145	2	1	79.0	67.7	60.9	56.0	45.6	35.3	29.3	23.6	18.8	15.6	13.8	68.	1110.
		2	101.9	87.9	79.4	73.2	60.2	47.0	39.3	31.8	25.6	21.3	10.1	-11.	852.
		3	44.1	36.1	31.7	28.7	22.5	16.6	13.4	10.4	8.0	6.5	98.8	-57.	4990.
135	2	1	87.1	75.1	67.3	62.4	50.7	39.3	32.7	26.5	21.2	17.7	13.3	24.	1090.
		2	80.6	69.3	62.2	57.6	46.7	36.0	29.7	24.1	19.3	16.1	13.7	-7.	1210.
		3	42.3	34.6	30.1	27.3	21.1	15.4	12.3	9.5	7.3	5.8	114.7	-123.	6280.
125	2	1	97.6	85.3	77.2	71.6	58.3	45.7	38.4	31.7	25.0	21.3	9.5	14.	816.
		2	58.5	49.1	43.7	39.9	31.4	23.6	19.2	15.5	11.6	9.5	31.4	-6.	2930.
		3	36.1	29.5	25.7	23.2	17.6	12.8	10.1	8.0	5.9	4.7	114.8	-12.	6980.

Index: 76C1W.IND

Data : 76C1W.DAT

110	2	1	63.5	53.7	47.7	43.7	35.0	26.5	21.7	17.3	13.6	11.1	24.6	14.	2240.
		2	39.2	32.1	27.9	25.4	19.7	14.4	11.5	9.0	6.9	5.5	63.2	-10.	6570.
		3	26.4	21.7	18.8	17.2	13.4	9.8	7.8	6.1	4.6	3.6	108.8	17.	7870.
105	2	1	58.8	49.2	43.6	39.6	31.3	23.6	19.2	15.2	11.8	9.7	34.2	15.	3180.
		2	38.2	30.9	27.0	24.3	18.7	13.6	10.9	8.4	6.4	5.3	71.4	-15.	7770.
		3	21.2	17.3	15.2	13.9	10.7	7.8	6.3	4.8	3.6	2.9	116.4	36.	9490.
100	2	1	54.4	45.7	40.5	36.6	29.1	21.7	17.6	13.9	10.8	8.8	44.7	12.	4240.
		2	35.1	28.6	24.7	21.9	16.8	12.0	9.4	7.2	5.4	4.3	70.0	-10.	7870.
		3	331.7	126.9	45.0	12.8	-6	2.5	3.5	3.2	2.6	2.1	115.4	-8.	10000.
90	2	1	42.1	35.4	31.4	28.6	23.2	18.1	15.1	12.1	9.8	8.2	67.5	-6.	6890.
		2	34.4	27.4	23.1	20.0	14.1	8.7	5.9	4.1	2.3	1.2	52.8	6.	6640.
83	2	1	38.3	31.3	27.1	24.2	18.6	13.5	10.7	8.3	6.2	5.0	70.5	-1.	7690.
		2	24.9	21.7	19.2	17.4	13.5	10.0	7.9	6.1	4.6	3.7	51.5	13.	7200.
75	2	1	37.0	29.9	25.7	23.1	17.6	12.7	10.0	7.7	5.8	4.6	66.1	-15.	7810.
		2	16.8	14.8	13.4	12.4	10.0	7.7	6.2	4.9	3.7	3.0	48.3	15.	7780.
65	2	1	29.3	24.2	21.0	18.8	14.7	10.4	8.1	6.4	4.9	4.0	51.8	-53.	6840.
		2	12.6	11.0	9.9	8.0	7.4	5.3	4.2	3.2	2.3	1.8	73.9	110.	14600.
50	2	1	12.0	10.4	10.1	9.1	7.5	5.7	4.6	3.6	2.8	2.2	64.0	36.	11200.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-77 C1N

INDEX FILE : 77C1N.IND

DATA FILE : 77C1N.DAT

LINE NO. : 771

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
151	2	1	71.0	60.5	54.1	49.3	39.7	30.2	24.8	19.8	15.6	12.8	33.8	-6.	83700.
		2	68.1	57.7	51.3	46.9	37.9	28.9	23.8	19.0	15.0	12.4	92.2	70.	2920.
145	2	1	69.7	59.1	52.9	48.5	38.9	29.7	24.3	19.4	15.2	12.6	38.0	-7.	10100.
		2	66.4	55.9	49.8	45.7	36.7	28.0	23.0	18.4	14.5	11.9	93.7	72.	2550.
140	2	1	66.1	56.3	50.5	46.3	37.2	28.5	23.4	18.8	14.8	12.2	40.8	-2.	6250.
		2	67.1	56.6	50.5	46.3	37.1	28.4	23.3	18.7	14.8	12.2	89.4	70.	2190.
133	2	1	68.5	58.5	52.2	48.2	39.0	29.8	24.5	19.7	15.6	12.9	45.1	7.	4420.
		2	65.8	55.4	49.1	45.3	36.4	27.7	22.7	18.3	14.5	12.0	82.0	57.	1790.
125	2	1	65.9	56.4	50.5	46.1	37.3	28.5	23.5	18.9	14.9	12.4	49.3	15.	3460.
		2	64.8	55.1	49.0	44.8	36.1	27.6	22.7	18.2	14.4	11.9	72.2	44.	1430.
118	2	1	68.7	58.1	51.9	47.2	38.0	28.9	23.7	19.0	14.9	12.3	47.4	28.	2760.
		2	62.8	53.1	47.5	43.4	35.0	26.7	22.0	17.6	13.9	11.5	64.7	25.	1230.
110	2	1	66.7	55.8	50.4	45.8	36.7	28.0	23.0	18.4	14.5	11.9	44.3	29.	2180.
		2	63.2	53.0	47.8	43.7	35.1	26.8	22.1	17.7	14.0	11.6	56.1	20.	1010.
103	2	1	65.0	55.2	49.0	44.9	36.2	27.6	22.7	18.1	14.3	11.8	42.3	23.	1820.
		2	64.0	54.2	47.9	44.0	35.3	26.8	22.1	17.6	13.9	11.5	48.8	16.	831.
95	2	1	62.1	53.1	47.7	43.1	35.2	26.8	22.2	17.7	13.9	11.5	36.6	18.	1430.
		2	61.8	52.1	46.3	41.6	33.7	25.4	20.9	16.7	13.1	10.9	44.7	17.	743.
88	2	1	62.3	53.4	48.1	43.7	35.4	27.2	22.4	18.0	14.2	11.7	29.8	14.	1080.
		2	59.3	49.5	43.8	39.4	31.4	23.7	19.3	15.3	12.0	9.9	52.0	17.	858.
80	2	1	61.2	52.9	47.1	43.2	34.9	26.6	21.9	17.5	13.6	11.2	25.2	10.	875.

		2	61.8	52.0	45.5	41.5	32.8	24.5	20.0	15.8	12.2	10.1	56.9	-50.	929.
73	2	1	62.8	53.6	48.3	44.3	35.5	27.1	22.3	17.8	14.1	11.6	22.9	6.	763.
		2	63.0	52.3	46.5	42.4	33.2	24.9	20.2	16.0	12.5	10.2	58.7	19.	964.
65	2	1	65.1	55.1	49.4	45.2	36.0	27.2	22.2	17.7	13.9	11.4	21.3	6.	712.
57	2	1	61.0	50.7	45.0	41.2	32.3	24.3	19.8	15.7	12.3	10.1	19.6	10.	638.
50	2	1	54.1	45.0	39.6	36.0	28.5	21.3	17.4	13.8	11.4	9.8	30.5	10.	1010.
43	2	1	57.7	47.8	42.5	38.2	30.2	22.7	18.4	14.5	11.2	9.2	36.0	1.	1190.
35	2	1	67.1	56.2	49.9	45.1	35.6	26.7	21.7	17.1	13.2	10.7	33.4	14.	1120.
30	2	1	72.6	60.7	54.1	49.0	39.1	29.4	23.9	18.9	14.7	12.0	28.1	21.	972.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-77 C1E

INDEX FILE : 77C1E.IND

DATA FILE : 77C1E.DAT

LINE NO. : 772

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
151	2	1	44.7	37.4	33.0	29.9	23.5	17.4	14.0	11.0	8.5	6.9	72.4	-7.	3380.
		2	83.5	70.8	63.1	57.8	46.3	35.3	28.9	23.1	18.2	15.0	110.2	69.	2730.
145	2	1	41.0	33.9	29.7	26.8	20.9	15.4	12.4	9.6	7.4	6.0	96.8	-5.	4560.
		2	109.2	93.2	83.3	76.2	61.5	47.2	38.9	31.2	24.7	20.5	73.7	69.	1880.
140	2	1	45.2	37.4	32.8	29.6	23.1	17.0	13.7	10.6	8.1	6.6	95.7	0.	4550.
		2	133.5	114.0	102.2	93.7	76.1	58.6	48.8	39.4	31.4	26.2	53.0	67.	1380.
133	2	1	61.0	51.3	45.5	41.4	32.9	24.8	20.2	16.0	12.5	10.2	90.8	8.	4360.
		2	112.4	95.4	85.3	78.4	63.3	48.6	40.3	32.5	25.9	21.6	51.6	54.	1410.
125	2	1	104.4	89.8	80.8	73.9	59.9	46.1	38.0	30.5	24.1	19.9	47.4	16.	2320.
		2	89.3	75.5	67.2	61.3	49.0	37.4	30.8	24.7	19.5	16.1	51.3	42.	1490.
118	2	1	139.5	121.2	109.0	100.1	82.0	63.7	53.0	42.9	34.2	28.6	30.5	26.	1510.
		2	65.9	55.7	48.9	44.4	35.5	26.9	22.1	17.6	13.9	11.6	53.7	24.	1630.
110	2	1	174.7	150.8	137.0	125.9	102.6	79.9	66.5	54.0	43.3	36.2	17.6	27.	902.
		2	53.4	43.6	39.4	35.7	28.2	21.5	17.6	14.1	11.3	9.3	48.0	20.	1580.
103	2	1	125.4	107.1	95.7	87.2	70.7	54.3	44.9	36.2	28.7	23.8	19.3	20.	1030.
		2	34.6	28.6	25.4	23.0	18.7	14.5	12.1	9.9	7.9	6.7	30.5	17.	1070.
95	2	1	71.3	59.4	52.6	48.0	37.9	28.7	23.5	18.7	14.7	12.1	28.4	15.	1610.
		2	-107.1	-88.8	-75.7	-64.9	-48.0	-31.8	-23.1	-16.3	-11.0	-7.9	5.0	18.	199.
88	2	1	54.6	45.1	39.7	35.6	28.2	21.2	17.3	13.7	10.8	8.8	32.6	10.	1980.
		2	78.7	63.6	55.2	49.5	37.6	26.7	21.1	16.0	11.9	9.4	-34.7	20.	1540.
80	2	1	45.0	36.5	32.1	29.0	23.0	17.3	14.2	11.3	8.9	7.3	28.5	7.	1900.

		2	86.6	71.7	62.5	56.4	43.9	32.2	25.7	20.0	15.3	12.3	-72.0	-47.	3820.
73	2	1	38.5	31.6	27.6	24.7	19.8	15.1	12.5	10.0	7.8	6.4	21.0	5.	1480.
		2	83.3	68.5	60.0	54.3	42.3	31.1	25.0	19.4	14.9	12.0	-95.2	23.	6050.
65	2	1	232.3	197.1	175.6	163.1	125.8	90.9	70.9	54.1	40.1	31.8	2.8	4.	222.
57	2	1	76.4	62.7	54.5	49.2	37.8	27.4	21.8	16.8	12.7	10.3	19.1	7.	1720.
50	2	1	64.4	52.6	45.7	40.8	31.4	22.7	17.9	13.8	10.4	8.2	44.6	6.	4740.
43	2	1	78.0	64.3	56.5	50.9	39.7	29.7	25.0	20.7	17.2	14.8	58.5	-2.	7470.
35	2	1	87.6	72.8	64.0	57.9	45.5	33.7	27.2	21.2	16.3	13.3	64.9	12.	10700.
30	2	1	81.6	68.2	60.3	54.8	43.4	32.4	26.3	20.7	16.0	13.1	73.0	18.	15000.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-77 C1S

INDEX FILE : 77C1S.IND

DATA FILE : 77C1S.DAT

LINE NO. : 773

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
151	2	1	56.5	48.2	42.9	38.5	30.8	23.2	18.8	14.8	11.4	9.2	9.1	-7.	1000.
		2	58.7	49.4	43.9	39.6	31.7	23.9	19.4	15.3	11.8	9.6	26.2	71.	1220.
145	2	1	59.7	49.6	44.6	41.7	32.9	25.1	20.7	16.5	12.9	10.5	10.0	-5.	1060.
		2	60.1	49.1	44.3	41.2	32.6	24.9	20.6	16.5	12.9	10.6	28.5	69.	1300.
140	2	1	60.1	51.5	45.3	41.5	33.6	25.9	21.0	17.0	13.4	11.2	9.7	1.	1010.
		2	59.1	49.4	43.4	39.8	32.0	24.5	19.9	16.1	12.6	10.5	29.1	66.	1280.
133	2	1	59.9	52.1	46.1	42.1	33.8	25.8	21.2	16.9	13.2	11.1	11.8	10.	1160.
		2	56.6	48.2	42.3	38.4	30.7	23.2	19.1	15.2	11.9	9.9	29.3	52.	1250.
125	2	1	58.5	49.1	45.0	39.9	32.4	24.6	20.1	16.1	12.7	10.4	13.8	17.	1330.
		2	56.8	47.0	42.6	38.2	30.7	23.2	18.9	15.1	11.9	9.8	29.7	41.	1210.
118	2	1	56.7	52.1	45.2	40.8	32.2	24.4	19.8	15.7	12.2	9.9	14.3	26.	1310.
		2	52.7	47.0	41.2	37.2	29.5	22.5	18.3	14.6	11.4	9.3	30.1	25.	1200.
110	2	1	57.4	48.5	44.0	38.9	31.3	23.8	19.3	15.4	12.0	9.8	14.4	26.	1290.
		2	54.9	45.9	41.4	37.0	29.6	22.5	18.3	14.5	11.3	9.3	30.9	21.	1170.
103	2	1	55.7	47.5	42.1	38.4	30.7	23.1	19.1	15.0	11.7	9.6	15.2	20.	1290.
		2	54.9	46.0	40.6	37.0	29.4	22.0	18.0	14.2	11.1	9.1	31.0	17.	1130.
95	2	1	54.8	46.7	41.6	38.0	30.2	23.2	18.9	15.1	11.8	9.7	15.1	13.	1240.
		2	52.9	43.9	38.8	35.2	27.7	20.8	16.8	13.3	10.3	8.4	32.3	20.	1130.
88	2	1	54.9	46.4	42.0	38.0	30.6	23.2	19.1	15.2	11.9	9.9	14.7	9.	1150.
		2	52.8	43.2	38.3	34.5	27.2	20.3	16.5	12.9	10.0	8.2	41.2	21.	1400.
80	2	1	54.5	46.4	41.0	37.6	30.2	22.9	18.7	14.8	11.6	9.5	14.8	6.	1120.

		2	57.4	47.3	41.2	37.6	29.6	21.9	17.7	13.9	10.8	8.8	48.5	-47.	1590.
73	2	1	54.3	46.0	41.3	37.3	29.7	22.5	18.2	14.6	11.3	9.3	15.4	4.	1130.
		2	57.4	47.4	42.0	37.7	29.6	21.9	17.7	13.9	10.7	8.7	53.4	23.	1690.
65	2	1	54.0	45.4	40.4	36.8	29.5	21.8	17.6	13.9	10.8	8.8	16.0	4.	1130.
57	2	1	49.7	41.6	36.3	32.8	25.9	19.3	15.7	12.4	9.6	7.8	16.5	6.	1110.
50	2	1	49.6	41.0	36.2	32.6	25.5	19.0	15.3	12.1	9.4	7.6	26.1	6.	1710.
43	2	1	56.3	46.9	41.0	37.2	29.1	21.6	17.6	13.7	10.6	8.7	31.5	-3.	2000.
35	2	1	60.5	50.2	44.2	39.8	31.0	22.8	18.2	14.1	10.6	8.5	32.2	12.	1960.
30	2	1	59.9	50.4	44.3	40.5	32.0	23.9	19.4	15.4	12.0	9.7	32.7	19.	1960.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-77 C1W

INDEX FILE : 77C1W.IND

DATA FILE : 77C1W.DAT

LINE NO. : 774

Station	Receive Mode	Dipole	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
151	2	1	65.5	55.3	49.5	45.1	35.8	27.2	22.1	17.6	13.8	11.2	27.3	-7.	1820.
		2	58.1	48.5	43.0	39.1	30.9	23.3	18.9	15.0	11.7	9.6	73.0	71.	2610.
145	2	1	64.8	55.2	49.1	44.6	35.7	27.0	22.0	17.4	13.6	11.2	26.2	-5.	1700.
		2	56.7	47.4	41.9	37.9	30.2	22.7	18.5	14.7	11.5	9.4	81.2	68.	2890.
140	2	1	66.0	56.2	50.2	46.3	37.0	28.3	23.2	18.6	14.6	12.1	21.5	2.	1460.
		2	56.1	46.8	41.2	37.7	29.8	22.4	18.2	14.5	11.3	9.3	82.9	65.	3120.
133	2	1	61.4	51.8	46.3	42.4	33.8	25.5	20.8	16.4	12.9	10.9	29.3	11.	1960.
		2	55.4	45.9	40.4	36.8	29.0	21.7	17.5	13.8	10.7	8.8	77.3	51.	2970.
125	2	1	55.9	46.9	41.8	37.8	30.2	22.7	18.4	14.5	11.3	9.3	40.7	17.	2760.
		2	55.5	46.1	41.0	37.1	29.4	22.0	17.9	14.1	10.9	8.9	70.4	40.	2820.
118	2	1	56.4	46.6	41.4	37.6	29.6	22.1	18.0	14.2	11.0	9.0	44.9	25.	3160.
		2	54.4	45.1	40.0	36.5	28.9	21.7	17.7	14.0	10.9	9.0	63.2	25.	2690.
110	2	1	54.7	46.0	40.5	36.6	29.0	21.7	17.5	13.7	10.7	8.6	43.8	25.	3180.
		2	53.4	45.3	39.5	36.1	28.5	21.4	17.3	13.6	10.7	8.7	57.9	21.	2660.
103	2	1	54.7	45.7	41.0	36.8	29.2	22.0	17.8	14.1	11.0	8.9	41.5	19.	3110.
		2	53.2	44.0	39.1	35.1	27.6	20.6	16.6	13.0	10.1	8.1	54.6	17.	2720.
95	2	1	56.0	47.4	42.5	38.5	30.8	23.3	19.1	15.2	11.9	9.8	34.5	12.	2750.
		2	46.4	38.1	33.5	30.1	23.5	17.3	13.9	10.9	8.3	6.7	51.3	19.	2820.
88	2	1	56.4	47.3	42.7	38.8	30.9	23.4	19.1	15.2	11.9	9.9	29.0	8.	2420.
		2	35.2	27.5	24.0	21.5	16.0	11.3	8.9	6.7	5.0	3.8	54.1	21.	3370.
80	2	1	52.8	44.8	39.7	35.9	28.5	21.5	17.5	13.8	10.7	8.7	26.5	5.	2370.

Index: 77C1W.IND

Data : 77C1W.DAT

		2	33.1	26.4	22.1	19.5	14.5	10.1	7.7	5.7	4.1	3.1	52.0	-46.	3820.
73	2	1	49.8	41.9	36.9	33.6	26.5	19.8	16.0	12.6	9.7	7.9	25.6	3.	2510.
		2	24.2	18.5	15.0	13.2	9.2	5.8	4.1	2.8	1.7	1.1	43.7	24.	3820.
65	2	1	50.4	41.6	36.8	33.2	26.1	19.4	15.6	12.3	9.5	7.7	27.3	4.	3010.
57	2	1	41.1	33.4	28.7	26.4	19.9	14.4	11.5	8.9	6.7	5.4	25.2	6.	3120.
50	2	1	18.5	12.4	10.6	8.4	5.6	3.3	2.2	1.4	.8	.3	27.6	7.	3980.
43	2	1	13.5	8.4	6.0	5.5	2.3	.3	-.2	-.7	-1.0	-1.1	25.0	-3.	4300.
35	2	1	11.7	7.4	5.7	3.7	1.4	-.1	-.9	-1.4	-1.7	-1.8	16.8	13.	3680.
30	2	1	8.4	5.5	4.3	3.5	1.4	.1	-.4	-1.1	-1.6	-1.9	11.3	20.	3110.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - MTS80 - detail

INDEX FILE : MTS80.IND

DATA FILE : MTS80.DAT

LINE NO. : 80

Station	Receive Mode	Dipole	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
76	2	1	-57.0	-20.2	-5.1	1.9	10.1	12.2	11.3	9.7	8.1	6.8	100.6	0.	451.
		2	136.8	110.0	95.9	86.1	68.8	52.2	42.7	34.0	26.7	21.9	45.1	27.	406.
74	2	1	-14.4	20.5	33.5	39.2	42.1	38.2	33.4	27.9	22.9	19.4	69.2	-10.	241.
		2	118.7	97.6	86.0	78.0	62.5	47.7	39.2	31.4	24.8	20.5	71.3	23.	499.
73	2	1	12.1	36.8	44.5	47.8	47.1	41.0	35.4	29.3	23.7	19.9	120.5	20.	582.
		2	101.5	84.8	74.5	67.8	53.9	40.9	33.7	27.0	21.3	17.7	60.2	1.	583.
70	2	1	81.6	84.8	83.1	80.2	70.3	57.4	48.8	40.2	32.6	27.5	216.5	5.	906.
		2	126.7	104.6	92.3	84.0	67.4	51.6	42.7	34.3	27.3	22.7	76.6	-3.	643.
68	2	1	37.1	34.8	32.8	30.9	26.0	20.4	16.9	13.5	10.7	8.9	723.2	-1.	6480.
		2	76.5	63.7	56.1	50.8	40.6	30.8	25.3	20.2	16.0	13.3	200.9	-65.	3600.
65	2	1	14.4	14.5	14.2	13.6	11.9	9.6	7.9	6.3	4.9	4.0	915.8	-10.	7180.
		2	38.6	32.5	28.7	26.0	20.6	15.5	12.7	10.0	7.9	6.5	521.3	-7.	8200.
60	2	1	29.7	29.9	29.6	28.6	25.3	20.8	17.7	14.5	11.8	9.9	666.0	104.	5970.
		2	72.3	60.3	53.4	48.3	38.1	28.6	23.4	18.6	14.7	12.1	123.6	-213.	2200.
55	2	1	11.8	27.9	34.8	38.0	39.3	35.3	30.8	25.5	20.7	17.3	101.9	39.	376.
		2	124.7	104.2	92.4	84.2	67.4	51.3	42.1	33.7	26.6	22.0	103.5	205.	760.
53	2	1	86.7	80.5	75.4	71.4	60.9	48.9	41.1	33.4	26.8	22.3	188.8	-45.	515.
		2	130.0	109.8	97.8	89.4	71.7	54.7	44.9	35.9	28.4	23.4	77.4	245.	424.
50	2	1	67.8	65.4	62.8	60.2	52.7	42.8	36.1	29.3	23.4	19.5	140.8	168.	421.
		2	139.0	120.6	108.3	99.4	80.6	61.9	51.1	41.1	32.6	27.1	56.3	10.	338.
47	2	1	37.9	52.4	56.3	57.3	54.1	46.1	39.6	32.7	26.5	22.2	134.2	-33.	561.

		2	138.1	115.7	102.3	93.0	73.8	55.7	45.7	36.6	29.1	24.2	33.7	28.	283.
45	2	1	53.8	63.8	67.4	68.2	64.5	55.9	48.5	40.4	33.2	28.1	116.8	69.	523.
		2	98.6	83.1	74.0	67.4	53.6	40.5	33.2	26.5	21.0	17.4	63.7	5.	573.
42	2	1	42.8	48.4	49.6	49.4	45.5	38.5	33.0	27.2	22.1	18.5	169.9	-6.	666.
		2	80.0	65.7	57.6	52.1	41.1	30.7	25.1	19.9	15.6	12.8	97.9	3.	771.
40	2	1	-8.9	1.9	6.9	9.5	12.0	11.9	10.7	9.1	7.6	6.5	208.0	-5.	816.
		2	59.1	48.8	42.8	38.7	30.4	22.6	18.4	14.6	11.5	9.5	113.1	3.	890.
35	2	1	-18.9	-9.3	-4.7	-2.1	.9	2.4	2.4	2.2	1.9	1.7	296.5	-3.	1163.
		2	27.0	21.8	18.8	16.7	12.5	8.9	7.0	5.3	4.1	3.3	126.5	4.	990.
30	2	1	-18.8	-11.5	-7.4	-4.7	-1.0	.7	1.0	1.0	.9	.8	286.1	-3.	945.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-80 C1N

INDEX FILE : 80C1N.IND

DATA FILE : 80C1N.DAT

LINE NO. : 801

Station	Receive	Dipole	M0	M1	M2	M3	M4	M5	M6	M7	M8	M9	Vp	SP	Apparent
	Mode							mV/V					mV	mV	Resist.
75	2	1	64.6	54.3	47.7	44.0	34.8	26.3	21.4	17.0	13.2	10.8	11.3	104.	19800.
		2	104.8	89.5	80.2	73.3	59.5	45.8	37.7	30.4	24.2	20.2	8.6	-15.	2510.
70	2	1	67.8	56.8	50.5	46.0	36.8	28.2	23.4	18.9	15.5	13.3	11.8	-54.	25100.
		2	84.5	72.1	64.5	59.1	47.8	36.6	30.4	24.3	19.2	16.1	10.1	123.	2310.
60	2	1	111.9	95.7	85.6	78.5	63.6	49.0	40.7	33.0	26.2	21.8	9.3	-30.	3870.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-80 C1E

INDEX FILE : 80C1E.IND

DATA FILE : 80C1E.DAT

LINE NO. : 802

Station	Receive	Dipole	M0	M1	M2	M3	M4	M5	M6	M7	M8	M9	Vp	SP	Apparent
	Mode							mV/V					mV	mV	Resist.
75	2	1	40.6	34.4	30.9	28.3	22.9	17.7	14.7	11.9	9.5	7.9	43.3	104.	4020.
		2	71.7	61.5	55.3	50.8	41.3	32.0	26.5	21.6	17.3	15.0	31.8	-13.	4070.
70	2	1	42.2	36.1	32.6	29.8	24.2	18.8	15.7	12.8	10.2	8.5	40.6	-52.	4030.
		2	69.0	58.8	52.9	48.3	39.0	29.9	24.6	19.8	15.4	12.8	32.4	120.	4630.
60	2	1	71.8	61.6	55.2	51.0	41.6	32.3	26.9	21.8	17.4	14.6	27.6	-28.	3210.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-80 C1S

INDEX FILE : 80C1S.IND

DATA FILE : 80C1S.DAT

LINE NO. : 803

Station	Receive	Dipole	M0	M1	M2	M3	M4	M5	M6	M7	M8	M9	Vp	SP	Apparent
	Mode							mV/V					mV	mV	Resist.
75	2	1	53.8	46.1	41.2	38.2	30.9	22.4	17.6	14.1	11.3	9.2	11.3	104.	734.
		2	57.4	48.2	42.4	37.9	26.6	16.0	13.9	12.6	10.1	8.2	8.3	-13.	584.
70	2	1	52.7	45.5	41.3	37.9	30.3	22.9	18.7	14.5	11.0	9.3	11.5	-52.	742.
		2	45.0	38.9	35.3	32.5	26.1	19.8	16.9	14.3	11.4	9.5	9.7	118.	703.
60	2	1	79.8	68.0	61.4	56.5	46.3	36.2	30.3	24.5	19.7	16.6	8.8	-28.	605.

IPR-11 DATA SUMMARY

SURVEY : MT. SICKER - DIRIP MTS-80 C1W

INDEX FILE : 80C1W.IND

DATA FILE : 80C1W.DAT

LINE NO. : 804

Station	Receive Mode	Dipole	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
75	2	1	80.4	68.4	61.1	55.8	44.9	34.2	28.1	22.4	17.5	14.4	96.3	103.	2920.
		2	78.8	67.0	59.9	54.6	43.9	33.4	27.4	21.8	17.1	14.1	37.7	-14.	1520.
70	2	1	79.8	67.8	60.6	55.4	44.5	33.9	27.8	22.2	17.5	14.0	100.8	-52.	3210.
		2	38.1	32.1	28.5	26.0	20.7	15.6	12.7	10.0	8.1	6.9	41.0	119.	1840.
60	2	1	94.4	80.7	72.0	65.9	53.2	40.7	33.4	26.8	21.0	17.4	62.2	-29.	2300.