

12 holes / 59 reported  
 with 0.10 oz/ton intercepts.  
 9/12 at or near previous sites. 830013

AGC Americas Gold Corp.  
 1996 Drill Hole Intersections  
 Maximum Dilution

Hole #	Orientation	Interval (m.)	Width (m.)	Au (oz. / ton)	Ag (oz. / ton)
133	000° @-90°	14.5 - 28.0	13.5	0.039	0.10
134	000° @-90°	27.0 - 31.0	4.0	0.073	0.45
135	180° @-50°	29.0 - 34.0	5.0	0.115	0.47
136	180° @-50°	32.0 - 36.0 77.0 - 80.0	4.0 3.0	0.044 0.039	0.45 1.84
137	000° @-90°	16.0 - 24.5	7.5	0.010	n/a
138	180° @-50°	24.5 - 27.5	3.0	0.019	0.22
139	000° @ -90°	51.0 - 55.0 71.0 - 74.0	4 3	0.062 0.046	8.15 0.22
140	270° @-50°	38.0- 41.0 50.0- 54.0	3 4	0.030 0.068	1.65 2.05
141	000° @-90°	11.0 - 14.0 21.0 - 25.0 38.0 - 48.0	3 4 10	0.216 0.057 0.074	0.30 trace 0.14
142	000° @-90°	22.0 - 25.0 40.0 - 41.0 65.0 - 67.0	3 1 2	0.091 0.078 0.090	0.26 0.86 1.48
143	000° @-60°	14.0 - 17.0 23.0 - 27.0 53.0 - 57.0	3 4 4	0.065 0.061 0.036	0.19 0.31 0.29
144	000° @-50°	11.0- 14.0 27.0 -32.0	3 5	0.380 0.257	0.58 2.60
145	180° @-50°	11.0 - 16.0	5	0.062	0.05
146	000° @-90°	15.0 - 16.0	1	0.060	0.11
147	000° @-90°	none			
148	000° @-90°	39.0 - 42.0 44.0 - 47.0	3 3	0.136 0.031	0.30 2.09

✓  
Prev.

✓  
✓  
Prev.

✓ New

Hole #	Orientation	Interval (m.)	Width (m.)	Au (oz. / ton)	Ag (oz. / ton)	
149	000° @-90°	76.0 - 78.0	2	0.019	0.30	
150	000° @-90°	47.0 - 48.0	1	0.053	0.75	
151	000° @-90°	32.0 - 39.0 64.0 - 65.0	7 1	0.082 0.103	2.16 0.13	✓ New
152	000° @-90°	14.0 - 18.0 24.0 - 26.0 31.0 - 33.0 45.0 - 48.0	4 2 3 3	0.079 0.083 0.049 0.067	0.13 0.78 0.08 0.09	
153	000° @-90°	4.0 - 6.0 32.0 - 35.0	2 3	0.224 0.051	3.59 0.05	✓ New
154	000° @-90°	33.0 - 37.0	4	0.032	0.12	
155	000° @-90°	52.0 - 55.0	3	trace	0.14	
156	210° @-65°	18.0 - 21.0 27.0 - 31.0	3 4	0.048 0.053	0.25 0.13	
157	032° @-65°	17.0 - 31.0	14	0.109	0.07	✓ Prev.
158	000° @-90°	11.0 - 21.0 30.0 - 32.0 45.0 - 48.0 51.0 - 56.0	10 2 3 5	0.138 0.038 0.023 0.034	0.14 n/a n/a n/a	✓
159	000° @-90°	5.0 - 9.0 32.0 - 36.0	4 4	0.020 0.082	n/a 0.38	
160	000° @-90°	7.0 - 15.0 20.0 - 26.0	8 6	0.017 0.018	0.09 0.08	
161	180° @-66°	11.0 - 19.0 90.0 - 91.0 109.0 - 118.0	8 1 9	0.016 0.063 0.121	n/a	
162	000° @-80°	53.0 - 58.0 61.0 - 68.0 91.0 - 108.0	5 7 17	0.041 0.044 0.019	n/a	
163	000° @-90°	10.0 - 13.0 97.0 - 101.0	3 4	0.054 0.050	n/a	

Hole #	Orientation	Interval (m.)	Width (m.)	Au (oz. / ton)	Ag (oz. / ton)
164	180° @-63°	44.0 - 47.0	3	0.280	n/a
		102.0 - 110.0	8	0.077	1.46
165	180° @-75°	72.0- 117.0	45.0	0.011	0.40
166	000° @-90°	97.0 - 102.0	5	0.124	n/a
167	000° @-90°	13.0- 16.0	3	0.050	n/a
		44.0 - 47.0	3	0.048	
168	000° @-90°	13.0 - 22.0	9.0	0.020	n/a
		32.0 - 46.0	14.0	0.053	
169	120° @-55°	core not available			
170	000° @-90°	6.3 - 43.0	36.7	0.051	n/a
		93.0 - 98.0	5	0.030	
171	000° @-90°	7.0 -14.0	7	0.024	n/a
		46.0 - 59.0	13.5	0.042	
172	000° @-90°	31.0 - 50.0	19	0.020	n/a
		80.0 - 83.0	3	0.028	
173	000° @-90°	18.0 - 22.0	4	0.027	n/a
		93.0 - 95.0	2	0.042	
174	000° @-90°	42.0 - 55.0	13	0.033	n/a
		86.0 - 87.0	1	0.041	
		93.0 - 95.0	2	0.065	
175	180° @-70°	33.0 - 70.0	37	0.048	n/a
176	000° @-90°	61.0 - 76.0	15	0.027	n/a
177	000° @-90°	8.0 - 37.0	29	0.041	n/a
178	180° @-50°	11.0 - 15.0	4	0.030	n/a
		34.0 - 39.0	5	0.040	
179	180° @-50°	none			
180	180° @-90°	14.0 - 17.0	3	0.016	n/a
		33.0 - 35.0	2	0.032	

✓ *Pres.*

✓ *Pres.*

Hole #	Orientation	Interval (m.)	Width (m.)	Au (oz. / ton)	Ag (oz. / ton)
181	000° @-90°	115.0 - 133.0	18	0.012	n/a
183	000° @-90°	9.0 - 12.0	3	0.015	n/a
184	000° @-50°	49.0 - 51.0 61.0 - 62.0 75.0 - 77.0	2 1 2	0.011 0.010 0.013	n/a
185	180° @-50°	14.0 - 16.0 16.0 - 19.0	2 3	0.023 0.050	0.03 0.13
186	000° @-90°	8.0 - 36.0	28	0.110	0.43
187	000° @-50°	4.0 - 59.0	55	0.128	0.40
188	180° @-50°	48.0 - 51.0	3	0.097	0.05
189	180° @-50°	51.0 - 59.0	8	0.012	n/a
190	180° @-50°	none			
191	000° @-90°	none			

✓ Down dip  
✓ Prev 15.16  
31.32.

n/a = not available or not calculated  
base metal intersections pending  
File:065ints wpd 23-JAN-97