Refer to this Map as: 92 C/16 East Half EDITION 1 ASE SERIES A 721




Use diagram only to obtain numerical values.
APPROXIMATE MEAN DECLINATION 1955 FOR CENTRE OF SHEET
Annual magnetic change 3′ westerly

Original Survey 1938
Resurveyed and compiled by the Surveys and Mapping Branch, Department of Lands and Forests, British Columbia, 1951
Cartography and reproduction by the Army Survey Establishment, R.C.E. Department of National Defence, 1953.
Converted from the 1:63,360 map to 1:50,000 by the A.S.E. 1955

# COWICHAN LAKE

## BRITISH COLUMBIA

Scale 1:50,000
1.25 Inches to 1 Mile approximately

1 ½ 0 1 2 3 Miles
1000 500 0 1000 2000 3000 4000 Metres
1000 500 0 1000 2000 3000 4000 Yards

inches 0 1 2
0 1 2 3 4 5 centimetres
This reference scale bar has been added to the original image. It will scale at the same rate as the image, therefore it can be used as a reference for the original size.

MAGNETIC DECLINATION 23° 26′ EAST AT CENTRE OF MAP, 1955
Annual magnetic change 3′ westerly

TO GIVE GRID REFERENCE ON THIS SHEET
FIGURES. IGNORE the SMALLER figures printed around the margin of the map. These are for finding the full co-ordinates.
USE ONLY THE LARGER FIGURES PRINTED IN THE MARGIN OR ON THE FACE OF THE MAP. Viz. 409

| POINT | HORIZONTAL CONTROL POINT | | |
|---|---|---|---|
| FOR STANDARD MILITARY GRID REFERENCE | | | |
| East | | North | |
| Take West edge of square in which point lies, and read the figure printed opposite this line on North or South margin or on the line itself on the face of the map. Estimate tenths Eastwards. | 18 | Take South edge of square in which point lies, and read the figure printed opposite this line on East or West margin or on the line itself on the face of the map. Estimate tenths Northwards | 07 |
| | 5 | | 5 |
| East | 185 | North | 075 |
| STANDARD MILITARY GRID REFERENCE | 185075 | (To nearest 100 Metres) | |
| Nearest similar grid reference - 100,000 Metres (Approximately 63 Miles) | | | |

ONE THOUSAND METRE
UNIVERSAL TRANSVERSE MERCATOR GRID
ZONE 10

## REFERENCE

Roads:
hard surface, all weather — more than 2 lanes
hard surface, all weather — 2 lanes — Route No. 18 — less than 2
loose surface, all weather — 2 lanes — wide or more
" less than 2 lanes — all weather — dry weather
Cart Track, Trail — Cart Track — Trail
Railways:
normal gauge, multiple track — Station
normal gauge, single track — Stop — Siding
abandoned, or under construction — abandoned
normal gauge, logging
Bridge, underpass or overpass
Tunnel
Boundary, International
" Province
" County or District
" Township or Parish
" City or Town
" Reservation, Indian, Military, etc
Power Transmission Line
Telephone or Telegraph, trunk route
Horizontal Control Point
Boundary Marker
Bench Mark — BM 3025′
Spot Elevation, (in feet) — 4582
Mine or Pit

Contour Interval 100 Feet
All Elevations in Feet above Mean Sea Level.

Universal Transverse Mercator Projection
North American Datum 1927

Copies may be obtained from The Map Distribution Office, Dept. of Mines and Technical Surveys, Ottawa.

## REFERENCE

House, Building
School
Church
" with conspicuous Tower or Spire
Post Office
Tower, Radio Mast, Lookout, etc.
Cemetery — Cem
Quarry
Sand or Gravel Pit
Cliff
Cutting
Embankment
Saw Mill — SM
Lighthouse
Wharf or Pier
Foreshore Flats — Sand — Mud
Swamp or Marsh
Lake or Pond, intermittent
Glacier or Snowfield
Stream, intermittent, indefinite
Irrigation Canals, Ditches
Inundated Land, seasonal
Contours, elevation — 500 — 400
" depression — 500 — 400
" approximate — 500 — 400
Forest, unclassified, Scrub

CONVERSION SCALE FOR ELEVATIONS
30 20 10 0 50 100 150 200 250 300 Metres
100 50 0 100 200 300 400 500 600 700 800 900 1000 Feet

INDEX TO ADJOINING SHEETS

| | | | |
|---|---|---|---|
| 124°30′ | | | 123°30′ |
| 49°00′ | 92 F/2 ALBERNI INLET | 92 F/1 NANAIMO LAKES | 92 G/4 NANAIMO |
| | 92 C/15 NITINAT | 92 C/16 COWICHAN LAKE | 92 B/13 DUNCAN |
| | 92 C/10 CARMANAH | 92 C/9 SAN JUAN | 92 B/12 SHAWNIGAN |
| 48°30′ | | | |

841113

COWICHAN LAKE
92 C/16 EAST HALF