Cataract

INDUCED POLARIZATION AND MAGNETIC INTENSITY SURVEY

INDUCED POLARIZATION (TIME DOMAIN) :

CHARGEABILITIES MEASURED FOR COMPLETE CYCLE

CHARGING TIME ..... secs
OFF TIME .... secs
DELAY TIME .... secs
INTEGRATION TIME.... secs

Where not specified, times are 2, 2, 0.45 and 0.65 secs respectively, modified to be equivalent to Newmont standard cycle 3; 3; 1

CONFIGURATION ..Pole - Dipole...

DIPOLE LENGTH....100m.....

C_1...... P_1

MAGNETIC INTENSITY :

FIELD COMPONENT..........

inches 0 1
0 1 2 centimetres

SURVEYED & COMPILED BY geoterrex ltd

FOR Chevron Standard Ltd

Cataract

Scales : HORIZONTAL : 1:5000
VERTICAL (Magnetics) : 1 cm=
CONTOUR INTERVALS (I.P.) :
Ma = milliseconds
Pa = 1,2,5 per decade, ohm-metres (pseudo - logarithmic)

L1+50W

Instruments :
I.P. Rx.
I.P. Tx.
MAGNETOMETER

SURVEY BY :	PLOTTED BY :
DATE :	GEOTERREX PROJECT No. 85-

841140