



FIG. 5

ASSAY RESULTS

	Hole	Interval(ft)	Width(ft)	AgO <sub>2</sub> /T	Zn <sub>t</sub>	Pb <sub>t</sub>	AuO <sub>2</sub> /T
A	FW88-8	308.4 - 321.5	13.1	18.89	2.11	1.00	-
B	FW88-22	182.0 - 224.7	42.7	17.17	3.07	1.79	-
C	FW88-22	534.8 - 538.1	3.3	5.53	1.53	1.25	-
D	FW88-24	218.8 - 257.2	38.4	12.95	1.93	0.97	-
E	FW88-25	86.6 - 148.9	62.3	6.04	0.77	0.52	-
	incl.	99.7 - 109.6	9.9	16.33	1.98	1.50	-
F	FW88-26	406.8 - 423.2	16.4	1.69	3.83	4.02	-
G	FW88-28	230.0 - 233.3	3.3	3.76	10.15	4.24	-
H	FW88-28	391.4 - 398.0	6.6	9.26	1.75	0.46	-
I	FW88-29	79.1 - 95.5	16.4	1.96	11.13	1.17	0.009
J	FW88-29	108.9 - 119.7	10.8	4.41	15.50	4.72	0.032
K	FW88-29	132.9 - 136.2	3.3	4.40	21.78	4.36	0.024
L	FW88-29	145.6 - 152.2	6.6	1.55	5.05	1.24	0.030
M	FW88-29	185.4 - 198.5	13.1	4.53	18.82	5.37	0.055
O	FW88-29	416.0 - 421.6	6.6	0.75	2.23	0.86	-
P	FW88-7	242.7 - 249.3	6.6	2.08	-	-	-
Q	FW88-31	371.4 - 404.2	32.8	3.75	-	-	-
	incl.	391.1 - 400.9	9.8	6.49	1.19	-	-
R	FW88-31	456.7 - 492.8	36.1	6.00	-	-	-
	incl.	456.7 - 463.2	6.6	15.79	1.87	2.07	-
	and	479.6 - 486.2	6.6	8.81	0.66	-	-

FW88-27 ?

860201