

# Cathedral

## GOLD CORPORATION

Porcher Is.  
(Edge Pass)

### NEWS RELEASE

886104

TRADING SYMBOL: CAT-T  
FOR RELEASE : January 10, 1989  
CONTACT : Pierre B. Lebel, President (604) 684-4659  
Eric Lavarack, Director of Investor Relations (604) 684-4659

#### PORCHER ISLAND MINERALIZATION EXTENDED AT DEPTH

The key objective of Cathedral's most recently completed drilling program at Porcher Island was to test the continuity and strength of AT Zone mineralization below 400 feet and significantly expand AT Zone ore reserves which presently average 1,550 tons per vertical foot to a depth of 400 feet.

Assay results indicate that AT Zone mineralization is persistent to a depth of at least 1,800 feet. Significant intersections, better than .10 opt over 7 feet, are tabulated below:

#### AT ZONE (Deep Intersections) Not included in existing ore reserves

| <u>HOLE</u> | <u>EAST M.</u> | <u>NORTH M.</u> | <u>FROM (M)</u> | <u>TO (M)</u> | <u>FT</u> | <u>AU OZ/T</u> |
|-------------|----------------|-----------------|-----------------|---------------|-----------|----------------|
| 41          | 4726           | 19135           | 148.10          | 149.02        | 3.0       | 0.258          |
| 45          | 4772           | 19142           | 117.25          | 118.80        | 5.1       | 0.205          |
|             | 4772           | 19142           | 294.55          | 295.05        | 1.6       | 3.820          |
| 62          | 4725           | 19230           | 323.74          | 329.40        | 18.6      | 0.195          |
|             | 4725           | 19230           | 384.73          | 387.60        | 9.4       | 0.161          |
|             | 4725           | 19230           | 403.00          | 404.47        | 4.8       | 0.179          |
| 65          | 4809           | 19191           | *               |               |           |                |
| 81          | 4673           | 19206           | 548.05          | 548.75        | 2.3       | 0.302          |
| 84          | 4774           | 19236           | 307.80          | 309.00        | 3.9       | 0.668          |
|             | 4774           | 19236           | 336.00          | 336.50        | 1.6       | 0.462          |
|             | 4774           | 19236           | 349.61          | 351.90        | 7.5       | 0.098          |
|             | 4774           | 19236           | 407.80          | 408.75        | 3.1       | 1.296          |
|             | 4774           | 19236           | 414.40          | 416.00        | 5.2       | 0.649          |
|             | 4774           | 19236           | 421.75          | 424.00        | 7.4       | 0.113          |
| 87          | 4605           | 19132           | 349.18          | 354.95        | 18.9      | 0.149          |
| 88          | 4828           | 19279           | 213.50          | 214.45        | 3.1       | 0.244          |
|             | 4828           | 19279           | 345.10          | 345.86        | 2.5       | 0.282          |

#### AT ZONE (Strike Extensions and Undercuts) Not included in existing ore reserves

| <u>HOLE</u> | <u>EAST M.</u> | <u>NORTH M.</u> | <u>FROM (M)</u> | <u>TO (M)</u> | <u>FT</u> | <u>AU OZ/T</u> |
|-------------|----------------|-----------------|-----------------|---------------|-----------|----------------|
| 79          | 4900           | 19197           | *               |               |           |                |
| 80          | 4900           | 19197           | 60.45           | 61.82         | 4.5       | 0.359          |
| 82          | 4850           | 19235           | 96.08           | 98.25         | 7.1       | 0.312          |
| 83          | 4850           | 19235           | 23.70           | 26.00         | 7.5       | 0.545          |
| 85          | 4875           | 19250           | 50.90           | 52.42         | 5.0       | 0.816          |
| 86          | 4875           | 19250           | *               |               |           |                |

To date 91 holes have been drilled at the Porcher Island property which is located 35 miles southwest of Prince Rupert, B.C. At least 4 mineralized zones have been identified. Ore reserves within the AT Zone are estimated by the Company at 623,000 tons grading 0.2 opt gold (cut and diluted). These reserves are contained within a main quartz-pyrite vein striking northeast-southwest and within east-west striking offshoots.

The exploration program also included three holes drilled in the Slope Zone with the following results:


SLOPE ZONE

| <u>HOLE</u> | <u>EAST M.</u> | <u>NORTH M.</u> | <u>FROM (M)</u> | <u>TO (M)</u> | <u>FT</u> | <u>AU OZ/T</u> |
|-------------|----------------|-----------------|-----------------|---------------|-----------|----------------|
| 89          | 4455           | 18782           | 63.45           | 64.05         | 2.0       | 0.557          |
|             | 4455           | 18782           | 108.20          | 109.04        | 2.8       | 0.292          |
| 90          | 4504           | 18760           | *               |               |           |                |
| 91          | 4605           | 18810           | *               |               |           |                |

\* No significant mineralization

Surface exploration activities were also carried out. One grab sample along the northeast extension of the AT Zone assayed 12.63 opt gold. Other significant grab samples of up to 0.328 opt gold were collected 6,500 feet southeast of the AT Zone within the same intrusive body.

The Company has commissioned an independent project review which will be used in completing its 1989 program and budget for Porcher Island.

  
\_\_\_\_\_  
Pierre B. Lebel  
President

The Toronto Stock Exchange has not reviewed this News Release and does not accept responsibility for the adequacy or accuracy of its content.

# Cathedral

## GOLD CORPORATION

### NEWS RELEASE

TRADING SYMBOL: CAT-T  
 FOR RELEASE : August 9, 1988  
 CONTACT : Pierre B. Lebel, President (604) 684-4659  
           Eric Lavarack, Director of Investor Relations (604) 684-4659

#### CATHEDRAL REPORTS SIGNIFICANT GOLD INTERSECTIONS AT PORCHER ISLAND

The season's first 21 infill diamond drill holes designed to test the AT mineralized zone have been completed on the Porcher Island property located 35 miles southwest of Prince Rupert, B.C.

Drilling in 1987 and 1988 on the AT zone, which hosts the former Surf Point Gold Mine where shallow gold was produced in 1935-1937, has demonstrated the presence of up to 5 parallel vein structures. Individual veins range up to 40 feet in true thickness with grades from 0.09 oz/ton to 1.62 oz/ton across full vein width.

The AT zone and its contained vein structures have been explored over a strike of 1,000 feet. It is open to depth and along strike and the north and south extensions of both zone and veins remain to be tested. The deepest present intersection in hole 16 occurs 700 feet below surface (0.15 oz/ton gold across 25 feet).

Intersections for holes 28 to 48 drilled since are:

| <u>HOLE</u> | <u>EAST M.</u> | <u>NORTH M.</u> | <u>INCL.</u> | <u>FROM M.</u>              | <u>TO M.</u> | <u>M.</u> | <u>FT</u> | <u>OZ/T</u> |
|-------------|----------------|-----------------|--------------|-----------------------------|--------------|-----------|-----------|-------------|
| 28          | 4550           | 18939           | 45           | NO SIGNIFICANT INTERSECTION |              |           |           |             |
| 29          | 4619           | 18989           | 45           | 23.20                       | 27.00        | 3.80      | 12.5      | 0.114       |
|             |                |                 |              | 50.00                       | 56.00        | 6.00      | 19.7      | 0.258       |
|             |                |                 |              | 66.00                       | 67.70        | 1.70      | 5.6       | 0.561       |
|             |                |                 |              | 91.40                       | 93.00        | 1.60      | 5.2       | 0.473       |
| 30          | 4619           | 18989           | 70           | 39.00                       | 43.10        | 4.10      | 13.4      | 0.437       |
|             |                |                 |              | 68.00                       | 71.50        | 3.50      | 11.5      | 0.094       |
|             |                |                 |              | 167.70                      | 168.10       | 0.40      | 1.3       | 0.646       |
|             |                |                 |              | 176.90                      | 177.40       | 0.50      | 1.6       | 0.520       |
| 31          | 4619           | 18989           | 45           | 9.90                        | 13.70        | 3.80      | 12.5      | 0.169       |
| 32          | 4673           | 19012           | 45           | ABANDONED                   |              |           |           |             |
| 33          | 4673           | 19012           | 50           | 32.00                       | 42.00        | 10.00     | 32.8      | 0.101       |
|             |                |                 |              | 46.50                       | 57.00        | 10.50     | 34.4      | 0.139       |
| 34          | 4673           | 19012           | 65           | 17.00                       | 17.60        | 0.60      | 2.0       | 0.480       |
|             |                |                 |              | 66.10                       | 72.50        | 6.40      | 21.0      | 0.702       |
| 35          | 4673           | 19012           | 55           | ABANDONED                   |              |           |           |             |
| 36          | 4673           | 19012           | 65           | 25.95                       | 30.00        | 4.05      | 13.3      | 0.196       |
|             |                |                 |              | 46.40                       | 69.40        | 23.00     | 75.4      | 0.159       |
|             |                |                 |              | 102.00                      | 104.30       | 2.30      | 7.5       | 0.439       |

| <u>HOLE</u> | <u>EAST M.</u> | <u>NORTH M.</u> | <u>INCL.</u> | <u>FROM M.</u>              | <u>TO M.</u> | <u>M.</u> | <u>FT</u> | <u>OZ/T</u> |  |
|-------------|----------------|-----------------|--------------|-----------------------------|--------------|-----------|-----------|-------------|--|
| 37          | 4700           | 19069           | 45           | 35.66                       | 40.76        | 5.10      | 16.7      | 0.530       |  |
|             |                |                 |              | 97.90                       | 102.50       | 4.60      | 15.1      | 0.193       |  |
| 38          | 4700           | 19069           | 60           | 49.00                       | 52.75        | 3.75      | 12.3      | 0.234       |  |
|             |                |                 |              | 66.60                       | 68.30        | 1.70      | 5.6       | 0.232       |  |
|             |                |                 |              | 112.00                      | 112.50       | 0.50      | 1.6       | 0.470       |  |
|             |                |                 |              | 131.00                      | 136.25       | 5.25      | 17.2      | 0.909       |  |
| 39          | 4725           | 19079           | 45           | 25.30                       | 28.40        | 3.10      | 10.2      | 0.153       |  |
|             |                |                 |              | 38.00                       | 45.25        | 7.25      | 23.8      | 0.126       |  |
| 40          | 4725           | 19079           | 62           | 5.00                        | 6.00         | 1.00      | 3.3       | 0.580       |  |
|             |                |                 |              | 61.50                       | 64.75        | 3.25      | 10.7      | 0.164       |  |
| 41          | 4725           | 19135           | 45           | 14.80                       | 23.50        | 8.70      | 28.5      | 0.195       |  |
|             |                |                 |              | 32.61                       | 33.00        | 0.39      | 1.3       | 1.392       |  |
|             |                |                 |              | 36.20                       | 39.10        | 2.90      | 9.5       | 0.220       |  |
|             |                |                 |              | 59.77                       | 60.00        | 0.23      | 0.8       | 1.362       |  |
|             |                |                 |              | 76.30                       | 76.50        | 0.20      | 0.7       | 1.406       |  |
| 42          | 4725           | 19135           | 60           | 23.47                       | 30.70        | 7.23      | 23.7      | 0.406       |  |
|             |                |                 |              | 38.70                       | 41.90        | 3.20      | 10.5      | 0.140       |  |
|             |                |                 |              | 91.60                       | 93.30        | 1.70      | 5.6       | 0.344       |  |
|             |                |                 |              | 157.70                      | 158.90       | 1.20      | 3.9       | 1.122       |  |
| 43          | 4727           | 19135           | 45           | NO SIGNIFICANT INTERSECTION |              |           |           |             |  |
| 44          | 4774           | 19140           | 45           | 9.90                        | 12.40        | 2.50      | 8.2       | 0.147       |  |
|             |                |                 |              | 55.10                       | 55.40        | 0.30      | 1.0       | 1.626       |  |
|             |                |                 |              | 138.60                      | 140.80       | 2.20      | 7.2       | 0.602       |  |
| 45          | 4774           | 19140           | 60           | 9.60                        | 15.15        | 5.55      | 18.2      | 0.147       |  |
|             |                |                 |              | 17.00                       | 20.00        | 3.00      | 9.8       | 0.102       |  |
|             |                |                 |              | 23.00                       | 23.70        | 0.70      | 2.3       | 0.576       |  |
| 46          | 4833           | 19128           | 45           | 6.70                        | 8.10         | 1.40      | 4.6       | 0.497       |  |
|             |                |                 |              | 10.50                       | 12.00        | 1.50      | 4.9       | 0.348       |  |
|             |                |                 |              | 43.70                       | 45.50        | 1.80      | 5.9       | 0.121       |  |
| 47          | 4833           | 19128           | 65           | 60.40                       | 60.70        | 0.30      | 1.0       | 1.524       |  |
| 48          | 4833           | 19130           | 55           | 28.60                       | 29.20        | 0.60      | 2.0       | 0.407       |  |

30 holes totalling 14,000 feet will further explore the AT and five additional zones within 3,000 feet of the AT mineralization. With features identical to those of the AT zone, additional tonnages from these 5 zones could be incorporated in a single mining operation.

An estimate of ore reserves to a depth of 500 feet in the AT zone will be prepared after all data has been received.

*Hugh C. Morris*

---

Hugh C. Morris  
Chairman

The Toronto Stock Exchange has not reviewed this News Release and does not accept responsibility for the adequacy or accuracy of its content.

| <u>HOLE</u> | <u>EAST M.</u> | <u>NORTH M.</u> | <u>INCL.</u> | <u>FROM M.</u>              | <u>TO M.</u> | <u>M.</u> | <u>FT</u> | <u>OZ/T</u> |  |
|-------------|----------------|-----------------|--------------|-----------------------------|--------------|-----------|-----------|-------------|--|
| 37          | 4700           | 19069           | 45           | 35.66                       | 40.76        | 5.10      | 16.7      | 0.530       |  |
|             |                |                 |              | 97.90                       | 102.50       | 4.60      | 15.1      | 0.193       |  |
| 38          | 4700           | 19069           | 60           | 49.00                       | 52.75        | 3.75      | 12.3      | 0.234       |  |
|             |                |                 |              | 66.60                       | 68.30        | 1.70      | 5.6       | 0.232       |  |
|             |                |                 |              | 112.00                      | 112.50       | 0.50      | 1.6       | 0.470       |  |
|             |                |                 |              | 131.00                      | 136.25       | 5.25      | 17.2      | 0.909       |  |
| 39          | 4725           | 19079           | 45           | 25.30                       | 28.40        | 3.10      | 10.2      | 0.153       |  |
|             |                |                 |              | 38.00                       | 45.25        | 7.25      | 23.8      | 0.126       |  |
| 40          | 4725           | 19079           | 62           | 5.00                        | 6.00         | 1.00      | 3.3       | 0.580       |  |
|             |                |                 |              | 61.50                       | 64.75        | 3.25      | 10.7      | 0.164       |  |
| 41          | 4725           | 19135           | 45           | 14.80                       | 23.50        | 8.70      | 28.5      | 0.195       |  |
|             |                |                 |              | 32.61                       | 33.00        | 0.39      | 1.3       | 1.392       |  |
|             |                |                 |              | 36.20                       | 39.10        | 2.90      | 9.5       | 0.220       |  |
|             |                |                 |              | 59.77                       | 60.00        | 0.23      | 0.8       | 1.362       |  |
|             |                |                 |              | 76.30                       | 76.50        | 0.20      | 0.7       | 1.406       |  |
| 42          | 4725           | 19135           | 60           | 23.47                       | 30.70        | 7.23      | 23.7      | 0.406       |  |
|             |                |                 |              | 38.70                       | 41.90        | 3.20      | 10.5      | 0.140       |  |
|             |                |                 |              | 91.60                       | 93.30        | 1.70      | 5.6       | 0.344       |  |
|             |                |                 |              | 157.70                      | 158.90       | 1.20      | 3.9       | 1.122       |  |
| 43          | 4727           | 19135           | 45           | NO SIGNIFICANT INTERSECTION |              |           |           |             |  |
| 44          | 4774           | 19140           | 45           | 9.90                        | 12.40        | 2.50      | 8.2       | 0.147       |  |
|             |                |                 |              | 55.10                       | 55.40        | 0.30      | 1.0       | 1.626       |  |
|             |                |                 |              | 138.60                      | 140.80       | 2.20      | 7.2       | 0.602       |  |
| 45          | 4774           | 19140           | 60           | 9.60                        | 15.15        | 5.55      | 18.2      | 0.147       |  |
|             |                |                 |              | 17.00                       | 20.00        | 3.00      | 9.8       | 0.102       |  |
|             |                |                 |              | 23.00                       | 23.70        | 0.70      | 2.3       | 0.576       |  |
| 46          | 4833           | 19128           | 45           | 6.70                        | 8.10         | 1.40      | 4.6       | 0.497       |  |
|             |                |                 |              | 10.50                       | 12.00        | 1.50      | 4.9       | 0.348       |  |
|             |                |                 |              | 43.70                       | 45.50        | 1.80      | 5.9       | 0.121       |  |
| 47          | 4833           | 19128           | 65           | 60.40                       | 60.70        | 0.30      | 1.0       | 1.524       |  |
| 48          | 4833           | 19130           | 55           | 28.60                       | 29.20        | 0.60      | 2.0       | 0.407       |  |

30 holes totalling 14,000 feet will further explore the AT and five additional zones within 3,000 feet of the AT mineralization. With features identical to those of the AT zone, additional tonnages from these 5 zones could be incorporated in a single mining operation.

An estimate of ore reserves to a depth of 500 feet in the AT zone will be prepared after all data has been received.

*Hugh C. Morris*

---

Hugh C. Morris  
Chairman

The Toronto Stock Exchange has not reviewed this News Release and does not accept responsibility for the adequacy or accuracy of its content.

# Cathedral

## GOLD CORPORATION

File  
→ Edge Pass

|                                |
|--------------------------------|
| LOG NO: <i>Jan 19/88 VAN 4</i> |
| ACTION: <i>[Signature]</i>     |
| FILE NO: <i>Edge Pass</i>      |

### NEWS RELEASE

TRADING SYMBOL: CAT-T  
 FOR RELEASE: January 7, 1988  
 CONTACT: Pierre Lebel, President (604) 684-4659

Cathedral Gold Corporation (CAT-T) has completed Phase I of its 1987 exploration program on its 100% owned Porcher Island gold property located 35 miles southwest of Prince Rupert, British Columbia.

Preliminary assay results from the 10 holes drilled in Phase I were :

| <u>Hole #</u> | <u>From</u> | <u>To</u> | <u>Ft</u> | <u>Au oz/t</u> |
|---------------|-------------|-----------|-----------|----------------|
| 1             | 49.0        | 53.0      | 4.0       | 0.105          |
|               | 176.0       | 182.0     | 6.0       | 0.418          |
| 2             | 173.0       | 177.0     | 4.0       | 0.158          |
|               | 217.0       | 224.0     | 7.0       | 0.052          |
|               | 343.0       | 352.1     | 9.1       | 0.084          |
|               | 186.0       | 195.0     | 9.0       | 0.058          |
| 3             | 228.0       | 261.6     | 33.6      | 0.287          |
|               | 172.8       | 188.0     | 15.2      | 0.076          |
| 4             | 219.0       | 296.0     | 77.0      | 0.205          |
|               | 68.3        | 75.0      | 6.7       | 0.233          |
| 5             | 86.0        | 98.2      | 12.2      | 0.139          |
|               | 97.0        | 99.0      | 2.0       | 0.131          |
| 6             | 116.4       | 131.0     | 14.6      | 0.089          |
|               | 150.0       | 157.0     | 7.0       | 0.258          |
| 7             | 177.5       | 180.0     | 2.5       | 0.115          |
|               | 319.0       | 328.4     | 9.4       | 0.110          |
|               | 373.0       | 381.0     | 8.0       | 0.353          |
|               | 235.0       | 268.3     | 33.3      | 0.119          |
|               | 311.0       | 313.0     | 2.0       | 0.172          |
|               | 528.8       | 529.3     | 0.5       | 0.621          |
|               | 589.0       | 589.5     | 0.5       | 0.680          |
|               | 708.0       | 713.0     | 5.0       | 0.099          |
|               | 725.5       | 727.0     | 1.5       | 1.453          |
|               | 728.0       | 737.0     | 9.0       | 0.194          |
| 8             | 763.0       | 766.0     | 3.0       | 0.299          |
|               | 351.0       | 357.3     | 6.3       | 0.186          |
| 9             | 38.0        | 53.0      | 15.0      | 0.105          |
|               | 100.0       | 132.0     | 32.0      | 0.210          |
|               | 161.0       | 176.0     | 15.0      | 0.099          |

These results confirm and extend the known quartz vein system on the property which remains open at depth below 500 ft. and on strike. Equally encouraging, the long intersections in Holes #3, #4, #8 and #10 support the concept of a large tonnage ore body grading in the order of 0.15 oz of gold per ton. This feature, if supported by additional drill results, could dramatically alter the scope of exploration and development activity at Porcher Island.

Phase II drilling, scheduled to commence on January 12, 1988, will further test the continuity and strength of the existing vein system as well as the property's bulk tonnage potential.

Cathedral recently added to its land holdings at Porcher Island increasing the total size of this property, which enjoys a tidewater location, to over 1,900 acres.

73,000 tons of Porcher Island ore was mined prior to 1937 in a conventional quartz vein setting. Mill recoveries were 95% and the recovered ore grade averaged 0.29 oz per ton gold.

Reserves at Porcher Island presently stand at 250,000 tons grading 0.26 oz of gold per ton.



---

Pierre B. Lebel  
President

PBL/il  
Cat#1