1710 - 609 GRANVILLE ST PO BOX 10363 VANCOUVER BC CANADA V7Y 1G5 (604) 683-7265 FAX 683-5306 BBS 683-7206

### George Cross News Letter

#### "Reliable Reporting"

WESTERN CANADIAN INVESTMENTS

COPYRIGHT
ALL REPRODUCTION
RIGHT RESERVED
PUBLISHED DAILY
SUBSCRIPTION RATE
\$350.00 + G.S.T.
PER YEAR

NO. 182 (2000) SEPTEMBER 22, 2000

NO. 182 (2000) SEPTEMBER 22, 2000

### REDHAWK RESOURCES INC. [RDK-CDNX] 6,503,155 SHS.

REMAC DRILLING RESULTS RECEIVED - Kristian Ross, president, Redhawk reports drill

hole assay results from zones B and C at its Remac zinc oxide project. The project is located 35 km southeast of the Cominco zinclead smelter complex at Trail in southeastern BC and 16 km northwest of the Pend D'Oreille zinc mine where Cominco recently announced a production decision. (SEE MAP OVERLEAF P.1)

Highlights from this first set of drill assays include hole R-2000-02 in zone B which ran 15.43% zinc and 1.55% lead over an estimated true width of 5.3 metres (17.3 ft) and hole R-2000-09 in zone C which ran 8.68% zinc and 4.27% lead an estimated true width of 12.2 metres (40.0 ft). Zone B was tested with four reverse circulation (RC) drill holes. (SEE ZONE B ASSAYS OVERLEAF P.2)

Zone B remains open to the west and to depth. Earlier surface trench results at Zone B included 12.8 metres (41.8 ft) grading 15% zinc (Trench B-2000-01). Trench zinc values are revised upward from the news release published in GCNL NO.147, 1Aug2000, P.4 based on receipt of final zinc assays.

Zone C. located 150 metres northeast of Zone B, was tested with three RC drill holes. (SEE ZONE C ASSAYS OVERLEAF P.2) Zone C remains open to the east of drill hole R-2000-09 and to depth. Earlier trench results at Zone C included 21.0 metres (69 ft) grading 6.93% zinc (Trench C-2000-01) and 18.1 metres (59.5 ft) grading 9.14% zinc (Trench C-2000-02). Trench zinc values are also revised upward from the news release published in GCNL NO.147, 1Aug2000, P.4 based on receipt of final zinc assays.

The \$400,000 year 2000 field program of trenching and RC drilling is now complete. Drill sample assays from zones F, G and H are still outstanding and expected in three to four weeks. The program was successful in locating and in testing for structural continuity and zinc grades in the oxidized portions of zones B,C,F,G and H.

Mineralization of the Remac property consists of a series of carbonate-hosted base metal deposits known to extend over a distance of three km on a southwesterly trend. The present program is targeting the oxidized upper portions of these deposits. Based on underground mining and drilling records, oxidation of these deposits ranges to depths of 450 metres.

Drill hole samples reported in this news release were collected under the supervision of George Gorzynski, P.Eng., and Gerald Klein, P.Eng. Assays results were compiled by Mr. Gorzynski. Both Mr. Gorzynski and Mr. Klein are designated as Qualified Persons who are acting as consulting geologists to Redhawk on the Remac project. All samples were sent to the Cominco Research Lab Vancouver, BC. Duplicate pulps of every 20th sample are sent to ALS Chemex Labs, North Vancouver, BC for confirmation assays.

Redhawk is the operator of the Remac project which is being funded by ZincOx Resources BV. The agreement calls for ZincOx to earn a 50% interest in the property by spending \$3,000,000 on exploration over a four years. ZincOx, based in London, England, is a world leader in the benification of zinc metal from oxide sources. (SEE GCNL NO.147, 1Aug2000, P.4 FOR PREVIOUS REMAC PROJECT INFORMATION)

82FW219 p. 10f3

# NO. 182 (2000) SEPTEMBER 22, 2000

## REDHAWK RESOURCES, INC. ZINCOX RESOURCES BV

### REMAC ZINC PROJECT SOUTHEASTERN BRITISH COLUMBIA

	DRILL	FROM	TO	SAMPLE	ESTIMATED	ESTIMATED	AVER!	GE GRA	DES
1	HOLE	(meters)	(meters)	LENGTH	TRUE WIDTH	TRUE WIDTH	Zn	Pb ·	Ag
	No.			(meters)	(meters)	(feet)	%	%	g/t

ZONE B DF	RILL RE	SULTS		Drill holes listed from east to west over 145m (475 ft.) strike length.						
R-2000-03	14.7	20.8	6.1	5.3	17.3	9.38	1.64	11.5		
R-2000-02	17.8	23.9	6.1	5.3	17.3	15.43	1.55	22.5		
R-2000-04	11.2	14.2	3.0	2.6	8.7	10.86	3.15	14.4		
R-2000-05	R-2000-05 Drill hole passed over the top of Zone B in overburden.									

DRILL	FROM	TO	SAMPLE	ESTIMATED	ESTIMATED	AVERAGE GRADES		RADES
HOLE	(meters)	(meters)	LENGTH	TRUE WIDTH	TRUE WIDTH	Zn	Pb	Ag
No.			(meters)	(meters)	(feet)	%	%	g/t

ZONE C DR	RILLRE	SULTS		Drill holes listed from east to west over 75m (245 ft) strike length					
R-2000-09	6.6	7.6	1.0	0.5	1.7	9.80	0.41	4.8	
	18.8 Including	43.2 2:	24.4	12.2	40.0	8.68	4.27	10.9	
·	18.8	30.0 43.2	11.2 13.2	5.6 6.6	18.3 21.7	5.52 11.36	5.53 3.21	8.0 13.3	
R-2000-08	8.3	18.5	10.2	5.1	16.7	7.62	0.85	27.1	
R-2000-01	3.0	4.0	1.0	0.9	2.9	7.99	0.25	2.7	
	29.5	32.5	3.0	2.7	8.7	5.62	0.02	3.7	

82FSW Z19 p. 20f3

NO. 182 (2000) SEPTEMBER 22, 2000

## REDHAWK RESOURCES, INC. ZINCOX RESOURCES BV

REMAC ZINC PROJECT SOUTHEASTERN BRITISH COLUMBIA

