

## EASTFIELD RESOURCES LTD.(ETF-V)

**DRILL TEST OF SILVER-GOLD - Glen L. Garratt, vice  
CLAIMS IN B.C. STARTS SOON president of Eastfield**

Resources Ltd., reports that the Phase I Program on their Indata project 120 km NW of Fort St. James, B.C., is progressing well with over 10 km of geochemical soil sampling and induced polarization surveying completed to date. A previously discovered and exceptionally high geochemical anomaly in soils, (up to 18.8 oz.silver/t and 0.067 oz.gold/t) has been hand trenched. This exposed a quartz vein-massive sulphide and oxide zone. This is the first bedrock discovery of the zone. The trenching was unable to uncover the full dimension of the zone but preliminary calculations indicate a minimum thickness of ten feet. A series of quartz-sulphide veins are present divided by strongly gossanous iron-oxide material. The trenches lie within a geochemical anomaly 600m long. Results of geochemical sampling along strike and assays of vein material are awaited.

The I.P. survey outlined a strong chargeability anomaly coincident with the geochemical anomaly. The I.P. anomaly extends for 600 meters and is open to the north. The discovery trenches lie within the I.P. anomaly and together with the geochemical data are an excellent drill target for a diamond drill test expected to start on Oct.15/87.

Also in B.C., Eastfield holds the Beekeeper property about 35 miles ENE of Williams Lake in the Horsefly region of the Quesnel Trough which has a significant alteration zone indicated with coincident geophysical and geochemical anomalies. The area is undergoing exploration by many companies with the most significant discovery to date being Dome Mines' QR deposit about 28 miles to the north.

# DELAWARE RESOURCES CORP.

| <u>SNIP STRUCTURAL ZONE</u>   |                     |                     |   |
|---|---------------------|---------------------|---|
| HOLE  | INTERVAL<br>feet    | CORE LENGTH<br>feet | GOLD in oz/ton<br>(uncut grade)                   |
| S-33  | 175.2 - 183.4       | 8.2                 | 0.127   |
|   | 194.2 - 199.1       | 4.9                 | 0.218   |
|   | 360.9 - 363.2       | 2.3                 | 0.269   |
| S-37  | 344.5 - 355.0       | 10.5                | 1.490<br>previously reported,<br>partial analysis |
| S-47  | 199.8 - 206.4       | 6.6                 | 2.610   |
|   | 245.7 - 253.9       | 8.2                 | 0.141   |
|   | 317.9 - 327.7       | 9.8                 | 0.112   |
|   | 455.7 - 465.5       | 9.8                 | 0.116   |
|   | 480.3 - 485.2       | 4.9                 | 0.093   |
| S-50  | 59.4 - 67.6         | 8.2                 | 0.388   |
|   | 92.2 - 102.0        | 9.8                 | 0.250   |
|   | 132.2 - 135.5       | 3.3                 | 0.129   |
|   | 269.7 - 279.5       | 9.8                 | fire assays pending                               |
|   | 318.9 - 328.7       | 9.8                 | fire assays pending                               |
| S-51  | 352.3 - 356.9       | 4.6                 | 4.430   |
|   | 440.3 - 463.3       | 23.0                | 0.093   |
|   | 549.9 - 559.7       | 9.8                 | 0.246   |
| S-52  | 153.5 - 166.0       | 12.5                | 0.234   |
|   | 208.7 - 218.5       | 9.8                 | 0.143   |
|   | 345.8 - 360.2       | 14.4                | 0.416   |
|   | 399.6 - 409.4       | 9.8                 | 0.116   |
| S-53  | 503.6 - 505.2       | 1.6                 | 1.120   |
|   | 616.4 - 621.3       | 4.9                 | 0.290   |
|   | 697.2 - 709.0       | 11.8                | 0.569   |
| S-54  | 290.4 - 298.9       | 8.5                 | 3.710   |
|   | 318.9 - 335.6       | 16.7                | incomplete fire<br>assays                         |
| including   | 334.0 - 335.6       | 1.6                 | 1.840   |
|   | 553.5 - 554.5       | 1.0                 | 9.320   |
|   | 687.0 - 689.0       | 2.0                 | 24.420  |
| S-55  | 302.8 - 309.4       | 6.6                 | 0.774   |
|   | 369.4 - 374.0       | 4.6                 | 1.310   |
|   | 394.4 - 407.5       | 13.1                | fire assays pending                               |
|   | 728.7 - 738.5       | 9.8                 | fire assays pending                               |
|   | 905.5 - 908.8       | 3.0                 | 1.98  |
| S-56, 57,<br>58, 59   | Fire assays pending |                     |   |
| S-60  | 77.4 - 100.4        | 23.0                | fire assays pending                               |
|   | 540.4 - 546.0       | 5.6                 | 5.237   |
| Intersections of interest from the reconnaissance drilling include: |                     |                     |   |
| S-22  | 296.9 - 306.7       | 9.8                 | 0.199   |
|   | 446.8 - 449.1       | 2.3                 | 0.326   |
|   | 510.8 - 520.6       | 9.8                 | 0.120   |
| S-26  | 86.3 - 91.5         | 5.2                 | 0.272   |
| S-27  | 259.2 - 262.2       | 3.0                 | 0.150   |
|   | 289.7 - 290.7       | 1.0                 | 0.549   |
|   | 472.4 - 472.7       | 0.3                 | 1.290   |
| S-29  | 61.4 - 63.0         | 1.6                 | 0.123   |
|   | 318.6 - 319.9       | 1.3                 | 0.096   |
|   | 329.4 - 336.6       | 7.2                 | 0.301   |
|   | 504.3 - 510.2       | 5.9                 | 0.179   |
| S-43  | 121.7 - 125.3       | 3.6                 | 0.452   |
|   | 515.1 - 519.1       | 3.0                 | 0.150   |
| S-38  | 637.1 - 640.4       | 3.3                 | 0.260   |
|   | 382.5 - 392.3       | 9.8                 | 0.263   |