

NO. 213(1990)
NOVEMBER 2, 1990

George Cross

Reliable K

EURUS RESOURCE CORP. (ERR-V)

THIOS RESOURCES INC. (THI-V)

HOLE NO.	INTERVAL METERS	LENGTH FEET	GOLD OZ/T	SILVER OZ/TON	LEAD %	ZINC %	COPPER %
RR90-1	11.20-20.85	31.7	0.080	25.7	2.07	5.35	0.58
Incl.	14.40-17.15	9.0	.121	40.2	2.77	7.21	1.00
	58.75-59.45	2.3	.057	11.4	1.17	4.37	.69
RR90-2	18.40-28.80	34.1	.048	14.3	1.28	4.27	.49
Incl.	22.82-24.50	5.5	.116	27.5	2.83	8.81	.60
	54.75-55.60	2.8	.030	6.17	.52	2.81	.96
RR90-3	18.00-20.20	7.2	.031	1.60	.66	2.95	.05
	29.50-30.50	3.3	.011	3.61	.38	1.94	.23
RR90-4	19.34-20.34	3.3	.113	6.78	.75	2.14	.26
	23.88-25.00	3.7	.031	2.09	.10	.72	.38
	28.18-30.76	8.5	.062	7.84	.61	2.79	.76
RR90-5	19.83-21.82	6.5	.038	2.39	.22	.78	.12
	28.39-34.00	18.4	.055	10.8	.90	3.26	.66
RR90-6	8.26- 9.08	2.7	.046	6.28	.46	.83	.17
	42.47-47.63	16.9	.070	7.05	.48	3.25	1.07
	52.58-57.00	14.5	.039	7.58	.66	3.18	.96
RR90-7	7.33- 9.00	5.5	.007	2.66	.31	1.16	.24
	13.47-19.00	18.1	.005	.54	.05	1.31	.39
RR90-8	12.30-16.90	15.1	.006	.70	.03	2.79	.72
RR90-9	11.24-12.07	2.7	.013	1.09	.20	1.08	.21
	17.00-22.00	16.4	.013	.60	.03	1.01	.32

104B Central

ROCK & ROLL ASSAYS - William Campbell, secretary,
reports Eurus Resource and Thios Resources have received assays from a recently completed 2,215-foot, nine-hole drilling program on the Rock & Roll project, 6 mi. NW of the SNIP deposit in the Iskut River area, NW B.C. Eurus and Thios are equal joint venture partners which can earn a 100% interest, subject to a 1% net smelter return royalty, from PRIME RESOURCES GROUP INC. (PRU-V) by paying \$500,000 and spending \$1,000,000 by 13Mar94. The nine holes tested sulphide mineralization hosted in the Black Dog zone. Holes RR90-1, 2 and 3 were drilled from the same site at -45, -60 and -75 degrees respectively. Holes RR90-4, 5 and 6 were drilled from a common setup which was located about 150 feet to the east. These holes were inclined at -45, -60 and -90 degrees. Holes RR90-7, 8 and 9 were drilled at similar respective dips from a site about 100 feet west of the first drill setup. All inclined holes were drilled at an Azimuth of 047 degrees. (SEE GCNL No.197, OCT.11/90, P.1 FOR PREVIOUS INFORMATION)