

JOPEC RESOURCES LTD. (JPR-V)						
SAMPLE NO.	THICKNESS FEET	LEAD %	ZINC %	CADMIUM %	SILVER OZ/TON	GOLD OZ/T
<u>Underground Samples, High Grade Zone</u>						
203001	4 ft.	4.95	10.76	0.063	2.67	0.006
203003	3	3.02	8.69	.052	1.74	.010
203004	4	7.30	19.02	.121	3.50	.004
<u>Underground Samples, Milling Ore Zone</u>						
203002(H.W.)	2	5.49	8.42	.051	3.27	.007
203007(H.W.)	5	1.29	5.62	.032	1.49	.012
<u>Trench Samples</u>						
203005	5	.80	15.26	.124	.23	.002
203006	5	6.49	33.50	.235	4.89	.002

H.W. = Hanging Wall

-----  
PEND D'OREILLE DRILL RESULTS - P.Santos, president, Jopec Resources has reported

the third batch of roto-hammer drill samples from the raise in the 3rd level and the surface trenches at the Big John mine has been assayed with results above. The company can earn a 100% interest in the property which is 17 km SW of Salmo, B.C. Excluding the hanging wall samples, the above samples have a weighted average grade of 4.49% lead, 18.52% zinc, 0.128% cadmium, 2.62 oz. silver/t and 0.004 oz. gold/t. Using Cominco's price quotations the high grade zone has a gross value of \$303.17 per ton. Roto-hammer drilling results have consistently given an average gross value of \$300 per ton. Detailed mapping shows the high grade zone is at least 12 feet thick.

Assays from the wall rocks show milling grade material, with an average grade of 1.77% lead, 6.24% zinc, 0.037% cadmium, 2.00 oz. silver/t and 0.010 oz. gold/t with a gross value of \$115.32-per ton.

Thirty km of line cutting has been completed in preparation for a geochemical survey to delineate further the geochemical anomalies associated with the mineralized zone. The catchment area underground to store water needed for the proposed underground diamond drilling is now full. (SEE GCNL No.68, 6Apr92, P.1 FOR PREVIOUS ASSAYS)

82FSW 139