

NO. 226 (1992)
NOVEMBER 24, 1992

George Cross News Letter
"Reliable Reporting"

JOPEC RESOURCES LTD. (JPR-V)

MORE PEND D'OREILLE ASSAYS - P.J. Santos, president,
reports Jopec Resources

Ltd. has completed the first phase of diamond drilling
at the Big John mine, part of the 100%-owned Pend
D'Oreille project located 17 km southwest of Salmo, B.C.

The program comprised underground diamond drilling to
determine geological structures controlling the nature
of the massive sulphide mineralization. SEE TABLE OF
ASSAYS OVERLEAF PAGE 4.

Holes 3 and 11 were drilled to intersect the miner-
alized zone. Detailed geochemical soil sampling is
being completed before the season ends in a few days.
(SEE GCNL No.203, Oct.21/92, P.2 FOR PREVIOUS DETAILS)

82FSW 139

p. 1 of 2

JOPEC RESOURCES LTD.

DDH NO.	Interval (feet)	Lead (%)	Zinc (%)	Iron (%)	Cadmium (%)	Silver (oz/ton)	Gold (oz/ton)
3	0 - 5	3.5	4.07	15.25	.022	2.06	.007
	5 - 10	6.38	6.83	12.05	.034	2.60	.002
	10 - 13	5.96	9.45	11.19	.050	2.75	.003
	13 - 18	.24	.17	1.16	.001	.14	.001
	18 - 20	6.48	4.18	3.65	.022	2.57	.001
11	85 - 87	13.07	24.31	7.65	.167	5.27	.007
	87 - 89	6.10	15.40	9.79	.106	2.62	.008
	89 - 92	3.65	5.01	8.23	.037	1.74	.005
	92 - 95	.82	.90	3.73	.007	.38	.002
	95 - 98	18.02	18.62	12.64	.144	7.26	.026

Several holes were drilled to explore the hanging wall side of the ore zone. The assays are as follows:

DDH NO.	Interval (feet)	Lead (%)	Zinc (%)	Iron (%)	Cadmium (%)	Silver (oz/ton)	Gold (oz/ton)
1	0 - 4	8.5	22.75	10.98	.131	5.09	.007
	4 - 8	1.5	.63	17.33	.003	.71	.002
	8 - 12	1.42	3.72	30.28	.019	.58	.003
8	0 - 6	2.89	6.72	19.82	.034	1.02	.001
	6 - 8	.03	.07	1.23	.001	.01	.001
	8 - 10	6.96	2.61	4.89	.014	2.15	.001
9	0 - 2	3.64	5.13	10.77	.034	1.86	.074

Several holes were drilled to explore the footwall side of the ore zone. The assays are as follows:

DDH NO.	Interval (feet)	Lead (%)	Zinc (%)	Iron (%)	Cadmium (%)	Silver (oz/ton)	Gold (oz/ton)
10	0 - 3	2.75	3.29	26.71	.023	.97	.010

All the holes drilled to explore the footwall side of the ore zone intersected the fault which borders the footwall of the ore zone. Beyond this fault, it is poorly mineralized.

Black Warrior

Further sampling was conducted on the Black Warrior vein system, one of several types of massive sulfide mineralization in the property. The assays of a sample taken from one of the horizontal veins are as follows:

Sample No	Copper (%)	Lead (%)	Zinc (%)	Cadmium (%)	Silver (oz/ton)	Gold (oz/ton)
203520	.290	85.31	.96	.029	114.05	.020

In a previous News Release (NR-92-13), three samples taken from the vertical vein had average assays as follows:

Sample Width (feet)	Copper (%)	Lead (%)	Zinc (%)	Cadmium (%)	Silver (oz/ton)	Gold (oz/ton)
3.00	14.97	26.82	1.36	.015	50.41	.237

82FSW 139 p. 2 of 2

George Cross Mining Letter
-Reliable Reporting-

NO. 226 (1992)
NOVEMBER 24, 1992