

1710 - 609 OKANVILLE ST
PO BOX 10363
VANCOUVER BC
CANADA V7Y 1G5
(604) 683 7265 FAX 683 5306

George Cross News Letter

"Reliable Reporting"
WESTERN CANADIAN INVESTMENTS

MINISTRY OF ENERGY, MINING
AND PETROLEUM RESOURCES

COPYRIGHT
ALL REPRODUCTION
RIGHT RESERVED
PUBLISHED DAILY
SUBSCRIPTION RATE
\$315.00 PER YEAR

NO. 77 (1993)
APRIL 22, 1993

APR 26 1993

LIBRARY

NO. 77(1993)
APRIL 22, 1993

DENTONIA RESOURCES LTD. [DTA-V]

CONDUCTORS & ANOMALIES DISCOVERED - Adolf Petancic,
director, reports

Dentonia Resources Ltd. has received the results of a helicopter-mounted magnetic/electromagnetic survey conducted by Geonex Aerodat over its 100%-owned Besshi property located about five km northeast of Aiken Lake on the Omineca Development Road north of Mackenzie, in north central B.C. The survey covered a belt of back-arc volcanic and sedimentary rocks of Upper Triassic age with showings of copper, gold and pyrrhotite-rich massive sulphides centred on Polaris Creek. The area was prospected by Cominco in the 1930's, and since World War II, areas of the property have been soil sampled in a search for porphyry copper and mother lode-type gold deposits. Recently completed metallogenic studies have led to a re-interpretation of the geology and confirmed a Besshi-type environment with the possibility to host massive sulphide deposits similar to Windy Craggy, Granduc and Greens Creek. In the recent geophysical survey, a total of 125 line-km were flown, a satellite-based global positioning device was used for accurate location of the anomalies.

Numerous electromagnetic conductors and magnetic anomalies were detected, with three being of particular interest. They are several hundred meters long with two coincident to geochemical soil anomalies containing zinc, copper and molybdenum.

The associated soil geochemical results suggest that base and precious metals are present with the geophysical anomalies and their strength and characteristics suggesting steeply-dipping horizons with widths of 5 meters to 10 meters. The areas to be tested are covered with overburden. Three to six drill holes are required to provide an initial test, which are scheduled for August/September. (SEE GCNL NO.74, 19Apr93, P.1 FOR OTHER PROJECT INFORMATION)

94C 13