

New Canamin
RESOURCES LTD

Hole #	Interval (ft)	Intercept (ft)	Cu %	Section	
94-223	32 - 130	98	0.375%	-	
	130 - 200	70	0.146%	-	
	200 - 260	60	0.304%	-	
	260 - 300	40	0.162%	-	
94-224	42 - 345	303	0.141%	-	
94-225	45 - 120	75	0.187%	-	-43°, 0° AZIMUTH
	120 - 250	130	0.359%	-	
	250 - 340	90	0.162%	-	

EAST ZONE

Hole #	Interval (ft)	Intercept (ft)	Cu %	Section	
94-192 *	60 - 330	270	0.374%	2066	-42.5°, 0° AZIMUTH
94-193	140 - 750	610	0.585%	2066	-65°, 205° AZIMUTH
	750 - 990	240	0.377%		
94-194 *	135 - 450	315	0.147%	2000	-45°, 070° AZIMUTH
94-195	40 - 310	270	0.082%	2000	-65°, 205° AZIMUTH
	310 - 710	400	0.528%		
	710 - 950	240	0.407%		
	950 - 1030	80	0.254%		
94-205	70 - 350	280	0.286%	2300	-60°, 205° AZIMUTH
	350 - 465	115	0.399%		
	465 - 796	331	0.625%		

* CORE ORIENTATION DRILL HOLE

93E 37 p. 30 of 3

