

1710 - 609 GRANVILLE ST
PO BOX 10363
VANCOUVER BC
CANADA V7Y 1G5
(604) 683-7265 FAX 683-5306

George Cross News Letter

"Reliable Reporting"

COPYRIGHT
ALL REPRODUCTION
RIGHT RESERVED
PUBLISHED DAILY
SUBSCRIPTION RATE
\$315.00 PER YEAR

WESTERN CANADIAN INVESTMENTS

RECEIVED
MAR 15 1994

NO. 50 (1994)
MARCH 14, 1994

E. M. P. R.

NO. 50 (1994)
MARCH 14, 1994

NEW CANAMIN RESOURCES LTD.

[NNI-V] 8,567,958 shs.

HOLE NO.	ANGLE DEGREES	INTERVAL FEET	LENGTH FEET	COPPER %
94-111	-90	42-180	138	0.456
		180-280	100	.314
		280-500	220	.487
94-112	-45N	60-170	110	.476
		170-334	164	.177
94-113	-45 290AZ	46-170	124	.653
		170-300	130	.397
		300-400	100	.195
94-114	-90	40-130	90	.370
		130-410	280	.217
		410-452	42	.440

Alan C. Savage, president New Canamin has reported copper assays from holes 94-111 and 112, in Phase I of the south-west Main Zone drilling, were completed from the same setup 100 ft. east of previously reported holes 94-108 and 109 on the 100% owned Huckleberry project located 70 miles east of Kamano, B.C.

Drill holes 94-112 (above) and 94-113 (below) extend the known better grade near surface mineralization 125 ft. to the granodiorite contact in the south-west corner of the deposit while 94-114 provided 90 ft. of the above cut-off grade mineralization, similarly near surface at the south-east corner of the deposit. Both of these "edge" holes contributed to increased tonnage and reduced strip ratio.

Kennecott Canada retains a back-in option for a 60% interest at feasibility (See GCNL No.49, P.1, March 11, 1994)

93E 37