

1710 - 609 GRANVILLE ST  
 PO BOX 10363  
 VANCOUVER BC  
 CANADA V7Y 1G5  
 (604) 683-7265 FAX 683-5306  
 BBS 683-7206

# George Cross News Letter

"Reliable Reporting"

WESTERN CANADIAN INVESTMENTS

COPYRIGHT  
 ALL REPRODUCTION  
 RIGHT RESERVED  
 PUBLISHED DAILY  
 SUBSCRIPTION RATE  
 \$315.00 PER YEAR

RECEIVED

NOV 18 1994

NO. 218 (1994)  
 NOVEMBER 15, 1994

NO. 218 (1994)  
 NOVEMBER 15, 1994

F M P R

## LYSANDER GOLD CORPORATION

[LYS-V] 6,809,509 SHS.

LORRAINE ASSAYS RECEIVED - D.K. Mustard, director, reports Lysander Gold Corp. has received assay results from two holes in the Upper Main Zone (L-94-9, L-94-10) and three holes from the Bishop Zone (L-94-5, L-94-6, L-94-7) of the Lorraine property near Germanson Landing, north-central B.C. Lysander holds an option to earn a 100% interest from Kennecott.

Upper Main Zone - Three holes were drilled from one station to prove the feasibility of drilling the steep face of Lorraine Mountain, to confirm the high copper values reported from small diameter diamond drill holes in 1970 and 1973, and to test the associated gold potential. Hole L-94-8 was previously reported as 302.0 feet containing 1.48% copper and 0.019 oz.gold/ton.

Significant assays for the remaining holes are:

HOLE NO.	AZ	DIP	INTERVAL FEET	LENGTH FEET	COPPER %	GOLD OZ/T
L-94-9	045	-45	5-242.0	237.0	0.90	0.017*
L-94-10	045	-38	5-208.5	203.5	0.81	0.01

(\*A sample from 153.5 to 163.5 (10 feet) gave 0.77 oz.gold/ton. A 506-gram sample from rejects was run for metallics, and returned assays of -100 mesh at 0.058 oz.gold/ton, +100 mesh 0.621 oz.gold/ton for an average of 0.081 oz.gold/ton. This latter number was used in calculation. However, the indications that particulate gold is present will require additional check assays, above and below the screens.)

Some 300 feet east of these holes and about 300 feet higher in elevation Granby drilled four small diameter holes from one station at the ridge-top in 1970. Results reported were 70-2, 1.06% copper over 190 feet; 70-3, 0.84% copper over 210 feet; 70-4, 0.70% copper over 180 feet and 70-5, 0.65% copper over 200 feet. All distances are from the collar. Gold was not reported.

There are no intervening drill holes, thus there is a significant area to be tested by a major drill program in 1995. It is believed this exploration is permissive with careful drill site preparation.

Bishop Zone - Hole L-94-5 was drilled 300 feet south of L-94-1 and holes L-94-6 and 7 an additional 300 feet to the south. All three holes caught the eastern margin of the Bishop Zone. Significant results are as follows:

HOLE NO.	AZ	DIP	INTERVAL FEET	LENGTH FEET	COPPER %	GOLD OZ/T
L-94-5	--	-90	37.4-139.1	101.7	0.49	TR
			253.9-337.0	83.1	0.47	TR
L-94-6	--	-90	318.1-367.3	49.2	1.09	TR
L-94-7	137	-45	35.4-104.3	68.9	0.77	TR

During 1995 additional drilling will confirm the geometry of the Bishop Zone and extensive exploration is required for the continuation into the adjacent Boot-Steel option where a number of drill targets were identified by BP Minerals in 1991 but were not tested in 1992 since BP left the minerals business. Lysander management is encouraged by initial drill results from the Lorraine option. (SEE GCNL NO.202, Oct.21/94, P.1 FOR PREVIOUS DRILL RESULTS)

93N 2