

1710 - 609 GRANVILLE ST
 PO BOX 10363
 VANCOUVER BC
 CANADA V7Y 1G5
 (604) 683-7265 FAX 683-5306
 BBS 683-7206

George Cross News Letter

"Reliable Reporting"

WESTERN CANADIAN INVESTMENTS

COPYRIGHT
 ALL REPRODUCTION
 RIGHT RESERVED
 PUBLISHED DAILY
 SUBSCRIPTION RATE
 \$350.00 PER YEAR

NO. 151 (1995)
 AUGUST 8, 1995

NO. 151 (1995)
 AUGUST 8, 1995

INTERNATIONAL WAYSIDE GOLD MINES LTD.

[IWA-V] 3,116,063 SHS.

MOSQUITO CONSOLIDATED GOLD MINES LTD.

[MSQ-V] 8,129,635 SHS.

CARIBOO GOLD QUARTZ - J.Frank Callaghan, president. International Wayside Gold Mines Ltd. and 50/50 joint venture partner Mosquito Consolidated Gold Mines Ltd. report Dr. Richard Hall, P.Eng., has provided sludge sample assays for holes 1 through 4 from underground drilling at the Cariboo Gold Quartz Mine near Wells, B.C. The drill core for hole 1 is being re-assayed for metallics as visible gold was reported in the core. The results for drill hole sludges and core for hole 3 are shown below. The complete assay results for holes 1, 2 and 4 are expected from the lab shortly. The drill core and sludges for holes 5 through 7 have been sent for assay. Hole 8 is being logged and hole 9 is in progress.

SLUDGES FEET	U/G HOLE 3 GRAMS/TONNE	CORE FEET	U/G HOLE 3 PPB GOLD	GOLD OZ/T
0 - 10	0.10	0 - 5.5	10	-
10 - 20	61.0	5.5 - 7.5	45	-
20 - 30	11.2	7.5 - 14.7	950	-
30 - 40	3.2	14.7 - 16.6	-	1.341
40 - 50	0.955	16.6 - 22.0	1590	-
50 - 60	.435	22.0 - 27.0	195	-
60 - 65	.385	27.0 - 30.0	-	0.578
		30.0 - 35.0	105	-
		35.0 - 42.0	90	-
		42.0 - 65.0	45	-

Average grade of sludges 10 - 40 ft. = 0.73 oz/ton

Underground drill hole 9503 was drilled into the Baker sequence of rocks on an azimuth of 345° at an angle of +30° for a distance of 65 feet to surface from the 1200 level. This hole intersected part of a pyrite type mineralization similar to the replacement type ore bodies historically mined at Wells. (SEE GCNL NO.126, 30Jun95, P.3 FOR PREVIOUS PROJECT INFORMATION)

93H 19