

1710 - 609 GRANVILLE ST  
PO BOX 10363  
VANCOUVER BC  
CANADA V7Y 1G5  
(604) 683-7265 FAX 683-5306  
BBS 683-7206

# George Cross News Letter

"Reliable Reporting"

WESTERN CANADIAN INVESTMENTS

COPYRIGHT  
ALL REPRODUCTION  
RIGHT RESERVED  
PUBLISHED DAILY  
SUBSCRIPTION RATE  
\$350.00 PER YEAR

NO. 232 (1995)  
DECEMBER 4, 1995

NO. 232 (1995)  
DECEMBER 4, 1995

**KENRICH MINING CORP.**  
[KRC-V] 18,679,228 SHS.

FINAL COREY PROJECT DRILL RESULTS - Ken Trociuk, chairman,  
reports Kenrich  
Mining Corp. has received final assay results for its recently  
completed 1995 drill program on the T.V. Zone on the 100%-owned  
Corey project, eight miles south of the Eskay Creek Deposit and 19  
miles north of Stewart, northwestern British Columbia.

Results to date indicate the T.V. Zone is much larger and more strongly mineralized than anticipated from surface work. The initial 22 drill holes, completed during September and October, start to outline a large zone of alteration with potential "bulk tonnage" gold and silver values. Though open to depth and along strike in both directions, 10 of 15 holes define a mineralized area with a length of 490 feet, a down-dip depth of 390 feet and true thickness of 30 to 85 feet. The weighted average grade of the holes reported here is 0.037 oz. gold/ton and 1.06 oz. silver/ton. Total length of the T.V. Zone is expected to exceed 2,500 feet, making this a major target. SEE TABLE OF ASSAYS OVERLEAF P.2.

Within the large bulk tonnage target is a black mudstone unit, the Hutchings Horizon, where banded pyrite and sphalerite mineralization has been encountered. This mineralization style is often accompanied by higher gold and silver grades. Given the compelling geological similarities to the Eskay Creek Mine, Kenrich will further follow the Hutchings Horizon in the next drill program, in anticipation of it leading to high grade mineral. During the course of this work, the much larger bulk tonnage target will be explored further.

The company has completed its field work for 1995. In addition to the first phase of drilling on the T.V. Zone, drill sites were prepared on the Bench Zone, and the GFJ was systematically mapped and sampled. Recent work has significantly enhanced these prospects, as well as the intervening Cumberland massive sulphide zone. Work will begin again in the new year, with drilling planned for all the currently known Eskay Creek - type targets, such as the T.V., Bench, Cumberland and Battlement Zones, as well as the GFJ high grade vein prospect.

Drill maps, cross section maps are being prepared. Kenrich will report the 1996 budget and program soon (SEE GCNL NO.212, NO.212, 3Nov95, P.1 FOR PREVIOUS COREY PROJECT DRILL RESULTS)

104B 385  
P. 10F2

1710 - 609 GRANVILLE ST  
 PO BOX 10363  
 VANCOUVER BC  
 CANADA V7Y 1G5  
 (604) 683-7265 FAX 683-5306  
 BBS 683-7206

# George Cross News Letter

"Reliable Reporting"

WESTERN CANADIAN INVESTMENTS

COPYRIGHT  
 ALL REPRODUCTION  
 RIGHT RESERVED  
 PUBLISHED DAILY  
 SUBSCRIPTION RATE  
 \$350.00 PER YEAR

NO. 232 (1995)  
 DECEMBER 4, 1995

NO. 232 (1995)  
 DECEMBER 4, 1995

104B 385  
 p. 20 FZ

## KENRICH MINING CORP.

COREY PROPERTY  
 19 MILES NORTH OF STEWART  
 NORTHWEST B.C.

### TV ZONE DRILLING RESULTS

HOLE	GRID LOCATION	DIP	AZ	FROM (feet)	TO (feet)	CORE LENGTH (feet)	Au oz/ton	Ag oz/ton
95-3	396N/670W	-45	270 includes	2.0 18.0	88.2 70.6	86.2 52.6	0.040 0.055	0.90 1.57
95-4	396N/670W	-70	270 includes	1.7 41.6	106.2 86.6	104.6 45.0	0.046 0.079	0.92 1.43
95-14	400N/613W	-45	270 includes	160.7 178.0	190.7 184.6	37.0 6.6	0.018 0.061	0.68 1.06
95-15	400N/613W	-75	270 includes	131.6 309.4	244.7 336.0	113.1 26.6	0.053 0.024	0.94 5.04
95-16	400N/613W	-90	270 includes	171.0 171.0	296.2 184.3	125.2 13.3	0.029 0.070	0.62 0.89

95-18	350N/620W	-75	270 includes	344.7 374.8	417.8 411.2	73.0 36.4	0.039 0.053	1.49 2.55
95-19	303N/625W	-45	270 includes	500.0 512.5	548.9 536.4	48.9 24.0	0.024 0.028	1.63 2.51
95-20	303N/625W	-75	270 includes	389.5 405.9	416.6 416.6	27.1 10.7	0.048 0.109	1.37 2.20
95-21	450N/632W	-45	270 includes and	55.8 55.8 73.5	191.6 70.2 127.3	135.8 14.4 53.8	0.030 0.078 0.030	1.42 0.63 2.25
95-22	450N/632W	-75	270 includes and	125.0 125.0 147.3	162.3 138.9 160.4	37.2 13.8 13.1	0.035 0.052 0.026	0.090 0.41 1.59