1710 - 609 GRANVILLE ST PO BCX 10363 VANCOUVER BC CANADA V7Y IG5 FAX 683-5306 (604) 683-7265

George Cross New's Letter

"Reliable Reporting"

WESTERN CANADIAN INVESTMENTS

COPYRIGHT ALL REPRODUCTION RIGHT RESERVED PUBLISHED DAILY SUBSCRIPTION RATE \$350.00 + GST

> NO. 202 (1996) **OCTOBER 18, 1996**

NO. 202 (1996) **OCTOBER 18, 1996**

INTERNATIONAL WAYSIDE GOLD MINES LTD.

7,027,732 SHS. IWA-VI

CARIBOO GOLD OUARTZ MINE - Frank Callaghan, president, DRILLING ASSAYS RECEIVED

International Wayside Gold Mines Ltd., reports further

drill results from its ongoing development program at the 100% optioned Cariboo Gold Ouartz Mine 60 miles east of Quesnel, at Wells, BC. Over the last two years Wayside has completed 102 drill holes on the property. On surface, 25 diamond drill holes have been completed thus far, and from underground locations, drilling "up" holes to surface on the 1200 Level, 17 diamond drill holes and 60 percussion holes have been completed. These holes are in addition to 165 holes drilled by previous operators for a total of 267 holes within the Rainbow, Heustis, Sanders, and Pinkerton zones over a strike length of 2,400 feet and a width of 400 feet. Also, 103 surface drill holes have been completed by others over a strike length of two miles on ground staked by Wayside adjoining the mine property.

Results obtained from drilling have indicated an open pit estimate of 1,100,000 tons of grading 0.12 oz.gold/ton and with a cut-off grade of 1.0 gram/tonne in the Sanders Zone (Pan Orvana 1990). These reserves will be added to, when the plotting of all the holes on mine level plans have been completed, and a total reserve picture can be constructed by the company's consulting mining engineers, from the various zones currently being worked now and throughout the winter.

Underground percussion drilling is presently in the Pinkerton Zone located at the furthermost point of the 1200 level adit, some 2,400 feet from the mine portal. Fifteen underground percussion holes have recently been completed, numbered UP39 to UP 54. Holes UP40, UP48, UP49 and a portion of UP50 are presented overleaf P.2. The portion of UP50 from 112 to 132 feet (20 ft) is awaiting assay. Eight holes (four percussion and four diamond drill) have been sampled and logged with assays pending. The surface diamond drill is now set up on the Pinkerton Zone. Plans and sections from 115 drill holes completed to date on the Rainbow Zone alone are being correlated, and results from channel sampling in the zone has identified several new drilling targets to extend the strike length. Some 2,000,000 tons of ore are expected from this zone. The grade has not yet been established, but 0.1 oz/ton is expected.

The Sanders and Heustis zones, previously reported on, are located between the Rainbow Zone and the Pinkerton Zone. All work and drill results being used to develop the new reserves are taking place above the 1200 level. The vertical distance from the Jack of Clubs Lake to the 1200 level is about 400 feet and from the 1200 level in the Sander Zone to the top of Cow Mountain is about 600 feet. From the top of Cow Mountain to the bottom of the mine workings (2000 Level) is some 1,500 feet. When weather stops further surface drilling, the work program will continue underground throughout the winter. (SEE GCNL NO.192, Oct.3/96, P.4 FOR PREVIOUS CARIBOO GOLD QUARTZ MINE PROJECT DATA)

93H 19 p. 10f2

INTERNATIONAL WAYSIDE GOLD MINES LTD. CARIBOO GOLD QUARTZ MINE WELLS/BARKERVILLE AREA, BC

| | ONDE | 71.97(LABEL) PT-12 | | | | | | | | |
|-----------|---|---|------------------|--|--|--|--|--|--|--|
| | UNDERGROUND PERCUSSION DRILLING PINKERTON | | | | SAMPLE | | | | Ĺ <u> </u> | |
| | | | | CO-ORDIN | LATES | LENGTH | | GOLD ABSA | | |
| LENGTH | BEARING | INCLINATION | COLLAR | | | Inter- | | | | |
| feet | degrees | degrees | ELEVATION | Northing | Easting | section | | | ozA | |
| 68 | 304 | 50 | 4341 | 4807 | 13075 | 0-8 | 8.00 | 1.620 | 0.05 | |
| | | | | | | 8-68 | 60.00 | Trace | | |
| 100 | 327 | +18 | 4337 | 4172 | 13118 | 4-40 | 38.00 | 3.803 | 0.110 | |
| Including | | | | | | 20-24 | 4.00 | 17.200 | 0.501 | |
| | | | | | | 58-100 | 42.00 | Trece | | |
| 92 | 331 | +38 | 4340.4 | 4172 | 13117 | 16-20 | 4.00 | 1.480 | 0.043 | |
| | | | | | | 28-32 | 4.00 | 1.520 | 0.044 | |
| 132 | 325 | +15 | | | | 32-112 | 78.00 | 7.388 | 0.215 | |
| | | | | | | 56-60 | 4.00 | 19.980, | 0.582 | |
| | | | | | | 68-72 | 4.00 | 21.430 | 0.625 | |
| | | | | | | 108-112 | 4.00 | 32.230 | 0.94 | |
| | | | | | | 112-132 | 20.00 | 7 | 7 | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | SURFACE DIAMOND DRILLING RAINBOW ZONE | | | | | SAMPLE | | | | |
| | | | | CO-ORDII | D-ORDINATES | | LENGTH | | GOLD ASSAY | |
| LENGTH | BEARING | INCLINATION | COLLAR | • | | Inter- | | | | |
| feet | degrees | degrees | ELEVATION | Northing | Easting | section | feet | gpt | oz/t | |
| 172 | 70 | -35 | | | | No significar | | cant | | |
| 202 | 185 | -45 | | | | 0-82 | | Trace | | |
| 187 | 185 | -45 | | | | | | | 0.095 | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | <u> </u> | |
| | 100 92 132 132 LENGTH feet 172 | feet degrees 68 304 100 327 92 331 132 325 SURFA LENGTH BEARING feet degrees 172 70 202 185 | 100 327 +18 | SURFACE DIAMOND DRILLING RAINBOW ZONE SURFACE DIAMOND COLLAR feet degrees degrees ELEVATION COLLAR degrees degrees degrees ELEVATION COLLAR degrees degrees ELEVATION COLLAR degrees degrees ELEVATION COLLAR degrees de | Test Description Descrip | SURFACE DIAMOND DRILLING RAINBOW ZONE CO-ORDINATES | SURFACE DIAMOND DRILLING RAINBOW ZONE SURFACE DIAMOND DRILLING RAINBOW ZONE SEATING SECTION SEATING SEATING SECTION SEATING SECTION SEATING SECTION SEATING SEATING SEATING SECTION SEATING SECTION SEATING SECTION SEATING SEATING SECTION SEATING SECTION SEATING SECTION SEATING SEATING SECTION SEATING SEATING SECTION SEATING SECTION SEATING SECTION SEATING SEATING SECTION SEATING SECTION SEATING SEATING SECTION SEATING SEATING SECTION SEATING SE | SURFACE DIAMOND DRILLING RAINBOW ZONE SURFACE DIAMOND RAINB | SURFACE DIAMOND DRILLING RAING RAING RAINBOW ZONE RAINBO | |

93H 19 p. 20fz

1710 - 609 GRANVILLE ST PO BGX 10363 VANCOUVER BC CANADA V7Y 1G5 (604) 683-7265 FAX 683-5306

George Cross News Letter

"Reliable Reporting"

WESTERN CANADIAN INVESTMENTS

COPYRIGHT
ALL REPRODUCTION
RIGHT RESERVED
PUBLISHED DAILY
SUBSCRIPTION RATE
\$350.00 + GST

NO. 202 (1996) OCTOBER 18, 1996 NO. 202 (1996) OCTOBER 18, 1996