

1710 - 609 GRANVILLE ST
PO BOX 10363
VANCOUVER BC
CANADA V7Y 1G5
(604) 683-7265 FAX 683-5306

George Cross News Letter

"Reliable Reporting"

WESTERN CANADIAN INVESTMENTS

COPYRIGHT
ALL REPRODUCTION
RIGHT RESERVED
PUBLISHED DAILY
SUBSCRIPTION RATE
\$350.00 + G.S.T.
PER YEAR

NO. 163 (1996)
AUGUST 22, 1996

NO. 163 (1996)
AUGUST 22, 1996

STIRRUP CREEK GOLD LTD.

[SGU-V] 5,055,800 SHS.
HIGH GRADE SAMPLES ADD TO - Larry W. Reaugh, president of
GOLD TONNAGE POTENTIAL Stirrup Creek Gold has reported
diamond drill hole assay results
from hole No. 9 to 12. (SEE TABLE OVERLEAF P.3.

The Zone V trench has been expanded in both directions from
the previously reported results. (SEE GCNL NO. 122, P.1, JUNE 24,
1996) Channel intervals 2.5 to 30 m were reported earlier and
averaged 0.67 oz/tonne (20.84 grams/tonne) over an average width
of 11 feet. Channels 19 to 22 continue from 35 to 48 metre grid east
and averaged 0.865 oz/tonne (26.90 grams/tonne) over an average
width of 6.2 feet. Channels 5 to -5 fill in and continue to grid west
from the original western end. The average of this interval is 0.22
oz/tonne (6.84 grams/tonne) over an average width of 9.66 feet. The
new trenching has expanded the surface length from 30 m to 60
metres in strike length averaging 0.634 oz/tonne (19.72
grams/tonne) over an average width of 9.0 feet and length of 197.0
feet.

Trenching 30 metres down slope exposed, below 6 m of
overburden a previously unknown quartz zone that was sampled from

grid west to east at 5 metre intervals from C37-0 - C37-25 over a
strike distance of 25 metres (82 ft) and averaged 0.077 oz/tonne
(2.39 grams/tonne) over an average width of 9.75 feet as shown on
overleaf P.3.

Recent results have greatly increased the potential of
establishing a large tonnage low grade deposit with a high grade
centre over significant lengths and widths.

920 51

p. 10f2

STIRRUP CREEK GOLD LTD.

WATSON BAR GOLD PROPERTY
30 KM. WEST OF CLINTON, SOUTHWEST BC

DRILL HOLE NO.	INTERVAL	WIDTH		AU	
		(METRES)	(FEET)	G/TONNE	OZ/TONNE
96-09	62.00 - 63.00	1.00	3' - 3"	4.14	0.133
96-10	34.66 - 35.33	0.66	2' - 2"	25.83	0.830
96-11 *	150.00 - 153.66	3.66	12' - 0"	23.77	0.764
	177.00 - 184.00	7.00	23' - 0"	1.04	0.034
96-12	76.00 - 77.33	1.33	4' - 3"	9.31	0.299
	95.00 - 13.33	8.33	27' - 3"	4.12	0.132

- Hole No. 11 is located 150 metres (500 feet) down dip from Hole No. 89-1 which returned 15 feet of .590 oz/tonne (18.35 grams/tonne).

INTERVAL METRES	WIDTH		AU	
	(METRES)	(FEET)	G/TONNE	OZ/TONNE
C22-35	1.5	5' - 0"	16.36	0.53
C21-40	2.0	6' - 6"	49.30	1.58
(Included)	0.5	1' - 7"	184.40	5.93
C20-45	1.5	5' - 0"	19.10	0.61
C19-48	2.5	8' - 2"	20.15	0.65
C23-5	2.0	6' - 6"	5.01	0.16
	1.5	5' - 0"	3.34	0.11
C24-2	2.0	6' - 6"	6.80	0.22
C25-0	2.0	6' - 6"	23.14	0.74
	2.0	6' - 6"	2.10	0.10
C26 -2W	2.0	6' - 6"	1.52	0.04
C27-5W	3.0	9' - 10"	4.54	0.15
C37-0	1.0	3' - 3"	2.45	0.08
	1.5	5' - 0"	2.00	0.06
C36-5	2.5	8' - 2"	2.27	0.07
C35-10	4.5	14' - 8"	1.56	0.05
C34-15	2.0	6' - 6"	5.75	0.18
	1.5	5' - 0"	2.86	0.09
C33-20	3.5	11' - 5"	1.83	0.06
C32-25	1.0	3' - 3"	1.79	0.06
	0.5	1' - 6"	2.33	0.07

920 51 p. 2 of 2