

SAMPSON ENGINEERING INC.

2696 West Eleventh Avenue
 Vancouver, British Columbia, Canada
 V6K 2L6

FAX (604) 734-7837

Telephone: (604) 736-7284

FILE

April 02, 1992

RECEIVED

APR 02 1992

WAYSIDE GOLD MINES LTD. and
 BRIGADIER RESOURCES LTD.
 1202-510 West Hastings Street
 Vancouver, B.C.
 V6B 1L8

Attention: J. Frank Callaghan

Dear Sirs:

Re: 1991 Drill Program

The four drill holes on the Wayside property totaling 3052 feet, intersected the Main Wayside Vein as well as the Notman Vein below the 9th level of the Old Wayside Mine workings.

Because the property is on the shore of Carpenter Lake and is crossed by the Lillooet-Goldbridge highway, drilling sites were limited. All four holes were therefore drilled from the same site, squeezed between the highway and the lake shore. Details are as follows:

Hole	Azimuth	Dip	Intersection Main Wayside Vein		Feet
91-1	232°	-85°	668.5	684.4	15.9
91-2	246°	-80°	588.0	615.4	27.4
91-3	260°	-75°	563.0	567.0	4.0
91-4	210°	-70°	511.5	519.0	7.5

Hole	Azimuth	Dip	Intersection Notman Vein		Feet
91-1	232°	-85°	161.5	169.0	7.5
91-2	246°	-80°	178.7	184.8	6.0
91-3	260°	-75°	183.3	194.0	9.5
91-4	210°	-70°	278.0	286.0	8.0

J.P. Elwell, P. Eng. in his December 19, 1980 Report on the Main Wayside Vein, quoted as follows:

"Hole 80-S10 which was drilled from the surface to cut the Wayside shear below the 9th level intersected a 15 foot section of vein in the hanging wall of the shear which averaged 1.76 oz/ton Au and 0.68 oz/ton Ag. Within this 15 feet, 5 feet assayed 4.78 oz/ton Au and 1.84 oz/ton Ag."

The following was quoted from S. McAllister, DDH 88-9 Chevron:

"A highly anomalous zone identified . . . at 544.15 to 557.02 feet yielded 2.093 g/ton Au over 13.0 feet. This zone is the highest intersection returned from the drilling program. This auriferous quartz veined zone possibly represents the down dip extension of the hanging wall veins found on the No. 9 level. The dips of these hanging wall veins are known to be flatter than the Main Vein zone.

Two additional zones . . . returned anomalous gold values from 574.54 to 591.89 feet and 627.03 to 637.04 feet. The maximum values of 620 and 520 ppb Au were from samples 79916 and 79017, respectively."

Peter D. Leriche, B.Sc., F.G.A.C. and Roger G. Kidlark, B.Sc., F.G.A.C. in their May 14, 1991 Report on the Wayside Property, quoted as follows:

"DDH 87-1: In 1987 Chevron drilled this hole to test for mineralization below level 9. Drill core sample 113203H was taken from 179.44 to 181.03 m. and returned a value of 1.840 oz Au/ton over a width of 1.59 meters."

Hole	Azimuth	Dip	Intersection Main Wayside Vein		Feet	Gold ppb	Gold oz/t
80-S 10	215°	-56°	665.0	690.0	5.0		0.48
80-S 10	215°	-56°	690.0	695.0	5.0		4.78
80-S 10	215°	-56°	695.0	700.0	5.0		0.019

Hole	Azimuth	Dip	Intersection Notman Vein		Feet	Gold ppb	Gold oz/t
87-1	212°	-53°	588.74	593.96	5.23		1.84
88-9	218°	-75°	491.53	495.69	4.2	360	
88-9	218°	-75°	495.69	498.45	2.8	315	
88-9	218°	-75°	544.15	557.02	12.87	2093	
88-9	218°	-75°	574.54	591.89	17.35	620	
88-9	218°	-75°	627.03	637.04	10.0	520	

In summary, the 1991 drill holes successfully intersected the "Main Wayside Vein" and the "Notman Vein" or (Hanging Wall Vein) proving that the ore bearing structure continues down dip below the 9th level of the old workings. Intersections in 91-1, 2 and 4 indicate that the veins have a true width in excess of minimum mining width (approximately 5 feet). The intersection in 91-3 is narrower, probably because the vein is intersected by a fault on the footwall side. Gold values intersected by the four holes are below ore grade.

However, values could increase again down dip and down plunge because the original workings show presence of low grade values between high grade in the stoped areas. Since the four 1991 holes all intersected the two vein structures at approximately the same levels down dip, they encountered a low grade zone similar to those occurring between high grade areas in the Wayside Mine Workings.

Hole	Intersection Main Wayside Vein		Width (feet)	Gold ppb
91-1	668.5	672.4	3.9	180
91-2	588.0	592.0	4.0	420
91-2	592.0	596.0	4.0	290
91-2	611.0	614.0	3.0	144
91-3	563.0	567.0	4.0	034
91-4	511.5	515.0	3.5	034
91-4	515.0	519.0	4.0	420

Hole	Intersection Notman Vein		Width (feet)	Gold ppb
91-1	161.5	169.0	7.5	004
91-2	178.7	184.8	6.0	006
91-3	183.3	194.0	9.5	034
91-4	278.0	286.0	8.0	102

Compilation of previous drill results with those from the 1991 program shows approximately 300 feet of gold bearing ground occurring in the Main Wayside Vein between the 9th level and the drill intersections. At an average width of 10 feet, and strike length of 200 feet (as indicated on 9th level plans) this would contain 50,000 tons.

The Notman or Hanging Wall Vein, was intersected by Chevron drilling (1987) and the 1991 program. Between the 5th level and recent drill intersections (300 feet below the 9th level) is a block of ground approximately 700 feet down dip by 200 feet strike length by 5 feet wide. This contains 58,000 tons.

Although expensive, the most effective method of exploration and evaluation of the Wayside veins would be a program of de-watering, rehabilitation, sampling and underground drilling of the lower levels of the Wayside workings as proposed by Leriche and Kidlark (14 May 1991).

The program proposed by Leriche and Kidlark consisted of:

- a) rehabilitation and de-watering down to Level 9;
- b) detailed geological mapping, sampling and computer modelling of all 9 levels;
- c) driving three crosscuts for underground drill stations;
- d) underground drilling (this has been reviewed by the writer in light of recent surface drilling results).

The program proposed by Leriche and Kidlark is regarded by the writer as the most effective method of exploring the Wayside veins below the existing workings. Surface drilling has been shown to be of limited usefulness. The proposed cost of the underground programs (\$377,000.00) is realistic based on recent costs for similar work programs in which the writer has been involved at Bralorne and Rosslund.

Yours truly,

SAMPSON ENGINEERING INC.



Chris J. Sampson

Chris Sampson, P.Eng.,
President

SAMPSON ENGINEERING INC.

2696 West Eleventh Avenue
Vancouver, British Columbia, Canada
V6K 2L6

FAX (604) 734-7837
(604) 734-7837

CERTIFICATE

I, CHRISTOPHER J. SAMPSON, of 2696 West 11th Avenue, Vancouver, B.C. V6K 2L6, hereby certify that:

1. I am a graduate (1966) of the Royal School of Mines, London University, England with a Bachelor of Science degree (Honours) in Economic Geology.
2. I have practised my profession of mining exploration for the past 25 years in Canada, Europe, United States and Central America. For the past 15 years I have been based in British Columbia.
3. I am a consulting geologist. I am a registered member in good standing of the Association of Professional Engineers of British Columbia.
4. I have not received, nor do I expect to receive, an interest direct or indirect, in the Properties or securities of Wayside Gold Mines Ltd., Brigadier Resources Ltd. or those of its associated companies.
5. Wayside Gold Mines Ltd., Brigadier Resources Ltd. and its affiliates are hereby authorized to use this letter report or quotes from it in conjunction with any prospectus or statement of material facts.
6. I have no interest in any other property or company holding property within 10 kilometres of the Wayside claims.

Vancouver, B.C.
March 23, 1992



Chris J. Sampson

Christopher J. Sampson, P.Eng.
Consulting Geologist