N
Con'd Sheet 2
6300N
6275N
6250N
6225N
6200N
6175N
6550E
6575E
6600E
6625E
6650E
6675E
6700E
6725E
6750E
GROUND CONDITIONS
GOOD
POOR
GOOD
Day Use Explosives Mag.
M-3
A9
Face June 14 1985
Face June 11 1985
Face June 6 1985
AZIMUTH = 44°10'
2" SHOTCRETE
NOTES: ALL SAFETY BAYS TO BE 2m HIGH 1.5m WIDE 1.0m DEEP
LASER TARGETS
LASER LOC'N N 6230.79 EL E 6608.25
START JULY 3/88
5x4m SLASH TO HERE
START SILL ELEV = 1392.70
EL 1390.00
TO TOWER STN.
M-1
LIFTER LINE ELEV = 1392.70
VENT DOOR SLASH (SEE SECTION ALSO)
Portal Elev. 1398
K1 ELEV 1392.147
K-9 ELEV. 1403.174
8.63m COLLAR
VENT DR.
RIGHT WALL
1402.96
1402.8
1403.16
1402.7
1402.15
1403.65
REF LINE THRU K-9
Vent Access
Period Aug 16, 1988 - Aug 31, 1988
Advance 2.9 m
Shotcrete 13.6 m²
SECTION THROUGH ℄ VENT ADIT
REF ELEV 1400.0
1415 ADIT
GRADE LINE
ROAD TO 1565
2 BENCH SLASHES
11
248309

CASSIAR MINING CORPORATION — McDAME EXPLORATION

1415 ADIT
SHEET 1
REVISION 1

248309

DRN C.T.
CKD
APR
1500 250 4
SCALE 1:250
86 07 21