827636

LOGISTICAL REPORT

INDUCED POLARIZATION/RESISTIVITY SURVEYS

LARA PROJECT, VANCOUVER ISLAND AREA, B.C.

on behalf of

MINNOVA INC.
4th floor - 311 Water Street
Vancouver, B.C. V6B 1B8

Field work completed: May 1 to 18, 1989

by

Alan Scott, Geophysicist
SCOTT GEOPHYSICS LTD.
4013 West 14th Avenue
Vancouver, B.C. V6R 2X3

May 27, 1989

TABLE OF CONTENTS

		page
1	Introduction	1
2	Survey Location	1
3	Survey Grid and Survey Coverage	1
4	Personnel	1
5	Instrumentation and procedures	2
6	Recommendations	2

1. INTRODUCTION

Induced polarization and resistivity surveys were conducted over portions of the Lara Project, Vancouver Island Area, B.C., within the period May 1 to 18, 1989. The work was conducted by Scott Geophysics Ltd. on behalf of Minnova Inc.

The pole dipole electrode array was used, with an "a" spacing of 25 meters and "n" separations of 1 to 5. The current electrode was to the south of the receiving electrodes on all survey lines.

2. SURVEY LOCATION

The Lara Project is located about 15 kilometers west southwest of Chemainus, B.C. Access is via secondary mining and logging roads north from kilometer 10 or kilometer 12 on the main Chemainus River haul road.

3. SURVEY GRID AND SURVEY COVERAGE

A total of 26.7 line kilometers of induced polarization survey were completed on the present survey of the Lara Project. Details of lines surveyed are given in the production reports.

4. PERSONNEL

Ken Moir, technician, was the party chief on the survey and operated the IPR11 receiver. Gary Wells, geologist, was the Minnova representative for the project.

5. INSTRUMENTATION AND PROCEDURES

A Scintrex IPR11 time domain microprocessor based receiver and a Scintrex 10.0 kw TSQ4 transmitter were used for the induced polarization survey. Readings were taken using a 2 second alternating square wave. The chargeability for the eighth slice (690 to 1050 milliseconds after shutoff; midpoint at 870 milliseconds) is the value that has been plotted on the accompanying plans and pseudosections.

The survey data was archived, processed, and plotted using a Sharp PC7000 microcomputer running Scintrex Soft II and proprietary software. All chargeability values were analyzed for their spectral characteristics using a curve matching procedure (Soft II).

6. RECOMMENDATIONS

A preliminary examination of the results of the induced polarization survey indicates the presence of weak to moderate chargeability highs that merit further work.

A detailed interpretation of the results of this survey, and correlation to geological and geochemical information, is required before any specific recommendations could be made.

Respectfully Submitted,



Alan Scott, Geophysicist

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 844

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
10325	1	220.3	74.0	3.4	72.74	.10	.20	-2000.00	-2000.000	1.10	-2000.00
	2	90.9	92.0	2.5	65.47	.01	.20	-2000.00	-2000.000	.97	-2000.00
	3	46.4	93.0	2.0	27.62	.10	.40	-2000.00	-2000.000	4.44	-2000.00
	4	47.2	159.0	2.5	101.42	100.00	.10	-2000.00	-2000.000	5.33	-2000.00
	5	52.9	267.0	3.0	56.34	.03	.30	-2000.00	-2000.000	3.21	-2000.00
10350	1	438.6	144.0	2.6	61.55	.03	.20	-2000.00	-2000.000	1.22	-2000.00
	2	114.6	113.0	2.4	38.54	.10	.30	-2000.00	-2000.000	1.34	-2000.00
	3	135.9	260.0	2.1	40.70	.03	.30	-2000.00	-2000.000	1.47	-2000.00
	4	89.4	295.0	3.4	80.73	.03	.20	-2000.00	-2000.000	2.33	-2000.00
	5	50.1	248.0	1.6	32.24	.03	.30	-2000.00	-2000.000	4.73	-2000.00
10375	1	312.1	111.0	2.1	33.92	.10	.30	-2000.00	-2000.000	2.23	-2000.00
	2	246.7	264.0	2.0	40.06	.03	.30	-2000.00	-2000.000	1.25	-2000.00
	3	131.9	280.0	3.4	90.75	.01	.20	-2000.00	-2000.000	1.54	-2000.00
	4	62.2	221.0	2.0	44.57	.10	.20	-2000.00	-2000.000	2.93	-2000.00
	5	64.7	346.0	2.9	27.15	.30	.50	-2000.00	-2000.000	5.96	-2000.00
10400	1	729.1	254.0	1.8	43.54	.01	.30	-2000.00	-2000.000	3.03	-2000.00
	2	283.7	296.0	3.8	99.82	.01	.20	-2000.00	-2000.000	1.59	-2000.00
	3	111.7	230.0	2.4	38.19	.10	.30	-2000.00	-2000.000	1.63	-2000.00
	4	93.6	326.0	3.3	86.56	.01	.20	-2000.00	-2000.000	1.15	-2000.00
	5	74.4	389.0	2.4	38.13	.10	.30	-2000.00	-2000.000	2.83	-2000.00
10425	1	1030.0	380.0	5.1	132.67	.01	.20	-2000.00	-2000.000	1.68	-2000.00
	2	245.2	271.0	3.2	84.61	.01	.20	-2000.00	-2000.000	1.35	-2000.00
	3	191.4	420.0	4.2	67.29	.10	.30	-2000.00	-2000.000	.91	-2000.00
	4	129.0	470.0	3.2	75.23	.03	.20	-2000.00	-2000.000	3.34	-2000.00
	5	93.6	518.0	3.1	73.26	.03	.20	-2000.00	-2000.000	1.11	-2000.00
10450	1	1225.0	490.0	3.6	95.53	.01	.20	-2000.00	-2000.000	2.32	-2000.00
	2	666.4	804.0	5.2	136.32	.01	.20	-2000.00	-2000.000	1.90	-2000.00
	3	402.5	970.0	4.1	66.14	.10	.30	-2000.00	-2000.000	1.72	-2000.00
	4	223.8	900.0	4.0	93.68	.03	.20	-2000.00	-2000.000	1.72	-2000.00
	5	79.8	481.0	4.0	94.99	.03	.20	-2000.00	-2000.000	3.38	-2000.00
10475	1	2754.0	1660.0	3.8	61.05	.10	.30	-2000.00	-2000.000	2.74	-2000.00
	2	983.8	1782.0	3.1	50.56	.10	.30	-2000.00	-2000.000	2.69	-2000.00
	3	526.1	1900.0	3.0	42.30	.30	.30	-2000.00	-2000.000	.93	-2000.00
	4	158.2	950.0	3.1	81.19	.01	.20	-2000.00	-2000.000	1.60	-2000.00
	5	86.0	779.0	4.9	123.99	.01	.20	-2000.00	-2000.000	1.93	-2000.00
10500	1	1954.0	1800.0	3.1	50.96	.10	.30	-2000.00	-2000.000	3.10	-2000.00
	2	812.3	2250.0	2.8	74.00	.01	.20	-2000.00	-2000.000	1.57	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	214.7	1180.0	2.8	66.70	.03	.20	-2000.00	-2000.000	1.42	-2000.00
	4	105.6	970.0	4.5	72.55	.10	.30	-2000.00	-2000.000	1.85	-2000.00
	5	63.0	873.0	2.5	49.29	.03	.30	-2000.00	-2000.000	1.55	-2000.00
10525	1	2030.0	1770.0	3.3	79.44	.03	.20	-2000.00	-2000.000	2.28	-2000.00
	2	429.9	1124.0	3.5	75.91	.10	.20	-2000.00	-2000.000	1.92	-2000.00
	3	201.7	1050.0	5.1	118.26	.03	.20	-2000.00	-2000.000	.60	-2000.00
	4	112.0	970.0	3.0	49.09	.10	.30	-2000.00	-2000.000	2.80	-2000.00
	5	94.1	1231.0	3.1	61.72	.03	.30	-2000.00	-2000.000	2.20	-2000.00
10550	1	1062.0	950.0	3.5	82.81	.03	.20	-2000.00	-2000.000	1.56	-2000.00
	2	374.5	1007.0	5.0	116.82	.03	.20	-2000.00	-2000.000	1.46	-2000.00
	3	188.2	1010.0	3.0	58.65	.03	.30	-2000.00	-2000.000	1.59	-2000.00
	4	147.6	1320.0	3.2	61.91	.03	.30	-2000.00	-2000.000	2.03	-2000.00
	5	106.4	1430.0	4.1	103.87	.01	.20	-2000.00	-2000.000	5.68	-2000.00
10575	1	970.1	951.0	5.6	129.95	.03	.20	-2000.00	-2000.000	1.61	-2000.00
	2	342.8	1009.0	4.1	107.37	.01	.20	-2000.00	-2000.000	1.38	-2000.00
	3	262.4	1540.0	3.6	58.69	.10	.30	-2000.00	-2000.000	1.39	-2000.00
	4	159.1	1560.0	4.5	73.06	.10	.30	-2000.00	-2000.000	1.97	-2000.00
	5	105.3	1540.0	4.1	78.80	.03	.30	-2000.00	-2000.000	1.81	-2000.00
10600	1	953.8	788.0	5.3	137.94	.01	.20	-2000.00	-2000.000	1.59	-2000.00
	2	516.5	1280.0	4.5	118.43	.01	.20	-2000.00	-2000.000	1.79	-2000.00
	3	278.7	1370.0	5.4	139.46	.01	.20	-2000.00	-2000.000	.89	-2000.00
	4	169.2	1390.0	4.9	127.82	.01	.20	-2000.00	-2000.000	1.94	-2000.00
	5	89.1	1103.0	6.4	148.79	.03	.20	-2000.00	-2000.000	1.80	-2000.00
10625	1	1658.0	1530.0	4.5	117.70	.01	.20	-2000.00	-2000.000	1.75	-2000.00
	2	597.3	1654.0	6.6	152.14	.03	.20	-2000.00	-2000.000	1.00	-2000.00
	3	297.5	1640.0	6.3	146.38	.03	.20	-2000.00	-2000.000	1.19	-2000.00
	4	135.5	1250.0	7.7	175.16	.03	.20	-2000.00	-2000.000	1.24	-2000.00
	5	87.0	1204.0	17.6	544.07	.30	.10	-2000.00	-2000.000	.86	-2000.00
10650	1	2380.0	2070.0	5.8	122.97	.10	.20	-2000.00	-2000.000	2.27	-2000.00
	2	587.2	1536.0	6.3	146.86	.03	.20	-2000.00	-2000.000	1.22	-2000.00
	3	247.4	1290.0	7.1	150.40	.10	.20	-2000.00	-2000.000	1.32	-2000.00
	4	141.7	1230.0	17.0	543.13	.10	.10	-2000.00	-2000.000	.69	-2000.00
	5	93.8	1227.0	17.3	505.61	100.00	.10	-2000.00	-2000.000	.82	-2000.00
10675	1	1131.0	2530.0	9.1	188.91	.10	.20	-2000.00	-2000.000	1.56	-2000.00
	2	242.9	1634.0	8.8	198.86	.03	.20	-2000.00	-2000.000	1.20	-2000.00
	3	115.3	1540.0	17.7	546.44	.30	.10	-2000.00	-2000.000	.58	-2000.00
	4	61.7	1384.0	18.7	535.70	100.00	.10	-2000.00	-2000.000	.82	-2000.00
10700	1	508.8	1770.0	8.6	194.16	.03	.20	-2000.00	-2000.000	1.45	-2000.00
	2	154.2	1610.0	16.9	560.34	.03	.10	-2000.00	-2000.000	.91	-2000.00
	3	77.6	1620.0	19.2	545.42	100.00	.10	-2000.00	-2000.000	1.19	-2000.00
10725	1	920.7	1927.0	14.5	515.39	.01	.10	-2000.00	-2000.000	1.04	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	2	284.9	1789.0	18.9	539.23	100.00	.10	-2000.00	-2000.000	.85	-2000.00
10750	1	416.0	1306.0	17.5	515.54	10.00	.10	-2000.00	-2000.000	.82	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 834

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
10325	1	381.1	128.0	2.7	59.10	.10	.20	-2000.00	-2000.000	1.43	-2000.00
	2	120.2	121.0	3.0	65.52	.10	.20	-2000.00	-2000.000	1.51	-2000.00
	3	56.9	115.0	2.9	39.94	.30	.30	-2000.00	-2000.000	4.84	-2000.00
	4	35.2	118.0	2.2	43.55	.03	.30	-2000.00	-2000.000	10.03	-2000.00
	5	18.6	94.0	2.5	28.41	.30	.40	-2000.00	-2000.000	3.02	-2000.00
10350	1	346.9	111.0	2.9	68.64	.03	.20	-2000.00	-2000.000	1.16	-2000.00
	2	113.6	109.0	3.1	66.61	.10	.20	-2000.00	-2000.000	1.04	-2000.00
	3	60.1	115.0	2.4	57.95	.03	.20	-2000.00	-2000.000	1.96	-2000.00
	4	29.1	93.0	2.5	28.04	.30	.40	-2000.00	-2000.000	2.84	-2000.00
	5	29.4	141.0	2.1	38.42	.03	.30	-2000.00	-2000.000	3.93	-2000.00
10375	1	286.5	105.0	2.5	65.39	.01	.20	-2000.00	-2000.000	1.44	-2000.00
	2	105.9	117.0	2.3	36.75	.10	.30	-2000.00	-2000.000	2.53	-2000.00
	3	44.0	97.0	2.2	43.65	.03	.30	-2000.00	-2000.000	1.51	-2000.00
	4	40.0	147.0	1.9	52.01	.01	.20	-2000.00	-2000.000	3.80	-2000.00
	5	34.7	192.0	1.9	52.01	.01	.20	-2000.00	-2000.000	13.75	-2000.00
10400	1	397.9	138.0	2.1	34.80	.10	.30	-2000.00	-2000.000	2.03	-2000.00
	2	108.5	113.0	2.5	40.71	.10	.30	-2000.00	-2000.000	1.58	-2000.00
	3	80.9	168.0	2.1	34.48	.10	.30	-2000.00	-2000.000	2.12	-2000.00
	4	58.9	205.0	2.1	41.71	.03	.30	-2000.00	-2000.000	1.93	-2000.00
	5	52.8	276.0	2.8	64.60	.01	.20	-2000.00	-2000.000	12.03	-2000.00
10425	1	221.3	115.0	2.2	34.84	.10	.30	-2000.00	-2000.000	3.41	-2000.00
	2	119.3	187.0	2.1	40.78	.03	.30	-2000.00	-2000.000	2.68	-2000.00
	3	70.4	220.0	2.5	67.44	.01	.20	-2000.00	-2000.000	2.76	-2000.00
	4	53.2	278.0	2.5	40.39	.10	.30	-2000.00	-2000.000	3.05	-2000.00
	5	52.1	408.0	2.3	56.33	.03	.20	-2000.00	-2000.000	4.05	-2000.00
10450	1	580.8	289.0	2.1	33.92	.10	.30	-2000.00	-2000.000	2.56	-2000.00
	2	211.0	315.0	2.9	47.41	.10	.30	-2000.00	-2000.000	2.34	-2000.00
	3	125.4	370.0	2.8	45.24	.10	.30	-2000.00	-2000.000	1.55	-2000.00
	4	109.9	540.0	2.7	44.25	.10	.30	-2000.00	-2000.000	2.05	-2000.00
	5	93.7	700.0	2.2	60.34	.01	.30	-2000.00	-2000.000	5.40	-2000.00
10475	1	799.2	386.0	2.9	55.34	.03	.30	-2000.00	-2000.000	2.12	-2000.00
	2	316.9	459.0	2.9	46.29	.10	.30	-2000.00	-2000.000	1.88	-2000.00
	3	246.2	710.0	3.0	78.66	.01	.20	-2000.00	-2000.000	1.14	-2000.00
	4	191.2	920.0	3.0	48.24	.10	.30	-2000.00	-2000.000	2.67	-2000.00
	5	43.1	312.0	2.7	60.15	.10	.20	-2000.00	-2000.000	2.60	-2000.00
10500	1	1579.0	740.0	3.1	50.96	.10	.30	-2000.00	-2000.000	2.15	-2000.00
	2	741.9	1043.0	3.0	78.58	.01	.20	-2000.00	-2000.000	1.57	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	515.9	1440.0	3.0	80.54	.01	.20	-2000.00	-2000.000	1.77	-2000.00
	4	82.1	384.0	2.7	52.69	.03	.30	-2000.00	-2000.000	2.00	-2000.00
	5	50.0	351.0	3.7	97.79	.01	.20	-2000.00	-2000.000	3.30	-2000.00
10525	1	2732.0	1420.0	2.8	73.29	.01	.20	-2000.00	-2000.000	1.11	-2000.00
	2	1375.0	2150.0	2.9	76.83	.01	.20	-2000.00	-2000.000	1.62	-2000.00
	3	232.3	720.0	2.4	46.52	.03	.30	-2000.00	-2000.000	1.74	-2000.00
	4	103.6	540.0	3.8	90.30	.03	.20	-2000.00	-2000.000	2.23	-2000.00
	5	92.0	722.0	3.3	87.54	.01	.20	-2000.00	-2000.000	5.91	-2000.00
10550	1	3813.0	2660.0	3.8	88.72	.03	.20	-2000.00	-2000.000	1.34	-2000.00
	2	472.1	988.0	2.9	68.65	.03	.20	-2000.00	-2000.000	1.22	-2000.00
	3	173.2	720.0	4.0	103.11	.01	.20	-2000.00	-2000.000	1.23	-2000.00
	4	143.6	1000.0	3.8	60.76	.10	.30	-2000.00	-2000.000	2.10	-2000.00
	5	93.9	982.0	3.5	92.56	.01	.20	-2000.00	-2000.000	2.16	-2000.00
10575	1	498.6	782.0	2.6	67.26	.01	.20	-2000.00	-2000.000	1.84	-2000.00
	2	163.7	771.0	4.0	104.85	.01	.20	-2000.00	-2000.000	1.25	-2000.00
	3	130.6	1220.0	4.2	110.38	.01	.20	-2000.00	-2000.000	1.15	-2000.00
	4	69.0	1083.0	3.7	98.22	.01	.20	-2000.00	-2000.000	1.50	-2000.00
	5	46.6	1096.0	4.0	78.76	.03	.30	-2000.00	-2000.000	2.64	-2000.00
10600	1	413.0	762.0	3.8	99.64	.01	.20	-2000.00	-2000.000	1.31	-2000.00
	2	241.7	1339.0	4.8	125.14	.01	.20	-2000.00	-2000.000	1.43	-2000.00
	3	126.7	1400.0	4.5	117.29	.01	.20	-2000.00	-2000.000	1.36	-2000.00
	4	72.1	1331.0	4.8	76.33	.10	.30	-2000.00	-2000.000	2.06	-2000.00
	5	49.5	1372.0	2.5	48.10	.03	.40	-2000.00	-2000.000	3.42	-2000.00
10625	1	977.3	1278.0	5.9	136.03	.03	.20	-2000.00	-2000.000	1.11	-2000.00
	2	331.5	1301.0	6.1	141.11	.03	.20	-2000.00	-2000.000	1.07	-2000.00
	3	167.4	1310.0	6.2	158.47	.01	.20	-2000.00	-2000.000	1.32	-2000.00
	4	95.3	1247.0	3.8	74.16	.03	.30	-2000.00	-2000.000	2.28	-2000.00
	5	39.2	768.0	13.1	473.45	.01	.10	-2000.00	-2000.000	1.18	-2000.00
10650	1	876.7	1376.0	5.5	77.36	.30	.30	-2000.00	-2000.000	2.41	-2000.00
	2	283.6	1335.0	6.8	156.09	.03	.20	-2000.00	-2000.000	.84	-2000.00
	3	143.2	1340.0	5.0	80.75	.10	.30	-2000.00	-2000.000	1.52	-2000.00
	4	49.6	779.0	14.9	503.88	.03	.10	-2000.00	-2000.000	.48	-2000.00
	5	39.4	927.0	21.8	357.05	10.00	.20	-2000.00	-2000.000	1.31	-2000.00
10675	1	983.7	1816.0	6.0	127.54	.10	.20	-2000.00	-2000.000	1.23	-2000.00
	2	265.3	1470.0	5.3	138.18	.01	.20	-2000.00	-2000.000	1.23	-2000.00
	3	84.4	933.0	15.2	267.70	1.00	.20	-2000.00	-2000.000	1.15	-2000.00
	4	55.0	1015.0	22.2	604.71	30.00	.10	-2000.00	-2000.000	1.20	-2000.00
	5	76.3	2114.0	18.3	525.26	100.00	.10	-2000.00	-2000.000	1.35	-2000.00
10700	1	784.9	1449.0	5.8	135.87	.03	.20	-2000.00	-2000.000	1.27	-2000.00
	2	192.7	1067.0	15.0	507.31	.03	.10	-2000.00	-2000.000	.71	-2000.00
	3	104.2	1150.0	24.1	385.56	10.00	.20	-2000.00	-2000.000	1.04	-2000.00
	4	132.5	2440.0	19.4	545.54	100.00	.10	-2000.00	-2000.000	1.17	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	433.9	1238.0	13.1	454.83	.03	.10	-2000.00	-2000.000	.75	-2000.00
	2	130.3	1115.0	24.8	394.40	10.00	.20	-2000.00	-2000.000	1.23	-2000.00
	3	149.0	2540.0	19.9	558.15	100.00	.10	-2000.00	-2000.000	1.08	-2000.00
10750	1	280.7	970.0	22.3	362.52	10.00	.20	-2000.00	-2000.000	1.11	-2000.00
	2	165.1	1720.0	20.3	562.63	100.00	.10	-2000.00	-2000.000	1.20	-2000.00
10775	1	449.9	1086.0	22.6	365.74	10.00	.20	-2000.00	-2000.000	1.04	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 824

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	373.3	154.0	1.8	48.39	.01	.20	-2000.00	-2000.000	2.01	-2000.00
	2	84.8	105.0	2.1	56.17	.01	.20	-2000.00	-2000.000	1.61	-2000.00
	3	35.0	86.0	1.9	46.89	.03	.20	-2000.00	-2000.000	7.28	-2000.00
	4	18.5	76.0	2.2	39.95	.03	.30	-2000.00	-2000.000	12.82	-2000.00
	5	17.7	109.0	1.6	21.21	.30	.40	-2000.00	-2000.000	10.43	-2000.00
10350	1	233.9	83.0	1.5	63.81	.01	.10	-2000.00	-2000.000	6.52	-2000.00
	2	78.7	84.2	1.8	45.39	.03	.20	-2000.00	-2000.000	3.09	-2000.00
	3	37.3	79.0	2.1	90.64	.10	.10	-2000.00	-2000.000	8.61	-2000.00
	4	30.9	110.0	2.2	18.82	.30	.50	-2000.00	-2000.000	11.10	-2000.00
	5	25.1	134.0	1.9	48.69	.01	.20	-2000.00	-2000.000	3.54	-2000.00
10375	1	181.5	98.0	1.8	45.22	.01	.20	-2000.00	-2000.000	3.34	-2000.00
	2	61.4	99.7	2.4	55.32	.03	.20	-2000.00	-2000.000	1.75	-2000.00
	3	40.8	132.0	1.3	30.00	.03	.40	-2000.00	-2000.000	9.72	-2000.00
	4	29.2	158.0	2.5	17.09	1.00	.50	-2000.00	-2000.000	10.82	-2000.00
	5	17.1	138.0	1.8	48.25	.01	.20	-2000.00	-2000.000	7.57	-2000.00
10400	1	340.9	111.0	1.9	47.28	.03	.20	-2000.00	-2000.000	3.68	-2000.00
	2	153.4	150.0	1.9	30.90	.10	.30	-2000.00	-2000.000	2.57	-2000.00
	3	93.3	182.0	1.9	47.58	.03	.20	-2000.00	-2000.000	3.81	-2000.00
	4	45.8	149.0	1.9	49.87	.01	.20	-2000.00	-2000.000	3.92	-2000.00
	5	44.1	216.0	3.7	87.59	.03	.20	-2000.00	-2000.000	3.91	-2000.00
10425	1	419.8	156.0	1.7	27.51	.10	.30	-2000.00	-2000.000	2.11	-2000.00
	2	176.1	197.0	2.0	52.33	.01	.20	-2000.00	-2000.000	1.52	-2000.00
	3	66.0	147.0	1.9	39.91	.30	.20	-2000.00	-2000.000	2.59	-2000.00
	4	55.2	206.0	3.7	96.50	.01	.20	-2000.00	-2000.000	1.64	-2000.00
	5	41.9	235.0	2.0	50.43	.01	.20	-2000.00	-2000.000	7.00	-2000.00
10450	1	642.6	221.0	2.0	52.87	.01	.20	-2000.00	-2000.000	1.91	-2000.00
	2	142.0	146.0	2.2	48.02	.10	.20	-2000.00	-2000.000	1.93	-2000.00
	3	98.8	204.0	3.7	87.32	.03	.20	-2000.00	-2000.000	1.63	-2000.00
	4	57.6	198.0	1.7	33.31	.03	.30	-2000.00	-2000.000	3.68	-2000.00
	5	43.4	224.0	.4	19.32	100.00	.40	-2000.00	-2000.000	42.65	-2000.00
10475	1	1579.0	610.0	3.4	134.65	.03	.10	-2000.00	-2000.000	1.44	-2000.00
	2	454.9	529.0	4.7	99.23	.10	.20	-2000.00	-2000.000	1.08	-2000.00
	3	202.9	470.0	3.0	65.17	.10	.20	-2000.00	-2000.000	1.43	-2000.00
	4	92.0	356.0	1.2	54.83	.10	.10	-2000.00	-2000.000	9.62	-2000.00
	5	44.5	258.0	.9	37.54	.01	.20	-2000.00	-2000.000	21.12	-2000.00
10500	1	2965.0	960.0	5.9	224.50	.10	.10	-2000.00	-2000.000	1.44	-2000.00
	2	914.0	896.0	4.5	181.32	.03	.10	-2000.00	-2000.000	1.58	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	300.7	580.0	2.5	103.44	.01	.10	-2000.00	-2000.000	2.31	-2000.00
	4	127.5	410.0	2.4	60.38	.03	.20	-2000.00	-2000.000	3.16	-2000.00
	5	45.8	224.0	1.6	29.94	.03	.30	-2000.00	-2000.000	12.56	-2000.00
10525	1	3378.0	2300.0	5.4	219.36	.01	.10	-2000.00	-2000.000	1.51	-2000.00
	2	627.1	1284.0	3.4	68.80	.30	.20	-2000.00	-2000.000	.80	-2000.00
	3	221.5	900.0	3.6	73.02	.30	.20	-2000.00	-2000.000	1.60	-2000.00
	4	64.4	439.0	2.4	26.88	.30	.40	-2000.00	-2000.000	1.93	-2000.00
	5	38.1	390.0	1.9	25.90	.10	.40	-2000.00	-2000.000	3.73	-2000.00
10550	1	3028.0	2160.0	4.8	197.13	.01	.10	-2000.00	-2000.000	1.81	-2000.00
	2	750.6	1606.0	5.8	225.73	.03	.10	-2000.00	-2000.000	1.15	-2000.00
	3	177.2	750.0	4.6	98.61	.10	.20	-2000.00	-2000.000	.88	-2000.00
	4	91.1	650.0	4.5	174.57	.10	.10	-2000.00	-2000.000	1.55	-2000.00
	5	79.7	852.0	4.4	94.70	.10	.20	-2000.00	-2000.000	1.91	-2000.00
10575	1	2784.0	2030.0	5.4	115.35	.10	.20	-2000.00	-2000.000	1.41	-2000.00
	2	502.6	1101.0	4.6	97.55	.10	.20	-2000.00	-2000.000	.92	-2000.00
	3	211.7	920.0	4.0	93.83	.03	.20	-2000.00	-2000.000	1.39	-2000.00
	4	167.4	1220.0	4.2	98.73	.03	.20	-2000.00	-2000.000	1.44	-2000.00
	5	131.9	1440.0	5.1	99.53	.03	.30	-2000.00	-2000.000	2.00	-2000.00
10600	1	1545.0	1180.0	2.9	76.78	.01	.20	-2000.00	-2000.000	1.34	-2000.00
	2	462.9	1063.0	3.3	85.64	.01	.20	-2000.00	-2000.000	1.23	-2000.00
	3	323.2	1480.0	3.6	94.71	.01	.20	-2000.00	-2000.000	1.09	-2000.00
	4	230.4	1760.0	4.9	93.72	.03	.30	-2000.00	-2000.000	1.88	-2000.00
	5	130.9	1500.0	6.6	139.88	.10	.20	-2000.00	-2000.000	1.52	-2000.00
10625	1	1333.0	870.0	2.7	44.21	.10	.30	-2000.00	-2000.000	2.42	-2000.00
	2	699.6	1372.0	3.5	90.86	.01	.20	-2000.00	-2000.000	1.83	-2000.00
	3	434.2	1700.0	4.8	79.13	.10	.30	-2000.00	-2000.000	2.81	-2000.00
	4	225.2	1470.0	6.7	153.79	.03	.20	-2000.00	-2000.000	1.48	-2000.00
	5	125.2	1220.0	10.3	356.33	.30	.10	-2000.00	-2000.000	1.82	-2000.00
10650	1	1702.0	1270.0	3.9	102.02	.01	.20	-2000.00	-2000.000	1.32	-2000.00
	2	740.0	1659.0	5.6	90.22	.10	.30	-2000.00	-2000.000	1.85	-2000.00
	3	326.2	1460.0	7.8	161.92	.10	.20	-2000.00	-2000.000	1.19	-2000.00
	4	146.1	1090.0	11.2	389.44	.10	.10	-2000.00	-2000.000	.76	-2000.00
	5	103.2	1150.0	13.6	435.93	1.00	.10	-2000.00	-2000.000	.84	-2000.00
10675	1	2025.0	1510.0	5.3	138.28	.01	.20	-2000.00	-2000.000	1.36	-2000.00
	2	650.8	1459.0	8.5	328.40	.01	.10	-2000.00	-2000.000	1.12	-2000.00
	3	234.9	1050.0	12.4	406.48	1.00	.10	-2000.00	-2000.000	.79	-2000.00
	4	152.6	1140.0	14.5	448.20	30.00	.10	-2000.00	-2000.000	.83	-2000.00
	5	46.6	522.0	18.7	542.27	10.00	.10	-2000.00	-2000.000	1.04	-2000.00
10700	1	1877.0	1370.0	8.5	330.19	.01	.10	-2000.00	-2000.000	1.42	-2000.00
	2	451.3	988.0	13.5	433.64	1.00	.10	-2000.00	-2000.000	.78	-2000.00
	3	264.9	1150.0	15.2	463.05	30.00	.10	-2000.00	-2000.000	.75	-2000.00
	4	77.3	564.0	19.7	561.72	10.00	.10	-2000.00	-2000.000	1.05	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	483.6	1168.0	14.5	460.12	1.00	.10	-2000.00	-2000.000	.87	-2000.00
	2	181.1	1312.0	16.3	488.96	10.00	.10	-2000.00	-2000.000	.77	-2000.00
	3	45.1	652.0	20.9	580.71	30.00	.10	-2000.00	-2000.000	1.03	-2000.00
10750	1	614.7	1608.0	11.6	380.75	3.00	.10	-2000.00	-2000.000	.67	-2000.00
	2	104.0	816.0	18.6	539.24	10.00	.10	-2000.00	-2000.000	.97	-2000.00
10775	1	286.8	1000.0	16.6	207.61	.30	.30	-2000.00	-2000.000	5.01	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 814

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
10325	1	361.9	112.5	1.2	55.50	.10	.10	-2000.00	-2000.000	10.70	-2000.00
	2	113.6	105.9	1.3	33.62	.03	.20	-2000.00	-2000.000	6.31	-2000.00
	3	54.0	100.5	1.4	38.89	.01	.20	-2000.00	-2000.000	18.44	-2000.00
	4	26.8	83.2	1.8	49.81	100.00	.20	-2000.00	-2000.000	11.19	-2000.00
	5	15.2	71.0	2.0	83.57	.01	.10	-2000.00	-2000.000	4.38	-2000.00
10350	1	288.5	100.0	1.5	36.58	.03	.20	-2000.00	-2000.000	3.47	-2000.00
	2	95.2	99.6	1.8	35.13	.03	.30	-2000.00	-2000.000	3.89	-2000.00
	3	41.8	87.0	.9	35.12	.01	.30	-2000.00	-2000.000	23.26	-2000.00
	4	19.7	68.0	3.1	47.68	100.00	.40	-2000.00	-2000.000	11.34	-2000.00
	5	19.8	103.0	2.0	74.77	100.00	.10	-2000.00	-2000.000	7.13	-2000.00
10375	1	308.6	129.0	1.6	31.61	.03	.30	-2000.00	-2000.000	2.85	-2000.00
	2	84.9	106.6	1.9	50.33	.01	.20	-2000.00	-2000.000	3.54	-2000.00
	3	35.0	87.0	2.0	78.21	1.00	.10	-2000.00	-2000.000	3.25	-2000.00
	4	27.5	115.0	.6	32.90	.01	.20	-2000.00	-2000.000	45.11	-2000.00
	5	21.9	137.0	1.9	35.23	100.00	.40	-2000.00	-2000.000	22.66	-2000.00
10400	1	462.4	139.6	1.6	43.15	.01	.20	-2000.00	-2000.000	3.23	-2000.00
	2	114.8	103.9	1.7	45.89	.01	.20	-2000.00	-2000.000	2.97	-2000.00
	3	78.8	142.3	1.4	31.42	.10	.20	-2000.00	-2000.000	5.40	-2000.00
	4	50.2	151.5	1.3	37.44	.01	.20	-2000.00	-2000.000	7.32	-2000.00
	5	41.7	188.8	1.3	12.57	1.00	.50	-2000.00	-2000.000	21.73	-2000.00
10425	1	402.3	143.0	1.5	41.12	.01	.20	-2000.00	-2000.000	3.62	-2000.00
	2	150.3	160.0	1.4	35.25	.03	.20	-2000.00	-2000.000	3.57	-2000.00
	3	88.4	188.0	1.4	34.57	.03	.20	-2000.00	-2000.000	8.36	-2000.00
	4	57.0	203.0	1.7	48.36	.01	.20	-2000.00	-2000.000	4.42	-2000.00
	5	42.3	226.0	2.2	35.92	.10	.30	-2000.00	-2000.000	3.15	-2000.00
10450	1	454.7	144.0	1.2	51.47	30.00	.10	-2000.00	-2000.000	33.13	-2000.00
	2	200.1	190.0	1.5	41.23	.01	.20	-2000.00	-2000.000	5.24	-2000.00
	3	122.7	230.0	2.0	52.74	.01	.20	-2000.00	-2000.000	2.42	-2000.00
	4	76.0	241.0	2.6	68.55	.01	.20	-2000.00	-2000.000	2.45	-2000.00
	5	49.6	236.0	1.7	39.46	.01	.20	-2000.00	-2000.000	24.54	-2000.00
10475	1	995.3	318.0	1.6	31.61	.03	.30	-2000.00	-2000.000	3.61	-2000.00
	2	427.1	410.0	2.6	66.93	.01	.20	-2000.00	-2000.000	2.09	-2000.00
	3	208.4	390.0	3.5	75.92	.10	.20	-2000.00	-2000.000	1.69	-2000.00
	4	113.2	360.0	2.7	58.89	.10	.20	-2000.00	-2000.000	1.72	-2000.00
	5	65.4	314.0	2.3	60.01	.01	.20	-2000.00	-2000.000	2.44	-2000.00
10500	1	1516.0	620.0	2.2	59.62	.01	.20	-2000.00	-2000.000	2.55	-2000.00
	2	648.7	804.0	3.8	89.33	.03	.20	-2000.00	-2000.000	1.85	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	294.6	720.0	3.3	76.75	.03	.20	-2000.00	-2000.000	1.35	-2000.00
	4	130.6	530.0	3.5	82.29	.03	.20	-2000.00	-2000.000	1.99	-2000.00
	5	89.0	551.0	3.1	73.22	.03	.20	-2000.00	-2000.000	2.01	-2000.00
10525	1	1507.0	690.0	3.2	75.67	.03	.20	-2000.00	-2000.000	2.20	-2000.00
	2	613.6	850.0	3.1	68.14	.10	.20	-2000.00	-2000.000	1.84	-2000.00
	3	284.8	780.0	3.4	80.09	.03	.20	-2000.00	-2000.000	1.58	-2000.00
	4	170.6	780.0	3.3	71.32	.10	.20	-2000.00	-2000.000	1.91	-2000.00
	5	76.8	532.0	2.8	117.90	.10	.10	-2000.00	-2000.000	6.32	-2000.00
10550	1	1376.0	900.0	2.5	58.63	.03	.20	-2000.00	-2000.000	1.74	-2000.00
	2	514.8	1010.0	3.2	76.24	.03	.20	-2000.00	-2000.000	1.73	-2000.00
	3	286.8	1120.0	3.1	66.55	.10	.20	-2000.00	-2000.000	1.72	-2000.00
	4	122.6	800.0	2.6	71.53	.01	.20	-2000.00	-2000.000	2.27	-2000.00
	5	124.3	1210.0	2.7	72.23	.01	.20	-2000.00	-2000.000	7.68	-2000.00
10575	1	820.4	696.0	2.6	42.58	.10	.30	-2000.00	-2000.000	2.52	-2000.00
	2	425.3	1082.0	2.5	61.20	.03	.20	-2000.00	-2000.000	2.09	-2000.00
	3	170.9	860.0	2.3	61.65	.01	.20	-2000.00	-2000.000	2.24	-2000.00
	4	165.1	1400.0	2.2	55.01	.01	.30	-2000.00	-2000.000	2.31	-2000.00
	5	126.2	1600.0	3.6	72.23	.03	.30	-2000.00	-2000.000	1.80	-2000.00
10600	1	1067.0	770.0	1.8	36.07	.03	.30	-2000.00	-2000.000	1.99	-2000.00
	2	391.1	856.0	1.8	35.69	.03	.30	-2000.00	-2000.000	2.67	-2000.00
	3	326.3	1420.0	1.8	43.50	.01	.30	-2000.00	-2000.000	1.61	-2000.00
	4	242.2	1760.0	3.1	76.63	.01	.30	-2000.00	-2000.000	1.11	-2000.00
	5	144.5	1580.0	8.8	184.14	.10	.20	-2000.00	-2000.000	1.84	-2000.00
10625	1	735.6	563.0	1.2	32.35	.03	.20	-2000.00	-2000.000	9.36	-2000.00
	2	510.3	1172.0	1.4	29.20	.03	.30	-2000.00	-2000.000	5.53	-2000.00
	3	368.9	1690.0	3.0	73.69	.01	.30	-2000.00	-2000.000	1.56	-2000.00
	4	178.6	1360.0	8.9	342.19	.01	.10	-2000.00	-2000.000	1.00	-2000.00
	5	88.1	1012.0	18.4	534.54	10.00	.10	-2000.00	-2000.000	.79	-2000.00
10650	1	946.3	724.0	1.4	28.65	.03	.30	-2000.00	-2000.000	4.67	-2000.00
	2	509.4	1170.0	2.9	71.02	.01	.30	-2000.00	-2000.000	2.43	-2000.00
	3	266.1	1220.0	8.8	338.27	.01	.10	-2000.00	-2000.000	1.22	-2000.00
	4	110.7	840.0	18.5	533.87	30.00	.10	-2000.00	-2000.000	.99	-2000.00
	5	34.0	390.0	20.0	564.55	10.00	.10	-2000.00	-2000.000	2.93	-2000.00
10675	1	1409.0	1000.0	3.7	73.55	.03	.30	-2000.00	-2000.000	1.79	-2000.00
	2	430.0	920.0	10.6	397.52	.01	.10	-2000.00	-2000.000	1.07	-2000.00
	3	165.0	700.0	19.5	552.25	30.00	.10	-2000.00	-2000.000	.89	-2000.00
	4	47.2	336.0	21.3	583.24	100.00	.10	-2000.00	-2000.000	1.55	-2000.00
	5	53.8	576.0	16.0	488.96	3.00	.10	-2000.00	-2000.000	1.00	-2000.00
10700	1	1163.0	910.0	12.1	443.48	.01	.10	-2000.00	-2000.000	.98	-2000.00
	2	304.4	716.0	20.9	579.19	30.00	.10	-2000.00	-2000.000	.90	-2000.00
	3	74.6	350.0	22.8	608.53	100.00	.10	-2000.00	-2000.000	1.18	-2000.00
	4	76.7	602.0	17.7	534.13	1.00	.10	-2000.00	-2000.000	.88	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	716.9	1125.0	19.9	557.39	100.00	.10	-2000.00	-2000.000	.79	-2000.00
	2	100.6	473.0	25.2	648.55	100.00	.10	-2000.00	-2000.000	1.22	-2000.00
	3	89.3	839.0	19.2	549.05	30.00	.10	-2000.00	-2000.000	.89	-2000.00
10750	1	143.7	451.0	25.2	398.07	10.00	.20	-2000.00	-2000.000	1.19	-2000.00
	2	91.8	864.3	21.1	579.79	100.00	.10	-2000.00	-2000.000	1.06	-2000.00
10775	1	220.6	860.0	21.4	365.02	.30	.20	-2000.00	-2000.000	3.85	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 804

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	380.9	127.0	1.1	50.24	1.00	.10	-2000.00	-2000.000	13.39	-2000.00
	2	124.1	124.0	1.5	36.38	.03	.20	-2000.00	-2000.000	3.43	-2000.00
	3	53.4	106.0	1.4	32.14	.10	.20	-2000.00	-2000.000	3.97	-2000.00
	4	32.2	107.0	1.3	33.50	.03	.20	-2000.00	-2000.000	4.69	-2000.00
	5	17.2	86.0	1.2	55.00	.10	.10	-2000.00	-2000.000	9.92	-2000.00
10350	1	453.9	146.0	1.0	48.88	30.00	.10	-2000.00	-2000.000	15.35	-2000.00
	2	119.7	116.0	1.4	35.36	.03	.20	-2000.00	-2000.000	4.12	-2000.00
	3	61.7	119.0	1.3	30.73	.10	.20	-2000.00	-2000.000	11.84	-2000.00
	4	28.7	92.0	1.2	51.24	1.00	.10	-2000.00	-2000.000	8.79	-2000.00
	5	19.1	92.0	1.2	52.85	1.00	.10	-2000.00	-2000.000	9.87	-2000.00
10375	1	466.6	138.2	1.0	48.74	30.00	.10	-2000.00	-2000.000	15.53	-2000.00
	2	147.3	130.9	1.2	55.82	.10	.10	-2000.00	-2000.000	10.77	-2000.00
	3	57.6	102.1	1.1	31.15	.03	.20	-2000.00	-2000.000	10.63	-2000.00
	4	31.2	92.3	1.8	40.87	100.00	.20	-2000.00	-2000.000	5.92	-2000.00
	5	25.0	110.9	.4	20.65	100.00	.30	-2000.00	-2000.000	50.68	-2000.00
10400	1	422.7	168.0	.7	20.97	100.00	.30	-2000.00	-2000.000	29.88	-2000.00
	2	93.1	110.9	1.3	56.76	.10	.10	-2000.00	-2000.000	5.85	-2000.00
	3	46.9	111.0	1.4	35.35	.03	.20	-2000.00	-2000.000	3.22	-2000.00
	4	30.0	119.0	.1	25.02	100.00	.20	-2000.00	-2000.000	78.20	-2000.00
	5	20.6	122.0	1.7	40.96	100.00	.50	-2000.00	-2000.000	20.23	-2000.00
10425	1	375.2	125.0	1.1	50.36	1.00	.10	-2000.00	-2000.000	16.00	-2000.00
	2	123.1	123.0	1.4	39.41	.01	.20	-2000.00	-2000.000	5.72	-2000.00
	3	62.5	124.0	1.2	29.99	.10	.20	-2000.00	-2000.000	17.65	-2000.00
	4	35.5	118.0	1.0	28.18	100.00	.20	-2000.00	-2000.000	15.92	-2000.00
	5	24.9	124.0	.8	26.80	100.00	.20	-2000.00	-2000.000	24.41	-2000.00
10450	1	503.0	153.3	1.0	48.31	1.00	.10	-2000.00	-2000.000	15.51	-2000.00
	2	170.2	155.6	1.1	51.39	1.00	.10	-2000.00	-2000.000	13.27	-2000.00
	3	78.6	143.3	1.1	51.03	1.00	.10	-2000.00	-2000.000	13.52	-2000.00
	4	49.7	151.4	1.3	56.22	1.00	.10	-2000.00	-2000.000	5.42	-2000.00
	5	41.3	189.0	1.3	27.96	30.00	.20	-2000.00	-2000.000	21.10	-2000.00
10475	1	578.7	181.7	.9	26.85	100.00	.20	-2000.00	-2000.000	22.04	-2000.00
	2	170.3	160.4	1.2	55.63	.10	.10	-2000.00	-2000.000	10.28	-2000.00
	3	92.4	173.7	1.4	34.56	.03	.20	-2000.00	-2000.000	4.83	-2000.00
	4	69.3	217.5	1.6	37.79	.03	.20	-2000.00	-2000.000	3.03	-2000.00
	5	62.2	292.7	1.2	32.89	.03	.20	-2000.00	-2000.000	9.23	-2000.00
10500	1	649.6	192.4	1.2	54.35	.10	.10	-2000.00	-2000.000	10.35	-2000.00
	2	253.4	225.1	1.7	27.63	.10	.30	-2000.00	-2000.000	1.76	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	161.7	286.0	1.9	17.45	.30	.50	-2000.00	-2000.000	2.77	-2000.00
	4	129.1	382.0	2.2	87.61	1.00	.10	-2000.00	-2000.000	3.68	-2000.00
	5	99.8	443.2	1.7	27.51	.10	.30	-2000.00	-2000.000	2.07	-2000.00
10525	1	534.2	304.0	1.6	26.34	.10	.30	-2000.00	-2000.000	3.83	-2000.00
	2	257.1	440.0	2.3	61.23	.01	.20	-2000.00	-2000.000	1.99	-2000.00
	3	184.8	630.0	2.6	69.08	.01	.20	-2000.00	-2000.000	1.75	-2000.00
	4	129.2	730.0	2.4	64.55	.01	.20	-2000.00	-2000.000	2.52	-2000.00
	5	67.0	573.0	2.2	42.48	.03	.30	-2000.00	-2000.000	2.44	-2000.00
10550	1	760.6	379.0	1.8	33.55	.03	.30	-2000.00	-2000.000	3.60	-2000.00
	2	455.4	680.0	2.5	59.42	.03	.20	-2000.00	-2000.000	2.50	-2000.00
	3	299.4	890.0	2.2	35.30	.10	.30	-2000.00	-2000.000	2.26	-2000.00
	4	148.2	730.0	2.2	54.88	.03	.20	-2000.00	-2000.000	3.26	-2000.00
	5	71.5	534.0	-1.0	40.05	100.00	.80	-2000.00	-2000.000	208.54	-2000.00
10575	1	883.7	504.0	1.9	31.85	.10	.30	-2000.00	-2000.000	3.75	-2000.00
	2	498.3	853.0	2.0	32.69	.10	.30	-2000.00	-2000.000	3.10	-2000.00
	3	233.1	790.0	2.0	38.03	.03	.30	-2000.00	-2000.000	2.70	-2000.00
	4	104.9	590.0	-1.0	40.05	100.00	.80	-2000.00	-2000.000	194.48	-2000.00
	5	136.7	1170.0	1.8	53.22	.01	.40	-2000.00	-2000.000	7.39	-2000.00
10600	1	984.0	657.0	1.4	39.94	.01	.20	-2000.00	-2000.000	7.67	-2000.00
	2	391.2	784.0	1.6	33.00	.03	.30	-2000.00	-2000.000	2.76	-2000.00
	3	158.8	630.0	-.8	40.05	100.00	.80	-2000.00	-2000.000	191.95	-2000.00
	4	191.9	1280.0	1.6	38.86	.03	.50	-2000.00	-2000.000	14.35	-2000.00
	5	93.9	940.0	17.1	506.10	30.00	.10	-2000.00	-2000.000	.90	-2000.00
10625	1	840.6	694.0	1.2	27.31	.03	.30	-2000.00	-2000.000	8.90	-2000.00
	2	261.9	649.0	-.9	40.05	100.00	.80	-2000.00	-2000.000	196.15	-2000.00
	3	283.0	1400.0	1.4	46.04	.01	.40	-2000.00	-2000.000	13.31	-2000.00
	4	129.7	1070.0	17.2	506.06	30.00	.10	-2000.00	-2000.000	.99	-2000.00
	5	45.0	558.0	19.6	548.75	100.00	.10	-2000.00	-2000.000	1.72	-2000.00
10650	1	640.8	428.0	-.7	40.05	100.00	.80	-2000.00	-2000.000	163.47	-2000.00
	2	555.1	1112.0	1.4	46.06	.01	.40	-2000.00	-2000.000	13.51	-2000.00
	3	237.0	940.0	17.1	508.21	10.00	.10	-2000.00	-2000.000	.89	-2000.00
	4	77.9	520.0	19.1	544.37	100.00	.10	-2000.00	-2000.000	1.02	-2000.00
	5	50.7	507.0	21.4	583.48	100.00	.10	-2000.00	-2000.000	1.24	-2000.00
10675	1	862.6	732.0	2.2	61.95	.01	.40	-2000.00	-2000.000	2.49	-2000.00
	2	295.0	751.0	18.1	525.46	30.00	.10	-2000.00	-2000.000	.97	-2000.00
	3	90.0	457.0	19.4	548.32	100.00	.10	-2000.00	-2000.000	1.14	-2000.00
	4	55.7	472.0	21.5	586.21	100.00	.10	-2000.00	-2000.000	.75	-2000.00
	5	59.0	750.0	13.9	436.74	10.00	.10	-2000.00	-2000.000	1.75	-2000.00
10700	1	453.2	569.0	19.7	562.81	10.00	.10	-2000.00	-2000.000	.70	-2000.00
	2	106.7	402.0	20.2	563.87	100.00	.10	-2000.00	-2000.000	.86	-2000.00
	3	60.2	452.0	21.9	592.68	100.00	.10	-2000.00	-2000.000	.90	-2000.00
	4	58.2	730.0	13.8	465.11	.10	.10	-2000.00	-2000.000	2.00	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	361.2	515.0	23.2	375.17	10.00	.20	-2000.00	-2000.000	1.39	-2000.00
	2	145.0	620.0	25.1	398.36	10.00	.20	-2000.00	-2000.000	1.27	-2000.00
	3	127.0	1080.0	16.0	495.89	1.00	.10	-2000.00	-2000.000	.93	-2000.00
10750	1	209.7	658.0	23.5	266.17	1.00	.30	-2000.00	-2000.000	3.05	-2000.00
	2	110.3	1039.0	17.3	217.62	.30	.30	-2000.00	-2000.000	4.45	-2000.00
10775	1	113.0	700.0	18.0	177.04	.30	.40	-2000.00	-2000.000	7.24	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 794

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
10325	1	723.3	212.2	.8	26.84	100.00	.20	-2000.00	-2000.000	23.63	-2000.00
	2	151.8	133.6	1.2	55.19	.10	.10	-2000.00	-2000.000	14.18	-2000.00
	3	76.2	133.8	1.2	51.72	100.00	.10	-2000.00	-2000.000	8.45	-2000.00
	4	36.9	108.3	1.2	55.57	.10	.10	-2000.00	-2000.000	10.18	-2000.00
	5	18.5	81.6	1.9	17.64	3.00	.40	-2000.00	-2000.000	6.78	-2000.00
10350	1	503.8	147.8	.8	26.63	100.00	.20	-2000.00	-2000.000	23.28	-2000.00
	2	122.4	107.7	1.2	54.53	.10	.10	-2000.00	-2000.000	10.92	-2000.00
	3	63.7	111.9	1.2	55.58	.10	.10	-2000.00	-2000.000	10.59	-2000.00
	4	28.3	82.9	1.0	50.80	.10	.10	-2000.00	-2000.000	88.91	-2000.00
	5	20.3	89.3	.9	26.93	100.00	.20	-2000.00	-2000.000	19.16	-2000.00
10375	1	524.5	152.4	1.0	27.10	100.00	.20	-2000.00	-2000.000	15.99	-2000.00
	2	144.9	126.3	1.2	53.86	.10	.10	-2000.00	-2000.000	9.35	-2000.00
	3	70.4	122.4	1.2	54.95	.10	.10	-2000.00	-2000.000	16.04	-2000.00
	4	32.6	94.8	1.0	28.75	100.00	.20	-2000.00	-2000.000	10.64	-2000.00
	5	17.5	76.1	.7	21.52	100.00	.50	-2000.00	-2000.000	29.54	-2000.00
10400	1	646.8	184.6	.9	48.00	100.00	.10	-2000.00	-2000.000	17.92	-2000.00
	2	131.5	112.6	1.1	53.24	.10	.10	-2000.00	-2000.000	11.31	-2000.00
	3	59.1	101.0	1.0	28.76	.10	.20	-2000.00	-2000.000	17.60	-2000.00
	4	27.5	78.5	.6	44.20	100.00	.80	-2000.00	-2000.000	48.68	-2000.00
	5	21.3	91.2	.8	19.74	100.00	.40	-2000.00	-2000.000	29.08	-2000.00
10425	1	393.5	112.3	.8	46.51	30.00	.10	-2000.00	-2000.000	22.13	-2000.00
	2	104.9	89.8	1.0	49.86	30.00	.10	-2000.00	-2000.000	13.41	-2000.00
	3	63.9	109.2	.7	25.57	100.00	.20	-2000.00	-2000.000	27.02	-2000.00
	4	31.2	89.0	.9	15.52	30.00	.40	-2000.00	-2000.000	32.26	-2000.00
	5	26.1	111.6	.7	19.30	100.00	.40	-2000.00	-2000.000	33.64	-2000.00
10450	1	629.2	205.0	.8	21.08	100.00	.30	-2000.00	-2000.000	25.67	-2000.00
	2	111.6	109.0	.9	26.14	100.00	.20	-2000.00	-2000.000	18.11	-2000.00
	3	61.8	121.0	.9	26.70	100.00	.20	-2000.00	-2000.000	20.17	-2000.00
	4	39.8	130.0	1.0	48.39	100.00	.10	-2000.00	-2000.000	18.45	-2000.00
	5	34.9	171.0	.9	27.28	100.00	.20	-2000.00	-2000.000	14.88	-2000.00
10475	1	460.7	149.0	.9	25.81	100.00	.20	-2000.00	-2000.000	24.56	-2000.00
	2	135.0	131.0	1.1	50.79	1.00	.10	-2000.00	-2000.000	11.33	-2000.00
	3	90.8	175.0	1.2	55.05	.10	.10	-2000.00	-2000.000	10.72	-2000.00
	4	64.7	209.0	1.3	30.51	.10	.20	-2000.00	-2000.000	6.85	-2000.00
	5	57.1	277.0	2.1	45.45	.10	.20	-2000.00	-2000.000	4.19	-2000.00
10500	1	485.6	139.8	.9	48.45	100.00	.10	-2000.00	-2000.000	15.77	-2000.00
	2	229.5	198.3	1.4	38.43	.01	.20	-2000.00	-2000.000	5.49	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	148.3	255.0	1.6	42.53	.01	.20	-2000.00	-2000.000	2.10	-2000.00
	4	107.0	308.0	2.4	63.60	.01	.20	-2000.00	-2000.000	1.82	-2000.00
	5	77.7	335.5	3.0	41.48	.30	.30	-2000.00	-2000.000	2.05	-2000.00
10525	1	941.9	264.0	1.4	35.08	.03	.20	-2000.00	-2000.000	5.60	-2000.00
	2	473.3	398.0	1.8	48.27	.01	.20	-2000.00	-2000.000	2.24	-2000.00
	3	297.6	499.0	2.9	68.52	.03	.20	-2000.00	-2000.000	1.34	-2000.00
	4	195.3	547.0	3.6	83.30	.03	.20	-2000.00	-2000.000	1.36	-2000.00
	5	172.1	723.0	3.7	79.52	.10	.20	-2000.00	-2000.000	1.96	-2000.00
10550	1	1335.0	399.0	1.1	53.47	.10	.10	-2000.00	-2000.000	12.03	-2000.00
	2	666.9	598.3	2.4	63.71	.01	.20	-2000.00	-2000.000	1.70	-2000.00
	3	456.3	816.0	3.3	71.52	.10	.20	-2000.00	-2000.000	1.66	-2000.00
	4	347.3	1038.0	3.7	86.47	.03	.20	-2000.00	-2000.000	1.33	-2000.00
	5	142.8	640.0	2.9	47.45	.10	.30	-2000.00	-2000.000	1.68	-2000.00
10575	1	1784.0	538.0	2.0	32.40	.10	.30	-2000.00	-2000.000	3.33	-2000.00
	2	964.9	873.9	3.0	72.18	.03	.20	-2000.00	-2000.000	2.28	-2000.00
	3	688.5	1244.0	3.5	82.32	.03	.20	-2000.00	-2000.000	1.99	-2000.00
	4	264.1	797.0	2.9	76.53	.01	.20	-2000.00	-2000.000	2.04	-2000.00
	5	123.7	560.0	1.0	26.54	.03	.40	-2000.00	-2000.000	22.09	-2000.00
10600	1	1411.0	730.0	2.7	70.78	.01	.20	-2000.00	-2000.000	2.17	-2000.00
	2	731.7	1148.0	3.4	79.30	.03	.20	-2000.00	-2000.000	1.71	-2000.00
	3	235.8	730.0	2.6	42.67	.10	.30	-2000.00	-2000.000	2.43	-2000.00
	4	106.8	550.0	.9	37.98	.01	.40	-2000.00	-2000.000	26.41	-2000.00
	5	81.1	636.0	5.8	133.50	.03	.20	-2000.00	-2000.000	1.54	-2000.00
10625	1	2486.0	1320.0	3.1	81.21	.01	.20	-2000.00	-2000.000	1.83	-2000.00
	2	661.4	1055.0	3.0	48.48	.10	.30	-2000.00	-2000.000	2.16	-2000.00
	3	252.9	800.0	1.2	41.52	.01	.40	-2000.00	-2000.000	14.68	-2000.00
	4	133.7	710.0	6.1	132.09	.10	.20	-2000.00	-2000.000	2.34	-2000.00
	5	85.2	680.0	13.4	431.37	1.00	.10	-2000.00	-2000.000	1.10	-2000.00
10650	1	1391.0	970.0	3.1	81.17	.01	.20	-2000.00	-2000.000	1.75	-2000.00
	2	358.9	751.0	1.5	46.30	.01	.40	-2000.00	-2000.000	5.20	-2000.00
	3	201.1	840.0	5.5	142.27	.01	.20	-2000.00	-2000.000	1.28	-2000.00
	4	106.7	740.0	13.6	427.55	30.00	.10	-2000.00	-2000.000	1.05	-2000.00
	5	56.6	591.0	18.2	546.19	1.00	.10	-2000.00	-2000.000	1.19	-2000.00
10675	1	912.4	636.0	1.6	47.44	.01	.40	-2000.00	-2000.000	4.23	-2000.00
	2	442.0	925.0	5.8	134.96	.03	.20	-2000.00	-2000.000	1.25	-2000.00
	3	210.6	870.0	13.5	427.40	10.00	.10	-2000.00	-2000.000	.94	-2000.00
	4	104.7	730.0	18.3	534.79	10.00	.10	-2000.00	-2000.000	1.22	-2000.00
	5	53.1	555.0	16.3	486.94	100.00	.10	-2000.00	-2000.000	1.04	-2000.00
10700	1	579.6	727.0	7.6	173.82	.03	.20	-2000.00	-2000.000	1.43	-2000.00
	2	171.4	645.0	14.7	458.43	3.00	.10	-2000.00	-2000.000	.94	-2000.00
	3	101.3	760.0	18.3	548.37	1.00	.10	-2000.00	-2000.000	1.06	-2000.00
	4	41.7	523.0	16.3	486.25	30.00	.10	-2000.00	-2000.000	1.24	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	411.5	717.0	17.0	528.27	.30	.10	-2000.00	-2000.000	.83	-2000.00
	2	130.4	682.0	19.7	604.93	.10	.10	-2000.00	-2000.000	1.07	-2000.00
	3	59.8	624.0	15.5	476.66	3.00	.10	-2000.00	-2000.000	1.12	-2000.00
10750	1	251.6	980.0	19.0	236.68	.30	.30	-2000.00	-2000.000	4.72	-2000.00
	2	76.2	897.0	14.7	145.37	.30	.40	-2000.00	-2000.000	7.17	-2000.00
10775	1	134.4	840.0	15.9	156.19	.30	.40	-2000.00	-2000.000	8.09	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 784

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	592.8	221.0	.7	20.80	100.00	.30	-2000.00	-2000.000	31.22	-2000.00
	2	123.5	138.0	.8	25.72	100.00	.20	-2000.00	-2000.000	23.90	-2000.00
	3	45.6	102.0	.9	27.30	100.00	.20	-2000.00	-2000.000	21.91	-2000.00
	4	24.4	91.0	.9	49.12	1.00	.10	-2000.00	-2000.000	17.40	-2000.00
	5	13.5	75.0	.8	21.23	100.00	.30	-2000.00	-2000.000	29.00	-2000.00
10350	1	602.9	189.3	.6	19.84	100.00	.40	-2000.00	-2000.000	36.84	-2000.00
	2	126.0	118.6	.9	48.58	30.00	.10	-2000.00	-2000.000	18.09	-2000.00
	3	62.1	116.7	1.2	53.99	.10	.10	-2000.00	-2000.000	9.97	-2000.00
	4	28.0	88.0	.9	48.25	30.00	.10	-2000.00	-2000.000	19.43	-2000.00
	5	19.3	90.9	.7	21.35	100.00	.30	-2000.00	-2000.000	29.29	-2000.00
10375	1	547.1	170.0	.8	46.87	30.00	.10	-2000.00	-2000.000	22.17	-2000.00
	2	147.2	137.2	1.3	33.61	.03	.20	-2000.00	-2000.000	7.02	-2000.00
	3	56.7	105.4	.7	26.34	100.00	.20	-2000.00	-2000.000	43.26	-2000.00
	4	27.9	86.6	1.7	37.02	100.00	.30	-2000.00	-2000.000	18.66	-2000.00
	5	20.4	95.1	.9	48.89	1.00	.10	-2000.00	-2000.000	20.56	-2000.00
10400	1	632.3	206.0	.9	47.41	30.00	.10	-2000.00	-2000.000	20.34	-2000.00
	2	118.2	115.0	1.1	50.51	30.00	.10	-2000.00	-2000.000	12.78	-2000.00
	3	58.3	114.0	1.0	48.62	30.00	.10	-2000.00	-2000.000	12.16	-2000.00
	4	32.7	106.0	.8	50.11	100.00	.80	-2000.00	-2000.000	79.97	-2000.00
	5	15.7	77.0	1.3	16.25	.30	.70	-2000.00	-2000.000	80.06	-2000.00
10425	1	378.2	107.9	.7	20.15	100.00	.30	-2000.00	-2000.000	28.77	-2000.00
	2	124.8	106.8	1.1	51.11	30.00	.10	-2000.00	-2000.000	13.03	-2000.00
	3	52.0	88.9	1.1	51.22	30.00	.10	-2000.00	-2000.000	20.34	-2000.00
	4	23.9	68.1	.4	19.70	100.00	.40	-2000.00	-2000.000	39.35	-2000.00
	5	21.6	92.4	-.1	40.05	100.00	.80	-2000.00	-2000.000	112.39	-2000.00
10450	1	491.6	116.0	1.1	49.61	30.00	.10	-2000.00	-2000.000	10.00	-2000.00
	2	148.2	104.9	1.3	32.91	.03	.20	-2000.00	-2000.000	7.71	-2000.00
	3	64.2	90.7	1.0	47.84	30.00	.10	-2000.00	-2000.000	14.80	-2000.00
	4	41.6	98.1	.1	42.00	100.00	.80	-2000.00	-2000.000	70.94	-2000.00
	5	37.9	134.2	.3	20.71	100.00	.50	-2000.00	-2000.000	58.03	-2000.00
10475	1	537.7	162.3	1.1	30.61	.03	.20	-2000.00	-2000.000	13.31	-2000.00
	2	107.6	97.4	1.0	49.36	30.00	.10	-2000.00	-2000.000	15.43	-2000.00
	3	66.8	120.8	.3	33.00	100.00	.70	-2000.00	-2000.000	55.91	-2000.00
	4	42.3	127.8	.8	21.18	100.00	.30	-2000.00	-2000.000	26.39	-2000.00
	5	39.7	179.8	1.3	33.36	.03	.20	-2000.00	-2000.000	9.02	-2000.00
10500	1	334.6	131.0	.8	21.05	100.00	.30	-2000.00	-2000.000	25.15	-2000.00
	2	123.5	145.0	.7	19.92	100.00	.30	-2000.00	-2000.000	27.98	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	69.5	163.0	1.0	52.80	.10	.10	-2000.00	-2000.000	19.03	-2000.00
	4	52.5	206.0	1.8	75.03	.01	.10	-2000.00	-2000.000	4.12	-2000.00
	5	46.4	273.0	2.8	66.68	.03	.20	-2000.00	-2000.000	2.30	-2000.00
10525	1	750.7	204.9	.8	26.58	100.00	.20	-2000.00	-2000.000	22.24	-2000.00
	2	274.7	225.0	1.5	30.32	.03	.30	-2000.00	-2000.000	2.80	-2000.00
	3	194.0	317.0	2.1	55.93	.01	.20	-2000.00	-2000.000	1.50	-2000.00
	4	141.8	387.0	3.4	79.84	.03	.20	-2000.00	-2000.000	1.36	-2000.00
	5	107.2	439.0	3.8	81.56	.10	.20	-2000.00	-2000.000	1.69	-2000.00
10550	1	994.4	343.0	1.4	30.47	.03	.30	-2000.00	-2000.000	5.73	-2000.00
	2	500.9	518.0	2.3	37.76	.10	.30	-2000.00	-2000.000	2.27	-2000.00
	3	346.0	710.0	3.7	95.16	.01	.20	-2000.00	-2000.000	1.23	-2000.00
	4	231.8	790.0	4.6	179.48	.10	.10	-2000.00	-2000.000	1.92	-2000.00
	5	126.2	650.0	3.0	82.30	.01	.20	-2000.00	-2000.000	2.09	-2000.00
10575	1	1938.0	690.0	1.7	33.14	.03	.30	-2000.00	-2000.000	2.80	-2000.00
	2	898.7	973.0	3.5	83.05	.03	.20	-2000.00	-2000.000	1.42	-2000.00
	3	612.7	1320.0	4.3	92.61	.10	.20	-2000.00	-2000.000	1.39	-2000.00
	4	304.0	1090.0	3.1	82.22	.01	.20	-2000.00	-2000.000	1.71	-2000.00
	5	50.8	275.0	2.8	21.77	.30	.70	-2000.00	-2000.000	13.77	-2000.00
10600	1	2001.0	860.0	3.6	85.32	.03	.20	-2000.00	-2000.000	1.93	-2000.00
	2	902.1	1164.0	3.9	83.41	.10	.20	-2000.00	-2000.000	1.27	-2000.00
	3	337.4	860.0	3.1	81.33	.01	.20	-2000.00	-2000.000	1.62	-2000.00
	4	62.2	267.0	3.1	75.97	.01	.30	-2000.00	-2000.000	2.00	-2000.00
	5	82.3	530.0	3.2	78.31	.01	.30	-2000.00	-2000.000	2.27	-2000.00
10625	1	3274.0	1370.0	4.1	89.05	.10	.20	-2000.00	-2000.000	1.74	-2000.00
	2	826.6	1038.0	3.1	82.38	.01	.20	-2000.00	-2000.000	1.94	-2000.00
	3	165.4	410.0	3.3	66.37	.03	.30	-2000.00	-2000.000	2.10	-2000.00
	4	149.7	620.0	3.2	79.69	.01	.30	-2000.00	-2000.000	1.76	-2000.00
	5	149.9	940.0	3.5	82.87	.03	.20	-2000.00	-2000.000	2.32	-2000.00
10650	1	3006.0	1680.0	3.0	59.46	.03	.30	-2000.00	-2000.000	2.05	-2000.00
	2	288.1	484.0	3.2	63.83	.03	.30	-2000.00	-2000.000	1.93	-2000.00
	3	249.7	830.0	3.2	81.08	.01	.30	-2000.00	-2000.000	2.46	-2000.00
	4	214.9	1200.0	3.4	92.10	.01	.20	-2000.00	-2000.000	2.55	-2000.00
	5	99.1	833.0	10.8	401.99	.01	.10	-2000.00	-2000.000	.98	-2000.00
10675	1	434.3	358.0	2.9	57.69	.03	.30	-2000.00	-2000.000	2.00	-2000.00
	2	320.4	794.0	3.4	82.73	.01	.30	-2000.00	-2000.000	1.68	-2000.00
	3	246.5	1210.0	3.4	54.64	.10	.30	-2000.00	-2000.000	1.51	-2000.00
	4	104.7	860.0	11.1	411.61	.01	.10	-2000.00	-2000.000	.73	-2000.00
	5	69.4	860.0	18.0	523.63	30.00	.10	-2000.00	-2000.000	.96	-2000.00
10700	1	551.3	786.0	4.3	85.25	.03	.30	-2000.00	-2000.000	1.97	-2000.00
	2	259.6	1111.0	3.3	53.98	.10	.30	-2000.00	-2000.000	2.76	-2000.00
	3	122.3	1040.0	11.5	397.82	.10	.10	-2000.00	-2000.000	.79	-2000.00
	4	65.4	933.0	18.3	532.87	10.00	.10	-2000.00	-2000.000	1.00	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	472.7	989.0	5.0	42.73	.30	.60	-2000.00	-2000.000	6.84	-2000.00
	2	141.5	888.0	14.3	475.21	.10	.10	-2000.00	-2000.000	1.18	-2000.00
	3	67.5	846.0	19.9	575.64	3.00	.10	-2000.00	-2000.000	1.26	-2000.00
10750	1	304.9	797.0	16.2	489.74	10.00	.10	-2000.00	-2000.000	.71	-2000.00
	2	143.9	1129.0	21.8	595.87	30.00	.10	-2000.00	-2000.000	.88	-2000.00
10775	1	360.3	1880.0	21.1	258.25	.30	.30	-2000.00	-2000.000	5.15	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 774

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	531.9	196.0	.7	20.48	100.00	.30	-2000.00	-2000.000	30.28	-2000.00
	2	124.9	138.0	1.0	48.89	30.00	.10	-2000.00	-2000.000	17.50	-2000.00
	3	49.3	108.0	.8	26.28	100.00	.20	-2000.00	-2000.000	19.57	-2000.00
	4	21.9	80.0	.9	27.35	100.00	.20	-2000.00	-2000.000	20.73	-2000.00
	5	12.9	71.0	.8	47.10	100.00	.10	-2000.00	-2000.000	20.88	-2000.00
10350	1	570.9	188.0	.7	46.25	30.00	.10	-2000.00	-2000.000	30.34	-2000.00
	2	137.1	135.0	1.0	48.60	1.00	.10	-2000.00	-2000.000	17.12	-2000.00
	3	48.9	96.0	.9	48.29	100.00	.10	-2000.00	-2000.000	22.12	-2000.00
	4	25.8	85.0	.9	47.80	30.00	.10	-2000.00	-2000.000	15.07	-2000.00
	5	15.3	75.0	.9	47.06	30.00	.10	-2000.00	-2000.000	15.28	-2000.00
10375	1	397.5	134.0	.7	20.11	100.00	.30	-2000.00	-2000.000	29.73	-2000.00
	2	112.4	113.0	.9	48.49	30.00	.10	-2000.00	-2000.000	15.82	-2000.00
	3	51.2	103.0	1.1	50.58	1.00	.10	-2000.00	-2000.000	15.14	-2000.00
	4	25.6	86.0	.7	26.61	100.00	.20	-2000.00	-2000.000	20.52	-2000.00
	5	13.1	66.0	.8	25.91	100.00	.20	-2000.00	-2000.000	21.78	-2000.00
10400	1	498.2	164.0	.9	47.66	30.00	.10	-2000.00	-2000.000	18.86	-2000.00
	2	129.2	128.0	1.1	53.48	.10	.10	-2000.00	-2000.000	12.88	-2000.00
	3	54.0	106.0	.9	52.23	.10	.10	-2000.00	-2000.000	33.80	-2000.00
	4	23.1	76.0	1.5	42.15	100.00	.60	-2000.00	-2000.000	29.43	-2000.00
	5	13.0	64.0	.7	21.13	100.00	.30	-2000.00	-2000.000	26.88	-2000.00
10425	1	477.9	144.2	1.0	50.37	.10	.10	-2000.00	-2000.000	16.19	-2000.00
	2	111.0	100.5	1.0	51.03	.10	.10	-2000.00	-2000.000	14.11	-2000.00
	3	47.4	85.6	1.0	48.63	30.00	.10	-2000.00	-2000.000	12.18	-2000.00
	4	21.2	64.0	.8	21.68	100.00	.30	-2000.00	-2000.000	33.46	-2000.00
	5	14.1	63.9	.1	32.83	100.00	.70	-2000.00	-2000.000	87.64	-2000.00
10450	1	504.9	158.5	.9	48.15	30.00	.10	-2000.00	-2000.000	18.91	-2000.00
	2	100.6	94.7	1.1	51.10	1.00	.10	-2000.00	-2000.000	13.89	-2000.00
	3	47.2	88.7	1.1	22.45	100.00	.30	-2000.00	-2000.000	11.69	-2000.00
	4	23.8	74.8	.9	48.92	1.00	.10	-2000.00	-2000.000	19.11	-2000.00
	5	21.9	103.3	-.4	40.05	100.00	.80	-2000.00	-2000.000	131.25	-2000.00
10475	1	219.3	105.0	.9	25.32	30.00	.20	-2000.00	-2000.000	21.43	-2000.00
	2	72.5	105.0	1.2	54.38	.10	.10	-2000.00	-2000.000	9.01	-2000.00
	3	29.3	84.0	.8	18.10	30.00	.30	-2000.00	-2000.000	25.12	-2000.00
	4	23.5	113.0	.0	41.47	100.00	.80	-2000.00	-2000.000	75.17	-2000.00
	5	24.4	176.0	.1	20.80	100.00	.50	-2000.00	-2000.000	63.62	-2000.00
10500	1	372.7	117.0	1.2	54.29	.10	.10	-2000.00	-2000.000	9.34	-2000.00
	2	111.4	104.9	1.3	37.68	.01	.20	-2000.00	-2000.000	8.09	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	70.9	133.2	.5	25.00	100.00	.60	-2000.00	-2000.000	42.46	-2000.00
	4	64.2	201.4	.9	47.44	30.00	.10	-2000.00	-2000.000	15.85	-2000.00
	5	97.6	459.6	2.6	41.35	.10	.30	-2000.00	-2000.000	1.70	-2000.00
10525	1	247.0	106.0	2.0	23.66	3.00	.30	-2000.00	-2000.000	19.87	-2000.00
	2	96.5	124.4	1.0	48.04	30.00	.10	-2000.00	-2000.000	15.30	-2000.00
	3	88.6	228.0	1.1	52.50	.10	.10	-2000.00	-2000.000	11.18	-2000.00
	4	111.0	470.0	3.0	70.13	.03	.20	-2000.00	-2000.000	3.04	-2000.00
	5	41.5	267.0	2.9	124.30	.01	.10	-2000.00	-2000.000	5.87	-2000.00
10550	1	346.9	117.0	1.0	52.41	.10	.10	-2000.00	-2000.000	15.83	-2000.00
	2	250.2	253.0	1.8	43.88	.01	.30	-2000.00	-2000.000	2.45	-2000.00
	3	256.1	510.0	3.1	76.98	.03	.20	-2000.00	-2000.000	2.90	-2000.00
	4	86.5	292.0	3.7	32.19	.30	.50	-2000.00	-2000.000	5.86	-2000.00
	5	34.3	173.0	.8	46.81	100.00	.10	-2000.00	-2000.000	19.54	-2000.00
10575	1	1072.0	440.0	1.8	43.82	.01	.30	-2000.00	-2000.000	2.39	-2000.00
	2	771.0	968.0	3.5	84.07	.03	.20	-2000.00	-2000.000	1.41	-2000.00
	3	228.3	570.0	4.5	188.62	.01	.10	-2000.00	-2000.000	3.03	-2000.00
	4	73.0	305.0	1.1	33.66	.01	.30	-2000.00	-2000.000	28.29	-2000.00
	5	33.3	208.0	1.3	28.72	.03	.30	-2000.00	-2000.000	9.30	-2000.00
10600	1	2847.0	1480.0	3.5	89.95	.01	.20	-2000.00	-2000.000	1.47	-2000.00
	2	565.5	887.0	4.6	107.96	.03	.20	-2000.00	-2000.000	1.40	-2000.00
	3	178.1	550.0	2.5	65.12	.01	.20	-2000.00	-2000.000	1.41	-2000.00
	4	72.9	381.0	1.6	40.82	.01	.30	-2000.00	-2000.000	6.90	-2000.00
	5	47.5	372.0	1.1	34.46	.01	.30	-2000.00	-2000.000	22.13	-2000.00
10625	1	1840.0	800.0	5.3	112.38	.10	.20	-2000.00	-2000.000	1.38	-2000.00
	2	456.6	597.0	3.2	69.81	.10	.20	-2000.00	-2000.000	1.35	-2000.00
	3	172.7	450.0	2.4	62.44	.01	.20	-2000.00	-2000.000	1.43	-2000.00
	4	107.2	460.0	2.1	51.36	.01	.30	-2000.00	-2000.000	2.05	-2000.00
	5	84.0	549.0	2.6	35.68	.10	.40	-2000.00	-2000.000	3.20	-2000.00
10650	1	1685.0	830.0	4.7	100.20	.10	.20	-2000.00	-2000.000	2.04	-2000.00
	2	554.1	828.0	4.1	96.92	.03	.20	-2000.00	-2000.000	1.58	-2000.00
	3	280.3	830.0	3.6	95.77	.01	.20	-2000.00	-2000.000	1.72	-2000.00
	4	201.2	1000.0	4.1	80.64	.03	.30	-2000.00	-2000.000	1.70	-2000.00
	5	110.0	820.0	7.3	153.22	.10	.20	-2000.00	-2000.000	1.26	-2000.00
10675	1	1988.0	1320.0	2.5	49.46	.03	.30	-2000.00	-2000.000	1.61	-2000.00
	2	626.4	1255.0	2.9	56.12	.03	.30	-2000.00	-2000.000	2.26	-2000.00
	3	342.9	1370.0	3.9	76.08	.03	.30	-2000.00	-2000.000	.99	-2000.00
	4	156.2	1040.0	7.6	158.34	.10	.20	-2000.00	-2000.000	1.15	-2000.00
	5	126.7	1260.0	8.8	330.29	.01	.10	-2000.00	-2000.000	1.53	-2000.00
10700	1	1336.0	830.0	2.3	45.28	.03	.30	-2000.00	-2000.000	1.94	-2000.00
	2	518.7	977.0	3.9	76.92	.03	.30	-2000.00	-2000.000	2.21	-2000.00
	3	227.2	850.0	7.8	303.09	.01	.10	-2000.00	-2000.000	.87	-2000.00
	4	143.4	900.0	8.7	333.46	.01	.10	-2000.00	-2000.000	1.29	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	1867.0	1300.0	5.4	139.06	.01	.20	-2000.00	-2000.000	1.31	-2000.00
	2	398.3	833.0	9.0	343.58	.01	.10	-2000.00	-2000.000	.96	-2000.00
	3	254.1	1060.0	10.1	378.81	.01	.10	-2000.00	-2000.000	1.00	-2000.00
10750	1	513.3	732.0	9.3	344.22	.03	.10	-2000.00	-2000.000	.69	-2000.00
	2	241.7	1034.0	12.1	412.89	.10	.10	-2000.00	-2000.000	1.08	-2000.00
10775	1	568.4	1189.0	12.3	420.28	.10	.10	-2000.00	-2000.000	.89	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 764

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	342.5	155.0	.8	25.48	100.00	.20	-2000.00	-2000.000	24.57	-2000.00
	2	95.3	130.1	1.1	31.36	.03	.20	-2000.00	-2000.000	14.07	-2000.00
	3	36.0	98.0	1.0	47.87	30.00	.10	-2000.00	-2000.000	15.15	-2000.00
	4	17.7	80.0	.7	27.20	100.00	.20	-2000.00	-2000.000	26.76	-2000.00
	5	10.6	72.0	.8	21.44	100.00	.30	-2000.00	-2000.000	29.14	-2000.00
10350	1	433.3	154.0	.7	20.46	100.00	.30	-2000.00	-2000.000	26.59	-2000.00
	2	99.1	106.0	1.0	30.13	.03	.20	-2000.00	-2000.000	14.12	-2000.00
	3	39.7	84.0	.7	25.97	100.00	.20	-2000.00	-2000.000	31.51	-2000.00
	4	21.5	76.0	1.2	20.92	30.00	.30	-2000.00	-2000.000	11.89	-2000.00
	5	13.5	72.0	.6	24.63	100.00	.20	-2000.00	-2000.000	42.71	-2000.00
10375	1	481.3	164.0	.9	48.27	1.00	.10	-2000.00	-2000.000	19.93	-2000.00
	2	105.5	108.0	1.1	31.19	.03	.20	-2000.00	-2000.000	10.93	-2000.00
	3	46.0	93.0	.8	25.73	100.00	.20	-2000.00	-2000.000	26.04	-2000.00
	4	24.0	82.0	1.0	28.20	100.00	.20	-2000.00	-2000.000	16.01	-2000.00
	5	13.4	68.0	.5	19.22	100.00	.40	-2000.00	-2000.000	42.98	-2000.00
10400	1	453.6	149.0	1.0	48.80	1.00	.10	-2000.00	-2000.000	13.47	-2000.00
	2	110.0	109.0	1.2	32.29	.03	.20	-2000.00	-2000.000	10.90	-2000.00
	3	49.6	98.0	1.2	54.43	.10	.10	-2000.00	-2000.000	11.99	-2000.00
	4	22.9	75.0	.6	20.56	100.00	.50	-2000.00	-2000.000	34.28	-2000.00
	5	15.3	75.0	.7	47.83	.10	.10	-2000.00	-2000.000	40.77	-2000.00
10425	1	393.1	148.0	.9	47.88	30.00	.10	-2000.00	-2000.000	19.63	-2000.00
	2	99.2	112.5	1.6	42.45	.01	.20	-2000.00	-2000.000	2.84	-2000.00
	3	40.2	91.0	.5	19.29	100.00	.30	-2000.00	-2000.000	41.94	-2000.00
	4	21.3	80.0	1.3	56.67	1.00	.10	-2000.00	-2000.000	13.37	-2000.00
	5	11.8	66.0	-.7	42.23	30.00	.10	-2000.00	-2000.000	103.88	-2000.00
10450	1	374.6	138.0	1.4	38.87	.01	.20	-2000.00	-2000.000	6.98	-2000.00
	2	93.5	103.6	1.1	51.16	30.00	.10	-2000.00	-2000.000	13.55	-2000.00
	3	42.4	93.0	1.2	34.90	.01	.20	-2000.00	-2000.000	15.90	-2000.00
	4	19.8	73.0	1.0	27.72	100.00	.20	-2000.00	-2000.000	19.42	-2000.00
	5	14.9	82.0	.6	20.03	100.00	.30	-2000.00	-2000.000	35.03	-2000.00
10475	1	235.1	123.0	.9	26.15	100.00	.20	-2000.00	-2000.000	19.68	-2000.00
	2	70.9	111.3	1.7	41.75	.01	.30	-2000.00	-2000.000	4.79	-2000.00
	3	27.6	86.0	.9	27.44	100.00	.20	-2000.00	-2000.000	22.02	-2000.00
	4	17.5	91.0	.8	25.82	100.00	.20	-2000.00	-2000.000	21.51	-2000.00
	5	28.9	227.0	1.5	32.27	.03	.30	-2000.00	-2000.000	9.28	-2000.00
10500	1	302.2	145.0	4.0	103.76	.01	.20	-2000.00	-2000.000	2.62	-2000.00
	2	69.2	100.3	1.5	40.89	.01	.20	-2000.00	-2000.000	5.35	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	42.2	122.0	1.2	36.64	.01	.20	-2000.00	-2000.000	11.47	-2000.00
	4	41.7	201.0	1.7	33.97	.03	.30	-2000.00	-2000.000	2.93	-2000.00
	5	20.6	149.0	1.8	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10525	1	201.0	123.0	.6	20.18	100.00	.30	-2000.00	-2000.000	40.20	-2000.00
	2	68.6	126.7	1.3	28.21	.03	.30	-2000.00	-2000.000	7.47	-2000.00
	3	58.4	215.0	1.3	29.23	.03	.40	-2000.00	-2000.000	10.72	-2000.00
	4	23.4	144.0	1.9	36.01	100.00	.50	-2000.00	-2000.000	13.24	-2000.00
	5	16.8	155.0	.4	25.07	100.00	.60	-2000.00	-2000.000	62.01	-2000.00
10550	1	262.9	150.0	2.0	16.97	.30	.50	-2000.00	-2000.000	33.85	-2000.00
	2	138.3	236.0	2.2	55.72	.01	.30	-2000.00	-2000.000	2.77	-2000.00
	3	46.4	158.0	1.2	32.37	.03	.20	-2000.00	-2000.000	10.06	-2000.00
	4	28.2	160.0	.7	20.17	100.00	.30	-2000.00	-2000.000	27.60	-2000.00
	5	24.2	206.0	1.2	27.85	.03	.30	-2000.00	-2000.000	10.16	-2000.00
10575	1	709.1	278.0	2.6	42.37	.10	.30	-2000.00	-2000.000	2.68	-2000.00
	2	144.8	170.0	2.2	42.05	.03	.30	-2000.00	-2000.000	2.72	-2000.00
	3	73.8	173.0	1.2	36.40	.01	.20	-2000.00	-2000.000	11.88	-2000.00
	4	57.5	225.0	2.0	39.65	.03	.30	-2000.00	-2000.000	1.95	-2000.00
	5	28.3	166.0	1.3	34.08	.01	.30	-2000.00	-2000.000	14.93	-2000.00
10600	1	1468.0	650.0	3.1	72.93	.03	.20	-2000.00	-2000.000	1.54	-2000.00
	2	383.3	515.0	3.3	78.32	.03	.20	-2000.00	-2000.000	2.64	-2000.00
	3	228.9	610.0	4.0	102.45	.01	.20	-2000.00	-2000.000	1.42	-2000.00
	4	93.7	420.0	4.0	93.96	.03	.20	-2000.00	-2000.000	1.44	-2000.00
	5	43.9	295.0	3.0	48.02	.10	.30	-2000.00	-2000.000	1.91	-2000.00
10625	1	2313.0	1030.0	3.8	81.91	.10	.20	-2000.00	-2000.000	1.59	-2000.00
	2	1106.0	1480.0	5.1	119.70	.03	.20	-2000.00	-2000.000	1.42	-2000.00
	3	400.1	1070.0	5.3	124.07	.03	.20	-2000.00	-2000.000	2.48	-2000.00
	4	172.1	770.0	4.7	108.92	.03	.20	-2000.00	-2000.000	1.59	-2000.00
	5	116.7	780.0	4.9	114.65	.03	.20	-2000.00	-2000.000	3.89	-2000.00
10650	1	1437.0	1120.0	3.5	92.36	.01	.20	-2000.00	-2000.000	1.81	-2000.00
	2	413.5	973.0	4.7	109.97	.03	.20	-2000.00	-2000.000	2.17	-2000.00
	3	190.6	890.0	3.9	62.52	.10	.30	-2000.00	-2000.000	3.46	-2000.00
	4	118.0	920.0	4.1	109.87	.01	.20	-2000.00	-2000.000	2.26	-2000.00
	5	68.6	808.0	4.4	102.12	.03	.20	-2000.00	-2000.000	2.16	-2000.00
10675	1	964.2	672.0	3.5	56.13	.10	.30	-2000.00	-2000.000	2.27	-2000.00
	2	372.6	779.0	3.4	55.56	.10	.30	-2000.00	-2000.000	3.28	-2000.00
	3	216.5	900.0	3.7	59.52	.10	.30	-2000.00	-2000.000	2.69	-2000.00
	4	120.6	840.0	3.8	99.56	.01	.20	-2000.00	-2000.000	1.40	-2000.00
	5	100.0	1040.0	3.8	60.93	.10	.30	-2000.00	-2000.000	2.61	-2000.00
10700	1	346.3	724.0	2.4	46.72	.03	.30	-2000.00	-2000.000	1.87	-2000.00
	2	143.2	899.0	3.2	62.31	.03	.30	-2000.00	-2000.000	1.91	-2000.00
	3	94.6	1185.0	3.2	61.90	.03	.30	-2000.00	-2000.000	2.42	-2000.00
	4	56.9	1191.0	3.5	103.24	.01	.20	-2000.00	-2000.000	8.09	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	229.2	790.0	2.3	44.60	.03	.30	-2000.00	-2000.000	1.51	-2000.00
	2	107.0	1110.0	3.1	60.83	.03	.30	-2000.00	-2000.000	3.98	-2000.00
	3	56.3	1170.0	3.3	65.61	.03	.30	-2000.00	-2000.000	4.43	-2000.00
10750	1	250.9	870.0	2.7	65.06	.01	.30	-2000.00	-2000.000	2.18	-2000.00
	2	113.0	1180.0	3.9	62.71	.10	.30	-2000.00	-2000.000	4.12	-2000.00
10775	1	379.7	1192.0	3.3	87.53	.01	.20	-2000.00	-2000.000	2.12	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 754

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	419.7	155.0	.5	21.19	100.00	.50	-2000.00	-2000.000	43.64	-2000.00
	2	157.7	174.0	.7	20.17	100.00	.30	-2000.00	-2000.000	25.07	-2000.00
	3	69.8	154.0	1.2	54.70	.10	.10	-2000.00	-2000.000	9.50	-2000.00
	4	29.4	108.0	.7	49.40	.10	.10	-2000.00	-2000.000	23.55	-2000.00
	5	18.7	103.0	1.5	31.56	30.00	.20	-2000.00	-2000.000	10.39	-2000.00
10350	1	569.6	198.0	.7	20.06	100.00	.30	-2000.00	-2000.000	29.12	-2000.00
	2	130.9	137.0	1.0	49.24	30.00	.10	-2000.00	-2000.000	13.35	-2000.00
	3	54.2	113.0	1.0	48.96	30.00	.10	-2000.00	-2000.000	15.15	-2000.00
	4	25.5	88.0	1.0	49.92	1.00	.10	-2000.00	-2000.000	13.60	-2000.00
	5	16.6	86.0	.7	25.64	100.00	.20	-2000.00	-2000.000	27.50	-2000.00
10375	1	227.9	105.0	.8	26.27	100.00	.20	-2000.00	-2000.000	21.19	-2000.00
	2	69.8	96.6	.9	46.54	30.00	.10	-2000.00	-2000.000	20.79	-2000.00
	3	29.6	81.0	1.1	50.49	100.00	.10	-2000.00	-2000.000	11.34	-2000.00
	4	16.8	77.0	.0	32.86	100.00	.70	-2000.00	-2000.000	77.96	-2000.00
	5	10.1	70.0	1.6	6.70	1.00	.80	-2000.00	-2000.000	45.52	-2000.00
10400	1	266.5	104.0	1.0	48.98	30.00	.10	-2000.00	-2000.000	17.79	-2000.00
	2	76.1	89.5	1.1	52.39	.10	.10	-2000.00	-2000.000	11.40	-2000.00
	3	36.0	84.0	.9	26.30	100.00	.20	-2000.00	-2000.000	19.93	-2000.00
	4	19.5	76.0	.3	26.05	100.00	.60	-2000.00	-2000.000	54.93	-2000.00
	5	11.6	68.0	1.0	20.05	100.00	.30	-2000.00	-2000.000	19.25	-2000.00
10425	1	388.6	131.0	1.5	30.70	.03	.30	-2000.00	-2000.000	3.75	-2000.00
	2	102.8	104.0	1.3	33.50	.03	.20	-2000.00	-2000.000	9.42	-2000.00
	3	47.4	95.0	.9	21.47	100.00	.30	-2000.00	-2000.000	20.61	-2000.00
	4	21.8	73.0	.9	48.10	100.00	.10	-2000.00	-2000.000	19.37	-2000.00
	5	14.7	74.0	.5	25.31	100.00	.60	-2000.00	-2000.000	41.86	-2000.00
10450	1	430.7	142.0	1.4	36.97	.01	.30	-2000.00	-2000.000	10.81	-2000.00
	2	114.7	113.0	1.2	31.62	.03	.20	-2000.00	-2000.000	9.03	-2000.00
	3	42.7	84.0	1.0	49.65	30.00	.10	-2000.00	-2000.000	16.22	-2000.00
	4	27.0	89.0	.9	20.53	100.00	.30	-2000.00	-2000.000	17.79	-2000.00
	5	15.0	74.0	-.8	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10475	1	380.3	145.0	1.2	32.47	.03	.20	-2000.00	-2000.000	9.64	-2000.00
	2	93.0	106.7	1.6	42.37	.01	.20	-2000.00	-2000.000	3.12	-2000.00
	3	42.0	96.0	.9	26.74	100.00	.20	-2000.00	-2000.000	18.06	-2000.00
	4	22.4	85.0	1.3	57.42	30.00	.10	-2000.00	-2000.000	8.62	-2000.00
	5	13.1	75.0	.1	25.28	100.00	.20	-2000.00	-2000.000	80.04	-2000.00
10500	1	370.3	129.0	1.3	37.55	.01	.20	-2000.00	-2000.000	10.56	-2000.00
	2	104.8	109.0	1.0	48.56	30.00	.10	-2000.00	-2000.000	14.85	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	46.7	97.0	1.0	49.07	1.00	.10	-2000.00	-2000.000	22.15	-2000.00
	4	24.0	83.0	1.3	36.02	.03	.20	-2000.00	-2000.000	8.73	-2000.00
	5	24.6	128.0	.4	19.32	100.00	.40	-2000.00	-2000.000	48.92	-2000.00
10525	1	272.0	164.0	1.0	49.22	30.00	.10	-2000.00	-2000.000	12.29	-2000.00
	2	68.9	124.8	1.2	55.32	.10	.10	-2000.00	-2000.000	14.06	-2000.00
	3	27.1	98.0	1.4	35.36	.03	.20	-2000.00	-2000.000	5.85	-2000.00
	4	24.5	147.0	.7	25.94	100.00	.20	-2000.00	-2000.000	27.25	-2000.00
	5	21.8	197.0	1.0	47.52	1.00	.10	-2000.00	-2000.000	27.38	-2000.00
10550	1	314.6	119.0	1.3	37.48	.01	.20	-2000.00	-2000.000	6.07	-2000.00
	2	83.1	94.3	1.8	17.75	.30	.50	-2000.00	-2000.000	2.69	-2000.00
	3	60.1	136.0	1.0	49.82	1.00	.10	-2000.00	-2000.000	12.71	-2000.00
	4	55.9	211.0	1.3	23.78	.10	.30	-2000.00	-2000.000	5.73	-2000.00
	5	45.7	259.0	1.7	28.96	.03	.30	-2000.00	-2000.000	24.89	-2000.00
10575	1	327.4	128.0	2.2	42.91	.03	.30	-2000.00	-2000.000	1.79	-2000.00
	2	140.4	165.0	1.7	23.32	.10	.40	-2000.00	-2000.000	5.47	-2000.00
	3	106.4	250.0	1.8	34.37	.03	.30	-2000.00	-2000.000	1.72	-2000.00
	4	77.8	305.0	1.8	44.19	.01	.30	-2000.00	-2000.000	2.54	-2000.00
	5	48.1	283.0	2.4	46.21	.03	.30	-2000.00	-2000.000	11.02	-2000.00
10600	1	366.9	188.0	2.0	39.66	.03	.30	-2000.00	-2000.000	1.75	-2000.00
	2	200.2	309.0	2.5	48.90	.03	.30	-2000.00	-2000.000	1.90	-2000.00
	3	123.3	380.0	2.9	75.99	.01	.20	-2000.00	-2000.000	1.74	-2000.00
	4	68.1	350.0	3.2	42.62	.10	.40	-2000.00	-2000.000	4.24	-2000.00
	5	35.5	274.0	3.1	49.10	.10	.30	-2000.00	-2000.000	2.20	-2000.00
10625	1	728.8	394.0	2.2	43.09	.03	.30	-2000.00	-2000.000	1.51	-2000.00
	2	319.4	518.0	3.2	85.41	.01	.20	-2000.00	-2000.000	1.35	-2000.00
	3	142.3	460.0	3.8	61.28	.10	.30	-2000.00	-2000.000	.93	-2000.00
	4	69.1	374.0	3.9	102.57	.01	.20	-2000.00	-2000.000	1.48	-2000.00
	5	32.5	263.0	2.9	72.10	.01	.30	-2000.00	-2000.000	16.06	-2000.00
10650	1	1374.0	660.0	3.3	77.25	.03	.20	-2000.00	-2000.000	1.83	-2000.00
	2	479.2	694.0	4.2	98.91	.03	.20	-2000.00	-2000.000	1.51	-2000.00
	3	203.7	580.0	4.7	99.97	.10	.20	-2000.00	-2000.000	.98	-2000.00
	4	86.3	416.0	3.3	86.76	.01	.20	-2000.00	-2000.000	1.66	-2000.00
	5	63.8	462.0	2.8	53.82	.03	.30	-2000.00	-2000.000	4.40	-2000.00
10675	1	1409.0	740.0	3.6	94.51	.01	.20	-2000.00	-2000.000	2.89	-2000.00
	2	467.2	745.0	5.0	105.95	.10	.20	-2000.00	-2000.000	1.40	-2000.00
	3	202.3	640.0	3.6	84.45	.03	.20	-2000.00	-2000.000	1.16	-2000.00
	4	125.1	660.0	3.1	51.27	.10	.30	-2000.00	-2000.000	2.89	-2000.00
	5	122.0	970.0	2.8	45.78	.10	.30	-2000.00	-2000.000	2.83	-2000.00
10700	1	753.0	656.0	4.4	104.59	.03	.20	-2000.00	-2000.000	2.35	-2000.00
	2	293.9	769.0	3.5	92.80	.01	.20	-2000.00	-2000.000	1.63	-2000.00
	3	160.0	830.0	3.0	59.85	.03	.30	-2000.00	-2000.000	2.63	-2000.00
	4	144.2	1250.0	2.6	64.43	.01	.30	-2000.00	-2000.000	2.38	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	260.6	681.0	2.5	49.37	.03	.30	-2000.00	-2000.000	2.03	-2000.00
	2	120.8	948.0	2.6	63.80	.01	.30	-2000.00	-2000.000	2.14	-2000.00
	3	101.8	1590.0	2.2	42.12	.03	.40	-2000.00	-2000.000	3.83	-2000.00
10750	1	275.9	721.0	2.4	47.07	.03	.30	-2000.00	-2000.000	1.72	-2000.00
	2	173.6	1362.0	1.6	33.11	.03	.40	-2000.00	-2000.000	4.43	-2000.00
10775	1	341.6	1190.0	2.2	54.32	.01	.30	-2000.00	-2000.000	2.65	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 744

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	536.8	156.0	1.1	31.27	.03	.20	-2000.00	-2000.000	13.16	-2000.00
	2	189.0	164.8	.6	21.60	100.00	.50	-2000.00	-2000.000	38.57	-2000.00
	3	77.4	134.7	.9	21.04	100.00	.30	-2000.00	-2000.000	20.01	-2000.00
	4	44.6	129.7	1.3	56.53	.10	.10	-2000.00	-2000.000	9.95	-2000.00
	5	23.5	102.4	.7	46.27	30.00	.10	-2000.00	-2000.000	25.43	-2000.00
10350	1	421.7	147.0	.7	19.51	100.00	.40	-2000.00	-2000.000	31.49	-2000.00
	2	110.2	115.0	.9	49.12	1.00	.10	-2000.00	-2000.000	13.11	-2000.00
	3	63.9	133.0	1.1	50.91	1.00	.10	-2000.00	-2000.000	8.82	-2000.00
	4	30.0	104.0	1.2	53.10	1.00	.10	-2000.00	-2000.000	6.69	-2000.00
	5	16.8	88.0	.8	48.39	30.00	.10	-2000.00	-2000.000	28.32	-2000.00
10375	1	279.3	94.0	1.5	34.15	100.00	.20	-2000.00	-2000.000	7.44	-2000.00
	2	118.0	119.0	1.1	34.34	.01	.20	-2000.00	-2000.000	21.25	-2000.00
	3	47.9	96.0	.8	47.40	30.00	.10	-2000.00	-2000.000	23.93	-2000.00
	4	24.6	83.0	1.4	30.62	30.00	.20	-2000.00	-2000.000	7.00	-2000.00
	5	18.0	91.0	1.0	50.94	.10	.10	-2000.00	-2000.000	23.34	-2000.00
10400	1	547.5	175.0	1.0	33.29	.01	.20	-2000.00	-2000.000	21.79	-2000.00
	2	114.9	110.0	1.3	53.65	30.00	.10	-2000.00	-2000.000	5.70	-2000.00
	3	52.2	100.0	1.1	50.62	30.00	.10	-2000.00	-2000.000	13.27	-2000.00
	4	31.7	101.0	.9	47.89	30.00	.10	-2000.00	-2000.000	18.20	-2000.00
	5	17.9	86.0	.9	30.20	100.00	.60	-2000.00	-2000.000	37.25	-2000.00
10425	1	462.0	138.1	1.3	32.99	.03	.20	-2000.00	-2000.000	7.22	-2000.00
	2	124.4	111.6	1.3	32.84	.03	.20	-2000.00	-2000.000	8.83	-2000.00
	3	61.2	109.5	1.2	52.11	30.00	.10	-2000.00	-2000.000	11.46	-2000.00
	4	30.8	92.1	.9	47.56	30.00	.10	-2000.00	-2000.000	17.42	-2000.00
	5	19.7	88.4	.0	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10450	1	454.5	164.0	1.3	37.88	.01	.20	-2000.00	-2000.000	7.43	-2000.00
	2	140.0	151.0	1.7	26.64	.10	.30	-2000.00	-2000.000	1.86	-2000.00
	3	56.7	122.0	1.2	54.73	.10	.10	-2000.00	-2000.000	9.01	-2000.00
	4	29.7	107.0	.4	20.42	100.00	.50	-2000.00	-2000.000	52.08	-2000.00
	5	12.3	66.0	1.0	52.29	.10	.10	-2000.00	-2000.000	13.80	-2000.00
10475	1	682.9	186.4	1.4	29.75	.03	.30	-2000.00	-2000.000	4.75	-2000.00
	2	157.3	128.8	1.4	29.04	.03	.30	-2000.00	-2000.000	11.63	-2000.00
	3	66.2	108.1	.7	20.26	100.00	.30	-2000.00	-2000.000	27.30	-2000.00
	4	24.7	67.3	1.2	29.69	.10	.20	-2000.00	-2000.000	13.39	-2000.00
	5	15.9	65.1	1.5	51.72	100.00	.80	-2000.00	-2000.000	63.72	-2000.00
10500	1	322.2	140.0	1.7	27.49	.10	.30	-2000.00	-2000.000	2.48	-2000.00
	2	86.2	112.7	1.1	34.26	.01	.20	-2000.00	-2000.000	13.37	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	34.6	90.0	1.4	13.66	3.00	.40	-2000.00	-2000.000	10.48	-2000.00
	4	17.1	74.0	1.0	48.61	1.00	.10	-2000.00	-2000.000	13.17	-2000.00
	5	12.8	83.0	1.1	36.66	.01	.20	-2000.00	-2000.000	76.82	-2000.00
10525	1	546.8	166.6	1.1	50.06	1.00	.10	-2000.00	-2000.000	11.89	-2000.00
	2	109.7	100.3	1.9	17.47	.30	.50	-2000.00	-2000.000	4.04	-2000.00
	3	48.4	88.3	2.3	45.96	100.00	.40	-2000.00	-2000.000	9.40	-2000.00
	4	31.0	94.3	.0	44.82	.10	.10	-2000.00	-2000.000	108.87	-2000.00
	5	28.9	132.0	.5	19.26	100.00	.40	-2000.00	-2000.000	44.84	-2000.00
10550	1	138.6	75.0	1.8	33.60	.03	.40	-2000.00	-2000.000	10.10	-2000.00
	2	45.3	73.6	1.2	32.98	.03	.20	-2000.00	-2000.000	13.60	-2000.00
	3	26.4	85.0	1.8	17.41	.30	.50	-2000.00	-2000.000	4.03	-2000.00
	4	23.5	127.0	-.5	24.57	100.00	.60	-2000.00	-2000.000	107.54	-2000.00
	5	18.4	149.0	1.7	31.04	100.00	.30	-2000.00	-2000.000	13.06	-2000.00
10575	1	413.5	152.0	2.7	43.05	.10	.30	-2000.00	-2000.000	1.83	-2000.00
	2	125.9	139.0	2.9	32.09	.30	.40	-2000.00	-2000.000	1.77	-2000.00
	3	78.5	173.0	1.3	33.28	.03	.20	-2000.00	-2000.000	8.37	-2000.00
	4	53.5	197.0	1.2	52.99	1.00	.10	-2000.00	-2000.000	9.33	-2000.00
	5	46.8	259.0	2.0	44.83	.10	.20	-2000.00	-2000.000	3.01	-2000.00
10600	1	413.4	149.0	3.6	57.58	.10	.30	-2000.00	-2000.000	.98	-2000.00
	2	166.3	180.0	2.2	30.42	.10	.40	-2000.00	-2000.000	2.08	-2000.00
	3	93.5	202.0	1.7	32.44	.03	.30	-2000.00	-2000.000	3.43	-2000.00
	4	72.8	262.0	2.5	49.67	.03	.30	-2000.00	-2000.000	2.18	-2000.00
	5	43.9	237.0	3.1	61.67	.03	.30	-2000.00	-2000.000	2.80	-2000.00
10625	1	461.0	203.0	3.1	49.99	.10	.30	-2000.00	-2000.000	2.09	-2000.00
	2	175.9	233.0	2.5	41.12	.10	.30	-2000.00	-2000.000	2.02	-2000.00
	3	111.3	290.0	3.4	53.84	.10	.30	-2000.00	-2000.000	1.23	-2000.00
	4	59.6	263.0	4.4	113.31	.01	.20	-2000.00	-2000.000	1.76	-2000.00
	5	40.9	271.0	3.7	58.59	.10	.30	-2000.00	-2000.000	2.83	-2000.00
10650	1	871.0	455.0	1.8	34.45	.03	.30	-2000.00	-2000.000	3.63	-2000.00
	2	334.3	524.0	3.8	97.38	.01	.20	-2000.00	-2000.000	1.43	-2000.00
	3	141.6	440.0	5.6	117.79	.10	.20	-2000.00	-2000.000	1.01	-2000.00
	4	73.6	385.0	5.2	120.32	.03	.20	-2000.00	-2000.000	1.64	-2000.00
	5	33.4	262.0	2.3	45.15	.03	.30	-2000.00	-2000.000	2.35	-2000.00
10675	1	258.9	1010.0	2.8	59.68	.03	.30	-2000.00	-2000.000	13.79	-2000.00
	2	84.9	999.0	6.0	156.88	.01	.20	-2000.00	-2000.000	2.29	-2000.00
	3	36.6	860.0	6.7	265.71	.01	.10	-2000.00	-2000.000	3.21	-2000.00
	4	14.1	550.0	4.1	167.14	.10	.10	-2000.00	-2000.000	7.69	-2000.00
	5	9.4	556.0	6.6	236.84	30.00	.10	-2000.00	-2000.000	6.19	-2000.00
10700	1	483.5	893.0	6.0	139.21	.03	.20	-2000.00	-2000.000	2.68	-2000.00
	2	192.0	1063.0	6.9	144.57	.10	.20	-2000.00	-2000.000	1.91	-2000.00
	3	65.1	719.0	4.6	98.23	.10	.20	-2000.00	-2000.000	2.34	-2000.00
	4	42.0	776.0	6.4	134.11	.10	.20	-2000.00	-2000.000	2.86	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	462.6	1117.0	5.0	130.55	.01	.20	-2000.00	-2000.000	3.27	-2000.00
	2	119.2	863.0	3.9	62.35	.10	.30	-2000.00	-2000.000	3.42	-2000.00
	3	69.5	1005.0	5.6	109.44	.03	.30	-2000.00	-2000.000	2.72	-2000.00
10750	1	400.2	698.0	2.9	75.44	.01	.20	-2000.00	-2000.000	3.06	-2000.00
	2	183.2	958.0	5.5	141.94	.01	.20	-2000.00	-2000.000	2.27	-2000.00
10775	1	695.6	873.0	5.8	135.63	.03	.20	-2000.00	-2000.000	1.79	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 734

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
10325	1	488.9	153.5	1.1	52.72	.10	.10	-2000.00	-2000.000	10.63	-2000.00
	2	148.7	140.0	.8	21.26	100.00	.30	-2000.00	-2000.000	24.51	-2000.00
	3	92.2	173.3	.5	25.74	100.00	.60	-2000.00	-2000.000	40.54	-2000.00
	4	55.3	173.5	.9	48.74	30.00	.10	-2000.00	-2000.000	18.68	-2000.00
	5	28.6	134.6	1.0	49.71	30.00	.10	-2000.00	-2000.000	14.01	-2000.00
10350	1	413.2	127.2	.3	32.87	100.00	.70	-2000.00	-2000.000	60.48	-2000.00
	2	179.5	165.7	.4	32.86	100.00	.70	-2000.00	-2000.000	46.70	-2000.00
	3	87.1	160.5	.8	26.25	100.00	.20	-2000.00	-2000.000	20.29	-2000.00
	4	40.5	124.7	1.2	27.82	30.00	.20	-2000.00	-2000.000	25.68	-2000.00
	5	28.6	132.0	1.0	27.06	100.00	.20	-2000.00	-2000.000	12.42	-2000.00
10375	1	375.6	190.0	.4	25.22	100.00	.60	-2000.00	-2000.000	47.44	-2000.00
	2	103.1	156.0	1.0	48.59	30.00	.10	-2000.00	-2000.000	15.03	-2000.00
	3	42.0	127.0	.9	27.21	100.00	.20	-2000.00	-2000.000	18.52	-2000.00
	4	25.4	128.0	.8	26.24	100.00	.20	-2000.00	-2000.000	22.85	-2000.00
	5	18.8	143.0	1.2	28.90	100.00	.20	-2000.00	-2000.000	25.95	-2000.00
10400	1	381.2	113.9	.9	27.38	100.00	.20	-2000.00	-2000.000	17.38	-2000.00
	2	114.0	102.2	1.0	48.09	30.00	.10	-2000.00	-2000.000	14.20	-2000.00
	3	60.5	108.3	.8	25.87	100.00	.20	-2000.00	-2000.000	21.63	-2000.00
	4	40.8	122.0	1.1	51.31	1.00	.10	-2000.00	-2000.000	13.60	-2000.00
	5	23.0	103.0	1.2	51.39	30.00	.10	-2000.00	-2000.000	14.41	-2000.00
10425	1	625.2	181.7	2.1	34.64	.10	.30	-2000.00	-2000.000	3.79	-2000.00
	2	142.4	124.2	.9	26.76	100.00	.20	-2000.00	-2000.000	21.85	-2000.00
	3	77.8	135.3	1.1	50.34	30.00	.10	-2000.00	-2000.000	7.54	-2000.00
	4	33.0	95.9	1.0	30.68	.03	.20	-2000.00	-2000.000	18.40	-2000.00
	5	19.2	83.7	.3	24.89	100.00	.60	-2000.00	-2000.000	56.90	-2000.00
10450	1	690.1	206.3	1.5	39.91	.01	.20	-2000.00	-2000.000	3.68	-2000.00
	2	168.2	150.8	1.1	50.70	30.00	.10	-2000.00	-2000.000	13.13	-2000.00
	3	60.5	108.3	1.3	33.38	.03	.20	-2000.00	-2000.000	4.63	-2000.00
	4	29.0	86.8	.5	19.50	100.00	.40	-2000.00	-2000.000	39.05	-2000.00
	5	15.5	69.4	.1	40.34	100.00	.80	-2000.00	-2000.000	62.06	-2000.00
10475	1	544.4	151.2	.9	27.47	100.00	.20	-2000.00	-2000.000	18.14	-2000.00
	2	130.5	108.7	1.4	35.31	.03	.20	-2000.00	-2000.000	3.76	-2000.00
	3	55.7	92.5	.7	20.19	100.00	.40	-2000.00	-2000.000	33.75	-2000.00
	4	27.5	76.3	.1	41.84	100.00	.80	-2000.00	-2000.000	63.06	-2000.00
	5	15.3	63.8	1.1	52.41	.10	.10	-2000.00	-2000.000	13.84	-2000.00
10500	1	319.6	98.3	1.5	40.24	.01	.20	-2000.00	-2000.000	3.10	-2000.00
	2	97.7	90.2	.9	27.13	100.00	.20	-2000.00	-2000.000	20.19	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	43.2	79.6	.5	25.06	100.00	.60	-2000.00	-2000.000	40.52	-2000.00
	4	20.6	63.4	1.2	27.05	.03	.30	-2000.00	-2000.000	8.87	-2000.00
	5	13.4	61.8	1.7	18.58	.30	.40	-2000.00	-2000.000	3.64	-2000.00
10525	1	433.1	132.0	.8	26.49	100.00	.20	-2000.00	-2000.000	22.75	-2000.00
	2	116.0	106.0	.8	21.02	100.00	.30	-2000.00	-2000.000	29.13	-2000.00
	3	48.6	88.6	1.9	31.09	.10	.30	-2000.00	-2000.000	2.76	-2000.00
	4	24.3	74.0	1.9	37.75	.03	.30	-2000.00	-2000.000	4.10	-2000.00
	5	17.9	81.9	.2	45.72	100.00	.80	-2000.00	-2000.000	81.38	-2000.00
10550	1	501.4	110.0	.9	26.41	100.00	.20	-2000.00	-2000.000	20.31	-2000.00
	2	123.0	81.0	2.1	35.02	.10	.30	-2000.00	-2000.000	2.12	-2000.00
	3	63.8	83.9	2.4	26.89	.30	.40	-2000.00	-2000.000	1.34	-2000.00
	4	39.0	85.5	.2	20.61	100.00	.50	-2000.00	-2000.000	57.47	-2000.00
	5	48.1	158.3	-1.7	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10575	1	413.3	99.8	2.2	35.60	.10	.30	-2000.00	-2000.000	1.97	-2000.00
	2	121.4	87.9	2.7	29.87	.30	.40	-2000.00	-2000.000	2.17	-2000.00
	3	60.8	87.9	.7	21.58	100.00	.30	-2000.00	-2000.000	30.40	-2000.00
	4	66.7	161.0	-1.4	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	62.0	224.8	4.5	184.17	.01	.10	-2000.00	-2000.000	1.48	-2000.00
10600	1	425.9	112.3	3.7	94.55	.01	.20	-2000.00	-2000.000	1.37	-2000.00
	2	138.3	109.4	1.9	17.12	.30	.50	-2000.00	-2000.000	3.03	-2000.00
	3	118.7	187.0	-.9	40.05	100.00	.80	-2000.00	-2000.000	206.36	-2000.00
	4	94.3	248.9	4.5	95.74	.10	.20	-2000.00	-2000.000	1.56	-2000.00
	5	62.5	247.5	4.2	170.27	.01	.10	-2000.00	-2000.000	1.56	-2000.00
10625	1	477.3	129.2	4.1	45.20	.30	.40	-2000.00	-2000.000	1.63	-2000.00
	2	245.6	199.4	1.3	28.29	.03	.30	-2000.00	-2000.000	10.89	-2000.00
	3	152.5	247.0	5.7	227.04	.01	.10	-2000.00	-2000.000	1.00	-2000.00
	4	86.0	232.8	5.5	216.62	.03	.10	-2000.00	-2000.000	1.37	-2000.00
	5	61.3	248.8	3.0	59.83	.03	.30	-2000.00	-2000.000	3.12	-2000.00
10650	1	764.1	282.0	2.3	44.51	.03	.30	-2000.00	-2000.000	1.95	-2000.00
	2	268.2	297.0	6.5	257.58	.01	.10	-2000.00	-2000.000	.72	-2000.00
	3	115.9	250.0	7.5	267.75	1.00	.10	-2000.00	-2000.000	.78	-2000.00
	4	74.9	276.0	4.8	124.85	.01	.20	-2000.00	-2000.000	1.69	-2000.00
	5	39.4	218.0	1.4	28.60	.03	.30	-2000.00	-2000.000	6.50	-2000.00
10675	1	1740.0	525.0	5.2	199.49	.10	.10	-2000.00	-2000.000	1.22	-2000.00
	2	397.3	359.8	10.0	336.20	100.00	.10	-2000.00	-2000.000	1.18	-2000.00
	3	217.5	393.0	6.5	261.06	.01	.10	-2000.00	-2000.000	1.61	-2000.00
	4	81.9	247.4	2.5	20.76	.30	.60	-2000.00	-2000.000	4.17	-2000.00
	5	39.5	179.1	2.1	50.56	.03	.20	-2000.00	-2000.000	2.28	-2000.00
10700	1	1866.0	680.0	13.9	433.33	100.00	.10	-2000.00	-2000.000	1.43	-2000.00
	2	767.3	850.0	9.4	347.30	.03	.10	-2000.00	-2000.000	1.50	-2000.00
	3	244.5	540.0	5.6	227.44	.01	.10	-2000.00	-2000.000	1.88	-2000.00
	4	105.8	390.0	4.2	172.13	.01	.10	-2000.00	-2000.000	2.11	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	1473.0	1150.0	11.0	384.07	.10	.10	-2000.00	-2000.000	1.65	-2000.00
	2	322.8	760.0	9.9	350.95	.10	.10	-2000.00	-2000.000	1.58	-2000.00
	3	114.4	530.0	9.0	304.75	3.00	.10	-2000.00	-2000.000	1.54	-2000.00
10750	1	698.7	843.0	6.5	137.25	.10	.20	-2000.00	-2000.000	2.29	-2000.00
	2	154.6	560.0	7.3	271.09	.10	.10	-2000.00	-2000.000	1.69	-2000.00
10775	1	394.2	728.0	6.1	141.60	.03	.20	-2000.00	-2000.000	2.15	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 724

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	412.2	117.6	.5	25.67	100.00	.60	-2000.00	-2000.000	39.92	-2000.00
	2	149.2	127.7	.9	26.81	100.00	.20	-2000.00	-2000.000	15.57	-2000.00
	3	84.6	144.5	1.0	48.56	1.00	.10	-2000.00	-2000.000	13.36	-2000.00
	4	60.7	173.1	.9	47.77	30.00	.10	-2000.00	-2000.000	18.19	-2000.00
	5	34.7	148.3	.9	28.35	100.00	.20	-2000.00	-2000.000	19.44	-2000.00
10350	1	530.7	124.3	.5	20.45	100.00	.50	-2000.00	-2000.000	39.23	-2000.00
	2	202.0	142.0	.9	48.06	30.00	.10	-2000.00	-2000.000	15.52	-2000.00
	3	119.6	167.0	.9	27.02	100.00	.20	-2000.00	-2000.000	15.61	-2000.00
	4	54.2	126.9	.6	25.13	100.00	.20	-2000.00	-2000.000	36.24	-2000.00
	5	40.0	140.5	1.0	48.27	30.00	.10	-2000.00	-2000.000	17.68	-2000.00
10375	1	502.6	129.3	.6	19.22	100.00	.40	-2000.00	-2000.000	37.65	-2000.00
	2	218.2	168.4	.8	25.53	100.00	.20	-2000.00	-2000.000	23.87	-2000.00
	3	81.4	125.4	.8	21.05	100.00	.30	-2000.00	-2000.000	22.58	-2000.00
	4	53.6	137.8	.9	47.50	30.00	.10	-2000.00	-2000.000	27.64	-2000.00
	5	38.1	147.0	1.1	48.03	30.00	.10	-2000.00	-2000.000	13.39	-2000.00
10400	1	574.6	150.3	.7	19.91	100.00	.30	-2000.00	-2000.000	28.19	-2000.00
	2	141.6	111.1	.8	25.94	100.00	.20	-2000.00	-2000.000	19.36	-2000.00
	3	78.5	122.9	.9	27.38	100.00	.20	-2000.00	-2000.000	23.59	-2000.00
	4	52.4	137.1	.9	27.53	100.00	.20	-2000.00	-2000.000	20.44	-2000.00
	5	30.7	120.3	.7	57.98	30.00	.10	-2000.00	-2000.000	33.42	-2000.00
10425	1	392.2	90.5	.8	25.98	100.00	.20	-2000.00	-2000.000	22.38	-2000.00
	2	151.9	105.2	.9	47.79	30.00	.10	-2000.00	-2000.000	18.03	-2000.00
	3	89.0	123.0	.9	48.70	30.00	.10	-2000.00	-2000.000	22.47	-2000.00
	4	47.6	109.9	1.5	64.09	100.00	.10	-2000.00	-2000.000	9.79	-2000.00
	5	29.6	102.6	.9	47.36	30.00	.10	-2000.00	-2000.000	28.66	-2000.00
10450	1	644.7	139.6	.9	26.76	100.00	.20	-2000.00	-2000.000	20.96	-2000.00
	2	225.3	146.3	1.0	48.20	30.00	.10	-2000.00	-2000.000	14.40	-2000.00
	3	86.9	112.6	1.1	51.79	1.00	.10	-2000.00	-2000.000	11.27	-2000.00
	4	51.2	110.8	.5	25.04	100.00	.20	-2000.00	-2000.000	40.91	-2000.00
	5	26.3	85.4	.9	20.27	100.00	.40	-2000.00	-2000.000	40.59	-2000.00
10475	1	886.6	185.5	1.1	50.28	30.00	.10	-2000.00	-2000.000	13.72	-2000.00
	2	187.2	117.5	1.2	53.44	1.00	.10	-2000.00	-2000.000	9.25	-2000.00
	3	92.8	116.3	.9	27.21	100.00	.20	-2000.00	-2000.000	18.79	-2000.00
	4	39.8	83.3	.8	20.69	100.00	.30	-2000.00	-2000.000	24.80	-2000.00
	5	25.8	80.8	.9	27.97	100.00	.60	-2000.00	-2000.000	30.18	-2000.00
10500	1	326.2	144.0	1.3	38.29	.01	.20	-2000.00	-2000.000	7.74	-2000.00
	2	88.0	116.7	1.1	52.43	.10	.10	-2000.00	-2000.000	14.14	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	34.5	91.0	.8	27.42	100.00	.20	-2000.00	-2000.000	22.56	-2000.00
	4	17.8	78.0	.7	19.26	100.00	.40	-2000.00	-2000.000	36.72	-2000.00
	5	10.8	71.0	-.3	40.05	100.00	.80	-2000.00	-2000.000	125.09	-2000.00
10525	1	422.8	120.6	1.1	53.40	.10	.10	-2000.00	-2000.000	13.28	-2000.00
	2	109.5	93.7	1.1	51.76	.10	.10	-2000.00	-2000.000	13.71	-2000.00
	3	57.6	98.5	.8	26.21	100.00	.20	-2000.00	-2000.000	23.42	-2000.00
	4	28.9	82.3	.3	43.50	100.00	.80	-2000.00	-2000.000	55.85	-2000.00
	5	15.7	67.3	.5	47.09	100.00	.10	-2000.00	-2000.000	40.17	-2000.00
10550	1	328.2	103.0	1.6	33.35	30.00	.20	-2000.00	-2000.000	8.37	-2000.00
	2	113.7	107.1	1.1	52.67	.10	.10	-2000.00	-2000.000	14.48	-2000.00
	3	44.6	83.8	.6	21.02	100.00	.50	-2000.00	-2000.000	36.59	-2000.00
	4	23.9	75.1	.8	49.12	.10	.10	-2000.00	-2000.000	30.03	-2000.00
	5	15.4	72.5	.4	19.34	100.00	.40	-2000.00	-2000.000	45.68	-2000.00
10575	1	401.7	124.8	.9	26.60	100.00	.20	-2000.00	-2000.000	20.19	-2000.00
	2	110.8	103.3	.7	20.39	100.00	.30	-2000.00	-2000.000	28.87	-2000.00
	3	47.2	87.8	1.2	36.70	.01	.20	-2000.00	-2000.000	12.31	-2000.00
	4	31.3	97.3	.9	27.82	100.00	.20	-2000.00	-2000.000	18.03	-2000.00
	5	39.7	185.2	.7	33.89	.01	.20	-2000.00	-2000.000	37.17	-2000.00
10600	1	271.8	89.0	.6	20.21	100.00	.30	-2000.00	-2000.000	34.70	-2000.00
	2	80.4	79.7	1.5	31.30	.03	.30	-2000.00	-2000.000	3.20	-2000.00
	3	45.4	89.0	.8	46.95	1.00	.10	-2000.00	-2000.000	24.16	-2000.00
	4	52.9	174.0	1.1	33.51	.01	.30	-2000.00	-2000.000	15.81	-2000.00
	5	45.6	226.0	4.2	169.37	.01	.10	-2000.00	-2000.000	2.24	-2000.00
10625	1	283.5	98.0	1.9	38.35	.03	.30	-2000.00	-2000.000	2.50	-2000.00
	2	96.5	101.0	1.5	37.82	.01	.30	-2000.00	-2000.000	5.01	-2000.00
	3	89.5	186.0	1.2	34.26	.01	.30	-2000.00	-2000.000	12.30	-2000.00
	4	65.0	226.0	4.7	180.28	.10	.10	-2000.00	-2000.000	1.23	-2000.00
	5	34.7	181.0	1.3	37.70	.01	.20	-2000.00	-2000.000	15.84	-2000.00
10650	1	372.9	124.0	3.0	47.56	.10	.30	-2000.00	-2000.000	1.73	-2000.00
	2	216.3	216.0	1.8	35.23	.03	.40	-2000.00	-2000.000	3.29	-2000.00
	3	125.6	250.0	6.0	115.23	10.00	.20	-2000.00	-2000.000	1.30	-2000.00
	4	56.1	187.0	1.9	37.14	.03	.30	-2000.00	-2000.000	3.76	-2000.00
	5	33.8	169.0	1.0	29.47	.03	.20	-2000.00	-2000.000	19.70	-2000.00
10675	1	618.2	206.0	2.5	61.08	.01	.30	-2000.00	-2000.000	2.22	-2000.00
	2	265.4	265.0	7.7	142.92	3.00	.20	-2000.00	-2000.000	.69	-2000.00
	3	94.5	188.0	3.4	69.75	.30	.20	-2000.00	-2000.000	1.73	-2000.00
	4	53.2	177.0	2.4	38.78	.10	.30	-2000.00	-2000.000	2.77	-2000.00
	5	29.7	148.0	.9	50.91	.10	.10	-2000.00	-2000.000	21.60	-2000.00
10700	1	1004.0	330.0	11.2	372.98	1.00	.10	-2000.00	-2000.000	1.40	-2000.00
	2	248.8	246.0	7.5	139.50	3.00	.20	-2000.00	-2000.000	.84	-2000.00
	3	107.2	210.0	5.1	190.11	30.00	.10	-2000.00	-2000.000	1.57	-2000.00
	4	54.5	180.0	3.4	36.38	.30	.40	-2000.00	-2000.000	2.92	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	1595.0	1310.0	8.5	194.07	.03	.20	-2000.00	-2000.000	1.47	-2000.00
	2	394.2	977.0	9.7	201.84	.10	.20	-2000.00	-2000.000	1.47	-2000.00
	3	129.2	630.0	9.4	340.99	.03	.10	-2000.00	-2000.000	1.14	-2000.00
10750	1	374.7	1176.0	5.7	147.93	.01	.20	-2000.00	-2000.000	1.27	-2000.00
	2	101.9	959.0	7.0	174.76	.01	.20	-2000.00	-2000.000	2.13	-2000.00
10775	1	202.4	700.0	4.9	127.77	.01	.20	-2000.00	-2000.000	3.00	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 714

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	473.1	163.0	4.7	91.60	.03	.30	-2000.00	-2000.000	2.94	-2000.00
	2	113.9	117.0	.7	25.54	100.00	.20	-2000.00	-2000.000	25.40	-2000.00
	3	77.6	160.0	.7	19.97	100.00	.30	-2000.00	-2000.000	26.87	-2000.00
	4	39.2	135.0	1.7	45.75	.01	.20	-2000.00	-2000.000	3.10	-2000.00
	5	32.6	168.0	.4	32.30	100.00	.70	-2000.00	-2000.000	48.47	-2000.00
10350	1	351.0	131.0	2.8	55.84	.03	.30	-2000.00	-2000.000	3.99	-2000.00
	2	134.1	150.0	1.2	29.23	100.00	.20	-2000.00	-2000.000	10.60	-2000.00
	3	55.8	124.0	1.4	39.73	.01	.20	-2000.00	-2000.000	4.29	-2000.00
	4	42.1	157.0	.5	44.38	100.00	.80	-2000.00	-2000.000	51.38	-2000.00
	5	27.3	153.0	1.0	10.67	1.00	.50	-2000.00	-2000.000	33.47	-2000.00
10375	1	360.9	143.0	2.2	42.66	.03	.30	-2000.00	-2000.000	3.51	-2000.00
	2	96.1	114.5	1.6	32.78	.03	.30	-2000.00	-2000.000	3.57	-2000.00
	3	61.2	145.0	.5	24.71	100.00	.60	-2000.00	-2000.000	44.25	-2000.00
	4	35.5	140.0	1.5	42.03	.01	.20	-2000.00	-2000.000	3.49	-2000.00
	5	16.7	99.0	1.0	20.87	100.00	.30	-2000.00	-2000.000	34.19	-2000.00
10400	1	214.6	96.0	1.3	33.30	.03	.20	-2000.00	-2000.000	6.39	-2000.00
	2	97.9	131.6	.3	43.66	100.00	.80	-2000.00	-2000.000	51.44	-2000.00
	3	47.8	128.0	1.4	35.33	.03	.20	-2000.00	-2000.000	3.67	-2000.00
	4	20.8	93.0	.8	20.89	100.00	.30	-2000.00	-2000.000	22.46	-2000.00
	5	15.3	103.0	.6	20.52	100.00	.40	-2000.00	-2000.000	31.98	-2000.00
10425	1	379.5	148.0	.1	40.60	100.00	.80	-2000.00	-2000.000	71.55	-2000.00
	2	109.1	128.0	1.3	37.50	.01	.20	-2000.00	-2000.000	5.82	-2000.00
	3	40.5	95.0	.6	20.66	100.00	.50	-2000.00	-2000.000	35.97	-2000.00
	4	25.8	101.0	.4	20.58	100.00	.50	-2000.00	-2000.000	56.06	-2000.00
	5	21.8	128.0	.3	48.86	.10	.10	-2000.00	-2000.000	58.50	-2000.00
10450	1	286.4	94.0	1.6	43.75	.01	.20	-2000.00	-2000.000	3.50	-2000.00
	2	78.1	77.4	.5	20.60	100.00	.30	-2000.00	-2000.000	38.97	-2000.00
	3	45.6	90.0	1.6	28.39	100.00	.40	-2000.00	-2000.000	8.47	-2000.00
	4	34.8	114.0	.0	24.62	100.00	.20	-2000.00	-2000.000	69.52	-2000.00
	5	18.1	89.0	.5	19.77	100.00	.30	-2000.00	-2000.000	43.19	-2000.00
10475	1	471.9	94.9	.2	24.54	100.00	.60	-2000.00	-2000.000	59.54	-2000.00
	2	193.2	116.6	1.0	27.99	100.00	.20	-2000.00	-2000.000	14.05	-2000.00
	3	117.9	142.0	1.1	50.93	1.00	.10	-2000.00	-2000.000	13.90	-2000.00
	4	53.0	106.7	.7	20.87	100.00	.30	-2000.00	-2000.000	29.03	-2000.00
	5	33.7	101.5	.1	24.50	100.00	.60	-2000.00	-2000.000	60.14	-2000.00
10500	1	341.5	164.0	1.1	49.66	30.00	.10	-2000.00	-2000.000	12.55	-2000.00
	2	126.8	183.0	1.5	41.50	.01	.20	-2000.00	-2000.000	4.17	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	45.9	132.0	1.1	50.24	1.00	.10	-2000.00	-2000.000	11.65	-2000.00
	4	23.3	112.0	.7	19.74	100.00	.30	-2000.00	-2000.000	35.71	-2000.00
	5	12.7	91.0	-.2	41.06	100.00	.80	-2000.00	-2000.000	105.48	-2000.00
10525	1	480.2	167.0	1.4	29.61	.03	.30	-2000.00	-2000.000	3.98	-2000.00
	2	109.7	114.0	1.0	50.64	.10	.10	-2000.00	-2000.000	14.25	-2000.00
	3	53.6	112.0	.5	19.29	100.00	.40	-2000.00	-2000.000	33.44	-2000.00
	4	25.5	88.0	.2	41.27	100.00	.80	-2000.00	-2000.000	88.77	-2000.00
	5	15.7	82.0	1.6	29.57	.03	.30	-2000.00	-2000.000	36.05	-2000.00
10550	1	289.6	124.0	1.0	48.42	30.00	.10	-2000.00	-2000.000	15.38	-2000.00
	2	88.2	113.7	.8	47.19	30.00	.10	-2000.00	-2000.000	21.61	-2000.00
	3	37.7	97.0	.2	40.84	100.00	.80	-2000.00	-2000.000	64.46	-2000.00
	4	18.1	77.0	1.8	29.02	100.00	.40	-2000.00	-2000.000	50.39	-2000.00
	5	13.5	87.0	1.5	17.64	.30	.70	-2000.00	-2000.000	38.06	-2000.00
10575	1	469.0	122.7	.7	45.22	30.00	.10	-2000.00	-2000.000	26.20	-2000.00
	2	132.1	103.6	.5	21.46	100.00	.50	-2000.00	-2000.000	41.53	-2000.00
	3	65.1	101.9	1.9	21.55	.30	.40	-2000.00	-2000.000	2.22	-2000.00
	4	36.0	94.2	2.0	18.91	.30	.50	-2000.00	-2000.000	2.49	-2000.00
	5	19.5	76.6	1.4	37.99	.01	.30	-2000.00	-2000.000	8.62	-2000.00
10600	1	323.3	92.2	.6	20.40	100.00	.30	-2000.00	-2000.000	36.10	-2000.00
	2	112.3	96.1	2.5	65.28	.01	.20	-2000.00	-2000.000	1.05	-2000.00
	3	54.4	92.9	2.5	52.45	.30	.20	-2000.00	-2000.000	2.25	-2000.00
	4	25.8	73.7	2.4	25.70	.30	.40	-2000.00	-2000.000	3.17	-2000.00
	5	34.2	146.4	1.2	30.23	100.00	.20	-2000.00	-2000.000	7.26	-2000.00
10625	1	406.9	190.0	2.8	46.25	.10	.30	-2000.00	-2000.000	3.08	-2000.00
	2	100.3	141.0	3.4	87.94	.01	.20	-2000.00	-2000.000	1.61	-2000.00
	3	36.8	103.0	2.8	30.36	.30	.40	-2000.00	-2000.000	1.48	-2000.00
	4	38.1	178.0	1.3	33.40	.03	.20	-2000.00	-2000.000	5.42	-2000.00
	5	39.6	278.0	1.8	44.07	.01	.30	-2000.00	-2000.000	5.09	-2000.00
10650	1	261.1	122.0	4.3	109.08	.01	.20	-2000.00	-2000.000	1.78	-2000.00
	2	72.5	101.9	4.0	92.20	.03	.20	-2000.00	-2000.000	1.80	-2000.00
	3	61.3	172.0	2.0	22.22	.30	.40	-2000.00	-2000.000	2.60	-2000.00
	4	51.4	240.0	2.4	47.11	.03	.30	-2000.00	-2000.000	2.04	-2000.00
	5	45.9	322.0	1.5	32.61	.03	.40	-2000.00	-2000.000	5.76	-2000.00
10675	1	210.5	132.0	5.2	71.91	.30	.30	-2000.00	-2000.000	1.23	-2000.00
	2	113.3	213.0	4.0	56.25	.30	.30	-2000.00	-2000.000	1.39	-2000.00
	3	74.0	278.0	3.7	58.39	.10	.30	-2000.00	-2000.000	2.44	-2000.00
	4	54.4	341.0	3.6	67.19	.03	.30	-2000.00	-2000.000	2.86	-2000.00
	5	26.7	251.0	1.9	40.82	.03	.40	-2000.00	-2000.000	10.94	-2000.00
10700	1	331.6	216.0	4.0	94.22	.03	.20	-2000.00	-2000.000	1.53	-2000.00
	2	139.0	272.0	4.9	125.70	.01	.20	-2000.00	-2000.000	2.49	-2000.00
	3	86.8	340.0	5.0	64.93	1.00	.30	-2000.00	-2000.000	1.45	-2000.00
	4	34.6	226.0	3.5	70.05	.03	.30	-2000.00	-2000.000	4.88	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	291.8	366.0	3.6	77.80	.10	.20	-2000.00	-2000.000	1.06	-2000.00
	2	124.2	467.0	5.2	99.07	.03	.30	-2000.00	-2000.000	3.45	-2000.00
	3	38.1	286.0	3.9	73.72	.03	.40	-2000.00	-2000.000	5.36	-2000.00
10750	1	424.6	1111.0	5.0	97.53	.03	.30	-2000.00	-2000.000	4.48	-2000.00
	2	85.0	667.5	6.2	161.17	.01	.20	-2000.00	-2000.000	4.65	-2000.00
10775	1	246.8	860.0	6.2	160.70	.01	.20	-2000.00	-2000.000	3.66	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 704

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10325	1	661.2	151.5	1.5	41.57	.01	.20	-2000.00	-2000.000	4.36	-2000.00
	2	203.2	139.7	1.1	34.78	.01	.20	-2000.00	-2000.000	12.22	-2000.00
	3	96.3	132.1	.6	19.44	100.00	.40	-2000.00	-2000.000	36.04	-2000.00
	4	49.3	113.1	1.3	56.07	.10	.10	-2000.00	-2000.000	7.83	-2000.00
	5	42.2	145.0	.9	47.76	30.00	.10	-2000.00	-2000.000	20.94	-2000.00
10350	1	212.5	119.0	.0	20.27	100.00	.50	-2000.00	-2000.000	66.76	-2000.00
	2	72.7	122.3	.4	21.05	100.00	.50	-2000.00	-2000.000	51.41	-2000.00
	3	31.7	106.0	.8	51.17	.10	.10	-2000.00	-2000.000	18.81	-2000.00
	4	25.1	140.0	.8	25.89	100.00	.20	-2000.00	-2000.000	41.00	-2000.00
	5	14.3	120.0	.3	20.08	100.00	.30	-2000.00	-2000.000	59.28	-2000.00
10375	1	365.2	127.0	.3	24.99	100.00	.60	-2000.00	-2000.000	54.94	-2000.00
	2	108.9	113.0	1.5	31.26	.03	.30	-2000.00	-2000.000	6.08	-2000.00
	3	73.8	154.0	.2	50.95	.01	.10	-2000.00	-2000.000	58.15	-2000.00
	4	31.1	108.0	2.6	96.90	100.00	.80	-2000.00	-2000.000	22.26	-2000.00
	5	23.7	124.0	1.1	50.66	1.00	.10	-2000.00	-2000.000	13.38	-2000.00
10400	1	289.8	109.0	1.6	42.85	.01	.20	-2000.00	-2000.000	4.95	-2000.00
	2	135.6	153.0	1.1	34.88	.01	.20	-2000.00	-2000.000	11.01	-2000.00
	3	48.1	108.0	1.2	35.98	.01	.20	-2000.00	-2000.000	9.43	-2000.00
	4	33.1	125.0	1.3	54.29	.10	.10	-2000.00	-2000.000	16.78	-2000.00
	5	23.8	135.0	.4	25.49	100.00	.20	-2000.00	-2000.000	32.11	-2000.00
10425	1	532.1	124.6	.8	26.02	100.00	.20	-2000.00	-2000.000	23.99	-2000.00
	2	139.3	97.9	.9	29.43	.03	.20	-2000.00	-2000.000	16.39	-2000.00
	3	78.5	110.1	.9	27.41	100.00	.20	-2000.00	-2000.000	17.92	-2000.00
	4	50.1	117.4	1.1	52.30	.10	.10	-2000.00	-2000.000	18.17	-2000.00
	5	29.6	103.9	.7	20.11	100.00	.30	-2000.00	-2000.000	24.64	-2000.00
10450	1	341.2	94.8	1.0	50.55	.10	.10	-2000.00	-2000.000	15.79	-2000.00
	2	123.3	102.7	1.0	51.18	.10	.10	-2000.00	-2000.000	14.51	-2000.00
	3	67.9	112.8	1.0	34.88	.01	.20	-2000.00	-2000.000	11.30	-2000.00
	4	36.1	100.2	.7	46.21	30.00	.10	-2000.00	-2000.000	19.85	-2000.00
	5	27.4	114.3	.9	50.57	.10	.10	-2000.00	-2000.000	22.97	-2000.00
10475	1	288.1	150.0	.1	19.01	100.00	.40	-2000.00	-2000.000	71.17	-2000.00
	2	95.5	149.8	1.2	32.22	.03	.20	-2000.00	-2000.000	11.27	-2000.00
	3	41.8	130.0	1.2	29.55	100.00	.20	-2000.00	-2000.000	17.10	-2000.00
	4	25.7	134.0	.8	28.72	.03	.20	-2000.00	-2000.000	20.58	-2000.00
	5	16.0	125.0	.5	19.40	100.00	.40	-2000.00	-2000.000	34.19	-2000.00
10500	1	328.0	171.0	.9	48.80	.10	.10	-2000.00	-2000.000	22.06	-2000.00
	2	89.9	141.1	.8	47.06	30.00	.10	-2000.00	-2000.000	22.47	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	45.1	141.0	1.4	28.45	.03	.30	-2000.00	-2000.000	4.52	-2000.00
	4	25.4	132.0	.7	26.19	100.00	.20	-2000.00	-2000.000	29.72	-2000.00
	5	13.1	103.0	.8	20.34	100.00	.30	-2000.00	-2000.000	23.07	-2000.00
10525	1	422.0	132.5	.7	20.61	100.00	.30	-2000.00	-2000.000	29.98	-2000.00
	2	155.0	146.0	1.3	37.45	.01	.20	-2000.00	-2000.000	8.10	-2000.00
	3	72.2	135.6	1.0	49.04	30.00	.10	-2000.00	-2000.000	15.85	-2000.00
	4	31.2	97.9	.6	20.48	100.00	.30	-2000.00	-2000.000	36.67	-2000.00
	5	21.6	101.5	1.6	32.37	.03	.30	-2000.00	-2000.000	3.64	-2000.00
10550	1	803.8	188.3	.9	46.96	30.00	.10	-2000.00	-2000.000	20.20	-2000.00
	2	213.8	150.2	1.3	37.86	.01	.20	-2000.00	-2000.000	10.57	-2000.00
	3	85.2	119.5	.6	20.15	100.00	.30	-2000.00	-2000.000	38.87	-2000.00
	4	46.5	108.9	1.9	44.67	.03	.20	-2000.00	-2000.000	4.31	-2000.00
	5	20.2	70.8	3.8	152.00	.03	.10	-2000.00	-2000.000	.76	-2000.00
10575	1	514.1	181.0	1.2	36.47	.01	.20	-2000.00	-2000.000	11.43	-2000.00
	2	131.9	139.0	1.0	29.68	.03	.20	-2000.00	-2000.000	15.53	-2000.00
	3	56.4	119.0	1.8	30.55	.10	.30	-2000.00	-2000.000	4.15	-2000.00
	4	21.9	77.0	3.6	38.48	.30	.40	-2000.00	-2000.000	3.28	-2000.00
	5	22.2	117.0	2.5	24.05	.30	.40	-2000.00	-2000.000	9.70	-2000.00
10600	1	377.4	191.0	1.3	36.04	.01	.30	-2000.00	-2000.000	9.85	-2000.00
	2	100.9	153.0	2.2	52.49	.01	.30	-2000.00	-2000.000	7.26	-2000.00
	3	31.0	94.0	4.0	42.64	.30	.40	-2000.00	-2000.000	2.37	-2000.00
	4	27.0	136.0	2.5	22.91	.30	.50	-2000.00	-2000.000	5.51	-2000.00
	5	22.6	171.0	-.2	40.05	100.00	.80	-2000.00	-2000.000	130.55	-2000.00
10625	1	644.9	238.0	1.5	38.14	.01	.30	-2000.00	-2000.000	3.50	-2000.00
	2	99.5	110.2	4.6	118.07	.01	.20	-2000.00	-2000.000	1.90	-2000.00
	3	68.6	151.0	3.1	34.12	.30	.40	-2000.00	-2000.000	1.31	-2000.00
	4	48.8	180.0	.3	42.38	100.00	.80	-2000.00	-2000.000	50.78	-2000.00
	5	50.1	277.0	2.0	50.62	.01	.30	-2000.00	-2000.000	2.78	-2000.00
10650	1	156.7	91.0	4.8	121.78	.01	.20	-2000.00	-2000.000	1.85	-2000.00
	2	80.1	139.7	4.0	104.17	.01	.20	-2000.00	-2000.000	1.08	-2000.00
	3	48.6	169.0	1.4	28.46	10.00	.20	-2000.00	-2000.000	9.77	-2000.00
	4	44.7	259.0	2.3	57.48	.01	.30	-2000.00	-2000.000	4.00	-2000.00
	5	29.8	259.0	3.4	56.21	.10	.30	-2000.00	-2000.000	4.24	-2000.00
10675	1	379.7	216.0	5.8	80.10	.30	.30	-2000.00	-2000.000	1.18	-2000.00
	2	128.6	220.0	3.8	53.13	.30	.30	-2000.00	-2000.000	1.19	-2000.00
	3	86.5	295.0	4.7	110.17	.03	.20	-2000.00	-2000.000	1.56	-2000.00
	4	52.8	301.0	5.2	112.27	.10	.20	-2000.00	-2000.000	2.93	-2000.00
	5	33.6	287.0	3.4	144.99	.01	.10	-2000.00	-2000.000	4.57	-2000.00
10700	1	515.4	279.0	2.7	70.14	.01	.20	-2000.00	-2000.000	1.57	-2000.00
	2	197.5	320.0	5.5	141.56	.01	.20	-2000.00	-2000.000	1.09	-2000.00
	3	96.6	313.0	5.9	134.94	.03	.20	-2000.00	-2000.000	1.18	-2000.00
	4	55.2	298.0	3.8	73.73	.03	.30	-2000.00	-2000.000	1.36	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	27.6	224.0	2.7	72.14	.03	.20	-2000.00	-2000.000	9.05	-2000.00
10725	1	316.4	827.0	5.6	144.81	.01	.20	-2000.00	-2000.000	2.34	-2000.00
	2	82.5	647.8	7.1	164.92	.03	.20	-2000.00	-2000.000	1.63	-2000.00
	3	34.4	539.0	5.2	82.75	.10	.30	-2000.00	-2000.000	1.64	-2000.00
	4	14.7	383.0	4.5	84.67	.03	.30	-2000.00	-2000.000	3.35	-2000.00
	5	7.5	293.1	2.4	20.56	.30	.70	-2000.00	-2000.000	6.07	-2000.00
10750	1	979.8	1139.0	8.1	169.46	.10	.20	-2000.00	-2000.000	2.01	-2000.00
	2	283.4	988.0	6.5	245.40	.10	.10	-2000.00	-2000.000	1.59	-2000.00
	3	115.5	800.0	6.0	215.28	10.00	.10	-2000.00	-2000.000	1.38	-2000.00
	4	37.9	440.0	4.3	168.33	.03	.10	-2000.00	-2000.000	1.75	-2000.00
	5	19.0	330.0	4.0	90.41	100.00	.30	-2000.00	-2000.000	15.08	-2000.00
10775	1	1231.0	1280.0	6.6	151.97	.03	.20	-2000.00	-2000.000	2.50	-2000.00
	2	301.9	947.0	7.6	296.97	.01	.10	-2000.00	-2000.000	1.92	-2000.00
	3	102.9	640.0	6.6	262.15	.01	.10	-2000.00	-2000.000	1.11	-2000.00
	4	43.7	457.0	6.4	146.99	.03	.20	-2000.00	-2000.000	1.74	-2000.00
	5	58.3	914.0	7.5	296.82	.01	.10	-2000.00	-2000.000	2.12	-2000.00
10800	1	922.2	877.0	6.3	145.77	.03	.20	-2000.00	-2000.000	2.30	-2000.00
	2	229.0	653.0	6.5	136.66	.10	.20	-2000.00	-2000.000	2.00	-2000.00
	3	95.2	542.0	6.5	102.95	.10	.30	-2000.00	-2000.000	1.30	-2000.00
	4	123.1	1170.0	8.3	172.71	.10	.20	-2000.00	-2000.000	1.64	-2000.00
	5	48.6	693.0	4.8	184.01	1.00	.10	-2000.00	-2000.000	4.05	-2000.00
10825	1	641.0	1118.0	4.6	108.36	.03	.20	-2000.00	-2000.000	2.58	-2000.00
	2	140.0	732.0	5.0	95.27	.03	.30	-2000.00	-2000.000	2.08	-2000.00
	3	139.1	1450.0	7.4	189.16	.01	.20	-2000.00	-2000.000	1.46	-2000.00
	4	49.2	857.0	4.3	39.94	.30	.50	-2000.00	-2000.000	3.22	-2000.00
	5	43.9	1149.0	9.2	227.48	.01	.20	-2000.00	-2000.000	1.32	-2000.00
10850	1	1028.0	870.0	3.9	63.34	.10	.30	-2000.00	-2000.000	2.51	-2000.00
	2	606.5	1544.0	7.9	164.85	.10	.20	-2000.00	-2000.000	.84	-2000.00
	3	189.7	960.0	5.9	224.38	.10	.10	-2000.00	-2000.000	1.76	-2000.00
	4	150.9	1280.0	11.2	369.04	30.00	.10	-2000.00	-2000.000	1.61	-2000.00
	5	130.4	1650.0	17.8	520.20	100.00	.10	-2000.00	-2000.000	1.82	-2000.00
10875	1	1091.0	1100.0	7.9	164.31	.10	.20	-2000.00	-2000.000	1.26	-2000.00
	2	262.9	798.0	7.0	132.75	1.00	.20	-2000.00	-2000.000	.51	-2000.00
	3	189.7	1150.0	11.7	393.70	.30	.10	-2000.00	-2000.000	.62	-2000.00
	4	150.7	1520.0	17.7	544.70	.30	.10	-2000.00	-2000.000	.76	-2000.00
	5	81.4	1236.0	17.1	512.45	3.00	.10	-2000.00	-2000.000	.61	-2000.00
10900	1	166.8	580.0	4.5	90.22	.03	.40	-2000.00	-2000.000	3.00	-2000.00
	2	89.1	932.0	14.6	448.44	100.00	.10	-2000.00	-2000.000	.80	-2000.00
	3	80.7	1680.0	20.6	570.18	100.00	.10	-2000.00	-2000.000	1.16	-2000.00
	4	33.3	1160.0	20.4	344.89	30.00	.20	-2000.00	-2000.000	1.70	-2000.00
	5	14.3	750.0	19.9	567.72	30.00	.10	-2000.00	-2000.000	1.70	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10925	1	655.4	1469.0	14.5	449.27	30.00	.10	-2000.00	-2000.000	.87	-2000.00
	2	429.3	2888.0	22.2	603.10	30.00	.10	-2000.00	-2000.000	.85	-2000.00
	3	137.8	1850.0	21.6	586.96	100.00	.10	-2000.00	-2000.000	1.07	-2000.00
	4	52.8	1184.0	22.1	596.05	100.00	.10	-2000.00	-2000.000	1.17	-2000.00
	5	27.1	913.0	22.3	362.72	10.00	.20	-2000.00	-2000.000	1.78	-2000.00
10950	1	1037.0	1350.0	18.4	549.32	1.00	.10	-2000.00	-2000.000	.80	-2000.00
	2	268.7	1054.0	20.0	559.81	100.00	.10	-2000.00	-2000.000	.83	-2000.00
	3	107.2	830.0	20.3	564.29	100.00	.10	-2000.00	-2000.000	.82	-2000.00
	4	48.3	632.0	20.6	340.37	10.00	.20	-2000.00	-2000.000	.91	-2000.00
	5	38.6	757.0	14.8	474.02	.30	.10	-2000.00	-2000.000	.75	-2000.00
10975	1	298.6	937.0	19.8	560.22	100.00	.10	-2000.00	-2000.000	.90	-2000.00
	2	90.0	847.5	21.0	346.63	10.00	.20	-2000.00	-2000.000	1.33	-2000.00
	3	40.5	761.0	22.2	383.68	100.00	.20	-2000.00	-2000.000	2.40	-2000.00
	4	26.0	815.0	16.5	307.17	100.00	.20	-2000.00	-2000.000	3.55	-2000.00
	5	11.8	554.0	16.0	268.24	100.00	.30	-2000.00	-2000.000	7.29	-2000.00
11000	1	378.4	1188.0	22.7	619.06	10.00	.10	-2000.00	-2000.000	.90	-2000.00
	2	119.4	1124.0	23.0	615.46	30.00	.10	-2000.00	-2000.000	.62	-2000.00
	3	56.6	1063.0	15.1	512.06	.03	.10	-2000.00	-2000.000	.64	-2000.00
	4	24.1	756.0	14.6	315.37	.03	.20	-2000.00	-2000.000	1.00	-2000.00
	5	23.5	1108.0	17.8	378.35	.03	.20	-2000.00	-2000.000	.76	-2000.00
11025	1	428.4	1490.0	21.4	612.88	1.00	.10	-2000.00	-2000.000	.91	-2000.00
	2	100.4	1050.0	16.5	499.77	3.00	.10	-2000.00	-2000.000	.72	-2000.00
	3	47.0	980.0	15.2	152.25	.30	.40	-2000.00	-2000.000	4.16	-2000.00
	4	37.3	1300.0	18.2	565.51	1.00	.10	-2000.00	-2000.000	3.82	-2000.00
	5	22.0	1150.0	23.9	442.75	.10	.20	-2000.00	-2000.000	1.25	-2000.00
11050	1	356.3	745.0	16.4	517.65	.30	.10	-2000.00	-2000.000	1.19	-2000.00
	2	123.0	772.0	14.5	515.52	.01	.10	-2000.00	-2000.000	1.33	-2000.00
	3	96.8	1212.0	18.5	623.31	.01	.10	-2000.00	-2000.000	.94	-2000.00
	4	49.5	1035.0	24.3	449.63	.10	.20	-2000.00	-2000.000	1.15	-2000.00
	5	26.7	837.0	21.4	405.90	.10	.20	-2000.00	-2000.000	1.09	-2000.00
11075	1	237.9	747.0	13.9	496.53	.01	.10	-2000.00	-2000.000	1.48	-2000.00
	2	147.0	1384.0	18.2	573.63	.10	.10	-2000.00	-2000.000	1.33	-2000.00
	3	67.4	1267.0	25.1	701.57	.30	.10	-2000.00	-2000.000	1.18	-2000.00
	4	29.9	937.0	23.7	631.31	30.00	.10	-2000.00	-2000.000	1.53	-2000.00
	5	15.1	709.0	22.9	372.27	10.00	.20	-2000.00	-2000.000	2.15	-2000.00
11100	1	636.0	1248.0	13.6	273.35	.10	.20	-2000.00	-2000.000	1.97	-2000.00
	2	242.3	1426.0	22.8	727.35	.01	.10	-2000.00	-2000.000	1.23	-2000.00
	3	86.0	1010.0	23.0	618.21	30.00	.10	-2000.00	-2000.000	1.22	-2000.00
	4	36.9	723.0	22.6	609.29	100.00	.10	-2000.00	-2000.000	1.17	-2000.00
11125	1	638.5	1055.0	16.3	320.85	.10	.20	-2000.00	-2000.000	1.93	-2000.00
	2	171.5	850.0	18.6	624.44	.01	.10	-2000.00	-2000.000	.85	-2000.00
	3	62.0	613.0	19.2	593.93	.10	.10	-2000.00	-2000.000	.79	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
11150	1	265.1	1040.0	14.1	188.28	30.00	.30	-2000.00	-2000.000	28.20	-2000.00
	2	66.1	778.0	16.8	522.15	.30	.10	-2000.00	-2000.000	1.08	-2000.00
11175	1	145.5	650.0	12.4	305.77	.01	.20	-2000.00	-2000.000	1.31	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 694

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10675	1	382.9	218.0	2.3	16.88	1.00	.50	-2000.00	-2000.000	2.17	-2000.00
	2	214.7	367.0	3.2	44.23	.30	.30	-2000.00	-2000.000	2.17	-2000.00
	3	77.7	265.0	8.9	321.53	.10	.10	-2000.00	-2000.000	1.59	-2000.00
	4	40.0	228.0	6.0	120.94	30.00	.20	-2000.00	-2000.000	2.94	-2000.00
	5	21.7	185.0	7.1	124.83	100.00	.30	-2000.00	-2000.000	4.87	-2000.00
10700	1	3524.0	2210.0	2.8	71.51	.01	.30	-2000.00	-2000.000	3.91	-2000.00
	2	680.6	1282.0	9.3	212.05	.03	.20	-2000.00	-2000.000	1.74	-2000.00
	3	239.6	900.0	6.9	257.91	.10	.10	-2000.00	-2000.000	1.22	-2000.00
	4	99.4	624.0	7.1	263.13	.10	.10	-2000.00	-2000.000	1.23	-2000.00
	5	38.8	365.0	3.8	100.32	.01	.20	-2000.00	-2000.000	2.10	-2000.00
10725	1	1531.0	1370.0	10.4	391.88	.01	.10	-2000.00	-2000.000	1.61	-2000.00
	2	408.1	1098.0	7.8	273.10	30.00	.10	-2000.00	-2000.000	1.24	-2000.00
	3	155.8	830.0	7.4	146.60	30.00	.20	-2000.00	-2000.000	1.14	-2000.00
	4	54.9	492.0	4.7	106.67	100.00	.20	-2000.00	-2000.000	3.95	-2000.00
	5	37.9	510.0	5.1	62.28	.10	.40	-2000.00	-2000.000	7.70	-2000.00
10750	1	1672.0	1500.0	9.5	328.33	1.00	.10	-2000.00	-2000.000	1.66	-2000.00
	2	506.9	1364.0	8.9	164.38	1.00	.20	-2000.00	-2000.000	1.28	-2000.00
	3	180.7	970.0	5.8	219.09	.10	.10	-2000.00	-2000.000	.50	-2000.00
	4	110.2	980.0	6.6	248.85	.10	.10	-2000.00	-2000.000	1.77	-2000.00
	5	59.0	793.0	7.2	282.74	.01	.10	-2000.00	-2000.000	2.10	-2000.00
10775	1	1324.0	1180.0	8.9	186.06	.10	.20	-2000.00	-2000.000	2.41	-2000.00
	2	368.8	992.0	6.9	160.72	.03	.20	-2000.00	-2000.000	2.18	-2000.00
	3	247.7	1330.0	7.6	176.69	.03	.20	-2000.00	-2000.000	1.90	-2000.00
	4	101.3	900.0	8.6	197.11	.03	.20	-2000.00	-2000.000	2.06	-2000.00
	5	76.0	1022.0	8.7	343.41	.01	.10	-2000.00	-2000.000	5.42	-2000.00
10800	1	1203.0	1020.0	5.7	148.63	.01	.20	-2000.00	-2000.000	2.88	-2000.00
	2	476.8	1213.0	6.7	175.88	.01	.20	-2000.00	-2000.000	3.06	-2000.00
	3	282.8	1430.0	8.2	209.75	.01	.20	-2000.00	-2000.000	2.37	-2000.00
	4	143.7	1210.0	8.5	220.26	.01	.20	-2000.00	-2000.000	2.78	-2000.00
	5	97.7	1243.0	7.7	123.02	.10	.30	-2000.00	-2000.000	2.96	-2000.00
10825	1	2204.0	1970.0	5.8	112.55	.03	.30	-2000.00	-2000.000	2.95	-2000.00
	2	610.2	1642.0	7.5	193.02	.01	.20	-2000.00	-2000.000	2.02	-2000.00
	3	327.3	1750.0	7.9	126.00	.10	.30	-2000.00	-2000.000	1.93	-2000.00
	4	205.8	1840.0	7.7	201.45	.01	.20	-2000.00	-2000.000	2.98	-2000.00
	5	127.3	1710.0	11.1	248.69	.03	.20	-2000.00	-2000.000	1.37	-2000.00
10850	1	1767.0	1490.0	5.7	.110.86	.03	.30	-2000.00	-2000.000	2.28	-2000.00
	2	573.2	1459.0	6.7	107.17	.10	.30	-2000.00	-2000.000	2.15	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
	3	383.6	1940.0	6.5	125.62	.03	.30	-2000.00	-2000.000	1.43	-2000.00
	4	204.3	1730.0	10.6	218.20	.10	.20	-2000.00	-2000.000	1.55	-2000.00
	5	121.2	1540.0	14.3	474.07	.10	.10	-2000.00	-2000.000	1.30	-2000.00
10875	1	1277.0	1140.0	5.6	109.09	.03	.30	-2000.00	-2000.000	2.10	-2000.00
	2	539.5	1452.0	5.8	113.88	.03	.30	-2000.00	-2000.000	1.16	-2000.00
	3	286.1	1530.0	10.1	228.06	.03	.20	-2000.00	-2000.000	1.01	-2000.00
	4	153.0	1370.0	13.9	498.61	.01	.10	-2000.00	-2000.000	1.01	-2000.00
	5	81.7	1098.0	13.0	262.05	.10	.20	-2000.00	-2000.000	1.16	-2000.00
10900	1	1309.0	1140.0	5.6	108.98	.03	.30	-2000.00	-2000.000	1.63	-2000.00
	2	549.7	1438.0	10.8	220.36	.10	.20	-2000.00	-2000.000	1.26	-2000.00
	3	249.1	1300.0	14.9	469.70	1.00	.10	-2000.00	-2000.000	.88	-2000.00
	4	121.0	1050.0	14.1	460.01	.30	.10	-2000.00	-2000.000	1.12	-2000.00
	5	53.3	696.0	9.3	357.29	.10	.10	-2000.00	-2000.000	3.25	-2000.00
10925	1	1748.0	1520.0	12.3	421.27	.10	.10	-2000.00	-2000.000	.89	-2000.00
	2	457.5	1197.0	16.8	497.75	30.00	.10	-2000.00	-2000.000	.65	-2000.00
	3	214.3	1110.0	15.3	490.18	.30	.10	-2000.00	-2000.000	.66	-2000.00
	4	76.8	669.0	10.1	206.59	.10	.20	-2000.00	-2000.000	.82	-2000.00
	5	60.8	795.0	10.3	210.52	.10	.20	-2000.00	-2000.000	.68	-2000.00
10950	1	1753.0	1570.0	18.4	530.36	100.00	.10	-2000.00	-2000.000	.83	-2000.00
	2	538.5	1449.0	18.0	524.38	30.00	.10	-2000.00	-2000.000	.65	-2000.00
	3	148.6	790.0	11.6	380.13	10.00	.10	-2000.00	-2000.000	.83	-2000.00
	4	107.1	960.0	11.6	391.31	.30	.10	-2000.00	-2000.000	.58	-2000.00
	5	129.1	1730.0	15.4	540.48	.01	.10	-2000.00	-2000.000	.94	-2000.00
10975	1	1581.0	1500.0	15.5	483.72	1.00	.10	-2000.00	-2000.000	.74	-2000.00
	2	265.2	757.0	11.2	376.25	1.00	.10	-2000.00	-2000.000	.77	-2000.00
	3	168.3	950.0	11.8	381.18	10.00	.10	-2000.00	-2000.000	.62	-2000.00
	4	184.0	1750.0	16.2	511.20	.30	.10	-2000.00	-2000.000	1.06	-2000.00
	5	99.7	1422.0	23.2	622.93	30.00	.10	-2000.00	-2000.000	1.19	-2000.00
11000	1	891.8	756.0	9.3	324.22	.30	.10	-2000.00	-2000.000	1.36	-2000.00
	2	372.4	948.0	10.1	350.45	.30	.10	-2000.00	-2000.000	.82	-2000.00
	3	382.3	1940.0	15.6	495.72	.30	.10	-2000.00	-2000.000	.79	-2000.00
	4	177.1	1500.0	22.9	641.54	1.00	.10	-2000.00	-2000.000	1.09	-2000.00
	5	102.7	1300.0	22.0	597.80	30.00	.10	-2000.00	-2000.000	.91	-2000.00
11025	1	878.3	745.0	7.1	284.48	.01	.10	-2000.00	-2000.000	1.98	-2000.00
	2	716.5	1824.0	13.3	266.17	.10	.20	-2000.00	-2000.000	1.23	-2000.00
	3	303.1	1540.0	21.3	627.13	.30	.10	-2000.00	-2000.000	1.02	-2000.00
	4	164.8	1390.0	20.5	578.77	10.00	.10	-2000.00	-2000.000	1.10	-2000.00
	5	88.0	1120.0	25.5	659.12	30.00	.10	-2000.00	-2000.000	1.07	-2000.00
11050	1	1439.0	1250.0	9.3	210.86	.03	.20	-2000.00	-2000.000	1.55	-2000.00
	2	478.3	1251.0	18.9	634.63	.01	.10	-2000.00	-2000.000	1.14	-2000.00
	3	257.1	1340.0	18.4	564.03	.30	.10	-2000.00	-2000.000	.97	-2000.00
	4	128.3	1110.0	23.6	656.45	1.00	.10	-2000.00	-2000.000	1.16	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	58.7	768.0	21.2	703.68	.01	.10	-2000.00	-2000.000	3.01	-2000.00
11075	1	521.6	655.0	16.1	523.06	.10	.10	-2000.00	-2000.000	1.29	-2000.00
	2	217.5	819.0	17.0	503.64	30.00	.10	-2000.00	-2000.000	1.62	-2000.00
	3	103.8	780.0	22.4	604.43	100.00	.10	-2000.00	-2000.000	1.48	-2000.00
	4	45.2	567.0	21.0	586.57	30.00	.10	-2000.00	-2000.000	2.53	-2000.00
	5	23.7	446.0	18.4	320.75	30.00	.20	-2000.00	-2000.000	3.13	-2000.00
11100	1	201.0	1050.0	15.9	391.15	.01	.20	-2000.00	-2000.000	2.26	-2000.00
	2	70.2	1102.0	20.7	437.23	.03	.20	-2000.00	-2000.000	1.33	-2000.00
	3	22.7	710.0	17.4	328.24	.03	.30	-2000.00	-2000.000	1.32	-2000.00
	4	10.5	540.0	11.5	162.01	.10	.50	-2000.00	-2000.000	2.24	-2000.00
	5	8.0	631.0	11.2	98.89	.30	.70	-2000.00	-2000.000	4.75	-2000.00
11125	1	1098.0	1720.0	17.0	564.26	.03	.10	-2000.00	-2000.000	1.46	-2000.00
	2	140.4	661.0	20.2	387.94	.10	.20	-2000.00	-2000.000	1.77	-2000.00
	3	53.0	498.0	15.7	334.82	.03	.20	-2000.00	-2000.000	1.22	-2000.00
	4	37.3	586.0	17.4	342.67	.10	.20	-2000.00	-2000.000	2.75	-2000.00
11150	1	226.3	780.0	20.4	625.62	.10	.10	-2000.00	-2000.000	1.33	-2000.00
	2	54.4	569.0	16.1	523.90	.10	.10	-2000.00	-2000.000	1.44	-2000.00
	3	33.5	690.0	17.2	590.36	.01	.10	-2000.00	-2000.000	1.39	-2000.00
11175	1	149.9	470.0	19.0	595.27	.10	.10	-2000.00	-2000.000	1.26	-2000.00
	2	63.3	596.2	19.0	592.52	.10	.10	-2000.00	-2000.000	1.14	-2000.00
11200	1	214.0	830.0	13.5	332.70	.01	.20	-2000.00	-2000.000	1.48	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 684

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10675	1	421.0	293.0	2.3	36.10	.10	.30	-2000.00	-2000.000	3.06	-2000.00
	2	132.6	277.0	2.6	37.95	.30	.30	-2000.00	-2000.000	7.02	-2000.00
	3	95.8	400.0	3.6	71.29	.03	.30	-2000.00	-2000.000	2.07	-2000.00
	4	27.0	188.0	5.9	81.45	.30	.30	-2000.00	-2000.000	4.72	-2000.00
	5	14.9	156.0	7.5	149.86	30.00	.20	-2000.00	-2000.000	5.69	-2000.00
10700	1	1876.0	650.0	1.9	37.06	.03	.30	-2000.00	-2000.000	3.01	-2000.00
	2	790.1	826.0	3.4	83.32	.01	.30	-2000.00	-2000.000	1.80	-2000.00
	3	158.4	330.0	6.1	126.47	.10	.20	-2000.00	-2000.000	1.80	-2000.00
	4	70.2	244.0	7.4	267.77	100.00	.10	-2000.00	-2000.000	4.53	-2000.00
	5	50.2	262.0	5.2	212.95	.01	.10	-2000.00	-2000.000	1.67	-2000.00
10725	1	2405.0	1880.0	4.2	104.69	.01	.30	-2000.00	-2000.000	2.82	-2000.00
	2	339.1	798.0	7.0	162.24	.03	.20	-2000.00	-2000.000	1.23	-2000.00
	3	115.8	540.0	9.2	311.48	100.00	.10	-2000.00	-2000.000	1.79	-2000.00
	4	61.2	480.0	6.1	253.24	.01	.10	-2000.00	-2000.000	2.78	-2000.00
	5	23.9	281.0	5.0	118.37	.03	.20	-2000.00	-2000.000	2.64	-2000.00
10750	1	1819.0	1260.0	7.2	152.73	.10	.20	-2000.00	-2000.000	3.04	-2000.00
	2	546.0	1142.0	9.9	332.94	100.00	.10	-2000.00	-2000.000	1.60	-2000.00
	3	245.4	1020.0	7.5	265.12	30.00	.10	-2000.00	-2000.000	1.09	-2000.00
	4	84.3	588.0	6.4	242.59	.10	.10	-2000.00	-2000.000	1.94	-2000.00
	5	45.8	479.0	6.2	223.14	30.00	.10	-2000.00	-2000.000	4.63	-2000.00
10775	1	337.9	1170.0	11.5	258.31	.03	.20	-2000.00	-2000.000	2.38	-2000.00
	2	124.8	1300.0	9.4	238.06	.01	.20	-2000.00	-2000.000	2.05	-2000.00
	3	39.3	820.0	8.7	77.21	.30	.50	-2000.00	-2000.000	4.37	-2000.00
	4	19.9	690.0	6.8	299.36	.10	.10	-2000.00	-2000.000	13.35	-2000.00
	5	17.3	900.0	8.4	159.89	.03	.30	-2000.00	-2000.000	2.43	-2000.00
10800	1	561.9	1102.0	8.7	198.11	.03	.20	-2000.00	-2000.000	2.09	-2000.00
	2	137.4	808.0	8.4	213.37	.01	.20	-2000.00	-2000.000	2.22	-2000.00
	3	56.5	664.0	8.4	212.85	.01	.20	-2000.00	-2000.000	1.33	-2000.00
	4	48.8	958.0	9.1	210.11	.03	.20	-2000.00	-2000.000	4.45	-2000.00
	5	27.2	800.0	9.5	180.15	.03	.30	-2000.00	-2000.000	2.82	-2000.00
10825	1	793.6	1245.0	9.2	354.33	.01	.10	-2000.00	-2000.000	2.18	-2000.00
	2	192.9	908.0	9.8	202.93	.10	.20	-2000.00	-2000.000	1.92	-2000.00
	3	150.9	1410.0	10.2	233.37	.03	.20	-2000.00	-2000.000	1.96	-2000.00
	4	71.1	1116.0	12.5	246.32	.10	.20	-2000.00	-2000.000	1.51	-2000.00
	5	40.8	961.0	10.5	398.38	.01	.10	-2000.00	-2000.000	1.76	-2000.00
10850	1	731.0	1275.0	9.3	235.94	.01	.20	-2000.00	-2000.000	2.05	-2000.00
	2	401.2	2099.0	10.9	272.53	.01	.20	-2000.00	-2000.000	1.37	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	155.6	1620.0	12.1	268.71	.03	.20	-2000.00	-2000.000	1.15	-2000.00
	4	74.3	1295.0	10.9	244.11	.03	.20	-2000.00	-2000.000	1.19	-2000.00
	5	52.2	1364.0	9.3	231.58	.01	.20	-2000.00	-2000.000	1.32	-2000.00
10875	1	840.7	1649.0	8.6	164.32	.03	.30	-2000.00	-2000.000	2.39	-2000.00
	2	225.6	1328.0	10.4	262.07	.01	.20	-2000.00	-2000.000	1.65	-2000.00
	3	95.9	1127.0	10.0	248.28	.01	.20	-2000.00	-2000.000	.73	-2000.00
	4	61.2	1200.0	8.7	221.04	.01	.20	-2000.00	-2000.000	1.73	-2000.00
	5	28.0	823.0	5.1	122.98	.01	.30	-2000.00	-2000.000	1.99	-2000.00
10900	1	569.5	1192.0	9.9	249.18	.01	.20	-2000.00	-2000.000	1.48	-2000.00
	2	167.6	1052.0	8.9	225.43	.01	.20	-2000.00	-2000.000	.74	-2000.00
	3	110.5	1380.0	8.1	207.28	.01	.20	-2000.00	-2000.000	1.58	-2000.00
	4	39.0	816.0	4.2	103.22	.01	.30	-2000.00	-2000.000	6.00	-2000.00
	5	23.4	733.0	6.5	73.92	.30	.40	-2000.00	-2000.000	4.16	-2000.00
10925	1	442.1	991.0	7.9	152.76	.03	.30	-2000.00	-2000.000	6.16	-2000.00
	2	200.3	1347.0	8.6	219.02	.01	.20	-2000.00	-2000.000	1.44	-2000.00
	3	61.8	829.0	5.5	106.25	.03	.30	-2000.00	-2000.000	2.19	-2000.00
	4	34.5	772.0	6.1	117.86	.03	.30	-2000.00	-2000.000	1.97	-2000.00
	5	28.4	953.0	7.3	114.27	.10	.30	-2000.00	-2000.000	2.51	-2000.00
10950	1	385.2	1209.0	8.5	137.87	.10	.30	-2000.00	-2000.000	3.24	-2000.00
	2	76.8	723.5	5.9	142.01	.01	.30	-2000.00	-2000.000	2.03	-2000.00
	3	43.4	815.0	6.6	129.38	.03	.30	-2000.00	-2000.000	1.07	-2000.00
	4	30.8	967.0	8.8	342.67	.01	.10	-2000.00	-2000.000	3.43	-2000.00
	5	36.5	1721.0	16.2	350.40	.03	.20	-2000.00	-2000.000	.87	-2000.00
10975	1	299.7	627.0	7.1	182.03	.01	.20	-2000.00	-2000.000	1.56	-2000.00
	2	124.2	779.0	7.5	172.74	.03	.20	-2000.00	-2000.000	1.29	-2000.00
	3	76.1	953.0	8.3	173.33	.10	.20	-2000.00	-2000.000	1.28	-2000.00
	4	83.8	1755.0	17.8	563.04	.10	.10	-2000.00	-2000.000	.99	-2000.00
	5	60.0	1884.0	21.1	688.25	.01	.10	-2000.00	-2000.000	1.88	-2000.00
11000	1	467.3	666.0	4.2	109.60	.01	.20	-2000.00	-2000.000	1.51	-2000.00
	2	219.3	939.0	6.1	139.50	.03	.20	-2000.00	-2000.000	1.37	-2000.00
	3	213.3	1820.0	16.4	504.23	1.00	.10	-2000.00	-2000.000	.69	-2000.00
	4	138.8	1980.0	20.1	616.89	.10	.10	-2000.00	-2000.000	.82	-2000.00
	5	50.6	1083.0	20.8	627.10	.10	.10	-2000.00	-2000.000	1.09	-2000.00
11025	1	437.4	624.0	3.4	54.39	.10	.30	-2000.00	-2000.000	2.48	-2000.00
	2	335.6	1436.0	14.6	484.00	.10	.10	-2000.00	-2000.000	1.13	-2000.00
	3	185.1	1580.0	18.5	578.03	.10	.10	-2000.00	-2000.000	.74	-2000.00
	4	65.6	936.0	19.9	566.78	30.00	.10	-2000.00	-2000.000	2.15	-2000.00
	5	49.6	1062.0	19.5	551.26	100.00	.10	-2000.00	-2000.000	.91	-2000.00
11050	1	448.9	829.0	12.4	250.49	.10	.20	-2000.00	-2000.000	1.55	-2000.00
	2	202.4	1121.0	17.2	588.42	.01	.10	-2000.00	-2000.000	.86	-2000.00
	3	64.6	713.0	18.8	561.41	1.00	.10	-2000.00	-2000.000	1.07	-2000.00
	4	46.5	858.0	18.2	537.27	3.00	.10	-2000.00	-2000.000	.89	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	22.6	627.0	22.0	644.12	.30	.10	-2000.00	-2000.000	1.55	-2000.00
11075	1	160.8	840.0	15.8	240.80	.10	.30	-2000.00	-2000.000	2.05	-2000.00
	2	38.2	599.0	17.9	627.14	.01	.10	-2000.00	-2000.000	3.15	-2000.00
	3	25.4	790.0	16.6	328.59	.10	.20	-2000.00	-2000.000	1.73	-2000.00
	4	11.9	620.0	20.4	433.11	.03	.20	-2000.00	-2000.000	2.08	-2000.00
	5	6.9	539.0	15.7	386.02	.01	.20	-2000.00	-2000.000	2.93	-2000.00
11100	1	324.6	536.0	20.5	577.27	10.00	.10	-2000.00	-2000.000	1.38	-2000.00
	2	153.3	760.0	16.5	492.59	30.00	.10	-2000.00	-2000.000	.95	-2000.00
	3	63.2	625.0	20.4	592.56	1.00	.10	-2000.00	-2000.000	1.15	-2000.00
	4	33.0	545.0	15.8	549.16	.01	.10	-2000.00	-2000.000	1.40	-2000.00
	5	19.9	493.0	13.8	491.10	.01	.10	-2000.00	-2000.000	1.68	-2000.00
11125	1	310.1	973.0	17.2	596.96	.01	.10	-2000.00	-2000.000	1.59	-2000.00
	2	86.5	815.0	23.0	699.99	.03	.10	-2000.00	-2000.000	1.35	-2000.00
	3	36.2	679.0	18.0	608.28	.01	.10	-2000.00	-2000.000	1.95	-2000.00
	4	19.4	607.0	16.1	308.42	.10	.20	-2000.00	-2000.000	2.16	-2000.00
11150	1	254.0	1130.0	21.0	637.71	.10	.10	-2000.00	-2000.000	1.31	-2000.00
	2	56.9	766.0	16.6	326.09	.10	.20	-2000.00	-2000.000	1.64	-2000.00
	3	26.6	710.0	12.7	298.90	.03	.20	-2000.00	-2000.000	5.86	-2000.00
11175	1	186.1	730.0	18.0	543.86	1.00	.10	-2000.00	-2000.000	1.73	-2000.00
	2	59.4	699.0	16.5	497.74	100.00	.10	-2000.00	-2000.000	2.86	-2000.00
11200	1	297.7	719.0	13.6	271.16	.10	.20	-2000.00	-2000.000	1.70	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 674

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10675	1	72.1	251.0	2.5	50.17	.03	.30	-2000.00	-2000.000	2.39	-2000.00
	2	21.4	223.0	2.1	18.72	.30	.50	-2000.00	-2000.000	7.55	-2000.00
	3	12.8	260.0	-.1	19.90	100.00	.30	-2000.00	-2000.000	95.44	-2000.00
	4	7.6	263.0	-.1	46.07	.10	.10	-2000.00	-2000.000	124.02	-2000.00
	5	3.8	197.0	-.1	52.74	.01	.50	-2000.00	-2000.000	142.40	-2000.00
10700	1	395.4	191.0	1.8	51.33	.01	.40	-2000.00	-2000.000	3.19	-2000.00
	2	179.5	260.0	1.2	35.28	.01	.30	-2000.00	-2000.000	13.64	-2000.00
	3	89.1	257.0	1.7	35.47	.03	.40	-2000.00	-2000.000	9.27	-2000.00
	4	39.9	192.0	3.1	60.04	.03	.40	-2000.00	-2000.000	2.86	-2000.00
	5	26.9	195.0	.9	33.89	.03	.50	-2000.00	-2000.000	45.57	-2000.00
10725	1	447.9	327.0	1.4	42.48	.01	.40	-2000.00	-2000.000	6.39	-2000.00
	2	150.0	328.0	2.5	61.69	.01	.30	-2000.00	-2000.000	3.83	-2000.00
	3	54.6	238.0	4.7	123.56	.01	.20	-2000.00	-2000.000	2.86	-2000.00
	4	30.3	221.0	4.6	174.47	1.00	.10	-2000.00	-2000.000	4.09	-2000.00
	5	17.8	194.0	6.5	244.02	.10	.10	-2000.00	-2000.000	2.36	-2000.00
10750	1	1019.0	630.0	3.1	61.94	.03	.30	-2000.00	-2000.000	3.57	-2000.00
	2	256.6	483.0	5.6	146.12	.01	.20	-2000.00	-2000.000	2.60	-2000.00
	3	109.1	410.0	6.1	140.59	.03	.20	-2000.00	-2000.000	2.01	-2000.00
	4	54.4	341.0	7.5	171.45	.03	.20	-2000.00	-2000.000	2.02	-2000.00
	5	35.2	331.0	5.5	86.09	.10	.30	-2000.00	-2000.000	1.87	-2000.00
10775	1	2265.0	940.0	6.0	140.04	.03	.20	-2000.00	-2000.000	2.25	-2000.00
	2	623.7	783.0	7.5	294.94	.01	.10	-2000.00	-2000.000	1.72	-2000.00
	3	265.0	660.0	9.0	343.45	.01	.10	-2000.00	-2000.000	1.10	-2000.00
	4	133.9	560.0	7.3	286.39	.01	.10	-2000.00	-2000.000	1.80	-2000.00
	5	80.4	505.0	5.5	222.83	.01	.10	-2000.00	-2000.000	2.62	-2000.00
10800	1	882.8	815.0	8.0	166.92	.10	.20	-2000.00	-2000.000	1.96	-2000.00
	2	315.4	873.0	9.7	199.65	.10	.20	-2000.00	-2000.000	1.54	-2000.00
	3	132.0	720.0	8.4	174.24	.10	.20	-2000.00	-2000.000	1.23	-2000.00
	4	70.7	653.0	6.6	167.64	.01	.20	-2000.00	-2000.000	.98	-2000.00
	5	31.9	442.0	5.5	48.22	.30	.50	-2000.00	-2000.000	22.44	-2000.00
10825	1	1090.0	920.0	10.5	234.75	.03	.20	-2000.00	-2000.000	2.11	-2000.00
	2	340.2	866.0	9.7	219.38	.03	.20	-2000.00	-2000.000	1.71	-2000.00
	3	155.7	790.0	7.9	165.55	.10	.20	-2000.00	-2000.000	1.31	-2000.00
	4	65.3	554.0	7.2	166.51	.03	.20	-2000.00	-2000.000	2.23	-2000.00
	5	57.0	725.0	5.9	136.55	.03	.20	-2000.00	-2000.000	1.58	-2000.00
10850	1	1531.0	1230.0	9.9	249.31	.01	.20	-2000.00	-2000.000	2.03	-2000.00
	2	434.2	1048.0	8.7	221.85	.01	.20	-2000.00	-2000.000	1.90	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	150.3	720.0	7.9	175.69	.03	.20	-2000.00	-2000.000	1.84	-2000.00
	4	119.2	950.0	6.1	164.71	.01	.20	-2000.00	-2000.000	4.21	-2000.00
	5	25.6	309.0	1.6	39.55	.03	.50	-2000.00	-2000.000	6.74	-2000.00
10875	1	1359.0	1180.0	7.9	204.03	.01	.20	-2000.00	-2000.000	2.89	-2000.00
	2	349.5	914.0	8.1	208.86	.01	.20	-2000.00	-2000.000	1.35	-2000.00
	3	233.2	1210.0	7.6	192.89	.01	.20	-2000.00	-2000.000	1.17	-2000.00
	4	44.7	389.0	3.1	61.88	.03	.40	-2000.00	-2000.000	3.44	-2000.00
	5	32.2	421.0	.9	38.52	.01	.40	-2000.00	-2000.000	55.36	-2000.00
10900	1	1507.0	1150.0	7.3	188.35	.01	.20	-2000.00	-2000.000	3.03	-2000.00
	2	750.9	1725.0	8.4	213.11	.01	.20	-2000.00	-2000.000	1.42	-2000.00
	3	128.5	580.0	4.3	35.66	.30	.60	-2000.00	-2000.000	4.32	-2000.00
	4	74.1	567.0	3.0	128.15	30.00	.10	-2000.00	-2000.000	13.68	-2000.00
	5	61.9	710.0	5.6	86.55	.10	.30	-2000.00	-2000.000	3.61	-2000.00
10925	1	2330.0	1820.0	7.2	186.20	.01	.20	-2000.00	-2000.000	3.18	-2000.00
	2	195.7	460.0	5.2	50.87	1.00	.40	-2000.00	-2000.000	4.49	-2000.00
	3	131.7	610.0	3.1	74.23	.01	.30	-2000.00	-2000.000	3.44	-2000.00
	4	86.3	677.0	5.8	95.64	.10	.30	-2000.00	-2000.000	2.35	-2000.00
	5	71.0	836.0	6.8	156.03	.03	.20	-2000.00	-2000.000	1.86	-2000.00
10947	1	74.0	232.2	3.9	98.48	.01	.30	-2000.00	-2000.000	5.54	-2000.00
	2	51.0	480.4	3.4	68.24	.03	.40	-2000.00	-2000.000	4.73	-2000.00
	3	42.5	798.0	6.8	176.62	.01	.20	-2000.00	-2000.000	2.94	-2000.00
	4	24.4	766.0	7.4	172.22	.03	.20	-2000.00	-2000.000	3.49	-2000.00
	5	23.1	1088.0	9.5	197.73	.10	.20	-2000.00	-2000.000	2.50	-2000.00
10972	1	173.2	670.0	2.3	54.44	.03	.50	-2000.00	-2000.000	5.07	-2000.00
	2	61.9	728.0	6.2	120.00	.03	.30	-2000.00	-2000.000	3.63	-2000.00
	3	34.9	820.0	6.6	127.41	.03	.30	-2000.00	-2000.000	2.82	-2000.00
	4	33.6	1310.0	10.1	251.62	.01	.20	-2000.00	-2000.000	2.30	-2000.00
	5	40.9	2400.0	13.2	321.35	.01	.20	-2000.00	-2000.000	2.05	-2000.00
10997	1	307.0	481.0	4.8	124.38	.01	.20	-2000.00	-2000.000	2.44	-2000.00
	2	120.6	568.0	6.9	273.40	.01	.10	-2000.00	-2000.000	1.84	-2000.00
	3	110.3	1030.0	10.2	385.38	.01	.10	-2000.00	-2000.000	1.22	-2000.00
	4	111.5	1750.0	13.5	486.39	.01	.10	-2000.00	-2000.000	1.28	-2000.00
	5	47.8	1124.0	14.5	482.28	.10	.10	-2000.00	-2000.000	1.29	-2000.00
11023	1	241.6	421.0	5.0	127.98	.01	.20	-2000.00	-2000.000	2.53	-2000.00
	2	169.7	888.0	10.1	380.08	.01	.10	-2000.00	-2000.000	1.42	-2000.00
	3	146.7	1530.0	13.7	489.49	.01	.10	-2000.00	-2000.000	1.21	-2000.00
	4	48.2	840.0	14.3	508.21	.01	.10	-2000.00	-2000.000	.91	-2000.00
	5	50.5	1320.0	17.8	546.53	.30	.10	-2000.00	-2000.000	1.11	-2000.00
11050	1	497.4	743.0	7.0	147.73	.10	.20	-2000.00	-2000.000	1.86	-2000.00
	2	318.1	1426.0	12.2	447.13	.01	.10	-2000.00	-2000.000	1.58	-2000.00
	3	97.6	873.0	14.3	443.44	30.00	.10	-2000.00	-2000.000	1.23	-2000.00
	4	75.0	1122.0	18.0	522.46	100.00	.10	-2000.00	-2000.000	2.04	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	43.4	972.0	20.9	347.34	10.00	.20	-2000.00	-2000.000	2.37	-2000.00
11075	1	827.8	1083.0	9.1	188.56	.10	.20	-2000.00	-2000.000	1.73	-2000.00
	2	169.9	666.0	11.7	416.84	.03	.10	-2000.00	-2000.000	.84	-2000.00
	3	126.2	980.0	16.2	523.37	.10	.10	-2000.00	-2000.000	.87	-2000.00
	4	55.9	731.0	17.4	531.34	1.00	.10	-2000.00	-2000.000	1.62	-2000.00
	5	26.2	513.0	16.2	538.80	.10	.10	-2000.00	-2000.000	1.98	-2000.00
11100	1	530.9	757.0	10.4	390.86	.01	.10	-2000.00	-2000.000	1.79	-2000.00
	2	253.3	1084.0	16.0	505.71	.30	.10	-2000.00	-2000.000	1.32	-2000.00
	3	96.2	822.0	18.3	548.62	1.00	.10	-2000.00	-2000.000	1.13	-2000.00
	4	34.0	484.0	17.3	533.60	.30	.10	-2000.00	-2000.000	1.31	-2000.00
	5	26.6	569.0	15.6	472.32	30.00	.10	-2000.00	-2000.000	1.83	-2000.00
11125	1	480.5	1508.0	17.1	329.05	.10	.20	-2000.00	-2000.000	1.69	-2000.00
	2	121.7	1146.0	21.5	647.23	.10	.10	-2000.00	-2000.000	1.34	-2000.00
	3	37.4	703.0	17.1	222.69	.30	.30	-2000.00	-2000.000	1.07	-2000.00
	4	23.3	730.0	19.6	359.57	100.00	.20	-2000.00	-2000.000	4.26	-2000.00
11150	1	426.6	956.0	18.4	562.26	.30	.10	-2000.00	-2000.000	1.45	-2000.00
	2	100.0	672.0	17.2	333.61	.10	.20	-2000.00	-2000.000	1.02	-2000.00
	3	52.3	702.0	15.5	509.87	.10	.10	-2000.00	-2000.000	1.83	-2000.00
11175	1	238.2	747.0	13.7	460.70	.10	.10	-2000.00	-2000.000	2.07	-2000.00
	2	94.3	888.7	13.2	447.22	.10	.10	-2000.00	-2000.000	2.25	-2000.00
11200	1	137.6	860.0	12.1	270.92	.03	.20	-2000.00	-2000.000	2.45	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 664

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	331.9	208.0	1.0	49.59	30.00	.10	-2000.00	-2000.000	15.82	-2000.00
	2	88.9	167.5	.9	48.96	30.00	.10	-2000.00	-2000.000	18.76	-2000.00
	3	43.1	162.0	1.3	37.79	.01	.20	-2000.00	-2000.000	9.67	-2000.00
	4	23.1	144.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	14.8	139.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10750	1	336.4	211.0	1.1	34.74	.01	.20	-2000.00	-2000.000	16.76	-2000.00
	2	83.3	156.8	1.6	32.24	.03	.30	-2000.00	-2000.000	4.64	-2000.00
	3	38.2	143.0	1.6	40.57	.01	.20	-2000.00	-2000.000	6.94	-2000.00
	4	22.2	139.0	.5	24.57	.03	.30	-2000.00	-2000.000	36.59	-2000.00
	5	30.8	290.0	.8	56.76	.01	.10	-2000.00	-2000.000	29.80	-2000.00
10775	1	342.8	149.0	1.5	30.39	.03	.30	-2000.00	-2000.000	3.80	-2000.00
	2	108.4	141.0	1.7	33.10	.03	.30	-2000.00	-2000.000	3.12	-2000.00
	3	53.8	140.0	1.7	70.16	1.00	.10	-2000.00	-2000.000	4.95	-2000.00
	4	66.6	290.0	1.6	38.91	.03	.20	-2000.00	-2000.000	3.10	-2000.00
	5	72.1	471.0	3.6	71.31	10.00	.20	-2000.00	-2000.000	3.91	-2000.00
10800	1	426.1	196.0	1.9	36.94	.03	.30	-2000.00	-2000.000	2.14	-2000.00
	2	123.1	170.0	1.9	50.94	.01	.20	-2000.00	-2000.000	3.02	-2000.00
	3	128.5	350.0	2.2	47.38	10.00	.20	-2000.00	-2000.000	6.20	-2000.00
	4	96.2	444.0	3.6	145.93	.01	.10	-2000.00	-2000.000	1.45	-2000.00
	5	30.6	212.0	2.1	35.52	30.00	.30	-2000.00	-2000.000	11.44	-2000.00
10825	1	443.4	214.0	2.2	43.67	.03	.30	-2000.00	-2000.000	1.85	-2000.00
	2	277.8	402.0	2.7	52.19	.03	.30	-2000.00	-2000.000	2.16	-2000.00
	3	187.1	540.0	3.9	85.63	.10	.20	-2000.00	-2000.000	2.41	-2000.00
	4	34.0	164.0	2.2	19.99	.30	.60	-2000.00	-2000.000	5.21	-2000.00
	5	17.9	129.0	1.4	36.86	.01	.30	-2000.00	-2000.000	6.57	-2000.00
10850	1	967.5	482.0	2.5	49.39	.03	.30	-2000.00	-2000.000	2.19	-2000.00
	2	431.9	645.0	4.4	113.15	.01	.20	-2000.00	-2000.000	1.41	-2000.00
	3	67.8	202.0	2.6	21.70	.30	.60	-2000.00	-2000.000	5.38	-2000.00
	4	30.5	152.0	1.8	54.00	.01	.40	-2000.00	-2000.000	5.19	-2000.00
	5	21.6	161.0	1.1	41.19	.01	.40	-2000.00	-2000.000	29.80	-2000.00
10875	1	1369.0	720.0	3.7	98.32	.01	.20	-2000.00	-2000.000	2.79	-2000.00
	2	148.2	236.0	2.8	68.36	.01	.30	-2000.00	-2000.000	1.49	-2000.00
	3	59.8	190.0	2.0	40.55	.03	.40	-2000.00	-2000.000	2.66	-2000.00
	4	37.3	198.0	2.1	27.98	.10	.50	-2000.00	-2000.000	5.06	-2000.00
	5	28.3	225.0	.7	24.57	.03	.30	-2000.00	-2000.000	39.77	-2000.00
10900	1	924.1	446.0	1.8	45.93	.01	.30	-2000.00	-2000.000	3.79	-2000.00
	2	255.8	370.0	2.1	51.03	.01	.30	-2000.00	-2000.000	3.09	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	140.8	400.0	2.4	58.27	.01	.30	-2000.00	-2000.000	2.82	-2000.00
	4	90.4	436.0	1.8	44.96	.01	.30	-2000.00	-2000.000	3.41	-2000.00
	5	72.0	521.0	1.9	36.92	.03	.30	-2000.00	-2000.000	5.03	-2000.00
10925	1	1305.0	650.0	1.6	40.75	.01	.30	-2000.00	-2000.000	4.94	-2000.00
	2	456.2	682.0	2.3	57.46	.01	.30	-2000.00	-2000.000	3.75	-2000.00
	3	250.1	740.0	1.8	45.41	.01	.30	-2000.00	-2000.000	4.16	-2000.00
	4	168.9	840.0	1.8	36.73	.03	.30	-2000.00	-2000.000	5.51	-2000.00
	5	117.7	870.0	4.7	101.51	.10	.20	-2000.00	-2000.000	2.56	-2000.00
10950	1	926.6	454.0	1.8	35.19	.03	.40	-2000.00	-2000.000	3.86	-2000.00
	2	389.3	573.0	1.5	39.03	.01	.30	-2000.00	-2000.000	6.42	-2000.00
	3	265.7	780.0	1.5	40.07	.01	.30	-2000.00	-2000.000	5.86	-2000.00
	4	167.0	810.0	4.1	99.91	.03	.20	-2000.00	-2000.000	3.03	-2000.00
	5	131.3	960.0	4.9	110.23	.03	.20	-2000.00	-2000.000	2.49	-2000.00
10975	1	731.2	353.0	1.2	36.42	.01	.20	-2000.00	-2000.000	12.94	-2000.00
	2	374.5	542.0	1.3	35.93	.01	.30	-2000.00	-2000.000	9.10	-2000.00
	3	215.4	620.0	4.2	98.73	.03	.20	-2000.00	-2000.000	1.92	-2000.00
	4	159.8	770.0	4.4	104.85	.03	.20	-2000.00	-2000.000	2.51	-2000.00
	5	126.0	910.0	6.4	135.76	.10	.20	-2000.00	-2000.000	2.13	-2000.00
11000	1	927.7	434.0	.9	49.07	.10	.10	-2000.00	-2000.000	22.94	-2000.00
	2	366.0	514.0	4.1	97.75	.03	.20	-2000.00	-2000.000	2.22	-2000.00
	3	238.0	660.0	4.5	117.69	.01	.20	-2000.00	-2000.000	1.78	-2000.00
	4	171.1	800.0	6.2	144.13	.03	.20	-2000.00	-2000.000	1.49	-2000.00
	5	133.9	940.0	7.3	151.79	.10	.20	-2000.00	-2000.000	1.70	-2000.00
11025	1	154.9	405.0	3.6	71.40	.03	.30	-2000.00	-2000.000	3.53	-2000.00
	2	74.1	581.4	4.9	94.46	.03	.30	-2000.00	-2000.000	2.90	-2000.00
	3	44.8	702.0	5.6	109.23	.03	.30	-2000.00	-2000.000	2.40	-2000.00
	4	31.9	835.0	6.2	147.95	.01	.30	-2000.00	-2000.000	2.19	-2000.00
	5	23.5	923.0	6.2	151.45	.01	.30	-2000.00	-2000.000	2.75	-2000.00
11050	1	363.4	518.0	5.0	117.60	.03	.20	-2000.00	-2000.000	1.96	-2000.00
	2	149.4	639.0	6.7	266.37	.01	.10	-2000.00	-2000.000	2.25	-2000.00
	3	90.8	775.0	7.2	270.90	1.00	.10	-2000.00	-2000.000	3.90	-2000.00
	4	62.4	890.0	8.7	112.95	.30	.30	-2000.00	-2000.000	3.19	-2000.00
	5	51.3	1097.0	10.1	378.85	1.00	.10	-2000.00	-2000.000	8.55	-2000.00
11075	1	359.4	564.0	4.0	105.57	.01	.20	-2000.00	-2000.000	3.16	-2000.00
	2	153.6	723.0	6.0	154.20	.01	.20	-2000.00	-2000.000	1.57	-2000.00
	3	100.1	940.0	7.0	160.55	.03	.20	-2000.00	-2000.000	1.58	-2000.00
	4	63.6	998.0	10.0	204.98	.10	.20	-2000.00	-2000.000	1.59	-2000.00
	5	46.4	1092.0	12.2	261.20	.03	.20	-2000.00	-2000.000	2.86	-2000.00
11100	1	435.8	594.0	4.4	70.63	.10	.30	-2000.00	-2000.000	2.88	-2000.00
	2	221.7	908.0	5.8	149.25	.01	.20	-2000.00	-2000.000	1.74	-2000.00
	3	134.3	1090.0	9.1	188.95	.10	.20	-2000.00	-2000.000	1.23	-2000.00
	4	82.4	1125.0	11.3	425.62	.01	.10	-2000.00	-2000.000	1.96	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	70.4	1441.0	12.9	258.72	.10	.20	-2000.00	-2000.000	1.31	-2000.00
11125	1	402.7	665.0	4.0	94.42	.01	.30	-2000.00	-2000.000	2.35	-2000.00
	2	200.8	995.0	7.6	196.18	.01	.20	-2000.00	-2000.000	1.78	-2000.00
	3	139.1	1370.0	9.9	225.11	.03	.20	-2000.00	-2000.000	1.49	-2000.00
	4	78.3	1294.0	12.0	180.97	.10	.30	-2000.00	-2000.000	1.74	-2000.00
	5	57.3	1420.0	14.6	320.03	.03	.20	-2000.00	-2000.000	1.08	-2000.00
11150	1	468.8	774.0	5.2	134.63	.01	.20	-2000.00	-2000.000	2.97	-2000.00
	2	234.5	1162.0	8.8	200.73	.03	.20	-2000.00	-2000.000	2.20	-2000.00
	3	158.8	1570.0	11.0	409.80	.01	.10	-2000.00	-2000.000	1.45	-2000.00
	4	92.0	1520.0	14.6	517.80	.01	.10	-2000.00	-2000.000	1.59	-2000.00
11175	1	219.8	690.0	6.0	95.84	.10	.30	-2000.00	-2000.000	1.99	-2000.00
	2	143.8	1354.0	9.1	227.63	.01	.20	-2000.00	-2000.000	1.94	-2000.00
	3	62.4	1172.0	12.6	280.95	.03	.20	-2000.00	-2000.000	1.15	-2000.00
11200	1	283.7	809.0	5.8	150.80	.01	.20	-2000.00	-2000.000	2.68	-2000.00
	2	124.5	1066.0	10.8	220.30	.10	.20	-2000.00	-2000.000	2.16	-2000.00
11225	1	108.7	850.0	7.4	191.63	.01	.20	-2000.00	-2000.000	3.48	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 654

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10725	1	750.9	336.0	1.5	38.59	.01	.30	-2000.00	-2000.000	5.86	-2000.00
	2	121.8	163.0	1.2	32.38	.03	.20	-2000.00	-2000.000	9.68	-2000.00
	3	57.4	154.0	.8	48.10	30.00	.10	-2000.00	-2000.000	28.03	-2000.00
	4	24.2	108.0	.4	42.78	100.00	.80	-2000.00	-2000.000	64.10	-2000.00
	5	17.4	117.0	.2	20.67	100.00	.50	-2000.00	-2000.000	59.75	-2000.00
10750	1	196.4	154.0	1.4	29.46	.03	.30	-2000.00	-2000.000	4.11	-2000.00
	2	63.5	149.6	1.4	32.34	.10	.20	-2000.00	-2000.000	3.67	-2000.00
	3	23.1	108.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	4	13.9	109.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	8.9	105.2	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10775	1	444.5	135.5	1.8	39.12	.10	.20	-2000.00	-2000.000	2.08	-2000.00
	2	120.3	110.0	.6	21.31	100.00	.50	-2000.00	-2000.000	32.69	-2000.00
	3	62.1	113.2	.8	46.06	30.00	.10	-2000.00	-2000.000	31.95	-2000.00
	4	31.4	95.7	1.3	38.56	.03	.20	-2000.00	-2000.000	9.19	-2000.00
	5	29.3	134.0	1.5	54.01	1.00	.10	-2000.00	-2000.000	9.91	-2000.00
10800	1	297.2	88.8	.2	43.12	100.00	.80	-2000.00	-2000.000	61.14	-2000.00
	2	123.1	110.4	1.2	27.26	.03	.30	-2000.00	-2000.000	10.41	-2000.00
	3	63.5	113.7	.2	19.22	100.00	.40	-2000.00	-2000.000	64.55	-2000.00
	4	37.8	113.0	2.0	17.85	.30	.50	-2000.00	-2000.000	11.69	-2000.00
	5	37.5	168.3	.5	25.90	100.00	.20	-2000.00	-2000.000	40.77	-2000.00
10825	1	494.5	176.0	3.1	83.34	.01	.20	-2000.00	-2000.000	3.89	-2000.00
	2	130.4	139.0	3.4	80.31	.03	.20	-2000.00	-2000.000	3.56	-2000.00
	3	77.7	165.0	2.8	119.83	.01	.10	-2000.00	-2000.000	3.93	-2000.00
	4	45.1	161.0	3.1	66.32	30.00	.20	-2000.00	-2000.000	5.38	-2000.00
	5	36.5	195.0	3.0	47.00	30.00	.30	-2000.00	-2000.000	6.31	-2000.00
10850	1	54.6	171.3	2.5	61.37	.01	.30	-2000.00	-2000.000	4.51	-2000.00
	2	23.3	219.1	3.3	85.80	.01	.20	-2000.00	-2000.000	1.81	-2000.00
	3	13.1	246.0	4.4	28.53	.30	.70	-2000.00	-2000.000	27.07	-2000.00
	4	8.0	251.9	2.6	51.70	100.00	.30	-2000.00	-2000.000	53.88	-2000.00
	5	4.9	231.6	4.5	33.65	1.00	.50	-2000.00	-2000.000	2.46	-2000.00
10875	1	1488.0	740.0	1.2	35.37	.01	.20	-2000.00	-2000.000	10.45	-2000.00
	2	339.3	507.0	2.0	49.28	.01	.30	-2000.00	-2000.000	2.74	-2000.00
	3	149.5	440.0	2.4	48.34	.03	.30	-2000.00	-2000.000	2.84	-2000.00
	4	78.1	389.0	2.7	52.13	.03	.30	-2000.00	-2000.000	2.64	-2000.00
	5	55.3	413.0	2.6	22.28	.30	.60	-2000.00	-2000.000	3.66	-2000.00
10900	1	491.3	321.0	1.4	30.08	.03	.30	-2000.00	-2000.000	5.47	-2000.00
	2	184.2	361.0	2.3	44.56	.03	.30	-2000.00	-2000.000	3.75	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	86.8	339.0	3.3	75.64	100.00	.20	-2000.00	-2000.000	9.28	-2000.00
	4	57.0	373.0	1.9	30.19	.10	.60	-2000.00	-2000.000	15.92	-2000.00
	5	41.5	407.0	1.9	41.29	.03	.30	-2000.00	-2000.000	21.87	-2000.00
10925	1	1067.0	360.0	1.5	37.56	.01	.30	-2000.00	-2000.000	4.52	-2000.00
	2	318.8	322.0	2.4	39.43	.10	.30	-2000.00	-2000.000	3.76	-2000.00
	3	182.0	360.0	2.9	76.26	.01	.20	-2000.00	-2000.000	3.15	-2000.00
	4	128.4	430.0	2.8	73.61	.01	.20	-2000.00	-2000.000	4.33	-2000.00
	5	123.0	620.0	4.5	74.63	30.00	.30	-2000.00	-2000.000	8.57	-2000.00
10950	1	614.9	283.0	1.5	38.17	.01	.30	-2000.00	-2000.000	3.12	-2000.00
	2	238.2	329.0	2.4	47.13	.03	.30	-2000.00	-2000.000	2.56	-2000.00
	3	158.0	430.0	2.3	55.83	.01	.30	-2000.00	-2000.000	3.27	-2000.00
	4	128.9	590.0	3.2	53.11	.10	.30	-2000.00	-2000.000	2.65	-2000.00
	5	126.0	870.0	4.5	86.07	.03	.30	-2000.00	-2000.000	3.24	-2000.00
10975	1	642.9	288.0	1.5	37.98	.01	.30	-2000.00	-2000.000	3.11	-2000.00
	2	319.5	429.0	2.0	49.38	.01	.30	-2000.00	-2000.000	2.82	-2000.00
	3	244.8	650.0	2.9	80.15	.01	.20	-2000.00	-2000.000	3.83	-2000.00
	4	186.0	830.0	4.7	108.92	.03	.20	-2000.00	-2000.000	2.39	-2000.00
	5	128.5	860.0	5.1	208.42	.01	.10	-2000.00	-2000.000	2.45	-2000.00
11000	1	786.5	418.0	1.1	35.04	.01	.20	-2000.00	-2000.000	13.26	-2000.00
	2	363.9	581.0	2.8	76.60	.01	.20	-2000.00	-2000.000	4.93	-2000.00
	3	272.4	860.0	3.8	73.52	.03	.30	-2000.00	-2000.000	1.56	-2000.00
	4	158.3	840.0	4.6	108.60	.03	.20	-2000.00	-2000.000	2.41	-2000.00
	5	102.0	810.0	5.9	222.24	.10	.10	-2000.00	-2000.000	1.41	-2000.00
11025	1	594.4	455.0	1.7	41.82	.01	.30	-2000.00	-2000.000	2.91	-2000.00
	2	321.8	739.0	3.5	68.51	.03	.30	-2000.00	-2000.000	2.37	-2000.00
	3	161.9	740.0	4.4	114.19	.01	.20	-2000.00	-2000.000	2.08	-2000.00
	4	97.3	744.0	5.4	115.20	.10	.20	-2000.00	-2000.000	1.99	-2000.00
	5	53.2	611.0	5.8	126.70	.10	.20	-2000.00	-2000.000	4.24	-2000.00
11050	1	687.0	490.0	3.3	63.51	.03	.30	-2000.00	-2000.000	3.36	-2000.00
	2	286.8	614.0	4.2	110.52	.01	.20	-2000.00	-2000.000	2.43	-2000.00
	3	162.1	690.0	5.3	121.79	.03	.20	-2000.00	-2000.000	1.51	-2000.00
	4	72.5	517.0	5.5	142.04	.01	.20	-2000.00	-2000.000	1.97	-2000.00
	5	65.0	696.0	7.0	274.37	.01	.10	-2000.00	-2000.000	2.15	-2000.00
11075	1	610.4	467.0	4.1	66.80	.10	.30	-2000.00	-2000.000	2.83	-2000.00
	2	243.9	560.0	4.8	124.02	.01	.20	-2000.00	-2000.000	1.59	-2000.00
	3	97.8	448.0	5.4	137.23	.01	.20	-2000.00	-2000.000	2.13	-2000.00
	4	83.2	636.0	5.9	115.79	.03	.30	-2000.00	-2000.000	1.82	-2000.00
	5	42.2	484.0	7.0	66.30	.30	.50	-2000.00	-2000.000	7.47	-2000.00
11100	1	697.8	486.0	4.7	75.84	.10	.30	-2000.00	-2000.000	2.68	-2000.00
	2	191.5	400.0	5.2	99.96	.03	.30	-2000.00	-2000.000	1.61	-2000.00
	3	146.0	600.0	5.9	94.93	.10	.30	-2000.00	-2000.000	1.58	-2000.00
	4	68.4	477.0	6.9	130.10	.03	.30	-2000.00	-2000.000	2.23	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
11125	1	398.9	329.0	4.6	119.81	.01	.20	-2000.00	-2000.000	2.51	-2000.00
	2	237.7	589.0	6.8	154.47	.03	.20	-2000.00	-2000.000	2.55	-2000.00
	3	98.8	488.0	7.8	162.04	.10	.20	-2000.00	-2000.000	3.29	-2000.00
11150	1	266.1	439.0	5.3	122.71	.03	.20	-2000.00	-2000.000	2.85	-2000.00
	2	89.2	442.0	7.8	274.34	1.00	.10	-2000.00	-2000.000	2.91	-2000.00
11175	1	116.3	365.0	5.2	133.18	.01	.20	-2000.00	-2000.000	2.46	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 644

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
10825	1	1158.0	400.0	2.4	47.77	.03	.30	-2000.00	-2000.000	4.58	-2000.00
	2	360.7	377.0	3.3	79.52	.03	.20	-2000.00	-2000.000	2.08	-2000.00
	3	198.4	410.0	4.8	76.06	.10	.30	-2000.00	-2000.000	1.82	-2000.00
	4	71.7	249.0	4.4	172.37	1.00	.10	-2000.00	-2000.000	5.14	-2000.00
	5	32.2	168.0	3.9	146.72	1.00	.10	-2000.00	-2000.000	3.29	-2000.00
10850	1	816.4	337.0	2.6	42.79	.10	.30	-2000.00	-2000.000	2.87	-2000.00
	2	324.7	402.0	4.6	121.68	.01	.20	-2000.00	-2000.000	2.50	-2000.00
	3	100.0	240.0	3.8	77.29	.03	.30	-2000.00	-2000.000	4.57	-2000.00
	4	41.0	169.0	4.8	42.45	1.00	.40	-2000.00	-2000.000	5.88	-2000.00
	5	24.7	152.0	2.8	63.21	.10	.20	-2000.00	-2000.000	3.50	-2000.00
10875	1	1338.0	420.0	4.5	118.14	.01	.20	-2000.00	-2000.000	2.15	-2000.00
	2	259.9	244.8	4.2	109.91	.01	.20	-2000.00	-2000.000	1.93	-2000.00
	3	92.7	174.3	3.7	96.47	.01	.20	-2000.00	-2000.000	1.97	-2000.00
	4	38.3	120.3	2.3	47.84	.03	.30	-2000.00	-2000.000	2.90	-2000.00
	5	26.0	122.2	2.0	57.01	.03	.60	-2000.00	-2000.000	31.67	-2000.00
10900	1	645.9	202.8	3.6	94.23	.01	.20	-2000.00	-2000.000	2.43	-2000.00
	2	182.6	172.0	3.8	99.89	.01	.20	-2000.00	-2000.000	2.13	-2000.00
	3	67.7	127.2	2.7	43.32	.10	.30	-2000.00	-2000.000	1.77	-2000.00
	4	31.6	99.2	2.0	17.73	.30	.50	-2000.00	-2000.000	7.55	-2000.00
	5	36.8	173.3	1.0	48.67	30.00	.10	-2000.00	-2000.000	22.27	-2000.00
10925	1	1013.0	302.0	5.2	134.42	.01	.20	-2000.00	-2000.000	1.85	-2000.00
	2	197.6	177.2	3.8	101.08	.01	.20	-2000.00	-2000.000	1.45	-2000.00
	3	80.1	143.4	2.5	39.33	.10	.30	-2000.00	-2000.000	2.06	-2000.00
	4	61.9	185.0	1.9	32.23	.10	.30	-2000.00	-2000.000	3.17	-2000.00
	5	58.5	262.5	.9	26.29	100.00	.20	-2000.00	-2000.000	34.72	-2000.00
10950	1	1004.0	315.0	5.1	133.69	.01	.20	-2000.00	-2000.000	2.66	-2000.00
	2	205.7	193.7	3.7	98.40	.01	.20	-2000.00	-2000.000	1.75	-2000.00
	3	133.1	250.0	2.9	27.55	.30	.50	-2000.00	-2000.000	2.62	-2000.00
	4	95.8	300.9	1.6	31.92	.03	.40	-2000.00	-2000.000	14.30	-2000.00
	5	77.0	362.7	.2	46.98	.10	.10	-2000.00	-2000.000	52.24	-2000.00
10975	1	776.5	304.0	4.9	128.64	.01	.20	-2000.00	-2000.000	2.30	-2000.00
	2	248.4	292.0	3.7	98.30	.01	.20	-2000.00	-2000.000	2.57	-2000.00
	3	155.0	360.0	2.4	47.90	.03	.30	-2000.00	-2000.000	2.42	-2000.00
	4	108.8	420.0	1.9	36.25	.03	.30	-2000.00	-2000.000	4.17	-2000.00
	5	66.0	388.0	2.5	41.48	.10	.30	-2000.00	-2000.000	4.11	-2000.00
11000	1	955.3	389.0	5.1	82.70	.10	.30	-2000.00	-2000.000	3.14	-2000.00
	2	315.5	385.0	2.5	49.21	.03	.30	-2000.00	-2000.000	1.97	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	213.9	520.0	1.4	37.84	.01	.30	-2000.00	-2000.000	9.03	-2000.00
	4	93.3	380.0	2.2	43.46	.03	.40	-2000.00	-2000.000	3.59	-2000.00
	5	72.5	443.0	3.6	50.54	.10	.40	-2000.00	-2000.000	1.60	-2000.00
11025	1	703.3	210.3	2.2	36.81	.10	.30	-2000.00	-2000.000	3.47	-2000.00
	2	483.1	433.4	1.6	40.75	.01	.30	-2000.00	-2000.000	3.95	-2000.00
	3	219.4	392.0	2.8	45.36	.10	.30	-2000.00	-2000.000	.90	-2000.00
	4	126.4	377.0	4.8	194.53	.01	.10	-2000.00	-2000.000	1.57	-2000.00
	5	138.4	620.0	5.2	120.56	.03	.20	-2000.00	-2000.000	1.14	-2000.00
11050	1	574.9	429.0	1.7	34.67	.03	.30	-2000.00	-2000.000	5.25	-2000.00
	2	165.2	370.0	2.8	46.20	.10	.30	-2000.00	-2000.000	1.75	-2000.00
	3	100.6	450.0	4.5	95.98	.10	.20	-2000.00	-2000.000	1.07	-2000.00
	4	74.7	558.0	5.5	115.75	.10	.20	-2000.00	-2000.000	1.48	-2000.00
	5	54.6	612.0	6.2	249.03	.01	.10	-2000.00	-2000.000	2.16	-2000.00
11075	1	640.1	275.0	2.1	51.06	.01	.30	-2000.00	-2000.000	3.91	-2000.00
	2	323.8	417.0	4.5	96.67	.10	.20	-2000.00	-2000.000	1.34	-2000.00
	3	240.2	610.0	5.4	114.99	.10	.20	-2000.00	-2000.000	1.19	-2000.00
	4	128.4	550.0	6.4	257.53	.01	.10	-2000.00	-2000.000	1.55	-2000.00
	5	104.3	670.0	7.1	279.88	.01	.10	-2000.00	-2000.000	1.19	-2000.00
11100	1	370.3	322.0	3.7	97.67	.01	.20	-2000.00	-2000.000	2.12	-2000.00
	2	235.7	616.0	5.5	126.82	.03	.20	-2000.00	-2000.000	1.51	-2000.00
	3	126.3	650.0	6.8	142.44	.10	.20	-2000.00	-2000.000	1.45	-2000.00
	4	67.3	587.0	7.6	157.64	.10	.20	-2000.00	-2000.000	2.50	-2000.00
11125	1	134.5	422.0	4.2	174.15	.01	.10	-2000.00	-2000.000	2.78	-2000.00
	2	58.1	547.5	6.6	241.12	30.00	.10	-2000.00	-2000.000	2.97	-2000.00
	3	30.8	579.0	8.1	161.75	30.00	.20	-2000.00	-2000.000	5.03	-2000.00
11150	1	203.6	376.0	3.2	44.92	.10	.40	-2000.00	-2000.000	2.50	-2000.00
	2	91.0	504.1	5.5	128.32	.03	.20	-2000.00	-2000.000	4.52	-2000.00
11175	1	165.0	370.0	2.7	56.82	.03	.30	-2000.00	-2000.000	4.71	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 594

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	353.2	120.0	1.7	39.40	.03	.20	-2000.00	-2000.000	2.70	-2000.00
	2	98.6	100.9	2.2	87.68	1.00	.10	-2000.00	-2000.000	2.74	-2000.00
	3	55.4	113.0	2.7	55.10	10.00	.20	-2000.00	-2000.000	4.86	-2000.00
	4	33.3	113.0	4.9	60.31	30.00	.40	-2000.00	-2000.000	4.41	-2000.00
	5	23.6	120.0	5.0	88.36	100.00	.40	-2000.00	-2000.000	6.53	-2000.00
10850	1	248.2	173.0	1.1	31.91	.03	.20	-2000.00	-2000.000	13.39	-2000.00
	2	81.8	171.2	2.4	43.73	100.00	.30	-2000.00	-2000.000	8.20	-2000.00
	3	38.0	158.0	2.9	63.03	100.00	.20	-2000.00	-2000.000	5.93	-2000.00
	4	22.9	159.0	3.7	68.18	100.00	.30	-2000.00	-2000.000	3.82	-2000.00
	5	15.6	163.0	5.1	99.63	100.00	.50	-2000.00	-2000.000	12.98	-2000.00
10875	1	612.8	260.0	1.2	32.21	.03	.20	-2000.00	-2000.000	8.67	-2000.00
	2	194.3	247.0	2.1	49.63	.03	.20	-2000.00	-2000.000	2.32	-2000.00
	3	96.3	244.0	2.8	108.00	10.00	.10	-2000.00	-2000.000	2.73	-2000.00
	4	55.5	235.0	3.6	80.06	100.00	.20	-2000.00	-2000.000	4.25	-2000.00
	5	34.7	220.0	4.3	57.09	30.00	.40	-2000.00	-2000.000	7.87	-2000.00
10900	1	628.9	282.0	1.3	37.94	.01	.20	-2000.00	-2000.000	10.00	-2000.00
	2	210.6	283.0	2.1	51.39	.03	.20	-2000.00	-2000.000	3.68	-2000.00
	3	104.7	280.0	2.9	120.05	.01	.10	-2000.00	-2000.000	1.83	-2000.00
	4	51.3	229.0	3.2	123.59	.10	.10	-2000.00	-2000.000	1.73	-2000.00
	5	36.6	246.0	3.7	70.80	100.00	.30	-2000.00	-2000.000	8.75	-2000.00
10925	1	476.6	277.0	1.3	36.72	.01	.20	-2000.00	-2000.000	9.20	-2000.00
	2	179.1	312.0	2.2	42.85	.03	.30	-2000.00	-2000.000	1.67	-2000.00
	3	80.3	279.0	2.6	48.88	.03	.30	-2000.00	-2000.000	2.75	-2000.00
	4	40.8	237.0	3.1	114.16	3.00	.10	-2000.00	-2000.000	2.98	-2000.00
	5	33.8	294.0	1.7	15.37	.30	.70	-2000.00	-2000.000	22.75	-2000.00
10950	1	576.5	377.0	1.4	29.76	.03	.30	-2000.00	-2000.000	5.08	-2000.00
	2	158.5	311.0	2.1	50.80	.01	.30	-2000.00	-2000.000	2.15	-2000.00
	3	85.1	333.0	2.4	22.20	.30	.50	-2000.00	-2000.000	3.41	-2000.00
	4	53.6	350.0	2.0	17.38	.30	.60	-2000.00	-2000.000	7.52	-2000.00
	5	29.2	286.0	1.5	32.55	.03	.40	-2000.00	-2000.000	28.00	-2000.00
10975	1	642.0	276.0	1.5	31.69	.03	.30	-2000.00	-2000.000	4.20	-2000.00
	2	229.6	296.0	2.1	41.55	.03	.30	-2000.00	-2000.000	3.07	-2000.00
	3	116.5	300.0	1.9	16.30	.30	.60	-2000.00	-2000.000	5.05	-2000.00
	4	65.4	281.0	1.6	32.54	.03	.40	-2000.00	-2000.000	3.11	-2000.00
	5	59.7	385.0	1.3	30.47	.03	.40	-2000.00	-2000.000	13.46	-2000.00
11000	1	874.9	361.0	1.3	27.66	.03	.30	-2000.00	-2000.000	6.65	-2000.00
	2	265.4	328.0	1.9	36.81	.03	.30	-2000.00	-2000.000	1.92	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	144.8	350.0	1.8	35.67	.03	.30	-2000.00	-2000.000	3.00	-2000.00
	4	86.7	358.0	1.9	43.64	.01	.30	-2000.00	-2000.000	3.17	-2000.00
	5	66.1	409.0	1.7	43.04	.01	.30	-2000.00	-2000.000	4.50	-2000.00
11025	1	819.6	279.0	1.3	37.96	.01	.20	-2000.00	-2000.000	7.17	-2000.00
	2	306.7	314.0	1.7	33.92	.03	.30	-2000.00	-2000.000	2.85	-2000.00
	3	216.4	440.0	1.9	37.83	.03	.30	-2000.00	-2000.000	2.40	-2000.00
	4	128.0	430.0	1.7	33.78	.03	.40	-2000.00	-2000.000	3.09	-2000.00
	5	113.3	580.0	2.5	48.53	.03	.30	-2000.00	-2000.000	2.27	-2000.00
11050	1	624.5	284.0	1.1	36.20	.01	.20	-2000.00	-2000.000	17.83	-2000.00
	2	322.1	439.0	1.8	35.09	.03	.30	-2000.00	-2000.000	2.60	-2000.00
	3	166.9	450.0	1.9	37.27	.03	.30	-2000.00	-2000.000	2.44	-2000.00
	4	133.1	600.0	2.6	41.47	.10	.30	-2000.00	-2000.000	2.12	-2000.00
	5	105.0	710.0	3.6	57.01	.10	.30	-2000.00	-2000.000	1.80	-2000.00
11075	1	702.2	306.0	1.4	38.45	.01	.20	-2000.00	-2000.000	7.22	-2000.00
	2	324.2	424.0	1.7	42.50	.01	.30	-2000.00	-2000.000	2.40	-2000.00
	3	221.1	570.0	2.3	45.96	.03	.30	-2000.00	-2000.000	2.23	-2000.00
	4	158.0	680.0	3.4	89.67	.01	.20	-2000.00	-2000.000	1.70	-2000.00
	5	111.7	730.0	3.6	94.26	.01	.20	-2000.00	-2000.000	1.65	-2000.00
11100	1	557.1	349.0	1.5	30.80	.03	.30	-2000.00	-2000.000	4.31	-2000.00
	2	280.3	528.0	2.1	51.36	.01	.30	-2000.00	-2000.000	2.24	-2000.00
	3	173.8	650.0	3.1	59.91	.03	.30	-2000.00	-2000.000	2.02	-2000.00
	4	112.5	700.0	3.3	63.62	.03	.30	-2000.00	-2000.000	2.83	-2000.00
11125	1	91.4	358.0	2.0	46.35	.10	.20	-2000.00	-2000.000	5.19	-2000.00
	2	44.7	526.0	3.5	141.59	100.00	.10	-2000.00	-2000.000	6.78	-2000.00
	3	26.1	610.0	4.1	67.07	30.00	.30	-2000.00	-2000.000	8.78	-2000.00
11150	1	124.7	391.0	3.3	132.79	30.00	.10	-2000.00	-2000.000	5.90	-2000.00
	2	57.3	540.2	5.2	90.90	100.00	.30	-2000.00	-2000.000	7.33	-2000.00
11175	1	284.3	446.0	2.6	51.09	.03	.30	-2000.00	-2000.000	2.68	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 584

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	622.8	195.5	1.7	33.15	.03	.30	-2000.00	-2000.000	3.10	-2000.00
	2	223.1	210.1	2.0	39.75	.03	.30	-2000.00	-2000.000	2.07	-2000.00
	3	114.2	214.0	2.2	35.95	.10	.30	-2000.00	-2000.000	2.51	-2000.00
	4	53.0	166.5	2.8	44.83	.10	.30	-2000.00	-2000.000	2.12	-2000.00
	5	35.4	166.6	2.9	26.63	.30	.50	-2000.00	-2000.000	4.27	-2000.00
10850	1	750.4	248.0	1.7	32.30	.03	.30	-2000.00	-2000.000	3.26	-2000.00
	2	245.3	243.0	2.2	62.06	.01	.20	-2000.00	-2000.000	3.24	-2000.00
	3	95.9	189.0	3.0	41.97	.30	.30	-2000.00	-2000.000	1.35	-2000.00
	4	47.5	157.0	3.8	48.99	1.00	.30	-2000.00	-2000.000	1.69	-2000.00
	5	38.3	189.0	4.0	19.22	1.00	.70	-2000.00	-2000.000	6.02	-2000.00
10875	1	490.3	296.0	1.3	33.48	.03	.20	-2000.00	-2000.000	6.72	-2000.00
	2	133.4	241.0	2.2	42.61	.03	.30	-2000.00	-2000.000	1.99	-2000.00
	3	58.7	212.0	2.8	32.09	.30	.40	-2000.00	-2000.000	1.60	-2000.00
	4	31.9	192.0	2.5	22.77	.30	.50	-2000.00	-2000.000	3.97	-2000.00
	5	22.9	207.0	1.3	30.73	.03	.40	-2000.00	-2000.000	19.53	-2000.00
10900	1	519.8	240.0	1.6	31.89	.03	.30	-2000.00	-2000.000	2.45	-2000.00
	2	176.3	244.0	3.3	127.21	30.00	.10	-2000.00	-2000.000	2.71	-2000.00
	3	79.3	219.0	3.7	141.95	100.00	.10	-2000.00	-2000.000	1.39	-2000.00
	4	49.5	228.0	3.2	126.40	100.00	.10	-2000.00	-2000.000	2.95	-2000.00
	5	37.3	258.0	3.7	55.43	30.00	.30	-2000.00	-2000.000	7.02	-2000.00
10925	1	812.5	349.0	1.7	23.77	.10	.40	-2000.00	-2000.000	4.08	-2000.00
	2	228.0	294.0	2.9	63.54	.10	.20	-2000.00	-2000.000	1.36	-2000.00
	3	119.4	300.0	3.4	133.10	100.00	.10	-2000.00	-2000.000	1.24	-2000.00
	4	66.4	285.0	3.5	71.68	30.00	.20	-2000.00	-2000.000	2.28	-2000.00
	5	54.8	353.0	3.4	74.55	30.00	.20	-2000.00	-2000.000	9.34	-2000.00
10950	1	888.8	367.0	1.7	28.15	.10	.30	-2000.00	-2000.000	4.06	-2000.00
	2	260.7	323.0	2.8	117.00	.01	.10	-2000.00	-2000.000	1.67	-2000.00
	3	132.2	320.0	3.1	119.35	30.00	.10	-2000.00	-2000.000	1.16	-2000.00
	4	93.4	386.0	3.5	78.03	100.00	.20	-2000.00	-2000.000	3.19	-2000.00
	5	71.2	441.0	3.9	85.67	100.00	.20	-2000.00	-2000.000	4.35	-2000.00
10975	1	766.5	286.0	1.9	29.43	.10	.30	-2000.00	-2000.000	3.66	-2000.00
	2	267.0	299.0	2.3	25.47	.30	.40	-2000.00	-2000.000	1.85	-2000.00
	3	163.2	360.0	2.4	26.34	.30	.40	-2000.00	-2000.000	1.91	-2000.00
	4	118.1	440.0	2.6	28.33	.30	.40	-2000.00	-2000.000	2.92	-2000.00
	5	86.0	482.0	3.8	96.43	.01	.20	-2000.00	-2000.000	1.35	-2000.00
11000	1	620.7	249.0	1.5	30.80	.03	.30	-2000.00	-2000.000	2.64	-2000.00
	2	308.5	372.0	1.8	25.27	.10	.40	-2000.00	-2000.000	2.08	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	168.2	400.0	2.2	30.47	.10	.40	-2000.00	-2000.000	2.08	-2000.00
	4	109.2	430.0	3.0	28.46	.30	.50	-2000.00	-2000.000	2.68	-2000.00
	5	126.1	760.0	3.5	32.59	.30	.50	-2000.00	-2000.000	3.42	-2000.00
11025	1	431.5	233.0	1.5	30.46	.03	.30	-2000.00	-2000.000	4.80	-2000.00
	2	211.0	342.0	1.8	25.66	.10	.40	-2000.00	-2000.000	4.53	-2000.00
	3	135.3	430.0	2.7	37.28	.10	.40	-2000.00	-2000.000	2.83	-2000.00
	4	126.4	680.0	2.9	25.61	.30	.60	-2000.00	-2000.000	3.29	-2000.00
	5	77.1	626.0	3.1	26.85	.30	.60	-2000.00	-2000.000	5.60	-2000.00
11050	1	623.6	343.0	1.3	27.80	.03	.30	-2000.00	-2000.000	7.31	-2000.00
	2	231.3	382.0	2.7	53.02	.03	.30	-2000.00	-2000.000	2.77	-2000.00
	3	225.7	740.0	3.4	54.56	.10	.30	-2000.00	-2000.000	1.91	-2000.00
	4	117.9	640.0	3.8	61.57	.10	.30	-2000.00	-2000.000	2.29	-2000.00
	5	82.5	681.0	4.5	73.25	.10	.30	-2000.00	-2000.000	1.83	-2000.00
11075	1	379.7	259.0	2.6	68.87	.01	.20	-2000.00	-2000.000	2.30	-2000.00
	2	303.4	621.0	3.5	83.93	.03	.20	-2000.00	-2000.000	1.76	-2000.00
	3	147.4	600.0	4.2	89.72	.10	.20	-2000.00	-2000.000	1.55	-2000.00
	4	97.6	666.0	5.3	112.24	.10	.20	-2000.00	-2000.000	1.38	-2000.00
	5	57.8	591.0	6.0	217.77	.30	.10	-2000.00	-2000.000	1.42	-2000.00
11100	1	502.9	607.0	3.2	83.32	.01	.20	-2000.00	-2000.000	1.87	-2000.00
	2	175.3	635.0	3.9	101.06	.01	.20	-2000.00	-2000.000	2.10	-2000.00
	3	106.0	760.0	4.9	104.15	.10	.20	-2000.00	-2000.000	2.24	-2000.00
	4	53.9	651.0	5.8	229.88	.01	.10	-2000.00	-2000.000	2.25	-2000.00
11125	1	206.4	498.0	3.3	71.95	.10	.20	-2000.00	-2000.000	2.58	-2000.00
	2	93.6	678.2	4.4	186.55	.01	.10	-2000.00	-2000.000	3.16	-2000.00
	3	50.5	731.0	5.9	208.99	100.00	.10	-2000.00	-2000.000	3.66	-2000.00
11150	1	308.2	744.0	3.6	95.88	.01	.20	-2000.00	-2000.000	1.81	-2000.00
	2	111.0	804.0	4.3	69.02	.10	.30	-2000.00	-2000.000	2.25	-2000.00
11175	1	175.4	680.0	3.6	70.86	.03	.30	-2000.00	-2000.000	1.72	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 574

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	612.9	356.0	1.7	33.39	.03	.30	-2000.00	-2000.000	3.45	-2000.00
	2	130.7	227.0	2.6	55.95	.10	.20	-2000.00	-2000.000	1.89	-2000.00
	3	50.5	175.0	3.7	74.00	10.00	.20	-2000.00	-2000.000	2.30	-2000.00
	4	28.2	163.0	4.9	70.62	30.00	.30	-2000.00	-2000.000	2.67	-2000.00
	5	23.0	200.0	4.0	70.61	100.00	.40	-2000.00	-2000.000	3.64	-2000.00
10850	1	448.3	213.0	1.6	31.69	.03	.30	-2000.00	-2000.000	3.30	-2000.00
	2	113.8	162.0	3.1	66.76	.10	.20	-2000.00	-2000.000	1.35	-2000.00
	3	63.0	179.0	4.0	76.77	3.00	.20	-2000.00	-2000.000	.95	-2000.00
	4	37.1	176.0	3.6	47.68	10.00	.30	-2000.00	-2000.000	2.59	-2000.00
	5	32.0	228.0	3.4	24.94	3.00	.50	-2000.00	-2000.000	2.10	-2000.00
10875	1	381.3	202.0	1.8	43.72	.01	.30	-2000.00	-2000.000	2.50	-2000.00
	2	126.4	201.0	3.0	27.65	.30	.50	-2000.00	-2000.000	2.16	-2000.00
	3	69.7	221.0	2.3	19.11	.30	.60	-2000.00	-2000.000	3.00	-2000.00
	4	50.5	268.0	1.3	30.20	.03	.40	-2000.00	-2000.000	25.16	-2000.00
	5	36.1	288.0	.5	32.44	.01	.20	-2000.00	-2000.000	53.06	-2000.00
10900	1	468.4	216.0	2.0	56.91	.01	.20	-2000.00	-2000.000	4.24	-2000.00
	2	162.3	224.0	2.5	27.82	.30	.40	-2000.00	-2000.000	2.72	-2000.00
	3	98.3	271.0	1.8	25.21	.10	.40	-2000.00	-2000.000	4.37	-2000.00
	4	64.0	295.0	1.1	27.37	.03	.30	-2000.00	-2000.000	20.70	-2000.00
	5	54.9	380.0	1.9	26.53	.10	.50	-2000.00	-2000.000	3.96	-2000.00
10925	1	435.7	220.0	1.9	49.01	.01	.20	-2000.00	-2000.000	2.17	-2000.00
	2	198.8	302.0	2.2	30.82	.30	.30	-2000.00	-2000.000	1.81	-2000.00
	3	116.5	350.0	2.3	45.20	3.00	.20	-2000.00	-2000.000	2.65	-2000.00
	4	84.9	430.0	3.8	77.61	30.00	.20	-2000.00	-2000.000	2.04	-2000.00
	5	63.6	483.0	5.4	107.23	30.00	.20	-2000.00	-2000.000	2.24	-2000.00
10950	1	635.4	273.0	1.1	31.22	.03	.20	-2000.00	-2000.000	11.03	-2000.00
	2	253.6	327.0	1.4	39.41	.01	.20	-2000.00	-2000.000	8.60	-2000.00
	3	171.9	440.0	2.6	24.12	.30	.50	-2000.00	-2000.000	3.26	-2000.00
	4	110.4	470.0	4.1	94.49	.03	.20	-2000.00	-2000.000	1.91	-2000.00
	5	100.2	640.0	5.2	55.81	.30	.40	-2000.00	-2000.000	2.00	-2000.00
10975	1	513.8	268.0	.9	48.03	30.00	.10	-2000.00	-2000.000	18.78	-2000.00
	2	259.2	406.0	2.3	60.55	.01	.20	-2000.00	-2000.000	1.90	-2000.00
	3	147.0	460.0	3.7	87.44	.03	.20	-2000.00	-2000.000	1.63	-2000.00
	4	122.2	630.0	5.4	217.00	.01	.10	-2000.00	-2000.000	3.08	-2000.00
	5	84.4	662.0	6.2	132.29	.10	.20	-2000.00	-2000.000	3.93	-2000.00
11000	1	671.0	324.0	1.9	30.15	.10	.30	-2000.00	-2000.000	2.76	-2000.00
	2	305.6	442.0	3.3	86.49	.01	.20	-2000.00	-2000.000	1.86	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	242.5	700.0	5.3	121.64	.03	.20	-2000.00	-2000.000	.93	-2000.00
	4	122.0	580.0	6.1	127.91	.10	.20	-2000.00	-2000.000	1.35	-2000.00
	5	80.0	579.0	9.8	338.83	.30	.10	-2000.00	-2000.000	.98	-2000.00
11025	1	828.0	388.0	2.7	72.37	.01	.20	-2000.00	-2000.000	2.53	-2000.00
	2	455.3	640.0	5.6	130.91	.03	.20	-2000.00	-2000.000	1.85	-2000.00
	3	206.8	580.0	6.5	260.71	.01	.10	-2000.00	-2000.000	1.42	-2000.00
	4	103.9	480.0	10.7	355.94	100.00	.10	-2000.00	-2000.000	1.49	-2000.00
	5	61.0	428.0	7.6	144.36	10.00	.20	-2000.00	-2000.000	2.74	-2000.00
11050	1	1043.0	530.0	5.7	147.13	.01	.20	-2000.00	-2000.000	1.45	-2000.00
	2	339.0	523.0	6.7	154.51	.03	.20	-2000.00	-2000.000	.78	-2000.00
	3	174.1	530.0	10.0	363.69	.03	.10	-2000.00	-2000.000	.84	-2000.00
	4	74.5	383.0	6.4	147.53	.03	.20	-2000.00	-2000.000	1.33	-2000.00
	5	70.6	545.0	8.4	192.16	.03	.20	-2000.00	-2000.000	1.04	-2000.00
11075	1	711.9	456.0	7.0	161.95	.03	.20	-2000.00	-2000.000	1.38	-2000.00
	2	267.3	513.0	11.2	390.53	.10	.10	-2000.00	-2000.000	.70	-2000.00
	3	98.9	379.0	7.3	101.17	.30	.30	-2000.00	-2000.000	1.06	-2000.00
	4	86.1	551.0	9.2	208.18	.03	.20	-2000.00	-2000.000	.85	-2000.00
	5	56.3	541.0	10.5	142.00	.30	.30	-2000.00	-2000.000	1.04	-2000.00
11100	1	344.9	492.0	12.6	404.82	3.00	.10	-2000.00	-2000.000	1.27	-2000.00
	2	100.4	429.0	8.9	309.71	1.00	.10	-2000.00	-2000.000	1.00	-2000.00
	3	75.3	643.0	10.5	352.16	3.00	.10	-2000.00	-2000.000	1.19	-2000.00
	4	46.0	655.0	11.9	387.95	30.00	.10	-2000.00	-2000.000	1.29	-2000.00
11125	1	299.3	494.0	8.7	195.25	.03	.20	-2000.00	-2000.000	1.00	-2000.00
	2	153.9	763.0	9.4	234.36	.01	.20	-2000.00	-2000.000	1.09	-2000.00
	3	80.4	795.0	9.7	151.16	.10	.30	-2000.00	-2000.000	1.18	-2000.00
11150	1	272.3	1060.0	9.1	187.24	.10	.20	-2000.00	-2000.000	1.39	-2000.00
	2	91.3	1074.0	10.9	365.30	1.00	.10	-2000.00	-2000.000	1.56	-2000.00
11175	1	165.8	1300.0	9.8	220.61	.03	.20	-2000.00	-2000.000	1.02	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 564

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	322.9	253.0	2.0	33.24	.10	.30	-2000.00	-2000.000	2.37	-2000.00
	2	92.3	217.3	3.9	151.60	.10	.10	-2000.00	-2000.000	3.20	-2000.00
	3	48.7	228.0	3.3	63.40	3.00	.20	-2000.00	-2000.000	1.42	-2000.00
	4	55.4	434.0	3.4	73.36	30.00	.20	-2000.00	-2000.000	4.23	-2000.00
	5	29.8	350.0	2.9	45.90	30.00	.30	-2000.00	-2000.000	6.04	-2000.00
10850	1	305.8	160.0	2.4	46.82	.03	.30	-2000.00	-2000.000	2.22	-2000.00
	2	134.4	211.0	2.6	28.62	.30	.40	-2000.00	-2000.000	2.91	-2000.00
	3	149.1	460.0	2.5	20.37	.30	.60	-2000.00	-2000.000	5.28	-2000.00
	4	54.3	284.0	.4	31.99	.01	.30	-2000.00	-2000.000	57.69	-2000.00
	5	42.0	329.0	.0	45.40	.10	.10	-2000.00	-2000.000	103.41	-2000.00
10875	1	311.0	195.0	1.8	47.76	.01	.20	-2000.00	-2000.000	1.56	-2000.00
	2	259.3	488.0	2.7	70.06	.01	.20	-2000.00	-2000.000	.98	-2000.00
	3	76.9	289.0	1.9	21.04	.30	.40	-2000.00	-2000.000	1.82	-2000.00
	4	53.3	334.0	1.4	39.04	.01	.20	-2000.00	-2000.000	5.79	-2000.00
	5	33.0	310.0	3.2	70.91	.10	.20	-2000.00	-2000.000	1.98	-2000.00
10900	1	742.9	448.0	2.2	42.94	.03	.30	-2000.00	-2000.000	2.36	-2000.00
	2	151.1	273.0	1.7	26.75	.10	.30	-2000.00	-2000.000	3.54	-2000.00
	3	98.4	355.0	.6	43.89	30.00	.10	-2000.00	-2000.000	31.00	-2000.00
	4	52.7	318.0	3.1	22.48	.30	.60	-2000.00	-2000.000	16.60	-2000.00
	5	40.1	363.0	2.8	25.91	.30	.50	-2000.00	-2000.000	2.59	-2000.00
10925	1	830.1	220.8	1.5	40.15	.01	.20	-2000.00	-2000.000	3.27	-2000.00
	2	426.9	340.7	.9	47.77	30.00	.10	-2000.00	-2000.000	18.12	-2000.00
	3	206.2	328.0	3.1	66.06	.10	.20	-2000.00	-2000.000	1.32	-2000.00
	4	138.1	367.0	3.5	145.28	.01	.10	-2000.00	-2000.000	1.14	-2000.00
	5	94.2	375.8	4.3	176.12	.01	.10	-2000.00	-2000.000	2.32	-2000.00
10950	1	2536.0	773.0	1.3	37.01	.01	.20	-2000.00	-2000.000	7.95	-2000.00
	2	756.1	691.5	3.6	78.13	.10	.20	-2000.00	-2000.000	1.43	-2000.00
	3	366.8	669.0	4.7	175.80	30.00	.10	-2000.00	-2000.000	2.06	-2000.00
	4	201.9	615.0	5.4	201.64	1.00	.10	-2000.00	-2000.000	1.98	-2000.00
	5	123.2	563.0	7.7	273.46	30.00	.10	-2000.00	-2000.000	2.37	-2000.00
10975	1	1078.0	560.0	2.9	77.24	.01	.20	-2000.00	-2000.000	2.35	-2000.00
	2	403.5	633.0	4.9	187.62	.10	.10	-2000.00	-2000.000	1.36	-2000.00
	3	204.2	630.0	5.6	212.53	.03	.10	-2000.00	-2000.000	2.19	-2000.00
	4	106.8	550.0	7.1	157.17	.10	.20	-2000.00	-2000.000	2.68	-2000.00
	5	72.8	571.0	8.4	315.26	.03	.10	-2000.00	-2000.000	1.55	-2000.00
11000	1	887.4	506.0	5.1	196.97	.10	.10	-2000.00	-2000.000	1.72	-2000.00
	2	315.8	540.0	5.8	121.19	.10	.20	-2000.00	-2000.000	1.65	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	185.1	630.0	7.7	295.29	.03	.10	-2000.00	-2000.000	1.27	-2000.00
	4	102.0	580.0	8.7	336.73	.01	.10	-2000.00	-2000.000	1.27	-2000.00
	5	78.3	670.0	10.9	363.03	.30	.10	-2000.00	-2000.000	2.02	-2000.00
11025	1	987.1	387.0	3.9	93.13	.03	.20	-2000.00	-2000.000	2.08	-2000.00
	2	482.8	568.0	6.7	154.61	.03	.20	-2000.00	-2000.000	1.13	-2000.00
	3	230.7	540.0	7.7	176.46	.03	.20	-2000.00	-2000.000	.90	-2000.00
	4	167.1	650.0	9.3	209.74	.03	.20	-2000.00	-2000.000	.73	-2000.00
	5	132.0	770.0	11.7	258.00	.03	.20	-2000.00	-2000.000	1.16	-2000.00
11050	1	556.8	406.0	5.7	147.64	.01	.20	-2000.00	-2000.000	1.27	-2000.00
	2	225.1	493.0	6.8	106.23	.10	.30	-2000.00	-2000.000	1.10	-2000.00
	3	142.7	620.0	8.2	88.25	.30	.40	-2000.00	-2000.000	1.48	-2000.00
	4	106.4	770.0	10.8	165.27	.10	.30	-2000.00	-2000.000	1.13	-2000.00
	5	78.6	861.0	12.1	129.22	.30	.40	-2000.00	-2000.000	1.83	-2000.00
11075	1	139.1	436.0	6.2	99.37	.10	.30	-2000.00	-2000.000	2.52	-2000.00
	2	63.9	601.8	7.1	137.35	.03	.30	-2000.00	-2000.000	1.27	-2000.00
	3	42.8	805.0	9.2	176.49	.03	.30	-2000.00	-2000.000	.82	-2000.00
	4	27.2	853.0	10.2	141.92	.10	.40	-2000.00	-2000.000	1.18	-2000.00
	5	17.6	827.0	11.0	153.80	.10	.40	-2000.00	-2000.000	2.66	-2000.00
11100	1	216.1	521.0	5.7	231.10	.01	.10	-2000.00	-2000.000	1.69	-2000.00
	2	110.7	802.0	10.5	350.30	10.00	.10	-2000.00	-2000.000	1.81	-2000.00
	3	76.7	1109.0	13.8	246.99	10.00	.20	-2000.00	-2000.000	2.51	-2000.00
	4	34.5	832.0	18.1	304.00	10.00	.20	-2000.00	-2000.000	1.61	-2000.00
11125	1	187.7	535.0	5.7	134.13	.03	.20	-2000.00	-2000.000	1.20	-2000.00
	2	101.1	865.0	9.6	218.60	.03	.20	-2000.00	-2000.000	3.32	-2000.00
	3	55.9	955.0	13.6	272.04	.10	.20	-2000.00	-2000.000	1.09	-2000.00
11150	1	166.5	650.0	7.4	158.49	.10	.20	-2000.00	-2000.000	4.02	-2000.00
	2	77.6	913.0	14.5	451.39	3.00	.10	-2000.00	-2000.000	1.42	-2000.00
11175	1	198.8	690.0	10.3	230.82	.03	.20	-2000.00	-2000.000	1.22	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 554

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	395.2	112.8	2.0	39.06	.03	.30	-2000.00	-2000.000	3.16	-2000.00
	2	221.0	189.2	2.7	71.40	.01	.20	-2000.00	-2000.000	1.46	-2000.00
	3	124.6	212.0	2.1	23.52	.30	.40	-2000.00	-2000.000	1.94	-2000.00
	4	88.7	253.1	1.8	33.78	.03	.30	-2000.00	-2000.000	2.58	-2000.00
	5	67.0	286.7	1.3	33.15	.03	.20	-2000.00	-2000.000	7.26	-2000.00
10850	1	620.4	374.0	1.5	30.90	.03	.30	-2000.00	-2000.000	3.42	-2000.00
	2	142.9	258.0	2.2	36.05	.10	.30	-2000.00	-2000.000	1.58	-2000.00
	3	90.6	327.0	1.9	31.64	.10	.30	-2000.00	-2000.000	2.79	-2000.00
	4	52.0	314.0	1.5	26.09	.10	.30	-2000.00	-2000.000	4.02	-2000.00
	5	51.4	465.0	1.0	30.70	.03	.20	-2000.00	-2000.000	9.86	-2000.00
10875	1	592.1	199.0	1.4	38.66	.01	.20	-2000.00	-2000.000	6.10	-2000.00
	2	272.2	275.0	1.8	48.41	.01	.20	-2000.00	-2000.000	2.45	-2000.00
	3	163.3	330.0	1.5	40.36	.01	.20	-2000.00	-2000.000	3.44	-2000.00
	4	124.1	410.0	1.4	32.22	.10	.20	-2000.00	-2000.000	5.82	-2000.00
	5	104.6	520.0	1.2	55.99	.10	.10	-2000.00	-2000.000	10.35	-2000.00
10900	1	849.4	381.0	1.0	50.30	.10	.10	-2000.00	-2000.000	14.37	-2000.00
	2	297.0	399.0	1.0	49.05	30.00	.10	-2000.00	-2000.000	15.81	-2000.00
	3	219.3	580.0	.8	20.61	100.00	.30	-2000.00	-2000.000	29.61	-2000.00
	4	158.0	700.0	.7	19.70	100.00	.40	-2000.00	-2000.000	28.36	-2000.00
	5	94.9	638.0	3.5	138.02	100.00	.10	-2000.00	-2000.000	2.99	-2000.00
10925	1	681.4	260.0	.4	20.82	100.00	.50	-2000.00	-2000.000	46.79	-2000.00
	2	416.9	478.0	.4	21.35	100.00	.50	-2000.00	-2000.000	52.83	-2000.00
	3	288.9	660.0	.1	32.08	100.00	.70	-2000.00	-2000.000	67.54	-2000.00
	4	155.2	590.0	3.1	78.95	.01	.20	-2000.00	-2000.000	2.19	-2000.00
	5	111.2	630.0	4.5	104.52	.03	.20	-2000.00	-2000.000	1.08	-2000.00
10950	1	788.9	353.0	.3	33.15	100.00	.70	-2000.00	-2000.000	58.15	-2000.00
	2	426.4	573.0	.1	43.27	100.00	.80	-2000.00	-2000.000	69.24	-2000.00
	3	233.0	620.0	2.7	58.73	.10	.20	-2000.00	-2000.000	1.42	-2000.00
	4	145.4	650.0	4.8	182.15	.30	.10	-2000.00	-2000.000	1.48	-2000.00
	5	125.3	840.0	3.4	143.73	.01	.10	-2000.00	-2000.000	2.03	-2000.00
10975	1	645.0	382.0	.0	41.66	100.00	.80	-2000.00	-2000.000	84.66	-2000.00
	2	300.3	533.0	2.4	64.15	.01	.20	-2000.00	-2000.000	1.80	-2000.00
	3	173.6	610.0	4.6	106.63	.03	.20	-2000.00	-2000.000	1.55	-2000.00
	4	146.2	860.0	3.1	50.54	.10	.30	-2000.00	-2000.000	2.25	-2000.00
	5	110.5	980.0	4.7	80.24	.10	.30	-2000.00	-2000.000	5.61	-2000.00
11000	1	592.6	387.0	2.2	34.83	.10	.30	-2000.00	-2000.000	2.28	-2000.00
	2	285.5	560.0	5.1	207.12	.01	.10	-2000.00	-2000.000	1.16	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	220.4	860.0	3.6	93.77	.01	.20	-2000.00	-2000.000	1.49	-2000.00
	4	161.3	1050.0	5.7	132.09	.03	.20	-2000.00	-2000.000	1.42	-2000.00
	5	103.3	1010.0	13.1	453.56	.03	.10	-2000.00	-2000.000	1.02	-2000.00
11025	1	411.5	391.0	4.9	200.33	.01	.10	-2000.00	-2000.000	1.49	-2000.00
	2	256.2	731.0	3.9	83.85	.10	.20	-2000.00	-2000.000	2.04	-2000.00
	3	173.6	980.0	5.8	123.41	.10	.20	-2000.00	-2000.000	2.30	-2000.00
	4	103.3	980.0	13.4	432.37	1.00	.10	-2000.00	-2000.000	1.37	-2000.00
	5	67.0	956.0	18.5	534.28	30.00	.10	-2000.00	-2000.000	1.53	-2000.00
11050	1	587.7	498.0	2.5	67.22	.01	.20	-2000.00	-2000.000	2.95	-2000.00
	2	311.5	793.0	5.0	107.24	.10	.20	-2000.00	-2000.000	2.73	-2000.00
	3	176.8	890.0	13.2	417.14	30.00	.10	-2000.00	-2000.000	1.72	-2000.00
	4	99.8	847.0	19.1	543.12	100.00	.10	-2000.00	-2000.000	1.70	-2000.00
	5	55.2	702.0	16.7	295.97	30.00	.20	-2000.00	-2000.000	2.84	-2000.00
11075	1	604.5	593.0	2.9	56.58	.03	.30	-2000.00	-2000.000	2.50	-2000.00
	2	250.5	737.0	12.0	414.16	.10	.10	-2000.00	-2000.000	1.36	-2000.00
	3	132.0	770.0	18.2	532.49	10.00	.10	-2000.00	-2000.000	1.27	-2000.00
	4	59.8	586.0	15.9	480.25	100.00	.10	-2000.00	-2000.000	1.54	-2000.00
	5	37.8	557.0	14.7	535.61	.01	.10	-2000.00	-2000.000	9.65	-2000.00
11100	1	596.5	535.0	12.6	458.04	.01	.10	-2000.00	-2000.000	1.21	-2000.00
	2	254.9	686.0	18.3	574.46	.10	.10	-2000.00	-2000.000	.87	-2000.00
	3	100.1	530.0	15.2	511.20	.03	.10	-2000.00	-2000.000	.83	-2000.00
	4	55.2	495.0	13.3	286.96	.03	.20	-2000.00	-2000.000	1.95	-2000.00
11125	1	601.1	699.0	20.7	598.67	1.00	.10	-2000.00	-2000.000	1.00	-2000.00
	2	139.5	486.0	19.0	543.62	100.00	.10	-2000.00	-2000.000	1.45	-2000.00
	3	66.4	462.0	15.6	511.25	.10	.10	-2000.00	-2000.000	4.94	-2000.00
11150	1	302.4	499.0	22.8	613.50	30.00	.10	-2000.00	-2000.000	1.22	-2000.00
	2	96.7	479.6	18.8	592.22	.03	.10	-2000.00	-2000.000	2.98	-2000.00
11175	1	243.3	477.0	22.6	636.55	1.00	.10	-2000.00	-2000.000	1.26	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 544

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
10825	1	398.2	250.0	.7	20.63	100.00	.30	-2000.00	-2000.000	31.24	-2000.00
	2	93.6	176.3	1.3	31.54	.10	.20	-2000.00	-2000.000	10.28	-2000.00
	3	51.8	194.0	2.3	43.70	100.00	.30	-2000.00	-2000.000	7.36	-2000.00
	4	37.7	237.0	2.7	49.93	100.00	.40	-2000.00	-2000.000	7.90	-2000.00
	5	35.1	330.0	3.5	44.81	30.00	.60	-2000.00	-2000.000	9.01	-2000.00
10850	1	403.7	239.0	.8	25.67	100.00	.20	-2000.00	-2000.000	22.37	-2000.00
	2	133.1	236.0	1.7	41.38	.03	.20	-2000.00	-2000.000	2.86	-2000.00
	3	76.6	271.0	2.0	38.65	100.00	.30	-2000.00	-2000.000	7.52	-2000.00
	4	66.6	394.0	2.0	26.40	30.00	.50	-2000.00	-2000.000	9.95	-2000.00
	5	62.6	556.0	2.5	50.60	100.00	.50	-2000.00	-2000.000	6.96	-2000.00
10875	1	717.6	250.0	.6	20.26	100.00	.30	-2000.00	-2000.000	35.43	-2000.00
	2	283.0	296.0	.9	29.86	.03	.20	-2000.00	-2000.000	23.13	-2000.00
	3	219.1	450.0	.4	25.20	100.00	.20	-2000.00	-2000.000	49.65	-2000.00
	4	172.3	600.0	.1	19.44	100.00	.30	-2000.00	-2000.000	64.30	-2000.00
	5	88.0	460.0	1.8	42.66	.03	.50	-2000.00	-2000.000	9.83	-2000.00
10900	1	543.9	328.0	.6	19.88	100.00	.30	-2000.00	-2000.000	36.02	-2000.00
	2	273.1	494.0	.8	47.02	30.00	.10	-2000.00	-2000.000	21.65	-2000.00
	3	197.7	710.0	.7	25.57	100.00	.20	-2000.00	-2000.000	25.24	-2000.00
	4	90.2	544.0	3.1	81.72	.01	.20	-2000.00	-2000.000	1.81	-2000.00
	5	58.3	528.0	4.1	98.14	.03	.20	-2000.00	-2000.000	2.22	-2000.00
10925	1	1175.0	380.0	.9	26.79	100.00	.20	-2000.00	-2000.000	19.83	-2000.00
	2	688.8	682.0	1.2	52.65	1.00	.10	-2000.00	-2000.000	8.24	-2000.00
	3	303.2	600.0	3.9	150.20	.30	.10	-2000.00	-2000.000	1.97	-2000.00
	4	180.9	590.0	5.7	209.16	100.00	.10	-2000.00	-2000.000	1.99	-2000.00
	5	125.1	620.0	4.5	92.55	30.00	.20	-2000.00	-2000.000	2.79	-2000.00
10950	1	1177.0	530.0	.5	18.91	100.00	.40	-2000.00	-2000.000	40.15	-2000.00
	2	457.6	624.0	3.4	89.38	.01	.20	-2000.00	-2000.000	1.92	-2000.00
	3	248.5	670.0	5.1	119.11	.03	.20	-2000.00	-2000.000	1.21	-2000.00
	4	160.8	730.0	3.7	59.81	.10	.30	-2000.00	-2000.000	1.56	-2000.00
	5	167.5	1140.0	8.9	202.53	.03	.20	-2000.00	-2000.000	1.23	-2000.00
10975	1	797.5	481.0	2.9	46.33	.10	.30	-2000.00	-2000.000	2.07	-2000.00
	2	363.3	658.0	5.2	135.13	.01	.20	-2000.00	-2000.000	.89	-2000.00
	3	229.7	830.0	4.1	66.25	.10	.30	-2000.00	-2000.000	1.97	-2000.00
	4	196.8	1180.0	9.0	226.34	.01	.20	-2000.00	-2000.000	1.00	-2000.00
	5	82.2	744.0	15.2	297.73	.10	.20	-2000.00	-2000.000	.72	-2000.00
11000	1	739.8	527.0	4.9	114.69	.03	.20	-2000.00	-2000.000	1.42	-2000.00
	2	389.1	833.0	4.6	119.66	.01	.20	-2000.00	-2000.000	1.22	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	300.6	1280.0	9.6	198.39	.10	.20	-2000.00	-2000.000	1.49	-2000.00
	4	117.0	830.0	16.6	534.00	.10	.10	-2000.00	-2000.000	.86	-2000.00
	5	54.1	578.0	16.3	567.66	.01	.10	-2000.00	-2000.000	1.51	-2000.00
11025	1	845.8	663.0	3.0	59.38	.03	.30	-2000.00	-2000.000	2.43	-2000.00
	2	521.9	1229.0	8.7	197.49	.03	.20	-2000.00	-2000.000	1.50	-2000.00
	3	171.5	800.0	16.7	524.55	.30	.10	-2000.00	-2000.000	1.06	-2000.00
	4	76.2	597.0	16.7	556.92	.03	.10	-2000.00	-2000.000	1.33	-2000.00
	5	40.2	473.0	17.0	502.85	100.00	.10	-2000.00	-2000.000	1.57	-2000.00
11050	1	1438.0	1000.0	6.9	176.87	.01	.20	-2000.00	-2000.000	1.56	-2000.00
	2	318.9	667.0	16.3	527.10	.10	.10	-2000.00	-2000.000	.91	-2000.00
	3	128.0	530.0	16.5	571.83	.01	.10	-2000.00	-2000.000	1.15	-2000.00
	4	62.3	434.0	16.8	524.57	.30	.10	-2000.00	-2000.000	.60	-2000.00
	5	51.4	538.0	15.8	134.88	1.00	.40	-2000.00	-2000.000	4.04	-2000.00
11075	1	246.0	514.0	18.2	527.64	30.00	.10	-2000.00	-2000.000	1.17	-2000.00
	2	75.1	471.3	18.8	558.67	1.00	.10	-2000.00	-2000.000	1.47	-2000.00
	3	31.3	392.0	19.3	323.54	10.00	.20	-2000.00	-2000.000	1.80	-2000.00
	4	23.9	501.0	17.2	301.34	30.00	.20	-2000.00	-2000.000	2.35	-2000.00
	5	15.1	475.0	14.1	271.19	100.00	.20	-2000.00	-2000.000	3.33	-2000.00
11100	1	297.0	621.0	21.8	679.06	.03	.10	-2000.00	-2000.000	1.10	-2000.00
	2	73.3	460.2	24.8	642.25	100.00	.10	-2000.00	-2000.000	.84	-2000.00
	3	45.9	575.0	22.3	597.98	100.00	.10	-2000.00	-2000.000	1.06	-2000.00
	4	33.4	698.0	17.6	210.83	1.00	.30	-2000.00	-2000.000	1.71	-2000.00
11125	1	264.9	594.0	23.6	657.91	1.00	.10	-2000.00	-2000.000	1.13	-2000.00
	2	114.8	772.0	24.7	645.30	30.00	.10	-2000.00	-2000.000	1.03	-2000.00
	3	64.5	865.0	20.9	580.39	30.00	.10	-2000.00	-2000.000	1.21	-2000.00
11150	1	190.8	660.0	20.5	571.85	30.00	.10	-2000.00	-2000.000	1.27	-2000.00
	2	72.9	763.0	21.2	585.06	100.00	.10	-2000.00	-2000.000	1.84	-2000.00
11175	1	240.7	830.0	13.6	472.76	.03	.10	-2000.00	-2000.000	1.31	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 534

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
11000	1	2281.0	1370.0	7.2	150.32	.10	.20	-2000.00	-2000.000	1.41	-2000.00
	2	439.2	795.0	8.3	174.13	.10	.20	-2000.00	-2000.000	1.39	-2000.00
	3	132.0	470.0	15.6	527.72	.03	.10	-2000.00	-2000.000	.72	-2000.00
	4	66.6	401.0	13.7	449.53	.30	.10	-2000.00	-2000.000	1.00	-2000.00
	5	33.4	302.0	21.2	586.87	30.00	.10	-2000.00	-2000.000	1.28	-2000.00
11025	1	1811.0	810.0	6.5	149.90	.03	.20	-2000.00	-2000.000	1.84	-2000.00
	2	332.0	446.0	15.4	492.77	.30	.10	-2000.00	-2000.000	.97	-2000.00
	3	132.4	350.0	14.3	443.96	30.00	.10	-2000.00	-2000.000	1.31	-2000.00
	4	67.4	302.0	22.9	370.54	10.00	.20	-2000.00	-2000.000	1.73	-2000.00
	5	54.2	364.0	17.6	300.93	10.00	.20	-2000.00	-2000.000	1.58	-2000.00
11050	1	1176.0	690.0	17.6	560.53	.10	.10	-2000.00	-2000.000	1.34	-2000.00
	2	286.0	508.0	16.6	497.66	3.00	.10	-2000.00	-2000.000	1.16	-2000.00
	3	122.1	430.0	25.9	406.92	10.00	.20	-2000.00	-2000.000	1.63	-2000.00
	4	83.7	495.0	19.5	556.32	10.00	.10	-2000.00	-2000.000	.88	-2000.00
	5	53.0	470.0	16.3	485.72	100.00	.10	-2000.00	-2000.000	1.32	-2000.00
11075	1	1021.0	580.0	19.7	591.49	.30	.10	-2000.00	-2000.000	1.15	-2000.00
	2	304.9	522.0	29.2	708.29	100.00	.10	-2000.00	-2000.000	1.07	-2000.00
	3	186.7	630.0	22.6	607.05	100.00	.10	-2000.00	-2000.000	1.04	-2000.00
	4	93.9	535.0	18.3	528.02	30.00	.10	-2000.00	-2000.000	1.11	-2000.00
	5	106.4	910.0	16.9	500.52	30.00	.10	-2000.00	-2000.000	1.22	-2000.00
11100	1	1503.0	730.0	25.3	755.77	.03	.10	-2000.00	-2000.000	1.19	-2000.00
	2	574.9	846.0	22.4	649.07	.30	.10	-2000.00	-2000.000	1.07	-2000.00
	3	240.2	700.0	18.7	558.21	1.00	.10	-2000.00	-2000.000	1.15	-2000.00
	4	211.4	1030.0	17.8	561.38	.10	.10	-2000.00	-2000.000	.94	-2000.00
	5	139.3	1020.0	18.2	546.18	1.00	.10	-2000.00	-2000.000	1.10	-2000.00
11125	1	1591.0	860.0	15.4	520.88	.03	.10	-2000.00	-2000.000	1.31	-2000.00
	2	474.8	771.0	14.9	491.29	.10	.10	-2000.00	-2000.000	1.46	-2000.00
	3	366.4	1180.0	14.8	507.22	.03	.10	-2000.00	-2000.000	1.18	-2000.00
	4	229.0	1230.0	16.1	521.62	.10	.10	-2000.00	-2000.000	1.26	-2000.00
	5	126.2	1020.0	16.6	528.95	.10	.10	-2000.00	-2000.000	1.13	-2000.00
11150	1	1253.0	670.0	7.1	162.04	.03	.20	-2000.00	-2000.000	1.76	-2000.00
	2	784.0	1273.0	9.1	349.83	.01	.10	-2000.00	-2000.000	2.13	-2000.00
	3	465.5	1500.0	11.4	423.63	.01	.10	-2000.00	-2000.000	1.32	-2000.00
	4	207.8	1120.0	12.9	466.25	.01	.10	-2000.00	-2000.000	1.07	-2000.00
	5	219.6	1780.0	12.8	443.55	.03	.10	-2000.00	-2000.000	1.10	-2000.00
11175	1	1503.0	900.0	5.9	137.62	.03	.20	-2000.00	-2000.000	1.86	-2000.00
	2	771.3	1397.0	8.6	196.46	.03	.20	-2000.00	-2000.000	1.41	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	314.7	1130.0	10.5	214.06	.10	.20	-2000.00	-2000.000	1.27	-2000.00
	4	314.5	1890.0	10.6	215.53	.10	.20	-2000.00	-2000.000	1.16	-2000.00
	5	116.4	1050.0	9.9	350.85	.10	.10	-2000.00	-2000.000	.98	-2000.00
11200	1	1923.0	1050.0	5.9	136.21	.03	.20	-2000.00	-2000.000	1.46	-2000.00
	2	642.3	1061.0	8.2	171.58	.10	.20	-2000.00	-2000.000	1.66	-2000.00
	3	614.0	2020.0	8.8	181.51	.10	.20	-2000.00	-2000.000	1.27	-2000.00
	4	207.0	1140.0	8.5	305.91	.10	.10	-2000.00	-2000.000	1.10	-2000.00
	5	266.4	2200.0	15.3	536.25	.01	.10	-2000.00	-2000.000	1.07	-2000.00
11225	1	1657.0	960.0	5.4	138.34	.01	.20	-2000.00	-2000.000	1.28	-2000.00
	2	1239.0	2160.0	6.7	154.52	.03	.20	-2000.00	-2000.000	1.63	-2000.00
	3	435.3	1510.0	6.7	265.12	.01	.10	-2000.00	-2000.000	1.23	-2000.00
	4	446.3	2590.0	14.0	500.47	.01	.10	-2000.00	-2000.000	1.14	-2000.00
	5	212.3	1850.0	15.6	504.94	.30	.10	-2000.00	-2000.000	1.41	-2000.00
11250	1	2188.0	1710.0	4.8	125.92	.01	.20	-2000.00	-2000.000	1.49	-2000.00
	2	569.2	1340.0	5.0	107.47	.10	.20	-2000.00	-2000.000	1.48	-2000.00
	3	610.8	2870.0	12.4	453.42	.01	.10	-2000.00	-2000.000	1.34	-2000.00
	4	261.3	2050.0	15.0	483.57	.30	.10	-2000.00	-2000.000	1.13	-2000.00
	5	123.6	1450.0	12.5	404.29	3.00	.10	-2000.00	-2000.000	.94	-2000.00
11275	1	1252.0	1000.0	3.9	91.54	.03	.20	-2000.00	-2000.000	1.10	-2000.00
	2	1071.0	2580.0	11.2	228.82	.10	.20	-2000.00	-2000.000	1.33	-2000.00
	3	386.0	1860.0	14.4	458.80	1.00	.10	-2000.00	-2000.000	1.22	-2000.00
	4	178.0	1430.0	11.4	387.20	.30	.10	-2000.00	-2000.000	.84	-2000.00
	5	55.1	665.0	10.6	356.13	.30	.10	-2000.00	-2000.000	1.60	-2000.00
11300	1	2656.0	1930.0	9.4	236.99	.01	.20	-2000.00	-2000.000	6.58	-2000.00
	2	2655.0	5810.0	10.9	147.60	.30	.30	-2000.00	-2000.000	3.75	-2000.00
	3	376.3	1640.0	10.2	342.46	3.00	.10	-2000.00	-2000.000	.53	-2000.00
	4	104.4	760.0	8.5	158.01	3.00	.20	-2000.00	-2000.000	3.39	-2000.00
	5	41.8	457.0	8.0	275.74	30.00	.10	-2000.00	-2000.000	2.19	-2000.00
11325	1	2193.0	1530.0	11.8	435.38	.01	.10	-2000.00	-2000.000	1.50	-2000.00
	2	552.3	1156.0	8.6	296.68	10.00	.10	-2000.00	-2000.000	.61	-2000.00
	3	139.8	580.0	6.9	242.87	100.00	.10	-2000.00	-2000.000	1.68	-2000.00
	4	53.1	370.0	5.8	120.56	.30	.20	-2000.00	-2000.000	3.16	-2000.00
	5	30.8	322.0	6.6	246.18	.10	.10	-2000.00	-2000.000	3.83	-2000.00
11350	1	1271.0	2850.0	11.1	226.72	.10	.20	-2000.00	-2000.000	1.55	-2000.00
	2	96.3	647.8	7.5	148.55	.30	.20	-2000.00	-2000.000	.87	-2000.00
	3	29.1	391.0	5.8	231.34	.01	.10	-2000.00	-2000.000	.74	-2000.00
	4	17.5	392.0	6.3	86.40	.30	.30	-2000.00	-2000.000	1.96	-2000.00
	5	13.6	458.0	5.5	204.10	.10	.10	-2000.00	-2000.000	2.47	-2000.00
11375	1	982.4	670.0	5.1	207.37	.01	.10	-2000.00	-2000.000	1.96	-2000.00
	2	223.8	458.0	4.8	112.95	.03	.20	-2000.00	-2000.000	1.30	-2000.00
	3	121.4	490.0	5.3	123.12	.03	.20	-2000.00	-2000.000	1.38	-2000.00
	4	95.2	649.0	4.6	188.75	.01	.10	-2000.00	-2000.000	1.53	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	118.6	1210.0	4.2	173.15	.01	.10	-2000.00	-2000.000	2.55	-2000.00
11400	1	187.7	453.0	3.4	90.05	.01	.20	-2000.00	-2000.000	1.86	-2000.00
	2	68.3	495.2	4.3	111.42	.01	.20	-2000.00	-2000.000	1.85	-2000.00
	3	44.6	644.0	3.8	81.83	.10	.20	-2000.00	-2000.000	2.14	-2000.00
	4	47.3	1142.0	3.2	126.32	.10	.10	-2000.00	-2000.000	2.94	-2000.00
	5	43.0	1559.0	12.5	235.37	.03	.30	-2000.00	-2000.000	1.79	-2000.00
11425	1	596.6	936.0	5.6	90.32	.10	.30	-2000.00	-2000.000	1.95	-2000.00
	2	212.6	1001.0	4.1	105.96	.01	.20	-2000.00	-2000.000	1.57	-2000.00
	3	159.6	1500.0	3.0	71.79	.03	.20	-2000.00	-2000.000	2.89	-2000.00
	4	119.4	1870.0	11.7	222.58	.03	.30	-2000.00	-2000.000	1.28	-2000.00
	5	59.0	1390.0	5.8	137.74	.01	.30	-2000.00	-2000.000	3.44	-2000.00
11450	1	591.3	1160.0	6.4	102.71	.10	.30	-2000.00	-2000.000	1.69	-2000.00
	2	262.4	1544.0	4.0	64.57	.10	.30	-2000.00	-2000.000	2.65	-2000.00
	3	160.2	1880.0	12.0	226.37	.03	.30	-2000.00	-2000.000	1.08	-2000.00
	4	72.7	1426.0	5.3	129.14	.01	.30	-2000.00	-2000.000	1.48	-2000.00
	5	49.5	1455.0	5.1	130.07	.01	.20	-2000.00	-2000.000	4.86	-2000.00
11475	1	1228.0	2020.0	8.2	130.06	.10	.30	-2000.00	-2000.000	1.69	-2000.00
	2	364.1	1805.0	13.8	258.79	.03	.30	-2000.00	-2000.000	.79	-2000.00
	3	131.2	1290.0	5.3	130.09	.01	.30	-2000.00	-2000.000	1.41	-2000.00
	4	88.7	1466.0	4.9	126.28	.01	.20	-2000.00	-2000.000	1.49	-2000.00
	5	100.6	2490.0	4.2	47.70	3.00	.30	-2000.00	-2000.000	5.39	-2000.00
11500	1	1060.0	2560.0	18.4	336.94	.03	.30	-2000.00	-2000.000	1.55	-2000.00
	2	183.7	1331.0	6.2	151.25	.01	.30	-2000.00	-2000.000	1.54	-2000.00
	3	94.4	1365.0	4.3	100.57	.03	.20	-2000.00	-2000.000	2.72	-2000.00
	4	96.5	2331.0	3.3	60.34	100.00	.30	-2000.00	-2000.000	6.10	-2000.00
11525	1	744.8	2338.0	17.4	320.42	.03	.30	-2000.00	-2000.000	.66	-2000.00
	2	146.2	1377.0	4.3	83.30	.03	.40	-2000.00	-2000.000	3.01	-2000.00
	3	118.3	2220.0	1.8	34.68	.03	.30	-2000.00	-2000.000	3.32	-2000.00
11550	1	745.5	1560.0	11.3	267.48	.01	.30	-2000.00	-2000.000	.91	-2000.00
	2	365.2	2293.0	6.4	153.49	.01	.30	-2000.00	-2000.000	1.56	-2000.00
11575	1	445.9	1750.0	7.0	136.26	.03	.30	-2000.00	-2000.000	1.42	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 534

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	724.2	349.0	.5	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	2	721.5	1045.0	.9	54.33	.01	.50	-2000.00	-2000.000	16.28	-2000.00
	3	70.3	203.0	2.5	36.00	.10	.40	-2000.00	-2000.000	2.11	-2000.00
	4	68.2	329.0	1.6	32.16	.03	.30	-2000.00	-2000.000	2.73	-2000.00
	5	70.2	508.0	.5	20.53	100.00	.50	-2000.00	-2000.000	51.83	-2000.00
10850	1	443.6	221.0	1.2	36.83	.01	.20	-2000.00	-2000.000	10.74	-2000.00
	2	111.2	166.0	2.2	29.92	.10	.40	-2000.00	-2000.000	2.30	-2000.00
	3	110.8	330.0	1.5	31.31	.03	.30	-2000.00	-2000.000	5.93	-2000.00
	4	95.1	474.0	1.6	23.04	.10	.40	-2000.00	-2000.000	7.34	-2000.00
	5	37.2	278.0	.8	24.91	.03	.30	-2000.00	-2000.000	39.95	-2000.00
10875	1	665.0	245.0	1.3	27.88	.03	.30	-2000.00	-2000.000	8.70	-2000.00
	2	342.2	379.0	1.8	25.13	.10	.40	-2000.00	-2000.000	1.78	-2000.00
	3	229.9	500.0	2.1	33.48	.10	.30	-2000.00	-2000.000	2.02	-2000.00
	4	72.7	268.0	1.9	16.62	.30	.60	-2000.00	-2000.000	6.35	-2000.00
	5	30.0	166.0	-.6	45.13	100.00	.80	-2000.00	-2000.000	123.74	-2000.00
10900	1	552.4	299.0	1.5	40.24	.01	.20	-2000.00	-2000.000	2.62	-2000.00
	2	222.4	361.0	2.2	58.15	.01	.20	-2000.00	-2000.000	2.49	-2000.00
	3	90.8	294.0	3.0	118.01	.10	.10	-2000.00	-2000.000	1.38	-2000.00
	4	24.8	134.0	1.0	15.48	30.00	.40	-2000.00	-2000.000	17.93	-2000.00
	5	35.4	287.0	3.8	84.85	100.00	.20	-2000.00	-2000.000	4.66	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 524

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	162.4	50.9	3.1	73.94	.03	.20	-2000.00	-2000.000	1.35	-2000.00
	2	70.6	66.4	1.9	78.21	1.00	.10	-2000.00	-2000.000	3.06	-2000.00
	3	39.2	73.6	1.5	33.12	30.00	.20	-2000.00	-2000.000	4.01	-2000.00
	4	37.8	118.7	.8	40.05	100.00	.80	-2000.00	-2000.000	35.02	-2000.00
	5	38.3	180.5	1.1	51.62	100.00	.80	-2000.00	-2000.000	25.41	-2000.00
10850	1	239.6	59.7	2.2	36.24	.10	.30	-2000.00	-2000.000	1.71	-2000.00
	2	105.7	79.0	2.1	20.49	.30	.50	-2000.00	-2000.000	1.90	-2000.00
	3	84.6	126.2	.4	25.69	100.00	.60	-2000.00	-2000.000	49.49	-2000.00
	4	78.6	195.9	.4	20.69	100.00	.50	-2000.00	-2000.000	47.00	-2000.00
	5	69.6	260.3	.3	20.82	100.00	.50	-2000.00	-2000.000	55.60	-2000.00
10875	1	200.3	157.0	1.7	34.04	.03	.30	-2000.00	-2000.000	2.08	-2000.00
	2	106.4	250.0	1.8	20.10	.30	.40	-2000.00	-2000.000	5.01	-2000.00
	3	73.4	345.0	1.5	17.61	.30	.40	-2000.00	-2000.000	9.36	-2000.00
	4	52.0	408.0	1.3	29.48	.03	.30	-2000.00	-2000.000	20.12	-2000.00
	5	48.3	568.0	4.2	38.47	.30	.50	-2000.00	-2000.000	3.59	-2000.00
10900	1	489.3	320.0	1.2	55.38	.10	.10	-2000.00	-2000.000	9.99	-2000.00
	2	229.8	450.0	1.6	38.60	.03	.20	-2000.00	-2000.000	1.84	-2000.00
	3	136.0	530.0	2.0	80.78	.10	.10	-2000.00	-2000.000	2.58	-2000.00
	4	112.6	730.0	5.2	198.66	.10	.10	-2000.00	-2000.000	1.69	-2000.00
	5	70.7	693.0	7.7	273.39	100.00	.10	-2000.00	-2000.000	2.16	-2000.00
10925	1	1204.0	360.0	1.1	52.98	.10	.10	-2000.00	-2000.000	11.96	-2000.00
	2	507.0	454.8	1.7	27.83	.10	.30	-2000.00	-2000.000	2.95	-2000.00
	3	410.0	734.0	4.4	95.93	.10	.20	-2000.00	-2000.000	1.92	-2000.00
	4	225.0	672.0	7.1	279.78	.01	.10	-2000.00	-2000.000	1.38	-2000.00
	5	135.6	608.0	9.9	352.77	.10	.10	-2000.00	-2000.000	1.65	-2000.00
10950	1	958.9	430.0	1.7	28.02	.10	.30	-2000.00	-2000.000	4.41	-2000.00
	2	494.7	665.0	4.4	69.28	.10	.30	-2000.00	-2000.000	1.93	-2000.00
	3	264.7	710.0	6.7	153.14	.03	.20	-2000.00	-2000.000	1.04	-2000.00
	4	146.0	650.0	9.4	193.14	.10	.20	-2000.00	-2000.000	1.44	-2000.00
	5	117.8	790.0	11.9	259.20	.03	.20	-2000.00	-2000.000	1.26	-2000.00
10975	1	859.4	562.0	4.1	106.09	.01	.20	-2000.00	-2000.000	1.63	-2000.00
	2	376.2	738.0	6.7	142.10	.10	.20	-2000.00	-2000.000	1.30	-2000.00
	3	185.5	720.0	9.2	190.66	.10	.20	-2000.00	-2000.000	1.32	-2000.00
	4	137.8	900.0	12.2	447.37	.01	.10	-2000.00	-2000.000	1.51	-2000.00
	5	51.7	507.0	12.6	444.22	.01	.10	-2000.00	-2000.000	1.51	-2000.00
11000	1	266.3	760.0	6.6	242.85	100.00	.10	-2000.00	-2000.000	3.17	-2000.00
	2	98.0	838.8	11.0	221.19	100.00	.20	-2000.00	-2000.000	4.08	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	62.8	1073.0	16.7	257.00	100.00	.30	-2000.00	-2000.000	5.38	-2000.00
	4	21.4	611.0	19.9	224.08	30.00	.40	-2000.00	-2000.000	6.15	-2000.00
	5	17.9	768.0	27.1	353.35	100.00	.40	-2000.00	-2000.000	6.12	-2000.00
11025	1	1332.0	800.0	7.1	158.94	.03	.20	-2000.00	-2000.000	1.97	-2000.00
	2	671.2	1215.0	10.8	241.68	.03	.20	-2000.00	-2000.000	1.48	-2000.00
	3	205.9	740.0	11.9	435.59	.01	.10	-2000.00	-2000.000	1.20	-2000.00
	4	158.5	950.0	15.8	515.63	.10	.10	-2000.00	-2000.000	1.14	-2000.00
	5	68.8	622.0	15.8	512.85	.10	.10	-2000.00	-2000.000	1.14	-2000.00
11050	1	1733.0	1080.0	8.5	194.87	.03	.20	-2000.00	-2000.000	1.42	-2000.00
	2	425.9	802.0	10.4	213.45	.10	.20	-2000.00	-2000.000	1.45	-2000.00
	3	296.7	1110.0	14.7	521.07	.01	.10	-2000.00	-2000.000	1.24	-2000.00
	4	120.0	750.0	15.4	521.49	.03	.10	-2000.00	-2000.000	1.23	-2000.00
	5	134.9	1270.0	15.3	518.46	.03	.10	-2000.00	-2000.000	1.21	-2000.00
11075	1	182.8	717.5	7.6	174.41	.03	.20	-2000.00	-2000.000	1.61	-2000.00
	2	104.6	1231.7	12.2	270.23	.03	.20	-2000.00	-2000.000	1.34	-2000.00
	3	38.0	142.0	13.1	289.24	.03	.20	-2000.00	-2000.000	1.23	-2000.00
	4	38.8	243.0	14.8	462.56	100.00	.10	-2000.00	-2000.000	4.50	-2000.00
	5	21.0	197.0	10.9	82.78	.30	.70	-2000.00	-2000.000	7.22	-2000.00
11100	1	440.0	1256.0	9.1	204.95	.03	.20	-2000.00	-2000.000	1.36	-2000.00
	2	130.4	1116.0	11.1	225.72	.10	.20	-2000.00	-2000.000	1.60	-2000.00
	3	116.6	1990.0	12.1	445.56	.01	.10	-2000.00	-2000.000	1.55	-2000.00
	4	53.4	1524.0	13.6	486.93	.01	.10	-2000.00	-2000.000	1.31	-2000.00
	5	26.0	1113.0	14.0	441.46	30.00	.10	-2000.00	-2000.000	2.74	-2000.00
11125	1	865.9	679.0	8.0	166.86	.10	.20	-2000.00	-2000.000	1.54	-2000.00
	2	629.1	1481.0	9.8	202.01	.10	.20	-2000.00	-2000.000	1.30	-2000.00
	3	256.3	1200.0	11.6	429.40	.01	.10	-2000.00	-2000.000	1.32	-2000.00
	4	118.1	920.0	12.3	413.93	.30	.10	-2000.00	-2000.000	1.34	-2000.00
	5	65.5	770.0	13.6	428.03	30.00	.10	-2000.00	-2000.000	1.87	-2000.00
11150	1	3211.0	2010.0	6.5	167.20	.01	.20	-2000.00	-2000.000	1.26	-2000.00
	2	734.0	1382.0	8.8	183.82	.10	.20	-2000.00	-2000.000	1.33	-2000.00
	3	263.9	990.0	9.8	349.71	.10	.10	-2000.00	-2000.000	1.30	-2000.00
	4	122.7	770.0	11.5	382.21	1.00	.10	-2000.00	-2000.000	1.30	-2000.00
	5	91.4	861.0	11.2	378.83	1.00	.10	-2000.00	-2000.000	1.82	-2000.00
11175	1	1091.0	1000.0	6.4	148.69	.03	.20	-2000.00	-2000.000	1.71	-2000.00
	2	300.4	832.0	7.7	286.18	.10	.10	-2000.00	-2000.000	1.66	-2000.00
	3	131.1	720.0	9.7	328.50	10.00	.10	-2000.00	-2000.000	1.45	-2000.00
	4	78.5	724.0	10.3	345.20	100.00	.10	-2000.00	-2000.000	1.76	-2000.00
	5	68.4	947.0	11.9	394.38	30.00	.10	-2000.00	-2000.000	2.90	-2000.00
11200	1	1367.0	1100.0	6.4	148.15	.03	.20	-2000.00	-2000.000	1.42	-2000.00
	2	342.8	827.0	7.2	266.55	.10	.10	-2000.00	-2000.000	1.22	-2000.00
	3	166.6	800.0	7.9	303.22	.01	.10	-2000.00	-2000.000	1.17	-2000.00
	4	123.3	990.0	9.7	352.04	.10	.10	-2000.00	-2000.000	1.96	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	122.4	1470.0	12.3	401.59	1.00	.10	-2000.00	-2000.000	1.15	-2000.00
11225	1	976.9	829.0	6.0	127.19	.10	.20	-2000.00	-2000.000	1.49	-2000.00
	2	350.8	893.0	6.4	136.27	.10	.20	-2000.00	-2000.000	1.91	-2000.00
	3	194.9	990.0	8.4	325.46	.01	.10	-2000.00	-2000.000	1.31	-2000.00
	4	160.8	1360.0	10.7	388.07	.03	.10	-2000.00	-2000.000	1.06	-2000.00
	5	132.9	1690.0	13.2	428.18	30.00	.10	-2000.00	-2000.000	2.68	-2000.00
11250	1	1922.0	1580.0	5.5	129.72	.03	.20	-2000.00	-2000.000	1.46	-2000.00
	2	544.8	1350.0	6.5	150.34	.03	.20	-2000.00	-2000.000	1.38	-2000.00
	3	309.3	1530.0	8.5	325.55	.01	.10	-2000.00	-2000.000	1.03	-2000.00
	4	204.6	1690.0	11.7	416.14	.03	.10	-2000.00	-2000.000	1.13	-2000.00
	5	147.5	1820.0	12.2	420.87	.10	.10	-2000.00	-2000.000	1.26	-2000.00
11275	1	1276.0	1140.0	5.4	124.71	.03	.20	-2000.00	-2000.000	1.20	-2000.00
	2	489.2	1316.0	6.5	137.39	.10	.20	-2000.00	-2000.000	1.48	-2000.00
	3	272.1	1460.0	9.9	372.40	.01	.10	-2000.00	-2000.000	.82	-2000.00
	4	169.4	1510.0	11.2	402.27	.03	.10	-2000.00	-2000.000	.95	-2000.00
	5	83.9	1129.0	12.0	418.30	.01	.10	-2000.00	-2000.000	6.33	-2000.00
11300	1	2272.0	1980.0	5.8	122.75	.10	.20	-2000.00	-2000.000	1.78	-2000.00
	2	412.6	1079.0	8.2	169.14	.10	.20	-2000.00	-2000.000	1.25	-2000.00
	3	303.4	1580.0	9.5	332.82	.30	.10	-2000.00	-2000.000	.74	-2000.00
	4	110.2	960.0	10.1	346.75	1.00	.10	-2000.00	-2000.000	1.35	-2000.00
	5	22.2	290.0	6.9	127.26	10.00	.20	-2000.00	-2000.000	4.54	-2000.00
11325	1	365.1	1270.0	7.6	174.25	.03	.20	-2000.00	-2000.000	1.01	-2000.00
	2	173.3	1810.0	8.4	176.23	.10	.20	-2000.00	-2000.000	1.29	-2000.00
	3	60.4	1260.0	8.9	341.85	.01	.10	-2000.00	-2000.000	1.26	-2000.00
	4	9.0	313.0	5.8	224.99	.01	.10	-2000.00	-2000.000	3.28	-2000.00
	5	10.4	540.0	7.7	284.25	100.00	.10	-2000.00	-2000.000	4.70	-2000.00
11350	1	1971.0	1620.0	7.5	191.88	.01	.20	-2000.00	-2000.000	.97	-2000.00
	2	1123.0	2780.0	7.5	174.54	.03	.20	-2000.00	-2000.000	1.30	-2000.00
	3	128.1	630.0	4.2	107.42	.01	.20	-2000.00	-2000.000	1.36	-2000.00
	4	111.9	920.0	5.7	231.70	.01	.10	-2000.00	-2000.000	2.07	-2000.00
	5	68.6	850.0	7.0	275.57	.01	.10	-2000.00	-2000.000	1.89	-2000.00
11375	1	2469.0	4300.0	8.2	209.51	.01	.20	-2000.00	-2000.000	1.10	-2000.00
	2	179.6	939.0	3.7	59.86	.10	.30	-2000.00	-2000.000	.84	-2000.00
	3	115.6	1200.0	4.4	93.93	.10	.20	-2000.00	-2000.000	1.50	-2000.00
	4	60.4	1053.0	5.1	121.51	.03	.20	-2000.00	-2000.000	2.16	-2000.00
	5	44.8	1170.0	5.2	190.95	3.00	.10	-2000.00	-2000.000	2.54	-2000.00
11400	1	354.3	695.0	2.9	56.68	.03	.30	-2000.00	-2000.000	2.01	-2000.00
	2	184.9	1088.0	4.4	114.91	.01	.20	-2000.00	-2000.000	1.45	-2000.00
	3	84.3	990.0	5.2	110.35	.10	.20	-2000.00	-2000.000	1.50	-2000.00
	4	57.4	1127.0	5.2	195.09	30.00	.10	-2000.00	-2000.000	2.18	-2000.00
	5	53.3	1568.0	7.9	160.73	.10	.20	-2000.00	-2000.000	3.13	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
11425	1	581.3	960.0	5.0	77.52	.10	.30	-2000.00	-2000.000	1.96	-2000.00
	2	197.3	978.0	5.0	129.32	.01	.20	-2000.00	-2000.000	1.25	-2000.00
	3	117.2	1150.0	4.5	96.63	.10	.20	-2000.00	-2000.000	1.28	-2000.00
	4	100.7	1660.0	6.4	167.72	.01	.20	-2000.00	-2000.000	2.61	-2000.00
	5	66.5	1648.0	7.8	154.21	.03	.30	-2000.00	-2000.000	3.14	-2000.00
11450	1	267.6	700.0	4.5	72.96	.10	.30	-2000.00	-2000.000	2.17	-2000.00
	2	106.5	836.0	4.0	94.47	.03	.20	-2000.00	-2000.000	1.43	-2000.00
	3	82.0	1284.0	5.8	93.99	.10	.30	-2000.00	-2000.000	2.55	-2000.00
	4	50.8	1329.0	7.2	141.33	.03	.30	-2000.00	-2000.000	2.16	-2000.00
	5	32.1	1260.0	7.2	115.84	.10	.30	-2000.00	-2000.000	2.38	-2000.00
11475	1	446.7	876.0	4.3	84.88	.03	.30	-2000.00	-2000.000	1.68	-2000.00
	2	219.4	1291.0	5.5	107.22	.03	.30	-2000.00	-2000.000	1.75	-2000.00
	3	110.9	1300.0	6.5	158.26	.01	.30	-2000.00	-2000.000	1.48	-2000.00
	4	63.1	1238.0	6.4	125.45	.03	.30	-2000.00	-2000.000	1.54	-2000.00
	5	80.5	2369.0	4.9	113.75	.03	.20	-2000.00	-2000.000	1.61	-2000.00
11500	1	626.7	1035.0	5.8	140.46	.01	.30	-2000.00	-2000.000	1.74	-2000.00
	2	241.0	1194.0	6.6	161.96	.01	.30	-2000.00	-2000.000	2.00	-2000.00
	3	122.2	1200.0	6.6	127.56	.03	.30	-2000.00	-2000.000	1.37	-2000.00
	4	140.4	2320.0	4.9	125.86	.01	.20	-2000.00	-2000.000	1.52	-2000.00
	5	107.0	2650.0	4.5	117.09	.01	.20	-2000.00	-2000.000	1.02	-2000.00
11525	1	197.5	1240.0	6.3	154.11	.01	.30	-2000.00	-2000.000	2.55	-2000.00
	2	70.4	1326.0	6.4	153.64	.01	.30	-2000.00	-2000.000	1.96	-2000.00
	3	66.5	2500.0	4.5	86.46	.03	.30	-2000.00	-2000.000	1.34	-2000.00
	4	44.5	2790.0	4.5	105.42	.03	.20	-2000.00	-2000.000	1.88	-2000.00
11550	1	322.1	1440.0	8.0	192.38	.01	.30	-2000.00	-2000.000	1.11	-2000.00
	2	207.3	2780.0	6.2	119.93	.03	.30	-2000.00	-2000.000	2.02	-2000.00
	3	119.2	3200.0	5.5	106.30	.03	.30	-2000.00	-2000.000	2.31	-2000.00
11575	1	156.2	1630.0	7.2	138.56	.03	.30	-2000.00	-2000.000	1.74	-2000.00
	2	66.8	2099.0	6.6	126.83	.03	.30	-2000.00	-2000.000	2.30	-2000.00
11600	1	362.5	1260.0	6.2	119.21	.03	.30	-2000.00	-2000.000	1.58	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 514

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
825	1	550.3	191.0	1.2	54.47	.10	.10	-2000.00	-2000.000	10.65	-2000.00
	2	157.3	164.0	1.7	27.61	.10	.30	-2000.00	-2000.000	1.49	-2000.00
	3	53.3	111.0	2.3	25.36	.30	.40	-2000.00	-2000.000	1.65	-2000.00
	4	64.4	224.0	2.4	26.41	.30	.40	-2000.00	-2000.000	3.38	-2000.00
	5	43.8	229.0	.9	28.52	100.00	.20	-2000.00	-2000.000	21.13	-2000.00
10850	1	378.0	152.0	.7	19.72	100.00	.40	-2000.00	-2000.000	31.70	-2000.00
	2	95.9	115.8	1.9	28.67	.10	.40	-2000.00	-2000.000	3.08	-2000.00
	3	94.8	228.0	2.2	20.45	.30	.50	-2000.00	-2000.000	3.06	-2000.00
	4	57.6	231.0	.7	46.82	30.00	.10	-2000.00	-2000.000	35.51	-2000.00
	5	25.4	153.0	-2.0	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10875	1	296.0	136.0	1.3	33.75	.03	.20	-2000.00	-2000.000	6.84	-2000.00
	2	183.1	253.0	2.5	40.52	.10	.30	-2000.00	-2000.000	.82	-2000.00
	3	89.3	246.0	1.8	37.12	.30	.20	-2000.00	-2000.000	1.15	-2000.00
	4	34.2	157.0	-.3	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	63.5	439.0	1.8	75.30	30.00	.10	-2000.00	-2000.000	4.87	-2000.00
10898	1	713.3	243.0	1.8	47.28	.01	.20	-2000.00	-2000.000	2.36	-2000.00
	2	230.6	236.0	1.9	27.23	.30	.30	-2000.00	-2000.000	2.01	-2000.00
	3	76.3	155.0	.0	40.05	100.00	.80	-2000.00	-2000.000	139.32	-2000.00
	4	129.5	440.0	2.0	21.60	.30	.40	-2000.00	-2000.000	4.27	-2000.00
	5	100.9	510.0	6.9	270.07	.01	.10	-2000.00	-2000.000	1.13	-2000.00
10922	1	470.6	147.7	1.6	43.02	.01	.20	-2000.00	-2000.000	2.77	-2000.00
	2	142.7	134.4	.0	40.05	100.00	.80	-2000.00	-2000.000	105.10	-2000.00
	3	218.7	411.0	1.9	31.34	.10	.30	-2000.00	-2000.000	2.41	-2000.00
	4	156.5	491.0	6.6	139.26	.10	.20	-2000.00	-2000.000	1.41	-2000.00
	5	115.4	543.0	6.9	255.74	.10	.10	-2000.00	-2000.000	1.31	-2000.00
10947	1	634.6	214.0	2.5	58.33	.03	.20	-2000.00	-2000.000	1.57	-2000.00
	2	662.5	671.0	3.5	94.01	.01	.20	-2000.00	-2000.000	1.86	-2000.00
	3	343.1	690.0	7.3	154.18	.10	.20	-2000.00	-2000.000	1.05	-2000.00
	4	207.5	700.0	7.1	281.19	.01	.10	-2000.00	-2000.000	1.04	-2000.00
	5	105.2	530.0	10.3	366.38	.10	.10	-2000.00	-2000.000	1.70	-2000.00
10972	1	2855.0	853.0	4.2	110.74	.01	.20	-2000.00	-2000.000	1.71	-2000.00
	2	943.5	846.4	7.4	169.40	.03	.20	-2000.00	-2000.000	1.23	-2000.00
	3	451.2	807.0	6.6	138.96	.10	.20	-2000.00	-2000.000	1.43	-2000.00
	4	202.6	605.0	9.4	211.58	.03	.20	-2000.00	-2000.000	1.15	-2000.00
	5	134.4	602.0	9.4	360.43	.01	.10	-2000.00	-2000.000	1.91	-2000.00
10997	1	2597.0	1530.0	11.8	263.00	.03	.20	-2000.00	-2000.000	1.45	-2000.00
	2	515.5	916.0	7.9	165.11	.10	.20	-2000.00	-2000.000	1.11	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	168.7	590.0	9.6	197.77	.10	.20	-2000.00	-2000.000	1.64	-2000.00
	4	97.1	575.0	9.4	340.41	.10	.10	-2000.00	-2000.000	1.84	-2000.00
	5	37.4	332.0	8.4	287.39	100.00	.10	-2000.00	-2000.000	2.22	-2000.00
11022	1	2877.0	1960.0	11.6	259.53	.03	.20	-2000.00	-2000.000	1.42	-2000.00
	2	573.9	1175.0	12.8	283.90	.03	.20	-2000.00	-2000.000	1.30	-2000.00
	3	240.5	980.0	11.2	250.54	.03	.20	-2000.00	-2000.000	1.36	-2000.00
	4	74.1	505.0	9.0	202.18	.03	.20	-2000.00	-2000.000	1.13	-2000.00
	5	92.2	943.0	10.9	220.69	.10	.20	-2000.00	-2000.000	1.16	-2000.00
11046	1	1161.0	3310.0	18.1	385.75	.03	.20	-2000.00	-2000.000	1.21	-2000.00
	2	247.5	2119.0	16.6	326.84	.10	.20	-2000.00	-2000.000	1.46	-2000.00
	3	56.5	966.0	13.8	276.65	.10	.20	-2000.00	-2000.000	1.45	-2000.00
	4	60.6	1729.0	15.7	507.58	.10	.10	-2000.00	-2000.000	1.47	-2000.00
	5	17.3	740.0	13.3	441.50	100.00	.10	-2000.00	-2000.000	3.76	-2000.00
11065	1	2308.0	3810.0	15.7	342.36	.03	.20	-2000.00	-2000.000	1.18	-2000.00
	2	348.7	1728.0	13.9	306.56	.03	.20	-2000.00	-2000.000	.93	-2000.00
	3	318.8	3150.0	15.0	299.30	.10	.20	-2000.00	-2000.000	1.25	-2000.00
	4	76.8	1269.0	13.3	294.39	.03	.20	-2000.00	-2000.000	1.02	-2000.00
	5	57.5	1424.0	14.9	299.01	.10	.20	-2000.00	-2000.000	1.18	-2000.00
11096	1	826.0	1995.0	9.5	239.62	.01	.20	-2000.00	-2000.000	1.41	-2000.00
	2	655.4	4749.0	12.3	272.31	.03	.20	-2000.00	-2000.000	1.24	-2000.00
	3	133.8	1930.0	11.4	254.74	.03	.20	-2000.00	-2000.000	1.18	-2000.00
	4	90.7	2190.0	13.8	276.83	.10	.20	-2000.00	-2000.000	1.60	-2000.00
	5	29.3	1059.0	13.1	444.11	.10	.10	-2000.00	-2000.000	1.76	-2000.00
11120	1	2624.0	4110.0	8.2	206.30	.01	.20	-2000.00	-2000.000	1.08	-2000.00
	2	397.1	1870.0	7.5	195.19	.01	.20	-2000.00	-2000.000	1.08	-2000.00
	3	246.4	2310.0	9.9	223.66	.03	.20	-2000.00	-2000.000	1.04	-2000.00
	4	72.8	1142.0	9.5	196.43	.10	.20	-2000.00	-2000.000	1.53	-2000.00
	5	26.7	628.0	9.5	370.99	.01	.10	-2000.00	-2000.000	2.46	-2000.00
11146	1	879.1	1200.0	4.4	70.95	.10	.30	-2000.00	-2000.000	2.42	-2000.00
	2	468.5	1918.0	7.5	173.88	.03	.20	-2000.00	-2000.000	1.43	-2000.00
	3	126.2	1030.0	7.2	150.42	.10	.20	-2000.00	-2000.000	1.42	-2000.00
	4	43.1	587.0	7.9	311.57	.01	.10	-2000.00	-2000.000	2.23	-2000.00
	5	44.2	904.0	9.3	364.44	.01	.10	-2000.00	-2000.000	4.88	-2000.00
11170	1	617.2	1938.0	6.2	159.65	.01	.20	-2000.00	-2000.000	1.22	-2000.00
	2	123.6	1164.0	5.7	144.52	.01	.20	-2000.00	-2000.000	1.09	-2000.00
	3	36.2	679.0	5.9	138.91	.03	.20	-2000.00	-2000.000	.94	-2000.00
	4	32.8	1030.0	7.9	161.95	.10	.20	-2000.00	-2000.000	1.13	-2000.00
	5	22.7	1068.0	9.0	343.49	.10	.10	-2000.00	-2000.000	5.77	-2000.00
11195	1	294.7	462.0	3.7	70.69	.03	.30	-2000.00	-2000.000	2.54	-2000.00
	2	70.2	330.5	4.6	119.26	.01	.20	-2000.00	-2000.000	.87	-2000.00
	3	55.7	523.0	6.0	140.49	.03	.20	-2000.00	-2000.000	1.74	-2000.00
	4	36.7	575.0	8.1	169.18	.10	.20	-2000.00	-2000.000	1.62	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	39.8	936.0	9.0	202.56	.03	.20	-2000.00	-2000.000	1.88	-2000.00
11220	1	449.1	783.0	4.2	66.33	.10	.30	-2000.00	-2000.000	2.41	-2000.00
	2	212.6	1112.0	5.4	138.79	.01	.20	-2000.00	-2000.000	1.24	-2000.00
	3	112.1	1170.0	7.1	162.32	.03	.20	-2000.00	-2000.000	.88	-2000.00
	4	108.7	1890.0	7.9	196.91	.01	.20	-2000.00	-2000.000	1.12	-2000.00
	5	104.9	2740.0	9.8	201.54	.10	.20	-2000.00	-2000.000	1.35	-2000.00
11246	1	362.7	669.0	3.7	71.76	.03	.30	-2000.00	-2000.000	2.02	-2000.00
	2	159.8	885.0	5.6	145.21	.01	.20	-2000.00	-2000.000	1.20	-2000.00
	3	144.0	1590.0	6.6	168.27	.01	.20	-2000.00	-2000.000	.96	-2000.00
	4	127.0	2340.0	8.5	192.34	.03	.20	-2000.00	-2000.000	1.21	-2000.00
	5	120.4	3330.0	10.8	220.64	.10	.20	-2000.00	-2000.000	1.13	-2000.00
11270	1	256.5	447.0	4.2	111.86	.01	.20	-2000.00	-2000.000	1.88	-2000.00
	2	202.1	1057.0	5.6	144.57	.01	.20	-2000.00	-2000.000	1.61	-2000.00
	3	165.0	1720.0	7.7	174.85	.03	.20	-2000.00	-2000.000	1.51	-2000.00
	4	141.2	2460.0	10.3	393.03	.01	.10	-2000.00	-2000.000	1.75	-2000.00
	5	85.3	2232.0	12.1	443.07	30.00	.10	-2000.00	-2000.000	8.84	-2000.00
11295	1	221.6	770.0	3.8	94.59	.01	.20	-2000.00	-2000.000	4.01	-2000.00
	2	135.8	1420.0	5.7	137.34	.03	.20	-2000.00	-2000.000	2.04	-2000.00
	3	100.2	2000.0	8.9	200.77	.03	.20	-2000.00	-2000.000	1.24	-2000.00
	4	55.1	1920.0	11.2	374.56	.30	.10	-2000.00	-2000.000	1.93	-2000.00
	5	28.3	1470.0	11.4	393.57	.10	.10	-2000.00	-2000.000	2.22	-2000.00
11320	1	588.0	971.0	4.3	69.19	.10	.30	-2000.00	-2000.000	2.12	-2000.00
	2	307.9	1526.0	7.4	170.40	.03	.20	-2000.00	-2000.000	1.15	-2000.00
	3	143.8	1420.0	9.7	368.64	.01	.10	-2000.00	-2000.000	1.07	-2000.00
	4	68.7	1135.0	10.6	396.30	.01	.10	-2000.00	-2000.000	.91	-2000.00
	5	23.8	589.0	10.7	398.97	.01	.10	-2000.00	-2000.000	1.29	-2000.00
11342	1	559.6	1171.0	5.6	89.46	.10	.30	-2000.00	-2000.000	1.47	-2000.00
	2	170.8	1072.0	8.5	176.00	.10	.20	-2000.00	-2000.000	1.03	-2000.00
	3	72.8	912.0	9.8	369.90	.01	.10	-2000.00	-2000.000	.75	-2000.00
	4	24.1	504.0	10.2	381.60	.01	.10	-2000.00	-2000.000	1.07	-2000.00
	5	16.9	530.0	9.2	189.96	.10	.20	-2000.00	-2000.000	1.55	-2000.00
11365	1	527.8	1104.0	5.8	133.57	.03	.20	-2000.00	-2000.000	1.36	-2000.00
	2	124.4	781.0	8.0	166.05	.10	.20	-2000.00	-2000.000	1.07	-2000.00
	3	36.6	458.0	8.4	326.16	.01	.10	-2000.00	-2000.000	1.20	-2000.00
	4	23.5	492.0	8.2	315.75	.01	.10	-2000.00	-2000.000	1.21	-2000.00
	5	17.7	554.0	8.6	330.15	.01	.10	-2000.00	-2000.000	1.46	-2000.00
11388	1	444.4	930.0	5.0	98.78	.03	.30	-2000.00	-2000.000	3.75	-2000.00
	2	90.3	566.8	6.4	146.05	.03	.20	-2000.00	-2000.000	4.28	-2000.00
	3	49.1	615.0	5.8	135.19	.03	.20	-2000.00	-2000.000	2.88	-2000.00
	4	32.8	687.0	6.5	166.00	.01	.20	-2000.00	-2000.000	2.35	-2000.00
	5	34.6	1085.0	7.2	190.88	.01	.20	-2000.00	-2000.000	2.95	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
11415	1	376.9	622.0	4.7	122.14	.01	.20	-2000.00	-2000.000	1.56	-2000.00
	2	155.4	770.0	4.5	117.53	.01	.20	-2000.00	-2000.000	1.48	-2000.00
	3	85.4	844.0	5.0	129.07	.01	.20	-2000.00	-2000.000	1.46	-2000.00
	4	80.2	1325.0	6.1	142.54	.03	.20	-2000.00	-2000.000	1.49	-2000.00
	5	40.9	1013.0	5.8	210.11	100.00	.10	-2000.00	-2000.000	3.27	-2000.00
11435	1	434.1	681.0	3.8	99.51	.01	.20	-2000.00	-2000.000	1.73	-2000.00
	2	176.6	831.0	4.1	65.36	.10	.30	-2000.00	-2000.000	1.99	-2000.00
	3	141.2	1320.0	5.1	131.06	.01	.20	-2000.00	-2000.000	1.19	-2000.00
	4	66.1	1037.0	4.3	109.07	.01	.20	-2000.00	-2000.000	1.45	-2000.00
	5	60.7	1428.0	7.9	189.27	.03	.20	-2000.00	-2000.000	5.46	-2000.00
11460	1	281.5	589.0	4.3	107.06	.01	.20	-2000.00	-2000.000	3.80	-2000.00
	2	170.1	1068.0	3.8	94.77	.01	.30	-2000.00	-2000.000	1.55	-2000.00
	3	91.0	1140.0	4.5	102.19	.03	.20	-2000.00	-2000.000	2.19	-2000.00
	4	62.9	1316.0	7.1	117.55	.10	.30	-2000.00	-2000.000	3.33	-2000.00
	5	58.6	1840.0	10.4	264.63	.01	.20	-2000.00	-2000.000	2.32	-2000.00
11480	1	483.5	2160.0	4.1	80.80	.03	.30	-2000.00	-2000.000	1.81	-2000.00
	2	122.7	1650.0	4.1	78.41	.03	.30	-2000.00	-2000.000	2.50	-2000.00
	3	67.3	1800.0	6.2	147.85	.01	.30	-2000.00	-2000.000	1.40	-2000.00
	4	53.5	2400.0	9.1	144.51	.10	.30	-2000.00	-2000.000	2.19	-2000.00
	5	28.3	1900.0	7.7	262.88	3.00	.10	-2000.00	-2000.000	3.38	-2000.00
11505	1	624.6	1634.0	4.3	83.90	.03	.30	-2000.00	-2000.000	1.95	-2000.00
	2	152.0	1193.0	7.3	178.12	.01	.30	-2000.00	-2000.000	8.85	-2000.00
	3	152.6	2390.0	6.6	72.98	.30	.40	-2000.00	-2000.000	6.70	-2000.00
	4	60.3	1577.0	6.0	139.98	.03	.20	-2000.00	-2000.000	1.97	-2000.00
11528	1	231.6	1450.0	6.8	163.60	.01	.30	-2000.00	-2000.000	1.64	-2000.00
	2	105.8	1990.0	8.2	156.57	.03	.30	-2000.00	-2000.000	2.32	-2000.00
	3	46.3	1740.0	5.9	236.51	.01	.10	-2000.00	-2000.000	2.62	-2000.00
11551	1	194.1	2030.0	5.8	243.21	.01	.50	-2000.00	-2000.000	158.36	-2000.00
	2	66.8	2099.0	4.3	67.19	.10	.30	-2000.00	-2000.000	4.12	-2000.00
11575	1	873.4	2742.0	8.7	166.98	.03	.30	-2000.00	-2000.000	1.45	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 504

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	591.1	232.0	3.6	150.40	.01	.10	-2000.00	-2000.000	1.49	-2000.00
	2	144.6	170.0	2.7	58.03	.10	.20	-2000.00	-2000.000	1.89	-2000.00
	3	70.4	165.0	2.1	48.93	.03	.20	-2000.00	-2000.000	2.35	-2000.00
	4	50.8	199.0	2.7	55.68	.30	.20	-2000.00	-2000.000	2.84	-2000.00
	5	21.2	125.0	2.1	23.67	.30	.40	-2000.00	-2000.000	3.17	-2000.00
10850	1	282.9	123.0	1.9	42.27	.10	.20	-2000.00	-2000.000	2.32	-2000.00
	2	104.3	136.0	2.0	45.03	.10	.20	-2000.00	-2000.000	2.69	-2000.00
	3	65.7	171.0	2.9	111.55	1.00	.10	-2000.00	-2000.000	1.69	-2000.00
	4	23.6	102.0	2.4	56.62	.03	.20	-2000.00	-2000.000	2.14	-2000.00
	5	42.5	278.0	1.3	35.80	100.00	.20	-2000.00	-2000.000	9.28	-2000.00
10875	1	306.5	137.0	1.9	30.51	.10	.30	-2000.00	-2000.000	2.12	-2000.00
	2	124.8	167.0	3.2	123.40	1.00	.10	-2000.00	-2000.000	1.31	-2000.00
	3	37.4	100.0	3.2	125.55	100.00	.10	-2000.00	-2000.000	1.05	-2000.00
	4	57.8	259.0	2.6	35.67	10.00	.30	-2000.00	-2000.000	2.72	-2000.00
	5	33.0	221.0	1.8	21.34	100.00	.40	-2000.00	-2000.000	37.71	-2000.00
10900	1	353.9	146.0	3.0	69.80	.03	.20	-2000.00	-2000.000	3.43	-2000.00
	2	73.4	91.0	3.2	45.26	.30	.30	-2000.00	-2000.000	1.72	-2000.00
	3	95.3	235.0	2.4	26.80	.30	.40	-2000.00	-2000.000	3.20	-2000.00
	4	50.5	208.0	1.6	23.56	.10	.40	-2000.00	-2000.000	6.27	-2000.00
	5	57.0	353.0	-2.7	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10925	1	147.1	69.0	3.4	72.64	.10	.20	-2000.00	-2000.000	.94	-2000.00
	2	141.3	201.0	3.3	46.65	.30	.30	-2000.00	-2000.000	.94	-2000.00
	3	67.0	190.0	2.6	28.88	.30	.40	-2000.00	-2000.000	1.51	-2000.00
	4	67.4	320.0	.3	25.54	100.00	.60	-2000.00	-2000.000	56.87	-2000.00
	5	50.2	358.0	2.3	44.32	.03	.30	-2000.00	-2000.000	2.17	-2000.00
10950	1	528.4	276.0	4.8	96.81	.30	.20	-2000.00	-2000.000	1.10	-2000.00
	2	160.2	251.0	4.5	104.52	.03	.20	-2000.00	-2000.000	1.04	-2000.00
	3	122.1	380.0	2.0	19.96	.30	.40	-2000.00	-2000.000	4.64	-2000.00
	4	71.4	373.0	3.1	33.76	.30	.40	-2000.00	-2000.000	2.58	-2000.00
	5	100.8	790.0	5.1	129.96	.01	.20	-2000.00	-2000.000	1.58	-2000.00
10973	1	313.2	196.0	5.0	107.29	.10	.20	-2000.00	-2000.000	1.75	-2000.00
	2	175.2	330.0	2.7	70.23	.01	.20	-2000.00	-2000.000	1.81	-2000.00
	3	89.8	337.0	3.5	146.36	.01	.10	-2000.00	-2000.000	1.72	-2000.00
	4	110.4	690.0	5.7	210.23	1.00	.10	-2000.00	-2000.000	1.55	-2000.00
	5	76.5	720.0	10.8	364.97	1.00	.10	-2000.00	-2000.000	1.86	-2000.00
10996	1	931.0	487.0	3.5	90.31	.01	.20	-2000.00	-2000.000	1.50	-2000.00
	2	291.3	457.0	3.7	95.70	.01	.20	-2000.00	-2000.000	1.52	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	273.5	850.0	5.0	115.89	.03	.20	-2000.00	-2000.000	1.66	-2000.00
	4	156.5	810.0	9.8	220.22	.03	.20	-2000.00	-2000.000	1.14	-2000.00
	5	104.9	820.0	11.4	251.80	.03	.20	-2000.00	-2000.000	1.53	-2000.00
11022	1	837.8	453.0	5.5	141.57	.01	.20	-2000.00	-2000.000	1.53	-2000.00
	2	494.1	802.0	5.2	121.83	.03	.20	-2000.00	-2000.000	1.03	-2000.00
	3	228.5	740.0	9.8	201.99	.10	.20	-2000.00	-2000.000	.91	-2000.00
	4	139.4	750.0	11.5	233.44	.10	.20	-2000.00	-2000.000	1.36	-2000.00
	5	86.0	698.0	12.0	440.73	.01	.10	-2000.00	-2000.000	1.25	-2000.00
11047	1	2349.0	4090.0	12.7	313.00	.01	.20	-2000.00	-2000.000	1.48	-2000.00
	2	290.5	1520.0	14.7	292.88	.10	.20	-2000.00	-2000.000	1.24	-2000.00
	3	93.9	980.0	13.9	480.52	.03	.10	-2000.00	-2000.000	2.19	-2000.00
	4	44.6	778.0	13.7	439.83	1.00	.10	-2000.00	-2000.000	3.96	-2000.00
	5	26.3	689.0	13.2	241.40	30.00	.20	-2000.00	-2000.000	5.82	-2000.00
11072	1	4356.0	7590.0	14.1	307.83	.03	.20	-2000.00	-2000.000	1.40	-2000.00
	2	556.3	2911.0	16.9	330.30	.10	.20	-2000.00	-2000.000	.83	-2000.00
	3	141.1	1470.0	15.1	298.34	.10	.20	-2000.00	-2000.000	1.06	-2000.00
	4	71.3	1242.0	13.5	486.14	.01	.10	-2000.00	-2000.000	1.26	-2000.00
	5	22.8	596.0	12.6	411.40	1.00	.10	-2000.00	-2000.000	1.72	-2000.00
11096	1	1025.0	3500.0	17.9	382.45	.03	.20	-2000.00	-2000.000	1.11	-2000.00
	2	195.0	2040.0	16.5	354.90	.03	.20	-2000.00	-2000.000	.86	-2000.00
	3	87.1	1810.0	14.1	282.42	.10	.20	-2000.00	-2000.000	1.10	-2000.00
	4	23.3	810.0	12.9	469.05	.01	.10	-2000.00	-2000.000	1.09	-2000.00
	5	9.4	494.0	13.0	287.56	.03	.20	-2000.00	-2000.000	3.30	-2000.00
11121	1	2229.0	4110.0	14.8	324.70	.03	.20	-2000.00	-2000.000	1.25	-2000.00
	2	704.0	3900.0	13.7	302.64	.03	.20	-2000.00	-2000.000	1.05	-2000.00
	3	145.9	1610.0	12.3	248.83	.10	.20	-2000.00	-2000.000	1.22	-2000.00
	4	50.5	932.0	12.6	463.41	.01	.10	-2000.00	-2000.000	1.65	-2000.00
	5	16.5	458.0	11.4	239.57	.10	.20	-2000.00	-2000.000	3.34	-2000.00
11147	1	2256.0	5900.0	10.7	267.43	.01	.20	-2000.00	-2000.000	1.18	-2000.00
	2	318.3	2498.0	9.1	206.08	.03	.20	-2000.00	-2000.000	1.00	-2000.00
	3	94.9	1487.0	9.4	192.27	.10	.20	-2000.00	-2000.000	1.14	-2000.00
	4	29.3	766.0	9.0	189.28	.10	.20	-2000.00	-2000.000	2.37	-2000.00
	5	42.7	1674.0	11.9	420.35	.03	.10	-2000.00	-2000.000	.92	-2000.00
11171	1	1293.0	2380.0	7.3	186.74	.01	.20	-2000.00	-2000.000	1.08	-2000.00
	2	328.2	1818.0	7.3	167.17	.03	.20	-2000.00	-2000.000	1.29	-2000.00
	3	94.9	1049.0	6.7	139.91	.10	.20	-2000.00	-2000.000	1.46	-2000.00
	4	131.2	2420.0	9.3	192.92	.10	.20	-2000.00	-2000.000	1.26	-2000.00
	5	77.7	2153.0	10.1	381.42	.01	.10	-2000.00	-2000.000	1.71	-2000.00
11197	1	719.8	1614.0	5.7	132.60	.03	.20	-2000.00	-2000.000	1.49	-2000.00
	2	174.6	1174.0	5.1	119.94	.03	.20	-2000.00	-2000.000	1.61	-2000.00
	3	228.1	3060.0	7.5	157.59	.10	.20	-2000.00	-2000.000	.97	-2000.00
	4	113.1	2530.0	8.4	325.57	.01	.10	-2000.00	-2000.000	1.55	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	87.9	2958.0	12.1	417.95	.10	.10	-2000.00	-2000.000	1.23	-2000.00
11222	1	840.8	1650.0	4.8	123.59	.01	.20	-2000.00	-2000.000	.99	-2000.00
	2	620.7	3654.0	7.2	165.41	.03	.20	-2000.00	-2000.000	1.39	-2000.00
	3	264.8	3110.0	7.1	149.08	.10	.20	-2000.00	-2000.000	1.44	-2000.00
	4	153.1	3000.0	11.0	365.95	100.00	.10	-2000.00	-2000.000	2.42	-2000.00
	5	30.1	886.0	11.1	215.76	10.00	.20	-2000.00	-2000.000	4.44	-2000.00
11248	1	1956.0	4380.0	7.3	184.66	.01	.20	-2000.00	-2000.000	1.17	-2000.00
	2	478.2	3217.0	6.6	139.56	.10	.20	-2000.00	-2000.000	1.45	-2000.00
	3	206.0	2760.0	9.4	333.89	.10	.10	-2000.00	-2000.000	.94	-2000.00
	4	35.0	784.0	11.0	359.06	100.00	.10	-2000.00	-2000.000	1.61	-2000.00
	5	22.3	750.0	13.0	228.25	10.00	.20	-2000.00	-2000.000	3.85	-2000.00
11273	1	887.9	1742.0	5.4	126.43	.03	.20	-2000.00	-2000.000	1.47	-2000.00
	2	294.8	1735.0	7.8	163.75	.10	.20	-2000.00	-2000.000	.87	-2000.00
	3	45.7	536.0	8.6	315.88	.10	.10	-2000.00	-2000.000	1.18	-2000.00
	4	28.2	554.0	9.8	208.42	.10	.20	-2000.00	-2000.000	1.88	-2000.00
	5	43.3	1273.0	11.3	232.64	.10	.20	-2000.00	-2000.000	1.72	-2000.00
11297	1	1120.0	2190.0	8.2	170.72	.10	.20	-2000.00	-2000.000	1.12	-2000.00
	2	89.1	524.5	8.3	112.73	.30	.30	-2000.00	-2000.000	.90	-2000.00
	3	38.8	456.0	7.5	70.44	.30	.50	-2000.00	-2000.000	2.63	-2000.00
	4	57.0	1118.0	8.7	73.00	.30	.60	-2000.00	-2000.000	3.64	-2000.00
	5	51.2	1506.0	9.6	191.74	.03	.30	-2000.00	-2000.000	5.98	-2000.00
11322	1	894.3	1404.0	8.0	166.96	.10	.20	-2000.00	-2000.000	1.85	-2000.00
	2	98.8	465.2	6.9	144.60	.10	.20	-2000.00	-2000.000	1.27	-2000.00
	3	99.2	932.0	9.5	194.48	.10	.20	-2000.00	-2000.000	1.07	-2000.00
	4	80.8	1268.0	11.2	226.97	.10	.20	-2000.00	-2000.000	.99	-2000.00
	5	41.9	986.0	12.5	249.04	.10	.20	-2000.00	-2000.000	1.54	-2000.00
11346	1	482.1	1376.0	7.0	110.46	.10	.30	-2000.00	-2000.000	1.62	-2000.00
	2	164.9	1412.0	7.1	134.97	.03	.30	-2000.00	-2000.000	1.44	-2000.00
	3	98.4	1681.0	8.0	73.84	.30	.50	-2000.00	-2000.000	2.89	-2000.00
	4	41.6	1188.0	9.1	72.12	.30	.60	-2000.00	-2000.000	4.23	-2000.00
	5	31.0	1327.0	8.7	79.05	.30	.60	-2000.00	-2000.000	5.64	-2000.00
11372	1	854.5	1412.0	6.3	160.18	.01	.20	-2000.00	-2000.000	1.02	-2000.00
	2	271.1	1344.0	7.9	198.01	.01	.20	-2000.00	-2000.000	.96	-2000.00
	3	99.8	987.0	9.5	212.61	.03	.20	-2000.00	-2000.000	.72	-2000.00
	4	69.6	1149.0	10.9	242.51	.03	.20	-2000.00	-2000.000	1.56	-2000.00
	5	19.0	470.0	11.6	227.02	.10	.20	-2000.00	-2000.000	6.77	-2000.00
11397	1	514.4	950.0	5.3	123.94	.03	.20	-2000.00	-2000.000	1.37	-2000.00
	2	135.6	751.0	7.8	177.83	.03	.20	-2000.00	-2000.000	1.13	-2000.00
	3	86.6	957.0	9.3	210.72	.03	.20	-2000.00	-2000.000	1.06	-2000.00
	4	21.9	405.0	9.7	375.69	.01	.10	-2000.00	-2000.000	1.93	-2000.00
	5	18.2	503.0	10.1	379.98	.03	.10	-2000.00	-2000.000	3.23	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
11422	1	262.3	686.0	5.8	133.44	.03	.20	-2000.00	-2000.000	1.47	-2000.00
	2	112.9	886.0	7.6	172.53	.03	.20	-2000.00	-2000.000	1.55	-2000.00
	3	38.4	601.0	8.4	325.09	.01	.10	-2000.00	-2000.000	1.61	-2000.00
	4	21.2	554.0	9.1	340.87	.01	.10	-2000.00	-2000.000	3.61	-2000.00
	5	13.4	525.0	9.9	354.27	.10	.10	-2000.00	-2000.000	4.84	-2000.00
11447	1	569.6	894.0	5.5	141.90	.01	.20	-2000.00	-2000.000	1.75	-2000.00
	2	145.3	684.0	6.2	131.86	.10	.20	-2000.00	-2000.000	1.65	-2000.00
	3	67.7	636.0	6.7	265.86	.01	.10	-2000.00	-2000.000	2.27	-2000.00
	4	37.7	591.0	8.4	297.42	1.00	.10	-2000.00	-2000.000	2.42	-2000.00
	5	58.8	1385.0	9.8	340.15	.30	.10	-2000.00	-2000.000	2.61	-2000.00
11472	1	380.7	747.0	5.0	129.45	.01	.20	-2000.00	-2000.000	1.26	-2000.00
	2	109.2	642.0	4.8	76.39	.10	.30	-2000.00	-2000.000	2.01	-2000.00
	3	49.9	586.0	5.9	92.76	.10	.30	-2000.00	-2000.000	1.64	-2000.00
	4	72.0	1412.0	7.0	110.97	.10	.30	-2000.00	-2000.000	1.85	-2000.00
	5	48.2	1418.0	9.0	69.61	.30	.60	-2000.00	-2000.000	9.26	-2000.00
11497	1	444.3	871.0	4.3	69.85	.10	.30	-2000.00	-2000.000	2.14	-2000.00
	2	111.8	658.0	4.9	128.55	.01	.20	-2000.00	-2000.000	2.24	-2000.00
	3	130.4	1530.0	6.0	154.02	.01	.20	-2000.00	-2000.000	1.69	-2000.00
	4	76.8	1506.0	7.2	162.03	.03	.20	-2000.00	-2000.000	3.25	-2000.00
11520	1	135.1	424.0	4.2	108.36	.01	.20	-2000.00	-2000.000	2.70	-2000.00
	2	118.2	1113.0	5.4	139.75	.01	.20	-2000.00	-2000.000	1.86	-2000.00
	3	62.2	1168.0	6.3	159.54	.01	.20	-2000.00	-2000.000	2.06	-2000.00
11542	1	283.1	980.0	4.0	64.84	.10	.30	-2000.00	-2000.000	1.95	-2000.00
	2	102.7	1070.0	5.1	133.21	.01	.20	-2000.00	-2000.000	4.64	-2000.00
11571	1	155.5	810.0	3.4	66.70	.03	.30	-2000.00	-2000.000	2.89	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 494

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10825	1	358.9	154.0	3.4	140.52	.01	.10	-2000.00	-2000.000	1.33	-2000.00
	2	100.0	129.0	3.4	135.10	.10	.10	-2000.00	-2000.000	1.55	-2000.00
	3	72.8	187.0	2.2	50.32	.03	.20	-2000.00	-2000.000	1.85	-2000.00
	4	18.5	79.0	2.3	54.37	100.00	.20	-2000.00	-2000.000	3.76	-2000.00
	5	19.7	127.0	3.3	47.24	30.00	.30	-2000.00	-2000.000	6.01	-2000.00
10850	1	217.6	113.0	3.2	44.40	.30	.30	-2000.00	-2000.000	2.80	-2000.00
	2	113.2	177.0	2.0	87.21	.10	.10	-2000.00	-2000.000	5.69	-2000.00
	3	29.2	91.0	1.7	33.43	.03	.30	-2000.00	-2000.000	4.31	-2000.00
	4	24.6	128.0	2.2	25.67	.30	.40	-2000.00	-2000.000	4.86	-2000.00
	5	11.6	90.0	3.5	18.64	.30	.70	-2000.00	-2000.000	24.25	-2000.00
10875	1	355.1	174.0	3.7	146.61	.03	.10	-2000.00	-2000.000	1.35	-2000.00
	2	62.7	92.3	2.7	62.70	.03	.20	-2000.00	-2000.000	1.33	-2000.00
	3	43.9	129.0	3.1	62.71	.30	.20	-2000.00	-2000.000	1.97	-2000.00
	4	18.3	89.0	3.2	78.21	100.00	.30	-2000.00	-2000.000	17.79	-2000.00
	5	26.4	194.0	3.2	23.38	.30	.50	-2000.00	-2000.000	27.97	-2000.00
10900	1	183.3	72.0	3.3	136.93	.01	.10	-2000.00	-2000.000	1.13	-2000.00
	2	98.7	117.6	3.5	48.47	.30	.30	-2000.00	-2000.000	1.15	-2000.00
	3	37.5	89.0	4.4	41.85	1.00	.40	-2000.00	-2000.000	.78	-2000.00
	4	45.8	182.0	3.4	46.81	.30	.30	-2000.00	-2000.000	3.19	-2000.00
	5	61.5	366.0	1.7	18.29	.30	.40	-2000.00	-2000.000	9.75	-2000.00
10925	1	489.9	139.8	3.3	69.92	.10	.20	-2000.00	-2000.000	1.16	-2000.00
	2	122.3	104.7	4.5	86.95	1.00	.20	-2000.00	-2000.000	.70	-2000.00
	3	113.2	193.0	4.3	91.15	.10	.20	-2000.00	-2000.000	1.14	-2000.00
	4	127.0	362.0	2.7	37.44	.30	.30	-2000.00	-2000.000	2.13	-2000.00
	5	63.1	270.0	.7	21.89	100.00	.30	-2000.00	-2000.000	19.38	-2000.00
10950	1	292.2	96.0	4.5	42.45	1.00	.40	-2000.00	-2000.000	1.57	-2000.00
	2	187.8	186.0	5.1	207.93	.01	.10	-2000.00	-2000.000	1.31	-2000.00
	3	170.4	330.0	3.8	141.03	.30	.10	-2000.00	-2000.000	1.69	-2000.00
	4	78.4	259.0	1.6	18.74	.30	.40	-2000.00	-2000.000	8.04	-2000.00
	5	52.2	258.0	1.2	30.30	100.00	.20	-2000.00	-2000.000	9.53	-2000.00
10975	1	347.5	218.0	5.8	151.58	.01	.20	-2000.00	-2000.000	2.63	-2000.00
	2	177.9	335.0	4.9	127.43	.01	.20	-2000.00	-2000.000	1.10	-2000.00
	3	83.6	314.0	3.2	83.10	.01	.20	-2000.00	-2000.000	1.28	-2000.00
	4	44.6	279.0	1.9	37.36	.03	.40	-2000.00	-2000.000	3.38	-2000.00
	5	22.9	215.0	.9	33.01	.01	.20	-2000.00	-2000.000	20.80	-2000.00
11000	1	332.6	237.0	5.4	222.55	.10	.10	-2000.00	-2000.000	7.93	-2000.00
	2	124.4	266.0	3.9	76.64	.03	.30	-2000.00	-2000.000	1.62	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	53.8	229.0	2.5	57.75	.01	.30	-2000.00	-2000.000	3.74	-2000.00
	4	24.0	171.0	4.1	61.52	30.00	.30	-2000.00	-2000.000	7.14	-2000.00
	5	68.6	734.0	6.1	119.64	10.00	.20	-2000.00	-2000.000	4.22	-2000.00
11025	1	1022.0	660.0	5.2	101.02	.03	.30	-2000.00	-2000.000	2.94	-2000.00
	2	171.2	335.0	2.9	72.60	.01	.30	-2000.00	-2000.000	3.54	-2000.00
	3	60.1	235.0	-.4	29.15	.01	.30	-2000.00	-2000.000	116.49	-2000.00
	4	122.0	790.0	5.3	212.83	.01	.10	-2000.00	-2000.000	5.75	-2000.00
	5	101.2	990.0	7.5	116.43	.10	.30	-2000.00	-2000.000	1.81	-2000.00
11050	1	667.6	381.0	2.9	58.15	.03	.30	-2000.00	-2000.000	3.51	-2000.00
	2	165.8	283.0	1.7	49.12	.01	.40	-2000.00	-2000.000	2.55	-2000.00
	3	273.0	930.0	3.7	89.65	.01	.30	-2000.00	-2000.000	2.16	-2000.00
	4	201.2	1140.0	7.3	167.98	.03	.20	-2000.00	-2000.000	1.88	-2000.00
	5	91.6	784.0	11.5	256.58	.03	.20	-2000.00	-2000.000	1.39	-2000.00
11075	1	279.9	219.0	1.7	53.20	.01	.40	-2000.00	-2000.000	5.74	-2000.00
	2	360.3	848.0	3.4	87.47	.01	.30	-2000.00	-2000.000	5.53	-2000.00
	3	221.8	1040.0	7.2	189.01	.01	.20	-2000.00	-2000.000	3.38	-2000.00
	4	87.9	690.0	11.5	288.45	.01	.20	-2000.00	-2000.000	1.91	-2000.00
	5	92.8	1093.0	13.3	296.83	.03	.20	-2000.00	-2000.000	1.88	-2000.00
11100	1	1658.0	1150.0	3.6	88.50	.01	.30	-2000.00	-2000.000	3.54	-2000.00
	2	506.8	1060.0	7.5	120.13	.10	.30	-2000.00	-2000.000	2.65	-2000.00
	3	158.2	660.0	11.6	288.08	.01	.20	-2000.00	-2000.000	2.65	-2000.00
	4	147.7	1030.0	14.1	310.17	.03	.20	-2000.00	-2000.000	1.60	-2000.00
	5	76.4	799.0	15.7	309.69	.10	.20	-2000.00	-2000.000	1.81	-2000.00
11125	1	1128.0	800.0	8.3	215.58	.01	.20	-2000.00	-2000.000	3.14	-2000.00
	2	239.8	513.0	13.8	336.55	.01	.20	-2000.00	-2000.000	1.96	-2000.00
	3	195.6	830.0	14.4	317.07	.03	.20	-2000.00	-2000.000	2.32	-2000.00
	4	89.5	638.0	16.6	325.83	.10	.20	-2000.00	-2000.000	1.83	-2000.00
	5	39.4	421.0	15.5	305.42	.10	.20	-2000.00	-2000.000	1.67	-2000.00
11150	1	1097.0	3130.0	17.7	428.40	.01	.20	-2000.00	-2000.000	2.37	-2000.00
	2	364.7	3123.0	20.5	484.52	.01	.20	-2000.00	-2000.000	2.07	-2000.00
	3	108.1	1840.0	21.7	457.34	.03	.20	-2000.00	-2000.000	2.49	-2000.00
	4	33.1	945.0	20.8	477.31	.01	.20	-2000.00	-2000.000	1.85	-2000.00
	5	15.0	640.0	18.7	625.58	.01	.10	-2000.00	-2000.000	2.33	-2000.00
11175	1	3454.0	7740.0	16.0	390.68	.01	.20	-2000.00	-2000.000	2.51	-2000.00
	2	648.0	4360.0	19.8	469.02	.01	.20	-2000.00	-2000.000	1.65	-2000.00
	3	196.5	2630.0	17.8	434.24	.01	.20	-2000.00	-2000.000	3.34	-2000.00
	4	49.1	1100.0	18.5	626.62	.01	.10	-2000.00	-2000.000	2.04	-2000.00
	5	12.0	404.0	17.7	604.30	.01	.10	-2000.00	-2000.000	3.80	-2000.00
11200	1	3543.0	7940.0	13.1	327.72	.01	.20	-2000.00	-2000.000	2.91	-2000.00
	2	797.0	5362.0	14.8	365.13	.01	.20	-2000.00	-2000.000	2.43	-2000.00
	3	131.3	1760.0	11.9	188.18	.10	.30	-2000.00	-2000.000	2.98	-2000.00
	4	29.9	670.0	17.8	319.06	100.00	.20	-2000.00	-2000.000	6.43	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	16.4	551.0	11.7	98.70	.30	.60	-2000.00	-2000.000	3.75	-2000.00
11225	1	3944.0	15400.0	11.7	284.52	.01	.30	-2000.00	-2000.000	4.31	-2000.00
	2	354.4	4170.0	10.2	247.68	.01	.30	-2000.00	-2000.000	3.58	-2000.00
	3	48.9	1140.0	7.5	164.45	.01	.30	-2000.00	-2000.000	11.57	-2000.00
	4	28.4	1110.0	7.7	214.02	.03	.50	-2000.00	-2000.000	8.01	-2000.00
	5	13.5	790.0	13.9	351.66	.01	.20	-2000.00	-2000.000	4.46	-2000.00
11250	1	1838.0	4800.0	7.4	179.04	.01	.30	-2000.00	-2000.000	2.92	-2000.00
	2	183.9	1443.0	7.9	151.11	.03	.30	-2000.00	-2000.000	2.49	-2000.00
	3	83.3	1304.0	5.6	154.56	.01	.40	-2000.00	-2000.000	3.80	-2000.00
	4	45.3	1184.0	10.0	234.47	.03	.20	-2000.00	-2000.000	5.07	-2000.00
	5	20.3	796.0	13.2	290.06	.03	.20	-2000.00	-2000.000	3.00	-2000.00
11275	1	365.8	1044.0	5.0	104.50	.03	.30	-2000.00	-2000.000	5.64	-2000.00
	2	135.0	1156.0	6.5	174.20	.01	.40	-2000.00	-2000.000	4.79	-2000.00
	3	71.5	1222.0	8.5	163.75	.03	.30	-2000.00	-2000.000	3.59	-2000.00
	4	30.2	862.0	10.6	271.58	.01	.20	-2000.00	-2000.000	4.10	-2000.00
	5	36.9	1581.0	11.0	279.39	.01	.20	-2000.00	-2000.000	3.71	-2000.00
11300	1	571.9	1197.0	5.8	113.70	.03	.30	-2000.00	-2000.000	4.70	-2000.00
	2	218.9	1374.0	6.1	150.49	.01	.30	-2000.00	-2000.000	2.24	-2000.00
	3	82.1	1028.0	7.5	146.14	.03	.30	-2000.00	-2000.000	3.16	-2000.00
	4	86.9	1819.0	8.3	133.67	.10	.30	-2000.00	-2000.000	3.11	-2000.00
	5	88.6	2782.0	11.6	261.45	.03	.20	-2000.00	-2000.000	2.23	-2000.00
11325	1	467.4	1128.0	5.0	121.44	.01	.30	-2000.00	-2000.000	3.48	-2000.00
	2	128.3	929.0	7.1	171.63	.01	.30	-2000.00	-2000.000	3.07	-2000.00
	3	111.0	1600.0	6.9	136.05	.03	.30	-2000.00	-2000.000	4.92	-2000.00
	4	104.0	2510.0	9.6	181.78	.03	.30	-2000.00	-2000.000	2.26	-2000.00
	5	72.1	2610.0	12.5	311.24	.01	.20	-2000.00	-2000.000	2.35	-2000.00
11350	1	328.5	937.0	7.0	52.08	.30	.80	-2000.00	-2000.000	17.70	-2000.00
	2	163.6	1401.0	6.2	154.39	.01	.30	-2000.00	-2000.000	4.56	-2000.00
	3	128.4	2190.0	8.8	170.18	.03	.30	-2000.00	-2000.000	3.22	-2000.00
	4	86.2	2461.0	11.8	294.62	.01	.20	-2000.00	-2000.000	3.58	-2000.00
	5	37.1	1587.0	11.2	155.89	.10	.40	-2000.00	-2000.000	2.54	-2000.00
11375	1	597.2	1250.0	5.6	127.51	.01	.30	-2000.00	-2000.000	4.28	-2000.00
	2	278.2	1747.0	7.9	152.74	.03	.30	-2000.00	-2000.000	3.02	-2000.00
	3	171.2	2140.0	9.4	179.42	.03	.30	-2000.00	-2000.000	3.04	-2000.00
	4	68.6	1436.0	11.3	282.55	.01	.20	-2000.00	-2000.000	1.77	-2000.00
	5	49.6	1557.0	15.7	299.11	30.00	.20	-2000.00	-2000.000	7.22	-2000.00
11397	1	262.2	1020.0	7.0	140.67	.03	.40	-2000.00	-2000.000	4.59	-2000.00
	2	136.4	1600.0	10.0	242.82	.01	.30	-2000.00	-2000.000	3.47	-2000.00
	3	48.6	1140.0	9.7	239.61	.01	.30	-2000.00	-2000.000	4.49	-2000.00
	4	34.1	1330.0	13.4	254.11	.03	.30	-2000.00	-2000.000	4.08	-2000.00
	5	15.6	910.0	14.2	271.24	.03	.30	-2000.00	-2000.000	4.51	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
11421	1	666.0	1608.0	6.1	149.95	.01	.30	-2000.00	-2000.000	2.96	-2000.00
	2	154.5	1119.0	8.1	196.01	.01	.30	-2000.00	-2000.000	3.02	-2000.00
	3	89.1	1287.0	10.8	253.10	.01	.30	-2000.00	-2000.000	2.85	-2000.00
	4	37.7	910.0	12.8	444.04	.10	.10	-2000.00	-2000.000	5.20	-2000.00
	5	14.8	536.0	17.2	593.97	.01	.10	-2000.00	-2000.000	2.86	-2000.00
11447	1	493.4	1549.0	7.4	182.79	.01	.30	-2000.00	-2000.000	4.92	-2000.00
	2	160.5	1511.0	9.4	227.40	.01	.30	-2000.00	-2000.000	3.42	-2000.00
	3	53.6	1008.0	10.6	202.35	.03	.30	-2000.00	-2000.000	4.72	-2000.00
	4	20.6	648.0	11.8	226.12	.03	.40	-2000.00	-2000.000	1.39	-2000.00
	5	17.4	821.0	16.1	562.10	.01	.10	-2000.00	-2000.000	3.68	-2000.00
11472	1	726.0	1424.0	8.1	156.50	.03	.30	-2000.00	-2000.000	2.42	-2000.00
	2	188.7	1110.0	8.2	159.68	.03	.30	-2000.00	-2000.000	2.92	-2000.00
	3	64.4	756.0	14.3	309.26	.03	.20	-2000.00	-2000.000	1.64	-2000.00
	4	45.7	897.0	13.1	490.68	.01	.10	-2000.00	-2000.000	3.11	-2000.00
	5	22.0	648.0	12.9	416.04	.30	.10	-2000.00	-2000.000	4.36	-2000.00
11497	1	379.7	917.0	7.7	203.37	.01	.20	-2000.00	-2000.000	6.65	-2000.00
	2	87.1	631.4	9.9	81.63	.30	.70	-2000.00	-2000.000	5.82	-2000.00
	3	57.7	834.0	13.5	298.04	.03	.20	-2000.00	-2000.000	2.69	-2000.00
	4	24.3	586.0	9.6	251.72	.01	.20	-2000.00	-2000.000	8.43	-2000.00
11523	1	173.3	770.0	10.5	200.05	.03	.30	-2000.00	-2000.000	3.14	-2000.00
	2	78.9	1061.0	11.7	219.17	.03	.30	-2000.00	-2000.000	2.63	-2000.00
	3	24.8	660.0	6.3	198.86	.01	.40	-2000.00	-2000.000	6.05	-2000.00
11548	1	179.9	800.0	7.0	308.98	.10	.10	-2000.00	-2000.000	23.26	-2000.00
	2	43.8	589.0	8.8	172.44	.03	.30	-2000.00	-2000.000	3.61	-2000.00
11575	1	102.9	460.0	6.8	165.95	.01	.30	-2000.00	-2000.000	3.64	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1114

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters					Fit/IP	Fit/EM
					M-IP	TAU-IP	C-IP	M-EM	TAU-EM		
10025	1	380.6	113.8	3.1	40.70	.30	.30	-2000.00	-2000.000	5.38	-2000.00
	2	215.7	193.5	5.6	63.26	.30	.40	-2000.00	-2000.000	3.35	-2000.00
	3	181.8	325.0	6.4	236.05	.10	.10	-2000.00	-2000.000	5.85	-2000.00
	4	85.5	255.7	5.2	56.09	.30	.40	-2000.00	-2000.000	1.54	-2000.00
	5	47.2	211.5	4.9	195.14	30.00	.10	-2000.00	-2000.000	4.40	-2000.00
10050	1	1088.0	316.0	4.6	179.52	.10	.10	-2000.00	-2000.000	.83	-2000.00
	2	509.5	444.3	7.0	249.46	1.00	.10	-2000.00	-2000.000	.48	-2000.00
	3	196.5	342.0	5.8	113.38	.30	.20	-2000.00	-2000.000	2.23	-2000.00
	4	94.2	273.7	6.1	117.94	.30	.20	-2000.00	-2000.000	2.59	-2000.00
	5	66.8	291.1	4.9	63.33	.30	.30	-2000.00	-2000.000	5.57	-2000.00
10075	1	2390.0	701.0	6.5	235.58	1.00	.10	-2000.00	-2000.000	.97	-2000.00
	2	739.1	650.6	5.7	214.07	.10	.10	-2000.00	-2000.000	.94	-2000.00
	3	294.0	516.0	6.5	233.98	10.00	.10	-2000.00	-2000.000	1.36	-2000.00
	4	165.4	485.0	5.1	192.63	100.00	.10	-2000.00	-2000.000	3.13	-2000.00
	5	96.0	422.5	6.8	260.18	.03	.10	-2000.00	-2000.000	1.09	-2000.00
10100	1	2392.0	910.0	2.1	56.17	.01	.20	-2000.00	-2000.000	2.44	-2000.00
	2	604.6	694.0	4.1	88.25	.10	.20	-2000.00	-2000.000	1.64	-2000.00
	3	318.6	730.0	3.0	76.68	.01	.20	-2000.00	-2000.000	2.53	-2000.00
	4	164.5	620.0	5.3	112.14	.10	.20	-2000.00	-2000.000	1.54	-2000.00
	5	99.2	569.0	5.4	209.94	.03	.10	-2000.00	-2000.000	1.55	-2000.00
10125	1	2313.0	940.0	3.7	79.30	.10	.20	-2000.00	-2000.000	1.65	-2000.00
	2	861.6	1054.0	2.3	37.90	.10	.30	-2000.00	-2000.000	2.12	-2000.00
	3	412.4	1000.0	4.7	101.29	.10	.20	-2000.00	-2000.000	1.88	-2000.00
	4	206.4	840.0	4.9	199.36	.01	.10	-2000.00	-2000.000	1.43	-2000.00
	5	236.8	1440.0	3.5	74.21	.10	.20	-2000.00	-2000.000	1.81	-2000.00
10150	1	1415.0	740.0	2.1	56.14	.01	.20	-2000.00	-2000.000	2.10	-2000.00
	2	544.0	854.0	4.6	98.26	.10	.20	-2000.00	-2000.000	1.95	-2000.00
	3	308.8	960.0	5.2	211.69	.01	.10	-2000.00	-2000.000	1.63	-2000.00
	4	286.0	1490.0	3.6	77.37	.10	.20	-2000.00	-2000.000	1.38	-2000.00
	5	419.0	3280.0	6.3	161.48	.01	.20	-2000.00	-2000.000	1.43	-2000.00
10175	1	1348.0	580.0	3.0	82.39	.01	.20	-2000.00	-2000.000	3.53	-2000.00
	2	545.3	713.0	4.9	200.39	.01	.10	-2000.00	-2000.000	2.27	-2000.00
	3	494.9	1290.0	3.3	134.30	.10	.10	-2000.00	-2000.000	2.42	-2000.00
	4	686.5	2990.0	6.0	155.14	.01	.20	-2000.00	-2000.000	1.21	-2000.00
	5	250.2	1630.0	9.6	334.99	1.00	.10	-2000.00	-2000.000	1.50	-2000.00
10200	1	903.5	388.0	4.9	201.14	.01	.10	-2000.00	-2000.000	2.29	-2000.00
	2	733.4	946.0	3.6	152.06	.01	.10	-2000.00	-2000.000	1.77	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	969.6	2490.0	6.1	157.25	.01	.20	-2000.00	-2000.000	1.43	-2000.00
	4	322.8	1380.0	10.0	355.17	.10	.10	-2000.00	-2000.000	1.03	-2000.00
	5	278.5	1790.0	12.4	438.35	.03	.10	-2000.00	-2000.000	.93	-2000.00
10225	1	1515.0	640.0	1.8	41.48	.03	.20	-2000.00	-2000.000	5.51	-2000.00
	2	1508.0	1910.0	5.0	130.68	.01	.20	-2000.00	-2000.000	1.64	-2000.00
	3	452.4	1140.0	10.1	378.82	.01	.10	-2000.00	-2000.000	.90	-2000.00
	4	354.5	1500.0	12.3	423.39	.10	.10	-2000.00	-2000.000	1.16	-2000.00
	5	113.6	720.0	10.8	357.44	30.00	.10	-2000.00	-2000.000	1.29	-2000.00
10250	1	1827.0	1390.0	3.4	55.23	.10	.30	-2000.00	-2000.000	2.79	-2000.00
	2	425.8	978.0	9.6	366.61	.01	.10	-2000.00	-2000.000	1.09	-2000.00
	3	247.5	1130.0	12.0	415.70	.10	.10	-2000.00	-2000.000	1.16	-2000.00
	4	74.2	568.0	10.8	359.95	100.00	.10	-2000.00	-2000.000	2.72	-2000.00
10275	1	1561.0	1020.0	10.5	214.91	.10	.20	-2000.00	-2000.000	1.25	-2000.00
	2	577.4	1133.0	12.1	445.91	.01	.10	-2000.00	-2000.000	1.11	-2000.00
	3	138.4	540.0	11.2	368.82	30.00	.10	-2000.00	-2000.000	1.92	-2000.00
10300	1	2157.0	1650.0	11.3	252.76	.03	.20	-2000.00	-2000.000	1.54	-2000.00
	2	281.0	645.0	13.0	428.61	.30	.10	-2000.00	-2000.000	1.80	-2000.00
10325	1	297.3	405.0	14.8	259.75	10.00	.20	-2000.00	-2000.000	1.41	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1124

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	460.7	178.0	6.3	59.17	1.00	.40	-2000.00	-2000.000	1.24	-2000.00
	2	185.8	216.0	7.1	91.28	1.00	.30	-2000.00	-2000.000	2.71	-2000.00
	3	78.0	181.0	6.5	87.39	.30	.30	-2000.00	-2000.000	7.40	-2000.00
	4	58.5	226.0	6.6	223.53	3.00	.10	-2000.00	-2000.000	8.53	-2000.00
	5	37.3	216.0	5.3	32.84	1.00	.60	-2000.00	-2000.000	12.96	-2000.00
10050	1	634.3	255.0	4.5	96.46	.10	.20	-2000.00	-2000.000	1.20	-2000.00
	2	174.8	211.0	5.4	68.98	1.00	.30	-2000.00	-2000.000	1.74	-2000.00
	3	111.2	260.0	5.3	71.64	.30	.30	-2000.00	-2000.000	3.31	-2000.00
	4	64.0	257.0	4.6	35.27	.30	.60	-2000.00	-2000.000	7.81	-2000.00
	5	47.3	285.0	4.2	36.15	.30	.50	-2000.00	-2000.000	8.44	-2000.00
10075	1	1520.0	540.0	2.7	69.93	.01	.20	-2000.00	-2000.000	1.07	-2000.00
	2	635.0	687.0	3.1	81.92	.01	.20	-2000.00	-2000.000	1.41	-2000.00
	3	354.9	760.0	3.3	71.82	.10	.20	-2000.00	-2000.000	3.44	-2000.00
	4	169.8	610.0	3.3	83.48	.01	.20	-2000.00	-2000.000	2.82	-2000.00
	5	116.9	630.0	4.6	107.39	.03	.20	-2000.00	-2000.000	2.11	-2000.00
10100	1	2872.0	950.0	1.6	32.16	.03	.30	-2000.00	-2000.000	2.48	-2000.00
	2	1262.0	1260.0	2.1	55.62	.01	.20	-2000.00	-2000.000	1.69	-2000.00
	3	649.7	1290.0	2.1	88.28	.01	.10	-2000.00	-2000.000	2.80	-2000.00
	4	369.3	1230.0	3.7	87.93	.03	.20	-2000.00	-2000.000	2.61	-2000.00
	5	183.1	910.0	2.9	67.34	.03	.20	-2000.00	-2000.000	3.10	-2000.00
10125	1	2247.0	940.0	1.5	31.19	.03	.30	-2000.00	-2000.000	3.39	-2000.00
	2	917.1	1151.0	1.7	33.27	.03	.30	-2000.00	-2000.000	2.31	-2000.00
	3	551.7	1380.0	3.5	55.04	.10	.30	-2000.00	-2000.000	2.17	-2000.00
	4	212.1	880.0	2.6	41.46	.10	.30	-2000.00	-2000.000	2.51	-2000.00
	5	145.6	910.0	-.4	40.05	100.00	.80	-2000.00	-2000.000	136.22	-2000.00
10150	1	1982.0	1030.0	1.2	27.40	.03	.30	-2000.00	-2000.000	7.99	-2000.00
	2	731.9	1149.0	3.6	93.72	.01	.20	-2000.00	-2000.000	1.98	-2000.00
	3	316.1	990.0	2.7	61.44	.10	.20	-2000.00	-2000.000	2.96	-2000.00
	4	175.8	920.0	-.2	40.05	100.00	.80	-2000.00	-2000.000	110.56	-2000.00
	5	266.9	2090.0	2.2	32.44	.10	.40	-2000.00	-2000.000	5.31	-2000.00
10175	1	1530.0	840.0	1.0	33.22	.01	.20	-2000.00	-2000.000	16.18	-2000.00
	2	558.2	922.0	2.8	73.27	.01	.20	-2000.00	-2000.000	1.73	-2000.00
	3	286.7	940.0	.0	40.34	100.00	.80	-2000.00	-2000.000	87.89	-2000.00
	4	390.5	2150.0	2.4	44.14	.03	.40	-2000.00	-2000.000	4.21	-2000.00
	5	281.7	2320.0	9.8	370.78	.01	.10	-2000.00	-2000.000	1.30	-2000.00
10200	1	1986.0	670.0	2.5	48.56	.03	.30	-2000.00	-2000.000	2.91	-2000.00
	2	824.7	835.0	.1	32.10	100.00	.70	-2000.00	-2000.000	65.36	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	875.5	1760.0	2.5	48.43	.03	.40	-2000.00	-2000.000	3.45	-2000.00
	4	632.1	2130.0	10.0	204.81	.10	.20	-2000.00	-2000.000	1.16	-2000.00
	5	449.4	2270.0	13.5	452.33	.10	.10	-2000.00	-2000.000	.92	-2000.00
10225	1	1370.0	610.0	-.1	40.05	100.00	.80	-2000.00	-2000.000	97.74	-2000.00
	2	1065.0	1430.0	2.2	43.27	.03	.40	-2000.00	-2000.000	2.07	-2000.00
	3	753.3	2020.0	10.0	376.22	.01	.10	-2000.00	-2000.000	1.11	-2000.00
	4	446.1	2000.0	13.7	469.38	.03	.10	-2000.00	-2000.000	.99	-2000.00
	5	207.8	1390.0	16.5	490.06	100.00	.10	-2000.00	-2000.000	1.23	-2000.00
10250	1	2848.0	1110.0	1.4	30.13	.03	.40	-2000.00	-2000.000	6.99	-2000.00
	2	1480.0	1740.0	9.7	199.48	.10	.20	-2000.00	-2000.000	1.18	-2000.00
	3	902.0	2110.0	13.5	452.76	.10	.10	-2000.00	-2000.000	.82	-2000.00
	4	308.8	1210.0	16.9	290.18	10.00	.20	-2000.00	-2000.000	1.44	-2000.00
	5	164.9	970.0	15.4	482.36	1.00	.10	-2000.00	-2000.000	1.24	-2000.00
10275	1	2544.0	1500.0	9.1	187.69	.10	.20	-2000.00	-2000.000	1.00	-2000.00
	2	1121.0	1990.0	12.9	436.02	.10	.10	-2000.00	-2000.000	.80	-2000.00
	3	317.2	1120.0	17.3	502.70	100.00	.10	-2000.00	-2000.000	1.33	-2000.00
	4	149.6	880.0	15.2	485.67	.30	.10	-2000.00	-2000.000	1.01	-2000.00
	5	45.4	403.0	11.7	257.59	.03	.20	-2000.00	-2000.000	2.47	-2000.00
10300	1	3727.0	1910.0	12.3	404.17	1.00	.10	-2000.00	-2000.000	.89	-2000.00
	2	564.0	870.0	18.2	308.76	10.00	.20	-2000.00	-2000.000	1.35	-2000.00
	3	261.8	800.0	16.3	501.61	1.00	.10	-2000.00	-2000.000	1.07	-2000.00
	4	76.4	393.0	12.8	258.33	.10	.20	-2000.00	-2000.000	1.80	-2000.00
	5	143.5	1100.0	22.2	375.50	30.00	.20	-2000.00	-2000.000	4.72	-2000.00
10325	1	1087.0	680.0	21.5	358.53	30.00	.20	-2000.00	-2000.000	1.09	-2000.00
	2	401.1	755.0	18.4	529.93	100.00	.10	-2000.00	-2000.000	1.06	-2000.00
	3	113.6	420.0	14.2	474.05	.10	.10	-2000.00	-2000.000	1.12	-2000.00
	4	183.7	1150.0	24.2	386.12	10.00	.20	-2000.00	-2000.000	1.36	-2000.00
	5	122.4	1150.0	22.9	391.06	100.00	.20	-2000.00	-2000.000	.78	-2000.00
10350	1	1760.0	1080.0	18.5	530.13	100.00	.10	-2000.00	-2000.000	1.19	-2000.00
	2	229.2	423.0	15.6	525.80	.03	.10	-2000.00	-2000.000	1.04	-2000.00
	3	409.6	1500.0	23.2	374.86	10.00	.20	-2000.00	-2000.000	1.42	-2000.00
	4	204.6	1250.0	23.6	384.65	30.00	.20	-2000.00	-2000.000	1.14	-2000.00
10375	1	1195.0	830.0	11.4	233.08	.10	.20	-2000.00	-2000.000	1.21	-2000.00
	2	933.1	1953.0	20.6	579.53	10.00	.10	-2000.00	-2000.000	1.63	-2000.00
	3	386.3	1610.0	23.1	378.48	30.00	.20	-2000.00	-2000.000	1.20	-2000.00
10400	1	4376.0	2740.0	12.3	450.44	.01	.10	-2000.00	-2000.000	1.61	-2000.00
	2	1112.0	2090.0	18.0	520.15	100.00	.10	-2000.00	-2000.000	1.70	-2000.00
10425	1	621.3	1625.0	11.7	230.38	100.00	.20	-2000.00	-2000.000	1.24	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1134

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	602.1	210.0	2.3	90.09	100.00	.10	-2000.00	-2000.000	2.01	-2000.00
	2	224.0	234.0	6.5	122.82	3.00	.20	-2000.00	-2000.000	.91	-2000.00
	3	128.4	260.0	5.3	80.91	.30	.30	-2000.00	-2000.000	5.62	-2000.00
	4	59.4	207.0	5.2	100.62	3.00	.20	-2000.00	-2000.000	2.48	-2000.00
	5	35.1	183.0	5.2	65.49	.30	.30	-2000.00	-2000.000	10.84	-2000.00
10050	1	616.6	261.0	6.2	239.52	.03	.10	-2000.00	-2000.000	.64	-2000.00
	2	250.7	319.0	5.6	111.68	.30	.20	-2000.00	-2000.000	1.09	-2000.00
	3	98.0	248.0	4.8	46.04	.30	.40	-2000.00	-2000.000	6.45	-2000.00
	4	52.6	223.0	4.1	187.21	.01	.10	-2000.00	-2000.000	5.37	-2000.00
	5	41.8	266.0	5.2	115.60	100.00	.20	-2000.00	-2000.000	11.25	-2000.00
10075	1	1560.0	466.0	4.9	198.68	.01	.10	-2000.00	-2000.000	.87	-2000.00
	2	399.3	358.2	4.4	167.11	.30	.10	-2000.00	-2000.000	.82	-2000.00
	3	205.4	367.0	4.2	160.52	.30	.10	-2000.00	-2000.000	2.23	-2000.00
	4	125.4	375.0	4.9	186.67	.01	.10	-2000.00	-2000.000	4.83	-2000.00
	5	91.5	410.4	4.5	180.01	3.00	.10	-2000.00	-2000.000	4.36	-2000.00
10100	1	1104.0	770.0	1.9	46.89	.03	.20	-2000.00	-2000.000	3.91	-2000.00
	2	438.0	916.0	2.2	24.08	.30	.40	-2000.00	-2000.000	4.41	-2000.00
	3	220.5	920.0	2.9	62.14	.10	.20	-2000.00	-2000.000	4.34	-2000.00
	4	140.4	970.0	3.3	135.86	.10	.10	-2000.00	-2000.000	6.12	-2000.00
	5	80.1	838.0	2.4	102.55	.10	.10	-2000.00	-2000.000	15.19	-2000.00
10125	1	2395.0	970.0	1.5	31.45	.03	.30	-2000.00	-2000.000	3.53	-2000.00
	2	1123.0	1370.0	2.4	38.51	.10	.30	-2000.00	-2000.000	2.91	-2000.00
	3	718.4	1750.0	3.0	67.26	.10	.20	-2000.00	-2000.000	2.58	-2000.00
	4	279.8	1140.0	2.2	52.54	.10	.20	-2000.00	-2000.000	4.76	-2000.00
	5	169.7	1030.0	-1.1	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10150	1	2355.0	860.0	2.0	46.66	.03	.20	-2000.00	-2000.000	2.60	-2000.00
	2	1222.0	1350.0	2.7	63.98	.03	.20	-2000.00	-2000.000	2.01	-2000.00
	3	552.5	1220.0	1.9	51.51	.01	.20	-2000.00	-2000.000	2.21	-2000.00
	4	245.9	900.0	-1.6	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	313.6	1730.0	1.1	34.71	.01	.30	-2000.00	-2000.000	21.98	-2000.00
10175	1	1777.0	880.0	2.6	67.46	.01	.20	-2000.00	-2000.000	1.80	-2000.00
	2	693.4	1036.0	2.0	53.49	.01	.20	-2000.00	-2000.000	2.98	-2000.00
	3	290.2	860.0	-1.5	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	4	303.4	1510.0	1.3	30.63	.03	.40	-2000.00	-2000.000	10.26	-2000.00
	5	306.8	2290.0	8.5	179.24	.10	.20	-2000.00	-2000.000	1.13	-2000.00
10200	1	1891.0	790.0	1.5	38.09	.01	.30	-2000.00	-2000.000	4.15	-2000.00
	2	650.6	817.0	-1.3	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	656.6	1640.0	1.8	34.92	.03	.40	-2000.00	-2000.000	4.46	-2000.00
	4	513.6	2150.0	9.3	352.37	.01	.10	-2000.00	-2000.000	1.34	-2000.00
	5	274.6	1720.0	13.5	237.81	10.00	.20	-2000.00	-2000.000	1.60	-2000.00
10225	1	1716.0	740.0	-.8	40.05	100.00	.80	-2000.00	-2000.000	199.13	-2000.00
	2	1323.0	1730.0	1.5	46.38	.01	.40	-2000.00	-2000.000	5.41	-2000.00
	3	943.2	2460.0	9.3	358.39	.01	.10	-2000.00	-2000.000	1.37	-2000.00
	4	388.1	1690.0	13.7	429.96	100.00	.10	-2000.00	-2000.000	1.26	-2000.00
	5	143.1	930.0	18.3	527.08	100.00	.10	-2000.00	-2000.000	1.15	-2000.00
10250	1	3259.0	1440.0	1.6	33.60	.03	.40	-2000.00	-2000.000	6.15	-2000.00
	2	1626.0	2150.0	9.9	203.23	.10	.20	-2000.00	-2000.000	1.12	-2000.00
	3	708.8	1870.0	13.8	432.00	30.00	.10	-2000.00	-2000.000	.67	-2000.00
	4	199.4	880.0	18.8	540.43	30.00	.10	-2000.00	-2000.000	.96	-2000.00
	5	117.8	780.0	16.5	491.86	30.00	.10	-2000.00	-2000.000	1.05	-2000.00
10275	1	2620.0	1640.0	9.7	199.91	.10	.20	-2000.00	-2000.000	1.06	-2000.00
	2	899.0	1693.0	14.3	442.71	100.00	.10	-2000.00	-2000.000	.61	-2000.00
	3	196.2	730.0	19.9	557.16	100.00	.10	-2000.00	-2000.000	.84	-2000.00
	4	108.9	680.0	17.0	501.32	30.00	.10	-2000.00	-2000.000	.73	-2000.00
	5	85.4	804.0	16.1	389.80	.01	.20	-2000.00	-2000.000	2.21	-2000.00
10300	1	2600.0	1450.0	13.1	414.80	100.00	.10	-2000.00	-2000.000	.93	-2000.00
	2	410.4	690.0	21.6	587.49	100.00	.10	-2000.00	-2000.000	1.09	-2000.00
	3	222.2	740.0	18.5	531.88	100.00	.10	-2000.00	-2000.000	.59	-2000.00
	4	141.2	790.0	16.7	361.68	.03	.20	-2000.00	-2000.000	1.75	-2000.00
10325	1	378.0	741.0	27.2	428.33	30.00	.20	-2000.00	-2000.000	1.29	-2000.00
	2	137.2	807.0	20.9	354.50	30.00	.20	-2000.00	-2000.000	2.23	-2000.00
	3	79.9	938.0	19.0	643.14	.01	.10	-2000.00	-2000.000	3.32	-2000.00
10350	1	627.4	938.0	20.9	344.50	10.00	.20	-2000.00	-2000.000	1.24	-2000.00
	2	211.5	948.0	19.0	639.61	.01	.10	-2000.00	-2000.000	1.93	-2000.00
10375	1	338.3	1062.0	21.6	702.66	.01	.10	-2000.00	-2000.000	1.11	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1144

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	1281.0	460.0	1.9	51.33	.01	.20	-2000.00	-2000.000	2.10	-2000.00
	2	168.3	182.0	4.6	92.75	.30	.20	-2000.00	-2000.000	2.00	-2000.00
	3	128.7	270.0	5.8	78.74	.30	.30	-2000.00	-2000.000	2.69	-2000.00
	4	87.9	317.0	4.9	43.47	.30	.50	-2000.00	-2000.000	5.98	-2000.00
	5	31.9	172.0	8.2	59.55	1.00	.50	-2000.00	-2000.000	10.15	-2000.00
10050	1	410.2	161.0	2.6	68.62	.01	.20	-2000.00	-2000.000	1.45	-2000.00
	2	226.5	266.0	4.9	197.63	.01	.10	-2000.00	-2000.000	1.10	-2000.00
	3	140.8	330.0	4.3	181.47	.01	.10	-2000.00	-2000.000	2.76	-2000.00
	4	46.5	182.0	8.0	143.97	100.00	.30	-2000.00	-2000.000	9.87	-2000.00
	5	38.9	228.0	6.7	97.35	30.00	.30	-2000.00	-2000.000	4.05	-2000.00
10075	1	558.7	318.0	3.1	73.39	.03	.20	-2000.00	-2000.000	1.73	-2000.00
	2	252.3	432.0	3.0	47.40	.10	.30	-2000.00	-2000.000	1.77	-2000.00
	3	88.8	303.0	5.8	38.86	3.00	.60	-2000.00	-2000.000	6.98	-2000.00
	4	52.8	301.0	5.6	117.37	100.00	.20	-2000.00	-2000.000	3.41	-2000.00
	5	45.0	385.0	3.1	85.52	.01	.20	-2000.00	-2000.000	4.45	-2000.00
10100	1	1099.0	570.0	2.0	49.88	.03	.20	-2000.00	-2000.000	4.56	-2000.00
	2	332.0	521.0	4.1	55.44	10.00	.30	-2000.00	-2000.000	2.75	-2000.00
	3	156.5	490.0	4.5	57.52	30.00	.40	-2000.00	-2000.000	5.30	-2000.00
	4	123.8	640.0	1.5	33.47	.03	.40	-2000.00	-2000.000	11.40	-2000.00
	5	71.3	559.0	3.0	56.61	10.00	.20	-2000.00	-2000.000	9.37	-2000.00
10125	1	1930.0	670.0	4.3	58.18	10.00	.30	-2000.00	-2000.000	3.50	-2000.00
	2	863.9	904.0	4.0	70.82	100.00	.30	-2000.00	-2000.000	3.70	-2000.00
	3	551.9	1150.0	1.1	34.83	.01	.30	-2000.00	-2000.000	17.54	-2000.00
	4	285.0	990.0	2.2	30.53	.10	.40	-2000.00	-2000.000	2.33	-2000.00
	5	121.4	630.0	-2.4	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10150	1	1891.0	860.0	3.7	65.07	100.00	.30	-2000.00	-2000.000	4.74	-2000.00
	2	1051.0	1430.0	.2	44.08	30.00	.10	-2000.00	-2000.000	68.21	-2000.00
	3	534.8	1450.0	1.3	29.32	.03	.40	-2000.00	-2000.000	11.87	-2000.00
	4	194.8	880.0	-3.8	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	377.8	2570.0	-1.2	32.34	100.00	.70	-2000.00	-2000.000	163.26	-2000.00
10175	1	2581.0	810.0	2.9	114.60	100.00	.10	-2000.00	-2000.000	4.01	-2000.00
	2	1217.0	1146.0	3.7	72.68	10.00	.20	-2000.00	-2000.000	2.28	-2000.00
	3	475.6	894.0	-1.9	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	4	694.8	2181.0	.2	45.06	.10	.10	-2000.00	-2000.000	63.02	-2000.00
	5	314.6	1481.0	7.0	163.27	.03	.20	-2000.00	-2000.000	1.91	-2000.00
10200	1	3937.0	1260.0	3.6	73.83	30.00	.20	-2000.00	-2000.000	2.72	-2000.00
	2	978.1	940.0	-.6	40.05	100.00	.80	-2000.00	-2000.000	137.40	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	1471.0	2800.0	1.5	30.97	.03	.40	-2000.00	-2000.000	7.33	-2000.00
	4	346.0	1100.0	8.9	321.90	.10	.10	-2000.00	-2000.000	1.64	-2000.00
	5	391.2	1880.0	10.0	184.39	10.00	.20	-2000.00	-2000.000	1.95	-2000.00
10225	1	1259.0	650.0	-.1	40.05	100.00	.80	-2000.00	-2000.000	90.38	-2000.00
	2	1530.0	2400.0	2.4	47.84	.03	.40	-2000.00	-2000.000	4.10	-2000.00
	3	394.3	1230.0	9.6	339.57	.10	.10	-2000.00	-2000.000	.74	-2000.00
	4	291.0	1520.0	10.8	194.24	10.00	.20	-2000.00	-2000.000	1.27	-2000.00
	5	104.2	810.0	16.4	304.77	100.00	.20	-2000.00	-2000.000	1.45	-2000.00
10250	1	2989.0	2180.0	5.1	207.70	.01	.10	-2000.00	-2000.000	2.34	-2000.00
	2	481.2	1054.0	12.0	385.46	30.00	.10	-2000.00	-2000.000	.69	-2000.00
	3	369.1	1610.0	12.4	230.83	30.00	.20	-2000.00	-2000.000	.93	-2000.00
	4	90.4	660.0	17.3	311.60	30.00	.20	-2000.00	-2000.000	2.26	-2000.00
	5	60.4	661.0	18.7	320.17	10.00	.20	-2000.00	-2000.000	1.61	-2000.00
10275	1	1104.0	2030.0	12.8	465.48	.01	.10	-2000.00	-2000.000	.83	-2000.00
	2	337.7	1871.0	14.9	457.42	100.00	.10	-2000.00	-2000.000	.38	-2000.00
	3	78.3	865.0	20.1	324.50	10.00	.20	-2000.00	-2000.000	1.54	-2000.00
	4	37.2	687.0	21.2	337.70	3.00	.20	-2000.00	-2000.000	2.31	-2000.00
	5	18.5	513.0	12.3	454.90	.01	.10	-2000.00	-2000.000	3.44	-2000.00
10300	1	670.8	1914.0	16.6	493.67	30.00	.10	-2000.00	-2000.000	.85	-2000.00
	2	94.2	806.3	23.3	373.02	10.00	.20	-2000.00	-2000.000	1.07	-2000.00
	3	52.5	896.0	24.1	380.54	10.00	.20	-2000.00	-2000.000	2.90	-2000.00
	4	20.1	573.0	15.2	478.72	.10	.10	-2000.00	-2000.000	5.74	-2000.00
	5	14.2	608.0	21.1	246.37	10.00	.30	-2000.00	-2000.000	5.77	-2000.00
10325	1	348.3	994.0	22.8	376.07	30.00	.20	-2000.00	-2000.000	1.45	-2000.00
	2	113.5	971.0	23.3	618.41	100.00	.10	-2000.00	-2000.000	1.19	-2000.00
	3	38.2	653.0	23.4	660.58	.10	.10	-2000.00	-2000.000	4.75	-2000.00
	4	19.9	567.0	21.7	375.06	100.00	.20	-2000.00	-2000.000	4.05	-2000.00
10350	1	671.3	1239.0	22.4	601.56	100.00	.10	-2000.00	-2000.000	.67	-2000.00
	2	120.2	666.0	23.4	625.09	30.00	.10	-2000.00	-2000.000	1.14	-2000.00
	3	66.4	734.0	27.4	444.00	100.00	.20	-2000.00	-2000.000	2.20	-2000.00
10375	1	478.4	625.0	21.3	588.93	30.00	.10	-2000.00	-2000.000	1.30	-2000.00
	2	161.9	635.0	26.4	433.65	100.00	.20	-2000.00	-2000.000	1.57	-2000.00
10400	1	337.3	1059.0	19.2	320.17	10.00	.20	-2000.00	-2000.000	1.38	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1154

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	795.2	438.0	1.5	35.89	.03	.20	-2000.00	-2000.000	3.01	-2000.00
	2	178.6	295.0	3.3	64.52	1.00	.20	-2000.00	-2000.000	1.21	-2000.00
	3	67.0	221.0	5.5	106.02	10.00	.20	-2000.00	-2000.000	1.35	-2000.00
	4	33.5	184.0	6.5	127.94	10.00	.20	-2000.00	-2000.000	2.59	-2000.00
	5	22.9	189.0	6.4	126.12	10.00	.20	-2000.00	-2000.000	4.45	-2000.00
10050	1	715.3	299.0	1.8	46.83	.01	.20	-2000.00	-2000.000	1.99	-2000.00
	2	186.0	233.0	4.1	160.56	.10	.10	-2000.00	-2000.000	1.21	-2000.00
	3	76.6	192.0	5.1	104.42	.30	.20	-2000.00	-2000.000	2.22	-2000.00
	4	47.6	199.0	5.4	112.32	.30	.20	-2000.00	-2000.000	4.27	-2000.00
	5	63.7	400.0	7.1	35.87	1.00	.70	-2000.00	-2000.000	11.61	-2000.00
10075	1	602.9	270.0	2.4	56.83	.03	.20	-2000.00	-2000.000	1.33	-2000.00
	2	168.7	227.0	4.4	55.96	1.00	.30	-2000.00	-2000.000	2.42	-2000.00
	3	91.2	244.0	4.9	61.96	1.00	.30	-2000.00	-2000.000	1.86	-2000.00
	4	108.2	480.0	5.1	54.75	.30	.40	-2000.00	-2000.000	7.18	-2000.00
	5	65.7	442.0	4.3	34.76	.30	.60	-2000.00	-2000.000	11.64	-2000.00
10100	1	674.9	249.0	2.2	47.87	.10	.20	-2000.00	-2000.000	2.27	-2000.00
	2	250.3	277.0	3.3	71.45	.10	.20	-2000.00	-2000.000	2.00	-2000.00
	3	273.9	600.0	4.4	166.17	100.00	.10	-2000.00	-2000.000	3.95	-2000.00
	4	141.0	520.0	4.8	92.65	30.00	.20	-2000.00	-2000.000	10.69	-2000.00
	5	34.5	191.0	2.9	104.67	.10	.10	-2000.00	-2000.000	12.33	-2000.00
10125	1	896.2	375.0	1.8	48.21	.01	.20	-2000.00	-2000.000	2.23	-2000.00
	2	646.0	811.0	2.8	72.86	.01	.20	-2000.00	-2000.000	1.29	-2000.00
	3	310.2	770.0	2.4	67.23	.03	.20	-2000.00	-2000.000	11.75	-2000.00
	4	59.2	247.0	1.1	58.23	.10	.10	-2000.00	-2000.000	22.67	-2000.00
	5	38.5	241.0	.4	62.33	100.00	.80	-2000.00	-2000.000	52.45	-2000.00
10150	1	1083.0	700.0	2.2	35.78	.10	.30	-2000.00	-2000.000	2.43	-2000.00
	2	406.2	797.0	2.1	50.76	.03	.20	-2000.00	-2000.000	2.59	-2000.00
	3	75.5	295.0	.8	21.87	100.00	.30	-2000.00	-2000.000	29.03	-2000.00
	4	42.4	277.0	.1	42.62	100.00	.80	-2000.00	-2000.000	111.28	-2000.00
	5	98.9	970.0	.4	45.92	100.00	.10	-2000.00	-2000.000	52.99	-2000.00
10175	1	1915.0	700.0	1.7	37.27	.10	.20	-2000.00	-2000.000	3.51	-2000.00
	2	295.6	327.0	.6	21.68	100.00	.50	-2000.00	-2000.000	38.00	-2000.00
	3	145.0	320.0	.0	40.05	100.00	.80	-2000.00	-2000.000	109.59	-2000.00
	4	307.8	1130.0	.6	45.25	30.00	.10	-2000.00	-2000.000	33.71	-2000.00
	5	105.6	580.0	4.4	36.17	.30	.60	-2000.00	-2000.000	6.09	-2000.00
10200	1	1387.0	670.0	1.2	55.35	.10	.10	-2000.00	-2000.000	13.22	-2000.00
	2	389.1	563.0	.6	19.35	100.00	.40	-2000.00	-2000.000	29.38	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	663.6	1910.0	1.0	33.76	.01	.20	-2000.00	-2000.000	19.37	-2000.00
	4	193.8	930.0	5.3	85.57	.10	.30	-2000.00	-2000.000	2.94	-2000.00
	5	113.4	820.0	8.2	90.73	3.00	.40	-2000.00	-2000.000	12.10	-2000.00
10225	1	2717.0	1020.0	1.7	38.00	.10	.20	-2000.00	-2000.000	5.89	-2000.00
	2	2118.0	2400.0	2.3	31.15	.10	.40	-2000.00	-2000.000	3.60	-2000.00
	3	578.2	1300.0	6.7	153.81	.03	.20	-2000.00	-2000.000	1.35	-2000.00
	4	259.0	970.0	10.3	212.41	30.00	.20	-2000.00	-2000.000	5.18	-2000.00
	5	185.7	1050.0	11.2	230.68	100.00	.20	-2000.00	-2000.000	3.95	-2000.00
10250	1	2716.0	1700.0	2.2	54.77	.01	.30	-2000.00	-2000.000	1.67	-2000.00
	2	435.2	819.0	7.8	171.51	.03	.20	-2000.00	-2000.000	2.41	-2000.00
	3	200.7	750.0	11.3	373.85	3.00	.10	-2000.00	-2000.000	3.92	-2000.00
	4	138.6	870.0	11.3	140.60	3.00	.30	-2000.00	-2000.000	3.58	-2000.00
	5	47.3	445.0	17.6	296.70	10.00	.20	-2000.00	-2000.000	4.29	-2000.00
10275	1	1969.0	1370.0	10.8	266.69	.01	.20	-2000.00	-2000.000	.98	-2000.00
	2	489.2	1024.0	15.8	486.48	3.00	.10	-2000.00	-2000.000	1.43	-2000.00
	3	269.7	1120.0	15.4	266.46	30.00	.20	-2000.00	-2000.000	1.88	-2000.00
	4	75.6	527.0	20.1	328.05	10.00	.20	-2000.00	-2000.000	1.57	-2000.00
	5	30.2	316.0	15.6	522.89	.10	.10	-2000.00	-2000.000	4.42	-2000.00
10300	1	579.9	1517.0	21.2	585.48	30.00	.10	-2000.00	-2000.000	.86	-2000.00
	2	257.4	2020.0	18.8	318.53	10.00	.20	-2000.00	-2000.000	1.59	-2000.00
	3	57.5	901.0	24.0	410.13	100.00	.20	-2000.00	-2000.000	4.06	-2000.00
	4	20.4	532.0	17.6	308.71	30.00	.20	-2000.00	-2000.000	5.64	-2000.00
	5	13.5	531.0	19.3	286.59	100.00	.30	-2000.00	-2000.000	10.41	-2000.00
10325	1	786.3	2468.0	14.4	253.31	10.00	.20	-2000.00	-2000.000	.94	-2000.00
	2	81.5	767.6	23.8	628.40	100.00	.10	-2000.00	-2000.000	1.17	-2000.00
	3	27.0	508.0	16.2	325.54	10.00	.20	-2000.00	-2000.000	9.00	-2000.00
	4	17.5	550.0	15.5	235.93	30.00	.30	-2000.00	-2000.000	9.61	-2000.00
	5	14.7	693.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10350	1	945.0	723.0	23.7	380.29	10.00	.20	-2000.00	-2000.000	1.25	-2000.00
	2	208.9	479.0	20.2	567.29	100.00	.10	-2000.00	-2000.000	1.35	-2000.00
	3	146.5	670.0	29.9	464.90	100.00	.20	-2000.00	-2000.000	1.47	-2000.00
	4	90.9	695.0	21.3	359.34	100.00	.20	-2000.00	-2000.000	1.73	-2000.00
10375	1	440.2	575.0	18.6	535.64	30.00	.10	-2000.00	-2000.000	1.22	-2000.00
	2	190.5	747.0	27.5	445.76	100.00	.20	-2000.00	-2000.000	1.14	-2000.00
	3	101.4	790.0	18.2	351.01	100.00	.20	-2000.00	-2000.000	4.75	-2000.00
10400	1	981.0	1540.0	21.4	352.03	10.00	.20	-2000.00	-2000.000	1.22	-2000.00
	2	268.2	1263.0	17.4	305.11	30.00	.20	-2000.00	-2000.000	1.09	-2000.00
10425	1	719.3	1411.0	16.2	287.03	30.00	.20	-2000.00	-2000.000	1.33	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1164

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	562.6	294.0	1.9	51.27	.01	.20	-2000.00	-2000.000	1.90	-2000.00
	2	145.0	227.0	3.8	141.72	10.00	.10	-2000.00	-2000.000	1.72	-2000.00
	3	63.2	198.0	5.5	67.58	3.00	.30	-2000.00	-2000.000	1.96	-2000.00
	4	32.4	169.0	5.9	57.64	1.00	.40	-2000.00	-2000.000	3.68	-2000.00
	5	20.0	156.0	6.9	64.75	1.00	.40	-2000.00	-2000.000	4.90	-2000.00
10050	1	456.1	220.0	2.2	53.44	.03	.20	-2000.00	-2000.000	1.79	-2000.00
	2	140.5	203.0	4.1	154.35	10.00	.10	-2000.00	-2000.000	.78	-2000.00
	3	59.3	171.0	5.6	52.48	1.00	.40	-2000.00	-2000.000	1.80	-2000.00
	4	35.9	173.0	6.4	236.97	.30	.10	-2000.00	-2000.000	1.67	-2000.00
	5	22.5	163.0	6.9	38.45	1.00	.60	-2000.00	-2000.000	7.07	-2000.00
10075	1	468.7	253.0	2.3	49.87	.10	.20	-2000.00	-2000.000	1.92	-2000.00
	2	137.1	222.0	4.3	84.02	1.00	.20	-2000.00	-2000.000	1.20	-2000.00
	3	66.0	214.0	5.8	110.94	3.00	.20	-2000.00	-2000.000	2.07	-2000.00
	4	36.7	198.0	5.9	116.26	3.00	.20	-2000.00	-2000.000	4.13	-2000.00
	5	30.4	247.0	5.8	75.01	1.00	.30	-2000.00	-2000.000	5.74	-2000.00
10100	1	403.4	253.0	2.2	48.53	.10	.20	-2000.00	-2000.000	2.29	-2000.00
	2	135.0	254.0	4.7	175.15	.30	.10	-2000.00	-2000.000	.94	-2000.00
	3	62.0	233.0	5.2	49.16	1.00	.40	-2000.00	-2000.000	1.67	-2000.00
	4	44.5	279.0	5.0	97.10	1.00	.20	-2000.00	-2000.000	2.32	-2000.00
	5	25.1	236.0	4.5	34.62	1.00	.50	-2000.00	-2000.000	5.88	-2000.00
10125	1	542.1	309.0	2.5	65.82	.01	.20	-2000.00	-2000.000	1.54	-2000.00
	2	167.8	287.0	3.5	75.41	.10	.20	-2000.00	-2000.000	.92	-2000.00
	3	98.2	335.0	3.4	54.15	.10	.30	-2000.00	-2000.000	1.41	-2000.00
	4	49.3	281.0	4.7	86.34	3.00	.20	-2000.00	-2000.000	5.79	-2000.00
	5	35.7	305.0	3.0	43.37	.30	.30	-2000.00	-2000.000	9.85	-2000.00
10150	1	126.8	306.0	1.9	79.74	.01	.10	-2000.00	-2000.000	8.41	-2000.00
	2	57.8	419.0	2.6	98.27	100.00	.10	-2000.00	-2000.000	21.62	-2000.00
	3	29.8	431.0	3.1	15.16	3.00	.80	-2000.00	-2000.000	58.12	-2000.00
	4	17.1	412.0	3.6	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	8.5	308.6	.7	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10175	1	923.1	445.0	1.7	32.94	.03	.30	-2000.00	-2000.000	2.77	-2000.00
	2	329.1	476.0	1.8	28.87	.10	.30	-2000.00	-2000.000	6.15	-2000.00
	3	191.5	550.0	1.9	46.76	.01	.20	-2000.00	-2000.000	6.23	-2000.00
	4	87.5	422.0	-.3	40.05	100.00	.80	-2000.00	-2000.000	185.67	-2000.00
	5	128.2	920.0	-.1	25.15	100.00	.60	-2000.00	-2000.000	107.91	-2000.00
10200	1	998.4	401.0	1.3	32.37	.03	.20	-2000.00	-2000.000	7.42	-2000.00
	2	473.3	571.0	1.4	35.95	.03	.20	-2000.00	-2000.000	5.67	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	198.2	470.0	-1.0	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	4	267.8	1070.0	-.4	44.27	100.00	.80	-2000.00	-2000.000	110.04	-2000.00
	5	154.7	930.0	6.2	149.27	.01	.20	-2000.00	-2000.000	8.99	-2000.00
10225	1	723.1	528.0	1.1	54.06	.10	.10	-2000.00	-2000.000	17.91	-2000.00
	2	223.0	488.0	-.8	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	3	275.9	1200.0	-.8	44.04	100.00	.80	-2000.00	-2000.000	127.93	-2000.00
	4	147.8	1070.0	6.0	40.03	.30	.70	-2000.00	-2000.000	20.05	-2000.00
	5	107.2	1170.0	6.5	105.01	30.00	.30	-2000.00	-2000.000	12.68	-2000.00
10250	1	530.0	346.0	-.8	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	2	540.1	1059.0	-.4	44.91	100.00	.80	-2000.00	-2000.000	102.33	-2000.00
	3	266.0	1040.0	5.8	156.93	.01	.20	-2000.00	-2000.000	2.82	-2000.00
	4	174.2	1130.0	7.1	131.57	10.00	.20	-2000.00	-2000.000	5.45	-2000.00
	5	57.2	561.0	17.4	298.23	10.00	.20	-2000.00	-2000.000	4.31	-2000.00
10275	1	1841.0	990.0	.7	32.35	.01	.20	-2000.00	-2000.000	30.47	-2000.00
	2	602.4	978.0	7.6	159.71	.10	.20	-2000.00	-2000.000	1.98	-2000.00
	3	329.2	1060.0	7.8	280.70	100.00	.10	-2000.00	-2000.000	1.71	-2000.00
	4	92.6	501.0	18.6	524.96	100.00	.10	-2000.00	-2000.000	2.30	-2000.00
	5	48.0	389.0	18.1	522.51	100.00	.10	-2000.00	-2000.000	5.46	-2000.00
10300	1	1567.0	890.0	9.9	202.21	.10	.20	-2000.00	-2000.000	.92	-2000.00
	2	534.3	915.0	9.7	179.88	10.00	.20	-2000.00	-2000.000	1.89	-2000.00
	3	137.2	460.0	19.7	570.80	1.00	.10	-2000.00	-2000.000	1.86	-2000.00
	4	61.3	350.0	18.7	552.21	3.00	.10	-2000.00	-2000.000	3.90	-2000.00
	5	32.6	279.0	18.1	192.87	.10	.40	-2000.00	-2000.000	13.81	-2000.00
10325	1	3294.0	1430.0	12.7	409.11	3.00	.10	-2000.00	-2000.000	.78	-2000.00
	2	422.6	552.0	23.3	619.75	100.00	.10	-2000.00	-2000.000	.92	-2000.00
	3	164.1	420.0	21.9	591.85	10.00	.10	-2000.00	-2000.000	1.43	-2000.00
	4	73.3	319.0	19.9	320.29	10.00	.20	-2000.00	-2000.000	3.54	-2000.00
	5	69.3	453.0	17.4	303.76	10.00	.20	-2000.00	-2000.000	2.06	-2000.00
10350	1	745.7	585.0	25.4	408.01	30.00	.20	-2000.00	-2000.000	1.71	-2000.00
	2	162.7	383.0	24.9	394.04	10.00	.20	-2000.00	-2000.000	3.37	-2000.00
	3	71.1	334.0	21.7	282.17	30.00	.30	-2000.00	-2000.000	6.04	-2000.00
	4	61.8	485.0	20.6	359.81	100.00	.20	-2000.00	-2000.000	4.10	-2000.00
10375	1	1186.0	900.0	21.4	589.31	30.00	.10	-2000.00	-2000.000	1.08	-2000.00
	2	223.1	512.0	22.0	379.13	100.00	.20	-2000.00	-2000.000	.49	-2000.00
	3	152.3	690.0	20.2	230.07	3.00	.30	-2000.00	-2000.000	1.81	-2000.00
10400	1	191.8	547.0	16.6	284.78	10.00	.20	-2000.00	-2000.000	1.52	-2000.00
	2	121.9	1043.0	18.8	321.58	30.00	.20	-2000.00	-2000.000	2.46	-2000.00
10425	1	2114.0	5100.0	9.1	187.61	.10	.20	-2000.00	-2000.000	1.25	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1174

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	520.1	272.0	2.3	48.85	.10	.20	-2000.00	-2000.000	2.49	-2000.00
	2	157.5	247.0	4.2	54.02	1.00	.30	-2000.00	-2000.000	.76	-2000.00
	3	71.3	223.0	5.4	105.29	10.00	.20	-2000.00	-2000.000	.59	-2000.00
	4	35.7	186.0	6.4	121.49	10.00	.20	-2000.00	-2000.000	.90	-2000.00
	5	19.4	152.0	6.7	125.36	3.00	.20	-2000.00	-2000.000	1.16	-2000.00
10050	1	552.2	288.0	2.3	54.79	.03	.20	-2000.00	-2000.000	1.94	-2000.00
	2	175.0	274.0	4.1	154.21	10.00	.10	-2000.00	-2000.000	.61	-2000.00
	3	71.3	223.0	5.6	70.29	3.00	.30	-2000.00	-2000.000	.95	-2000.00
	4	34.0	177.0	6.3	121.70	10.00	.20	-2000.00	-2000.000	1.45	-2000.00
	5	19.6	153.0	6.2	233.54	3.00	.10	-2000.00	-2000.000	3.06	-2000.00
10075	1	602.8	252.0	2.6	56.19	.10	.20	-2000.00	-2000.000	1.73	-2000.00
	2	206.7	259.0	4.5	166.89	10.00	.10	-2000.00	-2000.000	.92	-2000.00
	3	70.6	176.0	5.9	110.33	3.00	.20	-2000.00	-2000.000	1.23	-2000.00
	4	34.8	145.0	6.4	239.01	.10	.10	-2000.00	-2000.000	1.89	-2000.00
	5	33.3	209.0	6.2	120.47	.30	.20	-2000.00	-2000.000	3.37	-2000.00
10100	1	518.3	285.0	2.6	56.39	.10	.20	-2000.00	-2000.000	1.63	-2000.00
	2	113.1	186.0	4.7	60.24	1.00	.30	-2000.00	-2000.000	.82	-2000.00
	3	53.5	176.0	6.2	58.13	1.00	.40	-2000.00	-2000.000	2.32	-2000.00
	4	39.9	219.0	5.9	125.72	.10	.20	-2000.00	-2000.000	1.64	-2000.00
	5	25.9	213.0	5.6	77.63	.30	.30	-2000.00	-2000.000	2.84	-2000.00
10125	1	504.8	264.0	2.4	52.15	.10	.20	-2000.00	-2000.000	1.63	-2000.00
	2	138.9	218.0	4.7	183.79	.03	.10	-2000.00	-2000.000	.86	-2000.00
	3	84.5	264.0	5.4	74.14	.30	.30	-2000.00	-2000.000	1.17	-2000.00
	4	47.3	247.0	5.8	114.37	.30	.20	-2000.00	-2000.000	1.80	-2000.00
	5	29.0	227.0	4.0	36.75	.30	.50	-2000.00	-2000.000	5.88	-2000.00
10150	1	509.0	238.0	2.8	72.80	.01	.20	-2000.00	-2000.000	1.20	-2000.00
	2	226.6	318.0	4.1	95.45	.03	.20	-2000.00	-2000.000	.88	-2000.00
	3	97.9	274.0	4.7	65.27	.30	.30	-2000.00	-2000.000	1.63	-2000.00
	4	50.6	237.0	3.6	32.57	.30	.50	-2000.00	-2000.000	6.33	-2000.00
	5	32.4	228.0	1.1	32.85	.01	.30	-2000.00	-2000.000	46.90	-2000.00
10175	1	1130.0	520.0	2.2	59.66	.01	.20	-2000.00	-2000.000	2.59	-2000.00
	2	310.4	429.0	3.2	76.53	.03	.20	-2000.00	-2000.000	1.29	-2000.00
	3	123.2	340.0	2.7	24.56	.30	.50	-2000.00	-2000.000	2.59	-2000.00
	4	62.9	290.0	1.0	34.57	.03	.20	-2000.00	-2000.000	15.90	-2000.00
	5	50.2	347.0	-.6	42.46	100.00	.80	-2000.00	-2000.000	114.17	-2000.00
10200	1	1051.0	570.0	2.1	56.36	.01	.20	-2000.00	-2000.000	2.70	-2000.00
	2	275.9	455.0	2.1	33.32	.10	.30	-2000.00	-2000.000	2.88	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	118.3	390.0	1.4	24.68	100.00	.30	-2000.00	-2000.000	46.46	-2000.00
	4	79.1	435.0	-.2	42.91	100.00	.80	-2000.00	-2000.000	141.01	-2000.00
	5	64.9	536.0	2.2	26.63	.10	.30	-2000.00	-2000.000	58.04	-2000.00
10225	1	1033.0	550.0	1.6	30.92	.03	.30	-2000.00	-2000.000	4.28	-2000.00
	2	313.6	509.0	.6	20.33	100.00	.30	-2000.00	-2000.000	30.33	-2000.00
	3	176.6	570.0	-.6	40.05	100.00	.80	-2000.00	-2000.000	170.52	-2000.00
	4	124.5	670.0	.9	24.99	.03	.30	-2000.00	-2000.000	23.55	-2000.00
	5	105.2	850.0	3.5	76.99	10.00	.20	-2000.00	-2000.000	7.00	-2000.00
10250	1	783.1	501.0	.8	47.29	1.00	.10	-2000.00	-2000.000	22.25	-2000.00
	2	340.8	655.0	-.6	40.05	100.00	.80	-2000.00	-2000.000	132.55	-2000.00
	3	216.6	830.0	.8	32.22	.01	.30	-2000.00	-2000.000	22.28	-2000.00
	4	165.8	1060.0	3.0	79.81	.03	.20	-2000.00	-2000.000	5.59	-2000.00
	5	81.6	784.0	9.8	195.40	3.00	.20	-2000.00	-2000.000	4.05	-2000.00
10275	1	864.8	565.0	-.1	43.10	100.00	.80	-2000.00	-2000.000	84.02	-2000.00
	2	452.9	888.0	1.7	34.44	.03	.40	-2000.00	-2000.000	6.34	-2000.00
	3	306.5	1200.0	3.6	82.92	.10	.20	-2000.00	-2000.000	5.23	-2000.00
	4	120.2	780.0	11.3	211.59	10.00	.20	-2000.00	-2000.000	4.76	-2000.00
	5	102.4	1000.0	19.3	556.98	30.00	.10	-2000.00	-2000.000	2.67	-2000.00
10300	1	1824.0	810.0	2.2	55.08	.01	.30	-2000.00	-2000.000	3.68	-2000.00
	2	766.8	1031.0	4.3	92.61	.10	.20	-2000.00	-2000.000	1.74	-2000.00
	3	333.5	890.0	12.5	402.00	100.00	.10	-2000.00	-2000.000	1.07	-2000.00
	4	227.1	1010.0	20.4	588.16	3.00	.10	-2000.00	-2000.000	1.44	-2000.00
	5	79.9	537.0	22.4	378.36	100.00	.20	-2000.00	-2000.000	4.57	-2000.00
10325	1	1153.0	720.0	4.7	99.80	.10	.20	-2000.00	-2000.000	2.05	-2000.00
	2	389.7	734.0	14.0	438.29	100.00	.10	-2000.00	-2000.000	.87	-2000.00
	3	199.4	740.0	22.3	611.00	100.00	.10	-2000.00	-2000.000	1.53	-2000.00
	4	69.8	438.0	24.1	589.37	100.00	.10	-2000.00	-2000.000	5.03	-2000.00
	5	49.4	465.0	19.9	538.57	30.00	.10	-2000.00	-2000.000	2.80	-2000.00
10350	1	1108.0	610.0	15.7	273.09	10.00	.20	-2000.00	-2000.000	1.40	-2000.00
	2	451.6	746.0	24.7	637.88	100.00	.10	-2000.00	-2000.000	.75	-2000.00
	3	141.7	460.0	22.8	397.47	100.00	.20	-2000.00	-2000.000	3.20	-2000.00
	4	94.6	521.0	19.4	354.13	100.00	.20	-2000.00	-2000.000	4.84	-2000.00
	5	123.6	1020.0	20.8	367.41	100.00	.20	-2000.00	-2000.000	2.91	-2000.00
10375	1	1668.0	790.0	21.4	585.11	100.00	.10	-2000.00	-2000.000	.92	-2000.00
	2	278.5	397.0	22.4	362.90	10.00	.20	-2000.00	-2000.000	1.01	-2000.00
	3	189.8	540.0	21.3	296.23	100.00	.30	-2000.00	-2000.000	3.66	-2000.00
	4	238.2	1130.0	22.0	274.04	30.00	.30	-2000.00	-2000.000	4.30	-2000.00
	5	93.9	670.0	14.3	162.28	.30	.40	-2000.00	-2000.000	7.59	-2000.00
10400	1	1208.0	540.0	16.8	289.85	10.00	.20	-2000.00	-2000.000	1.75	-2000.00
	2	551.3	741.0	16.3	189.34	3.00	.30	-2000.00	-2000.000	2.41	-2000.00
	3	622.4	1670.0	18.1	314.10	30.00	.20	-2000.00	-2000.000	1.46	-2000.00
	4	184.7	820.0	14.9	266.87	30.00	.20	-2000.00	-2000.000	1.12	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	158.2	1060.0	15.2	296.09	100.00	.20	-2000.00	-2000.000	3.26	-2000.00
10425	1	2412.0	1260.0	9.4	322.26	1.00	.10	-2000.00	-2000.000	1.04	-2000.00
	2	1510.0	2370.0	13.6	427.25	100.00	.10	-2000.00	-2000.000	.79	-2000.00
	3	418.2	1310.0	11.7	210.37	10.00	.20	-2000.00	-2000.000	1.04	-2000.00
	4	254.3	1330.0	13.2	229.82	10.00	.20	-2000.00	-2000.000	2.81	-2000.00
	5	207.4	1620.0	13.1	233.23	10.00	.20	-2000.00	-2000.000	1.04	-2000.00
10450	1	4511.0	3290.0	8.0	167.04	.10	.20	-2000.00	-2000.000	1.48	-2000.00
	2	684.5	1499.0	8.0	279.35	100.00	.10	-2000.00	-2000.000	.76	-2000.00
	3	335.2	1460.0	9.4	174.44	10.00	.20	-2000.00	-2000.000	1.49	-2000.00
	4	242.5	1770.0	10.0	185.32	10.00	.20	-2000.00	-2000.000	1.38	-2000.00
10475	1	2153.0	1730.0	4.2	83.00	10.00	.20	-2000.00	-2000.000	2.30	-2000.00
	2	611.7	1477.0	7.1	135.30	10.00	.20	-2000.00	-2000.000	1.68	-2000.00
	3	434.8	2090.0	7.6	140.06	10.00	.20	-2000.00	-2000.000	3.25	-2000.00
10500	1	1782.0	1550.0	4.5	95.87	.10	.20	-2000.00	-2000.000	1.61	-2000.00
	2	755.4	1976.0	5.7	209.15	10.00	.10	-2000.00	-2000.000	1.28	-2000.00
10525	1	2770.0	1930.0	4.6	171.50	3.00	.10	-2000.00	-2000.000	1.30	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1184

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	384.3	182.0	3.5	145.45	.01	.10	-2000.00	-2000.000	1.10	-2000.00
	2	104.2	148.0	5.6	70.34	3.00	.30	-2000.00	-2000.000	.77	-2000.00
	3	59.6	169.0	6.6	129.91	30.00	.20	-2000.00	-2000.000	.73	-2000.00
	4	32.5	154.0	6.7	132.67	30.00	.20	-2000.00	-2000.000	1.27	-2000.00
	5	19.4	138.0	7.1	88.24	3.00	.30	-2000.00	-2000.000	.82	-2000.00
10050	1	220.7	135.0	3.6	136.70	3.00	.10	-2000.00	-2000.000	1.32	-2000.00
	2	111.8	206.0	5.3	102.89	10.00	.20	-2000.00	-2000.000	.95	-2000.00
	3	53.6	197.0	6.6	31.33	1.00	.70	-2000.00	-2000.000	4.24	-2000.00
	4	27.2	167.0	5.9	140.37	100.00	.20	-2000.00	-2000.000	8.25	-2000.00
	5	20.4	188.0	7.8	273.22	100.00	.10	-2000.00	-2000.000	1.79	-2000.00
10075	1	680.4	284.0	2.9	124.03	.01	.10	-2000.00	-2000.000	2.29	-2000.00
	2	183.3	230.0	5.0	96.73	10.00	.20	-2000.00	-2000.000	.87	-2000.00
	3	99.5	249.0	6.9	119.96	100.00	.30	-2000.00	-2000.000	2.80	-2000.00
	4	53.0	222.0	5.7	46.18	.30	.60	-2000.00	-2000.000	5.69	-2000.00
	5	18.9	118.0	6.4	88.62	.30	.30	-2000.00	-2000.000	1.34	-2000.00
10100	1	514.2	230.0	3.5	136.63	.10	.10	-2000.00	-2000.000	1.21	-2000.00
	2	153.0	205.0	5.4	104.10	10.00	.20	-2000.00	-2000.000	1.78	-2000.00
	3	82.1	220.0	7.1	251.14	10.00	.10	-2000.00	-2000.000	.86	-2000.00
	4	25.6	114.0	6.8	91.23	.30	.30	-2000.00	-2000.000	2.55	-2000.00
	5	34.0	228.0	6.2	84.40	.30	.30	-2000.00	-2000.000	2.06	-2000.00
10125	1	622.3	229.0	3.2	127.88	.10	.10	-2000.00	-2000.000	1.49	-2000.00
	2	229.8	254.0	5.9	112.41	1.00	.20	-2000.00	-2000.000	.99	-2000.00
	3	57.1	126.0	6.3	124.39	.30	.20	-2000.00	-2000.000	.91	-2000.00
	4	62.5	230.0	6.3	88.56	.30	.30	-2000.00	-2000.000	1.42	-2000.00
	5	34.4	190.0	4.4	91.55	.30	.20	-2000.00	-2000.000	2.62	-2000.00
10150	1	864.5	331.0	3.7	80.09	.10	.20	-2000.00	-2000.000	1.43	-2000.00
	2	145.9	167.0	5.1	108.02	.10	.20	-2000.00	-2000.000	.68	-2000.00
	3	118.8	270.0	6.0	82.98	.30	.30	-2000.00	-2000.000	1.49	-2000.00
	4	55.7	213.0	4.6	63.78	.30	.30	-2000.00	-2000.000	3.16	-2000.00
	5	31.0	178.0	2.0	47.26	.01	.30	-2000.00	-2000.000	10.83	-2000.00
10175	1	477.0	194.0	3.1	82.63	.01	.20	-2000.00	-2000.000	1.23	-2000.00
	2	253.5	310.0	4.9	125.72	.01	.20	-2000.00	-2000.000	1.05	-2000.00
	3	91.6	223.0	3.9	103.44	.01	.20	-2000.00	-2000.000	2.71	-2000.00
	4	43.5	177.0	1.1	41.02	.01	.40	-2000.00	-2000.000	18.32	-2000.00
	5	26.4	161.0	-.3	24.09	100.00	.20	-2000.00	-2000.000	101.42	-2000.00
10200	1	1636.0	730.0	3.2	51.67	.10	.30	-2000.00	-2000.000	2.33	-2000.00
	2	286.8	385.0	3.3	46.34	.30	.30	-2000.00	-2000.000	.59	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	95.9	257.0	2.2	29.45	.30	.30	-2000.00	-2000.000	4.88	-2000.00
	4	49.6	222.0	1.0	25.52	.03	.30	-2000.00	-2000.000	34.28	-2000.00
	5	74.7	502.0	.7	49.48	.10	.10	-2000.00	-2000.000	37.31	-2000.00
10225	1	1045.0	400.0	1.8	39.31	.10	.20	-2000.00	-2000.000	2.02	-2000.00
	2	241.5	277.0	1.1	53.73	.10	.10	-2000.00	-2000.000	13.59	-2000.00
	3	102.7	230.0	.2	19.55	100.00	.40	-2000.00	-2000.000	57.85	-2000.00
	4	134.4	510.0	.0	19.34	100.00	.30	-2000.00	-2000.000	76.66	-2000.00
	5	84.8	486.0	3.2	63.79	.03	.30	-2000.00	-2000.000	9.94	-2000.00
10250	1	786.1	493.0	1.5	40.37	.01	.20	-2000.00	-2000.000	5.49	-2000.00
	2	235.4	443.0	.7	45.60	30.00	.10	-2000.00	-2000.000	27.49	-2000.00
	3	236.6	880.0	.2	25.09	100.00	.20	-2000.00	-2000.000	64.95	-2000.00
	4	129.4	810.0	3.9	32.48	.30	.50	-2000.00	-2000.000	7.74	-2000.00
	5	67.9	639.0	12.2	79.57	.30	.60	-2000.00	-2000.000	16.95	-2000.00
10275	1	1007.0	450.0	1.1	31.29	.03	.20	-2000.00	-2000.000	14.52	-2000.00
	2	740.9	997.0	.4	49.78	.01	.10	-2000.00	-2000.000	51.44	-2000.00
	3	363.0	970.0	3.5	88.42	.03	.20	-2000.00	-2000.000	5.01	-2000.00
	4	179.0	800.0	11.0	220.21	30.00	.20	-2000.00	-2000.000	8.50	-2000.00
	5	57.5	386.0	18.6	317.34	10.00	.20	-2000.00	-2000.000	3.44	-2000.00
10300	1	2041.0	710.0	1.3	29.81	.03	.40	-2000.00	-2000.000	9.35	-2000.00
	2	800.4	837.0	4.4	103.30	.03	.20	-2000.00	-2000.000	1.14	-2000.00
	3	341.4	710.0	13.1	228.25	10.00	.20	-2000.00	-2000.000	4.14	-2000.00
	4	107.4	370.0	19.6	328.75	10.00	.20	-2000.00	-2000.000	1.26	-2000.00
	5	88.6	463.0	25.3	391.80	30.00	.20	-2000.00	-2000.000	3.34	-2000.00
10325	1	1622.0	640.0	5.1	108.43	.10	.20	-2000.00	-2000.000	1.36	-2000.00
	2	481.2	573.0	14.2	441.57	100.00	.10	-2000.00	-2000.000	1.24	-2000.00
	3	150.1	350.0	21.8	355.74	10.00	.20	-2000.00	-2000.000	.54	-2000.00
	4	109.3	430.0	22.2	372.73	3.00	.20	-2000.00	-2000.000	2.71	-2000.00
	5	120.3	710.0	23.8	393.54	100.00	.20	-2000.00	-2000.000	2.36	-2000.00
10350	1	2300.0	880.0	14.7	452.44	100.00	.10	-2000.00	-2000.000	.91	-2000.00
	2	375.0	430.0	24.5	388.56	10.00	.20	-2000.00	-2000.000	1.10	-2000.00
	3	281.2	640.0	26.5	441.50	100.00	.20	-2000.00	-2000.000	1.66	-2000.00
	4	222.2	850.0	23.8	389.44	30.00	.20	-2000.00	-2000.000	2.08	-2000.00
	5	138.7	790.0	21.1	368.56	100.00	.20	-2000.00	-2000.000	2.71	-2000.00
10375	1	684.6	447.0	19.6	325.17	10.00	.20	-2000.00	-2000.000	.77	-2000.00
	2	408.2	801.0	24.0	392.12	30.00	.20	-2000.00	-2000.000	1.37	-2000.00
	3	292.6	1140.0	23.4	376.59	30.00	.20	-2000.00	-2000.000	1.26	-2000.00
	4	136.3	890.0	20.0	340.26	30.00	.20	-2000.00	-2000.000	1.80	-2000.00
	5	83.5	819.0	14.1	441.03	100.00	.10	-2000.00	-2000.000	5.32	-2000.00
10400	1	1417.0	820.0	13.8	430.76	100.00	.10	-2000.00	-2000.000	.92	-2000.00
	2	684.5	1194.0	16.4	284.54	10.00	.20	-2000.00	-2000.000	1.68	-2000.00
	3	357.9	1240.0	15.9	296.34	100.00	.20	-2000.00	-2000.000	1.04	-2000.00
	4	135.0	780.0	12.1	159.88	10.00	.30	-2000.00	-2000.000	3.34	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	115.7	1000.0	13.3	241.32	30.00	.20	-2000.00	-2000.000	2.09	-2000.00
10425	1	2166.0	1360.0	9.2	334.27	.10	.10	-2000.00	-2000.000	2.26	-2000.00
	2	766.5	1444.0	12.0	106.78	3.00	.40	-2000.00	-2000.000	3.37	-2000.00
	3	266.6	1000.0	9.2	174.25	30.00	.20	-2000.00	-2000.000	1.86	-2000.00
	4	167.1	1040.0	10.9	198.89	10.00	.20	-2000.00	-2000.000	1.74	-2000.00
	5	138.5	1300.0	12.4	371.40	10.00	.10	-2000.00	-2000.000	3.72	-2000.00
10450	1	377.4	846.0	9.1	316.07	100.00	.10	-2000.00	-2000.000	2.39	-2000.00
	2	119.4	803.0	7.2	137.58	30.00	.20	-2000.00	-2000.000	9.02	-2000.00
	3	75.1	1009.0	8.3	65.34	3.00	.50	-2000.00	-2000.000	12.10	-2000.00
	4	48.7	1092.0	7.3	92.89	10.00	.50	-2000.00	-2000.000	26.23	-2000.00
	5	27.9	937.0	10.2	184.55	100.00	.30	-2000.00	-2000.000	19.33	-2000.00
10475	1	461.8	966.0	6.6	238.86	1.00	.10	-2000.00	-2000.000	3.89	-2000.00
	2	188.8	1185.0	7.6	269.30	100.00	.10	-2000.00	-2000.000	6.81	-2000.00
	3	108.0	1350.0	8.7	179.96	100.00	.20	-2000.00	-2000.000	19.75	-2000.00
	4	55.0	1151.0	9.9	185.97	30.00	.20	-2000.00	-2000.000	15.67	-2000.00
	5	47.4	1488.0	9.6	124.43	10.00	.30	-2000.00	-2000.000	18.56	-2000.00
10500	1	562.1	1103.0	4.7	178.65	.10	.10	-2000.00	-2000.000	2.23	-2000.00
	2	228.7	1346.0	6.3	230.70	100.00	.10	-2000.00	-2000.000	2.77	-2000.00
	3	102.9	1200.0	8.6	275.01	100.00	.10	-2000.00	-2000.000	7.36	-2000.00
	4	80.7	1584.0	7.7	147.38	30.00	.20	-2000.00	-2000.000	6.91	-2000.00
	5	45.6	1342.0	9.1	171.77	30.00	.20	-2000.00	-2000.000	6.57	-2000.00
10525	1	551.8	1155.0	4.4	169.35	.10	.10	-2000.00	-2000.000	1.85	-2000.00
	2	177.1	1112.0	5.8	215.18	1.00	.10	-2000.00	-2000.000	2.55	-2000.00
	3	125.8	1570.0	5.3	198.32	100.00	.10	-2000.00	-2000.000	4.54	-2000.00
	4	61.4	1285.0	6.9	63.30	1.00	.40	-2000.00	-2000.000	4.89	-2000.00
	5	39.2	1231.0	6.5	238.97	100.00	.10	-2000.00	-2000.000	7.89	-2000.00
10550	1	2440.0	1270.0	4.2	163.73	.10	.10	-2000.00	-2000.000	1.41	-2000.00
	2	1236.0	1940.0	3.8	145.70	1.00	.10	-2000.00	-2000.000	1.69	-2000.00
	3	560.1	1750.0	5.3	98.72	3.00	.20	-2000.00	-2000.000	.94	-2000.00
	4	298.6	1560.0	5.4	199.26	100.00	.10	-2000.00	-2000.000	1.28	-2000.00
	5	204.3	1600.0	5.6	208.18	100.00	.10	-2000.00	-2000.000	1.26	-2000.00
10575	1	2659.0	2310.0	3.8	152.72	.03	.10	-2000.00	-2000.000	1.72	-2000.00
	2	762.4	1994.0	4.6	170.88	3.00	.10	-2000.00	-2000.000	.37	-2000.00
	3	343.9	1790.0	4.6	171.82	100.00	.10	-2000.00	-2000.000	1.32	-2000.00
	4	204.7	1780.0	4.7	174.73	30.00	.10	-2000.00	-2000.000	1.43	-2000.00
	5	132.7	1730.0	5.3	199.73	.30	.10	-2000.00	-2000.000	1.46	-2000.00
10600	1	484.1	1381.0	2.6	71.01	.01	.20	-2000.00	-2000.000	2.81	-2000.00
	2	147.1	1259.0	3.5	145.31	.01	.10	-2000.00	-2000.000	1.13	-2000.00
	3	85.0	1452.0	3.8	147.30	30.00	.10	-2000.00	-2000.000	3.36	-2000.00
	4	48.7	1389.0	4.8	181.43	1.00	.10	-2000.00	-2000.000	2.50	-2000.00
	5	38.6	1654.0	4.9	96.37	10.00	.20	-2000.00	-2000.000	5.03	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10625	1	416.9	1006.0	2.0	43.37	.10	.20	-2000.00	-2000.000	3.33	-2000.00
	2	174.2	1262.0	2.6	109.84	.01	.10	-2000.00	-2000.000	4.29	-2000.00
	3	101.8	1470.0	3.7	138.61	.30	.10	-2000.00	-2000.000	4.67	-2000.00
	4	58.5	1412.0	3.8	141.54	.30	.10	-2000.00	-2000.000	7.69	-2000.00
	5	50.1	1815.0	4.2	165.66	.01	.10	-2000.00	-2000.000	11.11	-2000.00
10650	1	582.0	1405.0	2.2	35.73	.10	.30	-2000.00	-2000.000	2.80	-2000.00
	2	182.7	1323.0	3.3	134.82	.01	.10	-2000.00	-2000.000	2.68	-2000.00
	3	101.7	1470.0	3.2	130.91	.01	.10	-2000.00	-2000.000	5.39	-2000.00
	4	61.0	1472.0	4.0	94.18	.01	.20	-2000.00	-2000.000	7.55	-2000.00
	5	49.7	1800.0	4.7	183.60	.01	.10	-2000.00	-2000.000	8.00	-2000.00
10675	1	979.1	1921.0	2.4	57.58	.03	.20	-2000.00	-2000.000	3.61	-2000.00
	2	293.3	1726.0	2.7	105.70	.30	.10	-2000.00	-2000.000	1.07	-2000.00
	3	169.2	1980.0	3.0	64.89	.10	.20	-2000.00	-2000.000	1.57	-2000.00
	4	84.9	1666.0	3.9	76.43	3.00	.20	-2000.00	-2000.000	2.24	-2000.00
	5	66.5	1957.0	3.2	82.03	.01	.20	-2000.00	-2000.000	2.67	-2000.00
10700	1	1085.0	2000.0	2.1	50.45	.03	.20	-2000.00	-2000.000	2.52	-2000.00
	2	388.5	2152.0	2.6	61.00	.03	.20	-2000.00	-2000.000	1.87	-2000.00
	3	166.4	1840.0	3.3	125.38	30.00	.10	-2000.00	-2000.000	2.20	-2000.00
	4	115.6	2130.0	3.0	121.20	.10	.10	-2000.00	-2000.000	3.15	-2000.00
10725	1	484.0	1680.0	2.0	32.61	.10	.30	-2000.00	-2000.000	2.96	-2000.00
	2	159.3	1660.0	2.6	69.91	.01	.20	-2000.00	-2000.000	4.41	-2000.00
	3	90.0	1870.0	2.2	33.11	.30	.30	-2000.00	-2000.000	7.25	-2000.00
10750	1	743.8	2123.0	2.2	87.30	.10	.10	-2000.00	-2000.000	2.99	-2000.00
	2	259.0	2217.0	2.2	96.06	.01	.10	-2000.00	-2000.000	8.18	-2000.00
10775	1	681.0	1943.0	2.1	56.35	.01	.20	-2000.00	-2000.000	4.12	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1194

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	189.4	174.0	3.9	75.09	1.00	.20	-2000.00	-2000.000	.70	-2000.00
	2	56.3	155.8	6.0	75.28	3.00	.30	-2000.00	-2000.000	.66	-2000.00
	3	28.8	158.0	6.6	82.70	3.00	.30	-2000.00	-2000.000	1.31	-2000.00
	4	13.9	128.0	6.9	87.35	3.00	.30	-2000.00	-2000.000	1.29	-2000.00
	5	8.1	112.5	7.0	131.72	3.00	.20	-2000.00	-2000.000	2.15	-2000.00
10050	1	406.3	212.0	3.6	136.70	3.00	.10	-2000.00	-2000.000	1.53	-2000.00
	2	129.6	203.0	5.8	73.18	3.00	.30	-2000.00	-2000.000	.74	-2000.00
	3	49.5	154.0	6.8	84.77	3.00	.30	-2000.00	-2000.000	1.05	-2000.00
	4	25.0	130.0	7.4	91.91	3.00	.30	-2000.00	-2000.000	1.68	-2000.00
	5	22.1	173.0	8.0	148.45	3.00	.20	-2000.00	-2000.000	2.61	-2000.00
10075	1	353.8	217.0	3.4	129.20	3.00	.10	-2000.00	-2000.000	1.21	-2000.00
	2	86.0	158.9	5.7	108.13	3.00	.20	-2000.00	-2000.000	1.21	-2000.00
	3	43.3	159.0	6.8	86.32	3.00	.30	-2000.00	-2000.000	1.02	-2000.00
	4	28.9	177.0	8.0	75.19	1.00	.40	-2000.00	-2000.000	.96	-2000.00
	5	14.4	132.0	6.9	164.24	.01	.20	-2000.00	-2000.000	4.68	-2000.00
10100	1	280.0	162.0	3.9	75.72	1.00	.20	-2000.00	-2000.000	1.28	-2000.00
	2	93.0	162.2	6.2	78.03	3.00	.30	-2000.00	-2000.000	.97	-2000.00
	3	57.2	199.0	7.7	141.47	3.00	.20	-2000.00	-2000.000	1.24	-2000.00
	4	23.9	138.0	7.5	280.79	.03	.10	-2000.00	-2000.000	2.03	-2000.00
	5	15.8	138.0	6.1	243.39	.01	.10	-2000.00	-2000.000	4.01	-2000.00
10125	1	593.2	232.0	3.7	138.72	10.00	.10	-2000.00	-2000.000	1.12	-2000.00
	2	220.5	259.0	6.1	77.45	1.00	.30	-2000.00	-2000.000	1.18	-2000.00
	3	84.6	198.0	6.6	84.93	1.00	.30	-2000.00	-2000.000	1.01	-2000.00
	4	38.7	151.0	6.0	83.87	.30	.30	-2000.00	-2000.000	1.47	-2000.00
	5	31.0	182.0	4.1	45.26	.30	.40	-2000.00	-2000.000	3.14	-2000.00
10150	1	722.2	348.0	3.4	73.42	.10	.20	-2000.00	-2000.000	1.43	-2000.00
	2	167.3	242.0	4.9	97.75	.30	.20	-2000.00	-2000.000	.93	-2000.00
	3	50.8	146.0	5.9	80.14	.30	.30	-2000.00	-2000.000	1.94	-2000.00
	4	34.0	164.0	4.4	112.73	.01	.20	-2000.00	-2000.000	2.98	-2000.00
	5	19.2	139.0	1.9	36.22	.03	.40	-2000.00	-2000.000	11.08	-2000.00
10175	1	1189.0	540.0	1.8	48.43	.01	.20	-2000.00	-2000.000	2.98	-2000.00
	2	119.6	165.0	4.8	96.72	.30	.20	-2000.00	-2000.000	.47	-2000.00
	3	64.3	177.0	4.2	45.61	.30	.40	-2000.00	-2000.000	2.50	-2000.00
	4	30.6	141.0	2.5	27.49	.30	.40	-2000.00	-2000.000	4.82	-2000.00
	5	25.5	176.0	1.7	15.28	.30	.60	-2000.00	-2000.000	6.85	-2000.00
10200	1	782.0	299.0	2.0	47.36	.03	.20	-2000.00	-2000.000	1.59	-2000.00
	2	189.0	217.0	3.5	38.95	.30	.40	-2000.00	-2000.000	1.15	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	71.4	163.0	2.3	50.75	.10	.20	-2000.00	-2000.000	3.27	-2000.00
	4	47.6	182.0	1.6	24.49	.10	.50	-2000.00	-2000.000	13.00	-2000.00
	5	45.6	261.0	2.5	25.21	.30	.50	-2000.00	-2000.000	4.54	-2000.00
10225	1	816.6	523.0	1.7	47.88	.01	.20	-2000.00	-2000.000	4.76	-2000.00
	2	141.8	272.0	1.6	23.43	.30	.30	-2000.00	-2000.000	3.08	-2000.00
	3	60.8	233.0	1.5	42.08	.01	.20	-2000.00	-2000.000	5.02	-2000.00
	4	46.6	298.0	2.5	21.15	.30	.60	-2000.00	-2000.000	6.15	-2000.00
	5	56.3	540.0	1.9	17.45	.30	.60	-2000.00	-2000.000	14.08	-2000.00
10250	1	1751.0	640.0	1.3	32.76	.03	.20	-2000.00	-2000.000	5.55	-2000.00
	2	370.4	410.0	1.2	32.34	.03	.20	-2000.00	-2000.000	13.63	-2000.00
	3	217.5	480.0	3.0	48.75	.10	.30	-2000.00	-2000.000	1.11	-2000.00
	4	197.8	730.0	3.0	57.02	.03	.30	-2000.00	-2000.000	2.04	-2000.00
	5	104.1	570.0	7.5	274.69	.10	.10	-2000.00	-2000.000	1.71	-2000.00
10275	1	1263.0	490.0	1.4	38.90	.01	.20	-2000.00	-2000.000	7.10	-2000.00
	2	521.5	614.0	3.4	55.60	.10	.30	-2000.00	-2000.000	2.08	-2000.00
	3	418.1	980.0	3.1	81.21	.01	.20	-2000.00	-2000.000	2.11	-2000.00
	4	182.8	710.0	8.3	157.98	.30	.20	-2000.00	-2000.000	2.01	-2000.00
	5	103.6	600.0	15.5	261.94	3.00	.20	-2000.00	-2000.000	2.11	-2000.00
10300	1	837.2	477.0	4.9	104.01	.10	.20	-2000.00	-2000.000	1.95	-2000.00
	2	461.0	789.0	3.9	102.73	.01	.20	-2000.00	-2000.000	1.31	-2000.00
	3	220.9	750.0	8.8	301.19	1.00	.10	-2000.00	-2000.000	2.20	-2000.00
	4	97.1	554.0	16.6	276.85	10.00	.20	-2000.00	-2000.000	3.91	-2000.00
	5	31.6	270.0	16.1	277.77	10.00	.20	-2000.00	-2000.000	6.59	-2000.00
10325	1	1287.0	790.0	5.3	121.95	.03	.20	-2000.00	-2000.000	1.69	-2000.00
	2	432.0	797.0	11.6	379.37	10.00	.10	-2000.00	-2000.000	.59	-2000.00
	3	157.6	580.0	18.7	322.52	30.00	.20	-2000.00	-2000.000	1.39	-2000.00
	4	48.0	295.0	18.8	322.57	30.00	.20	-2000.00	-2000.000	1.57	-2000.00
	5	43.8	404.0	12.9	257.68	100.00	.20	-2000.00	-2000.000	2.95	-2000.00
10350	1	268.4	930.0	12.0	399.74	1.00	.10	-2000.00	-2000.000	4.29	-2000.00
	2	60.3	631.0	20.3	362.11	100.00	.20	-2000.00	-2000.000	11.79	-2000.00
	3	18.4	380.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	4	9.6	333.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	8.9	465.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10375	1	1302.0	670.0	16.8	289.42	10.00	.20	-2000.00	-2000.000	1.21	-2000.00
	2	275.5	425.0	19.5	332.05	30.00	.20	-2000.00	-2000.000	1.19	-2000.00
	3	190.2	580.0	19.3	327.20	30.00	.20	-2000.00	-2000.000	1.87	-2000.00
	4	151.3	770.0	20.0	346.90	100.00	.20	-2000.00	-2000.000	2.95	-2000.00
	5	109.1	840.0	15.6	191.59	3.00	.30	-2000.00	-2000.000	5.20	-2000.00
10400	1	1574.0	610.0	12.8	229.04	10.00	.20	-2000.00	-2000.000	1.14	-2000.00
	2	639.2	752.0	15.0	261.61	10.00	.20	-2000.00	-2000.000	.94	-2000.00
	3	528.2	1240.0	15.8	279.19	30.00	.20	-2000.00	-2000.000	1.48	-2000.00
	4	258.2	1010.0	14.3	273.90	100.00	.20	-2000.00	-2000.000	1.88	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	187.7	1100.0	15.0	260.92	10.00	.20	-2000.00	-2000.000	1.84	-2000.00
10425	1	1746.0	740.0	8.8	305.33	1.00	.10	-2000.00	-2000.000	1.08	-2000.00
	2	965.7	1229.0	10.8	357.77	30.00	.10	-2000.00	-2000.000	.99	-2000.00
	3	523.2	1320.0	10.5	190.75	10.00	.20	-2000.00	-2000.000	1.66	-2000.00
	4	300.5	1270.0	12.0	215.43	10.00	.20	-2000.00	-2000.000	1.68	-2000.00
	5	241.3	1530.0	13.4	244.90	30.00	.20	-2000.00	-2000.000	1.64	-2000.00
10450	1	2203.0	1210.0	7.4	155.53	.10	.20	-2000.00	-2000.000	1.54	-2000.00
	2	682.1	1127.0	7.1	251.64	30.00	.10	-2000.00	-2000.000	.71	-2000.00
	3	403.9	1330.0	8.7	299.63	100.00	.10	-2000.00	-2000.000	.83	-2000.00
	4	277.0	1520.0	9.9	192.90	30.00	.20	-2000.00	-2000.000	3.09	-2000.00
	5	171.9	1420.0	10.7	197.60	3.00	.20	-2000.00	-2000.000	3.06	-2000.00
10475	1	1211.0	950.0	4.7	193.36	.01	.10	-2000.00	-2000.000	1.22	-2000.00
	2	466.4	1098.0	6.6	248.84	.10	.10	-2000.00	-2000.000	2.61	-2000.00
	3	350.6	1640.0	7.8	166.39	100.00	.20	-2000.00	-2000.000	2.76	-2000.00
	4	172.2	1350.0	9.0	168.42	3.00	.20	-2000.00	-2000.000	3.82	-2000.00
	5	141.9	1670.0	8.9	176.65	30.00	.20	-2000.00	-2000.000	4.54	-2000.00
10500	1	472.1	871.0	3.7	97.40	.03	.20	-2000.00	-2000.000	6.34	-2000.00
	2	229.7	1272.0	7.3	124.85	10.00	.20	-2000.00	-2000.000	8.09	-2000.00
	3	123.3	1360.0	6.4	90.01	3.00	.30	-2000.00	-2000.000	11.36	-2000.00
	4	85.1	1572.0	7.4	162.15	100.00	.20	-2000.00	-2000.000	9.62	-2000.00
	5	57.8	1600.0	7.9	79.23	3.00	.40	-2000.00	-2000.000	14.34	-2000.00
10525	1	348.5	1094.0	3.7	98.41	.01	.20	-2000.00	-2000.000	4.18	-2000.00
	2	138.6	1305.0	5.2	192.82	3.00	.10	-2000.00	-2000.000	3.12	-2000.00
	3	89.0	1672.0	5.7	207.50	3.00	.10	-2000.00	-2000.000	4.19	-2000.00
	4	50.2	1575.0	6.1	139.75	.03	.20	-2000.00	-2000.000	8.38	-2000.00
	5	24.9	1173.0	8.1	163.64	100.00	.20	-2000.00	-2000.000	6.70	-2000.00
10550	1	589.7	1234.0	3.6	82.47	.03	.20	-2000.00	-2000.000	1.74	-2000.00
	2	290.8	1826.0	4.5	173.80	.10	.10	-2000.00	-2000.000	2.13	-2000.00
	3	144.4	1800.0	5.0	39.36	.30	.60	-2000.00	-2000.000	10.83	-2000.00
	4	62.4	1306.0	6.4	229.10	100.00	.10	-2000.00	-2000.000	3.75	-2000.00
	5	48.3	1515.0	6.6	133.06	30.00	.20	-2000.00	-2000.000	7.16	-2000.00
10575	1	805.8	2108.0	3.0	126.65	.01	.10	-2000.00	-2000.000	3.50	-2000.00
	2	193.0	1515.0	4.3	31.78	1.00	.50	-2000.00	-2000.000	2.96	-2000.00
	3	90.3	1415.0	4.6	96.30	10.00	.20	-2000.00	-2000.000	3.57	-2000.00
	4	57.1	1493.0	5.4	203.41	100.00	.10	-2000.00	-2000.000	3.30	-2000.00
	5	46.5	1823.0	5.4	107.17	3.00	.20	-2000.00	-2000.000	6.97	-2000.00
10600	1	924.7	1528.0	2.5	64.57	.01	.20	-2000.00	-2000.000	2.87	-2000.00
	2	249.2	1235.0	3.8	144.50	.30	.10	-2000.00	-2000.000	3.39	-2000.00
	3	148.2	1460.0	2.8	23.71	.30	.60	-2000.00	-2000.000	6.34	-2000.00
	4	110.9	1830.0	5.9	104.04	100.00	.30	-2000.00	-2000.000	8.29	-2000.00
	5	71.5	1772.0	4.4	93.51	10.00	.20	-2000.00	-2000.000	12.81	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10625	1	270.8	773.0	2.5	58.10	.03	.20	-2000.00	-2000.000	3.06	-2000.00
	2	134.9	1155.0	3.1	131.48	.01	.10	-2000.00	-2000.000	3.91	-2000.00
	3	95.6	1633.0	3.4	139.41	.03	.10	-2000.00	-2000.000	7.04	-2000.00
	4	55.3	1579.0	3.5	141.00	.10	.10	-2000.00	-2000.000	10.14	-2000.00
	5	34.7	1485.0	3.7	145.19	30.00	.10	-2000.00	-2000.000	16.80	-2000.00
10650	1	661.9	1222.0	2.8	73.13	.01	.20	-2000.00	-2000.000	1.93	-2000.00
	2	299.7	1660.0	3.1	50.17	.10	.30	-2000.00	-2000.000	2.09	-2000.00
	3	169.2	1870.0	2.9	46.61	.10	.30	-2000.00	-2000.000	1.82	-2000.00
	4	85.6	1581.0	2.9	23.67	.30	.60	-2000.00	-2000.000	5.03	-2000.00
	5	76.2	2110.0	3.0	26.58	.30	.60	-2000.00	-2000.000	3.08	-2000.00
10675	1	729.6	1431.0	3.0	65.51	.10	.20	-2000.00	-2000.000	1.92	-2000.00
	2	249.6	1469.0	3.3	139.30	.01	.10	-2000.00	-2000.000	3.63	-2000.00
	3	153.8	1800.0	3.4	47.53	10.00	.30	-2000.00	-2000.000	5.38	-2000.00
	4	99.7	1955.0	3.9	85.42	30.00	.20	-2000.00	-2000.000	7.06	-2000.00
	5	47.9	1408.0	4.4	68.05	30.00	.30	-2000.00	-2000.000	11.01	-2000.00
10700	1	942.1	1643.0	2.3	56.02	.03	.20	-2000.00	-2000.000	3.51	-2000.00
	2	367.8	1924.0	2.8	111.23	100.00	.10	-2000.00	-2000.000	2.15	-2000.00
	3	204.7	2130.0	3.3	127.17	.30	.10	-2000.00	-2000.000	3.47	-2000.00
	4	83.5	1456.0	3.3	128.63	.30	.10	-2000.00	-2000.000	6.57	-2000.00
10725	1	732.2	1532.0	1.9	52.03	.01	.20	-2000.00	-2000.000	2.51	-2000.00
	2	354.2	2224.0	2.6	69.88	.01	.20	-2000.00	-2000.000	2.24	-2000.00
	3	132.5	1660.0	2.6	111.01	.10	.10	-2000.00	-2000.000	6.63	-2000.00
10750	1	916.8	2398.0	2.3	60.67	.01	.20	-2000.00	-2000.000	2.42	-2000.00
	2	229.2	1799.0	2.2	58.18	.01	.20	-2000.00	-2000.000	4.81	-2000.00
10775	1	342.7	1530.0	1.9	52.06	.01	.20	-2000.00	-2000.000	4.57	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1204

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	267.6	129.0	6.6	126.04	10.00	.20	-2000.00	-2000.000	.97	-2000.00
	2	68.7	99.6	7.8	147.24	10.00	.20	-2000.00	-2000.000	1.22	-2000.00
	3	40.1	116.0	6.3	79.88	1.00	.30	-2000.00	-2000.000	1.06	-2000.00
	4	21.5	104.0	5.9	213.38	10.00	.10	-2000.00	-2000.000	1.28	-2000.00
	5	17.3	125.0	5.7	53.63	1.00	.40	-2000.00	-2000.000	3.71	-2000.00
10050	1	231.6	134.0	7.8	95.27	3.00	.30	-2000.00	-2000.000	1.47	-2000.00
	2	85.9	149.8	6.3	232.08	1.00	.10	-2000.00	-2000.000	1.72	-2000.00
	3	40.3	140.0	6.5	61.59	1.00	.40	-2000.00	-2000.000	1.28	-2000.00
	4	26.9	156.0	6.4	81.39	1.00	.30	-2000.00	-2000.000	2.70	-2000.00
	5	16.4	142.0	6.7	275.08	.01	.10	-2000.00	-2000.000	3.62	-2000.00
10075	1	406.1	212.0	5.4	104.69	10.00	.20	-2000.00	-2000.000	.62	-2000.00
	2	104.0	163.0	6.3	117.36	3.00	.20	-2000.00	-2000.000	1.72	-2000.00
	3	55.5	173.0	6.5	61.01	1.00	.40	-2000.00	-2000.000	.69	-2000.00
	4	29.6	154.0	7.7	97.15	1.00	.30	-2000.00	-2000.000	1.04	-2000.00
	5	14.5	113.0	7.1	97.88	.30	.30	-2000.00	-2000.000	1.80	-2000.00
10100	1	307.4	175.0	5.0	94.79	3.00	.20	-2000.00	-2000.000	.99	-2000.00
	2	111.0	190.0	6.4	60.35	1.00	.40	-2000.00	-2000.000	1.30	-2000.00
	3	48.3	164.0	7.6	147.99	.30	.20	-2000.00	-2000.000	1.67	-2000.00
	4	20.7	118.0	7.9	108.03	.30	.30	-2000.00	-2000.000	2.29	-2000.00
	5	15.0	128.0	5.0	46.35	.30	.50	-2000.00	-2000.000	3.87	-2000.00
10125	1	488.6	187.0	5.0	64.09	1.00	.30	-2000.00	-2000.000	.75	-2000.00
	2	128.0	147.0	7.5	94.93	1.00	.30	-2000.00	-2000.000	.54	-2000.00
	3	46.0	105.0	7.9	154.05	.30	.20	-2000.00	-2000.000	1.28	-2000.00
	4	30.1	115.0	6.2	86.52	.30	.30	-2000.00	-2000.000	1.42	-2000.00
	5	26.5	152.0	4.0	93.24	.03	.20	-2000.00	-2000.000	2.88	-2000.00
10150	1	365.8	201.0	5.7	112.81	.30	.20	-2000.00	-2000.000	.88	-2000.00
	2	75.7	125.0	7.4	145.08	.30	.20	-2000.00	-2000.000	1.38	-2000.00
	3	39.7	131.0	6.1	84.87	.30	.30	-2000.00	-2000.000	1.97	-2000.00
	4	29.8	164.0	4.3	47.19	.30	.40	-2000.00	-2000.000	3.33	-2000.00
	5	25.8	213.0	1.9	16.73	.30	.60	-2000.00	-2000.000	7.30	-2000.00
10175	1	310.7	162.0	5.1	107.11	.10	.20	-2000.00	-2000.000	1.07	-2000.00
	2	95.4	149.7	5.6	77.65	.30	.30	-2000.00	-2000.000	1.28	-2000.00
	3	55.7	174.0	4.3	47.24	.30	.40	-2000.00	-2000.000	1.92	-2000.00
	4	40.6	212.0	2.4	19.05	.30	.60	-2000.00	-2000.000	6.03	-2000.00
	5	18.4	144.0	.3	44.90	1.00	.10	-2000.00	-2000.000	57.79	-2000.00
10200	1	333.7	275.0	2.8	46.01	.10	.30	-2000.00	-2000.000	1.62	-2000.00
	2	90.2	223.6	3.9	43.74	.30	.40	-2000.00	-2000.000	1.08	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	48.8	241.0	2.8	54.58	.03	.30	-2000.00	-2000.000	2.84	-2000.00
	4	18.5	152.0	1.6	24.27	.10	.40	-2000.00	-2000.000	9.69	-2000.00
	5	25.9	321.0	1.3	38.68	.01	.30	-2000.00	-2000.000	14.42	-2000.00
10225	1	524.1	365.0	2.1	55.87	.01	.20	-2000.00	-2000.000	1.41	-2000.00
	2	136.7	286.0	2.2	59.56	.01	.20	-2000.00	-2000.000	2.08	-2000.00
	3	39.4	164.0	1.2	27.40	.03	.30	-2000.00	-2000.000	14.07	-2000.00
	4	42.2	294.0	1.6	42.20	.01	.30	-2000.00	-2000.000	11.43	-2000.00
	5	52.0	544.0	5.6	210.25	.10	.10	-2000.00	-2000.000	9.09	-2000.00
10250	1	749.4	522.0	1.6	42.73	.01	.20	-2000.00	-2000.000	2.63	-2000.00
	2	136.7	286.0	.8	27.18	100.00	.20	-2000.00	-2000.000	25.63	-2000.00
	3	102.4	420.0	1.0	34.21	.01	.20	-2000.00	-2000.000	22.48	-2000.00
	4	99.6	695.0	5.7	78.56	.30	.30	-2000.00	-2000.000	6.48	-2000.00
	5	36.5	382.0	2.5	60.84	.01	.30	-2000.00	-2000.000	21.00	-2000.00
10275	1	438.0	319.0	1.1	53.23	.10	.10	-2000.00	-2000.000	11.27	-2000.00
	2	215.4	471.0	1.1	35.68	.01	.20	-2000.00	-2000.000	14.34	-2000.00
	3	173.8	750.0	6.1	241.23	.01	.10	-2000.00	-2000.000	.95	-2000.00
	4	68.6	500.0	4.2	96.09	.10	.20	-2000.00	-2000.000	4.31	-2000.00
	5	31.6	346.0	10.6	352.80	100.00	.10	-2000.00	-2000.000	2.50	-2000.00
10300	1	1134.0	640.0	1.7	34.11	.03	.30	-2000.00	-2000.000	1.52	-2000.00
	2	548.8	939.0	7.1	256.39	.30	.10	-2000.00	-2000.000	.72	-2000.00
	3	184.2	620.0	5.1	189.83	1.00	.10	-2000.00	-2000.000	.95	-2000.00
	4	76.9	438.0	11.1	202.66	10.00	.20	-2000.00	-2000.000	1.31	-2000.00
	5	35.2	301.0	12.3	393.95	30.00	.10	-2000.00	-2000.000	1.26	-2000.00
10325	1	1435.0	900.0	8.9	308.94	1.00	.10	-2000.00	-2000.000	1.06	-2000.00
	2	318.0	599.0	7.3	259.35	30.00	.10	-2000.00	-2000.000	.96	-2000.00
	3	124.5	460.0	12.9	230.71	10.00	.20	-2000.00	-2000.000	.98	-2000.00
	4	45.3	284.0	14.0	248.07	10.00	.20	-2000.00	-2000.000	1.95	-2000.00
	5	35.1	330.0	13.8	240.53	10.00	.20	-2000.00	-2000.000	3.35	-2000.00
10350	1	1000.0	620.0	9.4	320.83	100.00	.10	-2000.00	-2000.000	1.20	-2000.00
	2	325.3	612.0	16.4	280.61	10.00	.20	-2000.00	-2000.000	1.16	-2000.00
	3	112.4	420.0	17.1	300.07	30.00	.20	-2000.00	-2000.000	1.36	-2000.00
	4	68.4	429.0	17.0	301.42	30.00	.20	-2000.00	-2000.000	2.11	-2000.00
	5	46.4	436.0	15.7	282.74	30.00	.20	-2000.00	-2000.000	2.71	-2000.00
10375	1	1555.0	1160.0	12.0	389.29	100.00	.10	-2000.00	-2000.000	.91	-2000.00
	2	320.5	718.0	15.8	271.89	10.00	.20	-2000.00	-2000.000	1.12	-2000.00
	3	178.7	790.0	16.2	284.53	10.00	.20	-2000.00	-2000.000	1.69	-2000.00
	4	86.9	649.0	16.0	284.04	10.00	.20	-2000.00	-2000.000	2.50	-2000.00
	5	101.5	1130.0	16.5	291.37	30.00	.20	-2000.00	-2000.000	1.36	-2000.00
10400	1	1193.0	740.0	15.0	282.19	100.00	.20	-2000.00	-2000.000	4.83	-2000.00
	2	455.0	857.0	13.9	245.11	10.00	.20	-2000.00	-2000.000	1.27	-2000.00
	3	218.0	810.0	13.8	241.88	10.00	.20	-2000.00	-2000.000	1.57	-2000.00
	4	195.8	1220.0	14.2	257.39	30.00	.20	-2000.00	-2000.000	1.78	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	99.5	937.0	14.1	243.46	10.00	.20	-2000.00	-2000.000	2.12	-2000.00
10425	1	1588.0	830.0	8.2	292.24	.30	.10	-2000.00	-2000.000	1.00	-2000.00
	2	525.9	825.0	9.8	330.78	100.00	.10	-2000.00	-2000.000	1.33	-2000.00
	3	468.7	1460.0	11.3	201.68	10.00	.20	-2000.00	-2000.000	1.33	-2000.00
	4	258.5	1350.0	11.9	210.45	3.00	.20	-2000.00	-2000.000	1.23	-2000.00
	5	176.2	1380.0	13.1	235.38	10.00	.20	-2000.00	-2000.000	1.46	-2000.00
10450	1	1078.0	630.0	5.9	124.59	.10	.20	-2000.00	-2000.000	1.35	-2000.00
	2	671.6	1193.0	7.7	270.77	10.00	.10	-2000.00	-2000.000	1.58	-2000.00
	3	342.7	1210.0	8.9	306.75	100.00	.10	-2000.00	-2000.000	1.12	-2000.00
	4	215.1	1270.0	10.7	197.26	10.00	.20	-2000.00	-2000.000	1.58	-2000.00
	5	182.5	1620.0	10.9	204.53	30.00	.20	-2000.00	-2000.000	2.25	-2000.00
10475	1	2164.0	1230.0	5.7	120.43	.10	.20	-2000.00	-2000.000	1.64	-2000.00
	2	690.6	1182.0	6.6	245.58	.10	.10	-2000.00	-2000.000	1.05	-2000.00
	3	413.2	1410.0	8.7	160.07	10.00	.20	-2000.00	-2000.000	1.72	-2000.00
	4	293.9	1670.0	8.8	168.35	30.00	.20	-2000.00	-2000.000	2.49	-2000.00
	5	251.5	2150.0	9.3	176.05	10.00	.20	-2000.00	-2000.000	1.84	-2000.00
10500	1	1145.0	870.0	4.6	187.70	.01	.10	-2000.00	-2000.000	1.38	-2000.00
	2	534.8	1228.0	6.8	243.75	30.00	.10	-2000.00	-2000.000	1.05	-2000.00
	3	358.1	1640.0	7.2	134.17	10.00	.20	-2000.00	-2000.000	2.20	-2000.00
	4	279.5	2140.0	8.1	150.65	10.00	.20	-2000.00	-2000.000	2.13	-2000.00
	5	158.9	1820.0	8.0	288.69	100.00	.10	-2000.00	-2000.000	3.42	-2000.00
10525	1	1476.0	1020.0	4.7	190.43	.01	.10	-2000.00	-2000.000	1.56	-2000.00
	2	762.0	1595.0	4.9	183.57	30.00	.10	-2000.00	-2000.000	1.54	-2000.00
	3	593.3	2470.0	6.1	117.06	10.00	.20	-2000.00	-2000.000	1.89	-2000.00
	4	289.6	2020.0	6.6	127.88	10.00	.20	-2000.00	-2000.000	3.67	-2000.00
	5	131.4	1370.0	6.6	242.33	100.00	.10	-2000.00	-2000.000	1.30	-2000.00
10550	1	1267.0	970.0	4.0	154.42	.10	.10	-2000.00	-2000.000	1.29	-2000.00
	2	785.5	1804.0	5.2	195.11	100.00	.10	-2000.00	-2000.000	1.26	-2000.00
	3	368.4	1680.0	6.1	214.86	100.00	.10	-2000.00	-2000.000	2.80	-2000.00
	4	153.2	1170.0	5.7	111.79	10.00	.20	-2000.00	-2000.000	2.31	-2000.00
	5	112.3	1290.0	6.7	133.09	10.00	.20	-2000.00	-2000.000	3.34	-2000.00
10575	1	2953.0	2060.0	3.7	150.85	.01	.10	-2000.00	-2000.000	1.28	-2000.00
	2	962.5	2014.0	4.3	159.89	1.00	.10	-2000.00	-2000.000	1.10	-2000.00
	3	343.0	1430.0	4.5	165.89	30.00	.10	-2000.00	-2000.000	2.02	-2000.00
	4	199.5	1390.0	5.5	201.92	1.00	.10	-2000.00	-2000.000	1.40	-2000.00
	5	106.9	1110.0	5.3	190.44	10.00	.10	-2000.00	-2000.000	1.79	-2000.00
10600	1	1972.0	1510.0	2.7	114.01	.01	.10	-2000.00	-2000.000	2.14	-2000.00
	2	544.4	1250.0	3.1	123.51	.10	.10	-2000.00	-2000.000	1.27	-2000.00
	3	320.0	1460.0	4.2	90.53	.10	.20	-2000.00	-2000.000	1.11	-2000.00
	4	132.1	1010.0	3.9	151.19	.30	.10	-2000.00	-2000.000	.84	-2000.00
	5	152.5	1750.0	4.5	91.16	.30	.20	-2000.00	-2000.000	.50	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10625	1	1211.0	950.0	1.5	36.86	.03	.20	-2000.00	-2000.000	8.08	-2000.00
	2	499.0	1175.0	3.1	132.38	.01	.10	-2000.00	-2000.000	1.73	-2000.00
	3	274.7	1290.0	2.9	115.54	.10	.10	-2000.00	-2000.000	2.17	-2000.00
	4	231.5	1810.0	3.5	138.40	.10	.10	-2000.00	-2000.000	2.00	-2000.00
	5	180.1	2120.0	4.1	155.69	10.00	.10	-2000.00	-2000.000	2.04	-2000.00
10650	1	1962.0	1460.0	3.2	69.75	.10	.20	-2000.00	-2000.000	2.33	-2000.00
	2	496.2	1112.0	2.6	110.79	.01	.10	-2000.00	-2000.000	3.23	-2000.00
	3	441.0	1970.0	3.2	68.76	.10	.20	-2000.00	-2000.000	2.44	-2000.00
	4	296.2	2210.0	3.7	146.69	.10	.10	-2000.00	-2000.000	2.33	-2000.00
	5	202.4	2260.0	3.7	153.95	.01	.10	-2000.00	-2000.000	4.41	-2000.00
10675	1	1598.0	1190.0	2.4	52.00	.10	.20	-2000.00	-2000.000	2.55	-2000.00
	2	860.4	1929.0	3.0	65.78	.10	.20	-2000.00	-2000.000	1.85	-2000.00
	3	633.9	2830.0	3.4	133.98	.10	.10	-2000.00	-2000.000	1.83	-2000.00
	4	306.4	2290.0	3.5	140.56	.03	.10	-2000.00	-2000.000	1.94	-2000.00
	5	224.7	2510.0	3.9	78.96	.30	.20	-2000.00	-2000.000	3.01	-2000.00
10700	1	3367.0	2850.0	3.1	73.05	.03	.20	-2000.00	-2000.000	1.25	-2000.00
	2	1363.0	3470.0	3.3	139.15	.01	.10	-2000.00	-2000.000	1.74	-2000.00
	3	483.3	2450.0	3.3	137.76	.01	.10	-2000.00	-2000.000	1.65	-2000.00
	4	321.2	2720.0	3.8	153.53	.01	.10	-2000.00	-2000.000	1.87	-2000.00
10725	1	2194.0	1960.0	2.8	61.13	.10	.20	-2000.00	-2000.000	2.35	-2000.00
	2	598.7	1611.0	2.8	115.71	.01	.50	-2000.00	-2000.000	17.31	-2000.00
	3	579.1	3110.0	3.1	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10750	1	2256.0	1600.0	1.9	79.22	.01	.10	-2000.00	-2000.000	2.69	-2000.00
	2	871.1	1864.0	3.0	124.75	.01	.10	-2000.00	-2000.000	2.58	-2000.00
10775	1	2206.0	1730.0	2.4	56.75	.03	.20	-2000.00	-2000.000	1.68	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1214

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	217.4	124.0	5.1	107.18	.10	.20	-2000.00	-2000.000	1.08	-2000.00
	2	83.3	142.6	5.9	75.66	1.00	.30	-2000.00	-2000.000	1.23	-2000.00
	3	36.0	123.0	5.6	113.18	.30	.20	-2000.00	-2000.000	1.86	-2000.00
	4	16.8	96.0	3.7	80.73	.10	.20	-2000.00	-2000.000	3.03	-2000.00
	5	16.7	142.0	4.2	60.40	.30	.30	-2000.00	-2000.000	3.33	-2000.00
10050	1	322.0	146.0	5.5	109.78	.30	.20	-2000.00	-2000.000	.71	-2000.00
	2	96.3	131.4	6.0	126.00	.10	.20	-2000.00	-2000.000	1.62	-2000.00
	3	38.8	105.0	3.4	54.02	.10	.30	-2000.00	-2000.000	2.59	-2000.00
	4	33.6	153.0	4.2	99.31	.03	.20	-2000.00	-2000.000	1.82	-2000.00
	5	19.5	133.0	3.8	62.22	.10	.30	-2000.00	-2000.000	4.54	-2000.00
10075	1	504.1	105.5	7.2	91.44	1.00	.30	-2000.00	-2000.000	.91	-2000.00
	2	150.3	94.3	4.0	64.24	.10	.30	-2000.00	-2000.000	.98	-2000.00
	3	119.0	149.0	4.6	117.13	.01	.20	-2000.00	-2000.000	1.53	-2000.00
	4	56.5	118.2	4.5	117.53	.01	.20	-2000.00	-2000.000	1.44	-2000.00
	5	35.2	110.5	4.9	54.17	.30	.40	-2000.00	-2000.000	1.41	-2000.00
10100	1	266.5	105.0	5.3	123.08	.03	.20	-2000.00	-2000.000	.85	-2000.00
	2	98.0	116.8	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	3	97.8	232.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	4	30.7	121.0	5.7	133.46	.03	.20	-2000.00	-2000.000	1.14	-2000.00
	5	19.8	117.0	6.1	67.49	.30	.40	-2000.00	-2000.000	1.87	-2000.00
10125	1	486.3	254.0	5.8	232.80	.01	.10	-2000.00	-2000.000	.91	-2000.00
	2	95.9	150.6	6.3	145.61	.03	.20	-2000.00	-2000.000	.81	-2000.00
	3	42.4	132.0	6.4	164.34	.01	.20	-2000.00	-2000.000	1.30	-2000.00
	4	24.6	128.0	7.1	111.03	.10	.30	-2000.00	-2000.000	1.37	-2000.00
	5	22.4	175.0	3.3	61.67	.03	.40	-2000.00	-2000.000	5.35	-2000.00
10150	1	221.2	115.0	5.6	89.82	.10	.30	-2000.00	-2000.000	.88	-2000.00
	2	70.9	111.3	6.4	100.61	.10	.30	-2000.00	-2000.000	.98	-2000.00
	3	37.2	116.0	6.8	128.77	.03	.30	-2000.00	-2000.000	2.04	-2000.00
	4	29.0	151.0	3.5	49.72	.10	.40	-2000.00	-2000.000	2.87	-2000.00
	5	26.2	205.0	2.8	31.03	.30	.40	-2000.00	-2000.000	8.12	-2000.00
10175	1	412.5	147.0	6.2	86.25	.30	.30	-2000.00	-2000.000	.51	-2000.00
	2	138.5	148.0	6.9	108.68	.10	.30	-2000.00	-2000.000	.92	-2000.00
	3	84.6	180.0	3.8	53.78	.10	.40	-2000.00	-2000.000	1.12	-2000.00
	4	58.6	208.0	2.7	38.89	.10	.40	-2000.00	-2000.000	2.09	-2000.00
	5	30.5	163.0	1.2	36.01	.01	.30	-2000.00	-2000.000	14.66	-2000.00
10200	1	386.9	192.0	8.5	212.83	.01	.20	-2000.00	-2000.000	.65	-2000.00
	2	114.3	170.0	4.6	88.78	.03	.30	-2000.00	-2000.000	1.47	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	63.7	190.0	3.2	45.77	.10	.40	-2000.00	-2000.000	2.04	-2000.00
	4	29.6	147.0	1.7	34.00	.03	.40	-2000.00	-2000.000	9.93	-2000.00
	5	32.5	243.0	1.6	47.99	.01	.40	-2000.00	-2000.000	14.99	-2000.00
10225	1	399.1	171.0	5.2	83.19	.10	.30	-2000.00	-2000.000	.46	-2000.00
	2	143.3	184.0	3.9	76.93	.03	.30	-2000.00	-2000.000	1.47	-2000.00
	3	56.3	145.0	2.2	19.53	.30	.60	-2000.00	-2000.000	4.45	-2000.00
	4	51.3	220.0	1.7	25.71	.10	.50	-2000.00	-2000.000	10.17	-2000.00
	5	85.0	548.0	1.5	14.88	.30	.60	-2000.00	-2000.000	17.31	-2000.00
10250	1	371.0	270.0	2.0	45.95	.01	.30	-2000.00	-2000.000	5.37	-2000.00
	2	83.3	182.4	1.4	30.30	.03	.40	-2000.00	-2000.000	7.27	-2000.00
	3	49.0	214.0	1.5	47.30	.01	.40	-2000.00	-2000.000	16.27	-2000.00
	4	69.4	506.0	1.7	49.22	.01	.40	-2000.00	-2000.000	10.46	-2000.00
	5	36.8	402.0	5.3	96.89	.03	.30	-2000.00	-2000.000	5.47	-2000.00
10275	1	1007.0	440.0	.8	46.35	30.00	.10	-2000.00	-2000.000	22.56	-2000.00
	2	283.6	376.0	.8	33.23	.01	.20	-2000.00	-2000.000	29.01	-2000.00
	3	295.4	780.0	1.2	34.91	.01	.30	-2000.00	-2000.000	17.85	-2000.00
	4	121.3	530.0	5.9	134.74	.03	.20	-2000.00	-2000.000	3.48	-2000.00
	5	35.9	238.0	13.2	160.29	1.00	.30	-2000.00	-2000.000	4.01	-2000.00
10300	1	736.9	525.0	1.4	43.20	.01	.40	-2000.00	-2000.000	5.32	-2000.00
	2	448.3	959.0	1.8	51.88	.01	.40	-2000.00	-2000.000	2.38	-2000.00
	3	174.1	740.0	6.1	139.74	.03	.20	-2000.00	-2000.000	2.34	-2000.00
	4	34.3	244.0	13.7	429.74	100.00	.10	-2000.00	-2000.000	1.77	-2000.00
	5	23.8	254.0	14.7	456.01	30.00	.10	-2000.00	-2000.000	3.00	-2000.00
10325	1	1852.0	830.0	2.6	62.31	.01	.30	-2000.00	-2000.000	2.62	-2000.00
	2	438.3	589.0	7.0	273.46	.01	.10	-2000.00	-2000.000	1.36	-2000.00
	3	101.6	270.0	14.2	249.58	10.00	.20	-2000.00	-2000.000	1.15	-2000.00
	4	59.4	266.0	16.0	275.47	10.00	.20	-2000.00	-2000.000	1.53	-2000.00
	5	53.0	356.0	14.8	259.63	10.00	.20	-2000.00	-2000.000	1.65	-2000.00
10350	1	1817.0	830.0	6.3	250.63	.01	.10	-2000.00	-2000.000	1.88	-2000.00
	2	296.8	411.0	14.8	266.72	30.00	.20	-2000.00	-2000.000	1.42	-2000.00
	3	146.6	400.0	17.9	311.39	30.00	.20	-2000.00	-2000.000	1.55	-2000.00
	4	122.2	560.0	16.8	297.54	30.00	.20	-2000.00	-2000.000	2.05	-2000.00
	5	95.9	664.0	16.5	294.31	30.00	.20	-2000.00	-2000.000	3.30	-2000.00
10375	1	888.3	581.0	12.4	390.37	100.00	.10	-2000.00	-2000.000	2.39	-2000.00
	2	338.0	663.0	17.6	299.33	10.00	.20	-2000.00	-2000.000	1.33	-2000.00
	3	311.2	1210.0	16.6	285.31	10.00	.20	-2000.00	-2000.000	1.43	-2000.00
	4	180.8	1180.0	16.9	289.19	10.00	.20	-2000.00	-2000.000	1.44	-2000.00
	5	96.7	948.0	18.0	304.53	10.00	.20	-2000.00	-2000.000	1.70	-2000.00
10400	1	1622.0	990.0	13.8	431.95	100.00	.10	-2000.00	-2000.000	1.23	-2000.00
	2	926.6	1711.0	14.2	440.45	100.00	.10	-2000.00	-2000.000	1.14	-2000.00
	3	519.7	1910.0	14.5	447.06	100.00	.10	-2000.00	-2000.000	1.57	-2000.00
	4	224.8	1380.0	16.8	287.76	10.00	.20	-2000.00	-2000.000	1.62	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	152.4	1400.0	14.2	249.66	10.00	.20	-2000.00	-2000.000	1.63	-2000.00
10425	1	2362.0	1300.0	8.8	320.43	.10	.10	-2000.00	-2000.000	1.73	-2000.00
	2	914.0	1510.0	11.3	368.61	30.00	.10	-2000.00	-2000.000	1.31	-2000.00
	3	377.2	1240.0	14.4	252.11	10.00	.20	-2000.00	-2000.000	1.10	-2000.00
	4	221.2	1210.0	11.8	234.06	30.00	.20	-2000.00	-2000.000	4.15	-2000.00
	5	216.5	1780.0	14.2	250.33	10.00	.20	-2000.00	-2000.000	1.67	-2000.00
10450	1	1960.0	1200.0	7.0	147.84	.10	.20	-2000.00	-2000.000	2.94	-2000.00
	2	629.0	1161.0	10.8	399.06	.01	.10	-2000.00	-2000.000	2.39	-2000.00
	3	318.8	1170.0	10.1	188.41	10.00	.20	-2000.00	-2000.000	1.84	-2000.00
	4	292.9	1800.0	11.8	382.92	10.00	.10	-2000.00	-2000.000	1.26	-2000.00
	5	195.8	1800.0	10.9	210.58	30.00	.20	-2000.00	-2000.000	4.92	-2000.00
10475	1	1422.0	820.0	7.9	307.40	.01	.10	-2000.00	-2000.000	2.25	-2000.00
	2	607.7	1060.0	7.2	291.51	.01	.10	-2000.00	-2000.000	1.95	-2000.00
	3	499.9	1740.0	9.6	327.89	3.00	.10	-2000.00	-2000.000	1.08	-2000.00
	4	305.0	1770.0	9.2	174.74	10.00	.20	-2000.00	-2000.000	1.55	-2000.00
	5	251.7	2190.0	10.4	354.18	30.00	.10	-2000.00	-2000.000	1.87	-2000.00
10500	1	2061.0	1190.0	5.3	122.13	.03	.20	-2000.00	-2000.000	2.78	-2000.00
	2	1157.0	2010.0	7.7	287.67	.10	.10	-2000.00	-2000.000	2.74	-2000.00
	3	612.2	2130.0	7.3	266.69	1.00	.10	-2000.00	-2000.000	2.57	-2000.00
	4	420.8	2440.0	9.5	180.91	.30	.20	-2000.00	-2000.000	1.85	-2000.00
	5	172.3	1500.0	8.9	159.31	10.00	.20	-2000.00	-2000.000	4.91	-2000.00
10525	1	3166.0	1710.0	5.6	120.01	.10	.20	-2000.00	-2000.000	3.04	-2000.00
	2	1186.0	1920.0	5.9	214.70	10.00	.10	-2000.00	-2000.000	1.90	-2000.00
	3	793.2	2570.0	7.7	299.79	.01	.10	-2000.00	-2000.000	1.33	-2000.00
	4	288.0	1550.0	7.3	71.75	.30	.40	-2000.00	-2000.000	5.59	-2000.00
	5	141.0	1140.0	7.8	281.33	.03	.10	-2000.00	-2000.000	3.33	-2000.00
10550	1	2163.0	1350.0	3.6	77.63	.10	.20	-2000.00	-2000.000	3.65	-2000.00
	2	1165.0	2190.0	6.0	128.36	.10	.20	-2000.00	-2000.000	2.37	-2000.00
	3	378.7	1420.0	5.4	202.74	100.00	.10	-2000.00	-2000.000	4.27	-2000.00
	4	169.3	1060.0	6.1	221.75	1.00	.10	-2000.00	-2000.000	4.44	-2000.00
	5	123.0	1150.0	6.5	240.72	1.00	.10	-2000.00	-2000.000	2.75	-2000.00
10575	1	3690.0	1830.0	4.7	191.47	.01	.10	-2000.00	-2000.000	1.42	-2000.00
	2	952.9	1424.0	4.1	157.34	100.00	.10	-2000.00	-2000.000	1.74	-2000.00
	3	367.7	1090.0	4.5	178.36	100.00	.10	-2000.00	-2000.000	3.42	-2000.00
	4	236.3	1170.0	5.2	201.92	100.00	.10	-2000.00	-2000.000	3.17	-2000.00
	5	140.5	1050.0	6.1	224.74	.03	.10	-2000.00	-2000.000	3.17	-2000.00
10600	1	2243.0	1530.0	1.8	77.64	.01	.10	-2000.00	-2000.000	5.04	-2000.00
	2	604.2	1237.0	2.6	61.24	.03	.20	-2000.00	-2000.000	3.32	-2000.00
	3	339.3	1380.0	3.2	72.81	.10	.20	-2000.00	-2000.000	3.52	-2000.00
	4	160.5	1090.0	4.3	92.31	.10	.20	-2000.00	-2000.000	3.14	-2000.00
	5	171.7	1750.0	4.4	187.58	.10	.10	-2000.00	-2000.000	5.63	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10625	1	1662.0	1130.0	1.5	38.94	.01	.30	-2000.00	-2000.000	4.78	-2000.00
	2	645.1	1321.0	2.3	45.41	.03	.30	-2000.00	-2000.000	3.55	-2000.00
	3	328.5	1340.0	3.1	82.83	.01	.20	-2000.00	-2000.000	2.83	-2000.00
	4	248.2	1690.0	3.8	87.27	.10	.20	-2000.00	-2000.000	3.57	-2000.00
	5	177.7	1810.0	4.3	189.89	.01	.10	-2000.00	-2000.000	4.32	-2000.00
10650	1	2102.0	1400.0	1.4	39.77	.01	.20	-2000.00	-2000.000	5.80	-2000.00
	2	695.0	1392.0	2.6	42.93	.10	.30	-2000.00	-2000.000	3.72	-2000.00
	3	489.1	1950.0	3.0	79.55	.01	.20	-2000.00	-2000.000	2.11	-2000.00
	4	274.0	1830.0	4.5	171.53	1.00	.10	-2000.00	-2000.000	2.15	-2000.00
	5	250.4	2500.0	3.9	92.89	.03	.20	-2000.00	-2000.000	2.04	-2000.00
10675	1	1957.0	1220.0	2.7	72.70	.01	.20	-2000.00	-2000.000	3.31	-2000.00
	2	1021.0	1920.0	3.5	92.57	.01	.20	-2000.00	-2000.000	1.71	-2000.00
	3	491.1	1840.0	4.2	173.08	.01	.10	-2000.00	-2000.000	2.27	-2000.00
	4	364.5	2280.0	3.8	91.28	.03	.20	-2000.00	-2000.000	2.89	-2000.00
	5	219.5	2060.0	3.4	144.76	.01	.10	-2000.00	-2000.000	4.59	-2000.00
10700	1	2123.0	1620.0	2.7	72.13	.01	.20	-2000.00	-2000.000	3.20	-2000.00
	2	796.4	1829.0	4.1	169.77	.01	.10	-2000.00	-2000.000	1.90	-2000.00
	3	512.5	2350.0	3.7	81.21	.10	.20	-2000.00	-2000.000	2.49	-2000.00
	4	247.8	1890.0	3.2	74.61	.03	.20	-2000.00	-2000.000	3.23	-2000.00
10725	1	571.7	1380.0	3.2	63.26	.03	.30	-2000.00	-2000.000	5.62	-2000.00
	2	222.1	1609.0	3.3	65.50	.03	.30	-2000.00	-2000.000	9.47	-2000.00
	3	129.2	1860.0	3.2	83.84	.01	.20	-2000.00	-2000.000	16.15	-2000.00
10750	1	1194.0	1870.0	1.9	38.53	.03	.30	-2000.00	-2000.000	5.42	-2000.00
	2	392.0	1846.0	1.9	50.80	.01	.20	-2000.00	-2000.000	8.39	-2000.00
10775	1	1267.0	2210.0	.8	21.81	100.00	.50	-2000.00	-2000.000	49.36	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1224

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	435.6	170.0	4.5	49.38	.30	.40	-2000.00	-2000.000	.96	-2000.00
	2	95.4	112.3	3.7	96.25	.01	.20	-2000.00	-2000.000	1.20	-2000.00
	3	56.6	133.0	2.8	65.13	.03	.20	-2000.00	-2000.000	1.17	-2000.00
	4	40.0	157.0	2.4	34.27	.10	.40	-2000.00	-2000.000	2.01	-2000.00
	5	29.9	176.0	2.5	40.39	.10	.30	-2000.00	-2000.000	2.34	-2000.00
10050	1	311.6	119.0	4.1	44.53	.30	.40	-2000.00	-2000.000	1.66	-2000.00
	2	111.1	127.0	2.9	75.29	.01	.20	-2000.00	-2000.000	1.40	-2000.00
	3	68.6	157.0	2.5	40.50	.10	.30	-2000.00	-2000.000	1.14	-2000.00
	4	41.7	159.0	2.4	38.59	.10	.30	-2000.00	-2000.000	1.69	-2000.00
	5	23.7	136.0	2.5	48.36	.03	.30	-2000.00	-2000.000	2.88	-2000.00
10075	1	362.5	133.0	3.7	59.13	.10	.30	-2000.00	-2000.000	1.20	-2000.00
	2	145.9	161.0	3.0	48.78	.10	.30	-2000.00	-2000.000	1.71	-2000.00
	3	72.7	160.0	2.5	49.07	.03	.30	-2000.00	-2000.000	1.79	-2000.00
	4	37.0	136.0	2.8	64.79	.10	.20	-2000.00	-2000.000	4.66	-2000.00
	5	26.7	147.0	3.4	28.23	.30	.60	-2000.00	-2000.000	7.39	-2000.00
10100	1	477.9	153.0	3.2	51.50	.10	.30	-2000.00	-2000.000	.82	-2000.00
	2	160.1	153.0	2.7	43.95	.10	.30	-2000.00	-2000.000	1.64	-2000.00
	3	74.6	143.0	2.6	36.34	.10	.40	-2000.00	-2000.000	2.40	-2000.00
	4	39.9	127.0	3.9	36.54	.30	.50	-2000.00	-2000.000	3.16	-2000.00
	5	24.3	116.0	4.2	82.91	.03	.30	-2000.00	-2000.000	2.29	-2000.00
10125	1	388.5	128.0	2.5	23.50	.30	.50	-2000.00	-2000.000	2.42	-2000.00
	2	126.7	125.0	2.6	50.57	.03	.30	-2000.00	-2000.000	1.15	-2000.00
	3	62.2	123.0	3.5	49.11	.10	.40	-2000.00	-2000.000	2.00	-2000.00
	4	29.7	98.0	4.3	83.22	.03	.30	-2000.00	-2000.000	1.74	-2000.00
	5	20.9	103.0	2.8	25.45	.30	.60	-2000.00	-2000.000	3.36	-2000.00
10150	1	312.0	120.0	2.7	43.38	.10	.30	-2000.00	-2000.000	1.64	-2000.00
	2	109.2	126.0	3.6	34.73	.30	.50	-2000.00	-2000.000	2.11	-2000.00
	3	47.8	110.0	3.9	54.77	.10	.40	-2000.00	-2000.000	1.77	-2000.00
	4	23.8	92.0	3.0	43.16	.10	.40	-2000.00	-2000.000	1.33	-2000.00
	5	35.9	208.0	2.0	40.33	.03	.40	-2000.00	-2000.000	2.19	-2000.00
10175	1	364.8	123.0	4.0	78.73	.03	.30	-2000.00	-2000.000	1.79	-2000.00
	2	103.3	104.0	4.3	83.83	.03	.30	-2000.00	-2000.000	.61	-2000.00
	3	50.2	101.0	3.6	50.37	.10	.40	-2000.00	-2000.000	1.26	-2000.00
	4	57.4	193.0	2.4	59.74	.01	.30	-2000.00	-2000.000	1.76	-2000.00
	5	40.2	203.0	1.1	34.96	.01	.30	-2000.00	-2000.000	18.08	-2000.00
10200	1	1922.0	1200.0	4.6	122.96	.01	.20	-2000.00	-2000.000	4.76	-2000.00
	2	58.5	110.2	5.6	89.53	.10	.30	-2000.00	-2000.000	.92	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	53.6	201.0	2.6	52.12	.03	.40	-2000.00	-2000.000	2.73	-2000.00
	4	31.4	197.0	1.2	29.47	.03	.40	-2000.00	-2000.000	13.37	-2000.00
	5	31.6	298.0	.7	25.81	.03	.40	-2000.00	-2000.000	34.75	-2000.00
10225	1	1087.0	420.0	11.1	248.98	.03	.20	-2000.00	-2000.000	2.90	-2000.00
	2	194.4	228.0	3.3	46.45	.10	.40	-2000.00	-2000.000	1.25	-2000.00
	3	93.2	219.0	1.7	33.14	.03	.40	-2000.00	-2000.000	9.04	-2000.00
	4	68.4	268.0	1.0	38.06	.01	.40	-2000.00	-2000.000	11.99	-2000.00
	5	106.9	620.0	1.1	34.59	.01	.30	-2000.00	-2000.000	19.63	-2000.00
10250	1	371.0	247.0	2.1	52.38	.01	.30	-2000.00	-2000.000	3.15	-2000.00
	2	106.1	212.0	1.4	30.30	.03	.40	-2000.00	-2000.000	7.01	-2000.00
	3	61.9	247.0	.6	29.43	.01	.30	-2000.00	-2000.000	36.81	-2000.00
	4	82.8	553.0	.9	32.15	.01	.30	-2000.00	-2000.000	33.34	-2000.00
	5	48.7	487.0	4.5	117.96	.01	.20	-2000.00	-2000.000	3.43	-2000.00
10275	1	812.4	364.0	1.3	36.63	.01	.20	-2000.00	-2000.000	6.46	-2000.00
	2	215.8	290.0	.0	20.65	100.00	.50	-2000.00	-2000.000	76.97	-2000.00
	3	221.0	590.0	1.2	34.64	.01	.30	-2000.00	-2000.000	15.53	-2000.00
	4	117.2	520.0	4.3	179.40	.01	.10	-2000.00	-2000.000	3.07	-2000.00
	5	52.0	349.0	11.9	386.24	100.00	.10	-2000.00	-2000.000	1.51	-2000.00
10300	1	1229.0	480.0	.4	19.89	100.00	.30	-2000.00	-2000.000	48.38	-2000.00
	2	687.4	809.0	2.4	64.40	.01	.20	-2000.00	-2000.000	2.40	-2000.00
	3	302.4	710.0	5.5	198.93	10.00	.10	-2000.00	-2000.000	1.32	-2000.00
	4	121.1	470.0	12.8	228.36	10.00	.20	-2000.00	-2000.000	1.21	-2000.00
	5	50.4	296.0	12.7	406.28	100.00	.10	-2000.00	-2000.000	1.36	-2000.00
10325	1	1697.0	800.0	3.7	79.34	.10	.20	-2000.00	-2000.000	2.90	-2000.00
	2	510.9	729.0	6.5	234.70	100.00	.10	-2000.00	-2000.000	1.56	-2000.00
	3	160.8	450.0	13.3	244.71	30.00	.20	-2000.00	-2000.000	1.28	-2000.00
	4	64.4	306.0	13.8	249.52	30.00	.20	-2000.00	-2000.000	1.71	-2000.00
	5	53.3	380.0	13.4	247.41	30.00	.20	-2000.00	-2000.000	2.18	-2000.00
10350	1	3001.0	1140.0	8.3	288.67	30.00	.10	-2000.00	-2000.000	1.35	-2000.00
	2	550.4	632.0	16.4	290.51	30.00	.20	-2000.00	-2000.000	1.25	-2000.00
	3	270.2	610.0	15.7	272.12	10.00	.20	-2000.00	-2000.000	1.19	-2000.00
	4	137.0	520.0	15.9	275.84	10.00	.20	-2000.00	-2000.000	1.27	-2000.00
	5	109.7	630.0	18.0	298.69	3.00	.20	-2000.00	-2000.000	2.43	-2000.00
10375	1	3460.0	1120.0	14.5	262.75	30.00	.20	-2000.00	-2000.000	1.43	-2000.00
	2	918.0	891.0	16.3	287.99	30.00	.20	-2000.00	-2000.000	1.12	-2000.00
	3	479.0	920.0	16.3	289.07	30.00	.20	-2000.00	-2000.000	1.25	-2000.00
	4	321.7	1040.0	18.3	335.82	100.00	.20	-2000.00	-2000.000	1.70	-2000.00
	5	252.2	1220.0	15.9	303.84	100.00	.20	-2000.00	-2000.000	2.25	-2000.00
10400	1	1508.0	860.0	16.9	296.50	30.00	.20	-2000.00	-2000.000	.94	-2000.00
	2	599.3	1026.0	16.4	287.37	30.00	.20	-2000.00	-2000.000	.99	-2000.00
	3	347.6	1180.0	18.4	318.05	30.00	.20	-2000.00	-2000.000	.93	-2000.00
	4	216.5	1230.0	16.3	282.29	10.00	.20	-2000.00	-2000.000	1.25	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	160.7	1370.0	14.9	184.21	1.00	.30	-2000.00	-2000.000	1.98	-2000.00
10425	1	1975.0	810.0	13.1	233.16	10.00	.20	-2000.00	-2000.000	1.20	-2000.00
	2	879.3	1089.0	16.9	294.32	30.00	.20	-2000.00	-2000.000	1.60	-2000.00
	3	637.1	1570.0	15.9	297.30	100.00	.20	-2000.00	-2000.000	1.33	-2000.00
	4	308.3	1270.0	15.5	285.53	100.00	.20	-2000.00	-2000.000	2.94	-2000.00
	5	195.9	1210.0	15.1	171.32	10.00	.30	-2000.00	-2000.000	8.08	-2000.00
10450	1	2159.0	1350.0	8.3	303.58	.03	.10	-2000.00	-2000.000	1.89	-2000.00
	2	725.9	1367.0	10.5	208.37	30.00	.20	-2000.00	-2000.000	5.14	-2000.00
	3	407.8	1530.0	11.8	210.92	10.00	.20	-2000.00	-2000.000	1.68	-2000.00
	4	210.5	1320.0	10.5	218.93	100.00	.20	-2000.00	-2000.000	6.89	-2000.00
	5	318.3	2990.0	11.5	212.18	30.00	.20	-2000.00	-2000.000	2.90	-2000.00
10475	1	1510.0	1050.0	8.9	303.76	10.00	.10	-2000.00	-2000.000	1.65	-2000.00
	2	615.2	1287.0	9.9	337.74	100.00	.10	-2000.00	-2000.000	2.44	-2000.00
	3	344.1	1430.0	9.0	326.98	.10	.10	-2000.00	-2000.000	1.49	-2000.00
	4	440.6	3070.0	11.3	362.92	.30	.10	-2000.00	-2000.000	2.98	-2000.00
	5	137.7	1440.0	7.0	27.23	1.00	.80	-2000.00	-2000.000	6.05	-2000.00
10500	1	1499.0	1020.0	7.7	274.47	30.00	.10	-2000.00	-2000.000	3.02	-2000.00
	2	648.5	1328.0	8.0	276.15	3.00	.10	-2000.00	-2000.000	1.44	-2000.00
	3	834.6	3410.0	9.1	113.34	1.00	.30	-2000.00	-2000.000	1.64	-2000.00
	4	225.2	1530.0	8.8	162.93	30.00	.20	-2000.00	-2000.000	2.35	-2000.00
	5	129.9	1330.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10525	1	2072.0	1620.0	4.3	177.01	.01	.10	-2000.00	-2000.000	2.64	-2000.00
	2	1627.0	3830.0	6.0	219.56	1.00	.10	-2000.00	-2000.000	1.87	-2000.00
	3	384.7	1800.0	5.7	115.39	30.00	.20	-2000.00	-2000.000	5.20	-2000.00
	4	197.1	1540.0	6.1	138.05	100.00	.20	-2000.00	-2000.000	6.95	-2000.00
	5	121.9	1430.0	7.6	27.03	1.00	.80	-2000.00	-2000.000	13.87	-2000.00
10550	1	3380.0	2860.0	4.8	195.43	.01	.10	-2000.00	-2000.000	1.95	-2000.00
	2	661.5	1684.0	4.6	172.20	100.00	.10	-2000.00	-2000.000	2.60	-2000.00
	3	310.6	1570.0	4.5	187.81	1.00	.10	-2000.00	-2000.000	5.32	-2000.00
	4	156.4	1320.0	5.3	195.11	10.00	.10	-2000.00	-2000.000	3.31	-2000.00
	5	105.2	1330.0	6.9	119.66	10.00	.20	-2000.00	-2000.000	8.38	-2000.00
10575	1	2124.0	1410.0	2.9	114.65	100.00	.10	-2000.00	-2000.000	2.51	-2000.00
	2	662.9	1328.0	3.6	51.43	.30	.30	-2000.00	-2000.000	2.44	-2000.00
	3	359.1	1430.0	3.7	40.27	.30	.40	-2000.00	-2000.000	4.40	-2000.00
	4	167.3	1110.0	4.9	66.97	.30	.30	-2000.00	-2000.000	4.12	-2000.00
	5	165.7	1660.0	5.7	61.39	.30	.40	-2000.00	-2000.000	5.51	-2000.00
10600	1	2740.0	1620.0	1.9	51.85	.01	.20	-2000.00	-2000.000	5.51	-2000.00
	2	1001.0	1770.0	2.2	59.22	.01	.20	-2000.00	-2000.000	3.00	-2000.00
	3	420.3	1490.0	3.4	137.60	.01	.10	-2000.00	-2000.000	3.90	-2000.00
	4	317.4	1880.0	4.5	183.17	.01	.10	-2000.00	-2000.000	2.24	-2000.00
	5	214.5	1900.0	4.3	94.39	.10	.20	-2000.00	-2000.000	2.60	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10625	1	1257.0	960.0	1.6	39.13	.03	.20	-2000.00	-2000.000	4.45	-2000.00
	2	461.4	1060.0	2.8	116.14	.01	.10	-2000.00	-2000.000	5.14	-2000.00
	3	339.6	1550.0	4.0	152.39	1.00	.10	-2000.00	-2000.000	2.87	-2000.00
	4	192.1	1470.0	4.1	160.85	100.00	.10	-2000.00	-2000.000	4.02	-2000.00
	5	163.7	1880.0	4.0	163.38	.01	.10	-2000.00	-2000.000	7.11	-2000.00
10650	1	1668.0	1340.0	2.5	26.83	.30	.40	-2000.00	-2000.000	2.72	-2000.00
	2	712.6	1721.0	3.7	151.48	1.00	.10	-2000.00	-2000.000	5.70	-2000.00
	3	371.6	1790.0	4.2	91.82	100.00	.20	-2000.00	-2000.000	4.86	-2000.00
	4	212.0	1700.0	4.0	156.51	100.00	.10	-2000.00	-2000.000	6.53	-2000.00
	5	218.5	2630.0	4.0	93.93	100.00	.20	-2000.00	-2000.000	10.89	-2000.00
10675	1	2133.0	1670.0	3.9	91.61	.03	.20	-2000.00	-2000.000	2.81	-2000.00
	2	719.8	1695.0	4.4	173.12	.10	.10	-2000.00	-2000.000	2.26	-2000.00
	3	460.8	2160.0	3.7	80.51	.10	.20	-2000.00	-2000.000	3.00	-2000.00
	4	353.0	2770.0	3.8	90.05	.03	.20	-2000.00	-2000.000	3.19	-2000.00
	5	154.7	1820.0	4.2	58.11	.30	.30	-2000.00	-2000.000	6.58	-2000.00
10700	1	1872.0	1580.0	3.3	138.42	.01	.10	-2000.00	-2000.000	3.62	-2000.00
	2	617.3	1571.0	3.6	84.52	.03	.20	-2000.00	-2000.000	3.24	-2000.00
	3	500.4	2540.0	3.3	82.25	.03	.20	-2000.00	-2000.000	6.80	-2000.00
	4	199.3	1690.0	4.4	164.95	.03	.10	-2000.00	-2000.000	4.34	-2000.00
10725	1	2578.0	2070.0	2.4	47.61	.03	.30	-2000.00	-2000.000	4.43	-2000.00
	2	1086.0	2620.0	3.0	79.86	.01	.20	-2000.00	-2000.000	4.08	-2000.00
	3	366.8	1760.0	3.3	86.61	.01	.20	-2000.00	-2000.000	5.96	-2000.00
10750	1	1032.0	1900.0	2.1	42.69	.03	.30	-2000.00	-2000.000	5.71	-2000.00
	2	274.4	1520.0	2.9	76.15	.01	.20	-2000.00	-2000.000	7.05	-2000.00
10775	1	565.9	1776.0	2.0	50.88	.01	.30	-2000.00	-2000.000	6.07	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1234

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	485.2	163.0	2.4	38.30	.10	.30	-2000.00	-2000.000	2.57	-2000.00
	2	159.9	161.0	2.2	42.01	.03	.30	-2000.00	-2000.000	2.94	-2000.00
	3	87.1	176.0	2.6	36.89	.10	.40	-2000.00	-2000.000	2.70	-2000.00
	4	60.0	202.0	2.5	59.38	.03	.20	-2000.00	-2000.000	5.48	-2000.00
	5	54.5	276.0	2.3	44.05	.03	.30	-2000.00	-2000.000	4.37	-2000.00
10050	1	390.7	144.0	1.7	42.87	.01	.30	-2000.00	-2000.000	2.06	-2000.00
	2	135.9	150.0	2.2	31.23	.10	.40	-2000.00	-2000.000	2.52	-2000.00
	3	88.0	194.0	.8	57.84	.01	.50	-2000.00	-2000.000	21.39	-2000.00
	4	66.5	245.0	3.2	11.16	1.00	.80	-2000.00	-2000.000	15.03	-2000.00
	5	28.8	159.0	2.8	52.33	.03	.30	-2000.00	-2000.000	4.20	-2000.00
10075	1	367.3	115.3	-1.0	40.56	.01	.40	-2000.00	-2000.000	55.38	-2000.00
	2	189.3	178.3	1.9	46.35	.01	.30	-2000.00	-2000.000	2.57	-2000.00
	3	123.2	231.0	1.9	46.92	.01	.30	-2000.00	-2000.000	3.18	-2000.00
	4	42.5	133.3	2.4	39.78	.10	.30	-2000.00	-2000.000	4.22	-2000.00
	5	28.7	135.2	2.1	41.93	.03	.40	-2000.00	-2000.000	6.15	-2000.00
10100	1	433.6	203.0	1.9	37.33	.03	.30	-2000.00	-2000.000	2.79	-2000.00
	2	155.5	218.0	1.8	44.39	.01	.30	-2000.00	-2000.000	3.54	-2000.00
	3	52.0	145.0	2.3	56.84	.01	.30	-2000.00	-2000.000	3.35	-2000.00
	4	26.0	121.0	2.1	44.21	.03	.30	-2000.00	-2000.000	4.95	-2000.00
	5	16.9	118.0	3.2	42.42	.10	.40	-2000.00	-2000.000	5.86	-2000.00
10125	1	316.4	174.0	1.5	39.70	.01	.30	-2000.00	-2000.000	7.57	-2000.00
	2	52.9	87.4	2.3	46.93	.03	.30	-2000.00	-2000.000	4.28	-2000.00
	3	31.5	104.0	1.9	45.59	.01	.30	-2000.00	-2000.000	5.71	-2000.00
	4	18.3	100.0	2.5	36.98	.10	.50	-2000.00	-2000.000	4.22	-2000.00
	5	11.8	97.0	1.7	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10150	1	158.3	71.0	1.7	34.58	.03	.40	-2000.00	-2000.000	2.39	-2000.00
	2	70.2	94.4	1.8	45.11	.01	.30	-2000.00	-2000.000	3.51	-2000.00
	3	35.2	94.0	2.5	50.98	.03	.40	-2000.00	-2000.000	2.59	-2000.00
	4	19.5	87.0	2.4	19.17	.30	.60	-2000.00	-2000.000	12.58	-2000.00
	5	25.4	170.0	.9	37.58	.01	.40	-2000.00	-2000.000	23.98	-2000.00
10175	1	178.3	151.0	3.3	24.07	.30	.80	-2000.00	-2000.000	54.84	-2000.00
	2	40.5	103.0	3.0	71.86	.01	.30	-2000.00	-2000.000	5.37	-2000.00
	3	19.4	98.0	1.9	45.56	.03	.50	-2000.00	-2000.000	3.69	-2000.00
	4	21.2	180.0	2.3	19.30	.30	.50	-2000.00	-2000.000	28.86	-2000.00
	5	21.4	272.0	-.7	18.98	100.00	.30	-2000.00	-2000.000	99.75	-2000.00
10200	1	260.1	120.0	3.0	72.96	.01	.30	-2000.00	-2000.000	1.16	-2000.00
	2	66.0	91.4	2.2	31.37	.10	.50	-2000.00	-2000.000	2.57	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	58.4	161.0	1.3	42.98	.01	.40	-2000.00	-2000.000	12.16	-2000.00
	4	53.8	248.0	-.3	19.26	100.00	.30	-2000.00	-2000.000	100.14	-2000.00
	5	80.1	555.0	.3	49.58	.01	.10	-2000.00	-2000.000	53.48	-2000.00
10225	1	134.8	98.0	2.7	53.52	.03	.40	-2000.00	-2000.000	2.99	-2000.00
	2	76.7	168.0	1.9	54.69	.01	.40	-2000.00	-2000.000	3.28	-2000.00
	3	57.6	251.0	.9	59.27	1.00	.10	-2000.00	-2000.000	34.33	-2000.00
	4	70.7	516.0	.1	31.53	.01	.20	-2000.00	-2000.000	103.16	-2000.00
	5	65.1	713.0	-.1	19.34	100.00	.40	-2000.00	-2000.000	90.87	-2000.00
10250	1	516.6	219.0	1.5	39.45	.01	.30	-2000.00	-2000.000	4.96	-2000.00
	2	188.5	239.0	.8	32.96	.01	.20	-2000.00	-2000.000	28.19	-2000.00
	3	215.0	540.0	.5	45.66	.10	.10	-2000.00	-2000.000	46.80	-2000.00
	4	145.6	610.0	.3	24.51	100.00	.20	-2000.00	-2000.000	57.28	-2000.00
	5	115.5	730.0	4.4	94.73	.10	.20	-2000.00	-2000.000	3.35	-2000.00
10275	1	859.0	414.0	2.0	49.02	.01	.30	-2000.00	-2000.000	3.04	-2000.00
	2	403.1	584.0	1.1	33.35	.01	.30	-2000.00	-2000.000	18.21	-2000.00
	3	232.8	670.0	.9	29.59	.03	.20	-2000.00	-2000.000	23.07	-2000.00
	4	150.0	720.0	4.1	45.28	.30	.40	-2000.00	-2000.000	2.34	-2000.00
	5	64.4	466.0	13.2	235.70	1.00	.20	-2000.00	-2000.000	1.03	-2000.00
10300	1	1553.0	670.0	1.5	39.41	.01	.30	-2000.00	-2000.000	5.34	-2000.00
	2	515.7	674.0	2.1	41.90	.03	.30	-2000.00	-2000.000	2.59	-2000.00
	3	310.2	800.0	5.0	201.48	.01	.10	-2000.00	-2000.000	1.47	-2000.00
	4	114.5	490.0	14.3	249.61	10.00	.20	-2000.00	-2000.000	1.66	-2000.00
	5	56.7	371.0	11.4	373.23	100.00	.10	-2000.00	-2000.000	2.68	-2000.00
10325	1	1687.0	750.0	4.0	151.05	1.00	.10	-2000.00	-2000.000	1.93	-2000.00
	2	534.9	719.0	7.0	248.74	10.00	.10	-2000.00	-2000.000	1.71	-2000.00
	3	201.0	530.0	15.6	270.30	10.00	.20	-2000.00	-2000.000	1.37	-2000.00
	4	79.3	355.0	11.9	206.94	3.00	.20	-2000.00	-2000.000	2.06	-2000.00
	5	52.0	350.0	14.7	256.40	10.00	.20	-2000.00	-2000.000	2.87	-2000.00
10350	1	3160.0	1940.0	8.4	157.45	10.00	.20	-2000.00	-2000.000	1.65	-2000.00
	2	645.2	1191.0	18.9	324.93	30.00	.20	-2000.00	-2000.000	1.13	-2000.00
	3	208.6	760.0	14.9	254.39	3.00	.20	-2000.00	-2000.000	1.42	-2000.00
	4	101.5	620.0	17.9	328.81	100.00	.20	-2000.00	-2000.000	3.24	-2000.00
	5	82.7	764.0	18.8	318.86	30.00	.20	-2000.00	-2000.000	1.80	-2000.00
10375	1	1805.0	1280.0	19.5	331.60	30.00	.20	-2000.00	-2000.000	1.16	-2000.00
	2	475.5	1018.0	15.3	273.35	30.00	.20	-2000.00	-2000.000	1.12	-2000.00
	3	215.8	920.0	17.5	303.39	30.00	.20	-2000.00	-2000.000	1.05	-2000.00
	4	144.1	1020.0	18.5	316.75	30.00	.20	-2000.00	-2000.000	1.34	-2000.00
	5	93.2	997.0	13.2	241.58	30.00	.20	-2000.00	-2000.000	2.56	-2000.00
10400	1	2422.0	1460.0	15.1	271.28	30.00	.20	-2000.00	-2000.000	1.48	-2000.00
	2	776.6	1406.0	16.3	288.70	30.00	.20	-2000.00	-2000.000	1.29	-2000.00
	3	421.9	1520.0	18.4	316.91	30.00	.20	-2000.00	-2000.000	1.03	-2000.00
	4	237.6	1430.0	13.0	412.68	100.00	.10	-2000.00	-2000.000	1.51	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	197.1	1780.0	12.6	154.44	1.00	.30	-2000.00	-2000.000	1.72	-2000.00
10425	1	2034.0	1300.0	11.4	206.11	10.00	.20	-2000.00	-2000.000	1.69	-2000.00
	2	784.5	1508.0	16.9	300.16	30.00	.20	-2000.00	-2000.000	1.88	-2000.00
	3	368.1	1410.0	12.6	239.48	30.00	.20	-2000.00	-2000.000	2.85	-2000.00
	4	282.8	1810.0	12.5	241.09	30.00	.20	-2000.00	-2000.000	4.97	-2000.00
	5	206.0	1980.0	11.1	413.62	.03	.10	-2000.00	-2000.000	4.04	-2000.00
10450	1	2688.0	1500.0	12.5	399.75	100.00	.10	-2000.00	-2000.000	1.53	-2000.00
	2	845.1	1421.0	9.3	312.77	30.00	.10	-2000.00	-2000.000	1.32	-2000.00
	3	544.9	1820.0	9.7	178.46	10.00	.20	-2000.00	-2000.000	3.66	-2000.00
	4	330.2	1850.0	10.3	328.15	100.00	.10	-2000.00	-2000.000	11.03	-2000.00
	5	174.7	1460.0	9.7	176.39	3.00	.20	-2000.00	-2000.000	4.30	-2000.00
10475	1	1997.0	1220.0	11.7	230.94	100.00	.20	-2000.00	-2000.000	2.45	-2000.00
	2	881.2	1627.0	10.0	196.29	.30	.20	-2000.00	-2000.000	1.46	-2000.00
	3	506.2	1860.0	10.1	210.81	100.00	.20	-2000.00	-2000.000	3.58	-2000.00
	4	226.9	1390.0	9.3	213.04	100.00	.20	-2000.00	-2000.000	9.42	-2000.00
	5	95.4	881.0	7.3	160.01	100.00	.30	-2000.00	-2000.000	17.81	-2000.00
10500	1	2274.0	1480.0	7.6	268.97	1.00	.10	-2000.00	-2000.000	2.08	-2000.00
	2	973.7	1910.0	8.5	160.55	10.00	.20	-2000.00	-2000.000	3.44	-2000.00
	3	388.8	1520.0	9.0	161.18	10.00	.20	-2000.00	-2000.000	3.26	-2000.00
	4	151.9	990.0	8.9	166.14	100.00	.20	-2000.00	-2000.000	6.23	-2000.00
	5	146.1	1430.0	8.7	51.93	1.00	.60	-2000.00	-2000.000	5.58	-2000.00
10525	1	2809.0	1830.0	4.6	184.67	.01	.10	-2000.00	-2000.000	1.83	-2000.00
	2	890.4	1747.0	5.6	126.88	100.00	.20	-2000.00	-2000.000	4.65	-2000.00
	3	327.3	1280.0	4.1	150.28	3.00	.10	-2000.00	-2000.000	2.37	-2000.00
	4	249.9	1630.0	6.4	43.28	1.00	.50	-2000.00	-2000.000	7.17	-2000.00
	5	165.3	1620.0	6.2	250.12	100.00	.10	-2000.00	-2000.000	8.17	-2000.00
10550	1	2697.0	1840.0	4.0	56.87	.10	.50	-2000.00	-2000.000	7.29	-2000.00
	2	778.3	1593.0	1.7	34.26	.03	.40	-2000.00	-2000.000	4.01	-2000.00
	3	525.5	2140.0	3.5	85.58	.03	.20	-2000.00	-2000.000	4.43	-2000.00
	4	253.9	1730.0	4.4	179.46	.10	.10	-2000.00	-2000.000	4.50	-2000.00
	5	193.6	1980.0	5.4	220.83	.01	.10	-2000.00	-2000.000	2.39	-2000.00
10575	1	1225.0	1010.0	.5	19.83	100.00	.30	-2000.00	-2000.000	48.44	-2000.00
	2	795.4	1971.0	2.5	66.20	.01	.20	-2000.00	-2000.000	2.00	-2000.00
	3	394.1	1940.0	3.9	26.34	.30	.60	-2000.00	-2000.000	14.99	-2000.00
	4	218.8	1800.0	4.5	100.14	.03	.20	-2000.00	-2000.000	3.16	-2000.00
	5	185.3	2290.0	4.0	107.16	.01	.20	-2000.00	-2000.000	2.35	-2000.00
10600	1	2916.0	2120.0	2.7	64.94	.03	.20	-2000.00	-2000.000	2.93	-2000.00
	2	676.6	1482.0	3.4	143.19	.01	.10	-2000.00	-2000.000	3.11	-2000.00
	3	454.9	1980.0	3.7	91.70	.03	.20	-2000.00	-2000.000	4.07	-2000.00
	4	301.0	2190.0	3.6	95.33	.01	.20	-2000.00	-2000.000	1.79	-2000.00
	5	196.7	2150.0	3.5	96.86	.01	.20	-2000.00	-2000.000	4.76	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10625	1	1830.0	1400.0	2.5	60.21	.03	.20	-2000.00	-2000.000	3.01	-2000.00
	2	606.5	1393.0	3.8	86.81	.03	.20	-2000.00	-2000.000	2.26	-2000.00
	3	420.2	1920.0	3.2	145.15	.01	.10	-2000.00	-2000.000	5.49	-2000.00
	4	242.6	1850.0	2.9	140.49	30.00	.10	-2000.00	-2000.000	13.16	-2000.00
	5	242.6	2780.0	3.7	161.94	.01	.10	-2000.00	-2000.000	9.21	-2000.00
10650	1	2056.0	1610.0	5.0	186.38	1.00	.10	-2000.00	-2000.000	1.92	-2000.00
	2	867.5	2042.0	4.6	173.33	100.00	.10	-2000.00	-2000.000	2.19	-2000.00
	3	421.2	1970.0	4.1	153.44	30.00	.10	-2000.00	-2000.000	2.97	-2000.00
	4	385.9	3020.0	4.3	154.11	3.00	.10	-2000.00	-2000.000	4.28	-2000.00
	5	164.4	1930.0	4.0	159.65	.10	.10	-2000.00	-2000.000	3.61	-2000.00
10675	1	2197.0	1600.0	3.7	141.82	.30	.10	-2000.00	-2000.000	3.03	-2000.00
	2	776.1	1700.0	3.6	146.74	.10	.10	-2000.00	-2000.000	1.63	-2000.00
	3	635.2	2770.0	4.0	148.55	3.00	.10	-2000.00	-2000.000	2.78	-2000.00
	4	246.3	1790.0	3.8	154.75	.01	.10	-2000.00	-2000.000	3.54	-2000.00
	5	208.0	2270.0	4.0	88.66	100.00	.20	-2000.00	-2000.000	7.10	-2000.00
10700	1	2006.0	1650.0	2.3	51.01	.10	.20	-2000.00	-2000.000	3.33	-2000.00
	2	1107.0	2740.0	2.9	63.43	.10	.20	-2000.00	-2000.000	3.53	-2000.00
	3	360.8	1780.0	3.0	43.42	.30	.30	-2000.00	-2000.000	4.06	-2000.00
	4	268.3	2210.0	2.7	44.34	.10	.30	-2000.00	-2000.000	10.98	-2000.00
10725	1	1164.0	2810.0	2.1	54.37	.01	.20	-2000.00	-2000.000	4.80	-2000.00
	2	271.4	1966.0	2.2	64.93	.01	.20	-2000.00	-2000.000	7.80	-2000.00
	3	166.7	2410.0	1.3	50.41	.01	.20	-2000.00	-2000.000	30.05	-2000.00
10750	1	816.0	2329.0	1.8	29.01	.10	.30	-2000.00	-2000.000	40.64	-2000.00
	2	273.0	2337.0	2.2	22.28	.30	.40	-2000.00	-2000.000	35.01	-2000.00
10775	1	388.8	2440.0	1.8	35.34	.03	.30	-2000.00	-2000.000	82.84	-2000.00

IPR-11 SPECTRAL ANALYSIS SUMMARY

LINE NO. : 1244

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10025	1	408.6	178.0	2.0	50.38	.01	.30	-2000.00	-2000.000	2.43	-2000.00
	2	137.8	180.0	3.2	62.65	.03	.30	-2000.00	-2000.000	1.41	-2000.00
	3	80.3	209.0	1.8	36.54	.03	.30	-2000.00	-2000.000	2.28	-2000.00
	4	61.7	269.0	1.9	37.33	.03	.30	-2000.00	-2000.000	2.04	-2000.00
	5	45.9	300.0	2.6	51.84	.03	.30	-2000.00	-2000.000	2.61	-2000.00
10050	1	488.5	213.0	2.9	56.60	.03	.30	-2000.00	-2000.000	1.16	-2000.00
	2	146.2	191.0	1.8	44.61	.01	.30	-2000.00	-2000.000	2.11	-2000.00
	3	96.3	251.0	1.8	34.15	.03	.30	-2000.00	-2000.000	2.06	-2000.00
	4	61.8	269.0	2.3	56.97	.01	.30	-2000.00	-2000.000	2.16	-2000.00
	5	29.5	192.0	3.2	52.35	.10	.30	-2000.00	-2000.000	4.19	-2000.00
10075	1	345.4	180.0	1.5	38.76	.01	.30	-2000.00	-2000.000	5.23	-2000.00
	2	134.2	210.0	1.4	28.60	.03	.30	-2000.00	-2000.000	6.73	-2000.00
	3	70.8	221.0	2.0	48.12	.01	.30	-2000.00	-2000.000	1.85	-2000.00
	4	31.8	166.0	3.0	49.04	.10	.30	-2000.00	-2000.000	2.06	-2000.00
	5	23.0	180.0	3.0	41.84	.10	.40	-2000.00	-2000.000	2.36	-2000.00
10100	1	384.5	172.0	1.8	42.63	.01	.30	-2000.00	-2000.000	2.22	-2000.00
	2	126.6	170.0	1.9	48.23	.01	.30	-2000.00	-2000.000	3.09	-2000.00
	3	53.8	144.0	2.8	27.08	.30	.50	-2000.00	-2000.000	1.87	-2000.00
	4	34.1	153.0	3.1	60.60	.03	.30	-2000.00	-2000.000	2.00	-2000.00
	5	18.6	125.0	2.4	46.74	.03	.40	-2000.00	-2000.000	4.08	-2000.00
10125	1	260.3	131.0	1.2	27.52	.03	.30	-2000.00	-2000.000	7.63	-2000.00
	2	73.6	111.8	2.6	23.16	.30	.50	-2000.00	-2000.000	3.34	-2000.00
	3	46.9	142.0	2.6	63.27	.01	.30	-2000.00	-2000.000	1.12	-2000.00
	4	21.5	108.0	2.3	45.90	.03	.30	-2000.00	-2000.000	1.72	-2000.00
	5	38.2	290.0	1.1	44.69	.01	.40	-2000.00	-2000.000	17.08	-2000.00
10150	1	194.9	101.0	2.3	37.72	.10	.30	-2000.00	-2000.000	2.38	-2000.00
	2	71.7	112.6	2.1	41.37	.03	.40	-2000.00	-2000.000	4.07	-2000.00
	3	35.9	112.0	2.4	65.30	.01	.20	-2000.00	-2000.000	3.28	-2000.00
	4	48.7	254.0	1.3	35.16	.01	.30	-2000.00	-2000.000	10.87	-2000.00
	5	32.3	253.0	.5	33.10	.01	.30	-2000.00	-2000.000	54.53	-2000.00
10175	1	230.3	131.0	2.7	37.89	.10	.40	-2000.00	-2000.000	1.59	-2000.00
	2	53.9	92.2	1.9	50.15	.01	.30	-2000.00	-2000.000	3.36	-2000.00
	3	66.1	225.0	.9	41.25	.01	.40	-2000.00	-2000.000	25.72	-2000.00
	4	40.7	232.0	.8	45.57	.10	.10	-2000.00	-2000.000	47.57	-2000.00
	5	28.5	244.0	1.7	27.51	100.00	.30	-2000.00	-2000.000	46.38	-2000.00
10200	1	186.5	87.0	2.6	63.70	.03	.20	-2000.00	-2000.000	2.99	-2000.00
	2	138.4	194.0	2.0	28.60	.10	.40	-2000.00	-2000.000	3.16	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	3	77.2	216.0	1.7	34.42	.03	.30	-2000.00	-2000.000	6.57	-2000.00
	4	47.4	221.0	.3	31.38	.01	.20	-2000.00	-2000.000	60.10	-2000.00
	5	44.7	314.0	-.2	42.99	100.00	.80	-2000.00	-2000.000	103.12	-2000.00
10225	1	402.3	210.0	3.1	117.46	.10	.10	-2000.00	-2000.000	3.86	-2000.00
	2	147.5	231.0	1.9	37.74	.03	.40	-2000.00	-2000.000	3.44	-2000.00
	3	78.7	246.0	1.1	33.62	.01	.30	-2000.00	-2000.000	12.92	-2000.00
	4	62.4	326.0	1.5	44.10	100.00	.80	-2000.00	-2000.000	71.06	-2000.00
	5	112.0	870.0	.0	34.44	.01	.20	-2000.00	-2000.000	56.03	-2000.00
10250	1	602.5	270.0	1.9	45.77	.01	.30	-2000.00	-2000.000	2.19	-2000.00
	2	177.5	238.0	1.5	41.26	.01	.30	-2000.00	-2000.000	4.95	-2000.00
	3	131.1	350.0	.4	20.84	100.00	.50	-2000.00	-2000.000	44.16	-2000.00
	4	176.2	790.0	.3	46.63	.10	.10	-2000.00	-2000.000	57.20	-2000.00
	5	142.6	950.0	1.4	36.77	.01	.30	-2000.00	-2000.000	8.26	-2000.00
10275	1	1295.0	580.0	1.8	45.48	.01	.30	-2000.00	-2000.000	2.55	-2000.00
	2	464.1	624.0	1.5	31.11	.03	.30	-2000.00	-2000.000	5.17	-2000.00
	3	523.0	1400.0	1.6	42.01	.01	.30	-2000.00	-2000.000	4.64	-2000.00
	4	311.8	1390.0	2.1	35.30	.10	.30	-2000.00	-2000.000	3.40	-2000.00
	5	178.7	1200.0	7.1	254.09	30.00	.10	-2000.00	-2000.000	1.16	-2000.00
10300	1	1227.0	630.0	1.2	27.40	.03	.30	-2000.00	-2000.000	10.51	-2000.00
	2	966.3	1492.0	2.0	50.50	.01	.30	-2000.00	-2000.000	1.90	-2000.00
	3	483.5	1490.0	2.3	37.25	.10	.30	-2000.00	-2000.000	1.91	-2000.00
	4	253.5	1300.0	7.1	252.41	1.00	.10	-2000.00	-2000.000	.88	-2000.00
	5	83.9	647.0	11.3	206.23	10.00	.20	-2000.00	-2000.000	1.74	-2000.00
10325	1	3033.0	1260.0	2.4	47.98	.03	.30	-2000.00	-2000.000	2.55	-2000.00
	2	1054.0	1320.0	2.6	62.35	.03	.20	-2000.00	-2000.000	1.19	-2000.00
	3	461.2	1150.0	7.6	269.81	100.00	.10	-2000.00	-2000.000	.78	-2000.00
	4	153.4	640.0	11.4	214.44	30.00	.20	-2000.00	-2000.000	1.39	-2000.00
	5	90.3	567.0	11.2	202.38	10.00	.20	-2000.00	-2000.000	2.19	-2000.00
10350	1	1622.0	1150.0	2.8	59.68	.10	.20	-2000.00	-2000.000	1.93	-2000.00
	2	526.8	1127.0	7.8	273.34	100.00	.10	-2000.00	-2000.000	.89	-2000.00
	3	160.5	680.0	11.4	205.74	10.00	.20	-2000.00	-2000.000	1.02	-2000.00
	4	77.6	553.0	11.0	206.62	30.00	.20	-2000.00	-2000.000	1.65	-2000.00
	5	59.3	634.0	17.4	306.47	30.00	.20	-2000.00	-2000.000	1.54	-2000.00
10375	1	2694.0	1760.0	10.6	351.11	100.00	.10	-2000.00	-2000.000	.99	-2000.00
	2	552.8	1084.0	12.5	223.57	10.00	.20	-2000.00	-2000.000	1.06	-2000.00
	3	293.5	1140.0	11.7	210.84	10.00	.20	-2000.00	-2000.000	1.07	-2000.00
	4	160.8	1050.0	18.5	319.04	30.00	.20	-2000.00	-2000.000	1.20	-2000.00
	5	112.1	1090.0	14.0	259.50	30.00	.20	-2000.00	-2000.000	2.21	-2000.00
10400	1	1248.0	950.0	15.1	262.77	10.00	.20	-2000.00	-2000.000	1.58	-2000.00
	2	572.1	1314.0	13.7	249.75	30.00	.20	-2000.00	-2000.000	2.89	-2000.00
	3	287.9	1320.0	19.8	351.81	100.00	.20	-2000.00	-2000.000	.99	-2000.00
	4	169.3	1290.0	15.9	288.20	100.00	.20	-2000.00	-2000.000	2.58	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
	5	143.8	1650.0	14.2	165.61	10.00	.30	-2000.00	-2000.000	5.21	-2000.00
10425	1	2959.0	1450.0	9.5	322.99	100.00	.10	-2000.00	-2000.000	1.42	-2000.00
	2	1215.0	1780.0	17.2	299.94	30.00	.20	-2000.00	-2000.000	.73	-2000.00
	3	585.4	1710.0	14.8	264.84	30.00	.20	-2000.00	-2000.000	1.02	-2000.00
	4	406.5	1990.0	12.8	234.96	30.00	.20	-2000.00	-2000.000	1.29	-2000.00
	5	252.7	1850.0	12.0	238.52	100.00	.20	-2000.00	-2000.000	2.19	-2000.00
10450	1	2885.0	1840.0	11.2	368.40	100.00	.10	-2000.00	-2000.000	1.20	-2000.00
	2	950.2	1826.0	12.0	213.96	10.00	.20	-2000.00	-2000.000	1.24	-2000.00
	3	543.9	2080.0	10.0	194.70	10.00	.20	-2000.00	-2000.000	3.66	-2000.00
	4	308.5	1970.0	9.0	200.21	30.00	.20	-2000.00	-2000.000	8.27	-2000.00
	5	195.4	1870.0	9.0	185.81	10.00	.20	-2000.00	-2000.000	6.69	-2000.00
10475	1	2313.0	1540.0	10.8	358.74	100.00	.10	-2000.00	-2000.000	.83	-2000.00
	2	838.5	1680.0	9.1	168.64	10.00	.20	-2000.00	-2000.000	1.87	-2000.00
	3	493.3	1970.0	8.6	164.26	10.00	.20	-2000.00	-2000.000	1.27	-2000.00
	4	253.1	1690.0	8.5	158.17	10.00	.20	-2000.00	-2000.000	1.59	-2000.00
	5	100.1	1000.0	9.9	110.98	10.00	.30	-2000.00	-2000.000	9.16	-2000.00
10500	1	2055.0	1430.0	9.6	181.33	10.00	.20	-2000.00	-2000.000	2.41	-2000.00
	2	895.6	1874.0	9.6	86.72	1.00	.40	-2000.00	-2000.000	3.36	-2000.00
	3	432.2	1800.0	8.8	172.02	30.00	.20	-2000.00	-2000.000	2.37	-2000.00
	4	144.8	1010.0	10.4	54.45	1.00	.60	-2000.00	-2000.000	7.53	-2000.00
	5	139.1	1450.0	10.9	72.32	.30	.60	-2000.00	-2000.000	25.00	-2000.00
10525	1	2666.0	1810.0	5.0	181.66	3.00	.10	-2000.00	-2000.000	1.25	-2000.00
	2	987.1	2021.0	5.6	108.18	10.00	.20	-2000.00	-2000.000	3.05	-2000.00
	3	286.7	1170.0	4.8	222.86	30.00	.10	-2000.00	-2000.000	18.39	-2000.00
	4	245.1	1670.0	6.9	127.55	100.00	.30	-2000.00	-2000.000	13.88	-2000.00
	5	81.4	833.0	7.5	141.80	100.00	.30	-2000.00	-2000.000	18.60	-2000.00
10550	1	2863.0	2240.0	2.8	65.71	.03	.20	-2000.00	-2000.000	2.37	-2000.00
	2	591.2	1392.0	3.4	128.69	1.00	.10	-2000.00	-2000.000	8.55	-2000.00
	3	433.9	2030.0	2.3	80.18	.03	.30	-2000.00	-2000.000	20.56	-2000.00
	4	127.3	990.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	5	163.3	1920.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
10575	1	1351.0	1170.0	2.1	85.39	.01	.10	-2000.00	-2000.000	3.26	-2000.00
	2	720.3	1884.0	2.6	62.00	.10	.20	-2000.00	-2000.000	6.36	-2000.00
	3	178.0	920.0	******	-2000.00	-2000.00	-2000.00	-2000.00	-2000.000	-2000.00	-2000.00
	4	219.1	1910.0	5.1	114.68	30.00	.20	-2000.00	-2000.000	12.89	-2000.00
	5	127.6	1660.0	5.1	28.30	1.00	.60	-2000.00	-2000.000	6.89	-2000.00
10600	1	2214.0	1820.0	1.4	35.93	.03	.20	-2000.00	-2000.000	5.38	-2000.00
	2	390.2	967.0	2.9	21.18	.30	.50	-2000.00	-2000.000	12.76	-2000.00
	3	420.7	2080.0	4.2	82.97	10.00	.20	-2000.00	-2000.000	3.35	-2000.00
	4	197.1	1620.0	3.6	160.86	.01	.10	-2000.00	-2000.000	4.77	-2000.00
	5	172.2	2130.0	4.7	63.52	.30	.30	-2000.00	-2000.000	7.74	-2000.00

Station	Dipole	Vp	Apparent Resist.	M7	Cole-Cole Parameters M-IP	TAU-IP	C-IP	M-EM	TAU-EM	Fit/IP	Fit/EM
10625	1	1171.0	910.0	2.2	86.04	.30	.10	-2000.00	-2000.000	4.22	-2000.00
	2	849.1	1999.0	4.1	81.97	10.00	.20	-2000.00	-2000.000	2.61	-2000.00
	3	348.7	1630.0	3.8	145.12	100.00	.10	-2000.00	-2000.000	2.78	-2000.00
	4	230.8	1810.0	4.2	160.64	100.00	.10	-2000.00	-2000.000	2.99	-2000.00
	5	231.0	2720.0	4.9	94.85	10.00	.20	-2000.00	-2000.000	5.01	-2000.00
10650	1	3687.0	2630.0	4.6	174.66	.30	.10	-2000.00	-2000.000	2.09	-2000.00
	2	923.2	1976.0	4.6	172.43	30.00	.10	-2000.00	-2000.000	1.97	-2000.00
	3	520.2	2220.0	4.3	169.85	.10	.10	-2000.00	-2000.000	2.58	-2000.00
	4	412.6	2940.0	3.6	97.29	.03	.20	-2000.00	-2000.000	7.93	-2000.00
	5	212.5	2270.0	3.9	155.11	.01	.10	-2000.00	-2000.000	4.04	-2000.00
10675	1	1952.0	1250.0	3.6	135.50	10.00	.10	-2000.00	-2000.000	2.40	-2000.00
	2	871.9	1676.0	4.3	159.57	1.00	.10	-2000.00	-2000.000	1.08	-2000.00
	3	648.0	2480.0	4.8	36.15	.30	.50	-2000.00	-2000.000	11.91	-2000.00
	4	277.3	1770.0	3.5	74.28	.10	.20	-2000.00	-2000.000	1.54	-2000.00
	5	229.3	2200.0	3.4	54.35	.30	.30	-2000.00	-2000.000	23.02	-2000.00
10700	1	2670.0	1820.0	3.2	125.41	.30	.10	-2000.00	-2000.000	2.26	-2000.00
	2	1269.0	2590.0	3.5	76.86	.10	.20	-2000.00	-2000.000	2.52	-2000.00
	3	508.0	2070.0	3.3	129.05	100.00	.10	-2000.00	-2000.000	4.33	-2000.00
	4	318.4	2170.0	3.3	135.84	.10	.10	-2000.00	-2000.000	3.89	-2000.00
10725	1	948.8	2482.0	2.4	39.27	.10	.30	-2000.00	-2000.000	3.26	-2000.00
	2	277.4	2177.0	2.5	54.32	.10	.20	-2000.00	-2000.000	4.46	-2000.00
	3	157.4	2460.0	2.8	119.21	100.00	.10	-2000.00	-2000.000	10.44	-2000.00
10750	1	615.7	2760.0	1.6	37.52	.03	.20	-2000.00	-2000.000	25.88	-2000.00
	2	185.6	2490.0	1.8	44.95	.01	.30	-2000.00	-2000.000	24.99	-2000.00
10775	1	545.6	2850.0	2.4	21.75	.30	.50	-2000.00	-2000.000	15.81	-2000.00

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 111W.IND
DATA FILE : 111W.DAT

LINE NO. : 1114

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	11.3	9.4	8.8	8.0	6.1	4.6	3.9	3.1	1.9	1.8	380.6	-30.	114.
		2	22.9	19.5	17.6	16.1	13.2	9.7	7.5	5.6	4.6	3.3	215.7	-43.	194.
		3	23.5	19.9	17.7	16.5	12.9	9.7	8.7	6.4	4.2	4.3	181.8	1.	325.
		4	20.7	17.7	15.8	14.4	11.4	8.3	6.8	5.2	3.7	3.0	85.5	13.	256.
		5	18.9	16.4	14.6	12.8	10.8	8.4	7.1	4.9	3.9	3.6	47.2	-28.	212.
10050	2	1	17.4	15.0	13.3	12.0	9.6	7.2	5.9	4.6	3.6	3.0	1088.0	-52.	316.
		2	25.3	21.9	19.6	17.6	14.3	10.8	8.8	7.0	5.4	4.4	509.5	3.	444.
		3	20.6	18.4	16.5	14.6	12.0	9.1	7.4	5.8	4.2	3.6	196.5	2.	342.
		4	21.3	19.4	17.3	15.0	12.6	9.5	7.7	6.1	4.4	3.7	94.2	-24.	274.
		5	16.4	15.3	13.6	11.3	9.9	7.6	6.2	4.9	3.2	2.7	66.8	3.	291.
10075	2	1	24.1	20.5	18.2	16.4	13.3	10.0	8.2	6.5	5.1	4.2	2390.0	1.	701.
		2	21.3	18.0	16.1	14.4	11.6	8.7	7.1	5.7	4.4	3.6	739.1	-8.	651.
		3	23.4	20.1	18.0	16.1	13.3	10.2	8.4	6.5	5.2	4.1	294.0	11.	516.
		4	18.4	15.8	14.2	12.4	10.4	8.0	6.5	5.1	4.3	3.1	165.4	-15.	485.
		5	25.7	22.0	19.8	17.2	14.2	10.5	8.6	6.8	5.3	4.3	96.0	18.	423.
10100	2	1	9.5	7.6	6.7	5.9	4.6	3.4	2.7	2.1	1.6	1.3	2392.0	-29.	910.
		2	16.5	13.6	12.2	10.8	8.7	6.4	5.2	4.1	3.2	2.6	604.6	25.	694.
		3	12.5	10.3	9.1	8.1	6.4	4.6	3.9	3.0	2.1	1.8	318.6	-16.	730.
		4	21.2	17.5	15.6	13.9	11.1	8.2	6.7	5.3	4.1	3.3	164.5	14.	620.
		5	20.8	17.3	15.5	13.7	11.1	8.2	6.9	5.4	4.1	3.4	99.2	4.	569.
10125	2	1	14.9	12.5	10.8	9.8	7.7	5.8	4.7	3.7	2.8	2.3	2313.0	-37.	940.
		2	10.3	8.7	7.3	6.6	5.2	3.8	3.0	2.3	1.8	1.4	861.6	-39.	1054.
		3	19.2	16.2	13.9	12.7	10.0	7.4	6.0	4.7	3.6	3.0	412.4	24.	1000.
		4	19.2	16.2	14.1	12.7	10.2	7.6	6.2	4.9	3.8	3.1	206.4	9.	840.
		5	13.7	11.7	10.1	9.0	7.4	5.4	4.5	3.5	2.6	2.1	236.8	-3.	1440.
10150	2	1	9.4	7.6	6.6	6.0	4.6	3.4	2.7	2.1	1.6	1.3	1415.0	-44.	740.

		2	18.8	15.4	13.5	12.3	9.6	7.2	5.8	4.6	3.5	2.9	544.0	29.	854.
		3	20.7	17.0	15.1	13.7	10.8	8.1	6.6	5.2	4.1	3.3	308.8	-5.	960.
		4	14.4	11.8	10.7	9.6	7.5	5.7	4.6	3.6	2.8	2.2	286.0	-5.	1490.
		5	27.0	21.9	19.5	17.5	13.6	10.1	8.0	6.3	4.8	3.9	419.0	-5.	3280.
10175	2	1	14.0	11.4	9.8	8.8	6.8	4.9	4.1	3.0	2.3	2.0	1348.0	13.	580.
		2	19.6	16.2	14.2	12.8	10.2	7.6	6.1	4.9	3.8	3.2	545.3	-16.	713.
		3	13.2	11.2	9.7	8.7	6.9	5.2	4.3	3.3	2.7	2.2	494.9	-11.	1290.
		4	25.8	21.5	18.7	16.7	13.1	9.6	7.8	6.0	4.6	3.7	686.5	0.	2990.
		5	36.5	31.5	27.5	24.9	20.0	14.9	12.3	9.6	7.7	6.3	250.2	3.	1630.
10200	2	1	19.6	16.2	14.2	12.9	10.2	7.6	6.1	4.9	3.9	3.2	903.5	-6.	388.
		2	14.5	12.0	10.7	9.6	7.6	5.7	4.6	3.6	2.9	2.3	733.4	-4.	946.
		3	26.1	21.4	19.0	16.8	13.3	9.8	7.8	6.1	4.7	3.8	969.6	-5.	2490.
		4	38.1	32.1	28.9	25.7	20.7	15.6	12.5	10.0	7.8	6.4	322.8	11.	1380.
		5	47.6	39.9	36.0	32.0	25.7	19.3	15.7	12.4	9.7	7.9	278.5	-18.	1790.
10225	2	1	7.6	6.1	5.3	4.7	3.6	2.6	2.0	1.8	1.4	1.1	1515.0	8.	640.
		2	22.0	18.0	15.7	14.1	11.0	8.0	6.5	5.0	3.8	3.1	1508.0	-6.	1910.
		3	38.9	32.8	29.0	26.4	20.9	15.8	12.8	10.1	7.7	6.3	452.4	8.	1140.
		4	47.4	39.8	35.1	32.0	25.5	19.1	15.7	12.3	9.6	7.9	354.5	-15.	1500.
		5	39.4	33.7	29.5	27.0	21.7	16.4	13.6	10.8	8.5	7.0	113.6	13.	720.
10250	2	1	15.5	12.7	10.8	9.8	7.6	5.5	4.4	3.4	2.5	2.1	1827.0	-16.	1390.
		2	37.6	31.6	28.1	24.9	20.3	15.1	12.3	9.6	7.5	6.1	425.8	-15.	978.
		3	46.0	38.7	34.7	30.6	25.0	18.8	15.4	12.0	9.5	7.7	247.5	-21.	1130.
		4	39.6	32.8	30.7	25.4	21.8	16.4	13.5	10.8	8.6	7.1	74.2	41.	568.
10275	2	1	42.1	35.1	30.8	28.0	22.1	16.5	13.4	10.5	8.1	6.6	1561.0	-30.	1020.
		2	47.5	39.7	35.1	32.0	25.4	19.0	15.5	12.1	9.4	7.7	577.4	-26.	1133.
		3	41.9	34.5	30.4	28.1	22.5	17.1	14.1	11.2	8.9	7.3	138.4	34.	540.
10300	2	1	46.8	38.5	34.0	31.0	24.2	17.8	14.4	11.3	8.8	7.1	2157.0	-32.	1650.
		2	49.8	40.5	36.2	33.5	26.2	19.9	16.2	13.0	10.1	8.3	281.0	31.	645.
10325	2	1	51.6	43.9	39.6	35.6	29.2	22.4	18.5	14.8	11.7	9.7	297.3	24.	405.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 112W.IND
DATA FILE : 112W.DAT

LINE NO. : 1124

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	22.0	19.1	17.5	15.6	12.8	9.7	8.0	6.3	4.8	3.8	460.7	22.	178.
		2	25.2	22.0	21.0	17.2	15.1	11.3	9.1	7.1	5.6	4.5	185.8	6.	216.
		3	23.4	21.4	19.7	14.3	14.3	11.2	8.5	6.5	4.7	3.6	78.0	-46.	181.
		4	21.9	20.3	19.6	12.5	13.1	9.1	7.9	6.6	5.0	3.8	58.5	14.	226.
		5	19.2	17.9	16.2	9.9	12.0	9.2	7.4	5.3	4.6	2.7	37.3	-20.	216.
10050	2	1	17.4	14.7	13.4	11.9	9.6	7.3	5.8	4.5	3.5	2.8	634.3	64.	255.
		2	19.2	16.3	15.5	13.6	11.3	8.5	6.7	5.4	4.1	3.3	174.8	-34.	211.
		3	19.2	16.3	15.9	13.6	11.3	8.4	6.3	5.3	4.0	3.1	111.2	5.	260.
		4	17.6	14.6	15.5	13.3	10.5	7.8	5.7	4.6	2.9	2.0	64.0	-10.	257.
		5	16.4	12.7	13.4	11.1	10.5	7.0	5.0	4.2	2.7	1.9	47.3	-8.	285.
10075	2	1	11.3	9.5	8.2	7.5	5.8	4.3	3.4	2.7	2.0	1.6	1520.0	-2.	540.
		2	13.2	11.0	9.5	8.6	6.8	5.1	4.1	3.1	2.4	1.9	635.0	19.	687.
		3	13.2	11.2	9.9	9.1	7.4	5.1	4.0	3.3	2.7	2.0	354.9	-46.	760.
		4	13.4	11.4	10.0	9.0	7.1	4.9	3.9	3.3	2.5	1.9	169.8	18.	610.
		5	19.1	16.1	14.1	12.6	10.0	7.1	5.8	4.6	3.4	2.9	116.9	-11.	630.
10100	2	1	7.7	6.4	5.5	4.7	3.7	2.7	2.1	1.6	1.2	1.0	2872.0	16.	950.
		2	9.1	7.5	6.6	5.8	4.6	3.3	2.7	2.1	1.6	1.3	1262.0	-28.	1260.
		3	8.3	7.0	6.2	5.2	4.3	3.2	2.6	2.1	1.6	1.3	649.7	-16.	1290.
		4	15.5	12.8	11.5	9.8	8.0	5.9	4.7	3.7	3.0	2.3	369.3	-3.	1230.
		5	11.8	9.8	8.9	7.3	6.0	4.4	3.6	2.9	2.2	1.8	183.1	-8.	910.
10125	2	1	7.7	5.9	5.3	4.7	3.5	2.6	2.0	1.5	1.2	.9	2247.0	-53.	940.
		2	7.9	6.2	5.6	5.0	3.8	2.8	2.2	1.7	1.3	1.0	917.1	17.	1151.
		3	15.1	12.2	10.7	9.7	7.4	5.6	4.5	3.5	2.6	2.0	551.7	-16.	1380.
		4	11.6	9.3	8.2	7.4	5.6	4.2	3.3	2.6	1.9	1.5	212.1	2.	880.
		5	.0	-.2	-.5	.0	-.6	-.4	-.4	-.4	-.4	-.5	145.6	-10.	910.
10150	2	1	6.8	5.3	4.7	4.1	3.2	2.2	1.7	1.2	.9	.7	1982.0	8.	1030.

		2	15.5	12.4	11.0	9.9	7.7	5.7	4.6	3.6	2.8	2.2	731.9	-6.	1149.
		3	11.6	9.4	8.6	7.3	6.0	4.4	3.7	2.7	2.2	1.8	316.1	-16.	990.
		4	.4	-.1	.4	-.3	-.1	-.3	-.2	-.2	-.2	-.1	175.8	-1.	920.
		5	12.1	9.3	8.6	6.7	5.6	4.0	3.1	2.2	1.7	1.2	266.9	19.	2090.
10175	2	1	6.6	4.9	3.9	3.6	2.5	1.7	1.3	1.0	.8	.6	1530.0	119.	840.
		2	12.2	9.8	8.7	7.8	6.1	4.5	3.5	2.8	2.1	1.7	558.2	-9.	922.
		3	1.1	.4	.7	.1	.1	.0	-.1	.0	-.1	.0	286.7	-13.	940.
		4	12.6	9.7	9.0	7.4	5.7	3.8	2.9	2.4	1.5	1.2	390.5	25.	2150.
		5	38.4	31.6	29.0	25.5	20.5	15.4	12.3	9.8	7.6	6.1	281.7	-19.	2320.
10200	2	1	11.7	9.2	8.2	7.2	5.5	4.0	3.2	2.5	1.9	1.5	1986.0	-14.	670.
		2	2.5	1.5	1.5	1.1	.7	.4	.3	.1	.1	.0	824.7	-14.	835.
		3	13.4	10.5	9.2	7.9	6.1	4.2	3.4	2.5	1.7	1.4	875.5	22.	1760.
		4	39.5	32.9	29.3	26.4	21.0	15.7	12.8	10.0	7.7	6.3	632.1	-13.	2130.
		5	50.7	42.6	38.8	34.4	27.5	20.7	17.1	13.5	10.4	8.6	449.4	-33.	2270.
10225	2	1	.8	.5	.3	-.1	.0	-.2	-.1	-.1	-.1	-.1	1370.0	-8.	610.
		2	12.5	9.9	8.4	7.2	5.5	3.8	2.9	2.2	1.5	1.2	1065.0	20.	1430.
		3	38.9	32.7	28.9	25.9	20.8	15.6	12.7	10.0	7.7	6.2	753.3	-32.	2020.
		4	51.4	43.4	38.4	34.7	27.9	21.1	17.2	13.7	10.6	8.5	446.1	-19.	2000.
		5	58.5	49.7	44.2	40.3	32.7	25.1	20.6	16.5	13.0	10.7	207.8	28.	1390.
10250	2	1	9.1	6.9	5.8	5.1	3.7	2.5	1.9	1.4	1.0	.7	2848.0	14.	1110.
		2	38.6	32.1	28.4	25.7	20.4	15.3	12.4	9.7	7.5	6.1	1480.0	-23.	1740.
		3	50.9	42.8	38.1	34.7	27.6	20.9	17.1	13.5	10.4	8.6	902.0	-25.	2110.
		4	59.0	50.2	45.0	41.1	33.2	25.5	21.1	16.9	13.3	11.1	308.8	17.	1210.
		5	57.5	48.4	43.0	39.1	31.3	23.6	19.4	15.4	12.1	10.0	164.9	28.	970.
10275	2	1	36.1	30.1	26.6	24.2	19.2	14.3	11.6	9.1	7.0	5.7	2544.0	-32.	1500.
		2	48.6	41.0	36.3	33.1	26.5	20.0	16.3	12.9	10.0	8.1	1121.0	-36.	1990.
		3	60.2	51.2	45.7	42.0	34.0	25.9	21.3	17.3	13.5	11.1	317.2	21.	1120.
		4	57.1	48.0	42.4	38.8	31.0	23.5	19.1	15.2	11.8	9.7	149.6	32.	880.
		5	48.8	39.8	34.0	30.9	24.5	18.1	14.8	11.7	8.9	7.3	45.4	13.	403.
10300	2	1	45.9	38.6	34.4	31.4	25.1	19.0	15.5	12.3	9.6	7.9	3727.0	-46.	1910.
		2	63.7	53.9	48.5	44.5	35.9	27.6	22.7	18.2	14.4	11.9	564.0	2.	870.
		3	60.6	50.6	45.5	41.5	33.0	25.0	20.4	16.3	12.6	10.5	261.8	34.	800.
		4	51.9	42.2	37.8	34.5	26.9	20.1	16.2	12.8	9.9	8.2	76.4	-11.	393.
		5	80.3	63.2	58.5	53.7	46.9	31.8	28.1	22.2	18.0	15.9	143.5	16.	1100.
10325	2	1	71.6	61.8	55.3	51.0	41.6	32.2	26.7	21.5	17.1	14.2	1087.0	3.	680.
		2	65.3	55.9	49.6	45.5	36.7	28.0	23.0	18.4	14.5	12.0	401.1	41.	755.
		3	54.2	45.9	40.2	36.8	29.2	22.0	18.0	14.2	11.1	9.1	113.6	-9.	420.
		4	83.0	71.3	63.6	58.3	47.4	36.5	30.2	24.2	19.2	16.0	183.7	22.	1150.
		5	73.6	64.8	57.8	53.9	44.2	34.4	28.5	22.9	18.2	14.9	122.4	-25.	1150.
10350	2	1	65.1	55.4	49.7	45.3	36.6	28.0	23.1	18.5	14.6	12.0	1760.0	-9.	1080.
		2	60.0	50.1	44.8	40.2	32.2	24.2	19.6	15.6	12.1	9.9	229.2	-13.	423.
		3	81.3	69.1	62.6	56.5	45.9	35.2	28.9	23.2	18.3	15.1	409.6	11.	1500.

		4	78.1	67.1	61.6	55.3	45.7	35.4	29.3	23.6	18.8	15.6	204.6	-28.	1250.
10375	2	1	45.7	38.5	34.1	30.8	24.2	17.9	14.5	11.4	8.9	7.2	1195.0	-6.	830.
		2	77.0	63.7	56.8	51.8	41.4	31.4	25.8	20.6	16.2	13.3	933.1	-13.	1953.
		3	77.5	66.1	59.9	54.8	44.7	34.5	28.6	23.1	18.3	15.2	386.3	-22.	1610.
10400	2	1	48.7	40.5	35.7	32.5	25.5	19.1	15.5	12.3	9.5	7.8	4376.0	-16.	2740.
		2	63.9	53.8	48.0	43.9	35.4	27.1	22.4	18.0	14.2	11.8	1112.0	-47.	2090.
10425	2	1	38.3	32.8	29.5	27.3	22.4	17.4	14.4	11.7	9.3	7.7	621.3	-41.	1625.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 113W.IND
DATA FILE : 113W.DAT

LINE NO. : 1134

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	8.2	6.8	6.1	5.5	4.5	3.5	2.8	2.3	1.8	1.4	602.1	-5.	210.
		2	23.0	19.5	17.9	16.2	13.3	10.1	8.3	6.5	5.1	4.1	224.0	-14.	234.
		3	21.9	18.6	17.1	15.4	13.4	9.4	7.8	5.3	4.9	3.4	128.4	7.	260.
		4	17.8	16.1	14.4	12.7	10.7	8.5	6.8	5.2	4.2	3.3	59.4	26.	207.
		5	18.6	15.5	14.5	12.3	9.5	8.1	5.4	5.2	4.3	2.3	35.1	-7.	183.
10050	2	1	23.3	19.8	17.7	16.0	13.0	9.8	7.9	6.2	4.8	3.9	616.6	-10.	261.
		2	21.2	18.1	16.3	14.6	11.9	8.8	7.2	5.6	4.3	3.4	250.7	12.	319.
		3	16.7	14.5	13.3	11.6	9.3	7.0	5.7	4.8	2.8	2.3	98.0	18.	248.
		4	17.2	15.2	14.1	11.4	10.0	7.6	5.7	4.1	3.8	2.8	52.6	-1.	223.
		5	19.0	14.9	12.5	10.1	11.4	7.9	6.4	5.2	5.2	3.3	41.8	-30.	266.
10075	2	1	18.8	15.9	14.0	12.7	10.2	7.6	6.2	4.9	3.8	3.1	1560.0	15.	466.
		2	16.2	14.1	12.4	11.1	9.1	6.8	5.6	4.4	3.4	2.8	399.3	45.	358.
		3	15.0	13.9	11.7	10.7	8.9	6.5	5.4	4.2	3.2	2.7	205.4	-34.	367.
		4	16.6	15.6	13.3	11.9	10.2	6.6	5.5	4.9	3.5	2.9	125.4	-33.	375.
		5	16.9	16.0	13.9	11.7	10.3	7.6	6.3	4.5	4.0	3.0	91.5	-1.	410.
10100	2	1	8.2	7.0	5.9	5.1	4.3	3.0	2.5	1.9	1.5	1.3	1104.0	49.	770.
		2	9.1	7.9	6.7	5.7	4.7	3.6	3.0	2.2	1.5	1.3	438.0	-32.	916.
		3	11.0	10.3	8.1	7.7	6.1	4.3	3.7	2.9	2.1	1.9	220.5	-37.	920.
		4	12.7	12.5	9.6	9.5	7.1	5.0	4.1	3.3	2.7	2.3	140.4	0.	970.
		5	9.7	10.6	7.0	7.4	5.3	3.2	2.7	2.4	1.9	2.0	80.1	-8.	838.
10125	2	1	7.8	6.0	5.3	4.9	3.6	2.6	2.0	1.5	1.2	.9	2395.0	-9.	970.
		2	10.8	8.5	7.7	7.0	5.2	3.8	3.0	2.4	1.8	1.4	1123.0	-28.	1370.
		3	12.7	10.2	9.1	8.4	6.4	4.9	4.0	3.0	2.4	2.0	718.4	-6.	1750.
		4	10.1	7.9	7.1	6.6	4.9	3.9	3.0	2.2	1.9	1.6	279.8	-12.	1140.
		5	-2.5	-2.9	-2.4	-2.3	-2.1	-1.7	-1.5	-1.1	-.9	-.8	169.7	11.	1030.
10150	2	1	8.4	6.8	5.8	5.3	4.1	3.1	2.5	2.0	1.5	1.2	2355.0	-29.	860.

		2	11.3	9.5	8.1	7.4	5.8	4.3	3.4	2.7	2.0	1.7	1222.0	-6.	1350.
		3	8.5	7.0	5.9	5.5	4.2	3.1	2.5	1.9	1.5	1.2	552.5	9.	1220.
		4	-4.3	-3.8	-3.8	-3.3	-2.9	-2.3	-1.9	-1.6	-1.3	-1.1	245.9	-1.	900.
		5	8.1	6.4	5.1	4.7	3.3	2.2	1.6	1.1	.7	.4	313.6	-12.	1730.
10175	2	1	10.9	9.2	7.9	7.1	5.5	4.1	3.3	2.6	1.9	1.6	1777.0	-38.	880.
		2	8.8	7.5	6.3	5.7	4.4	3.2	2.5	2.0	1.6	1.2	693.4	1.	1036.
		3	-4.8	-3.7	-3.7	-3.3	-3.2	-2.0	-1.6	-1.5	-1.3	-.8	290.2	-34.	860.
		4	8.9	7.4	5.9	5.2	3.7	2.7	2.1	1.3	.8	.8	303.4	24.	1510.
		5	34.2	29.0	25.2	23.0	18.3	13.8	11.1	8.5	6.7	5.4	306.8	-58.	2290.
10200	2	1	7.9	6.2	5.4	4.8	3.6	2.5	2.0	1.5	1.1	.8	1891.0	-13.	790.
		2	-3.3	-3.2	-2.9	-2.8	-2.3	-1.8	-1.5	-1.3	-1.0	-.8	650.6	3.	817.
		3	10.5	8.0	6.9	6.1	4.3	2.9	2.2	1.8	1.2	1.0	656.6	-10.	1640.
		4	36.1	30.0	26.7	24.2	19.2	14.3	11.6	9.3	7.1	5.9	513.6	-55.	2150.
		5	46.2	39.2	35.2	32.4	26.2	20.1	16.6	13.5	10.5	8.9	274.6	23.	1720.
10225	2	1	-1.2	-1.5	-1.3	-1.4	-1.2	-1.0	-.9	-.8	-.6	-.5	1716.0	7.	740.
		2	10.4	7.9	6.8	5.8	4.3	2.9	2.1	1.5	1.0	.8	1323.0	-5.	1730.
		3	36.9	30.7	27.4	24.6	19.6	14.6	11.9	9.3	7.3	6.0	943.2	-103.	2460.
		4	48.8	41.2	37.2	33.7	27.4	20.8	17.2	13.7	10.8	9.0	388.1	51.	1690.
		5	65.4	55.0	50.3	44.6	36.6	27.8	22.7	18.3	14.4	11.8	143.1	10.	930.
10250	2	1	10.1	7.5	6.9	5.7	4.3	2.9	2.2	1.6	1.1	.8	3259.0	-17.	1440.
		2	39.6	32.6	29.4	26.3	20.9	15.6	12.6	9.9	7.6	6.2	1626.0	-81.	2150.
		3	49.8	42.2	38.2	34.6	28.0	21.4	17.3	13.8	10.9	8.8	708.8	3.	1870.
		4	68.1	57.2	52.1	46.9	38.0	28.9	23.5	18.8	14.9	12.2	199.4	29.	880.
		5	60.1	49.9	45.8	41.0	33.2	25.3	20.8	16.5	12.9	10.6	117.8	-3.	780.
10275	2	1	38.7	32.4	28.6	25.8	20.5	15.3	12.4	9.7	7.5	6.1	2620.0	-87.	1640.
		2	50.6	43.4	38.8	35.3	28.6	21.8	17.9	14.3	11.2	9.2	899.0	22.	1693.
		3	70.5	60.4	54.0	48.8	39.7	30.1	24.8	19.9	15.6	12.8	196.2	2.	730.
		4	60.6	52.2	46.8	41.8	34.3	25.9	21.3	17.0	13.3	10.9	108.9	6.	680.
		5	70.8	58.0	50.1	44.6	35.0	26.2	20.1	16.1	12.4	10.0	85.4	44.	804.
10300	2	1	46.2	39.4	35.3	32.3	26.1	20.0	16.4	13.1	10.3	8.5	2600.0	30.	1450.
		2	75.7	64.8	58.0	52.9	42.8	32.8	27.0	21.6	17.0	14.0	410.4	3.	690.
		3	65.9	56.5	50.6	45.8	37.1	28.3	23.3	18.5	14.5	11.8	222.2	-2.	740.
		4	71.4	58.0	51.2	45.7	36.0	26.7	21.4	16.7	12.8	10.4	141.2	50.	790.
10325	2	1	91.3	78.8	70.9	64.1	52.9	40.8	33.8	27.2	21.7	18.0	378.0	6.	741.
		2	71.6	62.6	56.0	48.7	41.5	31.5	26.2	20.9	16.8	13.9	137.2	-13.	807.
		3	76.5	64.0	57.5	46.7	40.4	29.5	24.3	19.0	15.0	12.5	79.9	63.	938.
10350	2	1	72.2	61.6	55.7	50.6	41.1	31.5	26.0	20.9	16.6	13.7	627.4	-23.	938.
		2	76.5	62.6	56.0	49.6	39.7	29.6	24.1	19.0	14.8	12.1	211.5	61.	948.
10375	2	1	84.1	71.1	62.9	56.7	45.2	33.7	27.2	21.6	16.9	13.8	338.3	61.	1062.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 114W.IND
DATA FILE : 114W.DAT

LINE NO. : 1144

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	8.5	6.7	6.0	5.4	4.2	3.1	2.5	1.9	1.5	1.2	1281.0	14.	460.
		2	16.6	14.6	13.5	12.3	9.8	7.4	5.9	4.6	3.6	2.8	168.3	-8.	182.
		3	21.3	18.5	16.8	15.2	12.2	9.3	7.2	5.8	4.5	3.3	128.7	6.	270.
		4	19.4	16.8	15.1	13.5	10.8	8.1	6.2	4.9	3.7	2.3	87.9	27.	317.
		5	27.4	24.6	23.0	20.6	16.8	13.5	9.1	8.2	7.5	4.0	31.9	6.	172.
10050	2	1	11.1	8.9	8.1	7.2	5.7	4.2	3.4	2.6	2.0	1.6	410.2	24.	161.
		2	18.5	15.4	14.2	12.6	10.3	7.7	6.2	4.9	3.8	3.0	226.5	10.	266.
		3	17.5	14.1	13.1	11.2	9.7	6.9	5.5	4.3	3.5	2.8	140.8	21.	330.
		4	27.1	22.2	19.5	16.8	16.6	10.9	9.3	8.0	7.4	6.8	46.5	-1.	182.
		5	20.0	16.3	17.3	14.2	12.3	10.1	8.1	6.7	5.3	4.4	38.9	6.	228.
10075	2	1	13.1	10.6	9.4	8.6	6.7	4.9	3.9	3.1	2.4	1.9	558.7	16.	318.
		2	12.9	10.4	9.4	8.5	6.6	4.8	3.8	3.0	2.2	1.7	252.3	26.	432.
		3	15.0	13.3	13.4	13.0	11.8	10.3	8.9	5.8	5.3	4.6	88.8	-5.	303.
		4	18.0	14.9	13.9	11.9	10.1	8.1	7.1	5.6	4.3	3.6	52.8	32.	301.
		5	13.1	10.9	11.1	9.0	7.5	5.5	4.1	3.1	2.5	2.0	45.0	-15.	385.
10100	2	1	8.9	7.2	6.3	5.5	4.4	3.4	2.8	2.0	1.5	1.4	1099.0	36.	570.
		2	13.2	11.1	10.1	9.2	7.6	6.0	5.0	4.1	3.3	2.8	332.0	-4.	521.
		3	12.3	10.4	10.0	8.5	7.5	6.0	5.1	4.5	3.8	3.3	156.5	14.	490.
		4	9.3	7.1	7.4	5.0	4.4	3.3	2.3	1.5	1.1	.7	123.8	-5.	640.
		5	10.6	7.5	8.4	6.0	6.1	4.3	3.3	3.0	2.0	2.0	71.3	-7.	559.
10125	2	1	13.8	11.9	10.6	9.6	7.9	6.2	5.2	4.3	3.5	3.0	1930.0	-9.	670.
		2	11.8	10.3	9.3	8.3	7.0	5.6	4.7	4.0	3.2	2.8	863.9	10.	904.
		3	7.8	6.3	5.5	4.4	3.4	2.3	1.6	1.1	.8	.5	551.9	-11.	1150.
		4	10.3	8.6	7.7	6.4	5.2	3.7	2.9	2.2	1.6	1.2	285.0	1.	990.
		5	-5.0	-4.4	-3.5	-4.8	-3.7	-2.8	-2.8	-2.4	-1.8	-2.0	121.4	-3.	630.
10150	2	1	10.6	9.0	8.0	7.5	6.2	5.0	4.3	3.7	3.1	2.7	1891.0	7.	860.

		2	5.6	4.1	3.1	2.7	1.7	.8	.4	.2	-.1	-.2	1051.0	-8.	1430.
		3	8.2	6.7	5.6	5.1	3.7	2.5	1.8	1.3	.8	.6	534.8	9.	1450.
		4	-7.4	-6.9	-6.9	-6.4	-5.8	-5.0	-4.4	-3.8	-3.3	-2.9	194.8	-13.	880.
		5	3.5	2.0	.9	.8	-.1	-.8	-1.1	-1.2	-1.3	-1.3	377.8	-30.	2570.
10175	2	1	10.8	8.9	7.9	7.2	5.5	4.3	3.5	2.9	2.3	2.0	2581.0	0.	810.
		2	12.8	10.7	9.5	8.8	7.4	5.6	4.6	3.7	3.0	2.3	1217.0	-6.	1146.
		3	-2.9	-3.1	-3.0	-2.9	-2.9	-2.5	-2.2	-1.9	-1.7	-1.4	475.6	-7.	894.
		4	6.1	4.4	3.5	2.9	1.6	1.0	.5	.2	.0	-.1	694.8	-44.	2181.
		5	29.7	24.5	21.7	19.6	14.7	11.5	9.2	7.0	5.4	4.4	314.6	-22.	1481.
10200	2	1	12.3	10.5	9.1	8.4	6.9	5.2	4.4	3.6	2.8	2.4	3937.0	13.	1260.
		2	1.0	.4	-.2	-.3	-.6	-.5	-.6	-.6	-.6	-.5	978.1	-7.	940.
		3	8.6	7.3	5.5	5.5	3.9	2.7	2.0	1.5	1.0	.7	1471.0	-48.	2800.
		4	34.1	29.1	24.8	23.5	18.4	13.8	11.3	8.9	6.9	5.7	346.0	-27.	1100.
		5	34.4	29.9	25.4	24.5	19.5	15.2	12.6	10.0	7.9	6.6	391.2	-42.	1880.
10225	2	1	.8	.2	.4	.2	.3	.0	.0	-.1	-.1	-.1	1259.0	-7.	650.
		2	13.7	10.6	9.1	7.8	5.7	4.2	3.1	2.4	1.8	1.4	1530.0	-52.	2400.
		3	35.7	30.1	27.0	24.4	19.7	14.8	12.2	9.6	7.4	6.0	394.3	-42.	1230.
		4	36.0	30.8	28.0	25.4	21.1	16.1	13.6	10.8	8.4	6.8	291.0	-36.	1520.
		5	53.5	45.8	41.6	37.9	31.7	24.4	20.3	16.4	13.2	11.1	104.2	34.	810.
10250	2	1	20.5	16.8	14.7	13.2	10.5	7.9	6.4	5.1	4.0	3.3	2989.0	-54.	2180.
		2	42.6	36.7	32.8	29.6	24.0	18.2	15.0	12.0	9.3	7.7	481.2	-41.	1054.
		3	41.4	36.3	32.5	29.5	24.4	18.8	15.6	12.4	9.9	8.2	369.1	-17.	1610.
		4	59.5	52.1	46.3	42.1	35.3	27.3	22.4	17.3	14.9	11.6	90.4	10.	660.
		5	65.2	57.5	51.1	45.4	38.0	28.8	23.9	18.7	15.2	12.5	60.4	-16.	661.
10275	2	1	49.6	41.7	37.0	33.5	26.7	20.0	16.3	12.8	10.0	8.1	1104.0	-41.	2030.
		2	52.6	45.4	40.8	37.0	30.0	22.8	18.8	14.9	11.7	9.6	337.7	-43.	1871.
		3	65.5	57.1	51.6	46.9	38.0	29.3	24.6	20.1	15.5	12.3	78.3	16.	865.
		4	70.6	62.1	56.9	49.6	41.1	31.1	26.1	21.2	16.3	12.5	37.2	-13.	687.
		5	48.2	41.1	38.3	30.1	26.9	19.1	16.0	12.3	9.8	7.8	18.5	48.	513.
10300	2	1	60.0	50.6	45.4	41.4	33.3	25.5	20.8	16.6	13.0	10.7	670.8	-27.	1914.
		2	79.3	67.5	61.5	55.7	45.5	35.1	28.9	23.3	18.4	15.1	94.2	-2.	806.
		3	83.4	68.8	64.4	56.1	46.0	35.1	29.3	24.1	18.5	16.1	52.5	-14.	896.
		4	60.2	43.3	43.3	35.1	29.6	21.9	17.7	15.2	10.6	9.5	20.1	38.	573.
		5	69.5	50.7	55.2	44.4	39.3	30.7	25.3	21.1	17.1	14.2	14.2	7.	608.
10325	2	1	77.3	66.6	59.5	54.5	44.3	34.1	28.3	22.8	18.1	15.0	348.3	20.	994.
		2	81.3	71.6	62.6	57.4	46.5	35.4	29.3	23.3	18.4	15.2	113.5	-3.	971.
		3	81.4	75.4	61.5	57.3	44.8	32.9	29.2	23.4	15.6	14.5	38.2	8.	653.
		4	63.8	66.3	54.9	51.0	41.3	31.4	27.1	21.7	16.9	14.6	19.9	32.	567.
10350	2	1	79.7	67.7	60.9	55.3	44.8	34.1	28.0	22.4	17.5	14.2	671.3	-7.	1239.
		2	84.8	72.1	65.4	57.6	47.3	35.7	29.4	23.4	18.4	15.2	120.2	13.	666.
		3	87.5	76.0	70.5	61.9	52.1	40.5	34.4	27.4	21.4	18.9	66.4	26.	734.

10375	2	1	77.9	66.8	58.7	53.3	43.0	32.5	26.8	21.3	16.7	13.9	478.4	13.	625.
		2	85.6	76.0	66.2	61.2	50.6	39.0	32.9	26.4	21.1	17.7	161.9	16.	635.
10400	2	1	65.7	56.5	51.0	45.4	37.5	28.8	23.9	19.2	15.1	12.5	337.3	15.	1059.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 115W.IND
DATA FILE : 115W.DAT

LINE NO. : 1154

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	6.4	5.2	4.4	4.1	3.2	2.3	1.9	1.5	1.1	.9	795.2	-8.	438.
		2	12.0	10.3	9.0	8.5	6.8	5.1	4.2	3.3	2.5	2.1	178.6	-3.	295.
		3	18.5	16.3	14.3	13.6	10.9	8.4	7.0	5.5	4.2	3.5	67.0	22.	221.
		4	22.7	20.2	17.5	16.7	12.8	10.0	8.6	6.5	5.2	4.5	33.5	-21.	184.
		5	22.2	20.0	16.8	16.8	12.8	9.9	8.6	6.4	4.8	4.6	22.9	10.	189.
10050	2	1	7.6	6.3	5.4	4.9	3.9	2.8	2.3	1.8	1.3	1.1	715.3	-3.	299.
		2	15.2	13.3	11.5	10.8	8.6	6.5	5.3	4.1	3.2	2.6	186.0	26.	233.
		3	19.0	17.2	14.4	13.7	11.1	8.3	6.8	5.1	4.0	3.3	76.6	-13.	192.
		4	19.5	18.8	15.6	15.9	12.1	8.8	7.1	5.4	4.5	3.5	47.6	-1.	199.
		5	21.3	20.0	18.9	21.3	16.7	14.4	8.6	7.1	5.1	3.6	63.7	-14.	400.
10075	2	1	9.8	8.2	7.1	6.5	5.2	3.8	3.1	2.4	1.8	1.5	602.9	34.	270.
		2	15.5	13.3	11.8	10.8	8.9	6.7	5.6	4.4	3.5	2.6	168.7	-12.	227.
		3	16.9	15.3	13.4	12.1	10.2	7.4	6.1	4.9	3.6	3.0	91.2	6.	244.
		4	19.8	18.0	15.4	14.0	11.8	8.5	6.9	5.1	3.0	3.1	108.2	-18.	480.
		5	17.7	16.8	14.3	12.8	11.4	7.4	5.7	4.3	2.1	2.5	65.7	34.	442.
10100	2	1	8.9	7.4	6.4	5.8	4.6	3.5	2.7	2.2	1.7	1.4	674.9	-10.	249.
		2	12.7	11.1	9.8	8.7	7.1	5.1	4.4	3.3	2.5	2.1	250.3	-13.	277.
		3	15.6	13.5	12.1	11.0	8.8	6.2	5.3	4.4	3.7	2.7	273.9	-2.	600.
		4	15.4	13.1	12.1	11.4	9.2	5.2	5.3	4.8	4.3	2.8	141.0	31.	520.
		5	9.2	8.9	8.1	6.9	5.7	3.0	4.0	2.9	1.8	1.7	34.5	22.	191.
10125	2	1	8.1	6.4	5.7	5.1	4.0	2.9	2.3	1.8	1.4	1.1	896.2	4.	375.
		2	11.8	9.6	8.5	7.7	6.0	4.5	3.6	2.8	2.1	1.7	646.0	-24.	811.
		3	11.4	9.6	8.7	8.0	6.9	5.0	3.8	2.4	1.7	2.1	310.2	29.	770.
		4	5.8	4.5	4.3	3.7	2.7	2.2	2.4	1.1	.7	.5	59.2	20.	247.
		5	1.7	2.7	2.4	2.6	1.9	.4	.0	.4	1.5	1.8	38.5	-10.	241.
10150	2	1	9.9	7.9	7.1	6.2	4.9	3.5	2.9	2.2	1.7	1.3	1083.0	-24.	700.

		2	9.0	7.3	6.5	5.6	4.6	3.4	2.7	2.1	1.7	1.3	406.2	37.	797.
		3	4.0	3.3	2.9	2.3	2.0	1.4	1.3	.8	.4	.4	75.5	20.	295.
		4	.4	.3	2.2	-1.9	.9	-.2	.2	.1	.3	.1	42.4	-16.	277.
		5	4.9	4.4	5.3	-.3	2.5	1.2	.7	.4	1.1	.9	98.9	6.	970.
10175	2	1	7.2	5.6	5.1	4.5	3.6	2.6	2.1	1.7	1.3	1.1	1915.0	30.	700.
		2	3.2	2.3	2.2	1.8	1.5	1.0	.8	.6	.4	.3	295.6	14.	327.
		3	.3	.0	.3	-.6	-.2	-.4	-.2	.0	.1	.0	145.0	-5.	320.
		4	5.0	3.4	4.1	2.1	2.2	1.3	.9	.6	.4	.4	307.8	7.	1130.
		5	20.6	17.2	16.3	12.6	11.0	7.8	6.2	4.4	2.6	2.1	105.6	1.	580.
10200	2	1	5.8	4.6	4.0	3.6	2.8	2.0	1.5	1.2	.9	.6	1387.0	25.	670.
		2	3.8	2.6	2.3	1.7	1.4	1.1	1.1	.6	.5	.7	389.1	-19.	563.
		3	6.5	4.5	4.6	3.3	2.7	1.9	1.3	1.0	.7	.5	663.6	9.	1910.
		4	23.8	18.7	17.4	14.7	12.0	8.9	7.0	5.3	4.2	3.1	193.8	2.	930.
		5	31.7	26.5	26.1	19.5	17.4	17.2	13.8	8.2	9.3	5.9	113.4	-62.	820.
10225	2	1	7.2	6.1	5.2	4.6	3.7	2.6	2.0	1.7	1.3	1.2	2717.0	20.	1020.
		2	10.8	9.0	7.7	6.6	5.1	3.7	3.1	2.3	1.6	1.2	2118.0	5.	2400.
		3	27.1	23.5	20.1	18.0	14.4	10.5	8.7	6.7	5.1	4.1	578.2	-15.	1300.
		4	37.8	34.7	30.0	27.3	22.3	16.1	13.6	10.3	9.1	8.0	259.0	-36.	970.
		5	36.2	34.0	29.4	26.7	22.7	17.0	14.1	11.2	9.4	8.4	185.7	-32.	1050.
10250	2	1	11.0	8.9	7.8	6.8	5.3	3.8	2.9	2.2	1.7	1.3	2716.0	76.	1700.
		2	30.8	25.8	22.5	20.1	16.0	11.7	9.8	7.8	5.5	4.7	435.2	-19.	819.
		3	41.0	35.4	32.3	29.5	23.4	17.7	13.6	11.3	9.6	6.7	200.7	-28.	750.
		4	37.6	33.7	31.3	28.4	22.9	18.2	14.2	11.3	9.7	6.9	138.6	-30.	870.
		5	61.6	52.2	46.0	40.6	34.5	25.5	21.8	17.6	12.8	12.2	47.3	40.	445.
10275	2	1	45.3	37.6	32.9	29.7	23.2	17.4	13.9	10.8	8.1	6.5	1969.0	-23.	1370.
		2	57.3	49.5	44.5	40.8	33.1	24.0	19.7	15.8	12.7	10.1	489.2	-43.	1024.
		3	48.6	42.5	38.2	35.1	28.7	22.5	18.8	15.4	11.9	9.3	269.7	-31.	1120.
		4	67.3	58.8	52.1	47.7	38.8	30.4	25.2	20.1	15.1	12.5	75.6	35.	527.
		5	57.6	52.6	47.0	43.2	35.6	23.5	19.5	15.6	13.3	10.2	30.2	12.	316.
10300	2	1	76.8	65.1	58.6	52.6	42.7	32.6	26.6	21.2	16.6	13.7	579.9	-50.	1517.
		2	65.7	56.8	51.3	45.1	38.0	28.7	23.7	18.8	15.0	12.2	257.4	-39.	2020.
		3	80.9	70.4	64.7	53.6	47.0	35.3	29.1	24.0	20.6	16.2	57.5	50.	901.
		4	59.7	52.0	50.6	36.9	36.3	26.6	21.4	17.6	14.2	11.7	20.4	-6.	532.
		5	55.7	50.4	52.9	33.3	38.7	26.5	22.4	19.3	17.8	13.2	13.5	0.	531.
10325	2	1	49.2	42.8	38.2	34.8	28.5	21.7	18.0	14.4	11.4	9.4	786.3	-27.	2468.
		2	83.1	74.7	65.5	59.1	48.1	36.2	30.3	23.8	18.6	15.4	81.5	20.	768.
		3	64.9	62.1	53.2	48.3	40.0	27.7	23.5	16.2	15.0	15.0	27.0	17.	508.
		4	51.9	54.2	44.3	36.6	35.6	24.2	22.2	15.5	14.1	14.0	17.5	-5.	550.
		5	15.9	26.5	19.9	12.2	15.7	8.2	10.0	******	5.9	7.3	14.7	18.	693.
10350	2	1	82.4	70.5	63.2	57.7	46.7	35.8	29.5	23.7	18.7	15.4	945.0	31.	723.
		2	73.5	62.1	55.4	50.2	40.7	30.8	25.4	20.2	16.0	13.3	208.9	13.	479.
		3	95.0	82.8	75.0	67.4	55.6	43.5	36.5	29.9	23.5	19.0	146.5	9.	670.

		4	65.5	57.5	52.2	47.6	38.8	30.9	25.2	21.3	16.1	13.1	90.9	7.	695.
10375	2	1	67.8	57.2	51.0	46.4	37.2	28.3	23.3	18.6	14.6	12.1	440.2	31.	575.
		2	90.0	77.6	70.2	64.5	52.6	41.1	34.1	27.5	21.9	18.1	190.5	6.	747.
		3	64.8	56.8	50.5	45.9	38.6	29.0	23.2	18.2	15.8	14.3	101.4	2.	790.
10400	2	1	74.7	64.1	57.2	52.4	42.5	32.5	26.8	21.4	16.9	13.9	981.0	5.	1540.
		2	58.2	51.1	45.4	41.6	34.3	26.1	21.8	17.4	13.8	11.5	268.2	-4.	1263.
10425	2	1	54.8	47.1	42.4	38.5	31.6	24.3	20.1	16.2	12.8	10.6	719.3	-9.	1411.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 116W.IND
DATA FILE : 116W.DAT

LINE NO. : 1164

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	8.4	6.8	5.9	5.4	4.2	3.1	2.5	1.9	1.5	1.2	562.6	-6.	294.
		2	13.3	11.6	10.3	9.3	7.6	5.8	4.8	3.8	3.0	2.3	145.0	9.	227.
		3	17.0	15.7	13.9	12.5	10.6	8.0	6.8	5.5	4.2	3.4	63.2	0.	198.
		4	19.9	19.6	17.1	14.7	12.9	9.3	7.9	5.9	4.6	3.9	32.4	5.	169.
		5	22.4	23.2	19.3	16.5	14.6	10.2	9.0	6.9	5.3	4.1	20.0	-9.	156.
10050	2	1	9.5	7.6	6.8	6.2	4.8	3.6	2.9	2.2	1.7	1.4	456.1	23.	220.
		2	14.9	12.5	11.4	10.3	8.4	6.4	5.2	4.1	3.2	2.6	140.5	-3.	203.
		3	19.4	16.3	15.1	13.6	11.4	8.7	7.1	5.6	4.3	3.4	59.3	13.	171.
		4	23.8	19.9	18.7	16.2	13.6	10.3	8.1	6.4	5.0	4.1	35.9	-27.	173.
		5	22.9	18.5	17.8	14.6	14.1	10.8	8.0	6.9	4.7	3.4	22.5	8.	163.
10075	2	1	9.2	7.8	6.6	6.2	4.8	3.6	2.9	2.3	1.8	1.4	468.7	13.	253.
		2	15.7	13.7	11.8	11.2	8.9	6.7	5.5	4.3	3.4	2.7	137.1	12.	222.
		3	20.6	18.2	15.3	15.1	11.9	9.0	7.5	5.8	4.5	3.7	66.0	-23.	214.
		4	21.5	19.6	15.5	16.3	12.2	9.4	8.1	5.9	4.7	4.0	36.7	9.	198.
		5	20.6	19.2	13.9	16.1	12.0	9.1	7.7	5.8	4.5	3.7	30.4	-26.	247.
10100	2	1	9.1	7.5	6.5	5.9	4.8	3.4	2.9	2.2	1.7	1.4	403.4	14.	253.
		2	17.1	14.6	13.0	11.7	9.6	7.2	5.9	4.7	3.6	2.9	135.0	-11.	254.
		3	18.2	16.2	14.2	13.0	10.9	8.1	6.6	5.2	3.9	3.1	62.0	2.	233.
		4	18.1	16.3	14.3	12.4	10.5	7.7	6.6	5.0	3.9	3.1	44.5	-28.	279.
		5	16.3	15.0	12.4	10.6	10.4	7.5	6.1	4.5	3.6	2.6	25.1	24.	236.
10125	2	1	10.9	8.9	7.7	7.0	5.5	4.0	3.2	2.5	1.9	1.5	542.1	2.	309.
		2	13.5	11.7	10.2	9.4	7.4	5.5	4.5	3.5	2.7	2.2	167.8	-4.	287.
		3	14.0	12.3	10.6	9.8	7.7	5.5	4.3	3.4	2.5	2.0	98.2	-21.	335.
		4	14.7	14.1	12.4	11.9	9.9	6.5	5.1	4.7	3.6	2.8	49.3	10.	281.
		5	10.6	12.1	8.3	7.6	6.9	5.0	4.5	3.0	2.5	1.7	35.7	19.	305.
10150	2	1	7.1	5.7	6.5	4.2	4.1	2.9	2.2	1.9	1.5	1.2	126.8	5.	306.

		2	8.8	6.2	10.4	4.1	5.5	3.8	2.7	2.6	2.1	1.6	57.8	-26.	419.
		3	5.7	4.5	14.7	2.9	8.5	6.0	2.4	3.1	4.2	2.1	29.8	23.	431.
		4	2.2	-1.0	21.7	-4.2	9.1	5.5	1.5	3.6	4.0	2.2	17.1	27.	412.
		5	-8.3	-8.2	19.7	-20.5	5.2	.6	-1.4	.7	2.9	2.0	8.5	49.	309.
10175	2	1	7.9	6.4	5.5	4.9	3.7	2.9	2.2	1.7	1.2	1.0	923.1	-10.	445.
		2	8.0	6.6	5.6	5.1	4.1	2.6	2.2	1.8	1.5	1.0	329.1	15.	476.
		3	7.5	6.1	5.3	5.1	4.0	2.8	2.2	1.9	1.4	.9	191.5	35.	550.
		4	-.7	-1.5	-1.7	-.3	-.7	-1.0	-.9	-.3	-.2	-1.1	87.5	33.	422.
		5	4.2	1.7	.7	2.0	.6	-.1	-.2	-.1	-.2	-.8	128.2	-8.	920.
10200	2	1	6.3	4.5	4.1	3.8	2.8	2.0	1.5	1.3	1.0	.8	998.4	2.	401.
		2	6.8	4.7	4.7	4.0	3.2	2.4	2.0	1.4	1.1	.9	473.3	49.	571.
		3	-2.1	-3.4	-1.7	-2.2	-1.7	-1.3	-1.3	-1.0	-.6	-.6	198.2	17.	470.
		4	2.7	.2	1.4	.4	.2	-.3	-.6	-.4	-.3	-.2	267.8	8.	1070.
		5	26.0	19.2	20.0	16.8	13.6	9.2	5.8	6.2	4.4	3.6	154.7	-45.	930.
10225	2	1	5.6	4.4	3.8	3.3	2.7	2.0	1.6	1.1	.7	.5	723.1	55.	528.
		2	-2.8	-2.2	-2.0	-2.6	-2.1	-1.9	-1.5	-.8	-.4	-.1	223.0	18.	488.
		3	2.0	1.6	1.1	.6	.3	.0	-.4	-.8	-1.2	-.9	275.9	17.	1200.
		4	25.1	20.6	18.1	16.3	13.5	10.8	9.2	6.0	2.0	2.3	147.8	-48.	1070.
		5	23.0	21.0	18.7	16.2	12.8	8.9	7.0	6.5	6.4	5.7	107.2	-31.	1170.
10250	2	1	-2.4	-2.2	-1.8	-2.2	-1.6	-1.4	-1.1	-.8	-.6	-.5	530.0	22.	346.
		2	2.5	1.3	1.4	.1	.2	-.1	-.3	-.4	-.3	-.3	540.1	13.	1059.
		3	25.3	21.9	19.8	16.6	14.0	9.8	7.8	5.8	4.6	3.8	266.0	-49.	1040.
		4	23.7	20.5	19.3	14.4	14.3	10.3	9.0	7.1	5.3	4.5	174.2	-39.	1130.
		5	60.9	53.0	49.0	38.6	34.0	25.6	22.0	17.4	14.3	11.5	57.2	34.	561.
10275	2	1	6.4	4.7	4.1	3.3	2.4	1.6	1.2	.7	.5	.3	1841.0	-31.	990.
		2	31.1	25.6	23.0	20.1	16.2	12.0	9.5	7.6	5.9	4.8	602.4	-52.	978.
		3	28.4	23.9	22.3	19.3	16.2	12.3	10.2	7.8	6.2	5.2	329.2	-32.	1060.
		4	66.1	54.1	50.3	44.2	36.6	27.5	22.7	18.6	14.6	11.2	92.6	38.	501.
		5	69.5	53.6	51.4	41.2	35.9	26.5	21.1	18.1	14.3	12.3	48.0	4.	389.
10300	2	1	39.1	32.9	29.1	26.1	20.9	15.5	12.5	9.9	7.6	6.1	1567.0	-52.	890.
		2	33.5	28.7	25.9	22.9	19.1	14.7	12.3	9.7	7.6	6.5	534.3	-12.	915.
		3	70.4	61.5	55.5	48.1	40.0	29.2	23.8	19.7	15.2	12.5	137.2	28.	460.
		4	69.3	60.3	54.9	44.6	39.6	28.7	23.2	18.7	15.8	11.6	61.3	15.	350.
		5	63.4	59.0	56.7	44.1	37.8	19.7	17.2	18.1	11.0	6.7	32.6	-12.	279.
10325	2	1	46.8	39.5	35.3	32.1	25.8	19.6	16.0	12.7	9.9	8.1	3294.0	-39.	1430.
		2	82.6	70.8	63.5	57.6	46.7	35.6	29.3	23.3	18.5	15.2	422.6	14.	552.
		3	76.5	65.7	58.9	53.4	42.7	32.7	27.2	21.9	16.2	13.7	164.1	9.	420.
		4	64.1	56.1	51.4	46.4	37.3	29.7	24.4	19.9	13.7	12.9	73.3	1.	319.
		5	60.5	53.5	48.6	42.6	35.6	26.9	22.7	17.4	13.9	12.0	69.3	-22.	453.
10350	2	1	86.6	74.1	66.6	60.5	49.5	38.0	31.9	25.4	19.8	16.9	745.7	35.	585.
		2	83.9	73.6	67.7	60.7	49.7	38.7	29.1	24.9	20.8	15.4	162.7	-21.	383.
		3	66.0	57.5	55.1	47.9	39.2	36.2	30.6	21.7	16.5	15.6	71.1	2.	334.

		4	64.6	56.7	54.9	45.8	40.1	31.3	23.7	20.6	17.4	13.0	61.8	-26.	485.
10375	2	1	77.8	66.0	58.6	53.6	42.9	32.7	26.8	21.4	16.8	13.9	1186.0	1.	900.
		2	70.2	61.6	55.4	51.6	42.2	32.8	27.3	22.0	17.4	14.5	223.1	-16.	512.
		3	64.4	57.1	51.4	48.2	39.9	31.3	25.7	20.2	15.2	13.0	152.3	-11.	690.
10400	2	1	56.2	49.1	44.0	39.0	32.7	25.0	20.7	16.6	13.2	10.9	191.8	-10.	547.
		2	60.7	55.8	48.7	42.2	36.9	27.7	23.8	18.8	14.9	12.2	121.9	-15.	1043.
10425	2	1	36.4	30.1	26.7	24.2	19.1	14.3	11.5	9.1	7.0	5.7	2114.0	-26.	5100.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 117W.IND
DATA FILE : 117W.DAT

LINE NO. : 1174

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	9.3	7.5	6.6	6.0	4.7	3.5	2.8	2.3	1.7	1.4	520.1	4.	272.
		2	15.1	12.9	11.6	10.6	8.6	6.5	5.3	4.2	3.2	2.6	157.5	20.	247.
		3	18.5	15.9	14.5	13.2	10.8	8.3	6.8	5.4	4.3	3.5	71.3	-22.	223.
		4	21.3	18.3	16.8	15.2	12.6	9.7	8.0	6.4	5.0	4.1	35.7	-5.	186.
		5	23.2	19.8	18.4	16.4	13.6	10.4	8.5	6.7	5.2	4.2	19.4	8.	152.
10050	2	1	9.7	8.0	6.9	6.3	4.9	3.7	2.9	2.3	1.8	1.4	552.2	21.	288.
		2	14.6	12.7	11.3	10.3	8.4	6.4	5.2	4.1	3.2	2.6	175.0	-17.	274.
		3	18.3	16.2	14.8	13.3	11.1	8.5	7.0	5.6	4.3	3.5	71.3	-10.	223.
		4	21.4	18.7	17.3	15.1	12.8	9.8	8.0	6.3	4.9	4.1	34.0	8.	177.
		5	23.4	20.4	19.1	15.8	13.6	9.9	8.6	6.2	5.1	4.1	19.6	-2.	153.
10075	2	1	10.5	8.7	7.5	6.9	5.4	4.1	3.3	2.6	2.0	1.6	602.8	-3.	252.
		2	16.1	13.7	12.3	11.3	9.1	7.0	5.7	4.5	3.5	2.8	206.7	-9.	259.
		3	19.9	17.5	15.9	14.2	11.7	9.0	7.4	5.9	4.6	3.7	70.6	-12.	176.
		4	23.4	19.7	18.8	16.2	13.5	10.2	8.1	6.4	4.9	4.0	34.8	16.	145.
		5	22.7	18.8	18.6	15.2	13.0	9.7	7.8	6.2	4.7	3.6	33.3	-16.	209.
10100	2	1	10.6	8.6	7.6	7.0	5.5	4.1	3.3	2.6	2.0	1.6	518.3	-5.	285.
		2	16.9	14.3	13.0	11.9	9.6	7.3	5.9	4.7	3.6	2.9	113.1	-1.	186.
		3	22.2	18.5	17.0	15.7	12.6	9.6	7.8	6.2	4.8	3.6	53.5	8.	176.
		4	23.4	19.1	17.6	16.2	12.6	9.4	7.6	5.9	4.5	3.8	39.9	-19.	219.
		5	22.4	17.4	16.5	15.6	12.1	9.1	7.1	5.6	4.3	3.3	25.9	7.	213.
10125	2	1	9.7	8.0	7.1	6.3	5.1	3.8	3.1	2.4	1.8	1.5	504.8	5.	264.
		2	17.6	14.7	13.2	12.1	9.7	7.3	5.9	4.7	3.6	2.9	138.9	5.	218.
		3	20.6	17.4	15.8	14.6	11.4	8.6	6.9	5.4	4.0	3.2	84.5	-17.	264.
		4	22.1	18.2	16.3	15.6	11.9	9.1	7.3	5.8	4.4	3.5	47.3	7.	247.
		5	18.0	13.6	12.2	13.0	8.5	6.6	5.4	4.0	2.7	2.2	29.0	2.	227.
10150	2	1	11.6	9.8	8.5	7.6	6.0	4.5	3.6	2.8	2.1	1.7	509.0	19.	238.

		2	16.2	13.8	12.5	11.1	8.8	6.6	5.2	4.1	3.1	2.5	226.6	-3.	318.
		3	18.4	15.5	14.4	12.5	10.0	7.6	5.9	4.7	3.5	2.8	97.9	-8.	274.
		4	15.6	11.9	12.9	9.6	7.9	6.2	4.3	3.6	2.5	1.9	50.6	4.	237.
		5	8.4	4.0	8.2	3.5	3.1	2.7	.8	1.1	.4	.1	32.4	-10.	228.
10175	2	1	10.1	8.1	7.0	6.3	4.9	3.6	2.9	2.2	1.7	1.4	1130.0	0.	520.
		2	13.4	11.2	9.9	8.9	7.1	5.2	4.2	3.2	2.4	2.0	310.4	-7.	429.
		3	11.3	9.6	8.6	7.6	6.1	4.4	3.5	2.7	1.9	1.4	123.2	6.	340.
		4	6.2	5.1	4.5	3.8	3.4	2.4	1.6	1.0	1.1	1.2	62.9	-10.	290.
		5	1.8	1.1	1.1	.0	.2	-.2	-.4	-.6	-.6	-.5	50.2	26.	347.
10200	2	1	9.4	7.9	6.8	5.9	4.6	3.4	2.7	2.1	1.6	1.3	1051.0	-2.	570.
		2	8.8	7.8	6.3	6.1	4.5	3.4	2.7	2.1	1.5	1.2	275.9	8.	455.
		3	4.2	4.0	2.4	3.3	2.1	1.8	1.6	1.4	.0	.0	118.3	-7.	390.
		4	.7	1.6	-1.1	1.5	-.8	-.4	-.2	-.2	-1.0	-.9	79.1	21.	435.
		5	7.6	7.2	3.1	6.4	3.1	2.6	2.2	2.2	-.1	-.3	64.9	-18.	536.
10225	2	1	7.3	6.1	5.0	4.5	3.5	2.6	2.1	1.6	1.1	1.0	1033.0	12.	550.
		2	3.6	3.4	2.6	2.1	1.8	1.2	.9	.6	.5	.4	313.6	-7.	509.
		3	-1.4	-.3	-.8	-1.2	-.5	-.8	-.7	-.6	-.4	-.5	176.6	19.	570.
		4	6.3	6.0	4.5	3.4	3.3	1.6	1.3	.9	.7	.4	124.5	-15.	670.
		5	12.9	13.0	10.4	8.5	8.0	5.9	4.8	3.5	3.3	2.6	105.2	15.	850.
10250	2	1	5.4	4.0	3.2	3.1	2.2	1.5	1.2	.8	.6	.5	783.1	2.	501.
		2	.4	.3	-.1	-.1	-.4	-.6	-.4	-.6	-.5	-.5	340.8	25.	655.
		3	6.9	6.2	4.6	4.4	3.0	1.8	1.5	.8	.6	.5	216.6	-20.	830.
		4	13.5	12.8	10.0	9.7	7.3	5.2	4.4	3.0	2.6	2.2	165.8	16.	1060.
		5	36.8	34.3	28.5	27.8	22.5	16.8	13.6	9.8	8.8	7.0	81.6	3.	784.
10275	2	1	1.9	1.4	.5	.3	.2	.0	.0	-.1	.0	.0	864.8	52.	565.
		2	9.4	8.2	6.8	6.0	4.4	3.1	2.3	1.7	1.1	.8	452.9	-16.	888.
		3	15.1	14.0	10.8	9.8	8.4	5.8	5.2	3.6	3.0	2.5	306.5	20.	1200.
		4	39.9	37.1	29.5	27.2	23.7	16.5	15.0	11.3	9.7	7.7	120.2	0.	780.
		5	67.6	64.1	53.8	49.9	40.3	29.7	24.7	19.3	15.2	13.0	102.4	-13.	1000.
10300	2	1	12.1	9.3	8.2	6.9	5.3	3.7	2.9	2.2	1.6	1.3	1824.0	-10.	810.
		2	17.4	14.4	13.2	11.4	9.2	6.7	5.5	4.3	3.3	2.7	766.8	8.	1031.
		3	44.1	37.9	34.9	30.5	25.3	19.1	15.7	12.5	9.9	8.1	333.5	15.	890.
		4	75.3	64.9	58.8	51.6	42.4	31.8	25.7	20.4	16.6	13.0	227.1	-29.	1010.
		5	71.2	61.2	58.8	48.6	42.3	31.3	27.3	22.4	16.1	15.5	79.9	1.	537.
10325	2	1	19.2	15.6	13.9	12.3	9.8	7.3	5.9	4.7	3.6	2.9	1153.0	5.	720.
		2	49.8	42.3	38.3	34.7	28.1	21.8	17.7	14.0	11.1	9.1	389.7	-14.	734.
		3	80.8	68.7	62.3	55.9	45.7	35.4	28.5	22.3	18.2	15.0	199.4	-27.	740.
		4	76.6	63.9	60.4	54.3	43.7	30.7	25.3	24.1	17.2	13.7	69.8	25.	438.
		5	66.8	55.8	52.9	47.5	38.6	27.9	22.9	19.9	14.4	12.1	49.4	-7.	465.
10350	2	1	54.3	46.3	41.6	38.0	30.9	23.7	19.6	15.7	12.5	10.4	1108.0	-8.	610.
		2	86.2	73.8	66.5	60.2	49.2	37.6	30.9	24.7	19.3	15.7	451.6	-37.	746.
		3	75.9	66.3	60.3	53.2	44.1	33.9	28.1	22.8	19.2	16.3	141.7	15.	460.

		4	64.6	56.2	51.4	44.6	36.8	28.3	24.1	19.4	16.7	14.5	94.6	7.	521.
		5	68.9	60.0	55.5	47.6	40.5	30.6	25.0	20.8	17.1	14.1	123.6	2.	1020.
10375	2	1	76.4	64.9	58.1	52.8	42.6	32.5	26.7	21.4	16.8	13.8	1668.0	-27.	790.
		2	75.9	64.8	59.1	53.8	44.1	34.2	28.1	22.4	17.6	14.7	278.5	20.	397.
		3	60.0	51.9	47.5	42.3	36.5	28.2	24.7	21.3	17.4	13.6	189.8	-24.	540.
		4	67.4	57.0	52.4	46.3	39.1	29.6	25.7	22.0	18.3	14.8	238.2	-7.	1130.
		5	59.1	50.7	49.1	42.3	36.9	28.7	21.2	14.3	10.0	9.3	93.9	-7.	670.
10400	2	1	58.1	50.5	45.0	41.1	33.3	25.7	20.6	16.8	13.2	11.3	1208.0	68.	540.
		2	54.1	45.7	41.4	38.3	31.3	23.9	20.8	16.3	13.0	10.0	551.3	-46.	741.
		3	60.7	52.9	47.2	43.2	35.1	27.1	22.4	18.1	14.2	12.1	622.4	11.	1670.
		4	48.8	42.9	38.2	35.2	28.8	22.2	18.4	14.9	11.8	9.9	184.7	-15.	820.
		5	51.9	45.4	40.5	36.9	30.8	23.3	19.3	15.2	12.3	11.2	158.2	1.	1060.
10425	2	1	34.9	29.3	26.1	23.7	19.0	14.4	11.8	9.4	7.3	6.0	2412.0	17.	1260.
		2	48.6	41.3	37.0	33.7	27.3	20.8	17.0	13.6	10.6	8.8	1510.0	-14.	2370.
		3	39.6	33.9	30.7	27.9	22.9	17.7	14.6	11.7	9.3	7.5	418.2	12.	1310.
		4	44.9	38.0	34.2	30.7	25.4	19.6	16.3	13.2	10.5	7.8	254.3	-22.	1330.
		5	45.3	38.6	34.8	31.6	25.9	20.0	16.4	13.1	10.3	8.4	207.4	14.	1620.
10450	2	1	32.4	26.9	23.5	21.4	16.8	12.6	10.2	8.0	6.2	5.0	4511.0	-31.	3290.
		2	28.2	24.0	21.4	19.8	15.9	12.2	10.0	8.0	6.2	5.1	684.5	0.	1499.
		3	31.5	27.2	24.9	23.1	18.9	14.2	11.7	9.4	7.3	6.3	335.2	-27.	1460.
		4	35.2	29.6	26.5	24.8	20.0	15.2	12.6	10.0	7.9	6.5	242.5	9.	1770.
10475	2	1	14.9	12.7	11.2	10.2	8.2	6.3	5.2	4.2	3.3	2.8	2153.0	35.	1730.
		2	24.7	21.1	18.5	17.1	14.0	10.7	8.9	7.1	5.6	4.7	611.7	-38.	1477.
		3	25.7	22.3	19.4	17.8	14.2	10.9	9.4	7.6	5.5	5.0	434.8	20.	2090.
10500	2	1	18.0	14.9	13.2	11.9	9.3	7.0	5.7	4.5	3.5	2.8	1782.0	-11.	1550.
		2	21.1	18.0	15.8	14.6	11.5	8.8	7.2	5.7	4.5	3.7	755.4	14.	1976.
10525	2	1	17.2	14.4	12.8	11.6	9.3	7.1	5.9	4.6	3.6	2.9	2770.0	1.	1930.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 118W.IND
DATA FILE : 118W.DAT

LINE NO. : 1184

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	13.6	11.3	10.0	9.2	7.3	5.5	4.5	3.5	2.7	2.2	384.3	8.	182.
		2	18.4	16.1	14.7	13.5	11.1	8.5	7.0	5.6	4.3	3.5	104.2	-4.	148.
		3	21.1	18.6	17.0	15.7	12.9	9.9	8.2	6.6	5.2	4.2	59.6	-11.	169.
		4	21.2	19.1	17.3	16.1	13.3	10.2	8.5	6.7	5.3	4.3	32.5	-1.	154.
		5	22.6	20.4	18.4	17.2	14.1	10.7	8.9	7.1	5.5	4.5	19.4	26.	138.
10050	2	1	13.4	11.0	10.0	9.1	7.4	5.5	4.6	3.6	2.8	2.3	220.7	22.	135.
		2	18.1	15.3	14.1	12.8	10.6	8.1	6.7	5.3	4.2	3.4	111.8	14.	206.
		3	20.3	17.7	16.7	15.0	12.7	9.9	8.3	6.6	5.0	3.4	53.6	-29.	197.
		4	21.5	18.4	17.3	15.2	12.8	9.5	7.7	5.9	5.1	5.3	27.2	23.	167.
		5	26.7	23.1	21.8	18.7	15.7	11.8	9.7	7.8	6.2	4.9	20.4	6.	188.
10075	2	1	11.8	9.3	8.6	7.6	6.2	4.6	3.8	2.9	2.3	1.9	680.4	20.	284.
		2	16.8	14.3	13.2	12.0	9.9	7.6	6.3	5.0	3.9	3.2	183.3	-14.	230.
		3	20.5	17.6	16.4	15.1	12.6	9.8	8.4	6.9	5.8	4.9	99.5	11.	249.
		4	25.1	21.2	19.2	17.4	13.9	10.2	8.0	5.7	3.7	2.5	53.0	0.	222.
		5	24.5	20.8	18.9	17.4	13.9	10.3	8.4	6.4	4.8	3.9	18.9	-8.	118.
10100	2	1	13.3	11.0	9.8	9.0	7.1	5.4	4.4	3.5	2.7	2.2	514.2	-16.	230.
		2	18.3	15.8	14.2	13.2	10.7	8.3	6.8	5.4	4.3	3.3	153.0	18.	205.
		3	25.1	21.7	19.5	18.1	14.5	11.1	9.0	7.1	5.5	4.5	82.1	4.	220.
		4	24.7	21.5	19.1	18.0	14.1	10.5	8.6	6.8	5.2	3.9	25.6	-10.	114.
		5	23.5	20.4	17.8	17.2	13.1	9.8	7.9	6.2	4.5	3.6	34.0	-10.	228.
10125	2	1	12.4	10.1	9.2	8.4	6.7	5.0	4.1	3.2	2.5	2.1	622.3	20.	229.
		2	21.6	18.0	16.5	15.0	12.1	9.1	7.5	5.9	4.5	3.7	229.8	4.	254.
		3	23.3	19.8	18.2	16.5	13.3	9.9	8.0	6.3	4.8	3.9	57.1	-8.	126.
		4	24.3	20.8	19.3	17.1	13.9	10.3	8.3	6.3	4.9	3.9	62.5	-10.	230.
		5	16.7	14.5	13.9	11.8	9.9	7.2	5.8	4.4	3.5	2.8	34.4	-15.	190.
10150	2	1	15.0	12.2	11.1	9.9	7.9	5.9	4.7	3.7	2.9	2.3	864.5	6.	331.

		2	19.9	16.7	15.1	13.7	10.8	8.1	6.5	5.1	3.9	3.1	145.9	-13.	167.
		3	23.6	19.3	17.9	16.2	12.7	9.7	7.6	6.0	4.6	3.6	118.8	-3.	270.
		4	18.5	14.2	13.7	12.5	9.6	7.6	5.8	4.6	3.5	2.7	55.7	-18.	213.
		5	10.9	6.1	6.6	6.5	4.2	3.8	2.4	2.0	1.4	1.1	31.0	8.	178.
10175	2	1	13.6	11.1	9.8	8.8	6.9	5.1	4.1	3.1	2.4	1.9	477.0	5.	194.
		2	20.1	16.8	15.2	13.5	10.8	7.9	6.3	4.9	3.7	2.9	253.5	-6.	310.
		3	16.3	13.6	12.9	10.7	9.1	6.6	5.1	3.9	3.0	2.4	91.6	-18.	223.
		4	8.8	6.5	7.2	4.1	4.2	2.6	1.7	1.1	.8	.5	43.5	5.	177.
		5	5.6	3.2	4.7	.7	1.6	.5	-.1	-.3	-.3	-.6	26.4	20.	161.
10200	2	1	14.5	11.7	10.1	9.2	7.1	5.2	4.1	3.2	2.4	1.9	1636.0	-8.	730.
		2	12.8	11.1	9.8	8.9	7.1	5.2	4.2	3.3	2.5	2.0	286.8	-29.	385.
		3	7.4	7.3	6.5	5.6	4.5	3.1	2.7	2.2	1.5	1.3	95.9	24.	257.
		4	5.9	5.9	5.1	4.1	2.7	1.8	1.4	1.0	.2	.3	49.6	13.	222.
		5	4.8	4.9	4.6	2.9	2.5	1.4	1.1	.7	.4	.2	74.7	-21.	502.
10225	2	1	7.4	6.0	5.3	4.8	3.8	2.8	2.3	1.8	1.4	1.1	1045.0	-25.	400.
		2	5.2	4.4	4.1	3.5	2.7	1.9	1.5	1.1	.8	.6	241.5	31.	277.
		3	3.2	2.8	2.7	2.1	1.5	.7	.3	.2	.2	.0	102.7	9.	230.
		4	3.9	3.0	2.9	1.9	1.3	.4	.0	.0	.0	-.3	134.4	-25.	510.
		5	14.0	12.4	11.9	9.5	8.3	5.4	3.5	3.2	2.9	1.8	84.8	-13.	486.
10250	2	1	6.9	5.4	4.7	4.2	3.3	2.4	1.9	1.5	1.1	.8	786.1	36.	493.
		2	5.0	3.8	3.3	2.6	2.0	1.4	1.0	.7	.5	.4	235.4	7.	443.
		3	5.1	3.5	3.1	2.3	1.7	.9	.5	.2	.0	-.2	236.6	-25.	880.
		4	14.9	12.5	11.6	9.9	8.4	6.1	4.9	3.9	2.5	1.6	129.4	-12.	810.
		5	39.4	34.5	32.4	28.3	24.3	19.4	16.0	12.2	6.0	3.8	67.9	20.	639.
10275	2	1	6.2	5.0	4.1	3.5	2.7	1.9	1.4	1.1	.8	.6	1007.0	10.	450.
		2	6.1	5.0	3.6	2.9	2.1	1.2	.8	.4	.2	.0	740.9	-23.	997.
		3	15.2	14.1	11.4	10.0	8.1	5.7	4.7	3.5	2.9	2.5	363.0	-9.	970.
		4	41.2	38.0	31.5	28.0	22.3	15.9	12.9	11.0	9.9	8.6	179.0	28.	800.
		5	62.4	60.2	48.7	45.2	38.4	28.8	24.7	18.6	14.5	12.1	57.5	0.	386.
10300	2	1	9.2	7.0	6.0	5.0	3.7	2.5	1.8	1.3	.9	.7	2041.0	-22.	710.
		2	18.0	15.1	13.6	11.8	9.6	7.0	5.7	4.4	3.4	2.7	800.4	-21.	837.
		3	44.2	38.6	34.1	30.5	24.6	18.7	16.1	13.1	9.3	8.9	341.4	40.	710.
		4	66.6	59.3	52.3	47.0	39.3	29.8	24.9	19.6	15.6	12.9	107.4	2.	370.
		5	78.4	70.8	62.4	55.9	45.4	35.9	31.7	25.3	18.2	16.2	88.6	-7.	463.
10325	2	1	20.5	16.9	14.9	13.6	10.7	8.0	6.5	5.1	3.9	3.2	1622.0	-21.	640.
		2	50.1	42.8	38.2	35.2	28.3	21.7	17.8	14.2	11.3	9.3	481.2	36.	573.
		3	74.3	64.1	57.8	53.2	43.4	33.2	27.5	21.8	17.0	14.1	150.1	5.	350.
		4	80.4	69.3	62.0	59.1	49.0	34.6	28.7	22.2	17.8	15.3	109.3	-10.	430.
		5	75.1	66.4	58.5	53.2	42.9	34.8	29.3	23.8	18.4	14.7	120.3	-6.	710.
10350	2	1	52.5	44.5	39.8	36.4	29.4	22.4	18.4	14.7	11.6	9.5	2300.0	35.	880.
		2	83.4	71.1	64.4	58.8	48.0	37.0	30.5	24.5	19.4	16.0	375.0	0.	430.
		3	89.3	76.6	69.4	63.7	52.5	40.3	33.4	26.5	21.6	18.1	281.2	-14.	640.

		4	81.5	68.9	62.5	56.1	46.5	35.7	29.2	23.8	19.5	15.7	222.2	3.	850.
		5	70.5	59.1	55.0	48.3	40.3	31.1	25.2	21.1	17.3	13.9	138.7	3.	790.
10375	2	1	66.1	57.4	51.9	47.1	38.2	29.5	24.5	19.6	15.3	12.7	684.6	8.	447.
		2	81.5	69.5	62.6	57.0	47.3	36.3	29.9	24.0	19.3	15.9	408.2	-20.	801.
		3	75.0	65.6	59.5	53.5	44.6	34.4	29.1	23.4	18.3	14.8	292.6	-10.	1140.
		4	65.7	58.7	53.0	46.6	39.5	29.9	24.7	20.0	15.8	13.5	136.3	16.	890.
		5	49.2	45.5	40.3	34.0	29.0	20.1	16.2	14.1	12.0	9.4	83.5	16.	819.
10400	2	1	48.6	41.5	37.2	33.9	27.5	21.0	17.2	13.8	10.9	8.9	1417.0	5.	820.
		2	58.1	49.2	44.1	40.2	32.4	25.0	20.5	16.4	13.0	10.8	684.5	22.	1194.
		3	49.3	44.2	40.9	36.8	30.9	23.9	19.7	15.9	12.7	10.6	357.9	-21.	1240.
		4	40.1	34.5	31.9	27.6	24.0	18.7	15.9	12.1	10.3	8.8	135.0	-7.	780.
		5	43.9	37.4	34.5	30.5	25.8	20.6	16.4	13.3	10.6	8.3	115.7	10.	1000.
10425	2	1	36.3	30.4	26.8	24.2	19.2	14.4	11.7	9.2	7.0	6.1	2166.0	84.	1360.
		2	36.8	32.7	29.7	26.3	22.6	17.6	14.7	12.0	9.8	7.1	766.5	-57.	1444.
		3	29.6	26.6	24.2	21.2	18.0	13.4	11.2	9.2	7.0	5.9	266.6	-12.	1000.
		4	36.4	32.4	29.7	26.1	22.0	16.2	13.5	10.9	8.8	7.0	167.1	-2.	1040.
		5	39.8	35.5	32.3	27.2	22.7	17.5	14.4	12.4	8.6	7.1	138.5	-3.	1300.
10450	2	1	32.8	27.7	25.9	21.7	18.5	14.2	12.0	9.1	7.3	5.9	377.4	25.	846.
		2	21.8	20.3	21.3	14.6	14.9	9.9	7.6	7.2	5.5	4.8	119.4	-29.	803.
		3	25.5	22.7	26.0	15.2	17.9	13.2	12.8	8.3	7.1	5.7	75.1	40.	1009.
		4	28.3	23.7	29.9	11.1	19.0	16.6	18.2	7.3	10.9	7.2	48.7	-26.	1092.
		5	31.9	29.2	35.9	14.7	24.5	16.2	12.8	10.2	10.1	8.8	27.9	2.	937.
10475	2	1	24.9	20.7	19.9	15.6	13.6	9.9	8.2	6.6	5.1	4.4	461.8	4.	966.
		2	26.8	22.0	23.4	15.9	15.7	11.8	9.7	7.6	6.2	4.8	188.8	15.	1185.
		3	29.7	27.4	29.2	14.4	17.2	11.5	11.5	8.7	5.2	7.6	108.0	-24.	1350.
		4	33.2	28.3	33.6	16.6	19.8	13.8	12.3	9.9	6.6	7.4	55.0	-5.	1151.
		5	29.5	25.2	34.5	13.9	20.1	14.6	12.2	9.6	7.9	6.3	47.4	-8.	1488.
10500	2	1	17.8	14.7	13.5	11.5	9.5	7.0	5.8	4.7	3.6	3.0	562.1	42.	1103.
		2	21.9	19.0	18.3	14.8	12.9	9.7	8.0	6.3	5.0	4.1	228.7	-30.	1346.
		3	27.6	24.4	23.3	17.9	15.3	10.4	9.5	8.6	5.8	5.4	102.9	4.	1200.
		4	25.1	22.1	22.4	15.9	14.9	10.4	9.1	7.7	5.8	5.1	80.7	-20.	1584.
		5	30.2	26.2	26.1	18.8	17.5	12.5	11.1	9.1	6.7	6.1	45.6	9.	1342.
10525	2	1	16.7	13.9	12.6	10.8	9.0	6.7	5.6	4.4	3.4	2.8	551.8	-26.	1155.
		2	21.5	19.0	16.8	14.1	12.2	8.9	7.6	5.8	4.6	3.8	177.1	11.	1112.
		3	18.1	17.3	14.9	12.1	11.1	8.0	7.1	5.3	4.2	3.3	125.8	5.	1570.
		4	23.2	22.1	18.7	15.6	14.3	10.1	9.0	6.9	5.1	3.9	61.4	-23.	1285.
		5	21.6	22.6	19.0	13.9	13.9	9.7	9.1	6.5	5.0	4.3	39.2	-2.	1231.
10550	2	1	16.2	13.4	12.0	10.8	8.6	6.5	5.3	4.2	3.3	2.7	2440.0	6.	1270.
		2	14.5	12.0	10.8	9.7	7.7	5.9	4.8	3.8	3.0	2.5	1236.0	-1.	1940.
		3	18.0	15.6	14.2	12.9	10.4	7.9	6.5	5.3	4.0	3.3	560.1	-22.	1750.
		4	19.1	16.1	14.6	13.2	10.6	8.1	6.7	5.4	4.2	3.5	298.6	0.	1560.
		5	20.1	16.9	15.4	13.9	11.2	8.6	7.0	5.6	4.4	3.7	204.3	15.	1600.

10575	2	1	14.9	12.2	10.8	9.8	7.8	5.9	4.8	3.8	3.0	2.4	2659.0	-9.	2310.
		2	16.6	14.2	12.8	11.7	9.4	7.1	5.8	4.6	3.6	2.9	762.4	-21.	1994.
		3	16.2	13.7	12.5	11.1	9.0	6.9	5.6	4.6	3.6	2.9	343.9	-1.	1790.
		4	17.1	14.2	13.1	11.6	9.4	7.1	5.8	4.7	3.7	3.0	204.7	12.	1780.
		5	20.2	16.7	15.4	13.4	10.9	8.3	6.7	5.3	4.2	3.4	132.7	-1.	1730.
10600	2	1	11.9	9.4	8.4	7.5	5.8	4.3	3.4	2.6	2.1	1.7	484.1	-7.	1381.
		2	13.4	11.5	10.3	9.0	7.3	5.4	4.5	3.5	2.7	2.2	147.1	-9.	1259.
		3	13.5	11.9	10.9	9.4	7.9	5.8	5.2	3.8	2.9	2.6	85.0	11.	1452.
		4	17.8	15.6	14.1	11.8	10.0	7.3	6.2	4.8	3.8	3.2	48.7	0.	1389.
		5	16.4	15.2	13.9	11.2	10.0	7.2	6.5	4.9	3.6	3.4	38.6	19.	1654.
10625	2	1	8.3	6.6	5.9	5.1	4.2	3.1	2.5	2.0	1.6	1.2	416.9	-17.	1006.
		2	10.6	8.1	8.1	6.4	5.5	4.1	3.2	2.6	2.1	1.6	174.2	16.	1262.
		3	14.0	10.8	10.8	8.3	7.5	5.7	4.6	3.7	2.7	2.3	101.8	4.	1470.
		4	14.7	10.4	11.7	8.0	7.7	5.9	4.6	3.8	2.9	2.3	58.5	7.	1412.
		5	16.9	11.1	13.9	8.2	8.7	6.6	5.0	4.2	3.2	2.5	50.1	-29.	1815.
10650	2	1	10.0	7.9	7.1	6.1	4.9	3.6	2.8	2.2	1.7	1.3	582.0	14.	1405.
		2	12.8	10.3	9.9	8.2	6.7	5.1	4.0	3.3	2.5	2.0	182.7	18.	1323.
		3	12.7	9.9	10.2	7.8	6.5	4.9	3.7	3.2	2.5	1.9	101.7	4.	1470.
		4	15.6	11.4	12.6	9.1	7.7	5.8	4.4	4.0	2.9	2.1	61.0	-20.	1472.
		5	18.1	13.1	15.1	10.3	9.3	7.0	5.3	4.7	3.7	2.8	49.7	-20.	1800.
10675	2	1	10.5	8.6	6.9	6.6	5.1	3.8	3.1	2.4	1.9	1.5	979.1	8.	1921.
		2	9.9	8.7	7.5	7.0	5.6	4.2	3.4	2.7	2.1	1.7	293.3	16.	1726.
		3	11.7	10.1	8.6	8.0	6.3	4.7	3.9	3.0	2.3	1.9	169.2	-1.	1980.
		4	14.0	12.3	10.4	9.8	7.9	6.1	5.1	3.9	3.0	2.6	84.9	-41.	1666.
		5	13.0	11.4	9.2	8.6	7.0	4.9	4.1	3.2	2.4	1.9	66.5	45.	1957.
10700	2	1	8.9	7.1	6.4	5.8	4.5	3.3	2.7	2.1	1.7	1.3	1085.0	3.	2000.
		2	10.6	8.6	7.9	6.9	5.5	4.0	3.3	2.6	2.0	1.6	388.5	2.	2152.
		3	11.4	10.1	9.2	7.8	6.7	4.9	4.2	3.3	2.5	2.1	166.4	-42.	1840.
		4	11.6	9.8	9.2	7.4	6.3	4.6	3.9	3.0	2.4	2.0	115.6	46.	2130.
10725	2	1	9.0	7.5	6.6	5.5	4.5	3.2	2.6	2.0	1.5	1.2	484.0	9.	1680.
		2	11.6	9.9	8.5	6.7	6.1	4.2	3.5	2.6	2.0	1.6	159.3	-15.	1660.
		3	8.6	8.6	6.9	5.6	5.5	3.5	3.2	2.2	1.9	1.4	90.0	23.	1870.
10750	2	1	8.5	6.9	6.4	5.3	4.4	3.3	2.7	2.2	1.7	1.4	743.8	-7.	2123.
		2	9.6	7.6	7.2	4.8	4.8	3.4	2.8	2.2	1.8	1.5	259.0	20.	2217.
10775	2	1	9.7	7.2	6.9	5.8	4.6	3.3	2.7	2.1	1.7	1.3	681.0	15.	1943.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 119W.IND
DATA FILE : 119W.DAT

LINE NO. : 1194

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	13.9	12.0	10.7	9.8	7.9	6.0	4.9	3.9	3.0	2.4	189.4	-4.	174.
		2	19.6	17.4	15.8	14.4	11.9	9.1	7.5	6.0	4.6	3.8	56.3	-10.	156.
		3	21.3	19.2	17.5	15.9	13.2	10.2	8.4	6.6	5.1	4.1	28.8	-8.	158.
		4	22.7	20.6	18.7	16.7	14.0	10.7	8.8	6.9	5.4	4.4	13.9	15.	128.
		5	23.2	21.5	19.5	17.1	14.5	10.9	9.0	7.0	5.5	4.5	8.1	9.	113.
10050	2	1	13.4	11.3	9.9	8.9	7.3	5.6	4.6	3.6	2.8	2.3	406.3	-7.	212.
		2	19.0	16.9	15.3	13.8	11.5	8.9	7.3	5.8	4.5	3.7	129.6	-8.	203.
		3	21.8	19.6	17.8	16.0	13.5	10.3	8.6	6.8	5.3	4.3	49.5	7.	154.
		4	23.6	21.7	19.6	17.2	14.7	11.2	9.4	7.4	5.7	4.7	25.0	15.	130.
		5	26.7	25.0	22.4	19.2	16.6	12.4	10.3	8.0	6.1	5.1	22.1	-39.	173.
10075	2	1	12.4	10.5	9.5	8.5	6.9	5.3	4.3	3.4	2.7	2.1	353.8	-5.	217.
		2	19.5	17.1	15.5	14.0	11.5	8.9	7.3	5.7	4.5	3.6	86.0	1.	159.
		3	22.4	20.2	18.3	16.6	13.8	10.6	8.7	6.8	5.3	4.4	43.3	19.	159.
		4	27.5	24.8	22.1	20.1	16.5	12.4	10.2	8.0	6.2	4.9	28.9	-34.	177.
		5	26.1	24.0	20.0	17.5	14.4	10.3	8.1	6.9	4.4	4.0	14.4	35.	132.
10100	2	1	14.3	12.2	10.9	9.8	7.9	6.1	5.0	3.9	3.0	2.4	280.0	3.	162.
		2	20.5	17.9	16.4	14.7	12.2	9.5	7.8	6.2	4.8	4.0	93.0	37.	162.
		3	26.4	22.5	21.0	18.7	15.4	11.9	9.6	7.7	5.9	4.8	57.2	-49.	199.
		4	27.9	22.7	21.9	18.9	15.6	11.8	9.3	7.5	5.8	4.6	23.9	36.	138.
		5	24.4	18.3	18.2	15.4	13.0	10.2	7.8	6.1	4.7	3.7	15.8	-9.	138.
10125	2	1	13.3	11.2	10.2	9.1	7.4	5.6	4.6	3.7	2.9	2.3	593.2	41.	232.
		2	21.5	18.4	16.9	15.1	12.4	9.4	7.8	6.1	4.7	3.8	220.5	-49.	259.
		3	23.8	20.8	18.9	16.9	13.9	10.4	8.5	6.6	5.1	4.1	84.6	36.	198.
		4	23.1	19.9	18.2	15.9	13.2	9.6	7.9	6.0	4.6	3.7	38.7	-16.	151.
		5	16.3	14.3	13.3	10.8	9.5	6.6	5.4	4.1	3.1	2.4	31.0	33.	182.
10150	2	1	13.8	11.3	10.2	9.1	7.2	5.4	4.3	3.4	2.6	2.1	722.2	-44.	348.

		2	18.6	15.6	14.2	12.8	10.2	7.7	6.2	4.9	3.7	3.0	167.3	34.	242.
		3	22.3	18.7	17.5	15.7	12.5	9.4	7.5	5.9	4.3	3.4	50.8	-13.	146.
		4	18.5	14.2	13.9	12.4	9.6	7.2	5.4	4.4	3.3	2.6	34.0	30.	164.
		5	10.7	6.5	7.6	6.4	4.7	3.6	2.3	1.9	1.2	.8	19.2	-41.	139.
10175	2	1	8.3	6.5	5.8	5.1	4.0	2.9	2.3	1.8	1.4	1.1	1189.0	42.	540.
		2	18.0	15.5	13.9	12.8	10.1	7.6	6.1	4.8	3.7	3.0	119.6	-11.	165.
		3	16.0	14.4	12.4	12.0	9.3	6.8	5.5	4.2	3.1	2.4	64.3	26.	177.
		4	9.9	9.1	6.8	7.4	5.5	4.0	3.3	2.5	1.8	1.5	30.6	-37.	141.
		5	8.9	7.9	5.5	6.2	4.5	3.1	2.5	1.7	1.1	.9	25.5	-1.	176.
10200	2	1	8.3	6.8	5.9	5.5	4.3	3.2	2.6	2.0	1.5	1.2	782.0	-10.	299.
		2	14.5	12.2	10.9	9.9	7.8	5.8	4.6	3.5	2.6	2.1	189.0	24.	217.
		3	8.9	7.6	7.3	6.5	5.1	3.7	2.9	2.3	1.7	1.5	71.4	-36.	163.
		4	9.5	7.5	7.3	6.2	4.8	3.5	2.6	1.6	1.1	.6	47.6	-5.	182.
		5	12.6	9.3	9.3	8.1	6.1	4.5	3.7	2.5	1.9	1.5	45.6	-7.	261.
10225	2	1	8.5	6.5	5.6	5.2	3.9	2.8	2.3	1.7	1.4	1.1	816.6	28.	523.
		2	6.3	5.4	5.2	4.6	3.7	2.7	2.1	1.6	1.2	1.0	141.8	-36.	272.
		3	6.6	5.7	5.4	4.4	3.7	2.5	1.9	1.5	1.2	.9	60.8	1.	233.
		4	11.2	10.1	10.0	7.1	6.5	4.3	3.2	2.5	1.7	1.3	46.6	-16.	298.
		5	8.4	8.9	9.9	5.4	6.1	3.5	2.7	1.9	1.4	1.0	56.3	-30.	540.
10250	2	1	6.0	4.9	4.2	3.6	2.8	2.1	1.6	1.3	1.0	.8	1751.0	-37.	640.
		2	6.1	5.0	4.2	3.8	2.8	2.0	1.5	1.2	.8	.6	370.4	0.	410.
		3	13.1	10.9	9.5	8.6	6.7	5.0	3.9	3.0	2.3	1.8	217.5	-12.	480.
		4	13.7	11.0	9.6	8.6	6.7	4.8	3.7	3.0	2.2	1.7	197.8	-26.	730.
		5	28.9	23.5	21.3	19.1	15.5	11.5	9.3	7.5	5.7	4.8	104.1	27.	570.
10275	2	1	6.9	5.5	4.6	4.2	3.2	2.2	1.8	1.4	1.0	.8	1263.0	4.	490.
		2	15.1	12.6	10.8	9.9	7.7	5.6	4.5	3.4	2.7	2.0	521.5	-13.	614.
		3	13.3	11.2	9.3	8.9	6.8	4.9	4.0	3.1	2.3	1.9	418.1	-16.	980.
		4	30.8	26.6	22.6	21.5	16.9	12.7	10.4	8.3	6.0	5.0	182.8	6.	710.
		5	52.8	46.7	39.6	38.7	30.5	23.3	19.0	15.5	11.4	9.7	103.6	15.	600.
10300	2	1	19.9	16.3	14.5	12.8	10.3	7.7	6.1	4.9	3.8	3.0	837.2	-29.	477.
		2	16.9	13.6	12.5	11.0	8.6	6.3	5.1	3.9	3.0	2.4	461.0	-25.	789.
		3	32.1	26.1	25.2	21.4	17.8	13.6	10.7	8.8	6.7	5.5	220.9	31.	750.
		4	55.7	44.1	44.8	36.8	31.9	25.3	19.6	16.6	12.3	10.5	97.1	5.	554.
		5	58.7	42.4	48.0	35.7	31.5	24.4	19.8	16.1	12.6	10.8	31.6	-9.	270.
10325	2	1	21.7	17.9	15.7	14.1	11.1	8.3	6.7	5.3	4.0	3.3	1287.0	-19.	790.
		2	41.9	36.2	32.3	29.2	23.7	17.9	14.7	11.6	9.2	7.4	432.0	21.	797.
		3	61.8	54.9	49.2	44.3	36.4	28.4	23.4	18.7	14.5	12.5	157.6	-6.	580.
		4	61.3	55.7	49.6	43.9	36.8	28.0	23.4	18.8	14.7	12.3	48.0	8.	295.
		5	42.5	39.3	34.3	29.6	26.3	20.1	16.4	12.9	10.7	9.0	43.8	2.	404.
10350	2	1	44.7	37.4	37.2	28.1	25.2	18.6	15.2	12.0	9.5	8.0	268.4	33.	930.
		2	64.2	58.4	65.9	36.0	42.0	29.8	25.8	20.3	16.5	14.2	60.3	-17.	631.
		3	33.1	43.4	57.2	10.4	31.1	15.3	17.8	******	11.3	11.7	18.4	-4.	380.

		4	7.9	20.8	39.7	-10.6	17.5	6.0	9.7	******	5.7	6.7	9.6	14.	333.
		5	2.4	17.6	33.9	-15.7	13.7	7.4	15.5	******	5.2	6.4	8.9	10.	465.
10375	2	1	58.6	50.0	44.9	41.1	33.3	25.5	21.0	16.8	13.3	11.0	1302.0	-15.	670.
		2	65.4	56.7	50.5	46.6	37.9	29.1	24.2	19.5	15.3	12.7	275.5	-8.	425.
		3	63.6	56.0	49.6	46.1	36.8	28.1	23.4	19.3	14.9	12.8	190.2	12.	580.
		4	63.1	56.1	49.1	46.3	36.7	28.0	24.5	20.0	14.7	13.3	151.3	23.	770.
		5	55.5	48.9	40.0	37.9	32.5	25.4	22.6	15.6	11.9	10.6	109.1	-7.	840.
10400	2	1	44.2	37.7	33.8	31.0	25.2	19.4	16.0	12.8	10.1	8.4	1574.0	-9.	610.
		2	51.6	44.2	39.5	36.5	29.5	22.7	18.7	15.0	11.8	9.7	639.2	-6.	752.
		3	53.0	45.2	40.4	37.6	30.6	23.5	19.3	15.8	12.6	10.1	528.2	-2.	1240.
		4	47.6	40.3	35.9	34.2	27.1	21.3	18.0	14.3	11.5	9.6	258.2	14.	1010.
		5	51.1	43.5	38.5	37.5	29.3	23.1	19.2	15.0	11.6	9.5	187.7	20.	1100.
10425	2	1	32.8	27.5	24.5	22.3	17.9	13.5	11.0	8.8	6.9	5.6	1746.0	-4.	740.
		2	39.4	33.3	29.9	27.0	21.8	16.5	13.6	10.8	8.5	7.0	965.7	14.	1229.
		3	35.4	30.5	27.7	24.8	20.9	15.6	12.7	10.5	8.2	6.9	523.2	-8.	1320.
		4	40.5	35.1	32.3	28.5	23.7	18.5	15.4	12.0	9.1	7.7	300.5	18.	1270.
		5	43.7	38.4	35.4	30.9	26.3	20.7	17.0	13.4	10.4	8.8	241.3	-41.	1530.
10450	2	1	30.0	24.8	22.0	19.7	15.6	11.7	9.4	7.4	5.7	4.7	2203.0	-28.	1210.
		2	25.3	21.7	19.4	17.8	14.3	10.8	9.0	7.1	5.6	4.5	682.1	11.	1127.
		3	30.5	26.2	23.6	21.2	17.3	13.2	10.8	8.7	6.8	5.6	403.9	38.	1330.
		4	34.2	29.9	26.5	24.1	19.1	15.7	12.9	9.9	7.6	6.9	277.0	-71.	1520.
		5	37.4	32.9	29.7	27.0	22.3	17.4	13.5	10.7	9.2	6.8	171.9	27.	1420.
10475	2	1	18.5	15.4	13.9	12.2	9.9	7.4	6.0	4.7	3.7	3.0	1211.0	4.	950.
		2	26.2	21.3	19.6	16.6	13.6	10.2	8.3	6.6	5.2	4.3	466.4	41.	1098.
		3	24.6	23.1	20.9	17.8	15.8	11.9	10.1	7.8	6.5	5.3	350.6	-22.	1640.
		4	30.7	27.9	26.8	22.0	18.9	14.0	12.0	9.0	6.8	6.1	172.2	-40.	1350.
		5	30.7	27.3	25.6	19.9	17.8	13.4	11.4	8.9	7.4	6.2	141.9	12.	1670.
10500	2	1	17.1	14.2	13.1	10.2	8.9	7.2	5.6	3.7	3.4	2.5	472.1	34.	871.
		2	22.4	20.1	18.5	14.3	13.6	8.5	7.7	7.3	4.9	4.5	229.7	-87.	1272.
		3	23.2	22.3	20.8	13.2	15.2	11.7	9.8	6.4	6.4	4.2	123.3	25.	1360.
		4	25.1	23.7	22.7	14.0	15.9	11.5	9.8	7.4	6.4	5.1	85.1	10.	1572.
		5	25.7	26.0	25.4	13.5	18.3	13.0	11.1	7.9	7.9	5.1	57.8	6.	1600.
10525	2	1	17.6	13.5	11.7	10.3	8.0	5.9	4.8	3.7	2.9	2.3	348.5	-91.	1094.
		2	19.7	16.3	14.9	12.4	10.7	8.1	6.5	5.2	4.3	3.3	138.6	24.	1305.
		3	21.2	17.5	16.5	13.2	12.1	8.9	6.9	5.7	4.7	3.5	89.0	26.	1672.
		4	24.3	20.0	19.9	14.5	14.6	9.8	6.9	6.1	5.2	3.5	50.2	-9.	1575.
		5	27.3	21.0	20.6	16.2	14.1	11.3	9.8	8.1	6.2	5.7	24.9	3.	1173.
10550	2	1	14.5	11.7	10.6	9.6	7.5	5.6	4.5	3.6	2.7	2.1	589.7	23.	1234.
		2	17.5	13.9	13.0	11.5	9.1	7.0	5.6	4.5	3.5	2.9	290.8	21.	1826.
		3	20.4	16.1	16.6	14.1	12.0	9.3	7.5	5.0	2.9	2.2	144.4	-16.	1800.
		4	23.5	17.7	17.9	15.6	12.3	9.7	7.6	6.4	4.9	4.1	62.4	14.	1306.
		5	24.5	18.0	18.4	16.3	12.9	9.7	7.5	6.6	5.1	4.9	48.3	-1.	1515.

10575	2	1	12.6	9.7	8.8	7.8	6.2	4.6	3.8	3.0	2.4	1.9	805.8	45.	2108.
		2	14.9	12.8	12.0	10.8	8.9	6.8	5.5	4.3	3.2	2.4	193.0	-17.	1515.
		3	17.5	14.4	13.1	11.6	9.8	7.9	6.4	4.6	3.9	3.2	90.3	21.	1415.
		4	20.0	16.1	14.9	13.0	10.9	8.4	6.8	5.4	4.6	3.5	57.1	-11.	1493.
		5	17.8	15.9	17.4	15.7	11.7	8.5	6.8	5.4	4.4	3.7	46.5	-22.	1823.
10600	2	1	10.6	8.7	7.8	6.4	5.3	3.9	3.1	2.5	1.9	1.5	924.7	2.	1528.
		2	13.9	11.9	11.4	8.9	7.9	5.8	4.7	3.8	2.9	2.4	249.2	-1.	1235.
		3	13.2	11.5	11.2	7.9	7.3	5.0	3.9	2.8	1.9	1.3	148.2	13.	1460.
		4	17.3	15.0	15.7	10.7	10.9	8.2	6.9	5.9	5.1	4.5	110.9	-30.	1830.
		5	16.3	14.6	15.5	8.1	10.3	7.6	6.2	4.4	3.7	3.3	71.5	2.	1772.
10625	2	1	10.0	8.3	7.6	6.2	5.4	3.8	3.2	2.5	1.9	1.5	270.8	8.	773.
		2	12.1	10.6	9.8	7.6	6.8	4.8	4.0	3.1	2.4	2.0	134.9	11.	1155.
		3	12.2	12.1	10.9	7.9	7.9	5.1	4.5	3.4	2.6	2.2	95.6	-21.	1633.
		4	12.3	12.7	11.8	7.5	8.4	5.2	4.6	3.5	2.7	2.4	55.3	-9.	1579.
		5	11.9	14.0	13.3	6.5	9.3	5.2	5.0	3.7	3.0	2.5	34.7	-12.	1485.
10650	2	1	12.2	9.9	8.6	7.7	6.0	4.4	3.6	2.8	2.1	1.7	661.9	3.	1222.
		2	13.7	11.3	9.8	8.7	6.9	5.1	4.1	3.1	2.4	1.8	299.7	-33.	1660.
		3	12.3	10.5	9.1	7.9	6.5	4.8	3.8	2.9	2.2	1.7	169.2	11.	1870.
		4	13.0	11.2	9.8	8.3	7.0	4.7	3.8	2.9	2.0	1.4	85.6	-18.	1581.
		5	14.5	13.0	11.7	11.0	8.1	5.3	4.3	3.0	2.1	1.5	76.2	18.	2110.
10675	2	1	12.2	10.3	9.1	7.9	6.4	4.7	3.9	3.0	2.3	1.9	729.6	-3.	1431.
		2	13.8	10.9	10.2	8.4	6.9	5.1	4.2	3.3	2.6	2.1	249.6	-3.	1469.
		3	10.2	10.0	9.4	7.2	6.7	5.0	4.5	3.4	2.8	2.4	153.8	6.	1800.
		4	14.1	12.6	12.0	8.5	8.1	6.0	5.3	3.9	3.3	2.9	99.7	-6.	1955.
		5	14.5	11.8	13.2	8.1	8.2	5.9	5.6	4.4	3.9	3.2	47.9	16.	1408.
10700	2	1	10.3	8.2	7.3	6.3	5.0	3.7	2.9	2.3	1.8	1.5	942.1	22.	1643.
		2	9.8	8.3	8.1	6.9	5.8	4.4	3.5	2.8	2.2	1.8	367.8	-20.	1924.
		3	12.0	10.2	10.0	7.8	6.9	5.1	4.2	3.3	2.5	2.1	204.7	10.	2130.
		4	12.9	10.0	10.6	7.4	7.0	5.1	4.0	3.3	2.6	2.2	83.5	19.	1456.
10725	2	1	8.7	7.1	6.2	5.5	4.2	3.2	2.5	1.9	1.5	1.2	732.2	8.	1532.
		2	11.3	9.4	8.2	7.2	5.7	4.3	3.5	2.6	2.1	1.6	354.2	10.	2224.
		3	11.6	9.2	7.7	6.7	5.4	4.1	3.8	2.6	2.3	1.8	132.5	26.	1660.
10750	2	1	10.1	7.9	7.1	6.5	4.9	3.7	2.9	2.3	1.8	1.4	916.8	14.	2398.
		2	10.5	7.7	7.0	6.0	4.7	3.5	2.8	2.2	1.7	1.3	229.2	24.	1799.
10775	2	1	8.8	7.5	6.4	5.1	4.3	3.1	2.5	1.9	1.5	1.2	342.7	25.	1530.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 120W.IND
DATA FILE : 120W.DAT

LINE NO. : 1204

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	22.2	19.3	17.7	16.1	13.3	10.2	8.3	6.6	5.1	4.2	267.6	8.	129.
		2	26.4	22.8	21.0	19.1	15.7	12.1	9.9	7.8	6.1	4.9	68.7	-5.	100.
		3	21.8	19.0	17.5	15.8	12.9	9.8	7.9	6.3	4.9	3.9	40.1	19.	116.
		4	20.8	17.9	16.8	14.7	12.1	9.2	7.4	5.9	4.6	3.7	21.5	9.	104.
		5	20.1	17.5	16.2	13.0	11.9	9.1	7.2	5.7	4.3	3.4	17.3	-29.	125.
10050	2	1	24.7	21.6	19.8	18.5	15.1	11.7	9.7	7.8	6.1	4.8	231.6	12.	134.
		2	22.9	19.7	17.8	16.5	13.4	10.1	8.1	6.3	4.9	4.2	85.9	-9.	150.
		3	22.7	19.5	18.2	16.3	13.4	10.2	8.2	6.5	5.1	4.0	40.3	25.	140.
		4	22.9	19.4	18.8	15.9	13.4	10.0	8.0	6.4	5.0	3.8	26.9	-23.	156.
		5	26.5	21.9	21.7	17.2	15.0	11.1	8.7	6.7	5.5	4.5	16.4	-15.	142.
10075	2	1	18.1	16.0	14.3	13.1	10.8	8.3	6.8	5.4	4.2	3.5	406.1	0.	212.
		2	21.2	18.7	16.4	15.5	12.7	9.8	7.9	6.3	4.9	3.9	104.0	24.	163.
		3	22.3	19.6	17.9	16.2	13.3	10.1	8.2	6.5	4.9	4.0	55.5	-25.	173.
		4	27.6	23.7	21.6	19.5	15.8	12.1	9.6	7.7	5.8	4.8	29.6	-5.	154.
		5	27.4	23.5	22.0	19.3	15.5	11.4	8.9	7.1	5.4	4.2	14.5	-8.	113.
10100	2	1	17.1	14.9	13.5	12.3	10.1	7.7	6.3	5.0	3.9	3.1	307.4	12.	175.
		2	22.0	19.3	17.5	15.8	13.1	10.0	8.2	6.4	5.0	3.9	111.0	-24.	190.
		3	27.7	24.2	21.9	19.2	15.9	12.1	9.8	7.6	5.7	4.7	48.3	-4.	164.
		4	29.2	25.6	23.5	20.5	17.3	12.7	10.3	7.9	6.0	4.8	20.7	1.	118.
		5	21.0	18.8	17.6	13.8	12.0	8.6	6.6	5.0	3.4	2.7	15.0	-19.	128.
10125	2	1	17.6	15.3	13.8	12.6	10.2	7.8	6.3	5.0	3.9	3.1	488.6	-34.	187.
		2	26.4	22.9	20.8	19.0	15.4	11.7	9.5	7.5	5.8	4.7	128.0	19.	147.
		3	29.0	25.2	22.9	20.8	16.7	12.6	10.1	7.9	6.0	4.8	46.0	-8.	105.
		4	23.7	20.4	19.0	16.8	13.5	10.1	7.9	6.2	4.8	3.8	30.1	-9.	115.
		5	15.8	13.3	12.9	10.7	8.7	6.4	4.9	4.0	3.1	2.4	26.5	-8.	152.
10150	2	1	21.1	18.2	16.3	14.6	11.8	9.0	7.2	5.7	4.4	3.5	365.8	6.	201.

		2	27.2	23.9	21.6	19.4	15.8	11.7	9.5	7.4	5.6	4.5	75.7	-9.	125.
		3	23.2	20.7	18.6	16.4	13.4	10.1	7.9	6.1	4.6	3.6	39.7	-23.	131.
		4	16.5	15.3	13.7	11.3	9.6	7.3	5.6	4.3	3.2	2.5	29.8	10.	164.
		5	8.1	8.2	7.3	5.5	5.0	3.8	2.7	1.9	1.4	1.0	25.8	-24.	213.
10175	2	1	19.4	16.7	14.7	13.5	10.8	8.1	6.5	5.1	3.8	3.1	310.7	-11.	162.
		2	21.5	18.8	16.6	15.3	12.1	9.1	7.2	5.6	4.2	3.3	95.4	-16.	150.
		3	17.5	15.3	13.4	12.3	9.8	7.1	5.7	4.3	3.1	2.4	55.7	-2.	174.
		4	10.7	9.4	8.0	7.5	5.9	4.0	3.2	2.4	1.4	1.0	40.6	-13.	212.
		5	4.6	4.2	3.4	3.3	2.3	.9	.8	.3	.0	-.1	18.4	6.	144.
10200	2	1	12.1	10.1	9.3	8.0	6.3	4.7	3.7	2.8	2.2	1.7	333.7	-11.	275.
		2	16.4	13.8	12.5	11.2	8.8	6.5	5.1	3.9	3.0	2.3	90.2	2.	224.
		3	12.2	10.2	9.5	8.2	6.5	4.7	3.8	2.8	2.1	1.6	48.8	-20.	241.
		4	8.5	6.8	6.4	5.2	4.2	3.1	2.2	1.6	1.2	.7	18.5	13.	152.
		5	7.4	6.8	5.9	4.1	4.6	3.0	1.9	1.3	1.0	1.1	25.9	4.	321.
10225	2	1	8.9	7.4	6.5	5.8	4.7	3.4	2.8	2.1	1.6	1.3	524.1	3.	365.
		2	9.7	8.1	7.2	6.1	5.0	3.6	2.9	2.2	1.7	1.4	136.7	-19.	286.
		3	6.8	5.5	5.2	3.4	3.3	2.1	1.8	1.2	.8	.6	39.4	14.	164.
		4	8.8	7.3	7.1	4.0	4.3	2.7	2.4	1.6	1.2	1.1	42.2	9.	294.
		5	22.5	18.0	18.3	11.9	10.7	7.8	7.1	5.6	4.2	3.8	52.0	-2.	544.
10250	2	1	7.1	5.4	5.0	4.6	3.5	2.6	2.1	1.6	1.2	1.0	749.4	-18.	522.
		2	4.8	3.2	3.3	2.9	2.1	1.5	1.1	.8	.6	.4	136.7	19.	286.
		3	6.6	3.9	5.0	3.8	2.7	2.0	1.3	1.0	.8	.4	102.4	8.	420.
		4	23.6	16.3	18.6	15.1	11.9	9.5	7.0	5.7	4.4	3.3	99.6	-24.	695.
		5	14.7	6.1	12.0	7.5	5.5	4.5	2.8	2.5	2.3	1.3	36.5	0.	382.
10275	2	1	5.4	4.5	3.7	3.4	2.6	1.9	1.5	1.1	.8	.7	438.0	20.	319.
		2	6.4	5.2	4.4	3.8	2.9	2.0	1.5	1.1	.8	.6	215.4	10.	471.
		3	23.0	19.6	17.7	15.4	12.6	9.4	7.7	6.1	4.7	3.8	173.8	-11.	750.
		4	18.1	15.4	14.0	11.1	9.6	6.9	5.8	4.2	3.5	2.9	68.6	-40.	500.
		5	37.8	32.0	29.4	24.8	21.7	16.0	13.0	10.6	8.5	6.9	31.6	27.	346.
10300	2	1	8.2	6.6	5.8	5.1	4.0	2.9	2.3	1.7	1.3	1.0	1134.0	0.	640.
		2	26.3	22.3	19.8	18.0	14.5	10.9	8.9	7.1	5.5	4.5	548.8	9.	939.
		3	18.9	16.2	14.2	13.0	10.5	7.9	6.4	5.1	4.0	3.3	184.2	-36.	620.
		4	38.8	33.2	29.5	27.2	22.1	16.8	13.9	11.1	8.7	7.2	76.9	23.	438.
		5	44.2	38.0	33.5	30.5	24.6	18.5	15.5	12.3	9.5	8.0	35.2	7.	301.
10325	2	1	33.2	27.8	24.9	22.5	18.1	13.7	11.2	8.9	7.0	5.7	1435.0	1.	900.
		2	26.2	22.6	20.4	18.2	14.8	11.2	9.2	7.3	5.7	4.8	318.0	-47.	599.
		3	44.2	38.4	34.6	31.1	25.6	19.5	16.1	12.9	10.2	8.4	124.5	40.	460.
		4	47.6	42.3	38.3	32.9	28.1	21.0	17.8	14.0	11.0	9.2	45.3	11.	284.
		5	44.5	42.1	36.6	31.5	27.2	20.4	16.9	13.8	11.2	8.4	35.1	-11.	330.
10350	2	1	33.8	28.2	25.4	23.4	18.7	14.3	11.8	9.4	7.4	6.1	1000.0	-52.	620.
		2	55.6	47.5	42.9	39.3	31.9	24.6	20.3	16.4	12.9	10.7	325.3	29.	612.
		3	58.0	49.2	44.9	40.7	33.3	25.7	21.2	17.1	13.6	11.2	112.4	0.	420.

		4	58.8	49.6	45.5	40.4	33.7	25.6	21.0	17.0	13.8	11.4	68.4	0.	429.
		5	55.0	45.5	42.4	36.8	31.5	23.5	19.4	15.7	12.8	10.5	46.4	-21.	436.
10375	2	1	43.0	36.4	32.7	29.8	24.0	18.3	15.1	12.0	9.4	7.8	1555.0	23.	1160.
		2	54.0	46.0	41.5	37.8	30.9	23.8	19.4	15.8	12.4	10.2	320.5	8.	718.
		3	56.9	48.8	44.3	40.2	32.2	24.7	21.3	16.2	13.1	10.8	178.7	11.	790.
		4	56.7	48.8	44.4	40.4	32.4	24.8	22.0	16.0	12.7	10.7	86.9	-27.	649.
		5	55.7	47.3	43.3	38.9	32.3	24.8	20.4	16.5	13.2	10.8	101.5	55.	1130.
10400	2	1	50.9	43.2	33.2	35.8	29.2	22.5	18.7	15.0	11.9	9.8	1193.0	5.	740.
		2	48.3	40.5	37.0	33.6	27.3	21.0	17.3	13.9	10.9	9.0	455.0	0.	857.
		3	47.1	39.2	36.2	32.8	27.0	20.8	16.9	13.8	11.0	8.8	218.0	-9.	810.
		4	48.6	40.3	37.6	33.5	27.8	21.4	17.6	14.2	11.3	9.2	195.8	50.	1220.
		5	47.8	39.2	36.9	32.4	27.4	21.0	17.1	14.1	11.0	8.8	99.5	-10.	937.
10425	2	1	30.8	25.9	22.8	21.0	16.8	12.7	10.4	8.2	6.4	5.2	1588.0	16.	830.
		2	34.8	29.5	26.3	24.1	19.4	14.8	12.2	9.8	7.7	6.4	525.9	-29.	825.
		3	37.9	32.3	29.0	26.7	21.6	16.8	13.9	11.3	8.8	7.2	468.7	23.	1460.
		4	41.1	34.9	31.6	29.1	23.6	18.3	15.0	11.9	9.1	7.6	258.5	28.	1350.
		5	45.7	38.8	35.5	32.3	26.2	20.3	16.6	13.1	10.1	8.7	176.2	-24.	1380.
10450	2	1	23.6	19.4	17.4	15.6	12.4	9.2	7.6	5.9	4.5	3.7	1078.0	-13.	630.
		2	28.6	23.9	21.6	19.4	15.6	11.8	9.5	7.7	6.1	5.0	671.6	13.	1193.
		3	31.7	26.8	24.3	21.7	17.9	13.6	11.1	8.9	7.1	5.7	342.7	15.	1210.
		4	37.4	31.5	29.3	26.0	21.5	16.3	13.3	10.7	8.5	7.1	215.1	-17.	1270.
		5	36.6	31.2	29.5	25.1	20.9	16.2	13.4	10.9	8.6	7.1	182.5	4.	1620.
10475	2	1	22.8	18.8	16.5	15.1	11.9	8.9	7.2	5.7	4.4	3.6	2164.0	22.	1230.
		2	25.0	20.8	18.5	17.0	13.5	10.2	8.3	6.6	5.1	4.2	690.6	13.	1182.
		3	29.9	25.2	22.7	21.0	16.8	12.8	10.7	8.7	6.8	5.4	413.2	-37.	1410.
		4	29.8	25.3	22.7	20.7	16.6	12.8	10.6	8.8	7.1	5.6	293.9	22.	1670.
		5	33.1	28.1	25.4	23.5	18.7	14.5	11.8	9.3	7.3	6.3	251.5	4.	2150.
10500	2	1	18.0	15.0	13.3	11.9	9.5	7.1	5.8	4.6	3.6	2.9	1145.0	16.	870.
		2	24.8	21.0	18.9	17.0	13.7	10.6	8.5	6.8	5.3	4.4	534.8	-39.	1228.
		3	24.6	20.7	18.9	16.9	13.7	10.4	8.8	7.2	5.7	4.5	358.1	3.	1640.
		4	27.8	23.3	21.3	19.0	15.6	11.9	9.9	8.1	6.5	5.2	279.5	24.	2140.
		5	30.0	24.7	22.9	19.8	16.4	12.4	10.5	8.0	6.3	5.7	158.9	-28.	1820.
10525	2	1	18.5	15.0	13.6	12.3	9.7	7.3	5.9	4.7	3.6	2.9	1476.0	-39.	1020.
		2	18.2	14.9	13.6	12.4	9.9	7.5	6.2	4.9	3.9	3.2	762.0	7.	1595.
		3	21.3	17.9	16.2	14.8	11.9	9.0	7.6	6.1	4.9	3.9	593.3	27.	2470.
		4	23.2	19.5	17.8	16.4	13.1	9.5	8.3	6.6	5.7	4.3	289.6	-20.	2020.
		5	23.7	20.3	18.3	16.5	13.3	10.2	8.5	6.6	5.3	4.4	131.4	4.	1370.
10550	2	1	15.1	12.6	11.3	10.0	8.2	6.1	5.0	4.0	3.1	2.5	1267.0	13.	970.
		2	18.8	15.9	14.4	12.8	10.5	7.9	6.5	5.2	4.1	3.4	785.5	22.	1804.
		3	20.9	17.9	16.0	13.7	11.3	9.0	7.4	6.1	4.6	3.7	368.4	-15.	1680.
		4	20.0	17.3	15.8	13.5	11.6	8.6	7.2	5.7	4.6	3.8	153.2	10.	1170.
		5	24.4	20.9	19.4	16.1	13.9	10.5	8.6	6.7	5.5	4.7	112.3	-11.	1290.

10575	2	1	13.9	12.1	10.4	9.5	7.5	5.7	4.6	3.7	2.8	2.3	2953.0	9.	2060.
		2	15.7	13.5	11.8	10.8	8.6	6.6	5.3	4.3	3.3	2.7	962.5	-18.	2014.
		3	16.1	13.6	12.1	11.2	8.6	6.7	5.5	4.5	3.4	2.9	343.0	13.	1430.
		4	20.5	17.3	15.1	14.0	11.0	8.5	6.9	5.5	4.3	3.5	199.5	-30.	1390.
		5	19.2	16.0	14.2	13.2	10.3	8.0	6.4	5.3	4.0	3.3	106.9	-1.	1110.
10600	2	1	10.9	8.7	7.9	7.2	5.6	4.2	3.4	2.7	2.1	1.7	1972.0	-17.	1510.
		2	11.9	9.8	8.8	8.1	6.4	4.9	4.0	3.1	2.4	2.0	544.4	10.	1250.
		3	16.5	13.9	12.4	11.4	9.0	6.6	5.5	4.2	3.3	2.6	320.0	-22.	1460.
		4	14.7	12.5	11.1	10.2	8.1	6.1	5.0	3.9	3.1	2.5	132.1	-4.	1010.
		5	17.1	14.7	13.0	11.9	9.5	7.1	5.8	4.5	3.5	2.8	152.5	-10.	1750.
10625	2	1	6.2	6.4	4.3	4.0	3.2	2.3	2.0	1.5	1.2	1.0	1211.0	22.	950.
		2	12.4	10.5	9.1	8.3	6.6	4.9	4.0	3.1	2.5	2.0	499.0	6.	1175.
		3	10.9	9.5	8.1	7.5	6.0	4.4	3.8	2.9	2.2	1.9	274.7	-27.	1290.
		4	13.2	11.6	9.9	9.0	7.3	5.3	4.5	3.5	2.7	2.3	231.5	-5.	1810.
		5	14.9	13.3	11.3	10.3	8.5	6.2	5.3	4.1	3.2	2.7	180.1	-8.	2120.
10650	2	1	13.4	10.6	9.6	8.7	6.8	5.0	4.1	3.2	2.5	2.0	1962.0	-21.	1460.
		2	10.8	8.4	7.7	7.0	5.4	4.0	3.3	2.6	2.0	1.7	496.2	-15.	1112.
		3	13.0	10.3	9.5	8.5	6.6	4.9	4.0	3.2	2.5	2.0	441.0	0.	1970.
		4	14.5	11.6	10.9	9.6	7.6	5.7	4.7	3.7	3.0	2.4	296.2	-3.	2210.
		5	15.4	11.7	11.2	9.3	7.6	5.6	4.5	3.7	3.0	2.4	202.4	-11.	2260.
10675	2	1	9.9	8.1	7.0	6.3	5.0	3.7	3.1	2.4	1.8	1.5	1598.0	-6.	1190.
		2	12.3	10.4	8.8	8.1	6.5	4.8	3.9	3.0	2.3	1.9	860.4	4.	1929.
		3	12.8	11.1	9.4	8.8	7.0	5.2	4.4	3.4	2.6	2.2	633.9	-11.	2830.
		4	13.2	11.6	9.7	9.1	7.2	5.3	4.5	3.5	2.7	2.2	306.4	9.	2290.
		5	14.7	13.4	10.7	10.5	8.0	6.0	5.1	3.9	3.0	2.4	224.7	5.	2510.
10700	2	1	12.7	10.7	9.3	8.5	6.6	4.9	3.9	3.1	2.4	1.9	3367.0	1.	2850.
		2	13.1	11.2	9.7	8.7	6.9	5.2	4.2	3.3	2.6	2.1	1363.0	-12.	3470.
		3	12.9	10.9	9.6	8.5	6.9	5.1	4.1	3.3	2.6	2.1	483.3	-4.	2450.
		4	14.4	12.3	10.9	9.4	7.7	5.8	4.6	3.8	2.9	2.3	321.2	8.	2720.
10725	2	1	11.3	9.8	8.3	7.4	6.0	4.4	3.6	2.8	2.1	1.8	2194.0	-10.	1960.
		2	34.0	17.2	12.8	10.5	7.4	5.0	3.7	2.8	2.1	1.7	598.7	-21.	1611.
		3	-10.9	2.6	4.1	4.6	4.8	4.3	3.7	3.1	2.4	2.1	579.1	21.	3110.
10750	2	1	7.4	6.2	5.3	4.8	3.8	2.9	2.3	1.9	1.4	1.2	2256.0	-12.	1600.
		2	12.0	9.9	8.5	7.7	6.1	4.6	3.7	3.0	2.3	1.9	871.1	9.	1864.
10775	2	1	10.0	8.2	7.3	6.5	5.1	3.8	3.0	2.4	1.8	1.5	2206.0	6.	1730.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 121W.IND
DATA FILE : 121W.DAT

LINE NO. : 1214

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	19.4	16.4	14.8	13.4	10.8	8.0	6.5	5.1	3.9	3.1	217.4	-4.	124.
		2	21.3	18.4	16.7	15.1	12.3	9.2	7.6	5.9	4.5	3.6	83.3	11.	143.
		3	20.7	18.6	16.4	14.8	12.3	9.0	7.4	5.6	4.3	3.5	36.0	-20.	123.
		4	14.1	12.9	11.3	9.7	8.2	5.7	4.9	3.7	3.0	2.3	16.8	-1.	96.
		5	16.1	15.1	13.2	11.3	9.8	6.8	5.7	4.2	3.2	2.6	16.7	15.	142.
10050	2	1	21.0	17.7	15.9	14.4	11.5	8.7	7.0	5.5	4.2	3.4	322.0	17.	146.
		2	23.8	19.2	17.5	15.6	12.7	9.5	7.7	6.0	4.6	3.7	96.3	-10.	131.
		3	14.7	12.2	11.1	9.4	7.6	5.5	4.4	3.4	2.5	1.9	38.8	-7.	105.
		4	17.3	14.4	13.4	11.3	9.4	6.8	5.4	4.2	3.2	2.6	33.6	-6.	153.
		5	16.9	13.5	13.5	10.2	8.9	6.3	4.9	3.8	3.0	2.3	19.5	1.	133.
10075	2	1	25.8	22.4	20.2	18.4	14.9	11.3	9.2	7.2	5.5	4.4	504.1	-15.	106.
		2	16.9	14.2	12.6	11.3	9.0	6.6	5.3	4.0	3.0	2.4	150.3	-2.	94.
		3	18.5	15.6	14.0	12.5	10.1	7.4	5.9	4.6	3.4	2.7	119.0	-1.	149.
		4	18.6	15.6	14.2	12.6	10.1	7.4	5.9	4.5	3.5	2.7	56.5	-8.	118.
		5	20.3	17.0	15.5	13.6	11.1	8.1	6.3	4.9	3.7	2.9	35.2	7.	111.
10100	2	1	21.7	18.3	16.0	14.7	11.5	8.5	6.8	5.3	4.0	3.2	266.5	-1.	105.
		2	40.5	24.1	20.0	13.0	14.8	11.1	6.8	******	5.4	3.4	98.0	-10.	117.
		3	4.5	13.9	13.3	18.0	9.4	6.7	7.5	******	2.9	3.3	97.8	-2.	232.
		4	23.2	19.7	17.2	16.2	12.6	9.3	7.4	5.7	4.4	3.5	30.7	8.	121.
		5	26.2	22.0	19.1	17.9	13.9	10.1	8.0	6.1	4.5	3.5	19.8	-9.	117.
10125	2	1	22.5	19.0	16.9	15.2	12.1	9.1	7.4	5.8	4.5	3.6	486.3	4.	254.
		2	25.5	21.6	19.4	17.3	13.8	10.2	8.1	6.3	4.8	3.8	95.9	-9.	151.
		3	26.2	22.1	20.2	17.7	14.2	10.5	8.3	6.4	4.9	3.9	42.4	2.	132.
		4	29.3	24.7	22.6	19.6	15.8	11.6	9.1	7.1	5.3	4.2	24.6	-1.	128.
		5	16.2	12.8	12.6	9.9	8.2	5.5	4.0	3.3	2.3	1.7	22.4	-8.	175.
10150	2	1	24.1	20.1	17.7	16.2	12.5	9.2	7.3	5.6	4.3	3.4	221.2	-8.	115.

		2	26.6	22.4	19.8	18.2	14.1	10.4	8.3	6.4	4.8	3.8	70.9	11.	111.
		3	29.6	25.0	21.8	20.1	15.4	11.3	8.9	6.8	5.0	3.9	37.2	-19.	116.
		4	17.4	14.8	12.3	11.6	8.5	6.0	4.8	3.5	2.5	1.9	29.0	-4.	151.
		5	11.4	10.1	7.6	7.7	6.0	4.7	4.3	2.8	2.2	1.5	26.2	-19.	205.
10175	2	1	24.4	20.6	18.5	16.8	13.4	9.9	8.0	6.2	4.7	3.8	412.5	16.	147.
		2	28.7	24.2	21.6	19.6	15.4	11.3	9.0	6.9	5.2	4.1	138.5	-8.	148.
		3	18.3	15.0	13.3	11.9	9.2	6.5	5.1	3.8	2.8	2.2	84.6	-16.	180.
		4	13.7	11.0	9.9	8.6	6.8	4.7	3.7	2.7	2.0	1.5	58.6	-5.	208.
		5	8.0	6.1	5.7	4.6	3.6	2.3	1.8	1.2	.8	.6	30.5	27.	163.
10200	2	1	34.8	29.5	26.0	23.5	18.5	13.6	10.9	8.5	6.4	5.1	386.9	-10.	192.
		2	21.1	17.6	15.4	14.0	10.6	7.7	6.0	4.6	3.3	2.6	114.3	-19.	170.
		3	16.1	13.0	11.3	10.6	7.7	5.6	4.2	3.2	2.4	1.8	63.7	-15.	190.
		4	10.2	7.4	6.4	6.4	4.3	3.1	2.1	1.7	1.1	.7	29.6	24.	147.
		5	12.0	7.8	6.4	7.4	4.4	3.2	1.9	1.6	.9	.7	32.5	-10.	243.
10225	2	1	22.2	18.9	16.6	14.9	11.7	8.5	6.8	5.2	3.9	3.1	399.1	-18.	171.
		2	17.8	15.2	13.2	11.6	9.3	6.6	5.3	3.9	2.9	2.3	143.3	-15.	184.
		3	10.7	10.1	8.2	7.0	5.8	3.8	3.1	2.2	1.6	1.2	56.3	22.	145.
		4	9.4	10.3	7.1	6.1	5.6	3.1	2.8	1.7	1.2	1.0	51.3	-5.	220.
		5	6.9	9.9	6.3	5.1	5.1	2.4	2.7	1.5	1.1	.9	85.0	6.	548.
10250	2	1	10.2	7.9	6.6	5.8	4.3	3.0	2.4	2.0	1.4	1.0	371.0	-14.	270.
		2	9.0	7.2	5.9	5.2	3.7	2.5	1.9	1.4	1.0	.7	83.3	28.	182.
		3	10.3	9.0	6.7	6.1	4.4	2.9	2.2	1.5	.9	.5	49.0	-13.	214.
		4	10.1	9.7	6.5	6.6	4.4	2.9	2.3	1.7	1.1	.7	69.4	-2.	506.
		5	21.9	21.2	15.7	15.0	11.3	8.3	6.0	5.3	3.7	3.0	36.8	2.	402.
10275	2	1	5.2	3.8	3.2	2.8	2.0	1.4	1.1	.8	.6	.5	1007.0	25.	440.
		2	7.0	5.1	4.0	3.8	2.5	1.6	1.2	.8	.5	.4	283.6	-18.	376.
		3	8.3	6.0	4.8	5.1	3.2	2.2	1.6	1.2	.8	.5	295.4	12.	780.
		4	24.5	19.4	16.6	17.0	12.3	9.4	7.4	5.9	4.5	3.5	121.3	-11.	530.
		5	49.0	38.6	35.0	35.7	26.3	20.4	16.8	13.2	10.3	7.7	35.9	-17.	238.
10300	2	1	10.1	7.3	6.1	5.3	3.7	2.5	1.9	1.4	1.0	.8	736.9	-15.	525.
		2	11.5	8.5	7.3	6.4	4.6	3.2	2.4	1.8	1.3	1.0	448.3	9.	959.
		3	25.7	20.5	18.4	16.2	12.8	9.5	7.6	6.1	4.6	3.8	174.1	-13.	740.
		4	49.8	40.9	37.7	33.3	27.2	20.9	17.0	13.7	10.9	8.9	34.3	-9.	244.
		5	55.9	45.2	41.2	36.2	28.7	23.3	18.2	14.7	11.9	9.7	23.8	0.	254.
10325	2	1	13.0	10.3	8.8	7.6	5.9	4.2	3.3	2.6	1.9	1.5	1852.0	20.	830.
		2	27.1	22.6	20.0	17.9	14.3	10.8	8.7	7.0	5.4	4.4	438.3	-12.	589.
		3	48.6	41.2	37.7	34.2	27.8	21.5	17.6	14.2	11.2	9.3	101.6	-11.	270.
		4	55.5	46.2	42.4	38.6	31.1	24.1	19.7	16.0	12.6	10.4	59.4	-25.	266.
		5	52.1	43.0	39.9	36.4	29.2	22.5	18.3	14.8	11.7	9.6	53.0	37.	356.
10350	2	1	25.0	20.5	18.4	16.3	12.9	9.7	7.9	6.3	4.9	4.0	1817.0	-3.	830.
		2	50.0	42.9	39.3	35.0	28.9	22.2	18.4	14.8	11.7	9.7	296.8	-15.	411.
		3	60.2	51.7	47.5	41.8	35.0	26.8	22.2	17.9	14.3	11.8	146.6	-21.	400.

		4	57.3	49.1	45.5	39.3	33.1	25.3	20.9	16.8	13.4	11.2	122.2	23.	560.
		5	56.6	48.1	46.0	37.4	32.7	24.8	20.6	16.5	13.3	11.2	95.9	-9.	664.
10375	2	1	43.8	36.3	32.6	29.4	23.5	17.9	15.5	12.4	9.5	7.8	888.3	-20.	581.
		2	60.9	51.5	46.5	42.6	34.5	26.5	21.9	17.6	14.0	11.5	338.0	-6.	663.
		3	57.5	48.7	43.8	40.2	32.5	25.0	20.6	16.6	13.2	10.9	311.2	18.	1210.
		4	58.9	49.6	44.8	41.1	33.0	25.4	21.0	16.9	13.3	11.0	180.8	-25.	1180.
		5	62.5	52.6	47.7	43.9	34.9	26.9	22.3	18.0	14.1	11.9	96.7	10.	948.
10400	2	1	49.9	41.9	37.5	34.2	27.5	20.9	17.2	13.8	10.9	8.9	1622.0	-28.	990.
		2	50.7	42.8	38.4	35.0	28.1	21.6	17.7	14.2	11.2	9.2	926.6	34.	1711.
		3	51.5	43.5	38.9	35.5	28.6	21.9	18.1	14.5	11.5	9.5	519.7	-50.	1910.
		4	58.5	49.7	44.6	40.8	32.7	25.1	20.8	16.8	13.2	11.0	224.8	10.	1380.
		5	49.3	41.9	37.6	34.4	27.5	21.2	17.6	14.2	11.2	9.3	152.4	42.	1400.
10425	2	1	34.6	28.5	25.2	22.9	18.2	13.7	11.2	8.8	6.9	5.7	2362.0	116.	1300.
		2	41.2	34.5	30.8	28.2	22.6	17.1	14.0	11.3	8.8	7.3	914.0	-17.	1510.
		3	49.6	42.0	38.0	34.9	28.1	21.7	17.9	14.4	11.3	9.3	377.2	-14.	1240.
		4	44.2	36.5	32.8	29.8	23.5	19.2	16.2	11.8	10.6	8.4	221.2	46.	1210.
		5	49.9	41.3	37.9	34.8	27.9	21.5	17.5	14.2	11.3	9.2	216.5	29.	1780.
10450	2	1	28.9	23.5	20.4	18.4	14.7	10.9	9.1	7.0	5.3	4.6	1960.0	-12.	1200.
		2	41.0	34.8	31.3	28.3	22.1	16.7	13.0	10.8	8.7	6.5	629.0	-11.	1161.
		3	35.7	30.8	27.1	24.7	20.2	15.4	12.8	10.1	8.0	6.8	318.8	24.	1170.
		4	42.4	36.5	32.2	29.2	24.1	18.6	15.1	11.8	9.1	7.5	292.9	19.	1800.
		5	38.0	33.6	29.6	26.9	21.3	16.8	12.5	10.9	9.0	7.9	195.8	-12.	1800.
10475	2	1	31.8	25.9	23.1	20.7	16.3	12.1	9.9	7.9	6.1	5.0	1422.0	1.	820.
		2	28.8	24.2	21.4	19.2	15.4	11.7	9.5	7.2	6.0	4.7	607.7	21.	1060.
		3	35.6	30.6	26.9	24.3	19.6	14.8	12.3	9.6	7.6	6.1	499.9	9.	1740.
		4	31.9	28.5	25.3	22.8	18.7	14.4	12.1	9.2	7.3	6.1	305.0	-6.	1770.
		5	38.1	34.0	29.3	26.5	21.6	16.2	13.4	10.4	8.5	7.0	251.7	-15.	2190.
10500	2	1	22.3	17.9	15.7	14.0	11.0	8.1	6.7	5.3	4.1	3.3	2061.0	21.	1190.
		2	30.9	25.4	22.3	20.1	16.0	12.1	9.7	7.7	6.0	5.2	1157.0	0.	2010.
		3	28.5	23.6	20.8	18.9	15.1	11.3	9.4	7.3	5.9	5.0	612.2	-12.	2130.
		4	35.5	29.7	26.6	23.8	19.4	14.9	12.2	9.5	7.3	5.7	420.8	-27.	2440.
		5	29.8	25.0	21.9	20.5	16.3	12.7	11.0	8.9	7.3	5.0	172.3	22.	1500.
10525	2	1	23.7	19.3	16.7	14.8	11.7	8.9	7.1	5.6	4.3	3.6	3166.0	1.	1710.
		2	22.1	18.4	16.5	14.6	11.8	9.0	7.4	5.9	4.7	3.8	1186.0	-14.	1920.
		3	30.2	25.2	22.5	20.0	16.1	12.0	9.7	7.7	5.9	4.8	793.2	-2.	2570.
		4	26.6	22.3	20.1	17.1	14.5	10.7	9.0	7.3	5.0	3.6	288.0	1.	1550.
		5	28.5	23.8	21.7	18.2	15.2	11.2	9.5	7.8	6.0	4.5	141.0	11.	1140.
10550	2	1	15.3	12.1	10.5	9.5	7.4	5.5	4.5	3.6	2.8	2.3	2163.0	-28.	1350.
		2	24.6	20.5	17.6	16.2	12.7	9.3	7.7	6.0	4.7	3.9	1165.0	8.	2190.
		3	20.3	16.9	14.4	13.3	10.6	7.8	7.2	5.4	4.2	3.7	378.7	-14.	1420.
		4	23.0	19.9	16.6	15.2	12.0	8.9	7.9	6.1	4.5	4.2	169.3	4.	1060.
		5	24.9	21.9	18.3	17.0	13.5	9.9	8.5	6.5	5.2	4.4	123.0	11.	1150.

10575	2	1	18.1	15.6	13.4	12.3	9.8	7.3	5.9	4.7	3.6	3.0	3690.0	-13.	1830.
		2	14.4	12.8	10.9	10.1	8.3	6.2	5.2	4.1	3.2	2.7	952.9	-10.	1424.
		3	16.9	14.9	12.7	11.6	9.5	6.9	5.8	4.5	3.8	3.2	367.7	3.	1090.
		4	19.0	17.1	14.6	13.4	11.1	8.0	6.7	5.2	4.3	3.7	236.3	-13.	1170.
		5	21.5	19.0	16.4	14.0	12.1	9.0	7.6	6.1	4.4	3.6	140.5	-19.	1050.
10600	2	1	7.7	6.0	5.4	4.8	3.6	2.7	2.2	1.8	1.4	1.2	2243.0	-8.	1530.
		2	11.3	8.9	7.9	7.0	5.4	4.0	3.2	2.6	2.0	1.6	604.2	4.	1237.
		3	13.9	11.1	10.3	9.1	7.1	5.3	4.1	3.2	2.6	2.2	339.3	5.	1380.
		4	18.0	14.1	13.0	11.4	8.9	6.7	5.3	4.3	3.4	2.7	160.5	-4.	1090.
		5	19.4	15.3	14.6	12.9	10.4	7.4	6.0	4.4	3.6	3.4	171.7	22.	1750.
10625	2	1	8.5	6.4	5.5	5.0	3.5	2.5	2.0	1.5	1.2	.9	1662.0	0.	1130.
		2	11.2	8.8	7.6	6.9	5.1	3.7	2.9	2.3	1.8	1.4	645.1	4.	1321.
		3	14.2	11.4	9.9	9.0	6.8	5.0	4.0	3.1	2.4	1.9	328.5	-2.	1340.
		4	16.9	13.8	12.1	11.0	8.4	6.3	5.1	3.8	3.2	2.6	248.2	-4.	1690.
		5	18.8	15.2	13.2	12.3	9.5	7.2	5.9	4.3	3.9	2.9	177.7	29.	1810.
10650	2	1	7.1	5.5	4.8	4.2	3.2	2.3	1.8	1.4	1.1	.9	2102.0	9.	1400.
		2	12.4	9.8	8.5	7.5	5.8	4.2	3.4	2.6	2.0	1.6	695.0	-8.	1392.
		3	13.1	10.8	9.5	8.5	6.6	4.9	3.9	3.0	2.2	1.9	489.1	29.	1950.
		4	17.3	14.2	12.9	11.6	9.4	6.8	5.8	4.5	3.6	3.0	274.0	5.	1830.
		5	16.7	13.5	12.1	10.9	8.4	6.2	5.0	3.9	3.0	2.5	250.4	8.	2500.
10675	2	1	12.5	10.1	8.7	7.6	6.0	4.3	3.5	2.7	2.1	1.7	1957.0	-6.	1220.
		2	15.3	12.6	11.0	9.8	7.7	5.6	4.5	3.5	2.7	2.2	1021.0	15.	1920.
		3	16.7	14.0	12.4	11.0	8.7	6.4	5.3	4.2	3.2	2.7	491.1	5.	1840.
		4	16.5	13.6	12.0	10.5	8.3	6.0	4.9	3.8	2.9	2.5	364.5	-9.	2280.
		5	14.5	11.5	10.2	8.4	7.0	5.6	4.3	3.4	2.8	2.2	219.5	19.	2060.
10700	2	1	12.4	9.8	8.5	7.6	5.8	4.3	3.5	2.7	2.1	1.7	2123.0	1.	1620.
		2	16.4	13.6	11.8	10.9	8.5	6.4	5.2	4.1	3.2	2.6	796.4	-3.	1829.
		3	15.4	12.9	10.9	10.3	7.9	5.9	4.7	3.7	2.9	2.4	512.5	-28.	2350.
		4	13.5	11.0	9.1	8.8	6.6	5.0	4.0	3.2	2.5	1.9	247.8	30.	1890.
10725	2	1	16.1	12.5	11.2	8.6	7.2	5.1	4.1	3.2	2.5	2.0	571.7	-2.	1380.
		2	16.9	13.2	12.7	7.9	7.7	5.1	4.2	3.3	2.6	2.1	222.1	-16.	1609.
		3	15.2	12.2	12.7	5.5	7.2	4.7	4.3	3.2	2.5	2.0	129.2	18.	1860.
10750	2	1	10.0	7.8	6.7	5.6	4.3	3.1	2.4	1.9	1.5	1.2	1194.0	-1.	1870.
		2	9.6	7.2	6.3	4.8	4.0	2.9	2.3	1.9	1.5	1.2	392.0	14.	1846.
10775	2	1	3.4	2.3	2.0	1.8	1.5	1.1	1.0	.8	.7	-.3	1267.0	10.	2210.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 122W.IND
DATA FILE : 122W.DAT

LINE NO. : 1224

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	18.7	15.8	13.9	12.8	10.0	7.3	5.8	4.5	3.3	2.6	435.6	23.	170.
		2	15.1	12.8	11.5	10.5	8.2	6.0	4.8	3.7	2.8	2.2	95.4	-12.	112.
		3	11.2	9.2	8.4	7.5	5.9	4.4	3.5	2.8	2.1	1.7	56.6	-12.	133.
		4	11.4	9.3	8.5	7.5	5.9	4.2	3.2	2.4	1.8	1.4	40.0	-10.	157.
		5	11.1	8.9	8.2	7.2	5.6	4.1	3.2	2.5	1.8	1.5	29.9	-3.	176.
10050	2	1	16.4	13.9	12.3	11.3	8.9	6.6	5.3	4.1	3.0	2.4	311.6	9.	119.
		2	11.8	9.9	8.9	8.1	6.4	4.7	3.7	2.9	2.2	1.7	111.1	-3.	127.
		3	10.8	8.9	8.1	7.1	5.6	4.1	3.2	2.5	1.9	1.5	68.6	-23.	157.
		4	10.3	8.5	7.8	6.9	5.4	3.9	3.0	2.4	1.8	1.4	41.7	2.	159.
		5	11.3	8.9	8.6	7.3	5.7	4.1	3.2	2.5	1.9	1.4	23.7	-3.	136.
10075	2	1	15.3	13.2	11.4	10.5	8.2	6.1	4.8	3.7	2.8	2.2	362.5	-2.	133.
		2	13.1	11.2	9.6	8.8	6.8	5.0	3.9	3.0	2.2	1.8	145.9	-15.	161.
		3	11.5	9.7	8.3	7.5	5.8	4.2	3.3	2.5	1.9	1.4	72.7	-11.	160.
		4	12.2	10.2	9.0	8.2	6.2	4.8	3.5	2.8	2.3	2.0	37.0	7.	136.
		5	16.6	14.5	11.8	10.9	8.6	5.9	5.1	3.4	2.0	1.5	26.7	-16.	147.
10100	2	1	13.5	11.5	10.0	9.2	7.1	5.3	4.2	3.2	2.4	1.9	477.9	-12.	153.
		2	11.8	10.0	8.7	8.0	6.1	4.5	3.5	2.7	2.0	1.6	160.1	-5.	153.
		3	12.4	10.4	8.9	8.3	6.3	4.5	3.5	2.6	1.8	1.4	74.6	-29.	143.
		4	17.7	14.1	12.7	12.0	8.7	6.6	5.1	3.9	2.9	2.1	39.9	18.	127.
		5	19.5	15.8	14.0	13.2	9.7	7.2	5.5	4.2	3.1	2.6	24.3	-21.	116.
10125	2	1	11.2	9.0	8.2	7.3	5.8	4.2	3.3	2.5	1.8	1.4	388.5	-3.	128.
		2	11.9	9.6	8.7	7.7	6.0	4.3	3.4	2.6	1.9	1.5	126.7	-23.	125.
		3	16.4	13.4	12.3	10.7	8.4	6.0	4.6	3.5	2.6	2.0	62.2	-5.	123.
		4	19.2	15.7	14.6	12.8	10.0	7.1	5.6	4.3	3.2	2.5	29.7	-1.	98.
		5	15.2	12.1	11.2	9.8	7.4	5.2	3.9	2.8	2.1	1.5	20.9	7.	103.
10150	2	1	11.9	9.5	8.4	7.7	6.0	4.4	3.5	2.7	2.0	1.6	312.0	-17.	120.

		2	16.9	13.9	12.3	11.1	8.7	6.1	4.9	3.6	2.7	2.0	109.2	15.	126.
		3	18.4	15.2	13.4	12.1	9.4	6.6	5.3	3.9	2.9	2.2	47.8	-16.	110.
		4	14.9	12.2	10.9	9.8	7.5	5.2	4.1	3.0	2.2	1.7	23.8	4.	92.
		5	11.1	8.9	8.0	6.8	5.3	3.6	2.8	2.0	1.4	1.1	35.9	-3.	208.
10175	2	1	18.4	15.1	13.3	12.0	9.2	6.7	5.3	4.0	3.1	2.4	364.8	11.	123.
		2	19.8	16.3	14.5	13.0	10.0	7.2	5.6	4.3	3.2	2.5	103.3	-22.	104.
		3	17.4	14.1	12.5	11.2	8.5	6.2	4.8	3.6	2.6	2.0	50.2	5.	101.
		4	12.3	9.7	8.6	7.8	5.8	4.2	3.1	2.4	1.8	1.4	57.4	0.	193.
		5	8.3	6.1	5.4	4.7	3.3	2.3	1.6	1.1	.8	.5	40.2	29.	203.
10200	2	1	22.0	17.1	14.5	13.1	9.9	7.3	5.9	4.6	3.7	3.0	1922.0	-18.	1200.
		2	24.1	20.4	17.9	16.4	12.6	9.2	7.3	5.6	4.2	3.3	58.5	4.	110.
		3	14.1	11.5	9.7	8.8	6.5	4.6	3.6	2.6	1.9	1.5	53.6	-3.	201.
		4	8.8	7.2	5.7	5.2	3.7	2.5	1.8	1.2	.8	.6	31.4	50.	197.
		5	8.2	6.9	5.1	4.7	2.8	1.9	1.3	.7	.4	.2	31.6	-19.	298.
10225	2	1	47.5	38.3	33.3	29.9	23.4	17.3	14.0	11.1	8.7	7.1	1087.0	1.	420.
		2	15.9	13.0	11.4	10.2	7.9	5.6	4.4	3.3	2.4	1.9	194.4	7.	228.
		3	9.2	7.4	6.5	5.7	4.3	2.9	2.3	1.7	1.0	.7	93.2	13.	219.
		4	8.7	6.4	5.6	4.7	3.4	2.1	1.5	1.0	.8	.6	68.4	1.	268.
		5	8.3	6.0	5.5	4.6	3.3	2.1	1.6	1.1	.7	.5	106.9	32.	620.
10250	2	1	11.4	8.8	7.4	6.7	5.0	3.5	2.8	2.1	1.6	1.2	371.0	8.	247.
		2	9.1	6.9	5.8	5.2	3.7	2.6	1.9	1.4	1.0	.7	106.1	31.	212.
		3	7.7	5.4	4.6	3.4	2.6	1.6	1.0	.6	.4	.2	61.9	-29.	247.
		4	8.3	6.0	5.4	3.6	3.1	2.0	1.2	.9	.5	.2	82.8	31.	553.
		5	19.7	15.8	14.7	11.6	10.0	7.4	5.8	4.5	3.5	2.8	48.7	-26.	487.
10275	2	1	6.4	5.2	4.3	3.7	2.9	2.1	1.6	1.3	1.0	.8	812.4	3.	364.
		2	3.6	2.7	2.0	1.3	.9	.3	.1	.0	-.1	-.1	215.8	-1.	290.
		3	7.0	6.2	5.1	4.1	3.4	2.3	1.7	1.2	.8	.5	221.0	32.	590.
		4	16.7	15.0	12.9	10.9	9.1	6.6	5.5	4.3	3.5	2.8	117.2	-15.	520.
		5	41.1	36.7	32.5	28.6	24.1	18.1	15.1	11.9	9.4	7.7	52.0	-3.	349.
10300	2	1	4.7	3.3	2.6	2.1	1.4	.9	.6	.4	.3	.2	1229.0	14.	480.
		2	10.7	8.8	7.6	6.6	5.3	3.9	3.1	2.4	1.9	1.5	687.4	6.	809.
		3	19.9	17.0	14.8	13.7	11.0	8.3	6.8	5.5	4.2	3.5	302.4	-21.	710.
		4	44.0	38.1	33.6	31.1	25.1	19.2	15.9	12.8	10.1	8.3	121.1	4.	470.
		5	45.0	39.2	33.6	31.8	25.4	19.4	16.1	12.7	10.0	8.2	50.4	-9.	296.
10325	2	1	15.4	12.0	10.7	9.7	7.7	5.7	4.7	3.7	2.9	2.3	1697.0	25.	800.
		2	23.4	19.4	17.4	15.8	12.9	9.8	8.1	6.5	5.1	4.2	510.9	-22.	729.
		3	44.9	38.9	34.8	31.7	26.1	19.9	16.7	13.3	10.6	8.8	160.8	-23.	450.
		4	45.6	39.7	35.6	31.3	26.7	20.6	17.2	13.8	10.9	9.0	64.4	11.	306.
		5	45.1	40.0	35.6	31.0	26.6	20.0	17.0	13.4	10.8	9.0	53.3	2.	380.
10350	2	1	30.6	25.5	22.8	21.0	16.7	12.7	10.4	8.3	6.5	5.4	3001.0	-24.	1140.
		2	55.6	47.5	42.8	39.4	32.0	24.7	20.4	16.4	13.0	10.8	550.4	-35.	632.
		3	54.0	46.1	41.3	37.9	30.8	23.7	19.6	15.7	12.4	10.3	270.2	9.	610.

		4	54.9	47.0	42.0	38.6	31.3	24.0	19.9	15.9	12.6	10.5	137.0	-1.	520.
		5	59.8	53.7	48.4	45.2	35.4	27.1	21.6	18.0	13.2	11.7	109.7	2.	630.
10375	2	1	49.4	42.3	38.0	34.6	28.3	21.8	18.2	14.5	11.5	9.5	3460.0	-54.	1120.
		2	54.4	46.8	42.1	38.4	31.6	24.4	20.4	16.3	13.0	10.7	918.0	-1.	891.
		3	54.3	47.1	42.2	38.4	31.7	24.5	20.8	16.3	13.0	10.8	479.0	-3.	920.
		4	61.0	53.2	47.6	43.3	35.8	27.5	23.7	18.3	14.8	12.3	321.7	-3.	1040.
		5	52.5	46.5	41.4	37.4	31.2	24.1	21.1	15.9	13.2	11.1	252.2	-1.	1220.
10400	2	1	56.3	48.6	43.6	40.0	32.8	25.5	21.0	16.9	13.4	11.1	1508.0	-1.	860.
		2	54.0	46.7	41.7	38.5	31.7	24.4	20.2	16.4	13.0	10.6	599.3	50.	1026.
		3	61.2	53.2	47.5	43.8	35.9	27.9	22.9	18.4	14.5	12.2	347.6	-86.	1180.
		4	55.2	48.3	42.9	39.9	32.4	25.2	20.6	16.3	12.7	10.9	216.5	49.	1230.
		5	53.6	47.5	41.7	39.0	31.5	24.3	19.5	14.9	11.2	9.7	160.7	18.	1370.
10425	2	1	45.2	38.5	34.6	31.8	25.8	19.6	16.3	13.1	10.4	8.5	1975.0	39.	810.
		2	56.4	48.1	43.0	39.3	32.1	25.4	20.7	16.9	13.2	11.1	879.3	-64.	1089.
		3	52.1	45.4	40.7	37.4	30.6	23.5	19.8	15.9	12.7	10.5	637.1	16.	1570.
		4	50.0	43.1	37.7	34.1	28.3	23.5	18.5	15.5	11.8	10.3	308.3	19.	1270.
		5	45.0	38.2	32.6	28.6	23.8	23.3	17.7	15.1	9.8	9.1	195.9	21.	1210.
10450	2	1	31.5	25.9	22.9	20.7	16.7	12.6	10.5	8.3	6.2	5.0	2159.0	-51.	1350.
		2	38.8	32.5	29.6	26.4	21.2	16.0	12.7	10.5	9.0	7.8	725.9	51.	1367.
		3	40.5	34.0	31.0	27.6	23.1	17.8	14.7	11.8	9.3	7.4	407.8	0.	1530.
		4	38.1	32.2	29.0	24.8	20.9	14.7	12.6	10.5	9.7	7.4	210.5	26.	1320.
		5	38.8	32.2	30.4	26.0	22.0	16.6	13.7	11.5	9.2	7.4	318.3	10.	2990.
10475	2	1	32.9	27.5	24.2	22.3	17.6	13.6	11.3	8.9	7.0	5.6	1510.0	32.	1050.
		2	35.7	30.5	26.6	24.9	20.3	15.3	12.3	9.9	7.7	6.8	615.2	26.	1287.
		3	34.0	29.4	25.3	23.7	18.6	14.4	11.8	9.0	7.0	5.8	344.1	15.	1430.
		4	39.6	33.9	28.6	26.9	21.6	16.3	13.1	11.3	8.0	6.8	440.6	28.	3070.
		5	18.6	16.6	14.0	15.0	13.6	10.8	8.7	7.0	5.0	4.0	137.7	-27.	1440.
10500	2	1	29.6	23.9	21.3	19.6	15.5	11.7	9.6	7.7	6.3	5.2	1499.0	4.	1020.
		2	29.2	24.0	22.0	20.0	16.0	12.2	10.1	8.0	6.2	4.9	648.5	18.	1328.
		3	32.5	27.5	25.0	22.9	18.7	14.4	11.4	9.1	6.7	5.7	834.6	19.	3410.
		4	28.4	24.0	21.5	20.1	16.2	12.3	10.3	8.8	6.7	5.4	225.2	-19.	1530.
		5	32.0	27.5	25.1	22.5	17.9	14.4	11.2	******	9.7	13.3	129.9	11.	1330.
10525	2	1	17.5	14.2	12.3	11.3	8.9	6.6	5.4	4.3	3.4	2.7	2072.0	-2.	1620.
		2	22.8	18.9	16.4	15.3	12.2	9.2	7.6	6.0	4.7	3.9	1627.0	14.	3830.
		3	19.6	16.5	14.4	14.2	11.4	7.8	7.2	5.7	5.0	3.6	384.7	-35.	1800.
		4	23.6	18.5	16.1	15.5	12.2	8.9	7.5	6.1	5.4	4.6	197.1	25.	1540.
		5	19.8	18.2	15.9	15.1	12.8	8.4	8.3	7.6	6.3	3.1	121.9	-5.	1430.
10550	2	1	19.0	15.5	14.0	12.4	9.9	7.4	6.0	4.8	3.7	3.1	3380.0	-3.	2860.
		2	16.7	13.8	12.5	10.8	8.9	6.9	5.7	4.6	3.5	3.0	661.5	-35.	1684.
		3	19.7	15.5	14.5	12.2	10.2	8.0	6.9	4.5	4.0	3.3	310.6	3.	1570.
		4	20.2	15.7	15.0	12.6	11.1	8.3	6.6	5.3	4.2	3.4	156.4	7.	1320.
		5	23.8	18.2	17.5	13.4	11.4	8.4	8.2	6.9	4.8	4.1	105.2	-7.	1330.

10575	2	1	10.8	9.0	7.7	7.1	5.8	4.4	3.6	2.9	2.3	1.9	2124.0	-36.	1410.
		2	14.2	12.0	10.4	9.9	8.0	6.0	4.8	3.6	2.7	2.3	662.9	10.	1328.
		3	14.8	12.8	10.7	10.4	8.3	6.3	5.1	3.7	2.5	2.1	359.1	-23.	1430.
		4	18.5	16.1	13.0	13.1	10.4	7.9	6.6	4.9	3.6	2.8	167.3	28.	1110.
		5	21.7	19.4	16.0	16.2	12.8	9.8	8.0	5.7	3.9	3.2	165.7	0.	1660.
10600	2	1	9.4	7.2	6.2	5.5	4.2	3.0	2.4	1.9	1.5	1.2	2740.0	1.	1620.
		2	10.1	7.9	6.8	6.2	4.8	3.6	2.9	2.2	1.7	1.4	1001.0	-20.	1770.
		3	13.7	10.8	9.3	8.5	6.6	5.0	4.1	3.4	2.6	2.1	420.3	3.	1490.
		4	18.0	14.3	12.8	11.8	9.2	6.9	5.7	4.5	3.5	2.8	317.4	5.	1880.
		5	18.1	14.5	12.5	11.9	9.2	7.0	5.7	4.3	3.4	2.8	214.5	24.	1900.
10625	2	1	7.1	5.4	5.0	4.4	3.4	2.6	2.1	1.6	1.2	1.1	1257.0	-20.	960.
		2	11.6	8.8	8.0	6.6	5.7	4.3	3.4	2.8	2.3	1.7	461.4	3.	1060.
		3	15.6	12.2	11.5	10.1	8.1	6.3	4.9	4.0	3.2	2.6	339.6	-10.	1550.
		4	15.7	11.8	11.7	10.4	8.2	6.6	5.1	4.1	3.4	2.8	192.1	37.	1470.
		5	17.1	12.1	12.2	9.0	8.3	6.2	4.9	4.0	3.3	2.4	163.7	-10.	1880.
10650	2	1	10.2	8.1	7.4	6.7	5.3	4.0	3.2	2.5	1.8	1.4	1668.0	5.	1340.
		2	15.8	12.9	11.4	9.7	8.0	5.8	4.9	3.7	3.2	2.8	712.6	-9.	1721.
		3	14.1	12.2	10.9	9.2	7.9	5.8	4.9	4.2	3.5	2.8	371.6	13.	1790.
		4	14.9	12.7	11.7	9.1	8.1	5.7	4.8	4.0	3.5	2.8	212.0	14.	1700.
		5	15.0	13.1	11.9	8.3	8.2	5.5	4.8	4.0	3.8	3.1	218.5	6.	2630.
10675	2	1	16.9	13.6	11.6	10.4	8.3	6.1	5.0	3.9	3.0	2.4	2133.0	-11.	1670.
		2	17.4	14.7	12.7	11.5	9.2	6.8	5.7	4.4	3.4	2.9	719.8	3.	1695.
		3	15.0	12.9	10.6	10.1	7.9	5.6	4.8	3.7	2.9	2.4	460.8	9.	2160.
		4	15.5	13.7	11.0	10.9	8.4	5.8	5.0	3.8	2.9	2.4	353.0	10.	2770.
		5	16.0	14.8	11.4	11.5	8.4	6.2	6.1	4.2	3.2	2.4	154.7	-42.	1820.
10700	2	1	13.8	11.1	9.6	8.6	6.7	5.1	4.1	3.3	2.6	2.1	1872.0	3.	1580.
		2	15.3	12.4	10.7	9.6	7.5	5.5	4.5	3.6	2.8	2.3	617.3	6.	1571.
		3	14.9	12.2	10.6	9.7	7.5	5.4	4.1	3.3	2.5	2.5	500.4	-3.	2540.
		4	16.8	13.3	11.4	10.2	8.3	6.5	5.4	4.4	3.2	2.5	199.3	-24.	1690.
10725	2	1	11.8	9.3	7.8	6.9	5.3	3.9	3.1	2.4	1.9	1.5	2578.0	12.	2070.
		2	14.1	11.0	9.4	8.3	6.5	4.8	3.8	3.0	2.3	1.9	1086.0	-1.	2620.
		3	16.2	12.0	10.0	8.8	7.1	5.2	4.2	3.3	2.5	2.0	366.8	-25.	1760.
10750	2	1	11.3	8.5	7.2	6.1	4.8	3.4	2.8	2.1	1.7	1.3	1032.0	-3.	1900.
		2	14.2	10.8	9.1	7.3	6.1	4.5	3.7	2.9	2.3	1.7	274.4	-27.	1520.
10775	2	1	11.1	8.7	6.9	6.1	4.7	3.2	2.7	2.0	1.6	1.3	565.9	-23.	1776.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 123W.IND
DATA FILE : 123W.DAT

LINE NO. : 1234

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	10.7	8.5	7.6	6.7	5.2	3.8	3.0	2.4	1.8	1.4	485.2	-24.	163.
		2	10.2	8.0	7.1	6.2	4.8	3.5	2.7	2.2	1.6	1.3	159.9	18.	161.
		3	12.9	10.4	9.3	8.1	6.3	4.5	3.4	2.6	2.0	1.4	87.1	4.	176.
		4	11.0	8.7	7.8	6.6	5.2	3.8	3.1	2.5	1.8	1.7	60.0	-6.	202.
		5	11.1	8.5	7.9	6.2	5.1	3.7	2.8	2.3	1.7	1.3	54.5	-12.	276.
10050	2	1	9.0	6.9	6.1	5.4	4.1	3.0	2.3	1.7	1.3	1.0	390.7	23.	144.
		2	11.3	8.9	7.8	7.0	5.3	3.8	2.9	2.2	1.6	1.2	135.9	4.	150.
		3	11.6	9.0	8.0	6.9	4.7	2.6	1.5	.8	.8	1.0	88.0	-7.	194.
		4	9.5	7.4	6.6	5.4	5.1	4.4	4.0	3.2	2.2	1.1	66.5	-2.	245.
		5	12.1	10.1	9.1	7.4	6.1	4.3	3.6	2.8	2.1	1.5	28.8	-13.	159.
10075	2	1	8.9	7.2	6.0	5.5	3.8	2.2	1.8	-1.0	.8	.6	367.3	11.	115.
		2	9.5	7.8	6.2	5.9	4.5	3.1	2.5	1.9	1.4	1.1	189.3	1.	178.
		3	9.4	8.1	6.2	6.1	4.5	3.2	2.6	1.9	1.4	1.1	123.2	10.	231.
		4	10.5	9.5	7.2	7.4	5.5	3.9	3.3	2.4	1.8	1.5	42.5	-31.	133.
		5	10.8	10.1	7.0	7.5	5.3	3.6	3.0	2.1	1.5	1.2	28.7	1.	135.
10100	2	1	9.4	7.3	6.2	5.7	4.3	3.1	2.5	1.9	1.4	1.1	433.6	-4.	203.
		2	9.7	7.5	6.2	5.8	4.3	3.0	2.4	1.8	1.3	1.0	155.5	14.	218.
		3	11.9	9.7	7.9	7.8	5.5	3.8	3.0	2.3	1.7	1.3	52.0	-34.	145.
		4	10.4	9.1	6.9	7.2	5.3	3.8	2.9	2.1	1.6	1.4	26.0	-27.	121.
		5	14.2	12.2	9.6	10.0	7.1	4.8	4.0	3.2	2.4	1.6	16.9	26.	118.
10125	2	1	9.1	6.8	5.9	5.0	3.8	2.7	2.0	1.5	1.1	.8	316.4	-2.	174.
		2	11.7	9.4	8.1	6.9	5.3	3.8	3.0	2.3	1.8	1.5	52.9	-11.	87.
		3	10.3	7.9	6.8	5.6	4.4	3.0	2.3	1.9	1.4	1.0	31.5	10.	104.
		4	14.8	12.3	10.9	9.4	7.2	5.0	3.7	2.5	1.7	1.5	18.3	-5.	100.
		5	13.8	11.2	10.5	9.2	7.4	5.1	2.8	1.7	.0	-6.2	11.8	-5.	97.
10150	2	1	9.7	7.6	6.6	5.9	4.4	3.1	2.3	1.7	1.2	.9	158.3	-15.	71.

		2	9.7	7.5	6.6	5.9	4.3	3.0	2.4	1.8	1.4	1.0	70.2	2.	94.
		3	14.0	11.1	9.8	8.8	6.5	4.5	3.4	2.5	1.8	1.5	35.2	-2.	94.
		4	11.1	8.6	7.8	7.1	5.1	3.9	3.2	2.4	1.8	.8	19.5	-22.	87.
		5	8.8	6.1	5.7	4.9	3.3	2.0	1.4	.9	.4	.5	25.4	10.	170.
10175	2	1	17.1	14.3	12.2	11.3	9.1	6.7	4.8	3.3	1.3	-.7	178.3	1.	151.
		2	15.5	12.7	10.5	9.2	6.9	4.8	3.8	3.0	2.3	1.5	40.5	-2.	103.
		3	12.7	11.2	8.8	7.5	5.6	3.6	2.8	1.9	1.3	1.0	19.4	-14.	98.
		4	8.2	9.5	6.6	5.5	4.6	3.2	3.3	2.3	1.4	.2	21.2	0.	180.
		5	3.2	5.3	2.6	1.4	1.1	-.2	-.5	-.7	-.4	.4	21.4	0.	272.
10200	2	1	14.7	11.9	10.4	9.2	7.1	5.1	4.0	3.0	2.2	1.7	260.1	2.	120.
		2	13.2	10.6	8.9	7.6	6.0	4.0	3.1	2.2	1.6	1.2	66.0	-18.	91.
		3	9.0	7.6	6.1	5.1	4.0	2.5	2.0	1.3	.8	.6	58.4	4.	161.
		4	4.4	3.7	2.6	1.6	1.2	.2	.0	-.3	-.5	-.6	53.8	-12.	248.
		5	5.7	5.5	4.0	2.6	2.4	1.0	.8	.3	.1	.1	80.1	50.	555.
10225	2	1	14.9	11.8	9.9	8.8	6.7	4.7	3.7	2.7	2.0	1.5	134.8	-8.	98.
		2	11.6	9.8	7.5	6.8	5.1	3.4	2.7	1.9	1.3	1.0	76.7	5.	168.
		3	7.2	6.6	4.0	3.8	2.7	1.6	1.2	.9	1.4	1.6	57.6	-9.	251.
		4	5.9	7.4	3.0	3.8	2.5	1.1	1.1	.1	-.7	-1.0	70.7	41.	516.
		5	3.0	6.3	.9	2.4	1.5	.4	.5	-.1	-.2	-.1	65.1	-43.	713.
10250	2	1	8.8	6.5	5.8	5.0	3.8	2.6	2.1	1.5	1.1	.9	516.6	21.	219.
		2	6.8	4.8	4.3	3.5	2.5	1.6	1.2	.8	.5	.4	188.5	-20.	239.
		3	5.8	3.9	3.8	2.6	2.0	1.1	.8	.5	.2	.1	215.0	34.	540.
		4	4.6	3.2	3.4	1.9	1.7	.8	.7	.3	.0	.0	145.6	-42.	610.
		5	17.9	14.5	14.0	11.2	9.5	6.9	5.5	4.4	3.4	2.8	115.5	30.	730.
10275	2	1	10.3	8.0	6.8	6.0	4.6	3.3	2.6	2.0	1.5	1.2	859.0	-9.	414.
		2	7.8	5.9	5.0	4.3	3.1	2.0	1.5	1.1	.7	.5	403.1	3.	584.
		3	5.8	4.6	3.9	3.3	2.6	1.8	1.2	.9	.6	.4	232.8	0.	670.
		4	17.5	14.9	13.0	11.5	9.2	6.7	5.4	4.1	3.0	2.3	150.0	18.	720.
		5	46.6	41.5	36.3	33.1	27.1	20.3	16.8	13.2	10.2	8.3	64.4	-10.	466.
10300	2	1	8.9	6.7	5.5	5.0	3.8	2.6	2.1	1.5	1.1	.9	1553.0	39.	670.
		2	10.2	8.0	7.0	6.2	4.8	3.5	2.8	2.1	1.6	1.3	515.7	-36.	674.
		3	19.6	15.9	14.4	12.9	10.4	7.8	6.3	5.0	3.8	3.1	310.2	30.	800.
		4	49.0	41.0	37.8	33.9	27.9	21.3	17.5	14.3	11.4	9.2	114.5	-24.	490.
		5	41.3	33.2	31.9	27.5	22.9	17.2	13.9	11.4	9.3	7.3	56.7	9.	371.
10325	2	1	15.2	12.4	11.0	10.1	8.1	6.1	5.0	4.0	3.1	2.6	1687.0	-36.	750.
		2	26.2	21.7	19.4	17.4	14.0	10.7	8.8	7.0	5.5	4.5	534.9	5.	719.
		3	53.4	45.4	41.3	37.3	30.7	23.5	19.3	15.6	12.3	10.3	201.0	-14.	530.
		4	41.0	34.0	32.0	27.8	23.7	17.9	14.5	11.9	8.9	7.3	79.3	6.	355.
		5	51.1	41.9	40.2	33.8	29.2	22.0	17.8	14.7	11.6	9.7	52.0	-5.	350.
10350	2	1	29.6	24.9	22.1	20.5	16.5	12.7	10.5	8.4	6.6	5.4	3160.0	-13.	1940.
		2	63.5	54.4	49.0	45.0	36.8	28.4	23.5	18.9	15.0	12.5	645.2	-29.	1191.
		3	51.5	43.7	39.7	35.8	29.4	22.7	18.6	14.9	11.5	9.1	208.6	8.	760.

		4	58.9	49.8	45.9	40.9	33.9	26.5	22.2	17.9	15.0	12.7	101.5	-12.	620.
		5	62.1	52.4	48.8	42.6	35.8	28.0	23.0	18.8	14.8	12.0	82.7	2.	764.
10375	2	1	64.4	55.4	49.8	46.0	37.6	29.1	24.3	19.5	15.5	12.9	1805.0	-29.	1280.
		2	51.3	44.3	39.7	36.3	29.7	22.9	19.0	15.3	12.1	10.0	475.5	5.	1018.
		3	57.1	49.9	44.9	40.9	33.7	26.0	21.6	17.5	13.9	11.5	215.8	-13.	920.
		4	60.2	52.6	47.5	42.9	36.0	27.4	22.5	18.5	14.8	12.1	144.1	-3.	1020.
		5	43.2	38.8	34.8	29.5	25.9	19.5	16.5	13.2	10.5	8.8	93.2	14.	997.
10400	2	1	51.5	43.7	39.2	36.2	29.3	22.7	18.8	15.1	12.0	9.9	2422.0	-12.	1460.
		2	55.2	46.9	42.1	39.1	31.7	24.5	20.3	16.3	13.0	10.7	776.6	-14.	1406.
		3	61.6	52.7	47.2	43.9	35.7	27.7	22.8	18.4	14.5	12.0	421.9	-4.	1520.
		4	46.0	39.0	34.3	32.3	26.0	20.1	16.2	13.0	10.2	8.5	237.6	3.	1430.
		5	45.7	38.7	33.6	32.3	25.7	19.8	15.9	12.6	9.5	7.9	197.1	-11.	1780.
10425	2	1	39.9	33.4	29.9	27.4	22.3	17.4	14.0	11.4	8.9	7.4	2034.0	-22.	1300.
		2	58.3	49.6	44.8	41.2	33.2	25.1	21.5	16.9	13.7	11.2	784.5	-5.	1508.
		3	43.9	37.6	34.1	30.7	24.8	18.9	17.0	12.6	10.5	8.7	368.1	16.	1410.
		4	44.7	38.2	34.9	30.6	24.8	18.8	18.4	12.5	10.5	8.5	282.8	-8.	1810.
		5	43.6	36.7	34.4	30.7	24.5	16.6	15.4	11.1	9.5	7.2	206.0	46.	1980.
10450	2	1	44.8	37.5	33.7	30.5	24.6	18.9	15.5	12.5	9.9	8.1	2688.0	-43.	1500.
		2	33.5	27.6	25.3	22.7	18.6	14.0	11.5	9.3	7.2	5.9	845.1	-7.	1421.
		3	33.6	28.0	26.7	23.2	19.4	13.9	11.6	9.7	8.1	6.1	544.9	37.	1820.
		4	33.5	27.6	28.2	23.8	20.7	12.7	10.9	10.3	9.5	5.6	330.2	3.	1850.
		5	34.5	28.0	27.0	23.0	20.5	15.2	12.3	9.7	6.9	6.5	174.7	-12.	1460.
10475	2	1	39.3	33.2	29.9	27.3	22.1	17.1	14.2	11.7	9.4	7.8	1997.0	-25.	1220.
		2	38.8	32.6	29.4	26.5	21.7	16.4	13.3	10.0	7.8	6.3	881.2	15.	1627.
		3	34.4	30.2	27.5	24.5	20.0	14.8	12.7	10.1	8.5	7.3	506.2	44.	1860.
		4	34.7	30.0	27.7	25.3	19.4	14.0	12.3	9.3	9.2	8.4	226.9	-24.	1390.
		5	27.9	25.7	24.1	23.7	16.5	11.1	10.1	7.3	8.5	9.2	95.4	11.	881.
10500	2	1	28.5	23.7	21.2	19.0	15.1	11.9	9.4	7.6	5.8	5.0	2274.0	8.	1480.
		2	30.0	25.0	23.0	20.4	17.4	12.3	10.8	8.5	7.2	5.4	973.7	31.	1910.
		3	30.1	25.5	23.4	20.6	16.9	12.3	10.8	9.0	7.0	5.4	388.8	-29.	1520.
		4	25.8	22.6	21.0	18.2	14.1	11.5	11.0	8.9	6.1	5.0	151.9	-8.	990.
		5	29.8	25.7	24.6	20.4	18.7	13.5	11.6	8.7	6.9	4.6	146.1	1.	1430.
10525	2	1	17.9	14.8	12.9	11.6	9.4	7.1	5.7	4.6	3.5	2.8	2809.0	-10.	1830.
		2	20.0	17.1	15.3	13.6	11.1	8.3	7.5	5.6	4.6	4.2	890.4	-22.	1747.
		3	14.7	12.9	10.9	9.7	8.2	6.1	5.1	4.1	3.1	2.5	327.3	35.	1280.
		4	21.4	18.5	15.6	14.0	11.7	9.7	7.0	6.4	4.6	3.1	249.9	-29.	1630.
		5	25.1	22.5	19.7	17.5	13.0	9.1	9.1	6.2	6.2	4.6	165.3	1.	1620.
10550	2	1	21.7	19.7	18.0	15.4	12.0	6.6	4.9	4.0	3.0	2.2	2697.0	-23.	1840.
		2	9.5	7.8	6.6	5.3	4.3	3.0	2.4	1.7	1.2	1.0	778.3	-10.	1593.
		3	15.5	12.5	11.1	9.3	8.1	5.7	4.4	3.5	2.8	2.4	525.5	2.	2140.
		4	18.6	15.2	13.7	11.8	9.8	6.7	6.0	4.4	3.5	3.1	253.9	2.	1730.
		5	21.8	18.0	16.1	13.7	11.4	8.7	6.9	5.4	4.2	3.5	193.6	-3.	1980.

10575	2	1	4.3	3.2	2.6	2.1	1.5	.9	.7	.5	.2	.1	1225.0	10.	1010.
		2	11.0	9.1	7.9	6.9	5.5	4.1	3.2	2.5	1.9	1.5	795.4	1.	1971.
		3	14.4	11.9	10.7	9.2	7.4	5.2	4.7	3.9	2.5	1.2	394.1	-14.	1940.
		4	17.4	14.8	13.2	11.4	9.1	6.6	5.5	4.5	3.4	2.5	218.8	10.	1800.
		5	17.1	14.6	12.9	11.0	9.4	6.8	5.4	4.0	3.1	2.5	185.3	22.	2290.
10600	2	1	12.0	9.4	8.3	7.4	5.8	4.3	3.5	2.7	2.1	1.7	2916.0	-22.	2120.
		2	14.0	11.3	10.2	9.0	7.1	5.2	4.2	3.4	2.7	2.2	676.6	-29.	1482.
		3	16.3	13.1	11.7	10.6	8.4	6.3	5.2	3.7	2.8	2.6	454.9	25.	1980.
		4	15.6	12.7	11.4	10.1	8.0	5.9	4.7	3.6	2.7	2.3	301.0	-4.	2190.
		5	16.4	13.2	12.1	10.5	7.9	5.6	4.5	3.5	2.9	2.4	196.7	4.	2150.
10625	2	1	10.9	8.6	7.6	6.8	5.3	4.0	3.2	2.5	2.0	1.6	1830.0	-5.	1400.
		2	15.6	12.4	11.1	10.0	7.8	5.8	4.7	3.8	2.8	2.3	606.5	3.	1393.
		3	14.4	11.4	10.5	9.3	7.4	5.4	4.0	3.2	2.8	2.3	420.2	27.	1920.
		4	14.9	11.3	10.5	9.1	7.4	5.2	3.8	2.9	3.4	2.8	242.6	-30.	1850.
		5	16.6	12.5	11.8	10.3	8.4	6.0	4.1	3.7	3.6	2.4	242.6	1.	2780.
10650	2	1	18.9	15.8	13.8	12.6	10.1	7.7	6.3	5.0	3.9	3.3	2056.0	-21.	1610.
		2	16.8	14.0	12.2	11.3	9.1	6.9	5.6	4.6	3.6	3.0	867.5	41.	2042.
		3	15.0	12.6	11.0	10.2	8.2	5.9	4.9	4.1	3.3	2.6	421.2	-22.	1970.
		4	15.7	13.1	11.3	10.4	8.4	5.8	4.9	4.3	3.3	2.6	385.9	-9.	3020.
		5	15.9	13.4	11.2	10.6	8.5	6.2	5.1	4.0	3.1	2.8	164.4	42.	1930.
10675	2	1	14.4	11.9	10.2	9.2	7.4	5.5	4.6	3.7	2.9	2.4	2197.0	24.	1600.
		2	14.2	11.9	10.7	9.6	7.9	5.9	4.8	3.6	2.9	2.4	776.1	-23.	1700.
		3	14.6	12.5	11.1	9.7	8.1	5.8	4.8	4.0	3.2	2.5	635.2	-10.	2770.
		4	14.6	12.8	11.2	9.5	7.9	5.6	4.5	3.8	3.0	2.3	246.3	39.	1790.
		5	13.0	11.6	10.7	8.4	7.3	5.8	4.5	4.0	3.6	2.8	208.0	12.	2270.
10700	2	1	9.9	7.7	7.0	6.1	4.9	3.6	3.0	2.3	1.8	1.5	2006.0	-37.	1650.
		2	12.3	9.6	8.9	7.6	6.2	4.6	3.6	2.9	2.2	1.9	1107.0	-20.	2740.
		3	12.5	9.8	9.6	8.0	6.7	5.0	4.2	3.0	2.2	1.9	360.8	42.	1780.
		4	12.4	9.1	9.4	7.6	6.1	4.5	3.8	2.7	1.6	2.0	268.3	-17.	2210.
10725	2	1	9.6	7.4	6.6	5.4	4.5	3.2	2.6	2.1	1.6	1.2	1164.0	-6.	2810.
		2	11.1	8.9	8.3	6.3	5.5	3.8	2.9	2.2	1.9	1.7	271.4	37.	1966.
		3	9.6	8.3	7.1	5.3	4.6	2.6	1.3	1.3	1.5	1.9	166.7	-8.	2410.
10750	2	1	7.9	6.8	5.4	5.1	3.9	2.9	2.4	1.8	1.4	-.3	816.0	29.	2329.
		2	8.1	7.6	5.7	5.6	4.3	3.2	2.9	2.2	1.6	-.1	273.0	4.	2337.
10775	2	1	8.6	7.3	6.1	4.9	4.1	2.9	2.4	1.8	1.4	-1.7	388.8	-2.	2440.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 124W.IND
DATA FILE : 124W.DAT

LINE NO. : 1244

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10025	2	1	10.5	7.9	7.1	6.6	4.9	3.5	2.7	2.0	1.5	1.2	408.6	5.	178.
		2	14.7	11.8	10.7	9.6	7.4	5.3	4.2	3.2	2.4	1.9	137.8	-2.	180.
		3	8.8	6.8	6.4	5.5	4.3	3.1	2.4	1.8	1.4	1.1	80.3	-15.	209.
		4	9.0	6.9	6.4	5.7	4.4	3.2	2.5	1.9	1.4	1.1	61.7	10.	269.
		5	12.6	9.7	8.7	8.1	6.0	4.3	3.4	2.6	2.0	1.6	45.9	42.	300.
10050	2	1	13.6	11.1	9.7	8.6	6.6	4.8	3.8	2.9	2.1	1.7	488.5	9.	213.
		2	8.8	7.3	6.3	5.6	4.3	3.1	2.4	1.8	1.3	1.1	146.2	-5.	191.
		3	7.9	6.5	5.7	5.1	4.0	2.9	2.3	1.8	1.3	1.0	96.3	11.	251.
		4	11.5	9.3	8.0	7.0	5.5	3.9	3.1	2.3	1.7	1.4	61.8	34.	269.
		5	14.0	11.8	10.3	9.4	7.3	5.3	4.3	3.2	2.2	2.1	29.5	-52.	192.
10075	2	1	8.0	6.6	5.6	4.8	3.7	2.5	1.9	1.5	1.2	1.0	345.4	-9.	180.
		2	6.9	5.7	4.9	4.2	3.3	2.3	1.8	1.4	1.0	.7	134.2	11.	210.
		3	9.9	8.1	6.9	6.1	4.7	3.3	2.6	2.0	1.4	1.1	70.8	34.	221.
		4	13.4	11.2	9.8	8.7	6.8	5.0	3.8	3.0	2.3	1.8	31.8	-62.	166.
		5	14.3	11.7	10.4	9.3	7.0	5.1	4.1	3.0	2.2	1.6	23.0	3.	180.
10100	2	1	8.5	6.9	6.0	5.2	4.1	2.9	2.3	1.8	1.3	1.0	384.5	9.	172.
		2	10.1	8.2	7.2	6.2	4.8	3.4	2.5	1.9	1.4	1.1	126.6	19.	170.
		3	12.8	10.9	9.6	8.4	6.7	4.8	3.8	2.8	2.1	1.6	53.8	-40.	144.
		4	14.3	12.0	10.5	9.1	7.2	5.2	4.2	3.1	2.2	1.8	34.1	4.	153.
		5	12.3	11.4	9.0	7.9	6.0	4.2	3.2	2.4	1.7	1.2	18.6	-3.	125.
10125	2	1	6.9	5.6	4.8	4.1	3.1	2.2	1.7	1.2	1.0	.7	260.3	20.	131.
		2	11.0	9.3	8.2	7.2	5.7	4.2	3.3	2.6	1.7	1.3	73.6	-56.	112.
		3	12.4	10.4	9.0	8.0	6.2	4.4	3.4	2.6	1.9	1.5	46.9	26.	142.
		4	10.9	9.2	8.0	7.0	5.4	3.8	3.0	2.3	1.7	1.4	21.5	-14.	108.
		5	9.5	8.2	5.9	6.2	4.4	2.8	2.3	1.1	1.0	.5	38.2	11.	290.
10150	2	1	10.5	8.4	7.5	6.6	5.3	3.8	3.0	2.3	1.7	1.4	194.9	-42.	101.

		2	11.1	8.9	7.9	6.8	5.3	3.6	2.9	2.1	1.6	1.1	71.7	-15.	113.
		3	11.2	8.9	8.0	6.9	5.4	3.9	3.1	2.4	1.9	1.5	35.9	18.	112.
		4	7.6	6.4	5.6	4.1	3.4	2.2	1.6	1.3	.9	.7	48.7	8.	254.
		5	6.2	5.2	5.3	4.4	4.3	1.9	1.5	.5	.1	-.2	32.3	2.	253.
10175	2	1	12.8	10.5	9.2	8.5	6.4	4.6	3.6	2.7	2.0	1.5	230.3	14.	131.
		2	10.2	8.1	7.2	6.8	5.0	3.5	2.6	1.9	1.5	1.2	53.9	-5.	92.
		3	8.2	7.3	6.0	5.6	4.1	2.7	1.7	.9	.5	.4	66.1	10.	225.
		4	5.8	4.4	3.2	3.0	1.8	1.1	.8	.8	.4	-.1	40.7	-10.	232.
		5	3.6	1.8	6.7	5.6	2.2	1.8	1.3	1.7	1.5	.6	28.5	-9.	244.
10200	2	1	11.5	9.2	8.2	7.4	5.7	4.1	3.4	2.6	2.1	1.7	186.5	-8.	87.
		2	10.3	7.8	6.9	6.6	4.8	3.5	2.7	2.0	1.5	1.1	138.4	14.	194.
		3	8.9	6.4	5.7	5.4	3.8	2.7	2.1	1.7	1.4	1.1	77.2	-16.	216.
		4	6.6	4.3	3.7	3.8	2.3	1.5	.8	.3	.0	-.2	47.4	-3.	221.
		5	2.6	.6	.4	1.0	.0	-.1	-.3	-.2	-.3	-.3	44.7	-3.	314.
10225	2	1	11.5	9.9	8.5	7.3	5.7	4.5	3.7	3.1	2.3	1.9	402.3	19.	210.
		2	9.9	8.6	7.4	6.1	4.9	3.4	2.6	1.9	1.4	1.0	147.5	-13.	231.
		3	6.9	6.3	5.4	3.9	3.2	2.1	1.6	1.1	.9	.6	78.7	-12.	246.
		4	.8	1.5	1.3	-.1	.0	-.5	.6	1.5	.9	.5	62.4	6.	326.
		5	5.6	5.6	4.9	3.0	3.0	1.9	1.4	.0	-.1	.1	112.0	0.	870.
10250	2	1	9.3	7.4	6.5	5.6	4.4	3.1	2.4	1.9	1.4	1.1	602.5	-12.	270.
		2	8.8	7.0	6.2	5.2	4.1	2.8	2.2	1.5	1.2	.9	177.5	-14.	238.
		3	3.1	2.4	2.2	1.4	1.2	.8	.6	.4	.4	.3	131.1	17.	350.
		4	5.9	4.4	3.8	2.8	2.1	1.1	.6	.3	.0	.0	176.2	-11.	790.
		5	7.8	6.2	5.7	4.3	3.6	2.4	1.9	1.4	1.0	.7	142.6	-48.	950.
10275	2	1	9.5	7.5	6.3	5.7	4.3	3.1	2.4	1.8	1.4	1.1	1295.0	-17.	580.
		2	7.5	6.2	5.3	4.8	3.7	2.6	2.0	1.5	1.1	.8	464.1	7.	624.
		3	8.9	7.3	6.0	5.5	4.1	2.8	2.3	1.6	1.2	.9	523.0	2.	1400.
		4	9.4	8.4	6.6	6.4	5.0	3.5	2.9	2.1	1.6	1.3	311.8	-55.	1390.
		5	25.8	22.4	19.4	18.0	14.5	10.9	9.1	7.1	5.6	4.6	178.7	87.	1200.
10300	2	1	7.5	5.6	4.8	4.1	3.1	2.1	1.6	1.2	.9	.7	1227.0	12.	630.
		2	10.6	8.4	7.3	6.4	4.9	3.4	2.7	2.0	1.5	1.2	966.3	2.	1492.
		3	10.2	8.2	7.4	6.5	5.1	3.7	3.0	2.3	1.7	1.4	483.5	-55.	1490.
		4	26.1	21.9	19.8	17.8	14.3	10.9	8.9	7.1	5.5	4.5	253.5	70.	1300.
		5	39.8	33.4	30.6	27.1	22.4	17.1	14.1	11.3	9.0	7.4	83.9	-19.	647.
10325	2	1	11.7	9.3	8.2	7.1	5.5	4.0	3.2	2.4	1.8	1.5	3033.0	69.	1260.
		2	10.9	9.1	8.1	7.1	5.7	4.2	3.4	2.6	2.0	1.6	1054.0	-49.	1320.
		3	27.1	23.1	20.8	18.7	15.3	11.6	9.6	7.6	6.0	4.9	461.2	75.	1150.
		4	38.5	33.6	29.8	27.2	22.3	17.1	14.2	11.4	9.1	7.5	153.4	-26.	640.
		5	38.3	34.3	29.2	26.5	21.9	17.0	14.1	11.2	8.5	7.2	90.3	40.	567.
10350	2	1	11.2	9.2	7.9	7.4	5.9	4.3	3.5	2.8	2.1	1.7	1622.0	-53.	1150.
		2	27.4	23.3	20.9	19.1	15.5	11.8	9.7	7.8	6.1	5.0	526.8	76.	1127.
		3	38.6	33.0	30.0	27.2	22.3	17.2	14.2	11.4	9.0	7.4	160.5	-31.	680.

		4	37.3	31.4	28.9	25.8	21.3	16.3	13.7	11.0	8.7	7.2	77.6	32.	553.
		5	59.0	50.0	46.5	41.7	34.7	26.6	21.4	17.4	14.0	11.6	59.3	-40.	634.
10375	2	1	37.5	31.7	28.4	26.0	21.0	16.1	13.2	10.6	8.3	6.8	2694.0	60.	1760.
		2	42.9	36.6	32.9	30.2	24.5	18.9	15.5	12.5	9.9	8.1	552.8	-24.	1084.
		3	39.8	34.1	30.9	28.1	22.9	17.6	14.5	11.7	9.3	7.6	293.5	8.	1140.
		4	61.6	52.7	48.2	43.6	36.0	27.9	22.8	18.5	14.7	12.3	160.8	-43.	1050.
		5	48.5	40.7	38.0	33.4	28.4	22.0	17.4	14.0	11.5	9.5	112.1	33.	1090.
10400	2	1	51.4	44.0	39.2	36.2	29.4	23.3	18.9	15.1	11.7	10.0	1248.0	-32.	950.
		2	45.2	39.3	35.5	33.2	26.8	19.4	17.0	13.7	11.5	8.9	572.1	8.	1314.
		3	64.4	55.9	50.0	47.0	38.1	29.6	24.6	19.8	15.7	13.1	287.9	1.	1320.
		4	50.9	43.5	37.7	35.7	28.4	23.1	19.0	15.9	12.3	10.0	169.3	-13.	1290.
		5	43.3	36.3	31.1	29.9	22.6	20.0	16.3	14.2	10.9	8.5	143.8	16.	1650.
10425	2	1	33.9	28.5	25.5	23.3	18.8	14.4	11.9	9.5	7.5	6.2	2959.0	15.	1450.
		2	56.9	49.0	44.3	40.7	33.3	25.9	21.4	17.2	13.6	11.2	1215.0	-4.	1780.
		3	49.0	42.0	38.1	34.8	28.5	22.1	18.3	14.8	11.7	9.7	585.4	-19.	1710.
		4	42.8	36.6	33.7	30.4	24.8	19.0	15.8	12.8	10.0	8.4	406.5	7.	1990.
		5	40.3	34.1	31.3	28.2	23.3	17.9	14.8	12.0	10.0	8.0	252.7	15.	1850.
10450	2	1	40.0	33.7	30.2	27.6	22.3	17.0	14.1	11.2	8.8	7.3	2885.0	-10.	1840.
		2	40.8	34.9	31.1	28.8	23.4	17.9	14.6	12.0	9.4	7.7	950.2	-23.	1826.
		3	36.6	31.8	28.2	25.7	20.4	15.8	13.7	10.0	8.3	7.4	543.9	13.	2080.
		4	36.6	32.2	28.3	25.4	19.3	15.4	13.9	9.0	7.9	8.0	308.5	18.	1970.
		5	35.2	31.0	27.1	24.2	19.0	14.9	13.0	9.0	7.6	7.5	195.4	11.	1870.
10475	2	1	38.5	32.8	29.2	26.8	21.7	16.5	13.6	10.8	8.5	7.0	2313.0	-22.	1540.
		2	31.6	27.2	24.0	21.9	17.5	13.6	11.2	9.1	7.2	5.9	838.5	5.	1680.
		3	29.5	26.2	23.3	21.5	17.3	13.6	11.3	8.6	6.9	5.7	493.3	29.	1970.
		4	28.6	25.4	22.2	20.3	16.4	13.0	10.8	8.5	6.5	5.5	253.1	-2.	1690.
		5	27.0	25.1	21.0	18.7	13.8	12.9	10.5	9.9	5.9	6.1	100.1	10.	1000.
10500	2	1	34.1	29.0	26.1	23.8	19.3	14.8	12.1	9.6	7.6	6.7	2055.0	-7.	1430.
		2	32.3	27.8	25.2	22.5	18.7	14.5	11.9	9.6	7.6	5.5	895.6	22.	1874.
		3	30.1	25.5	23.4	20.9	17.5	13.3	10.9	8.8	6.9	6.1	432.2	-4.	1800.
		4	30.1	26.2	24.5	20.8	17.3	13.9	11.9	10.4	7.7	5.0	144.8	8.	1010.
		5	35.4	29.5	28.8	22.9	20.6	16.8	14.1	10.9	8.7	2.8	139.1	11.	1450.
10525	2	1	18.1	15.3	13.6	12.3	9.9	7.7	6.2	5.0	3.8	3.1	2666.0	4.	1810.
		2	19.5	16.5	14.9	13.4	11.0	8.1	6.7	5.6	4.6	3.7	987.1	-2.	2021.
		3	23.0	19.3	17.3	14.7	12.4	10.4	6.1	4.8	4.4	5.8	286.7	0.	1170.
		4	25.5	20.3	18.1	15.3	13.3	10.2	6.7	6.9	6.5	6.1	245.1	-2.	1670.
		5	27.7	21.6	19.3	15.9	13.6	13.8	7.4	7.5	6.8	8.2	81.4	10.	833.
10550	2	1	11.3	9.4	8.4	7.7	5.9	4.2	3.6	2.8	2.2	1.7	2863.0	7.	2240.
		2	12.7	10.2	9.4	8.2	6.9	6.1	3.8	3.4	2.3	2.4	591.2	14.	1392.
		3	17.4	15.0	15.4	14.7	10.7	5.6	5.8	2.3	3.4	3.2	433.9	4.	2030.
		4	18.2	15.7	17.5	15.2	11.0	3.6	6.9	******	4.4	2.2	127.3	-9.	990.
		5	21.1	14.2	12.4	8.8	9.9	12.1	4.7	******	4.0	3.8	163.3	-2.	1920.

10575	2	1	7.9	6.7	5.8	5.2	4.3	3.0	2.5	2.1	1.6	1.2	1351.0	18.	1170.
		2	11.5	10.0	8.6	7.3	6.0	4.6	3.8	2.6	2.0	2.0	720.3	5.	1884.
		3	12.8	12.0	10.5	8.6	6.5	4.8	4.6	******	2.4	5.1	178.0	-9.	920.
		4	20.9	18.6	15.3	12.0	8.9	8.2	8.4	5.1	4.2	4.3	219.1	2.	1910.
		5	14.6	14.4	12.3	10.8	10.4	8.1	5.8	5.1	3.1	2.9	127.6	5.	1660.
10600	2	1	6.8	5.1	4.6	4.0	3.2	2.4	1.9	1.4	1.1	1.0	2214.0	-9.	1820.
		2	10.2	8.3	7.5	6.7	5.1	3.5	2.8	2.9	1.8	1.0	390.2	18.	967.
		3	14.9	12.1	11.7	9.9	8.3	6.4	5.0	4.2	3.4	2.8	420.7	-33.	2080.
		4	15.2	12.2	11.6	10.1	8.6	6.4	4.6	3.6	3.0	2.6	197.1	8.	1620.
		5	17.2	13.6	14.4	11.9	10.2	8.0	5.1	4.7	3.8	2.6	172.2	0.	2130.
10625	2	1	8.8	6.8	6.2	5.2	4.3	3.3	2.8	2.2	1.7	1.4	1171.0	25.	910.
		2	14.5	12.2	11.2	10.4	8.1	6.2	5.0	4.1	3.3	2.8	849.1	-47.	1999.
		3	13.8	11.3	10.2	9.2	7.4	5.6	4.6	3.8	3.1	2.4	348.7	20.	1630.
		4	15.5	12.5	12.0	10.1	8.4	6.3	5.1	4.2	3.4	2.7	230.8	-20.	1810.
		5	17.6	14.0	13.8	11.1	9.4	7.1	5.7	4.9	3.9	3.3	231.0	6.	2720.
10650	2	1	17.6	14.9	12.9	11.6	9.3	7.1	5.7	4.6	3.6	3.0	3687.0	15.	2630.
		2	17.0	14.5	12.7	11.3	9.2	7.0	5.7	4.6	3.6	3.0	923.2	23.	1976.
		3	16.6	14.4	12.6	10.8	9.1	6.8	5.6	4.3	3.3	2.9	520.2	-27.	2220.
		4	17.3	15.2	13.0	10.6	8.8	6.4	5.2	3.6	3.1	3.0	412.6	10.	2940.
		5	14.1	12.2	11.2	9.2	7.7	6.1	4.7	3.9	3.1	2.2	212.5	-12.	2270.
10675	2	1	13.5	11.1	9.8	8.8	7.1	5.4	4.4	3.6	2.8	2.3	1952.0	17.	1250.
		2	15.7	13.4	11.9	10.7	8.6	6.5	5.3	4.3	3.3	2.7	871.9	-25.	1676.
		3	15.9	13.3	11.5	10.5	9.1	7.7	5.1	4.8	2.6	2.0	648.0	11.	2480.
		4	13.6	11.6	10.2	9.0	7.3	5.4	4.4	3.5	2.7	2.1	277.3	-7.	1770.
		5	15.1	13.1	11.1	10.0	7.6	5.2	8.4	3.4	2.8	2.3	229.3	-5.	2200.
10700	2	1	12.5	10.3	8.9	8.2	6.5	5.0	4.1	3.2	2.5	2.1	2670.0	-27.	1820.
		2	14.6	12.1	10.3	9.5	7.5	5.6	4.5	3.5	2.7	2.3	1269.0	17.	2590.
		3	12.1	10.5	8.9	8.4	6.5	4.8	3.8	3.3	2.7	2.2	508.0	-18.	2070.
		4	13.2	11.7	9.3	9.2	7.1	5.2	4.3	3.3	2.8	2.2	318.4	-1.	2170.
10725	2	1	10.8	9.0	7.9	6.6	5.5	3.9	3.1	2.4	1.9	1.4	948.8	24.	2482.
		2	9.9	8.8	7.6	6.1	5.5	3.9	3.3	2.5	1.8	1.6	277.4	-20.	2177.
		3	10.4	10.3	9.0	6.5	6.4	3.9	3.7	2.8	2.8	2.0	157.4	-5.	2460.
10750	2	1	7.3	5.0	5.1	4.1	3.3	2.4	1.9	1.6	1.2	.2	615.7	-8.	2760.
		2	10.4	6.5	7.9	4.9	4.3	3.1	2.4	1.8	1.4	.3	185.6	-11.	2490.
10775	2	1	10.8	9.5	7.4	6.7	5.4	3.8	3.2	2.4	1.9	.7	545.6	-7.	2850.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 84W.IND
DATA FILE : 84W.DAT

LINE NO. : 844

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	13.3	11.2	9.9	9.0	7.0	5.4	4.3	3.4	2.6	2.1	220.3	15.	74.
		2	10.3	8.7	7.7	7.0	5.4	4.1	3.2	2.5	1.9	1.5	90.9	-6.	92.
		3	9.1	7.9	7.2	6.5	5.0	3.3	2.5	2.0	1.3	1.1	46.4	14.	93.
		4	9.6	7.9	6.8	6.0	4.7	4.0	3.2	2.5	2.2	1.6	47.2	-22.	159.
		5	13.0	10.2	9.4	8.9	6.7	4.8	3.8	3.0	2.1	1.7	52.9	-7.	267.
10350	2	1	10.7	9.0	7.9	7.1	5.5	4.1	3.3	2.6	2.0	1.6	438.6	-10.	144.
		2	10.4	8.6	7.6	6.7	5.3	3.9	3.1	2.4	1.8	1.4	114.6	7.	113.
		3	9.5	8.1	7.0	6.1	4.8	3.5	2.7	2.1	1.5	1.2	135.9	-23.	260.
		4	14.0	12.1	10.4	9.1	7.3	5.4	4.3	3.4	2.6	2.2	89.4	0.	295.
		5	7.3	6.8	5.5	4.4	3.8	2.7	2.2	1.6	1.2	1.0	50.1	-57.	248.
10375	2	1	9.3	7.7	6.6	6.0	4.7	3.4	2.7	2.1	1.6	1.2	312.1	1.	111.
		2	9.6	7.8	6.7	6.1	4.7	3.4	2.7	2.0	1.5	1.2	246.7	-22.	264.
		3	15.1	12.3	10.8	9.8	7.6	5.6	4.5	3.4	2.6	2.1	131.9	0.	280.
		4	8.5	6.7	5.9	5.5	4.2	3.2	2.6	2.0	1.6	1.3	62.2	-11.	221.
		5	12.2	10.1	9.4	9.3	6.7	4.5	4.2	2.9	2.2	1.5	64.7	2.	346.
10400	2	1	9.3	7.2	6.2	5.3	4.2	2.9	2.4	1.8	1.3	1.0	729.1	-33.	254.
		2	16.7	13.7	11.9	10.7	8.4	6.1	4.9	3.8	2.9	2.3	283.7	6.	296.
		3	10.1	8.6	7.3	6.6	5.3	3.8	3.1	2.4	1.8	1.4	111.7	-37.	230.
		4	14.0	11.9	10.1	9.2	7.3	5.3	4.3	3.3	2.5	2.0	93.6	22.	326.
		5	10.5	8.8	7.3	6.5	5.2	3.8	3.0	2.4	1.8	1.4	74.4	-2.	389.
10425	2	1	22.1	18.2	15.8	14.2	11.1	8.2	6.5	5.1	3.9	3.2	1030.0	-7.	380.
		2	13.6	11.4	9.9	9.0	7.0	5.2	4.1	3.2	2.5	2.0	245.2	-19.	271.
		3	17.7	15.0	13.1	11.9	9.4	6.9	5.5	4.2	3.2	2.5	191.4	6.	420.
		4	13.3	11.1	9.5	8.6	6.7	5.0	3.9	3.2	2.4	2.1	129.0	2.	470.
		5	12.7	10.8	9.4	8.6	6.7	5.0	4.0	3.1	2.3	1.9	93.6	11.	518.
10450	2	1	15.9	13.1	11.2	10.1	7.9	5.8	4.6	3.6	2.8	2.3	1225.0	-17.	490.

		2	22.8	18.9	16.2	14.7	11.4	8.4	6.7	5.2	4.0	3.3	666.4	8.	804.
		3	18.0	15.2	12.8	11.7	9.1	6.7	5.3	4.1	3.1	2.5	402.5	-14.	970.
		4	16.6	14.0	11.9	10.9	8.5	6.3	5.1	4.0	3.0	2.5	223.8	24.	900.
		5	17.1	14.3	12.2	10.8	8.1	6.5	5.4	4.0	3.1	2.5	79.8	3.	481.
10475	2	1	17.2	14.0	11.9	11.0	8.4	6.1	4.8	3.8	2.8	2.3	2754.0	-10.	1660.
		2	14.2	11.6	9.9	9.0	6.9	5.1	4.0	3.1	2.3	1.9	983.8	-7.	1782.
		3	11.8	10.1	8.9	8.2	6.4	4.8	3.8	3.0	2.3	1.8	526.1	11.	1900.
		4	13.2	10.9	9.4	8.7	6.7	5.0	3.9	3.1	2.4	1.9	158.2	6.	950.
		5	20.8	17.0	14.6	13.5	10.4	7.7	6.0	4.9	3.6	2.9	86.0	-1.	779.
10500	2	1	14.5	11.5	10.2	8.9	6.9	5.1	4.0	3.1	2.4	1.9	1954.0	-9.	1800.
		2	11.6	9.8	9.0	7.8	6.1	4.6	3.6	2.8	2.2	1.7	812.3	16.	2250.
		3	11.4	9.7	8.8	7.7	6.0	4.5	3.6	2.8	2.2	1.7	214.7	-5.	1180.
		4	19.8	16.4	14.6	12.8	9.9	7.3	5.8	4.5	3.5	2.7	105.6	5.	970.
		5	11.6	9.6	8.5	7.4	5.8	4.1	3.2	2.5	1.9	1.5	63.0	-1.	873.
10525	2	1	14.4	11.6	10.1	9.1	7.2	5.3	4.3	3.3	2.6	2.1	2030.0	3.	1770.
		2	14.4	11.9	10.4	9.4	7.5	5.5	4.4	3.5	2.7	2.2	429.9	-9.	1124.
		3	20.6	17.5	15.3	13.9	11.0	8.1	6.5	5.1	3.9	3.1	201.7	-1.	1050.
		4	13.8	11.3	9.7	8.7	6.8	4.8	3.9	3.0	2.3	1.8	112.0	7.	970.
		5	14.6	12.1	10.3	9.2	7.2	5.1	4.2	3.1	2.4	1.9	94.1	-63.	1231.
10550	2	1	14.6	12.0	10.4	9.6	7.5	5.6	4.5	3.5	2.7	2.2	1062.0	-6.	950.
		2	21.0	17.3	15.1	13.9	10.7	7.9	6.4	5.0	3.8	3.1	374.5	1.	1007.
		3	13.8	11.3	9.7	9.1	6.9	5.0	3.9	3.0	2.2	1.8	188.2	0.	1010.
		4	14.7	11.9	10.3	9.3	7.2	5.2	4.1	3.2	2.4	1.9	147.6	-60.	1320.
		5	18.2	14.7	12.6	11.9	7.8	6.4	4.8	4.1	3.0	2.4	106.4	54.	1430.
10575	2	1	23.4	19.2	16.8	15.2	12.0	8.8	7.1	5.6	4.3	3.5	970.1	-8.	951.
		2	17.9	14.7	12.8	11.6	9.0	6.6	5.3	4.1	3.1	2.5	342.8	-11.	1009.
		3	16.0	13.2	11.5	10.5	8.2	6.0	4.7	3.6	2.7	2.2	262.4	-49.	1540.
		4	20.2	16.5	14.3	13.1	10.1	7.3	5.9	4.5	3.4	2.8	159.1	57.	1560.
		5	18.7	15.2	13.1	12.0	9.2	6.7	5.4	4.1	3.0	2.4	105.3	2.	1540.
10600	2	1	23.2	18.8	16.6	14.8	11.7	8.5	6.9	5.3	4.0	3.3	953.8	-17.	788.
		2	20.0	16.1	14.2	12.7	10.0	7.3	5.9	4.5	3.4	2.8	516.5	-43.	1280.
		3	23.0	18.8	16.8	15.0	11.8	8.7	7.0	5.4	4.1	3.3	278.7	47.	1370.
		4	21.8	17.5	15.5	13.7	10.8	7.9	6.3	4.9	3.7	3.0	169.2	3.	1390.
		5	27.4	22.1	19.6	17.6	13.8	10.2	8.2	6.4	4.9	4.0	89.1	-8.	1103.
10625	2	1	19.5	15.9	13.7	12.6	9.8	7.3	5.8	4.5	3.5	2.8	1658.0	-50.	1530.
		2	27.0	22.5	20.0	18.0	14.1	10.5	8.4	6.6	5.1	4.1	597.3	43.	1654.
		3	26.5	21.9	19.3	17.4	13.6	10.1	8.1	6.3	4.8	3.9	297.5	4.	1640.
		4	31.8	26.3	23.1	20.8	16.4	12.1	9.8	7.7	5.9	4.7	135.5	-18.	1250.
		5	66.2	55.7	49.5	45.0	36.1	27.2	22.2	17.6	13.7	11.2	87.0	-14.	1204.
10650	2	1	23.7	19.4	17.0	15.3	12.1	9.0	7.3	5.8	4.5	3.7	2380.0	36.	2070.
		2	26.0	21.8	19.2	17.3	13.6	10.1	8.1	6.3	4.9	4.0	587.2	6.	1536.
		3	28.9	24.0	21.3	19.2	15.1	11.3	9.1	7.1	5.5	4.5	247.4	-23.	1290.

		4	63.9	53.9	48.0	43.7	34.9	26.4	21.5	17.0	13.2	10.8	141.7	-14.	1230.
		5	61.0	51.9	46.5	42.5	34.3	26.3	21.6	17.3	13.5	11.1	93.8	19.	1227.
10675	2	1	37.0	30.7	26.9	24.4	19.2	14.3	11.6	9.1	7.1	5.7	1131.0	-5.	2530.
		2	36.0	30.0	26.3	23.8	18.7	13.9	11.2	8.8	6.8	5.4	242.9	-25.	1634.
		3	66.0	56.0	49.8	45.4	36.4	27.5	22.4	17.7	13.8	11.2	115.3	16.	1540.
		4	67.0	56.8	50.8	46.2	37.5	28.6	23.4	18.7	14.7	12.0	61.7	-8.	1384.
10700	2	1	35.4	29.2	25.6	23.1	18.2	13.5	10.9	8.6	6.6	5.3	508.8	-26.	1770.
		2	64.9	54.2	48.3	43.9	34.8	26.5	21.4	16.9	13.1	10.7	154.2	13.	1610.
		3	68.1	58.5	51.9	46.9	39.0	28.9	24.2	19.2	15.2	12.4	77.6	-5.	1620.
10725	2	1	56.7	47.3	42.0	38.3	30.3	22.8	18.5	14.5	11.2	9.1	920.7	13.	1927.
		2	67.8	57.2	51.2	46.9	37.8	28.9	23.7	18.9	14.8	12.1	284.9	-11.	1789.
10750	2	1	63.9	53.9	48.2	44.0	35.3	26.9	22.0	17.5	13.7	11.1	416.0	-11.	1306.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 83W.IND
DATA FILE : 83W.DAT

LINE NO. : 834

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	10.7	9.1	7.8	7.5	5.8	4.3	3.5	2.7	2.1	1.7	381.1	-18.	128.
		2	12.1	10.2	8.7	8.2	6.4	4.8	3.9	3.0	2.3	1.9	120.2	11.	121.
		3	11.2	9.3	8.0	7.6	6.0	4.5	3.6	2.9	2.4	1.6	56.9	-8.	115.
		4	10.3	8.4	7.2	6.8	5.2	3.6	3.0	2.2	1.3	1.6	35.2	7.	118.
		5	11.0	8.8	8.0	7.4	5.7	4.2	3.5	2.5	1.8	1.5	18.6	7.	94.
10350	2	1	12.0	10.1	8.8	7.9	6.2	4.6	3.7	2.9	2.2	1.8	346.9	3.	111.
		2	11.9	10.2	9.0	8.2	6.5	4.9	4.0	3.1	2.4	1.9	113.6	-19.	109.
		3	10.2	8.6	7.4	6.7	5.2	3.8	3.1	2.4	1.9	1.5	60.1	4.	115.
		4	10.3	9.3	7.7	7.4	5.6	4.0	3.4	2.5	1.8	1.5	29.1	8.	93.
		5	9.2	7.5	6.3	5.6	4.4	3.3	2.5	2.1	1.5	1.1	29.4	-14.	141.
10375	2	1	10.4	8.6	7.6	7.2	5.4	4.0	3.2	2.5	1.9	1.5	286.5	-16.	105.
		2	9.9	8.1	7.2	6.5	5.0	3.7	2.9	2.3	1.8	1.3	105.9	7.	117.
		3	10.3	8.3	7.4	6.6	5.1	3.7	2.9	2.2	1.7	1.3	44.0	5.	97.
		4	9.1	7.1	6.1	5.4	4.3	3.1	2.5	1.9	1.5	1.2	40.0	-19.	147.
		5	8.5	6.5	6.3	7.2	4.6	2.7	2.0	1.9	1.7	1.2	34.7	9.	192.
10400	2	1	9.5	7.8	6.7	6.3	4.7	3.5	2.8	2.1	1.6	1.3	397.9	0.	138.
		2	11.1	9.1	7.8	7.2	5.6	4.1	3.3	2.5	1.9	1.5	108.5	-2.	113.
		3	9.4	7.7	6.6	6.2	4.8	3.4	2.7	2.1	1.6	1.3	80.9	-9.	168.
		4	9.9	8.1	6.9	6.4	5.0	3.6	2.8	2.1	1.6	1.2	58.9	8.	205.
		5	9.2	10.4	8.4	6.8	5.1	3.3	2.8	2.8	2.1	1.4	52.8	-26.	276.
10425	2	1	9.7	7.9	6.7	6.1	4.8	3.6	2.8	2.2	1.5	1.3	221.3	-7.	115.
		2	9.4	7.9	6.6	6.1	4.8	3.4	2.8	2.1	1.6	1.2	119.3	-8.	187.
		3	11.2	9.3	7.6	7.2	5.7	4.1	3.3	2.5	1.9	1.6	70.4	7.	220.
		4	10.9	9.2	7.3	7.1	5.7	4.0	3.3	2.5	1.9	1.5	53.2	-24.	278.
		5	9.8	8.5	6.5	6.6	5.3	3.7	3.1	2.3	1.8	1.5	52.1	22.	408.
10450	2	1	9.4	7.7	6.7	6.0	4.6	3.4	2.7	2.1	1.6	1.2	580.8	-17.	289.

		2	13.1	10.7	9.4	8.4	6.5	4.7	3.7	2.9	2.2	1.8	211.0	5.	315.
		3	12.2	10.3	8.8	8.0	6.2	4.5	3.6	2.8	2.1	1.7	125.4	-20.	370.
		4	11.8	10.1	8.6	7.8	6.1	4.4	3.6	2.7	2.0	1.7	109.9	17.	540.
		5	12.0	10.6	8.9	7.9	5.7	3.9	3.5	2.2	1.9	1.4	93.7	8.	700.
10475	2	1	12.9	10.6	9.3	8.2	6.4	4.7	3.7	2.9	2.1	1.7	799.2	5.	386.
		2	12.5	10.4	9.2	8.1	6.3	4.7	3.6	2.9	2.2	1.7	316.9	-19.	459.
		3	12.7	10.7	9.5	8.3	6.6	4.8	3.8	3.0	2.3	1.8	246.2	14.	710.
		4	13.2	11.0	9.8	8.4	6.7	4.9	3.8	3.0	2.3	1.7	191.2	9.	920.
		5	10.9	9.3	8.6	7.5	6.0	4.2	3.5	2.7	2.2	1.7	43.1	-1.	312.
10500	2	1	14.1	11.6	9.9	8.9	7.0	5.1	4.1	3.1	2.4	1.9	1579.0	-32.	740.
		2	12.8	10.8	9.2	8.2	6.5	4.8	3.9	3.0	2.3	1.8	741.9	7.	1043.
		3	13.2	11.1	9.5	8.5	6.7	4.9	4.0	3.0	2.3	1.9	515.9	10.	1440.
		4	12.1	10.5	8.8	7.8	6.2	4.4	3.6	2.7	2.0	1.6	82.1	1.	384.
		5	16.5	13.7	11.7	9.8	8.4	6.1	4.8	3.7	2.9	2.2	50.0	-1.	351.
10525	2	1	11.9	9.8	8.5	7.9	6.1	4.5	3.6	2.8	2.1	1.7	2732.0	0.	1420.
		2	12.7	10.4	9.0	8.3	6.4	4.7	3.7	2.9	2.2	1.8	1375.0	12.	2150.
		3	10.9	8.9	7.7	7.1	5.4	3.9	3.1	2.4	1.8	1.4	232.3	-4.	720.
		4	16.2	13.3	11.5	10.5	8.2	6.0	4.8	3.8	3.0	2.4	103.6	-1.	540.
		5	14.8	11.6	10.2	9.5	6.4	5.9	4.6	3.3	2.5	2.0	92.0	-12.	722.
10550	2	1	15.7	13.1	11.3	10.3	8.1	6.0	4.8	3.8	2.9	2.3	3813.0	9.	2660.
		2	12.0	10.1	8.7	8.0	6.2	4.6	3.7	2.9	2.2	1.8	472.1	-10.	988.
		3	16.8	14.1	12.0	11.1	8.7	6.3	5.1	4.0	3.0	2.4	173.2	9.	720.
		4	16.6	14.0	11.7	10.9	8.4	6.1	4.8	3.8	2.8	2.3	143.6	-18.	1000.
		5	14.9	12.7	10.5	10.2	7.7	5.7	4.5	3.5	2.7	2.2	93.9	38.	982.
10575	2	1	10.9	9.0	8.0	7.1	5.5	4.1	3.3	2.6	2.0	1.5	498.6	-4.	782.
		2	17.2	14.4	12.5	11.3	8.8	6.4	5.2	4.0	3.1	2.4	163.7	11.	771.
		3	18.1	15.2	13.1	12.0	9.3	6.8	5.4	4.2	3.2	2.6	130.6	-7.	1220.
		4	15.9	13.6	11.6	10.8	8.3	6.1	4.8	3.7	2.8	2.3	69.0	23.	1083.
		5	18.3	15.8	13.0	12.1	9.2	6.5	5.3	4.0	3.0	2.5	46.6	-32.	1096.
10600	2	1	16.4	13.8	11.9	10.7	8.3	6.1	4.9	3.8	2.9	2.3	413.0	18.	762.
		2	20.5	17.1	14.7	13.4	10.5	7.7	6.2	4.8	3.7	3.0	241.7	-28.	1339.
		3	19.1	16.0	13.7	12.8	9.8	7.3	5.8	4.5	3.4	2.8	126.7	42.	1400.
		4	21.2	17.5	14.9	13.9	10.6	7.7	6.1	4.8	3.6	2.8	72.1	-34.	1331.
		5	13.5	10.7	8.7	8.5	6.0	4.2	3.2	2.5	1.8	1.3	49.5	18.	1372.
10625	2	1	24.4	20.2	17.8	16.0	12.6	9.3	7.5	5.9	4.5	3.6	977.3	-30.	1278.
		2	25.0	20.8	18.4	16.5	13.1	9.7	7.8	6.1	4.7	3.8	331.5	47.	1301.
		3	26.3	21.6	19.0	16.9	13.4	9.9	8.0	6.2	4.7	3.8	167.4	-38.	1310.
		4	18.5	14.8	12.9	11.1	8.7	6.3	4.9	3.8	2.8	2.2	95.3	16.	1247.
		5	51.3	42.8	38.1	34.0	27.2	20.5	16.7	13.1	10.1	8.2	39.2	-41.	768.
10650	2	1	22.0	18.7	16.3	14.8	12.7	8.7	7.0	5.5	4.2	3.4	876.7	40.	1376.
		2	27.7	23.3	20.4	18.5	14.5	10.8	8.7	6.8	5.2	4.2	283.6	-46.	1335.
		3	22.2	18.6	16.1	14.4	11.3	8.2	6.5	5.0	3.8	3.0	143.2	-10.	1340.

		4	55.8	47.8	42.4	38.4	30.7	23.0	18.7	14.9	11.4	9.3	49.6	-7.	779.
		5	75.9	65.4	58.6	53.0	43.1	32.9	27.4	21.8	17.2	14.2	39.4	42.	927.
10675	2	1	24.2	20.1	17.9	16.2	12.7	9.5	7.7	6.0	4.7	3.7	983.7	-44.	1816.
		2	23.1	18.9	16.7	15.0	11.7	8.6	6.9	5.3	4.1	3.2	265.3	-17.	1470.
		3	55.9	47.0	42.0	38.5	31.0	23.7	19.4	15.2	11.9	9.4	84.4	-1.	933.
		4	80.7	68.3	61.3	55.9	44.8	34.0	27.6	22.2	17.4	14.6	55.0	43.	1015.
		5	65.0	55.0	49.8	44.7	36.2	27.8	22.8	18.3	13.9	11.9	76.3	4.	2114.
10700	2	1	24.4	20.4	17.9	15.9	12.6	9.3	7.5	5.8	4.5	3.6	784.9	-37.	1449.
		2	56.5	47.8	42.4	38.5	30.8	23.2	19.0	15.0	11.6	9.4	192.7	5.	1067.
		3	83.5	71.6	64.0	58.6	47.7	36.6	30.2	24.1	19.0	15.7	104.2	48.	1150.
		4	67.8	58.1	51.6	47.3	38.3	29.2	24.1	19.4	15.3	12.4	132.5	1.	2440.
10725	2	1	49.3	41.5	37.1	33.7	26.9	20.3	16.5	13.1	10.2	8.2	433.9	-39.	1238.
		2	86.5	74.0	66.0	60.5	49.0	37.7	31.0	24.8	19.6	16.1	130.3	43.	1115.
		3	70.2	59.5	53.6	49.2	39.7	30.4	24.9	19.9	15.8	12.9	149.0	4.	2540.
10750	2	1	77.5	65.9	59.3	54.5	44.1	33.8	27.8	22.3	17.6	14.4	280.7	44.	970.
		2	71.0	59.9	54.2	49.6	40.2	30.8	25.3	20.3	16.0	13.0	165.1	5.	1720.
10775	2	1	78.2	66.9	59.9	55.4	44.6	34.3	28.2	22.6	17.7	14.5	449.9	-7.	1086.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 82W.IND
DATA FILE : 82W.DAT

LINE NO. : 824

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	8.0	6.3	5.8	5.1	4.0	2.9	2.4	1.8	1.4	1.1	373.3	-55.	154.
		2	9.2	7.4	6.8	6.0	4.7	3.4	2.7	2.1	1.6	1.3	84.8	19.	105.
		3	8.2	6.6	6.0	5.2	4.1	3.2	2.7	1.9	1.3	1.4	35.0	25.	86.
		4	9.2	7.6	7.1	6.0	5.0	3.2	2.3	2.2	1.9	.9	18.5	-9.	76.
		5	8.2	6.7	6.2	4.9	4.1	3.2	2.8	1.6	1.7	1.0	17.7	3.	109.
10350	2	1	6.1	5.4	4.4	3.6	3.0	2.1	1.9	1.5	1.1	.9	233.9	13.	83.
		2	8.0	6.7	5.7	5.1	4.0	3.1	2.4	1.8	1.5	1.2	78.7	20.	84.
		3	9.0	7.7	6.5	5.9	4.6	3.1	2.6	2.1	1.7	1.7	37.3	-27.	79.
		4	8.3	7.3	6.0	5.6	4.6	3.7	2.8	2.2	1.5	.8	30.9	22.	110.
		5	7.8	6.9	5.3	5.1	4.1	2.9	2.4	1.9	1.4	1.1	25.1	6.	134.
10375	2	1	7.5	5.7	5.5	4.8	3.7	2.7	2.2	1.8	1.3	1.0	181.5	20.	98.
		2	9.6	7.8	7.1	6.3	5.0	3.7	3.0	2.4	1.8	1.4	61.4	-28.	100.
		3	8.0	6.5	5.8	5.0	3.8	2.7	2.1	1.3	.8	.9	40.8	21.	132.
		4	8.3	7.1	6.3	5.5	4.6	3.5	2.7	2.5	2.1	1.1	29.2	8.	158.
		5	8.4	6.9	5.5	4.2	4.1	2.9	2.3	1.8	1.5	1.1	17.1	1.	138.
10400	2	1	8.5	6.5	6.0	5.4	4.2	3.1	2.6	1.9	1.5	1.3	340.9	-35.	111.
		2	8.4	6.6	6.0	5.4	4.3	3.1	2.5	1.9	1.5	1.1	153.4	23.	150.
		3	8.7	6.7	6.2	5.5	4.3	3.1	2.5	1.9	1.5	1.3	93.3	6.	182.
		4	8.0	6.2	6.1	5.0	4.3	3.0	2.5	1.9	1.5	1.1	45.8	1.	149.
		5	16.3	13.0	10.8	9.7	8.1	5.8	5.0	3.7	2.8	2.3	44.1	-27.	216.
10425	2	1	7.5	6.2	5.4	4.8	3.7	2.7	2.2	1.7	1.3	1.0	419.8	22.	156.
		2	8.6	7.0	6.2	5.5	4.3	3.2	2.5	2.0	1.5	1.2	176.1	7.	197.
		3	6.8	6.3	5.7	5.1	4.2	3.1	2.5	1.9	1.5	1.2	66.0	-1.	147.
		4	16.0	12.9	11.4	10.5	8.1	6.1	4.7	3.7	2.8	2.2	55.2	-26.	206.
		5	8.7	6.8	6.3	5.0	4.1	2.6	2.6	2.0	1.4	1.2	41.9	13.	235.
10450	2	1	8.8	7.1	6.3	5.5	4.4	3.2	2.6	2.0	1.5	1.2	642.6	0.	221.

		2	8.9	7.2	6.6	5.8	4.7	3.4	2.8	2.2	1.7	1.4	142.0	-11.	146.
		3	15.6	12.6	11.4	10.0	8.0	6.0	4.7	3.7	2.8	2.3	98.8	-17.	204.
		4	8.0	6.1	5.9	4.7	3.9	2.8	2.2	1.7	1.3	1.0	57.6	8.	198.
		5	3.7	2.3	2.8	1.5	1.5	1.2	.6	.4	.4	.3	43.4	1.	224.
10475	2	1	12.6	10.8	9.3	8.7	6.8	5.2	4.2	3.4	2.6	2.1	1579.0	-16.	610.
		2	18.3	15.5	13.5	12.4	9.8	7.3	5.9	4.7	3.6	2.9	454.9	-18.	529.
		3	11.9	10.3	8.8	8.1	6.4	4.7	3.8	3.0	2.3	1.9	202.9	9.	470.
		4	5.4	4.7	3.9	3.5	2.7	1.9	1.6	1.2	.9	.7	92.0	1.	356.
		5	6.7	5.9	4.6	3.9	2.6	2.0	2.2	.9	1.1	.5	44.5	19.	258.
10500	2	1	23.0	18.8	17.0	15.4	12.2	9.2	7.5	5.9	4.6	3.8	2965.0	-31.	960.
		2	17.8	14.5	13.1	11.9	9.4	7.1	5.8	4.5	3.6	2.9	914.0	3.	896.
		3	9.8	7.7	7.2	6.5	5.1	3.8	3.1	2.5	1.9	1.5	300.7	2.	580.
		4	10.8	8.4	7.9	7.1	5.5	4.0	3.2	2.4	2.0	1.6	127.5	15.	410.
		5	7.7	6.0	5.2	4.3	3.2	2.5	1.9	1.6	.8	.7	45.8	-21.	224.
10525	2	1	21.3	17.5	15.6	14.4	11.2	8.5	6.9	5.4	4.3	3.4	3378.0	-5.	2300.
		2	12.9	10.8	9.7	9.0	7.1	5.3	4.3	3.4	2.6	2.1	627.1	-1.	1284.
		3	13.9	11.5	10.2	9.7	7.5	5.6	4.6	3.6	2.8	2.2	221.5	16.	900.
		4	10.2	8.5	7.3	7.0	5.3	4.0	3.2	2.4	1.8	1.4	64.4	-23.	439.
		5	9.1	7.4	5.9	5.8	4.4	3.2	2.5	1.9	1.3	1.0	38.1	18.	390.
10550	2	1	19.2	15.7	14.0	12.8	10.1	7.5	6.1	4.8	3.7	3.1	3028.0	-16.	2160.
		2	22.4	18.6	16.6	15.1	12.0	9.0	7.3	5.8	4.5	3.7	750.6	17.	1606.
		3	18.3	15.2	13.7	12.4	9.8	7.3	5.9	4.6	3.5	2.9	177.2	-25.	750.
		4	17.4	14.3	12.9	11.8	9.2	6.9	5.7	4.5	3.5	2.9	91.1	15.	650.
		5	17.9	14.5	12.9	11.5	9.4	7.0	5.7	4.4	3.4	2.8	79.7	-14.	852.
10575	2	1	21.9	18.0	16.0	14.6	11.4	8.5	6.9	5.4	4.2	3.4	2784.0	-1.	2030.
		2	18.2	15.2	13.5	12.3	9.7	7.2	5.8	4.6	3.5	2.8	502.6	-33.	1101.
		3	16.4	13.6	12.0	10.9	8.5	6.3	5.1	4.0	3.1	2.5	211.7	22.	920.
		4	17.3	14.2	12.6	11.5	9.0	6.7	5.4	4.2	3.3	2.6	167.4	-13.	1220.
		5	23.7	19.5	16.8	15.2	11.5	8.4	6.7	5.1	3.9	3.1	131.9	8.	1440.
10600	2	1	12.6	10.3	9.0	8.1	6.4	4.7	3.8	2.9	2.2	1.8	1545.0	-34.	1180.
		2	13.9	11.5	10.0	9.0	7.1	5.3	4.2	3.3	2.5	2.0	462.9	22.	1063.
		3	15.3	12.9	11.1	10.1	7.9	5.8	4.7	3.6	2.8	2.2	323.2	-12.	1480.
		4	22.5	18.3	15.8	14.2	10.9	7.9	6.3	4.9	3.6	2.9	230.4	7.	1760.
		5	27.0	22.4	19.5	17.7	14.1	10.5	8.5	6.6	5.1	4.1	130.9	-6.	1500.
10625	2	1	12.3	9.6	8.8	7.8	6.1	4.4	3.6	2.7	2.1	1.6	1333.0	11.	870.
		2	15.0	11.9	10.8	9.7	7.5	5.5	4.5	3.5	2.7	2.1	699.6	-18.	1372.
		3	22.5	18.0	16.0	14.2	11.0	7.9	6.3	4.8	3.7	3.0	434.2	14.	1700.
		4	27.3	22.4	20.1	18.4	14.2	10.5	8.7	6.7	5.2	4.1	225.2	-5.	1470.
		5	39.0	33.1	28.8	26.3	21.2	16.1	12.8	10.3	7.9	6.8	125.2	-2.	1220.
10650	2	1	16.6	13.4	12.1	10.9	8.5	6.3	5.1	3.9	3.0	2.4	1702.0	-28.	1270.
		2	25.2	20.4	17.9	16.2	12.5	9.1	7.3	5.6	4.3	3.4	740.0	15.	1659.
		3	30.7	25.5	22.7	20.7	16.3	12.2	9.9	7.8	6.0	4.9	326.2	-6.	1460.

		4	42.4	35.6	31.8	29.1	23.1	17.4	14.1	11.2	8.7	7.1	146.1	-3.	1090.
		5	50.0	42.1	37.8	34.6	27.5	20.9	17.1	13.6	10.6	8.7	103.2	-12.	1150.
10675	2	1	23.2	19.0	16.7	15.0	11.7	8.6	6.9	5.3	4.1	3.2	2025.0	0.	1510.
		2	33.3	27.9	24.8	22.4	17.8	13.3	10.8	8.5	6.6	5.3	650.8	-20.	1459.
		3	46.1	39.0	34.8	31.7	25.3	19.1	15.6	12.4	9.7	7.9	234.9	12.	1050.
		4	52.7	44.7	40.0	36.4	29.3	22.2	18.2	14.5	11.4	9.3	152.6	-17.	1140.
		5	68.7	58.1	51.9	47.2	37.8	28.7	23.4	18.7	14.8	12.0	46.6	7.	522.
10700	2	1	33.7	28.2	24.9	22.6	17.8	13.4	10.8	8.5	6.6	5.4	1877.0	-31.	1370.
		2	49.9	42.3	37.6	34.3	27.4	20.8	16.9	13.5	10.5	8.6	451.3	12.	988.
		3	54.7	46.5	41.5	37.9	30.5	23.3	19.1	15.2	11.9	9.8	264.9	-20.	1150.
		4	72.4	60.9	54.2	49.5	39.8	30.3	24.8	19.7	15.4	12.7	77.3	-4.	564.
10725	2	1	53.6	45.7	40.3	37.0	29.5	22.4	18.3	14.5	11.4	9.3	483.6	-6.	1168.
		2	58.9	50.4	44.5	41.0	32.8	25.0	20.4	16.3	12.7	10.4	181.1	-22.	1312.
		3	76.3	64.8	57.2	52.6	42.2	32.1	26.4	20.9	16.3	13.5	45.1	7.	652.
10750	2	1	42.4	36.2	32.1	29.4	23.6	17.9	14.6	11.6	9.1	7.4	614.7	-24.	1608.
		2	68.1	57.7	51.0	46.7	37.6	28.6	23.4	18.6	14.6	11.9	104.0	7.	816.
10775	2	1	59.7	50.6	45.3	41.5	33.3	25.4	20.9	16.6	13.0	8.7	286.8	13.	1000.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 81W.IND
DATA FILE : 81W.DAT

LINE NO. : 814

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	5.9	4.6	3.9	3.6	2.7	2.0	1.6	1.2	.9	.7	361.9	-27.	113.
		2	6.4	4.9	4.3	3.9	3.0	2.1	1.7	1.3	1.0	.8	113.6	29.	106.
		3	6.6	5.3	4.5	4.1	3.2	2.3	1.9	1.4	.7	.5	54.0	-17.	101.
		4	7.7	6.4	5.5	5.2	4.0	3.0	2.4	1.8	2.0	1.7	26.8	-5.	83.
		5	7.9	6.4	5.7	5.4	3.9	3.0	2.3	2.0	1.5	1.3	15.2	-8.	71.
10350	2	1	6.6	5.3	4.6	4.2	3.2	2.4	2.0	1.5	1.1	.9	288.5	22.	100.
		2	8.9	6.8	5.9	5.3	4.0	2.9	2.3	1.8	1.4	1.0	95.2	-21.	100.
		3	7.5	5.9	5.4	4.7	3.6	2.6	1.7	.9	.7	.4	41.8	-9.	87.
		4	7.6	5.9	5.5	4.9	3.8	3.2	3.0	3.1	2.3	2.2	19.7	-1.	68.
		5	7.3	5.4	5.4	4.0	3.5	2.9	2.3	2.0	1.4	1.2	19.8	17.	103.
10375	2	1	7.6	6.1	5.2	4.6	3.6	2.6	2.1	1.6	1.2	.9	308.6	-23.	129.
		2	8.6	6.8	5.9	5.2	4.1	3.0	2.5	1.9	1.5	1.1	84.9	3.	107.
		3	7.6	6.3	5.6	5.1	4.0	2.9	2.4	2.0	1.6	1.3	35.0	-9.	87.
		4	6.1	4.6	4.1	3.7	2.7	1.8	1.1	.6	.2	.0	27.5	2.	115.
		5	5.6	5.1	4.8	2.0	3.6	3.0	1.7	1.9	2.1	1.5	21.9	15.	137.
10400	2	1	7.4	5.9	5.1	4.5	3.5	2.6	2.1	1.6	1.2	1.0	462.4	-3.	140.
		2	7.7	6.2	5.3	4.8	3.8	2.7	2.2	1.7	1.3	1.1	114.8	-10.	104.
		3	6.0	4.8	4.1	4.0	3.0	2.2	1.8	1.4	1.0	.8	78.8	16.	142.
		4	6.8	5.0	4.1	4.2	3.0	2.2	1.7	1.3	1.0	.8	50.2	-1.	152.
		5	6.1	4.3	4.3	4.7	5.3	2.0	2.5	1.3	1.3	.9	41.7	-6.	189.
10425	2	1	6.9	5.5	4.8	4.4	3.3	2.4	1.9	1.5	1.2	.9	402.3	-11.	143.
		2	6.4	5.1	4.5	4.0	3.1	2.3	1.8	1.4	1.1	.9	150.3	6.	160.
		3	6.4	5.1	4.5	4.0	3.0	2.2	1.8	1.4	1.0	.7	88.4	3.	188.
		4	8.0	6.4	5.8	5.0	4.0	3.0	2.2	1.7	1.4	1.2	57.0	-4.	203.
		5	10.0	8.0	7.2	6.0	5.0	3.7	2.8	2.2	1.7	1.3	42.3	-9.	226.
10450	2	1	5.2	3.9	3.4	3.3	2.4	1.8	1.4	1.2	.8	.0	454.7	4.	144.

		2	7.2	5.4	4.8	4.6	3.2	2.4	1.9	1.5	1.2	.9	200.1	9.	190.
		3	8.8	6.9	6.1	5.8	4.3	3.2	2.6	2.0	1.5	1.2	122.7	-6.	230.
		4	11.5	8.9	8.0	7.3	5.6	4.1	3.4	2.6	2.0	1.6	76.0	-10.	241.
		5	7.0	5.1	4.7	4.1	3.5	2.1	1.7	1.7	.8	.3	49.6	5.	236.
10475	2	1	7.7	6.3	5.3	4.6	3.6	2.6	2.0	1.6	1.2	1.0	995.3	-3.	318.
		2	10.8	9.0	7.9	6.9	5.5	4.1	3.2	2.6	1.9	1.6	427.1	-4.	410.
		3	14.2	11.9	10.6	9.3	7.4	5.6	4.4	3.5	2.7	2.2	208.4	-10.	390.
		4	10.9	9.1	8.2	7.1	5.7	4.3	3.4	2.7	2.1	1.7	113.2	0.	360.
		5	9.8	7.8	7.3	6.1	5.0	3.6	3.0	2.3	1.7	1.4	65.4	-5.	314.
10500	2	1	9.8	8.4	7.0	6.2	4.9	3.6	2.9	2.2	1.7	1.4	1516.0	-3.	620.
		2	15.6	13.4	11.4	10.2	8.1	6.0	4.8	3.8	2.9	2.4	648.7	-28.	804.
		3	13.1	11.3	9.7	8.7	7.0	5.2	4.2	3.3	2.5	2.0	294.6	28.	720.
		4	14.4	12.2	10.4	9.3	7.5	5.5	4.4	3.5	2.7	2.2	130.6	-17.	530.
		5	12.6	11.2	9.3	8.4	6.7	5.0	4.0	3.1	2.3	1.9	89.0	-2.	551.
10525	2	1	13.7	11.1	9.7	8.7	6.9	5.0	4.1	3.2	2.4	2.0	1507.0	-23.	690.
		2	12.8	10.6	9.3	8.4	6.7	4.9	4.0	3.1	2.4	2.0	613.6	14.	850.
		3	14.2	11.7	10.2	9.2	7.3	5.3	4.4	3.4	2.6	2.1	284.8	0.	780.
		4	13.4	11.1	9.7	8.8	7.0	5.1	4.2	3.3	2.5	2.1	170.6	-8.	780.
		5	11.6	10.0	8.9	8.1	6.0	4.4	3.6	2.8	2.1	2.1	76.8	11.	532.
10550	2	1	10.4	8.4	7.4	6.7	5.3	3.9	3.2	2.5	1.9	1.5	1376.0	3.	900.
		2	13.6	11.1	9.7	8.8	6.9	5.1	4.1	3.2	2.5	2.0	514.8	-3.	1010.
		3	12.5	10.2	9.0	8.2	6.5	4.8	3.9	3.1	2.4	1.9	286.8	-3.	1120.
		4	11.7	9.6	8.5	7.7	5.9	4.4	3.4	2.6	2.1	1.7	122.6	11.	800.
		5	12.8	10.4	8.3	7.2	5.9	4.0	3.9	2.7	1.9	1.8	124.3	-15.	1210.
10575	2	1	11.9	9.4	8.2	7.6	5.8	4.2	3.4	2.6	2.0	1.6	820.4	-25.	696.
		2	10.9	8.8	7.7	7.2	5.5	4.1	3.3	2.5	2.0	1.6	425.3	-1.	1082.
		3	10.2	8.1	7.1	6.8	5.1	3.8	3.0	2.3	1.8	1.4	170.9	13.	860.
		4	11.0	8.7	7.6	7.2	5.3	3.8	3.0	2.2	1.7	1.3	165.1	-12.	1400.
		5	17.6	14.0	12.3	11.1	8.4	6.1	4.8	3.6	2.8	2.2	126.2	-7.	1600.
10600	2	1	8.5	7.0	6.0	5.5	4.1	3.0	2.4	1.8	1.4	1.1	1067.0	-1.	770.
		2	8.3	7.0	5.8	5.4	4.1	3.0	2.3	1.8	1.4	1.1	391.1	6.	856.
		3	8.7	7.4	6.1	5.6	4.2	3.0	2.3	1.8	1.3	1.0	326.3	-10.	1420.
		4	15.8	12.9	10.9	9.9	7.4	5.3	4.1	3.1	2.3	1.8	242.2	-2.	1760.
		5	35.7	29.9	26.2	23.3	18.8	13.9	11.2	8.8	7.0	5.6	144.5	-50.	1580.
10625	2	1	6.0	5.1	4.1	3.6	2.8	2.0	1.6	1.2	.9	.7	735.6	4.	563.
		2	7.3	6.0	5.0	4.4	3.4	2.4	1.8	1.4	1.0	.8	510.3	-13.	1172.
		3	15.2	12.6	10.6	9.5	7.2	5.1	3.9	3.0	2.2	1.7	368.9	-2.	1690.
		4	34.7	29.4	25.9	23.4	18.6	14.0	11.3	8.9	6.9	5.6	178.6	-49.	1360.
		5	66.8	56.9	50.7	46.2	37.0	28.2	23.1	18.4	14.4	11.8	88.1	59.	1012.
10650	2	1	7.1	5.7	4.9	4.3	3.2	2.3	1.8	1.4	1.0	.8	946.3	-21.	724.
		2	15.0	12.1	10.4	9.2	6.9	4.9	3.8	2.9	2.1	1.6	509.4	-5.	1170.
		3	34.5	29.0	25.7	23.1	18.4	13.8	11.1	8.8	6.8	5.5	266.1	-46.	1220.

		4	67.4	57.3	51.0	46.3	37.2	28.3	23.2	18.5	14.5	11.9	110.7	61.	840.
		5	73.5	60.7	54.9	48.4	39.9	30.9	26.3	20.0	14.7	13.0	34.0	-4.	390.
10675	2	1	18.2	14.6	12.6	11.3	8.6	6.2	4.9	3.7	2.8	2.2	1409.0	-9.	1000.
		2	41.4	34.7	30.6	28.0	22.1	16.6	13.5	10.6	8.2	6.7	430.0	-35.	920.
		3	70.7	59.8	53.4	48.8	39.1	29.8	24.4	19.5	15.2	12.5	165.0	53.	700.
		4	75.9	64.1	57.3	52.3	42.0	32.2	26.5	21.3	16.8	14.0	47.2	-6.	336.
		5	59.2	49.8	44.4	40.6	32.4	24.6	20.1	16.0	12.6	10.2	53.8	-6.	576.
10700	2	1	47.1	39.6	35.0	31.6	25.2	18.9	15.3	12.1	9.4	7.6	1163.0	-40.	910.
		2	75.9	64.3	57.3	52.3	42.0	32.0	26.2	20.9	16.3	13.4	304.4	44.	716.
		3	81.0	68.6	61.3	56.0	45.1	34.6	28.4	22.8	17.9	14.8	74.6	-10.	350.
		4	65.8	55.3	49.5	44.9	35.9	27.3	22.3	17.7	13.8	11.3	76.7	3.	602.
10725	2	1	70.6	60.0	53.8	49.1	39.6	30.3	24.9	19.9	15.6	12.8	716.9	42.	1125.
		2	88.8	75.6	67.7	61.9	50.1	38.4	31.6	25.2	20.0	16.4	100.6	1.	473.
		3	69.6	59.2	52.9	48.2	38.8	29.4	24.2	19.2	15.2	12.5	89.3	-19.	839.
10750	2	1	87.4	74.8	67.0	61.5	49.7	38.1	31.2	25.2	19.8	16.3	143.7	-21.	451.
		2	75.1	63.7	56.9	52.0	42.0	32.1	26.3	21.1	16.6	13.7	91.8	-4.	864.
10775	2	1	77.8	66.0	58.6	53.5	43.0	32.7	26.8	21.4	16.7	11.6	220.6	-4.	860.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 80W.IND
DATA FILE : 80W.DAT

LINE NO. : 804

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	5.3	4.2	3.6	3.2	2.4	1.7	1.4	1.1	.8	.6	380.9	-8.	127.
		2	6.6	5.3	4.6	4.2	3.2	2.4	1.9	1.5	1.1	.9	124.1	2.	124.
		3	6.2	5.0	4.3	3.9	3.1	2.2	1.8	1.4	1.1	.9	53.4	-29.	106.
		4	6.0	4.9	4.1	3.8	2.9	2.2	1.8	1.3	1.0	.8	32.2	54.	107.
		5	5.7	4.6	3.7	3.5	2.7	2.0	1.6	1.2	.9	.7	17.2	-10.	86.
10350	2	1	5.1	3.9	3.3	3.1	2.3	1.6	1.3	1.0	.7	.6	453.9	-5.	146.
		2	6.5	5.2	4.4	4.1	3.1	2.3	1.8	1.4	1.1	.9	119.7	-23.	116.
		3	5.9	4.7	4.1	3.9	2.9	2.2	1.7	1.3	.9	.6	61.7	49.	119.
		4	5.4	4.1	3.6	3.4	2.4	1.8	1.4	1.2	.9	.8	28.7	-7.	92.
		5	5.6	4.2	3.6	3.5	2.6	2.0	1.5	1.2	.9	.7	19.1	-25.	92.
10375	2	1	5.2	3.8	3.2	3.1	2.3	1.6	1.3	1.0	.7	.6	466.6	-26.	138.
		2	5.9	4.5	4.0	3.7	2.8	2.0	1.6	1.2	.9	.7	147.3	48.	131.
		3	5.9	4.5	3.9	3.7	2.7	1.9	1.5	1.1	.8	.7	57.6	0.	102.
		4	6.1	4.9	4.3	4.2	3.3	2.5	2.1	1.8	1.6	1.2	31.2	-31.	92.
		5	4.4	3.2	2.3	2.8	1.8	1.1	.8	.4	.2	.0	25.0	-10.	111.
10400	2	1	4.2	3.3	2.7	2.4	1.8	1.3	1.0	.7	.5	.4	422.7	41.	168.
		2	5.7	4.6	4.0	3.6	2.8	2.1	1.7	1.3	1.0	.8	93.1	-7.	111.
		3	6.3	5.1	4.3	4.1	3.1	2.3	1.9	1.4	1.1	.9	46.9	-19.	111.
		4	4.4	3.3	2.6	3.4	1.6	.6	.4	.1	-.1	-.5	30.0	-8.	119.
		5	5.6	4.7	3.7	3.6	2.8	2.9	1.6	1.7	2.3	1.7	20.6	4.	122.
10425	2	1	5.7	4.1	3.8	3.4	2.0	1.8	1.4	1.1	.8	.6	375.2	-13.	125.
		2	6.8	5.2	4.6	4.3	3.2	2.3	1.8	1.4	1.1	.8	123.1	-20.	123.
		3	5.9	4.5	4.0	3.8	2.8	2.1	1.7	1.2	.7	.5	62.5	-7.	124.
		4	5.0	3.7	3.1	3.1	2.1	1.5	1.2	1.0	1.1	.9	35.5	7.	118.
		5	4.8	3.4	2.8	3.2	2.1	1.3	1.1	.8	.6	.5	24.9	-11.	124.
10450	2	1	5.2	4.2	3.4	3.0	2.3	1.6	1.3	1.0	.7	.6	503.0	-35.	153.

		2	5.3	4.3	3.7	3.3	2.5	1.8	1.5	1.1	.8	.6	170.2	-8.	156.
		3	5.3	4.3	3.7	3.3	2.5	1.8	1.4	1.1	.8	.6	78.6	7.	143.
		4	5.5	4.5	4.1	3.6	2.8	2.1	1.7	1.3	1.1	1.0	49.7	-6.	151.
		5	5.3	3.9	3.4	2.9	2.2	1.9	1.5	1.3	.6	.5	41.3	-11.	189.
10475	2	1	4.5	3.7	2.9	3.0	2.0	1.4	1.1	.9	.6	.5	578.7	-11.	182.
		2	5.7	4.7	3.9	3.6	2.8	2.0	1.6	1.2	.9	.7	170.3	8.	160.
		3	6.1	5.1	4.4	3.9	3.1	2.3	1.8	1.4	1.0	.8	92.4	-6.	174.
		4	6.6	5.5	4.7	4.2	3.4	2.5	2.0	1.6	1.2	.9	69.3	-11.	218.
		5	5.9	5.3	4.6	3.5	2.7	2.1	1.7	1.2	.9	.8	62.2	4.	293.
10500	2	1	5.7	4.6	3.8	3.4	2.7	1.9	1.5	1.2	.9	.7	649.6	1.	192.
		2	7.5	6.2	5.3	4.8	3.8	2.8	2.2	1.7	1.3	1.0	253.4	-9.	225.
		3	8.3	7.1	6.0	5.4	4.3	3.1	2.5	1.9	1.3	1.0	161.7	-3.	286.
		4	8.6	7.2	6.2	5.6	4.5	3.3	2.7	2.2	1.8	1.5	129.1	-2.	382.
		5	7.4	6.3	5.4	4.8	3.7	2.7	2.2	1.7	1.3	1.0	99.8	-8.	443.
10525	2	1	7.6	5.8	5.1	4.6	3.5	2.6	2.1	1.6	1.2	1.0	534.2	-9.	304.
		2	10.2	8.1	7.2	6.5	5.0	3.7	3.0	2.3	1.8	1.4	257.1	-16.	440.
		3	11.5	9.1	8.2	7.3	5.7	4.2	3.4	2.6	2.0	1.6	184.8	12.	630.
		4	10.9	8.5	7.7	6.8	5.3	3.9	3.1	2.4	1.9	1.5	129.2	-5.	730.
		5	10.3	8.0	7.2	6.4	4.8	3.6	2.8	2.2	1.6	1.3	67.0	1.	573.
10550	2	1	8.2	6.5	5.5	5.0	3.8	2.7	2.2	1.8	1.3	1.0	760.6	-16.	379.
		2	10.6	8.6	7.4	6.8	5.3	3.9	3.2	2.5	1.9	1.6	455.4	8.	680.
		3	9.8	7.9	6.9	6.2	4.8	3.6	2.8	2.2	1.6	1.3	299.4	-6.	890.
		4	9.8	7.9	6.9	6.3	4.9	3.6	2.9	2.2	1.8	1.5	148.2	6.	730.
		5	-1.2	-1.4	-1.5	-1.3	-1.4	-1.1	-1.1	-1.0	-.5	-.8	71.5	-23.	534.
10575	2	1	9.1	7.0	6.1	5.8	4.3	3.1	2.5	1.9	1.5	1.2	883.7	-1.	504.
		2	9.3	7.3	6.3	5.9	4.5	3.2	2.6	2.0	1.5	1.2	498.3	-8.	853.
		3	9.1	7.2	6.3	5.9	4.4	3.3	2.6	2.0	1.4	1.1	233.1	6.	790.
		4	-.5	-1.1	-1.2	-1.0	-1.3	-1.3	-1.2	-1.0	-.5	-.5	104.9	-27.	590.
		5	12.2	9.2	7.9	6.7	5.0	3.3	2.5	1.8	1.2	.8	136.7	22.	1170.
10600	2	1	7.3	5.5	4.8	4.3	3.2	2.3	1.8	1.4	1.1	.8	984.0	-11.	657.
		2	8.0	6.3	5.6	5.0	3.8	2.7	2.2	1.6	1.3	1.0	391.2	4.	784.
		3	-1.0	-1.2	-1.2	-1.2	-1.2	-1.1	-1.0	-.8	-.5	-.4	158.8	-25.	630.
		4	11.6	9.0	7.6	6.4	4.7	3.1	2.2	1.6	.9	.5	191.9	14.	1280.
		5	62.3	52.9	47.5	43.0	34.5	26.2	21.5	17.1	13.5	11.0	93.9	8.	940.
10625	2	1	7.2	5.3	4.7	4.0	3.0	2.2	1.7	1.2	.9	.7	840.6	4.	694.
		2	-.7	-1.3	-1.0	-1.3	-1.2	-1.1	-1.0	-.9	-.7	-.7	261.9	-26.	649.
		3	11.0	8.1	7.2	5.8	4.2	2.8	2.0	1.4	.9	.6	283.0	15.	1400.
		4	62.5	52.6	47.3	42.7	34.5	26.3	21.5	17.2	13.5	11.0	129.7	10.	1070.
		5	68.8	57.8	52.7	47.3	38.5	28.9	24.5	19.6	15.5	12.6	45.0	-13.	558.
10650	2	1	-.1	-.5	-.9	-.6	-.9	-.8	-.8	-.7	-.5	-.5	640.8	-30.	428.
		2	10.9	8.5	6.8	6.2	4.2	2.7	2.0	1.4	.9	.6	555.1	12.	1112.
		3	62.5	53.0	47.0	43.2	34.6	26.3	21.5	17.1	13.4	11.0	237.0	16.	940.

		4	68.5	58.1	51.7	47.5	38.2	29.1	24.0	19.1	15.1	12.4	77.9	-19.	520.
		5	75.7	64.4	57.2	52.3	42.3	32.6	26.5	21.4	16.7	13.9	50.7	20.	507.
10675	2	1	13.6	10.8	8.9	7.8	5.7	3.9	2.9	2.2	1.5	1.1	862.6	8.	732.
		2	65.9	55.9	49.7	45.3	36.4	27.7	22.7	18.1	14.2	11.6	295.0	16.	751.
		3	68.9	58.5	52.2	47.7	38.5	29.5	24.2	19.4	15.3	12.6	90.0	-18.	457.
		4	76.5	65.1	58.0	53.1	42.9	32.8	27.0	21.5	16.8	13.7	55.7	17.	472.
		5	52.0	43.5	38.3	35.1	27.9	21.1	17.5	13.9	11.0	9.0	59.0	1.	750.
10700	2	1	72.1	61.0	54.7	50.0	40.1	30.6	24.8	19.7	15.5	12.6	453.2	13.	569.
		2	72.2	61.1	54.8	50.2	40.3	30.7	25.3	20.2	15.9	13.0	106.7	-23.	402.
		3	76.9	65.6	58.7	54.1	43.5	33.3	27.4	21.9	17.2	14.1	60.2	14.	452.
		4	52.7	45.0	40.0	36.1	28.2	21.0	17.2	13.8	10.9	9.1	58.2	6.	730.
10725	2	1	81.5	69.3	62.1	57.0	46.0	35.2	29.0	23.2	18.3	15.1	361.2	-27.	515.
		2	87.9	74.6	67.1	61.3	49.7	38.1	31.6	25.1	19.8	16.3	145.0	15.	620.
		3	59.8	50.0	45.0	40.5	32.7	24.7	20.2	16.0	12.5	10.2	127.0	-3.	1080.
10750	2	1	83.5	71.1	63.2	57.9	46.6	35.5	29.3	23.5	18.5	13.3	209.7	-2.	658.
		2	64.5	54.7	48.4	44.2	35.4	26.7	21.8	17.3	13.4	9.0	110.3	0.	1039.
10775	2	1	68.8	57.5	51.1	46.3	36.9	27.8	22.7	18.0	14.1	8.3	113.0	2.	700.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 79W.IND
DATA FILE : 79W.DAT

LINE NO. : 794

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	4.7	3.8	3.0	2.7	2.0	1.4	1.1	.8	.6	.5	723.3	33.	212.
		2	5.6	4.7	3.9	3.6	2.8	2.0	1.5	1.2	.8	.6	151.8	-8.	134.
		3	4.9	4.2	3.4	3.0	2.3	1.7	1.4	1.2	.9	.8	76.2	33.	134.
		4	5.4	4.9	4.0	3.5	2.8	2.0	1.6	1.2	.9	.7	36.9	-50.	108.
		5	6.1	5.2	4.2	4.2	3.4	2.9	2.6	1.9	1.4	1.1	18.5	-64.	82.
10350	2	1	4.8	3.4	3.1	2.6	2.0	1.4	1.1	.8	.6	.5	503.8	13.	148.
		2	5.9	4.4	4.0	3.4	2.7	1.9	1.5	1.2	.9	.7	122.4	39.	108.
		3	5.9	4.4	4.1	3.5	2.8	2.0	1.6	1.2	.9	.7	63.7	-40.	112.
		4	5.6	4.1	3.8	3.2	2.5	1.7	1.3	1.0	.7	-1.4	28.3	-4.	83.
		5	4.6	3.2	3.2	2.5	2.1	1.5	1.2	.9	.7	.5	20.3	6.	89.
10375	2	1	4.6	3.4	2.9	2.8	2.1	1.5	1.2	1.0	.7	.6	524.5	58.	152.
		2	5.5	4.4	3.7	3.5	2.6	1.9	1.5	1.2	.9	.7	144.9	-54.	126.
		3	5.6	4.6	3.9	3.7	2.8	1.9	1.5	1.2	.7	.6	70.4	24.	122.
		4	4.6	3.7	3.0	3.0	2.2	1.7	1.4	1.0	1.1	.8	32.6	-13.	95.
		5	3.0	2.5	1.9	2.0	1.4	1.0	.8	.7	.6	.5	17.5	-9.	76.
10400	2	1	4.8	3.7	3.2	2.9	2.1	1.5	1.2	.9	.7	.5	646.8	-41.	185.
		2	5.5	4.3	3.7	3.5	2.6	1.9	1.5	1.1	.8	.7	131.5	29.	113.
		3	5.5	4.4	3.9	3.7	2.9	2.1	1.5	1.0	.6	.6	59.1	-8.	101.
		4	2.2	1.4	1.2	1.0	.4	.3	.4	.6	.8	.4	27.5	-18.	79.
		5	3.0	2.6	2.6	2.5	1.5	1.1	.9	.8	.5	.4	21.3	20.	91.
10425	2	1	5.1	3.6	3.4	2.8	2.1	1.4	1.1	.8	.6	.5	393.5	24.	112.
		2	5.1	3.7	3.6	3.1	2.4	1.7	1.4	1.0	.8	.6	104.9	-31.	90.
		3	4.4	3.1	2.9	2.6	1.9	1.3	1.0	.7	.5	.4	63.9	17.	109.
		4	4.4	1.7	2.8	2.8	2.0	1.6	1.1	.9	.7	.3	31.2	11.	89.
		5	4.1	2.5	2.2	2.1	1.4	1.0	.9	.7	.6	.4	26.1	24.	112.
10450	2	1	4.2	3.4	2.8	2.4	1.8	1.3	1.0	.8	.6	.5	629.2	-8.	205.

		2	4.2	3.4	2.9	2.5	2.0	1.4	1.1	.9	.7	.5	111.6	0.	109.
		3	4.3	3.4	3.1	2.6	2.1	1.5	1.1	.9	.6	.5	61.8	7.	121.
		4	4.5	3.6	3.5	2.9	2.3	1.5	1.2	1.0	.6	.5	39.8	24.	130.
		5	4.5	3.2	3.0	2.8	2.2	1.6	1.2	.9	.8	.6	34.9	-51.	171.
10475	2	1	4.5	3.5	3.0	2.6	1.8	1.3	1.0	.9	.6	.4	460.7	6.	149.
		2	5.3	4.3	3.6	3.2	2.5	1.8	1.4	1.1	.8	.7	135.0	13.	131.
		3	5.7	4.7	3.9	3.5	2.7	1.9	1.6	1.2	.8	.8	90.8	24.	175.
		4	5.8	4.9	4.1	3.7	2.9	2.1	1.7	1.3	1.0	1.0	64.7	-57.	209.
		5	8.5	7.2	6.2	5.4	4.4	3.2	2.6	2.1	1.5	1.4	57.1	15.	277.
10500	2	1	4.7	4.0	3.1	2.8	2.2	1.6	1.2	.9	.7	.6	485.6	27.	140.
		2	6.4	5.5	4.4	4.0	3.1	2.3	1.8	1.4	1.0	.8	229.5	17.	198.
		3	6.8	5.8	4.8	4.4	3.5	2.6	2.1	1.6	1.2	1.0	148.3	-36.	255.
		4	10.2	8.8	7.3	6.7	5.3	3.9	3.1	2.4	1.8	1.5	107.0	-7.	308.
		5	11.6	10.1	8.4	7.9	6.2	4.7	3.8	3.0	2.2	1.8	77.7	27.	336.
10525	2	1	6.5	5.1	4.4	4.0	3.1	2.2	1.8	1.4	1.1	.8	941.9	27.	264.
		2	8.1	6.5	5.7	5.1	4.0	2.9	2.3	1.8	1.4	1.1	473.3	-45.	398.
		3	12.1	9.9	8.7	7.9	6.2	4.6	3.7	2.9	2.2	1.8	297.6	2.	499.
		4	14.6	12.0	10.6	9.6	7.6	5.6	4.5	3.6	2.7	2.2	195.3	16.	547.
		5	15.2	12.4	10.9	9.8	7.8	5.8	4.7	3.7	2.8	2.3	172.1	4.	723.
10550	2	1	5.7	4.4	3.8	3.4	2.6	1.9	1.5	1.1	.8	.7	1335.0	-42.	399.
		2	10.5	8.5	7.4	6.8	5.3	3.9	3.1	2.4	1.8	1.5	666.9	12.	598.
		3	13.4	11.1	9.7	8.9	7.0	5.2	4.2	3.3	2.5	2.1	456.3	-9.	816.
		4	15.2	12.5	11.0	10.0	7.9	5.8	4.7	3.7	2.8	2.3	347.3	13.	1038.
		5	12.9	10.5	9.1	8.4	6.6	4.8	3.8	2.9	2.2	1.8	142.8	1.	640.
10575	2	1	9.2	7.3	6.5	5.6	4.4	3.2	2.5	2.0	1.5	1.2	1784.0	17.	538.
		2	12.8	10.4	9.3	8.2	6.5	4.8	4.1	3.0	2.3	1.9	964.9	9.	874.
		3	14.6	11.8	10.7	9.4	7.4	5.5	4.4	3.5	2.7	2.2	688.5	-1.	1244.
		4	12.8	10.3	9.2	8.1	6.3	4.6	3.7	2.9	2.2	1.8	264.1	-7.	797.
		5	9.6	6.2	5.0	4.5	2.9	2.3	1.4	1.0	.7	.4	123.7	6.	560.
10600	2	1	11.6	9.5	8.2	7.4	5.8	4.3	3.5	2.7	2.0	1.7	1411.0	28.	730.
		2	13.9	11.5	10.0	9.0	7.2	5.3	4.3	3.4	2.6	2.1	731.7	-19.	1148.
		3	11.7	9.8	8.4	7.3	5.9	4.2	3.4	2.6	2.0	1.6	235.8	8.	730.
		4	8.8	6.8	5.5	4.5	3.3	2.1	1.5	.9	.5	.3	106.8	1.	550.
		5	23.9	19.8	17.4	15.4	12.4	9.1	7.3	5.8	4.4	3.6	81.1	6.	636.
10625	2	1	13.4	10.7	9.5	8.6	6.7	4.9	4.0	3.1	2.4	1.9	2486.0	5.	1320.
		2	13.4	10.6	9.4	8.7	6.6	4.8	3.9	3.0	2.3	1.8	661.4	4.	1055.
		3	9.5	7.0	5.9	5.2	3.7	2.4	1.8	1.2	.8	.5	252.9	6.	800.
		4	25.7	20.9	18.4	16.8	13.2	9.7	7.9	6.1	4.8	4.0	133.7	0.	710.
		5	49.7	41.8	37.1	34.0	27.2	20.5	16.8	13.4	10.5	8.6	85.2	1.	680.
10650	2	1	13.5	11.0	9.6	8.6	6.8	4.9	4.0	3.1	2.3	1.9	1391.0	3.	970.
		2	10.3	7.9	6.6	5.8	4.3	2.8	2.2	1.5	1.0	.8	358.9	0.	751.
		3	23.4	19.2	16.9	15.2	12.0	8.9	7.2	5.5	4.2	3.4	201.1	8.	840.

		4	49.7	41.9	37.5	34.0	27.4	20.8	17.1	13.6	10.7	8.8	106.7	-8.	740.
		5	68.3	57.4	51.1	46.0	37.0	27.9	23.0	18.2	14.2	11.7	56.6	-5.	591.
10675	2	1	10.3	8.1	6.7	6.0	4.3	2.9	2.1	1.6	1.1	.8	912.4	-12.	636.
		2	24.3	20.2	17.6	16.0	12.5	9.3	7.4	5.8	4.4	3.6	442.0	4.	925.
		3	49.7	42.2	37.4	34.3	27.4	20.9	17.0	13.5	10.6	8.7	210.6	-16.	870.
		4	67.8	57.3	50.7	46.4	37.0	28.1	23.0	18.3	14.4	11.8	104.7	-2.	730.
		5	58.1	49.6	44.1	40.4	32.5	24.7	20.3	16.3	12.8	10.6	53.1	50.	555.
10700	2	1	31.8	26.2	22.9	20.7	16.2	12.0	9.7	7.6	5.8	4.7	579.6	8.	727.
		2	54.3	45.8	40.7	37.1	29.9	22.6	18.5	14.7	11.5	9.4	171.4	-8.	645.
		3	68.6	57.7	51.1	46.5	37.3	28.2	23.1	18.3	14.3	11.7	101.3	-5.	760.
		4	59.3	49.8	44.1	40.4	32.6	24.8	20.4	16.3	12.7	10.5	41.7	42.	523.
10725	2	1	63.2	53.4	47.8	43.4	34.7	26.3	21.4	17.0	13.3	10.6	411.5	-37.	717.
		2	74.3	62.1	55.4	50.3	40.2	30.4	24.8	19.7	15.4	12.3	130.4	17.	682.
		3	57.6	48.0	43.2	39.2	31.4	23.9	19.5	15.5	12.2	9.7	59.8	44.	624.
10750	2	1	71.0	60.1	53.1	48.5	38.6	29.2	23.8	19.0	14.8	9.8	251.6	-7.	980.
		2	55.5	46.5	41.0	37.5	30.0	22.7	18.5	14.7	11.4	6.8	76.2	39.	897.
10775	2	1	59.6	49.9	44.3	40.3	32.3	24.4	20.0	15.9	12.6	7.2	134.4	40.	840.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 78W.IND
DATA FILE : 78W.DAT

LINE NO. : 784

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	4.4	3.2	2.9	2.2	1.8	1.2	1.0	.7	.5	.4	592.8	27.	221.
		2	4.3	3.2	3.1	2.3	1.9	1.3	1.1	.8	.6	.4	123.5	-49.	138.
		3	4.7	3.5	3.4	2.5	2.1	1.5	1.2	.9	.6	.5	45.6	11.	102.
		4	5.4	4.1	3.8	2.9	2.4	1.7	1.3	.9	.7	.6	24.4	6.	91.
		5	4.2	3.2	3.1	2.1	1.9	1.3	1.1	.8	.5	.4	13.5	-9.	75.
10350	2	1	3.9	2.8	2.4	2.1	1.5	1.1	.8	.6	.4	.4	602.9	-49.	189.
		2	5.0	3.8	3.3	3.0	2.3	1.6	1.3	.9	.7	.5	126.0	13.	119.
		3	5.7	4.4	3.8	3.4	2.6	1.9	1.5	1.2	.9	.7	62.1	-7.	117.
		4	4.9	3.8	3.2	2.9	2.3	1.6	1.3	.9	.6	.5	28.0	6.	88.
		5	4.1	3.2	2.9	2.6	1.8	1.3	1.1	.7	.5	.4	19.3	-8.	91.
10375	2	1	5.2	3.7	3.3	2.8	2.1	1.5	1.1	.8	.6	.5	547.1	11.	170.
		2	6.5	4.9	4.5	3.8	2.9	2.1	1.7	1.3	1.0	.8	147.2	-4.	137.
		3	4.6	3.2	3.1	2.5	2.0	1.4	1.1	.7	.1	.1	56.7	3.	105.
		4	6.6	5.2	5.0	4.2	3.2	2.3	1.9	1.7	2.2	1.7	27.9	-4.	87.
		5	5.4	3.8	3.6	3.1	2.4	1.7	1.3	.9	.6	.5	20.4	2.	95.
10400	2	1	4.9	4.1	3.1	2.8	2.2	1.5	1.2	.9	.6	.5	632.3	-2.	206.
		2	4.9	4.2	3.4	3.1	2.4	1.7	1.4	1.1	.8	.6	118.2	2.	115.
		3	4.6	4.0	3.3	2.9	2.3	1.7	1.3	1.0	.8	.6	58.3	-5.	114.
		4	2.9	2.2	1.4	.9	.2	-.5	-.6	.8	1.6	.9	32.7	9.	106.
		5	8.0	7.2	6.9	6.0	6.6	5.7	5.1	1.3	-1.1	-.2	15.7	-6.	77.
10425	2	1	3.8	3.0	2.6	2.3	1.6	1.2	.9	.7	.5	.4	378.2	3.	108.
		2	5.1	4.0	3.6	3.2	2.4	1.8	1.4	1.1	.8	.6	124.8	-6.	107.
		3	5.1	4.0	3.7	3.2	2.4	1.8	1.4	1.1	.7	.4	52.0	6.	89.
		4	3.8	2.5	2.4	2.2	1.5	1.1	.7	.4	.4	.4	23.9	8.	68.
		5	.0	-.6	.4	-.3	-.2	.0	-.2	-.1	-.1	.0	21.6	-40.	92.
10450	2	1	5.0	3.9	3.5	3.0	2.2	1.6	1.4	1.1	.9	.7	491.6	-10.	116.

		2	6.1	4.7	4.3	3.8	2.8	2.1	1.6	1.3	1.0	.7	148.2	5.	105.
		3	4.9	3.6	3.4	3.0	2.2	1.6	1.2	1.0	.7	.6	64.2	6.	91.
		4	1.9	.7	.9	.7	.3	.4	.1	.1	.1	.0	41.6	-33.	98.
		5	3.4	1.7	2.1	2.1	1.0	.7	.4	.3	.1	.1	37.9	21.	134.
10475	2	1	6.0	4.6	4.0	3.4	2.6	1.8	1.4	1.1	.8	.6	537.7	11.	162.
		2	5.1	4.0	3.5	3.0	2.3	1.7	1.3	1.0	.7	.6	107.6	0.	97.
		3	2.5	1.8	1.5	1.3	.9	.6	.4	.3	.2	.1	66.8	-27.	121.
		4	4.0	3.3	2.8	2.5	1.8	1.4	1.0	.8	.6	.4	42.3	25.	128.
		5	6.2	5.0	4.2	3.8	2.9	2.1	1.7	1.3	.9	.7	39.7	-19.	180.
10500	2	1	4.1	3.4	2.7	2.5	1.8	1.3	1.0	.8	.6	.5	334.6	6.	131.
		2	3.7	2.9	2.5	2.2	1.6	1.2	.9	.7	.5	.4	123.5	-15.	145.
		3	5.6	4.4	4.0	3.5	2.6	1.9	1.4	1.0	.7	.5	69.5	1.	163.
		4	7.3	5.6	5.1	4.6	3.4	2.7	2.2	1.8	1.4	1.1	52.5	-3.	206.
		5	11.9	9.4	8.6	7.9	5.9	4.5	3.6	2.8	2.2	1.7	46.4	37.	273.
10525	2	1	4.5	3.5	3.0	2.7	2.0	1.4	1.1	.8	.6	.5	750.7	-14.	205.
		2	7.4	5.9	5.1	4.6	3.5	2.5	1.9	1.5	1.1	.9	274.7	10.	225.
		3	9.2	7.4	6.6	6.0	4.6	3.4	2.7	2.1	1.6	1.3	194.0	-18.	317.
		4	14.0	11.5	10.1	9.4	7.2	5.4	4.3	3.4	2.6	2.1	141.8	40.	387.
		5	15.3	12.6	11.0	10.2	7.9	6.0	4.8	3.8	2.9	2.4	107.2	-22.	439.
10550	2	1	7.7	6.1	5.1	4.7	3.5	2.5	2.0	1.4	1.1	.8	994.4	8.	343.
		2	10.4	8.4	7.2	6.7	5.1	3.8	3.0	2.3	1.8	1.4	500.9	-8.	518.
		3	15.4	12.7	11.1	10.2	7.9	5.9	4.7	3.7	2.8	2.2	346.0	39.	710.
		4	18.1	15.0	13.1	12.1	9.5	7.2	5.8	4.6	3.6	3.0	231.8	-11.	790.
		5	13.6	11.3	9.7	8.9	6.9	5.0	4.1	3.0	2.4	1.9	126.2	-10.	650.
10575	2	1	8.0	6.2	5.5	5.0	3.8	2.7	2.2	1.7	1.3	1.0	1938.0	-18.	690.
		2	14.7	12.0	10.6	9.7	7.5	5.6	4.5	3.5	2.7	2.2	898.7	34.	973.
		3	17.2	14.2	12.6	11.6	9.1	6.8	5.5	4.3	3.4	2.7	612.7	-17.	1320.
		4	13.7	11.1	9.7	8.9	6.8	5.0	4.0	3.1	2.4	1.9	304.0	-3.	1090.
		5	14.1	11.1	11.6	10.1	6.3	4.7	3.5	2.8	2.2	1.0	50.8	-33.	275.
10600	2	1	15.0	12.5	10.9	9.7	7.7	5.7	4.6	3.6	2.8	2.3	2001.0	53.	860.
		2	15.5	13.0	11.4	10.2	8.2	6.1	5.0	3.9	3.0	2.4	902.1	-50.	1164.
		3	13.3	11.0	9.6	8.5	6.7	4.9	4.0	3.1	2.4	1.9	337.4	-3.	860.
		4	15.7	12.6	10.8	9.5	7.5	5.3	4.2	3.1	2.2	1.8	62.2	-10.	267.
		5	16.3	13.0	11.1	9.7	7.4	5.3	4.2	3.2	2.4	1.9	82.3	16.	530.
10625	2	1	16.9	13.6	12.4	11.0	8.8	6.5	5.3	4.1	3.2	2.6	3274.0	-37.	1370.
		2	13.8	10.9	10.0	8.8	6.9	5.0	4.0	3.1	2.4	1.9	826.6	-7.	1038.
		3	16.5	13.0	11.6	10.1	7.8	5.6	4.4	3.3	2.5	2.0	165.4	-2.	410.
		4	16.8	13.2	11.5	10.1	7.7	5.4	4.3	3.2	2.4	1.9	149.7	0.	620.
		5	15.0	12.2	10.7	9.5	7.5	5.5	4.4	3.5	2.7	2.2	149.9	12.	940.
10650	2	1	14.3	11.1	10.1	9.2	6.9	5.0	4.0	3.0	2.3	1.8	3006.0	-33.	1680.
		2	15.8	12.5	11.0	10.0	7.5	5.4	4.2	3.2	2.4	1.9	288.1	11.	484.
		3	17.3	13.6	11.8	10.7	7.9	5.6	4.3	3.2	2.4	1.9	249.7	-2.	830.

		4	15.5	12.4	11.1	10.1	7.7	5.6	4.5	3.4	2.6	2.2	214.9	14.	1200.
		5	41.6	34.6	30.8	28.4	22.4	16.8	13.7	10.8	8.4	6.8	99.1	-9.	833.
10675	2	1	14.1	11.7	9.8	8.8	6.7	4.9	3.8	2.9	2.2	1.7	434.3	4.	358.
		2	17.3	14.0	12.0	10.6	8.0	5.7	4.4	3.4	2.5	1.9	320.4	1.	794.
		3	14.8	12.4	10.7	9.6	7.5	5.5	4.4	3.4	2.6	2.0	246.5	9.	1210.
		4	42.5	36.1	31.8	28.8	23.0	17.4	14.1	11.1	8.6	7.0	104.7	-4.	860.
		5	65.3	55.5	49.3	44.9	36.2	27.5	22.6	18.0	14.2	11.6	69.4	0.	860.
10700	2	1	21.0	17.2	14.7	13.2	10.0	7.2	5.7	4.3	3.3	2.5	551.3	4.	786.
		2	15.2	12.5	10.4	9.6	7.5	5.4	4.3	3.3	2.5	2.0	259.6	-5.	1111.
		3	43.4	36.9	32.5	29.7	23.6	17.9	14.5	11.5	8.9	7.3	122.3	10.	1040.
		4	66.8	56.8	50.2	46.1	36.8	28.1	23.1	18.3	14.2	11.8	65.4	5.	933.
10725	2	1	24.8	20.5	18.0	16.1	12.4	8.8	6.5	5.0	4.0	2.3	472.7	10.	989.
		2	54.4	44.5	40.9	36.9	29.4	22.1	18.1	14.3	11.2	9.1	141.5	8.	888.
		3	74.0	62.1	55.9	50.7	40.5	31.5	24.8	19.9	15.8	12.8	67.5	-2.	846.
10750	2	1	59.3	50.5	44.9	41.2	33.0	25.0	20.5	16.2	12.7	10.4	304.9	21.	797.
		2	78.8	67.0	59.6	54.5	43.8	33.3	27.3	21.8	17.2	14.0	143.9	1.	1129.
10775	2	1	76.3	64.2	57.5	52.7	42.3	32.2	26.4	21.1	16.6	11.0	360.3	-1.	1880.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 77W.IND
DATA FILE : 77W.DAT

LINE NO. : 774

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	4.1	3.2	2.6	2.3	1.7	1.2	.9	.7	.5	.4	531.9	9.	196.
		2	5.0	4.0	3.4	3.0	2.3	1.6	1.3	1.0	.7	.5	124.9	-28.	138.
		3	4.2	3.5	2.9	2.6	2.0	1.4	1.1	.8	.7	.5	49.3	-8.	108.
		4	4.4	3.6	3.2	2.8	2.1	1.5	1.2	.9	.6	.5	21.9	10.	80.
		5	4.6	3.7	3.3	2.8	2.1	1.4	1.1	.8	.6	.5	12.9	4.	71.
10350	2	1	5.1	3.8	3.4	2.8	2.1	1.4	1.0	.7	.5	.3	570.9	-25.	188.
		2	5.1	3.9	3.6	3.1	2.3	1.7	1.3	1.0	.7	.5	137.1	-13.	135.
		3	4.8	3.6	3.4	2.8	2.1	1.6	1.2	.9	.6	.4	48.9	16.	96.
		4	5.0	3.6	3.6	2.9	2.1	1.6	1.2	.9	.8	.9	25.8	-5.	85.
		5	4.9	3.5	3.6	2.7	2.1	1.5	1.2	.9	.8	.6	15.3	11.	75.
10375	2	1	4.0	3.0	2.4	2.4	1.7	1.1	.9	.7	.5	.4	397.5	-28.	134.
		2	4.9	3.9	3.1	3.1	2.3	1.6	1.3	.9	.7	.6	112.4	15.	113.
		3	5.3	4.3	3.4	3.3	2.4	1.7	1.5	1.1	.7	.6	51.2	16.	103.
		4	4.5	3.6	2.8	2.9	2.2	1.4	1.0	.7	.8	.6	25.6	-15.	86.
		5	4.3	3.5	2.5	2.7	2.0	1.3	1.1	.8	.6	.5	13.1	13.	66.
10400	2	1	5.1	3.8	3.2	3.0	2.2	1.5	1.2	.9	.7	.5	498.2	12.	164.
		2	5.8	4.5	3.8	3.5	2.6	1.8	1.5	1.1	.8	.7	129.2	2.	128.
		3	5.3	4.2	3.7	3.5	2.7	1.9	1.4	.9	.5	.1	54.0	4.	106.
		4	4.8	3.7	3.1	2.8	2.1	1.4	1.4	1.5	1.6	2.0	23.1	6.	76.
		5	4.2	3.0	2.6	2.3	1.9	1.4	1.1	.7	.6	.4	13.0	-17.	64.
10425	2	1	5.6	4.2	3.5	3.2	2.4	1.7	1.3	1.0	.7	.6	477.9	10.	144.
		2	5.5	4.1	3.5	3.4	2.5	1.7	1.4	1.0	.8	.6	111.0	9.	101.
		3	5.1	3.8	3.4	3.2	2.3	1.6	1.2	1.0	.9	.7	47.4	-7.	86.
		4	4.2	3.0	2.6	2.6	1.9	1.5	1.2	.8	.3	.3	21.2	-7.	64.
		5	3.5	1.5	1.6	.5	1.0	.6	-.4	.1	-.2	-.1	14.1	19.	64.
10450	2	1	5.0	4.1	3.3	2.9	2.2	1.6	1.2	.9	.7	.5	504.9	17.	159.

		2	5.3	4.5	3.6	3.3	2.5	1.8	1.4	1.1	.8	.6	100.6	8.	95.
		3	3.9	3.5	2.7	2.6	1.9	1.6	1.3	1.1	1.0	.7	47.2	-19.	89.
		4	4.6	4.2	3.4	3.3	2.6	1.8	1.2	.9	.5	.8	23.8	13.	75.
		5	.1	.4	-.3	.0	-.4	-.4	-.4	-.4	-.5	-.6	21.9	-19.	103.
10475	2	1	4.8	3.8	3.1	2.8	2.1	1.5	1.2	.9	.6	.5	219.3	11.	105.
		2	5.5	4.4	3.8	3.4	2.7	1.9	1.6	1.2	.9	.7	72.5	-18.	105.
		3	4.4	3.3	2.6	2.6	2.0	1.4	1.2	.8	.5	.5	29.3	14.	84.
		4	1.6	.7	.5	.7	.4	.1	.2	.0	.0	.0	23.5	-27.	113.
		5	3.6	2.0	1.7	2.0	1.1	.6	.6	.1	.0	.0	24.4	29.	176.
10500	2	1	5.6	4.3	3.9	3.4	2.6	1.9	1.6	1.2	.9	.7	372.7	-4.	117.
		2	6.5	5.1	4.6	4.0	3.1	2.2	1.7	1.3	1.0	.7	111.4	16.	105.
		3	2.4	1.9	1.7	1.5	1.1	.8	.7	.5	.3	.2	70.9	-8.	133.
		4	4.8	3.8	3.2	3.0	2.2	1.5	1.2	.9	.7	.6	64.2	7.	201.
		5	11.3	9.3	8.1	7.3	5.7	4.2	3.3	2.6	1.9	1.5	97.6	1.	460.
10525	2	1	6.5	5.1	4.6	4.0	3.7	2.7	2.2	2.0	1.7	.5	247.0	10.	106.
		2	5.0	3.7	3.5	2.8	2.3	1.6	1.2	1.0	.7	.6	96.5	-23.	124.
		3	5.5	4.3	4.1	3.1	2.6	1.8	1.4	1.1	.9	.7	88.6	22.	228.
		4	12.5	10.1	9.5	7.7	6.4	4.7	3.7	3.0	2.3	1.8	111.0	-8.	470.
		5	12.4	9.6	9.6	7.2	6.2	4.6	3.5	2.9	2.3	1.9	41.5	21.	267.
10550	2	1	5.9	4.3	3.9	3.4	2.6	1.8	1.4	1.0	.8	.6	346.9	4.	117.
		2	9.3	7.1	6.4	5.5	4.2	3.0	2.4	1.8	1.3	1.0	250.2	17.	253.
		3	13.8	11.1	10.1	8.9	7.0	5.1	4.1	3.1	2.5	2.1	256.1	-18.	510.
		4	15.0	12.3	11.1	9.9	7.8	5.9	4.8	3.7	2.6	1.7	86.5	6.	292.
		5	5.0	3.6	3.3	2.6	2.0	1.4	1.1	.8	.6	.7	34.3	21.	173.
10575	2	1	9.3	7.1	6.3	5.5	4.2	3.0	2.4	1.8	1.3	1.0	1072.0	29.	440.
		2	15.0	12.2	10.9	9.8	7.7	5.7	4.6	3.5	2.7	2.2	771.0	-26.	968.
		3	18.7	15.1	13.6	12.2	9.5	7.0	5.7	4.5	3.7	2.9	228.3	2.	570.
		4	7.5	5.3	4.7	4.3	3.3	2.3	1.6	1.1	.3	.4	73.0	24.	305.
		5	7.9	5.3	4.8	4.4	3.3	2.3	1.9	1.3	1.0	.7	33.3	-6.	208.
10600	2	1	14.8	12.1	10.7	9.4	7.5	5.5	4.4	3.5	2.6	2.1	2847.0	-18.	1480.
		2	19.2	15.9	14.0	12.5	9.9	7.3	5.9	4.6	3.5	2.9	565.5	14.	887.
		3	10.5	8.6	7.7	6.7	5.4	4.0	3.2	2.5	1.9	1.5	178.1	12.	550.
		4	8.9	6.9	6.0	5.1	4.0	2.8	2.2	1.6	1.1	.8	72.9	-14.	381.
		5	8.2	6.2	5.5	4.3	3.3	2.1	1.6	1.1	.7	.4	47.5	-8.	372.
10625	2	1	21.2	17.7	15.5	14.0	11.1	8.3	6.7	5.3	4.1	3.3	1840.0	5.	800.
		2	13.0	10.9	9.6	8.6	6.8	5.1	4.1	3.2	2.5	2.0	456.6	-7.	597.
		3	10.1	8.5	7.3	6.6	5.2	3.8	3.1	2.4	1.8	1.4	172.7	4.	450.
		4	10.3	8.5	7.1	6.4	4.9	3.5	2.8	2.1	1.6	1.2	107.2	-15.	460.
		5	12.7	10.3	8.5	8.3	5.9	4.2	3.4	2.6	1.8	1.4	84.0	-7.	549.
10650	2	1	19.0	15.6	13.6	12.6	9.8	7.3	5.9	4.7	3.6	3.0	1685.0	-1.	830.
		2	17.0	14.1	12.3	11.3	8.8	6.5	5.3	4.1	3.2	2.6	554.1	-17.	828.
		3	16.0	13.1	11.3	10.4	8.0	5.9	4.7	3.6	2.8	2.2	280.3	5.	830.

		4	19.2	15.6	13.5	12.5	9.4	6.8	5.4	4.1	3.1	2.5	201.2	-13.	1000.
		5	29.0	24.1	21.3	19.5	15.4	11.5	9.4	7.3	5.7	4.6	110.0	22.	820.
10675	2	1	11.8	9.6	8.3	7.4	5.7	4.2	3.3	2.5	1.9	1.5	1988.0	-22.	1320.
		2	13.4	10.9	9.4	8.4	6.4	4.7	3.7	2.9	2.2	1.7	626.4	2.	1255.
		3	18.2	14.9	12.9	11.6	8.9	6.5	5.1	3.9	2.9	2.3	342.9	0.	1370.
		4	30.2	25.2	22.2	20.1	16.0	11.9	9.7	7.6	5.9	4.7	156.2	11.	1040.
		5	33.2	28.4	24.6	22.2	17.9	13.4	10.9	8.8	6.5	5.4	126.7	-3.	1260.
10700	2	1	10.9	8.8	7.6	6.8	5.2	3.8	3.0	2.3	1.7	1.4	1336.0	12.	830.
		2	18.4	14.9	12.9	11.6	8.9	6.5	5.1	3.9	3.0	2.4	518.7	-2.	977.
		3	30.2	25.3	22.5	20.4	16.3	12.2	9.8	7.8	6.0	4.9	227.2	5.	850.
		4	34.0	28.2	25.0	22.7	18.0	13.5	10.9	8.7	6.7	5.5	143.4	-12.	900.
10725	2	1	23.2	18.9	16.7	15.1	11.6	8.6	6.9	5.4	4.1	3.3	1867.0	7.	1300.
		2	34.9	29.2	26.0	23.7	18.7	14.1	11.4	9.0	6.9	5.6	398.3	7.	833.
		3	39.1	32.5	28.9	26.2	20.8	15.8	12.8	10.1	7.8	6.3	254.1	-7.	1060.
10750	2	1	35.4	30.1	26.7	24.1	19.3	14.6	11.9	9.3	7.3	5.9	513.3	-2.	732.
		2	45.7	38.4	33.9	30.8	24.7	18.6	15.2	12.1	9.4	7.6	241.7	12.	1034.
10775	2	1	46.4	39.2	34.6	31.7	25.2	19.1	15.5	12.3	9.6	7.8	568.4	2.	1189.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 76W.IND
DATA FILE : 76W.DAT

LINE NO. : 764

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	4.4	3.4	2.8	2.5	1.8	1.3	1.0	.8	.6	.4	342.5	-1.	155.
		2	6.3	4.8	4.0	3.6	2.6	1.9	1.5	1.1	.8	.6	95.3	-19.	130.
		3	5.0	3.8	3.3	2.9	2.2	1.6	1.2	1.0	.7	.6	36.0	6.	98.
		4	4.7	3.6	3.2	2.9	2.0	1.5	1.1	.7	.6	.4	17.7	5.	80.
		5	4.0	3.0	2.9	2.6	1.7	1.4	1.2	.8	.4	.4	10.6	-13.	72.
10350	2	1	4.3	2.9	2.7	2.3	1.7	1.2	1.0	.7	.6	.5	433.3	-17.	154.
		2	6.2	4.3	3.9	3.4	2.6	1.8	1.4	1.0	.8	.6	99.1	15.	106.
		3	4.9	3.4	2.9	2.6	1.9	1.3	1.0	.7	.5	.3	39.7	0.	84.
		4	4.7	3.3	3.3	3.1	2.5	1.8	1.4	1.2	1.1	1.1	21.5	-17.	76.
		5	4.9	3.4	2.7	2.3	1.5	1.1	1.0	.6	.5	.0	13.5	-1.	72.
10375	2	1	5.4	4.3	3.4	3.1	2.3	1.6	1.2	.9	.7	.5	481.3	5.	164.
		2	5.8	4.9	3.8	3.6	2.7	1.9	1.5	1.1	.8	.7	105.5	-3.	108.
		3	4.8	3.6	2.7	2.4	1.9	1.3	1.0	.8	.5	.5	46.0	-1.	93.
		4	4.6	3.8	3.0	2.8	2.3	1.7	1.3	1.0	.7	.6	24.0	-12.	82.
		5	3.2	3.1	2.5	1.8	1.4	.8	.7	.5	.4	.2	13.4	14.	68.
10400	2	1	5.0	4.2	3.6	3.1	2.3	1.7	1.3	1.0	.8	.6	453.6	-6.	149.
		2	6.5	4.9	4.2	3.6	2.8	2.0	1.5	1.2	.9	.7	110.0	-12.	109.
		3	6.1	4.6	3.9	3.3	2.6	1.9	1.5	1.2	.9	.7	49.6	-8.	98.
		4	2.9	2.3	1.8	1.6	1.2	.9	.7	.6	.5	.4	22.9	19.	75.
		5	6.9	3.5	3.2	4.0	1.4	1.7	1.1	.7	.1	.7	15.3	11.	75.
10425	2	1	5.2	4.0	3.4	2.8	2.2	1.5	1.2	.9	.7	.5	393.1	-21.	148.
		2	7.1	5.6	5.0	4.3	3.5	2.5	2.1	1.6	1.2	1.0	99.2	-13.	113.
		3	4.4	3.0	2.5	1.9	1.3	.7	.6	.5	.4	.4	40.2	0.	91.
		4	5.4	4.5	4.0	3.4	2.9	2.3	2.0	1.3	.9	.6	21.3	33.	80.
		5	4.2	7.8	5.2	1.2	.3	.5	.8	-.7	-.5	.0	11.8	-26.	66.
10450	2	1	7.0	5.3	4.7	4.1	3.1	2.3	1.8	1.4	1.0	.8	374.6	-18.	138.

		2	5.3	3.9	3.6	3.2	2.4	1.8	1.4	1.1	.8	.6	93.5	20.	104.
		3	7.5	5.1	4.2	3.1	2.6	1.9	1.4	1.2	.9	.7	42.4	11.	93.
		4	4.9	3.5	3.1	2.8	2.2	1.6	1.2	1.0	.7	.5	19.8	-28.	73.
		5	3.8	3.2	2.5	1.9	1.6	1.3	.6	.6	.4	.4	14.9	34.	82.
10475	2	1	4.1	3.5	2.9	2.5	2.0	1.4	1.1	.9	.6	.5	235.1	14.	123.
		2	9.3	6.8	5.7	5.0	3.9	2.8	2.2	1.7	1.3	1.0	70.9	8.	111.
		3	4.8	3.7	3.1	2.7	2.1	1.5	1.2	.9	.6	.5	27.6	-21.	86.
		4	4.4	3.3	2.8	2.4	2.0	1.3	1.1	.8	.6	.5	17.5	32.	91.
		5	7.8	6.2	5.6	4.6	3.8	2.6	2.1	1.5	1.1	1.2	28.9	-9.	227.
10500	2	1	17.9	14.2	12.3	11.1	8.6	6.3	5.1	4.0	3.0	2.4	302.2	20.	145.
		2	7.3	5.6	4.8	4.4	3.3	2.4	1.9	1.5	1.1	.9	69.2	-19.	100.
		3	6.9	5.2	4.4	4.0	2.9	2.0	1.6	1.2	.9	.7	42.2	31.	122.
		4	8.3	6.5	5.6	4.9	4.1	2.9	2.3	1.7	1.3	1.0	41.7	-7.	201.
		5	7.7	3.6	6.0	3.5	-3.2	6.6	4.7	1.8	.4	.8	20.6	5.	149.
10525	2	1	4.0	3.1	2.7	2.3	1.6	1.1	.8	.6	.3	.2	201.0	-26.	123.
		2	7.1	5.7	4.8	4.2	3.3	2.3	1.7	1.3	1.0	.7	68.6	29.	127.
		3	8.4	6.8	5.6	5.0	3.6	2.6	1.7	1.3	.9	.6	58.4	-16.	215.
		4	4.4	3.9	3.1	3.1	2.2	1.9	2.4	1.9	1.6	1.5	23.4	9.	144.
		5	2.4	2.5	1.4	1.6	.6	.7	.6	.4	.3	-.3	16.8	50.	155.
10550	2	1	7.8	6.5	5.7	5.2	4.2	3.2	3.0	2.0	1.0	.0	262.9	27.	150.
		2	12.0	9.3	7.8	7.1	5.3	3.8	3.0	2.2	1.7	1.3	138.3	-11.	236.
		3	6.4	4.8	3.9	3.8	2.8	2.0	1.6	1.2	.9	.7	46.4	10.	158.
		4	3.7	2.9	2.3	2.6	1.7	1.2	1.0	.7	.5	.4	28.2	42.	160.
		5	7.3	5.7	4.6	4.6	3.1	2.2	1.7	1.2	.9	.7	24.2	-27.	206.
10575	2	1	11.8	9.7	8.3	7.5	5.8	4.2	3.4	2.6	1.9	1.6	709.1	-17.	278.
		2	10.0	8.1	6.9	6.2	4.8	3.5	2.8	2.2	1.6	1.3	144.8	5.	170.
		3	7.0	5.3	4.3	3.8	2.8	2.0	1.6	1.2	.9	.7	73.8	41.	173.
		4	9.7	7.7	6.6	6.1	4.6	3.3	2.6	2.0	1.5	1.2	57.5	-22.	225.
		5	7.3	6.7	5.2	4.1	3.6	1.6	1.6	1.3	.8	.8	28.3	-12.	166.
10600	2	1	12.7	10.5	9.1	8.4	6.6	4.9	4.0	3.1	2.4	1.9	1468.0	2.	650.
		2	14.3	11.5	9.9	9.0	7.1	5.2	4.2	3.3	2.5	2.1	383.3	42.	515.
		3	16.7	13.8	12.0	10.8	8.5	6.3	5.1	4.0	3.0	2.4	228.9	-29.	610.
		4	16.5	13.7	12.0	10.8	8.6	6.3	5.1	4.0	3.1	2.5	93.7	-15.	420.
		5	13.1	10.9	9.3	8.5	6.5	4.8	3.9	3.0	2.2	1.8	43.9	-7.	295.
10625	2	1	15.4	12.7	11.4	10.1	8.0	6.0	4.8	3.8	2.9	2.4	2313.0	31.	1030.
		2	21.2	17.5	15.5	13.9	11.0	8.1	6.6	5.1	4.0	3.2	1106.0	-34.	1480.
		3	22.6	18.1	16.0	14.2	11.3	8.4	6.8	5.3	4.1	3.4	400.1	-14.	1070.
		4	19.3	15.8	14.0	12.5	9.9	7.4	6.0	4.7	3.6	2.9	172.1	-18.	770.
		5	21.8	16.0	14.5	13.3	10.6	7.7	6.2	4.9	3.8	3.1	116.7	16.	780.
10650	2	1	15.3	12.4	10.9	9.9	7.6	5.6	4.5	3.5	2.7	2.2	1437.0	-59.	1120.
		2	20.2	16.2	14.1	12.8	10.1	7.4	6.0	4.7	3.6	2.9	413.5	18.	973.
		3	18.0	14.1	12.2	11.1	8.5	6.1	5.0	3.9	3.0	2.3	190.6	-39.	890.

		4	18.5	15.0	12.8	12.1	9.3	6.7	5.4	4.1	3.2	2.6	118.0	9.	920.
		5	18.4	14.9	13.0	11.9	9.3	6.9	5.7	4.4	3.4	2.6	68.6	9.	808.
10675	2	1	15.7	12.6	11.1	9.8	7.7	5.6	4.5	3.5	2.6	2.1	964.2	15.	672.
		2	15.9	12.6	10.9	9.6	7.5	5.6	4.4	3.4	2.6	2.1	372.6	-47.	779.
		3	16.8	13.5	11.9	10.6	8.1	5.9	4.7	3.7	2.8	2.2	216.5	18.	900.
		4	16.6	13.5	11.9	10.7	8.3	6.1	4.9	3.8	2.9	2.3	120.6	11.	840.
		5	17.1	13.9	12.1	10.7	8.4	6.2	4.8	3.8	2.9	2.2	100.0	1.	1040.
10700	2	1	11.2	9.1	8.0	7.0	5.3	3.9	3.1	2.4	1.8	1.4	346.3	-47.	724.
		2	15.1	12.2	10.5	9.4	7.2	5.2	4.1	3.2	2.4	1.9	143.2	45.	899.
		3	15.3	12.3	10.5	9.3	7.2	5.2	4.1	3.2	2.4	1.8	94.6	-24.	1185.
		4	17.9	14.7	12.7	11.5	7.8	6.0	5.5	3.5	2.8	2.7	56.9	-3.	1191.
10725	2	1	10.7	8.7	7.6	6.8	5.2	3.7	3.0	2.3	1.7	1.3	229.2	35.	790.
		2	15.7	11.7	10.1	9.1	7.0	5.0	4.0	3.1	2.3	1.9	107.0	-29.	1110.
		3	17.1	12.6	10.8	9.9	7.5	5.4	4.3	3.3	2.6	2.0	56.3	1.	1170.
10750	2	1	13.6	10.5	9.1	8.3	6.2	4.5	3.5	2.7	2.0	1.5	250.9	-10.	870.
		2	18.5	14.0	12.3	11.0	8.5	6.2	5.0	3.9	3.0	2.3	113.0	2.	1180.
10775	2	1	14.7	11.5	10.3	9.4	7.3	5.4	4.3	3.3	2.6	2.0	379.7	5.	1192.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 75W.IND
DATA FILE : 75W.DAT

LINE NO. : 754

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	3.6	2.2	2.1	1.7	1.2	.9	.7	.5	.4	.3	419.7	-25.	155.
		2	3.6	2.8	2.6	2.3	1.8	1.2	1.0	.7	.6	.4	157.7	-21.	174.
		3	5.6	4.4	3.9	3.5	2.7	1.9	1.6	1.2	.9	.7	69.8	0.	154.
		4	5.5	4.3	3.8	3.3	2.4	1.5	1.1	.7	.6	.6	29.4	13.	108.
		5	5.4	4.3	3.8	3.4	2.7	2.2	2.0	1.5	1.1	.7	18.7	-1.	103.
10350	2	1	4.0	2.8	2.5	2.3	1.6	1.2	.9	.7	.5	.4	569.6	-27.	198.
		2	5.0	3.8	3.4	3.2	2.3	1.7	1.3	1.0	.8	.6	130.9	9.	137.
		3	5.0	3.8	3.4	3.2	2.3	1.6	1.3	1.0	.7	.6	54.2	-12.	113.
		4	5.3	4.0	3.6	3.3	2.4	1.8	1.4	1.0	.8	.6	25.5	11.	88.
		5	4.4	3.4	2.9	2.6	1.8	1.3	1.0	.7	.5	.4	16.6	11.	86.
10375	2	1	4.3	3.4	2.9	2.6	2.0	1.4	1.1	.8	.6	.5	227.9	-3.	105.
		2	4.8	3.9	3.3	3.0	2.0	1.4	1.1	.9	.6	.5	69.8	-14.	97.
		3	4.8	3.9	3.3	3.1	2.3	1.7	1.3	1.1	.9	.6	29.6	17.	81.
		4	2.6	1.9	1.3	1.3	.5	-.1	-.5	.0	.3	.3	16.8	4.	77.
		5	3.2	4.5	2.8	4.1	3.1	3.2	3.2	1.6	.0	.2	10.1	-6.	70.
10400	2	1	5.1	4.0	3.3	3.1	2.3	1.6	1.3	1.0	.7	.5	266.5	-8.	104.
		2	5.4	4.3	3.7	3.4	2.6	1.8	1.4	1.1	.8	.7	76.1	21.	90.
		3	4.2	3.4	3.0	2.6	2.0	1.4	1.1	.9	.6	.5	36.0	0.	84.
		4	2.8	2.1	1.9	1.6	1.2	.8	.5	.3	.2	.0	19.5	-2.	76.
		5	3.6	3.2	2.8	2.3	1.7	1.0	1.0	1.0	.8	.9	11.6	-2.	68.
10425	2	1	7.7	6.0	5.4	4.5	3.5	2.5	2.0	1.5	1.1	.9	388.6	15.	131.
		2	6.3	4.8	4.5	3.7	3.0	2.1	1.7	1.3	.9	.7	102.8	-7.	104.
		3	4.3	3.1	3.0	2.3	1.9	1.4	1.1	.9	.7	.6	47.4	0.	95.
		4	4.7	3.7	3.3	2.8	2.2	1.5	1.2	.9	.6	.5	21.8	-4.	73.
		5	2.9	2.0	1.7	1.4	1.1	.8	.6	.5	.4	.4	14.7	11.	74.
10450	2	1	8.0	6.1	5.3	4.8	3.5	2.5	1.9	1.4	1.0	.6	430.7	-10.	142.

		2	6.0	4.6	4.0	3.7	2.7	1.9	1.5	1.2	.9	.7	114.7	6.	113.
		3	4.6	3.7	3.4	3.2	2.4	1.8	1.4	1.0	.7	.5	42.7	-8.	84.
		4	3.9	3.0	2.6	2.4	1.7	1.3	1.0	.9	.8	.6	27.0	8.	89.
		5	2.0	3.1	3.8	1.0	-1.0	1.2	-1.0	-.8	-3.9	-7.7	15.0	8.	74.
10475	2	1	6.1	5.1	4.1	3.7	2.8	2.0	1.6	1.2	.9	.7	380.3	5.	145.
		2	6.5	5.9	4.9	4.5	3.5	2.6	2.0	1.6	1.2	.9	93.0	-28.	107.
		3	4.3	3.5	2.9	2.6	2.0	1.5	1.2	.9	.7	.5	42.0	26.	96.
		4	5.3	4.7	4.1	3.5	2.7	2.0	1.7	1.3	1.1	1.1	22.4	8.	85.
		5	4.4	3.1	3.3	2.7	1.9	.8	.6	.1	.0	-.7	13.1	2.	75.
10500	2	1	6.7	5.5	4.6	3.8	3.0	2.1	1.7	1.3	.9	.7	370.3	-24.	129.
		2	4.8	4.1	3.4	2.8	2.3	1.6	1.3	1.0	.7	.6	104.8	31.	109.
		3	4.9	4.4	3.7	3.0	2.4	1.7	1.3	1.0	.6	.4	46.7	8.	97.
		4	6.3	5.7	4.6	3.9	3.3	2.4	1.8	1.3	1.1	1.1	24.0	-12.	83.
		5	3.9	4.2	2.2	1.6	1.2	1.0	.7	.4	.4	.4	24.6	6.	128.
10525	2	1	5.2	3.9	3.4	3.0	2.3	1.7	1.3	1.0	.8	.7	272.0	24.	164.
		2	5.8	4.5	4.0	3.5	2.7	2.0	1.6	1.2	.8	.6	68.9	-12.	125.
		3	6.0	5.0	4.6	4.1	3.4	2.4	1.9	1.4	1.0	.8	27.1	18.	98.
		4	4.4	3.2	2.9	2.7	2.1	1.3	1.0	.7	.5	.4	24.5	-2.	147.
		5	5.4	3.7	3.4	3.5	2.6	1.5	1.0	1.0	.6	.3	21.8	-2.	197.
10550	2	1	6.6	5.1	4.4	4.0	3.0	2.2	1.7	1.3	1.0	.8	314.6	-10.	119.
		2	8.3	6.9	6.2	5.7	4.4	3.2	2.5	1.8	1.3	1.1	83.1	22.	94.
		3	4.9	3.9	3.6	3.4	2.5	1.8	1.4	1.0	.8	.6	60.1	-8.	136.
		4	6.6	5.2	4.7	4.3	3.3	2.4	1.9	1.3	1.0	.8	55.9	-3.	211.
		5	7.6	5.7	4.8	5.0	3.1	1.6	2.0	1.7	1.0	.3	45.7	47.	259.
10575	2	1	10.3	8.4	7.1	6.7	5.0	3.6	2.8	2.2	1.6	1.3	327.4	17.	128.
		2	7.8	6.5	5.6	5.2	4.0	2.8	2.2	1.7	1.1	.8	140.4	-14.	165.
		3	8.0	6.7	5.7	5.3	4.0	2.9	2.3	1.8	1.3	1.0	106.4	-4.	250.
		4	8.8	7.1	6.2	5.7	4.3	3.0	2.3	1.8	1.3	1.1	77.8	49.	305.
		5	11.9	8.6	7.9	6.0	5.2	3.8	3.8	2.4	1.5	1.5	48.1	-33.	283.
10600	2	1	9.2	7.9	6.5	6.0	4.7	3.4	2.6	2.0	1.5	1.2	366.9	-10.	188.
		2	11.2	9.6	8.1	7.4	5.8	4.2	3.3	2.5	1.8	1.5	200.2	2.	309.
		3	12.0	10.4	8.8	8.1	6.4	4.7	3.6	2.9	2.2	1.8	123.3	45.	380.
		4	14.5	12.3	10.3	9.5	7.2	5.3	4.3	3.2	2.1	1.6	68.1	-31.	350.
		5	12.9	11.4	9.5	8.7	6.8	5.1	4.0	3.1	2.2	1.8	35.5	-16.	274.
10625	2	1	10.4	8.4	7.3	6.5	5.0	3.6	2.9	2.2	1.6	1.3	728.8	-9.	394.
		2	14.0	11.5	10.1	9.0	7.2	5.2	4.2	3.2	2.5	2.0	319.4	12.	518.
		3	16.4	13.7	12.1	10.8	8.5	6.2	4.9	3.8	2.9	2.3	142.3	-3.	460.
		4	16.7	13.8	12.0	10.8	8.7	6.3	5.2	3.9	3.0	2.4	69.1	-11.	374.
		5	15.3	13.5	10.9	8.6	5.3	5.0	4.8	2.9	2.7	1.3	32.5	26.	263.
10650	2	1	13.9	11.2	9.8	8.9	7.0	5.2	4.2	3.3	2.5	2.0	1374.0	14.	660.
		2	17.8	14.5	12.8	11.6	9.0	6.7	5.4	4.2	3.2	2.6	479.2	0.	694.
		3	18.7	15.4	13.8	12.5	9.9	7.4	6.0	4.7	3.6	2.9	203.7	-5.	580.

		4	14.5	11.7	10.3	9.4	7.3	5.3	4.2	3.3	2.5	2.0	86.3	11.	416.
		5	13.2	9.6	9.4	7.7	6.4	4.5	3.6	2.8	2.0	1.7	63.8	-13.	462.
10675	2	1	16.3	13.1	11.2	10.2	7.8	5.7	4.6	3.6	2.7	2.2	1409.0	-21.	740.
		2	20.1	16.6	14.6	13.3	10.5	7.8	6.3	5.0	3.8	3.1	467.2	-19.	745.
		3	14.5	12.2	10.7	9.9	7.7	5.7	4.6	3.6	2.8	2.2	202.3	31.	640.
		4	14.5	11.6	10.1	9.3	7.1	5.1	4.0	3.1	2.4	1.9	125.1	-23.	660.
		5	12.9	10.5	9.0	8.2	6.2	4.6	3.6	2.8	2.1	1.7	122.0	-22.	970.
10700	2	1	19.1	15.5	13.7	12.0	9.5	7.0	5.7	4.4	3.4	2.8	753.0	-23.	656.
		2	15.3	12.5	11.0	9.7	7.7	5.7	4.6	3.5	2.7	2.2	293.9	20.	769.
		3	14.2	11.7	10.2	8.9	6.9	5.0	3.9	3.0	2.3	1.9	160.0	-15.	830.
		4	13.1	10.7	9.6	7.9	6.2	4.3	3.5	2.6	2.0	1.5	144.2	-18.	1250.
10725	2	1	12.0	9.5	8.3	7.4	5.7	4.1	3.3	2.5	1.9	1.5	260.6	12.	681.
		2	13.6	10.3	9.1	8.1	6.2	4.4	3.4	2.6	1.9	1.5	120.8	-18.	948.
		3	12.1	8.9	7.8	7.0	5.2	3.7	2.9	2.2	1.5	1.2	101.8	-5.	1590.
10750	2	1	11.5	9.1	8.0	7.2	5.5	3.9	3.1	2.4	1.8	1.4	275.9	-21.	721.
		2	10.1	7.2	6.1	5.5	4.0	2.8	2.2	1.6	1.2	.9	173.6	-9.	1362.
10775	2	1	11.3	8.8	7.6	6.7	5.1	3.7	2.9	2.2	1.7	1.3	341.6	-8.	1190.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 74W.IND
DATA FILE : 74W.DAT

LINE NO. : 744

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	6.0	4.8	4.0	3.5	2.7	1.9	1.5	1.1	.8	.6	536.8	78.	156.
		2	3.1	2.7	2.0	1.8	1.4	1.0	.8	.6	.4	.3	189.0	-74.	165.
		3	3.5	3.1	2.6	2.5	1.9	1.4	1.1	.9	.6	.5	77.4	7.	135.
		4	5.7	4.8	3.8	3.6	2.7	2.1	1.7	1.3	.9	.7	44.6	-14.	130.
		5	5.0	4.0	3.2	2.9	2.1	1.4	.9	.7	.5	.6	23.5	23.	102.
10350	2	1	3.7	2.5	2.3	2.1	1.5	1.1	.9	.7	.5	.4	421.7	-81.	147.
		2	5.1	3.9	3.6	3.1	2.6	1.7	1.3	.9	.8	.7	110.2	18.	115.
		3	5.2	4.0	3.6	3.3	2.5	1.8	1.5	1.1	.9	.7	63.9	-25.	133.
		4	5.5	4.2	3.8	3.5	2.6	1.9	1.6	1.2	1.0	.9	30.0	14.	104.
		5	4.9	3.9	3.4	3.2	2.2	1.6	1.2	.8	.5	.3	16.8	-17.	88.
10375	2	1	5.6	4.2	3.6	3.2	2.6	2.2	1.9	1.5	1.2	1.0	279.3	18.	94.
		2	5.7	7.1	3.7	3.4	2.5	1.8	1.4	1.1	.8	.7	118.0	-37.	119.
		3	4.9	3.8	3.3	3.0	2.3	1.5	1.1	.8	.6	.4	47.9	16.	96.
		4	5.5	4.1	3.5	3.3	2.8	2.0	1.9	1.4	1.1	.9	24.6	-14.	83.
		5	5.8	4.4	3.7	3.3	2.2	1.8	1.3	1.0	.5	.5	18.0	34.	91.
10400	2	1	5.5	6.8	3.7	3.2	2.4	1.7	1.4	1.0	.8	.6	547.5	-30.	175.
		2	5.0	4.3	3.8	3.3	2.6	1.9	1.5	1.3	1.0	.8	114.9	15.	110.
		3	5.0	4.1	3.6	3.1	2.4	1.8	1.3	1.1	.8	.6	52.2	-9.	100.
		4	4.9	3.9	3.3	2.9	2.2	1.6	1.2	.9	.7	.5	31.7	24.	101.
		5	3.5	2.2	2.2	1.8	1.5	.9	1.3	.9	1.6	.3	17.9	8.	86.
10425	2	1	5.9	5.1	4.3	3.6	2.9	2.1	1.6	1.3	.9	.8	462.0	-5.	138.
		2	6.0	5.0	4.2	3.5	2.9	2.1	1.6	1.3	.9	.7	124.4	-18.	112.
		3	5.0	4.2	3.7	3.0	2.5	1.8	1.5	1.2	.9	.6	61.2	28.	110.
		4	4.8	4.0	3.5	2.7	2.2	1.5	1.2	.9	.6	.7	30.8	7.	92.
		5	-13.9	-6.4	-1.9	.6	-5.0	-.1	-.6	.0	.1	-.2	19.7	-13.	88.
10450	2	1	6.8	5.4	4.5	4.1	3.0	2.2	1.7	1.3	1.0	.8	454.5	-41.	164.

		2	6.9	5.9	5.1	4.7	3.7	2.7	2.1	1.7	1.2	1.0	140.0	53.	151.
		3	5.4	4.5	3.9	3.5	2.6	2.0	1.6	1.2	.9	.7	56.7	-15.	122.
		4	3.1	2.3	1.9	1.6	1.0	.5	.5	.4	.2	.2	29.7	20.	107.
		5	5.2	4.4	3.8	3.3	2.6	2.0	1.4	1.0	.8	.6	12.3	18.	66.
10475	2	1	7.7	5.6	5.0	4.5	3.4	2.4	1.9	1.4	1.1	.9	682.9	27.	186.
		2	8.9	5.1	4.6	4.2	3.2	2.3	1.8	1.4	1.1	.8	157.3	-19.	129.
		3	4.1	2.9	2.5	2.3	1.7	1.2	1.0	.7	.6	.4	66.2	24.	108.
		4	6.0	4.5	4.1	3.7	2.8	2.0	1.6	1.2	.8	.6	24.7	21.	67.
		5	4.0	1.3	.9	1.2	.7	.9	2.1	1.5	.5	.5	15.9	-24.	65.
10500	2	1	7.6	6.2	5.3	4.8	3.7	2.7	2.2	1.7	1.3	1.0	322.2	-35.	140.
		2	6.6	5.0	4.1	3.5	2.6	1.8	1.4	1.1	.8	.7	86.2	9.	113.
		3	3.7	3.9	3.7	3.5	3.0	2.3	1.7	1.4	1.0	.7	34.6	34.	90.
		4	5.1	4.1	3.4	3.0	2.4	1.7	1.3	1.0	.8	.6	17.1	-18.	74.
		5	6.4	7.8	3.8	4.2	4.5	-.9	-1.2	1.1	1.7	.6	12.8	-11.	83.
10525	2	1	5.5	4.0	3.6	3.1	2.4	1.7	1.4	1.1	.8	.7	546.8	-1.	167.
		2	7.7	6.4	6.1	5.5	4.3	3.2	2.5	1.9	1.4	1.0	109.7	14.	100.
		3	7.2	5.9	5.5	5.0	4.2	3.3	2.8	2.3	2.3	2.1	48.4	-21.	88.
		4	5.7	4.1	3.5	2.9	1.7	.7	.4	.0	-.8	-1.0	31.0	-6.	94.
		5	3.6	2.2	2.3	1.8	1.9	.4	.6	.5	.4	.3	28.9	-48.	132.
10550	2	1	9.7	7.6	6.2	5.6	4.3	3.1	2.3	1.8	1.0	.7	138.6	14.	75.
		2	6.2	4.9	4.3	3.9	2.9	2.0	1.7	1.2	.8	.6	45.3	-17.	74.
		3	8.3	6.9	6.0	5.6	4.3	3.2	2.5	1.8	1.3	.9	26.4	-12.	85.
		4	3.0	2.1	1.2	1.4	.7	-.5	-.4	-.5	-.6	-.3	23.5	4.	127.
		5	5.6	3.7	3.4	3.4	2.6	3.1	2.0	1.7	1.4	1.2	18.4	-23.	149.
10575	2	1	11.7	9.4	8.2	7.7	5.9	4.3	3.5	2.7	2.0	1.6	413.5	-23.	152.
		2	12.0	9.9	8.8	8.2	6.4	4.7	3.8	2.9	2.2	1.7	125.9	-18.	139.
		3	5.9	4.9	4.1	3.9	3.0	2.1	1.7	1.3	.9	.7	78.5	-3.	173.
		4	5.4	4.4	3.6	3.5	2.6	1.9	1.6	1.2	.9	.7	53.5	-2.	197.
		5	8.5	7.1	6.0	5.5	4.2	3.2	2.6	2.0	1.6	1.3	46.8	0.	259.
10600	2	1	15.4	12.7	11.3	10.3	8.0	5.9	4.7	3.6	2.7	2.1	413.4	-23.	149.
		2	10.2	8.4	7.3	6.8	5.1	3.7	2.9	2.2	1.6	1.2	166.3	2.	180.
		3	7.4	6.2	5.3	5.1	3.7	2.8	2.1	1.7	1.2	.9	93.5	-8.	202.
		4	11.3	9.6	8.4	8.0	5.7	4.2	3.3	2.5	1.9	1.5	72.8	1.	262.
		5	14.3	12.0	10.1	9.9	7.0	5.2	4.1	3.1	2.4	1.9	43.9	22.	237.
10625	2	1	13.8	11.2	9.9	8.7	7.0	5.1	4.1	3.1	2.3	1.8	461.0	-8.	203.
		2	11.4	9.2	8.1	7.2	5.7	4.2	3.3	2.5	1.9	1.5	175.9	-12.	233.
		3	14.3	11.8	10.5	9.4	7.5	5.5	4.4	3.4	2.5	2.0	111.3	2.	290.
		4	18.9	15.3	13.4	12.0	9.5	7.0	5.5	4.4	3.3	2.7	59.6	6.	263.
		5	16.6	13.2	11.5	10.3	8.0	5.9	4.6	3.7	2.7	2.2	40.9	34.	271.
10650	2	1	8.6	7.0	5.6	5.1	3.9	2.9	2.3	1.8	1.3	1.0	871.0	-10.	455.
		2	15.7	13.3	11.3	10.4	8.1	6.0	4.8	3.8	2.8	2.3	334.3	4.	524.
		3	22.0	18.6	16.2	14.8	11.8	8.8	7.1	5.6	4.3	3.4	141.6	-8.	440.

		4	21.7	18.0	15.5	14.1	11.0	8.2	6.6	5.2	3.9	3.2	73.6	43.	385.
		5	10.8	8.9	7.4	6.8	5.4	3.9	3.1	2.3	1.7	1.3	33.4	-17.	262.
10675	2	1	16.4	12.1	10.0	8.6	6.6	4.7	3.6	2.8	2.0	2.4	258.9	10.	1010.
		2	27.0	21.8	18.7	16.7	13.3	9.9	8.0	6.0	4.6	3.7	84.9	-6.	999.
		3	27.6	22.1	18.9	17.3	13.7	10.3	8.5	6.7	5.2	4.3	36.6	39.	860.
		4	18.9	14.3	11.5	11.1	8.4	6.4	5.2	4.1	3.3	3.0	14.1	-15.	550.
		5	27.0	20.4	16.5	16.6	12.8	9.7	8.2	6.6	5.2	4.4	9.4	-5.	556.
10700	2	1	25.6	20.4	17.9	16.3	12.6	9.4	7.6	6.0	4.7	3.8	483.5	-3.	893.
		2	28.2	22.8	20.1	18.5	14.4	10.8	8.7	6.9	5.3	4.3	192.0	43.	1063.
		3	18.8	15.2	13.4	12.3	9.5	7.1	5.8	4.6	3.6	2.9	65.1	-23.	719.
		4	26.6	21.2	18.7	17.1	13.2	9.9	7.9	6.4	5.0	3.9	42.0	-3.	776.
10725	2	1	23.0	18.1	15.6	14.1	10.8	8.0	6.4	5.0	3.9	3.0	462.6	36.	1117.
		2	17.9	14.1	12.2	11.0	8.4	6.2	4.9	3.9	3.0	2.3	119.2	-27.	863.
		3	26.4	21.0	18.4	16.5	13.1	9.3	7.2	5.6	4.4	3.4	69.5	2.	1005.
10750	2	1	12.9	10.5	8.9	8.0	6.3	4.5	3.6	2.9	2.2	1.7	400.2	-25.	698.
		2	24.2	19.5	16.8	15.1	11.8	8.7	7.1	5.5	4.2	3.4	183.2	7.	958.
10775	2	1	24.8	20.2	17.7	16.1	12.6	9.2	7.4	5.8	4.5	3.6	695.6	5.	873.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 73W.IND
DATA FILE : 73W.DAT

LINE NO. : 734

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	5.7	4.1	3.8	3.4	2.5	1.8	1.5	1.1	.9	.7	488.9	-4.	154.
		2	3.8	2.9	2.8	2.6	1.9	1.4	1.1	.8	.6	.4	148.7	-3.	140.
		3	2.8	1.9	1.8	1.6	1.2	.8	.6	.5	.4	.4	92.2	-24.	173.
		4	5.2	3.7	3.4	3.0	2.3	1.6	1.3	.9	.7	.5	55.3	14.	174.
		5	5.3	3.7	3.5	3.1	2.3	1.7	1.4	1.0	.8	.6	28.6	22.	135.
10350	2	1	2.5	2.0	1.4	1.2	.8	.5	.3	.3	.1	.1	413.2	-3.	127.
		2	2.1	2.0	1.4	1.4	1.0	.8	.5	.4	.3	.2	179.5	-20.	166.
		3	4.3	3.8	2.8	2.7	2.0	1.4	1.0	.8	.6	.7	87.1	5.	161.
		4	4.8	4.2	3.3	3.1	2.4	1.8	1.5	1.2	.9	.2	40.5	23.	125.
		5	4.3	3.7	2.9	2.7	2.1	1.5	1.2	1.0	.8	.7	28.6	7.	132.
10375	2	1	2.9	2.1	1.5	1.6	1.0	.7	.6	.4	.3	.3	375.6	-28.	190.
		2	5.0	3.8	3.1	3.2	2.3	1.6	1.3	1.0	.7	.6	103.1	5.	156.
		3	3.9	3.7	2.6	3.1	2.2	1.6	1.2	.9	.7	.5	42.0	20.	127.
		4	4.6	3.4	2.4	2.9	2.0	1.4	1.1	.8	.6	.5	25.4	9.	128.
		5	5.9	4.2	1.4	3.5	2.5	1.8	1.4	1.2	.9	.7	18.8	-12.	143.
10400	2	1	4.5	3.7	3.1	2.8	2.1	1.5	1.2	.9	.7	.6	381.2	4.	114.
		2	4.8	3.9	3.2	2.9	2.2	1.6	1.3	1.0	.7	.6	114.0	27.	102.
		3	4.3	3.5	2.8	2.5	1.9	1.3	1.1	.8	.6	.5	60.5	0.	108.
		4	5.4	4.4	3.6	3.2	2.5	1.8	1.5	1.1	.8	.6	40.8	-12.	122.
		5	5.7	4.4	3.5	2.5	2.4	2.0	1.3	1.2	.9	.7	23.0	-1.	103.
10425	2	1	10.0	7.9	6.7	6.1	4.7	3.4	2.7	2.1	1.6	1.3	625.2	17.	182.
		2	4.6	3.6	3.0	2.8	2.0	1.4	1.1	.9	.6	.5	142.4	-1.	124.
		3	4.9	4.0	3.3	3.0	2.4	1.8	1.4	1.1	.9	.8	77.8	-8.	135.
		4	6.0	4.9	4.0	3.6	2.7	1.8	1.4	1.0	.7	.5	33.0	-6.	96.
		5	2.9	2.2	1.5	1.3	1.0	.6	.4	.3	.2	.1	19.2	7.	84.
10450	2	1	6.8	5.3	4.7	4.1	3.2	2.3	1.9	1.5	1.1	.9	690.1	-2.	206.

		2	5.1	4.0	3.6	3.1	2.4	1.7	1.4	1.1	.8	.6	168.2	-1.	151.
		3	6.0	4.8	4.3	3.8	2.9	2.2	1.7	1.3	1.0	.8	60.5	0.	108.
		4	3.6	2.7	2.4	1.9	1.5	1.1	.7	.5	.4	.3	29.0	-9.	87.
		5	1.1	.8	.7	.8	.4	.2	.1	.1	.3	.3	15.5	-16.	69.
10475	2	1	4.7	3.7	3.1	2.8	2.1	1.5	1.2	.9	.7	.6	544.4	-9.	151.
		2	6.4	5.2	4.4	4.1	3.1	2.3	1.8	1.4	1.1	.9	130.5	-1.	109.
		3	3.6	2.9	2.5	2.2	1.6	1.2	.9	.7	.5	.3	55.7	-11.	93.
		4	1.8	1.0	.9	.8	.4	.3	.2	.1	.2	.2	27.5	-19.	76.
		5	5.5	4.3	3.7	3.5	2.5	1.8	1.4	1.1	.8	.6	15.3	1.	64.
10500	2	1	6.5	5.6	4.5	4.3	3.3	2.4	1.9	1.5	1.1	.9	319.6	-3.	98.
		2	4.5	3.8	2.9	2.9	2.1	1.5	1.1	.9	.7	.5	97.7	-4.	90.
		3	2.5	2.0	1.5	1.6	1.1	.8	.6	.5	.4	.3	43.2	-13.	80.
		4	6.6	5.5	4.6	4.3	3.1	2.2	1.5	1.2	.9	.7	20.6	-16.	63.
		5	6.8	5.7	5.0	5.0	3.7	2.7	2.2	1.7	1.2	.9	13.4	1.	62.
10525	2	1	4.5	3.7	3.0	2.6	1.9	1.4	1.1	.8	.6	.5	433.1	-14.	132.
		2	4.2	3.4	2.7	2.4	1.8	1.3	1.0	.8	.5	.4	116.0	-14.	106.
		3	8.3	7.2	6.1	5.6	4.3	3.1	2.4	1.9	1.5	1.1	48.6	-20.	89.
		4	9.0	7.5	5.8	5.6	4.5	3.2	2.5	1.9	1.4	1.2	24.3	7.	74.
		5	-.3	1.1	2.4	2.0	.7	.4	.4	.2	.0	-.2	17.9	-4.	82.
10550	2	1	4.7	3.4	2.9	2.7	1.9	1.4	1.1	.9	.7	.5	501.4	-14.	110.
		2	9.6	7.8	6.9	6.4	4.8	3.5	2.8	2.1	1.6	1.3	123.0	-4.	81.
		3	10.2	8.5	7.5	7.0	5.4	4.0	3.1	2.4	1.8	1.4	63.8	-9.	84.
		4	2.9	2.1	1.7	1.9	1.2	.8	.4	.2	.1	.0	39.0	0.	86.
		5	-4.0	-3.8	-3.7	-3.0	-2.9	-2.3	-2.1	-1.7	-1.2	-1.2	48.1	10.	158.
10575	2	1	9.7	7.8	7.0	6.3	4.8	3.6	2.8	2.2	1.7	1.3	413.3	-1.	100.
		2	11.5	9.5	8.5	7.8	6.0	4.4	3.5	2.7	2.0	1.5	121.4	-10.	88.
		3	3.8	3.2	2.9	2.6	2.0	1.4	1.1	.7	.5	.3	60.8	-2.	88.
		4	-3.0	-3.1	-2.8	-2.7	-2.4	-1.9	-1.7	-1.4	-1.2	-1.0	66.7	12.	161.
		5	17.8	14.7	13.1	11.7	9.4	7.0	5.7	4.5	3.5	2.8	62.0	12.	225.
10600	2	1	14.9	12.9	11.1	10.0	8.0	5.9	4.7	3.7	2.7	2.2	425.9	1.	112.
		2	7.8	6.8	5.9	5.2	4.2	3.1	2.4	1.9	1.3	1.0	138.3	4.	109.
		3	-1.3	-1.2	-1.4	-1.5	-1.2	-1.1	-1.0	-.9	-.8	-.7	118.7	3.	187.
		4	17.8	15.0	13.1	11.7	9.4	7.0	5.7	4.5	3.5	2.8	94.3	6.	249.
		5	16.3	13.6	12.0	10.7	8.6	6.4	5.2	4.2	3.2	2.6	62.5	6.	248.
10625	2	1	16.9	14.1	12.5	11.4	9.1	6.7	5.4	4.1	3.1	2.4	477.3	-4.	129.
		2	6.9	5.5	4.8	4.3	3.3	2.3	1.8	1.3	.9	.6	245.6	1.	199.
		3	21.9	18.2	16.2	14.8	11.8	8.9	7.2	5.7	4.4	3.5	152.5	7.	247.
		4	21.4	17.7	15.9	14.4	11.4	8.6	7.0	5.5	4.4	3.5	86.0	2.	233.
		5	14.7	11.6	10.0	8.9	6.8	5.0	4.0	3.0	2.4	1.8	61.3	17.	249.
10650	2	1	10.5	8.3	7.6	6.7	5.3	3.8	3.0	2.3	1.7	1.3	764.1	7.	282.
		2	24.9	20.8	18.7	17.0	13.6	10.2	8.3	6.5	5.0	4.1	268.2	13.	297.
		3	28.0	23.4	21.2	19.2	15.4	11.7	9.5	7.5	5.9	4.8	115.9	-5.	250.

		4	20.9	16.8	14.9	13.4	10.5	7.7	6.2	4.8	3.6	3.0	74.9	20.	276.
		5	7.3	5.5	5.0	3.8	3.5	2.3	1.8	1.4	1.0	.8	39.4	-14.	218.
10675	2	1	20.0	16.5	15.0	13.4	10.7	8.1	6.6	5.2	4.1	3.3	1740.0	-3.	525.
		2	35.2	29.8	27.1	24.5	19.8	15.2	12.5	10.0	7.9	6.5	397.3	-8.	360.
		3	25.8	21.3	19.1	17.0	13.6	10.2	8.3	6.5	5.2	4.2	217.5	44.	393.
		4	12.4	9.9	8.8	7.7	5.9	4.3	3.4	2.5	1.6	1.2	81.9	-46.	247.
		5	8.9	7.0	6.5	5.7	4.6	3.5	2.8	2.1	1.6	1.3	39.5	32.	179.
10700	2	1	49.2	41.5	37.4	34.1	27.5	21.1	17.3	13.9	11.0	9.1	1866.0	-26.	680.
		2	36.7	30.2	27.0	24.4	19.3	14.6	11.9	9.4	7.4	6.0	767.3	47.	850.
		3	22.5	18.4	16.5	14.8	11.7	8.7	7.1	5.6	4.4	3.6	244.5	-53.	540.
		4	16.8	13.4	12.2	10.9	8.6	6.5	5.3	4.2	3.3	2.6	105.8	31.	390.
10725	2	1	42.4	35.0	31.0	28.5	22.4	16.9	13.8	11.0	8.6	7.1	1473.0	30.	1150.
		2	38.2	31.3	27.7	25.8	20.2	15.3	12.5	9.9	7.7	6.3	322.8	-59.	760.
		3	33.0	27.2	24.3	22.6	17.8	13.6	11.3	9.0	6.9	5.6	114.4	36.	530.
10750	2	1	26.9	21.9	19.2	17.4	13.6	10.1	8.2	6.5	5.0	4.1	698.7	-35.	843.
		2	28.5	23.6	20.8	19.0	15.0	11.3	9.2	7.3	5.7	4.7	154.6	37.	560.
10775	2	1	26.1	21.2	18.5	16.5	13.0	9.6	7.8	6.1	4.7	3.8	394.2	42.	728.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 72W.IND
DATA FILE : 72W.DAT

LINE NO. : 724

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	2.7	1.9	1.8	1.6	1.2	.9	.7	.5	.4	.3	412.2	-28.	118.
		2	4.3	3.3	3.0	2.6	2.1	1.5	1.2	.9	.7	.6	149.2	7.	128.
		3	5.2	3.9	3.5	3.1	2.3	1.7	1.3	1.0	.8	.6	84.6	42.	145.
		4	5.0	3.7	3.3	2.9	2.2	1.6	1.2	.9	.7	.5	60.7	-47.	173.
		5	4.8	3.6	3.1	2.8	2.2	1.7	1.4	.9	.7	.5	34.7	20.	148.
10350	2	1	3.0	2.1	1.9	1.5	1.2	.9	.7	.5	.4	.3	530.7	-4.	124.
		2	4.9	3.7	3.4	2.8	2.2	1.6	1.3	.9	.7	.6	202.0	46.	142.
		3	4.5	3.4	3.2	2.5	2.1	1.5	1.2	.9	.8	.6	119.6	-53.	167.
		4	4.4	3.2	3.0	2.3	1.8	1.2	.9	.6	.4	.2	54.2	21.	127.
		5	5.1	3.8	3.5	2.7	2.2	1.6	1.3	1.0	.7	.5	40.0	-39.	141.
10375	2	1	3.7	2.5	2.3	2.1	1.4	1.0	.8	.6	.4	.3	502.6	37.	129.
		2	4.3	3.1	2.9	2.6	1.9	1.3	1.0	.8	.6	.4	218.2	-56.	168.
		3	4.3	2.9	2.9	2.6	1.8	1.3	1.0	.8	.7	.6	81.4	17.	125.
		4	5.1	3.5	3.5	3.0	2.1	1.5	1.2	.9	.5	.3	53.6	-30.	138.
		5	5.0	3.6	3.6	3.0	2.2	1.4	1.2	1.1	.8	.7	38.1	24.	147.
10400	2	1	3.8	2.8	2.5	2.2	1.6	1.2	.9	.7	.5	.4	574.6	-58.	150.
		2	4.3	3.2	2.9	2.5	1.9	1.4	1.1	.8	.7	.5	141.6	23.	111.
		3	4.6	3.5	3.2	2.8	2.1	1.5	1.2	.9	.6	.4	78.5	-47.	123.
		4	4.8	3.6	3.2	2.8	2.1	1.5	1.2	.9	.7	.5	52.4	36.	137.
		5	6.2	4.5	4.0	3.8	2.6	1.9	1.5	.7	.9	1.7	30.7	3.	120.
10425	2	1	4.6	3.2	2.9	2.6	1.9	1.3	1.1	.8	.6	.5	392.2	13.	91.
		2	4.9	3.8	3.3	2.9	2.2	1.6	1.2	.9	.7	.5	151.9	-52.	105.
		3	5.0	3.8	3.4	3.0	2.3	1.6	1.3	.9	.6	.4	89.0	35.	123.
		4	6.3	4.9	4.2	3.8	2.9	2.1	1.8	1.5	1.3	1.2	47.6	9.	110.
		5	5.1	3.9	3.6	3.0	2.1	1.3	1.2	.9	.5	.3	29.6	-9.	103.
10450	2	1	4.5	3.5	2.9	2.8	2.0	1.5	1.1	.9	.6	.5	644.7	-54.	140.

		2	4.9	3.8	3.2	3.0	2.2	1.6	1.3	1.0	.7	.6	225.3	41.	146.
		3	5.3	4.3	3.6	3.5	2.5	1.9	1.5	1.1	.8	.7	86.9	-2.	113.
		4	4.6	3.4	2.7	2.6	1.7	1.1	.8	.5	.3	.2	51.2	-4.	111.
		5	4.1	2.4	2.1	2.4	2.1	1.1	1.0	.9	.4	.1	26.3	-12.	85.
10475	2	1	5.1	4.2	3.4	3.1	2.4	1.7	1.3	1.1	.8	.6	886.6	35.	186.
		2	5.5	4.1	3.8	3.5	2.7	2.0	1.6	1.2	.9	.7	187.2	-6.	118.
		3	4.4	3.6	3.0	2.8	2.1	1.5	1.2	.9	.7	.5	92.8	3.	116.
		4	4.1	3.3	2.6	2.3	1.7	1.3	1.0	.8	.6	.5	39.8	-18.	83.
		5	2.3	2.1	1.3	1.4	1.8	1.7	1.5	.9	.3	.6	25.8	26.	81.
10500	2	1	7.0	5.4	4.6	4.0	3.1	2.2	1.8	1.3	1.0	.8	326.2	-7.	144.
		2	5.6	4.4	3.8	3.3	2.5	1.8	1.4	1.1	.8	.6	88.0	12.	117.
		3	4.6	3.7	3.2	2.7	2.1	1.5	1.2	.8	.6	.5	34.5	-6.	91.
		4	3.5	2.6	2.2	1.9	1.5	1.1	.9	.7	.4	.2	17.8	2.	78.
		5	-.6	.6	.1	.5	-.4	-.6	-.7	-.3	-.4	.1	10.8	-16.	71.
10525	2	1	5.9	4.6	3.7	3.4	2.6	1.8	1.5	1.1	.8	.7	422.8	4.	121.
		2	5.5	4.3	3.6	3.3	2.5	1.7	1.4	1.1	.8	.6	109.5	-44.	94.
		3	4.2	3.5	2.8	2.6	2.0	1.4	1.1	.8	.6	.4	57.6	37.	99.
		4	2.0	1.5	.9	.9	.5	.4	.3	.3	.3	.3	28.9	-9.	82.
		5	4.7	3.8	2.9	3.0	2.2	1.5	1.0	.5	.2	.2	15.7	4.	67.
10550	2	1	5.9	4.8	3.8	3.8	2.8	2.2	1.8	1.6	1.4	1.0	328.2	-38.	103.
		2	5.6	4.5	3.7	3.5	2.5	1.8	1.4	1.1	.8	.6	113.7	29.	107.
		3	3.0	2.4	1.9	1.7	1.3	.9	.7	.6	.4	.4	44.6	-14.	84.
		4	5.4	4.5	3.5	3.4	2.3	1.5	1.1	.8	.5	.3	23.9	9.	75.
		5	3.5	3.0	2.3	2.0	1.4	1.0	.6	.4	.3	.2	15.4	9.	73.
10575	2	1	4.6	3.6	3.0	2.6	2.0	1.4	1.1	.9	.7	.5	401.7	-6.	125.
		2	4.0	3.1	2.6	2.3	1.7	1.2	1.0	.7	.5	.4	110.8	-17.	103.
		3	6.4	5.2	4.5	3.9	3.0	2.1	1.6	1.2	.9	.6	47.2	1.	88.
		4	4.8	3.7	3.2	2.6	2.1	1.6	1.3	.9	.7	.6	31.3	32.	97.
		5	6.9	4.8	4.3	3.9	2.6	1.7	1.3	.7	.5	.1	39.7	-7.	185.
10600	2	1	4.2	3.2	2.5	2.2	1.7	1.1	.8	.6	.4	.4	271.8	-17.	89.
		2	7.6	6.2	5.3	4.8	3.7	2.6	2.1	1.5	1.1	.9	80.4	6.	80.
		3	5.1	4.0	3.4	3.0	2.3	1.5	1.1	.8	.6	.4	45.4	20.	89.
		4	7.4	5.7	5.0	4.2	3.1	2.3	1.5	1.1	.8	.5	52.9	-20.	174.
		5	16.5	13.3	11.8	10.6	8.6	6.5	5.2	4.2	3.1	2.6	45.6	-6.	226.
10625	2	1	9.3	7.6	6.5	5.8	4.5	3.2	2.5	1.9	1.4	1.2	283.5	-2.	98.
		2	7.8	6.3	5.3	4.8	3.7	2.6	2.0	1.5	1.0	.8	96.5	18.	101.
		3	7.5	5.8	4.9	4.2	3.2	2.2	1.7	1.2	.8	.6	89.5	-11.	186.
		4	17.8	14.9	13.4	12.1	9.7	7.1	5.9	4.7	3.6	3.0	65.0	-18.	226.
		5	6.5	5.8	4.0	3.0	4.0	2.6	1.5	1.3	1.0	.8	34.7	-18.	181.
10650	2	1	12.8	10.8	9.3	8.5	6.6	4.9	3.8	3.0	2.2	1.7	372.9	19.	124.
		2	9.9	8.0	6.6	5.9	4.5	3.1	2.4	1.8	1.2	.9	216.3	-2.	216.
		3	20.6	17.9	15.6	14.8	11.9	9.1	7.5	6.0	4.7	3.8	125.6	-30.	250.

		4	8.9	7.2	5.9	5.6	4.2	3.2	2.4	1.9	1.5	1.1	56.1	-12.	187.
		5	6.8	4.8	3.4	3.4	2.3	1.8	1.2	1.0	.7	.6	33.8	40.	169.
10675	2	1	12.9	10.0	8.6	8.0	6.0	4.2	3.3	2.5	1.8	1.4	618.2	-9.	206.
		2	26.6	23.0	20.7	19.4	15.5	11.9	9.7	7.7	6.0	4.9	265.4	-33.	265.
		3	13.2	10.8	9.7	9.2	7.2	5.4	4.4	3.4	2.7	2.1	94.5	-17.	188.
		4	10.9	8.5	7.4	6.9	5.3	3.9	3.2	2.4	1.8	1.4	53.2	46.	177.
		5	5.7	4.0	3.7	3.3	2.5	1.9	1.2	.9	.8	.4	29.7	-4.	148.
10700	2	1	41.9	35.1	30.9	28.3	22.6	17.1	14.0	11.2	8.7	7.2	1004.0	-42.	330.
		2	26.2	22.9	20.2	18.4	15.1	11.5	9.5	7.5	5.8	4.8	248.8	-8.	246.
		3	18.7	15.7	14.0	12.8	10.4	7.8	6.4	5.1	4.0	3.4	107.2	34.	210.
		4	13.6	11.2	10.0	8.9	7.2	5.4	4.4	3.4	2.5	1.9	54.5	-9.	180.
10725	2	1	35.6	29.1	25.7	23.2	18.2	13.5	10.9	8.5	6.6	5.3	1595.0	-29.	1310.
		2	39.8	32.7	29.1	26.4	20.7	15.4	12.5	9.7	7.6	6.1	394.2	23.	977.
		3	35.6	29.5	26.3	24.0	19.1	14.5	11.7	9.4	7.1	5.8	129.2	-4.	630.
10750	2	1	24.6	20.6	17.9	15.9	12.5	9.2	7.3	5.7	4.4	3.5	374.7	30.	1176.
		2	29.9	24.0	20.8	18.7	14.8	11.0	8.9	7.0	5.2	4.1	101.9	6.	959.
10775	2	1	22.4	17.7	15.3	13.8	10.6	7.8	6.3	4.9	3.7	3.0	202.4	1.	700.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 71W.IND
DATA FILE : 71W.DAT

LINE NO. : 714

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	22.2	17.7	15.5	13.6	10.6	7.6	6.1	4.7	3.6	2.9	473.1	0.	163.
		2	4.3	3.4	2.9	2.4	1.9	1.3	1.0	.7	.6	.4	113.9	-10.	117.
		3	3.6	2.9	2.6	2.1	1.7	1.2	1.0	.7	.5	.4	77.6	-21.	160.
		4	7.6	6.2	5.4	4.6	3.8	2.7	2.2	1.7	1.3	1.1	39.2	31.	135.
		5	2.5	1.8	1.5	1.0	1.0	.8	.6	.4	.3	.2	32.6	-24.	168.
10350	2	1	13.9	11.1	9.2	8.5	6.3	4.6	3.6	2.8	2.1	1.8	351.0	-9.	131.
		2	4.8	3.4	3.2	2.6	2.5	1.7	1.5	1.2	.9	.7	134.1	-14.	150.
		3	6.8	5.5	4.6	4.2	3.2	2.3	1.9	1.4	1.1	.9	55.8	30.	124.
		4	2.0	1.6	1.1	1.1	.9	.5	.4	.5	.3	.1	42.1	-33.	157.
		5	4.3	2.8	4.6	5.9	3.8	1.7	2.1	1.0	.7	.5	27.3	18.	153.
10375	2	1	10.4	8.2	7.0	6.3	4.8	3.5	2.8	2.2	1.7	1.3	360.9	-26.	143.
		2	8.1	6.5	5.5	4.9	3.7	2.7	2.1	1.6	1.3	1.0	96.1	27.	115.
		3	2.4	2.0	1.5	1.4	1.1	.7	.6	.5	.3	.2	61.2	-34.	145.
		4	7.0	5.8	4.9	4.3	3.4	2.5	2.1	1.5	1.2	1.0	35.5	21.	140.
		5	3.3	3.3	2.9	3.2	1.8	1.1	.6	1.0	.4	.4	16.7	-1.	99.
10400	2	1	6.2	4.9	4.3	4.0	2.9	2.1	1.6	1.3	1.0	.8	214.6	20.	96.
		2	1.9	1.5	1.1	1.0	.8	.5	.4	.3	.3	.2	97.9	-25.	132.
		3	6.3	5.3	4.4	4.1	3.1	2.3	1.8	1.4	1.1	.9	47.8	14.	128.
		4	4.1	3.2	2.6	2.5	1.8	1.3	.9	.8	.7	.6	20.8	0.	93.
		5	3.0	2.8	1.9	2.0	2.2	1.2	1.4	.6	.5	.3	15.3	-7.	103.
10425	2	1	1.2	.8	.6	.4	.3	.2	.1	.1	.1	.1	379.5	-28.	148.
		2	6.5	5.1	4.5	4.0	3.0	2.2	1.7	1.3	1.0	.8	109.1	11.	128.
		3	3.2	2.1	1.9	1.6	1.2	.9	.7	.6	.5	.4	40.5	1.	95.
		4	3.4	2.2	2.0	1.6	1.0	.6	.6	.4	.2	.0	25.8	-7.	101.
		5	5.3	4.2	3.8	3.6	2.3	1.5	.5	.3	.0	-.1	21.8	-7.	128.
10450	2	1	7.5	5.8	5.1	4.7	3.5	2.6	2.1	1.6	1.3	1.0	286.4	9.	94.

		2	4.2	3.1	2.7	2.5	1.8	1.1	.9	.5	.3	.3	78.1	6.	77.
		3	4.5	3.3	3.2	3.1	2.4	2.0	1.8	1.6	1.4	1.2	45.6	-13.	90.
		4	4.6	3.3	2.8	2.5	1.6	.8	.4	.0	-.1	-.2	34.8	-7.	114.
		5	3.6	3.4	1.9	3.3	1.4	1.0	.7	.5	.3	.3	18.1	13.	89.
10475	2	1	2.8	1.9	1.5	1.3	.8	.5	.3	.2	.2	.1	471.9	-1.	95.
		2	4.5	3.6	3.2	2.9	2.2	1.6	1.3	1.0	.8	.6	193.2	-14.	117.
		3	5.4	4.3	3.6	3.4	2.4	1.8	1.4	1.1	.8	.6	117.9	85.	142.
		4	4.3	3.2	2.7	2.5	1.8	1.2	1.0	.7	.6	.4	53.0	22.	107.
		5	3.0	1.9	1.5	1.2	.2	.3	.4	.1	.4	.5	33.7	5.	102.
10500	2	1	4.9	3.9	3.4	3.1	2.3	1.7	1.3	1.1	.8	.6	341.5	-14.	164.
		2	7.1	5.6	4.9	4.4	3.3	2.5	1.9	1.5	1.2	.9	126.8	-14.	183.
		3	5.4	4.0	3.6	3.3	2.4	1.7	1.4	1.1	.8	.7	45.9	18.	132.
		4	4.0	3.1	2.6	2.2	1.5	1.0	.9	.7	.5	.2	23.3	3.	112.
		5	1.4	.0	-.4	.3	-.3	.0	-.3	-.2	.0	.0	12.7	4.	91.
10525	2	1	7.4	5.8	5.0	4.4	3.3	2.4	1.9	1.4	1.1	.9	480.2	-13.	167.
		2	5.4	4.2	3.7	3.2	2.5	1.7	1.3	1.0	.8	.6	109.7	7.	114.
		3	3.5	2.7	2.3	2.0	1.5	1.0	.8	.5	.4	.6	53.6	7.	112.
		4	1.5	.7	.5	.2	.1	.0	.0	.2	.0	-.4	25.5	15.	88.
		5	6.9	4.8	5.9	5.8	2.7	2.1	2.1	1.6	.8	.0	15.7	19.	82.
10550	2	1	5.1	3.8	3.5	2.8	2.2	1.6	1.3	1.0	.7	.6	289.6	11.	124.
		2	5.1	3.7	3.4	2.7	2.1	1.5	1.2	.8	.6	.5	88.2	15.	114.
		3	1.3	.8	1.0	.5	.5	.3	.3	.2	.0	.1	37.7	-16.	97.
		4	8.2	4.8	3.5	2.0	.7	1.9	2.2	1.8	1.1	1.8	18.1	38.	77.
		5	7.9	8.6	9.7	8.9	8.5	4.2	2.6	1.5	1.7	.0	13.5	-29.	87.
10575	2	1	5.2	3.6	3.2	2.6	1.9	1.4	1.0	.7	.6	.4	469.0	12.	123.
		2	2.9	2.3	2.3	1.8	1.4	.9	.7	.5	.4	.2	132.1	-7.	104.
		3	8.1	6.7	6.2	5.4	4.3	3.2	2.5	1.9	1.5	1.1	65.1	-10.	102.
		4	8.9	7.3	6.7	5.9	4.6	3.4	2.6	2.0	1.5	1.1	36.0	8.	94.
		5	7.8	6.3	5.8	4.8	3.7	2.6	2.1	1.4	1.0	.7	19.5	15.	77.
10600	2	1	4.9	3.2	2.6	2.2	1.6	1.1	.9	.6	.5	.4	323.3	-8.	92.
		2	10.5	8.6	7.6	7.0	5.4	4.0	3.2	2.5	1.9	1.5	112.3	-11.	96.
		3	9.6	8.1	7.4	6.8	5.5	4.1	3.4	2.5	1.9	1.6	54.4	2.	93.
		4	9.6	7.8	7.3	6.7	5.2	3.7	2.9	2.4	1.8	1.3	25.8	18.	74.
		5	4.8	3.4	3.5	2.9	2.5	1.9	1.6	1.2	1.0	.8	34.2	-37.	146.
10625	2	1	13.2	10.3	9.1	8.1	6.3	4.6	3.7	2.8	2.2	1.7	406.9	-16.	190.
		2	13.8	11.5	10.4	9.4	7.4	5.5	4.4	3.4	2.6	2.0	100.3	-3.	141.
		3	11.1	9.4	8.5	7.7	6.2	4.5	3.6	2.8	2.0	1.6	36.8	9.	103.
		4	6.2	4.8	4.4	3.7	3.0	2.1	1.7	1.3	1.0	.9	38.1	-22.	178.
		5	9.4	7.4	6.5	5.3	4.3	3.0	2.4	1.8	1.3	.9	39.6	26.	278.
10650	2	1	17.5	14.5	12.7	11.6	9.2	6.9	5.5	4.3	3.2	2.5	261.1	-23.	122.
		2	15.8	13.4	11.9	10.9	8.6	6.4	5.1	4.0	3.0	2.3	72.5	14.	102.
		3	8.6	7.1	6.2	5.7	4.5	3.3	2.6	2.0	1.5	1.1	61.3	-30.	172.

		4	11.5	9.2	7.8	7.3	5.4	4.0	3.1	2.4	1.8	1.4	51.4	23.	240.
		5	9.8	7.4	5.9	5.7	4.0	2.9	2.2	1.5	1.1	.8	45.9	-23.	322.
10675	2	1	20.5	17.0	15.3	13.8	11.0	8.3	6.7	5.2	3.9	3.1	210.5	9.	132.
		2	16.0	13.3	12.0	10.7	8.7	6.5	5.2	4.0	3.0	2.4	113.3	-28.	213.
		3	15.9	12.7	11.5	10.0	8.1	6.0	4.8	3.7	2.8	2.1	74.0	55.	278.
		4	15.6	12.6	11.7	9.9	8.0	5.8	4.6	3.6	2.5	2.0	54.4	-51.	341.
		5	12.5	9.0	8.2	6.5	4.9	3.5	2.8	1.9	1.8	.9	26.7	27.	251.
10700	2	1	16.7	13.7	12.0	11.0	8.7	6.5	5.2	4.0	3.1	2.4	331.6	-27.	216.
		2	21.4	17.0	14.7	13.3	10.5	7.8	6.2	4.9	3.8	2.9	139.0	66.	272.
		3	17.5	15.4	13.7	13.1	10.4	7.9	6.5	5.0	3.9	3.2	86.8	-68.	340.
		4	18.5	13.3	11.4	10.5	7.9	6.1	4.8	3.5	2.7	2.1	34.6	12.	226.
10725	2	1	14.1	12.3	10.8	9.7	7.7	5.7	4.6	3.6	2.8	2.2	291.8	61.	366.
		2	25.1	18.9	16.5	14.7	11.5	8.4	6.7	5.2	3.9	3.0	124.2	-71.	467.
		3	22.3	15.5	13.5	11.9	9.2	6.8	5.1	3.9	2.7	2.0	38.1	11.	286.
10750	2	1	24.9	18.9	16.1	14.5	11.0	8.1	6.4	5.0	3.9	3.1	424.6	-71.	1111.
		2	29.4	22.4	18.9	17.0	13.3	9.8	7.9	6.2	4.9	3.9	85.0	22.	668.
10775	2	1	28.8	22.6	19.4	17.2	13.3	9.9	7.9	6.2	4.8	3.8	246.8	29.	860.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 70W.IND
DATA FILE : 70W.DAT

LINE NO. : 704

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10325	2	1	7.2	5.6	4.7	4.4	3.4	2.4	2.0	1.5	1.2	1.0	661.2	12.	152.
		2	6.6	4.8	4.1	3.6	2.7	1.9	1.5	1.1	.8	.7	203.2	-19.	140.
		3	3.7	2.8	2.2	2.1	1.5	1.0	.8	.6	.4	.4	96.3	0.	132.
		4	6.0	4.6	3.9	3.6	2.7	2.0	1.6	1.3	1.0	.8	49.3	-3.	113.
		5	5.3	3.8	3.2	2.9	2.1	1.6	1.2	.9	.6	.5	42.2	-14.	145.
10350	2	1	3.4	2.3	1.7	1.5	1.0	.4	.1	.0	-.1	.4	212.5	-21.	119.
		2	3.7	2.4	1.9	1.7	1.1	.7	.6	.4	.3	.2	72.7	8.	122.
		3	5.8	4.4	3.7	3.4	2.4	1.7	1.3	.8	.7	.7	31.7	-17.	106.
		4	4.8	3.4	2.9	2.7	1.8	1.3	1.0	.8	.4	.0	25.1	-3.	140.
		5	4.5	3.0	2.6	2.5	1.5	.9	.5	.3	.1	-.1	14.3	15.	120.
10375	2	1	3.0	2.1	1.6	1.3	.9	.6	.5	.3	.2	.2	365.2	8.	127.
		2	8.2	6.4	5.2	4.5	3.5	2.5	2.0	1.5	1.2	1.0	108.9	-19.	113.
		3	5.5	4.5	3.7	3.3	2.6	1.3	.8	.2	.0	-.1	73.8	11.	154.
		4	4.4	3.4	2.7	2.2	1.8	2.3	2.3	2.6	2.6	2.5	31.1	6.	108.
		5	5.3	4.3	3.5	3.0	2.6	1.7	1.5	1.1	.8	.6	23.7	-17.	124.
10400	2	1	7.7	5.8	5.0	4.6	3.5	2.5	2.0	1.6	1.2	1.0	289.8	-25.	109.
		2	6.6	4.7	4.1	3.8	2.7	1.9	1.5	1.1	.9	.7	135.6	20.	153.
		3	6.4	5.0	4.3	3.8	2.8	2.0	1.6	1.2	.9	.7	48.1	-16.	108.
		4	5.8	4.3	3.8	3.5	2.6	1.8	1.5	1.3	.8	.5	33.1	-3.	125.
		5	4.7	3.4	2.9	2.5	1.8	1.2	.8	.4	.5	.6	23.8	-1.	135.
10425	2	1	4.5	3.3	2.8	2.5	1.9	1.4	1.1	.8	.6	.4	532.1	12.	125.
		2	6.2	4.6	4.0	3.4	2.5	1.6	1.2	.9	.8	.7	139.3	-20.	98.
		3	4.7	3.6	3.1	2.8	2.1	1.5	1.2	.9	.7	.6	78.5	-11.	110.
		4	5.7	4.3	3.7	3.3	2.5	1.8	1.4	1.1	.7	.5	50.1	9.	117.
		5	4.2	3.1	2.6	2.2	1.6	1.1	.9	.7	.7	.7	29.6	9.	104.
10450	2	1	5.8	4.2	3.7	3.2	2.3	1.7	1.3	1.0	.8	.6	341.2	8.	95.

		2	5.6	4.1	3.8	3.2	2.5	1.7	1.4	1.0	.8	.6	123.3	-4.	103.
		3	6.4	4.8	4.3	3.7	2.8	1.9	1.6	1.0	.9	.7	67.9	-3.	113.
		4	5.0	3.6	3.2	2.8	2.1	1.4	1.1	.7	.7	.6	36.1	19.	100.
		5	5.9	4.2	3.7	3.1	2.3	1.6	1.4	.9	.7	.4	27.4	8.	114.
10475	2	1	3.5	2.9	2.2	1.9	1.3	.7	.4	.1	-.1	-.3	288.1	-15.	150.
		2	6.1	5.1	4.0	3.6	2.7	2.0	1.6	1.2	.8	.7	95.5	-10.	150.
		3	4.7	4.1	3.1	2.8	2.2	1.8	1.5	1.2	.8	.5	41.8	22.	130.
		4	5.6	4.9	3.7	3.4	2.5	1.5	1.1	.8	.6	.7	25.7	14.	134.
		5	3.7	3.0	2.2	2.0	1.3	1.1	.9	.5	.5	.5	16.0	-28.	125.
10500	2	1	5.7	4.2	3.5	3.0	2.2	1.5	1.2	.9	.6	.5	328.0	-9.	171.
		2	5.2	3.9	3.3	2.8	2.1	1.5	1.1	.8	.6	.5	89.9	20.	141.
		3	7.1	5.6	4.7	4.2	3.2	2.3	1.8	1.4	1.0	.8	45.1	-8.	141.
		4	4.9	3.7	3.0	2.5	1.9	1.2	1.1	.7	.5	.4	25.4	0.	132.
		5	4.4	3.3	2.5	2.1	1.6	1.1	1.1	.8	.8	.7	13.1	18.	103.
10525	2	1	4.2	3.2	2.7	2.2	1.8	1.2	1.0	.7	.5	.4	422.0	13.	133.
		2	7.0	5.2	4.5	3.8	3.0	2.1	1.7	1.3	1.0	.8	155.0	1.	146.
		3	5.2	4.0	3.4	3.0	2.3	1.6	1.3	1.0	.7	.6	72.2	-24.	136.
		4	4.6	3.2	2.7	2.2	1.7	1.1	.8	.6	.4	.4	31.2	29.	98.
		5	8.1	6.2	5.4	4.8	3.7	2.7	2.2	1.6	1.2	.9	21.6	-4.	102.
10550	2	1	5.0	3.9	3.1	2.7	2.1	1.5	1.2	.9	.6	.5	803.8	3.	188.
		2	6.8	5.5	4.5	4.0	3.0	2.2	1.7	1.3	.9	.7	213.8	-14.	150.
		3	4.2	3.3	2.5	2.2	1.6	1.1	.8	.6	.3	.3	85.2	11.	120.
		4	7.8	6.6	5.7	5.1	4.0	2.8	2.2	1.9	1.5	1.2	46.5	3.	109.
		5	14.4	12.2	10.8	9.9	7.9	5.9	4.8	3.8	2.9	2.4	20.2	-5.	71.
10575	2	1	6.9	5.1	4.4	4.0	2.8	2.0	1.6	1.2	.9	.7	514.1	-26.	181.
		2	6.3	4.5	3.8	3.5	2.4	1.7	1.3	1.0	.8	.6	131.9	0.	139.
		3	8.1	6.8	6.1	5.7	4.3	3.1	2.4	1.8	1.3	1.2	56.4	5.	119.
		4	14.2	11.8	10.6	9.9	7.8	5.8	4.6	3.6	2.7	1.9	21.9	-1.	77.
		5	9.2	7.1	6.4	6.1	4.5	3.5	2.7	2.5	1.9	1.1	22.2	6.	117.
10600	2	1	8.3	6.4	5.0	4.6	3.2	2.3	1.7	1.3	1.1	.7	377.4	4.	191.
		2	10.5	8.7	7.3	6.7	5.1	3.7	2.9	2.2	1.3	1.4	100.9	8.	153.
		3	15.3	13.3	11.7	10.9	8.6	6.4	5.1	4.0	2.8	2.3	31.0	-11.	94.
		4	10.8	9.0	7.9	7.3	5.7	4.3	3.4	2.5	1.5	1.4	27.0	26.	136.
		5	-.2	-.4	-.2	-.1	-.3	-.3	-.3	-.2	-.7	-.2	22.6	-25.	171.
10625	2	1	8.2	6.2	5.4	4.7	3.6	2.5	2.0	1.5	1.1	.9	644.9	-8.	238.
		2	18.5	15.6	14.0	12.7	10.1	7.5	6.0	4.6	3.5	2.7	99.5	-11.	110.
		3	12.6	10.5	9.7	8.6	6.9	5.1	4.0	3.1	2.3	1.8	68.6	18.	151.
		4	1.6	1.1	1.2	.9	.8	.6	.5	.3	.2	.1	48.8	-22.	180.
		5	10.9	8.2	7.4	6.4	4.8	3.5	2.7	2.0	1.5	1.2	50.1	-7.	277.
10650	2	1	19.6	16.2	14.2	13.0	10.3	7.7	6.2	4.8	3.6	2.8	156.7	-10.	91.
		2	16.8	14.2	12.2	11.3	8.9	6.5	5.2	4.0	3.0	2.4	80.1	25.	140.
		3	4.8	4.4	3.5	3.4	2.7	2.1	1.8	1.4	.9	.7	48.6	-32.	169.

		4	12.5	10.2	8.1	7.4	5.7	3.9	3.0	2.3	1.7	1.3	44.7	33.	259.
		5	16.0	13.4	10.8	9.9	7.6	5.4	4.7	3.4	2.6	2.1	29.8	-8.	259.
10675	2	1	22.9	19.1	16.8	15.5	12.3	9.2	7.4	5.8	4.4	3.5	379.7	15.	216.
		2	14.8	12.5	11.0	10.1	8.1	6.1	4.9	3.8	2.9	2.3	128.6	-38.	220.
		3	19.9	16.3	14.2	12.9	10.1	7.5	6.0	4.7	3.6	2.9	86.5	36.	295.
		4	22.0	17.8	15.6	14.0	11.0	8.2	6.6	5.2	4.0	3.4	52.8	13.	301.
		5	14.5	11.4	10.1	9.1	7.0	5.2	4.2	3.4	2.8	2.3	33.6	-23.	287.
10700	2	1	11.3	9.3	8.1	7.4	5.9	4.4	3.5	2.7	2.0	1.6	515.4	-39.	279.
		2	23.5	19.4	16.9	15.5	12.1	8.9	7.1	5.5	4.1	3.3	197.5	43.	320.
		3	23.7	19.8	17.5	16.1	12.7	9.4	7.6	5.9	4.4	3.5	96.6	-2.	313.
		4	17.2	14.1	12.5	11.3	8.8	6.4	5.0	3.8	2.8	2.2	55.2	-14.	298.
		5	13.1	10.9	10.1	7.9	5.7	4.9	4.0	2.7	2.2	2.2	27.6	-15.	224.
10725	2	1	25.0	20.0	17.3	15.6	12.1	8.9	7.2	5.6	4.3	3.4	316.4	34.	827.
		2	30.4	24.8	21.7	19.7	15.4	11.4	9.2	7.1	5.5	4.4	82.5	-2.	648.
		3	22.9	18.5	16.2	14.8	11.4	8.4	6.8	5.2	3.9	3.1	34.4	-12.	539.
		4	19.9	15.9	13.9	13.3	9.8	7.4	6.0	4.5	3.2	2.5	14.7	1.	383.
		5	14.4	11.4	10.4	8.8	6.5	4.7	3.9	2.4	1.5	1.1	7.5	1.	293.
10750	2	1	33.0	27.1	23.7	21.6	17.0	12.7	10.3	8.1	6.3	5.2	979.8	-7.	1139.
		2	25.4	21.1	18.5	16.9	13.5	10.1	8.3	6.5	5.1	4.2	283.4	-6.	988.
		3	22.0	18.3	16.2	15.0	12.0	9.1	7.5	6.0	4.6	3.8	115.5	-31.	800.
		4	16.3	13.4	11.8	10.9	8.8	6.7	5.4	4.3	3.3	2.6	37.9	23.	440.
		5	16.5	12.6	12.2	11.1	8.4	6.8	6.4	4.0	4.0	4.8	19.0	22.	330.
10775	2	1	27.8	22.6	19.7	17.7	13.9	10.3	8.3	6.6	5.1	4.2	1231.0	4.	1280.
		2	30.0	24.9	21.9	19.8	15.6	11.7	9.5	7.6	5.9	4.9	301.9	-16.	947.
		3	25.6	21.4	19.0	17.2	13.7	10.4	8.3	6.6	5.2	4.2	102.9	4.	640.
		4	26.5	21.8	19.1	17.3	13.5	10.1	8.0	6.4	4.9	4.0	43.7	20.	457.
		5	30.2	24.9	21.8	19.6	15.6	11.9	9.5	7.5	5.9	4.9	58.3	3.	914.
10800	2	1	26.4	21.8	18.8	16.9	13.3	9.9	8.0	6.3	4.9	4.0	922.2	-36.	877.
		2	26.4	21.8	18.9	17.1	13.6	10.1	8.2	6.5	5.0	4.1	229.0	33.	653.
		3	28.1	23.4	20.2	18.2	14.4	10.6	8.5	6.5	4.9	3.9	95.2	2.	542.
		4	33.2	27.8	24.2	21.9	17.6	13.0	10.5	8.3	6.4	5.3	123.1	30.	1170.
		5	19.2	16.0	13.7	12.4	10.0	7.3	5.9	4.8	4.0	3.3	48.6	-68.	693.
10825	2	1	20.0	16.2	13.9	12.6	9.8	7.3	5.9	4.6	3.5	2.9	641.0	5.	1118.
		2	23.2	18.7	16.0	14.4	11.1	8.0	6.4	5.0	3.7	2.9	140.0	7.	732.
		3	31.8	26.2	22.8	20.6	16.1	11.8	9.5	7.4	5.7	4.6	139.1	21.	1450.
		4	17.1	16.8	14.3	12.8	10.0	7.1	5.6	4.3	3.0	2.4	49.2	-70.	857.
		5	38.5	31.5	27.9	24.9	19.8	14.3	11.6	9.2	6.9	5.5	43.9	16.	1149.
10850	2	1	17.6	14.2	12.3	11.6	8.6	6.3	5.0	3.9	3.0	2.4	1028.0	-1.	870.
		2	31.5	26.3	23.2	21.2	16.8	12.5	10.1	7.9	6.1	4.9	606.5	14.	1544.
		3	22.9	19.0	16.7	15.4	12.2	9.1	7.4	5.9	4.7	3.8	189.7	-42.	960.
		4	41.7	34.8	30.8	28.3	22.6	17.2	14.0	11.2	8.8	7.3	150.9	9.	1280.
		5	64.7	54.5	48.2	44.1	35.4	27.0	22.2	17.8	14.2	11.8	130.4	9.	1650.

10875	2	1	31.7	26.2	23.2	21.0	16.6	12.4	10.0	7.9	6.1	4.9	1091.0	6.	1100.
		2	25.6	21.8	19.7	17.9	14.4	10.9	8.9	7.0	5.4	4.4	262.9	-53.	798.
		3	43.5	36.7	32.9	29.8	23.9	18.1	14.8	11.7	9.1	7.4	189.7	3.	1150.
		4	65.8	55.3	49.6	45.0	36.1	27.3	22.3	17.7	13.8	11.2	150.7	14.	1520.
		5	62.6	52.7	47.7	43.1	34.8	26.4	21.6	17.1	13.3	10.8	81.4	-38.	1236.
10900	2	1	26.6	21.0	17.2	15.0	11.2	7.8	6.0	4.5	3.3	2.6	166.8	-49.	580.
		2	51.1	44.2	39.2	35.8	29.1	22.2	18.3	14.6	11.4	9.4	89.1	-7.	932.
		3	71.9	62.5	55.2	50.4	41.0	31.2	25.9	20.6	16.2	13.4	80.7	36.	1680.
		4	68.4	60.5	52.8	48.2	39.8	30.2	25.4	20.4	16.1	13.5	33.3	-30.	1160.
		5	71.1	63.4	55.1	50.5	41.6	30.7	26.4	19.9	16.0	12.9	14.3	6.	750.
10925	2	1	52.9	44.7	40.1	36.5	29.3	22.3	18.3	14.5	11.4	9.4	655.4	-1.	1469.
		2	80.2	68.1	60.3	55.6	44.9	34.0	27.9	22.2	17.4	14.3	429.3	29.	2888.
		3	75.5	64.8	57.5	52.9	42.9	32.9	27.0	21.6	17.0	13.9	137.8	-39.	1850.
		4	77.9	66.8	58.8	54.2	43.8	33.5	27.7	22.1	17.3	14.3	52.8	13.	1184.
		5	78.0	67.6	58.3	54.0	43.8	33.8	27.8	22.3	17.6	14.5	27.1	-46.	913.
10950	2	1	68.1	57.4	51.3	46.8	37.4	28.4	23.1	18.4	14.4	11.7	1037.0	22.	1350.
		2	70.2	60.0	53.9	49.7	39.9	30.6	25.1	20.0	15.8	12.9	268.7	-28.	1054.
		3	71.2	60.8	54.6	50.2	40.4	30.9	25.4	20.3	15.9	13.1	107.2	0.	830.
		4	71.1	60.9	54.9	50.7	40.7	31.4	25.8	20.6	16.2	13.2	48.3	-46.	632.
		5	54.6	46.1	41.2	37.9	30.1	22.8	18.7	14.8	11.5	9.3	38.6	47.	757.
10975	2	1	71.1	61.0	54.4	49.5	39.9	30.5	25.0	19.8	15.7	13.0	298.6	-24.	937.
		2	72.0	61.7	55.9	50.7	41.2	31.7	26.6	21.0	16.8	13.9	90.0	-4.	848.
		3	73.5	64.1	56.9	51.8	42.6	32.8	26.6	22.2	17.7	15.1	40.5	-48.	761.
		4	53.6	46.5	41.8	37.5	31.0	24.1	20.3	16.5	13.4	11.9	26.0	49.	815.
		5	55.5	48.7	41.4	36.2	31.4	24.3	22.9	16.0	15.4	12.9	11.8	22.	554.
11000	2	1	83.3	70.5	62.7	57.5	46.0	34.9	28.6	22.7	17.8	14.6	378.4	29.	1188.
		2	82.4	70.1	62.6	57.5	46.2	35.2	28.8	23.0	17.9	14.7	119.4	-49.	1124.
		3	57.4	48.4	43.0	39.3	31.3	23.5	19.1	15.1	11.7	9.5	56.6	39.	1063.
		4	58.5	48.9	43.2	39.4	31.0	23.1	18.7	14.6	11.1	8.9	24.1	22.	756.
		5	72.3	60.6	53.8	48.5	38.2	28.3	22.9	17.8	13.6	10.7	23.5	-17.	1108.
11025	2	1	79.6	67.2	59.5	54.6	43.6	33.0	26.9	21.4	16.7	13.7	428.4	-47.	1490.
		2	60.4	51.4	45.5	41.9	33.6	25.4	20.8	16.5	12.9	10.5	100.4	38.	1050.
		3	57.4	48.6	42.5	39.1	31.3	23.7	19.4	15.2	11.1	8.0	47.0	18.	980.
		4	72.2	61.0	53.3	48.5	38.6	28.6	23.1	18.2	15.0	13.2	37.3	-5.	1300.
		5	94.7	79.7	69.3	63.2	50.1	37.3	30.3	23.9	18.5	14.8	22.0	14.	1150.
11050	2	1	62.5	52.0	46.5	42.0	33.6	25.4	20.8	16.4	12.9	10.5	356.3	47.	745.
		2	57.3	47.4	42.4	38.1	30.3	22.7	18.4	14.5	11.2	9.1	123.0	40.	772.
		3	72.1	60.1	53.7	48.4	38.6	28.9	23.6	18.5	14.3	11.6	96.8	-34.	1212.
		4	96.8	80.0	71.4	64.1	51.0	38.2	31.1	24.3	18.7	15.1	49.5	19.	1035.
		5	86.1	71.4	63.9	57.0	45.7	34.0	27.6	21.4	16.3	13.3	26.7	-8.	837.
11075	2	1	54.8	45.6	40.1	36.3	28.8	21.6	17.6	13.9	10.7	8.7	237.9	43.	747.
		2	70.0	58.6	51.7	47.0	37.3	28.1	22.9	18.2	14.2	11.6	147.0	-29.	1384.

		3	95.0	79.9	70.6	64.3	51.2	38.6	31.5	25.1	19.6	16.0	67.4	12.	1267.
		4	87.8	73.7	65.5	59.6	47.6	36.2	29.6	23.7	18.7	15.4	29.9	-3.	937.
		5	81.7	68.8	61.5	56.1	45.0	34.5	28.4	22.9	18.2	15.2	15.1	28.	709.
11100	2	1	55.5	45.7	40.1	36.3	28.5	21.3	17.3	13.6	10.6	8.7	636.0	-33.	1248.
		2	88.4	73.8	65.3	59.3	47.0	35.3	28.7	22.8	17.8	14.5	242.3	16.	1426.
		3	83.9	70.9	63.2	57.7	46.1	35.0	28.8	23.0	18.1	15.0	86.0	-18.	1010.
		4	81.9	69.4	61.6	56.4	45.3	34.6	28.4	22.6	18.0	14.7	36.9	34.	723.
11125	2	1	66.8	54.6	48.2	43.5	34.2	25.5	20.7	16.3	12.7	10.3	638.5	25.	1055.
		2	71.8	59.7	53.5	48.4	38.6	29.0	23.5	18.6	14.5	11.7	171.5	-12.	850.
		3	72.1	60.2	54.3	49.0	39.3	29.8	24.2	19.2	14.9	12.1	62.0	22.	613.
11150	2	1	57.2	47.3	11.6	37.5	29.6	22.1	17.9	14.1	11.0	8.9	265.1	-4.	1040.
		2	63.0	52.5	46.6	42.7	34.1	25.8	21.1	16.8	12.9	10.6	66.1	27.	778.
11175	2	1	53.4	43.6	38.3	34.4	26.9	19.8	15.9	12.4	9.5	7.6	145.5	26.	650.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 69W.IND
DATA FILE : 69W.DAT

LINE NO. : 694

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10675	2	1	7.4	6.5	5.9	5.8	4.6	3.5	2.9	2.3	1.7	1.4	382.9	-4.	218.
		2	11.9	10.1	9.0	8.6	6.8	5.1	4.1	3.2	2.4	1.9	214.7	5.	367.
		3	34.4	28.6	25.3	23.2	18.3	13.7	11.1	8.9	7.0	5.7	77.7	-5.	265.
		4	20.9	17.5	15.5	14.5	11.6	8.8	7.3	6.0	4.8	4.1	40.0	19.	228.
		5	22.0	18.7	16.7	16.1	12.8	10.1	8.5	7.1	6.0	5.4	21.7	-28.	185.
10700	2	1	15.6	12.5	10.4	9.4	6.9	4.8	3.7	2.8	2.1	1.7	3524.0	0.	2210.
		2	39.2	32.4	28.2	25.6	20.0	14.7	11.9	9.3	7.2	5.9	680.6	-6.	1282.
		3	26.3	22.2	19.7	17.9	14.2	10.7	8.7	6.9	5.4	4.5	239.6	8.	900.
		4	26.8	22.8	20.0	18.4	14.6	10.9	8.9	7.1	5.5	4.6	99.4	-20.	624.
		5	16.5	13.5	11.8	10.8	8.3	6.1	4.8	3.8	3.0	2.4	38.8	29.	365.
10725	2	1	41.0	34.2	30.2	27.4	21.6	16.1	13.1	10.4	8.1	6.7	1531.0	-9.	1370.
		2	28.3	23.8	21.3	19.6	15.6	11.9	9.7	7.8	6.1	5.1	408.1	12.	1098.
		3	25.0	21.5	19.5	17.9	14.5	11.2	9.2	7.4	5.9	4.9	155.8	-30.	830.
		4	16.7	13.9	12.5	11.5	9.2	7.1	5.8	4.7	4.1	3.3	54.9	37.	492.
		5	20.9	17.9	15.4	13.6	10.5	7.7	5.9	5.1	2.7	2.7	37.9	-18.	510.
10750	2	1	36.1	30.3	26.8	24.2	19.3	14.6	11.9	9.5	7.5	6.2	1672.0	9.	1500.
		2	32.0	27.6	24.6	22.5	18.0	13.7	11.2	8.9	7.0	5.4	506.9	-26.	1364.
		3	21.6	18.4	16.5	15.0	11.9	9.0	7.3	5.8	4.5	3.7	180.7	23.	970.
		4	25.7	21.6	19.0	17.2	13.6	10.2	8.3	6.6	5.2	4.3	110.2	-11.	980.
		5	28.6	23.8	20.7	19.0	14.8	11.1	9.0	7.2	5.5	4.6	59.0	-4.	793.
10775	2	1	36.9	30.4	26.6	23.8	18.7	13.9	11.3	8.9	7.0	5.7	1324.0	-24.	1180.
		2	29.5	24.2	21.3	19.0	14.8	10.9	8.8	6.9	5.4	4.4	368.8	3.	992.
		3	32.7	26.9	23.6	21.1	16.4	12.2	9.8	7.6	5.9	4.8	247.7	-11.	1330.
		4	36.8	30.3	26.6	23.7	18.5	13.6	10.9	8.6	6.6	5.4	101.3	15.	900.
		5	38.1	30.4	25.8	22.3	17.5	14.4	10.8	8.7	7.1	5.8	76.0	30.	1022.
10800	2	1	25.7	20.7	18.0	16.1	12.4	9.0	7.2	5.7	4.4	3.6	1203.0	39.	1020.

		2	30.7	24.9	21.6	19.3	14.9	10.7	8.6	6.7	5.2	4.3	476.8	-7.	1213.
		3	36.6	29.7	25.9	23.2	17.9	13.0	10.4	8.2	6.3	5.1	282.8	-16.	1430.
		4	38.8	31.5	27.5	24.5	18.9	13.7	10.9	8.5	6.6	5.4	143.7	36.	1210.
		5	35.4	28.7	25.1	22.3	17.2	12.3	9.8	7.7	5.9	4.7	97.7	-35.	1243.
10825	2	1	27.6	22.1	19.2	17.0	13.0	9.4	7.4	5.8	4.4	3.6	2204.0	-41.	1970.
		2	33.3	27.3	24.0	21.4	16.6	12.0	9.6	7.5	5.7	4.6	610.2	8.	1642.
		3	35.5	29.0	25.4	22.7	17.6	12.8	10.3	7.9	6.1	4.8	327.3	33.	1750.
		4	35.4	28.7	25.3	22.5	17.4	12.5	9.9	7.7	5.9	4.9	205.8	-29.	1840.
		5	46.1	38.0	33.7	30.2	23.7	17.7	14.2	11.1	8.5	7.0	127.3	-8.	1710.
10850	2	1	27.3	22.1	19.1	16.9	12.9	9.3	7.4	5.7	4.2	3.5	1767.0	-5.	1490.
		2	30.1	24.7	21.6	19.2	14.9	10.8	8.6	6.7	5.1	4.1	573.2	19.	1459.
		3	30.2	24.7	21.5	19.3	14.8	10.7	8.5	6.5	4.9	3.9	383.6	-24.	1940.
		4	43.2	36.0	31.8	28.5	22.5	16.7	13.5	10.6	8.2	6.7	204.3	-1.	1730.
		5	54.6	45.6	40.6	36.8	29.2	21.9	17.8	14.3	11.1	9.1	121.2	-2.	1540.
10875	2	1	26.3	21.4	18.6	16.5	12.7	9.2	7.3	5.6	4.3	3.4	1277.0	34.	1140.
		2	27.6	22.7	19.7	17.5	13.5	9.7	7.6	5.8	4.4	3.5	539.5	-36.	1452.
		3	41.7	34.8	30.6	27.6	21.7	16.1	13.0	10.1	7.8	6.3	286.1	-12.	1530.
		4	54.3	45.6	40.4	36.5	29.1	21.7	17.7	13.9	10.8	8.8	153.0	8.	1370.
		5	52.1	43.6	38.4	34.8	27.5	20.5	16.6	13.0	10.1	8.2	81.7	15.	1098.
10900	2	1	26.4	21.3	18.7	16.7	12.8	9.2	7.3	5.6	4.2	3.4	1309.0	3.	1140.
		2	43.0	35.7	31.8	28.8	22.7	16.9	13.7	10.8	8.4	6.8	549.7	-13.	1438.
		3	55.4	46.6	41.6	37.9	30.4	23.0	18.8	14.9	11.6	9.6	249.1	-3.	1300.
		4	53.5	44.8	39.7	36.3	29.0	21.8	17.8	14.1	11.1	9.0	121.0	23.	1050.
		5	38.5	32.4	29.3	25.6	20.8	16.2	12.8	9.3	7.8	6.7	53.3	-23.	696.
10925	2	1	46.6	39.6	34.8	31.9	25.4	19.1	15.5	12.3	9.6	7.8	1748.0	-22.	1520.
		2	60.3	51.7	45.9	42.0	33.8	25.7	21.1	16.8	13.1	10.8	457.5	-8.	1197.
		3	57.2	48.8	43.1	39.5	31.5	23.8	19.4	15.3	11.9	9.8	214.3	17.	1110.
		4	40.0	33.9	29.7	26.9	21.4	16.0	12.9	10.1	7.7	6.2	76.8	-12.	669.
		5	40.4	34.5	30.2	27.4	21.8	16.2	13.2	10.3	7.9	6.4	60.8	31.	795.
10950	2	1	66.0	55.8	50.2	45.8	36.8	28.1	23.1	18.4	14.4	11.9	1753.0	-22.	1570.
		2	65.1	55.2	49.6	45.2	36.4	27.7	22.7	18.0	14.2	11.6	538.5	16.	1449.
		3	42.7	36.1	32.3	29.5	23.7	17.9	14.7	11.6	9.1	7.5	148.6	-20.	790.
		4	43.2	36.5	32.7	29.8	23.8	18.0	14.7	11.6	9.0	7.3	107.1	39.	960.
		5	59.6	50.1	44.4	40.2	32.0	24.0	19.6	15.4	12.0	9.8	129.1	-8.	1730.
10975	2	1	57.4	48.7	43.4	39.5	31.5	23.9	19.5	15.5	12.1	9.9	1581.0	12.	1500.
		2	41.4	35.4	31.5	28.7	23.0	17.4	14.2	11.2	8.8	7.3	265.2	-17.	757.
		3	42.4	36.3	32.4	29.5	23.7	18.1	14.8	11.8	9.2	7.4	168.3	24.	950.
		4	60.8	51.4	45.7	41.5	33.0	24.9	20.3	16.2	12.7	10.4	184.0	1.	1750.
		5	85.1	72.1	64.1	58.4	46.8	35.5	29.1	23.2	18.3	15.1	99.7	-36.	1422.
11000	2	1	35.0	29.7	26.0	23.5	18.8	14.2	11.6	9.3	7.2	5.9	891.8	-16.	756.
		2	37.8	32.3	28.6	26.0	20.7	15.7	12.7	10.1	7.9	6.5	372.4	37.	948.
		3	58.4	49.6	43.9	39.9	31.9	24.1	19.6	15.6	12.1	9.9	382.3	-21.	1940.

		4	84.5	71.6	63.6	57.9	46.3	35.1	28.7	22.9	17.9	14.8	177.1	-26.	1500.
		5	79.0	67.2	60.4	54.9	43.5	33.5	27.5	22.0	17.2	14.1	102.7	-4.	1300.
11025	2	1	28.8	23.9	21.1	19.1	15.0	11.2	9.1	7.1	5.6	4.6	878.3	43.	745.
		2	52.6	44.1	39.0	35.3	27.9	20.8	16.9	13.3	10.3	8.4	716.5	-16.	1824.
		3	80.3	67.7	60.2	54.6	43.5	32.9	26.9	21.3	16.7	13.7	303.1	-44.	1540.
		4	75.5	64.0	57.1	51.7	41.4	31.5	25.8	20.5	16.1	13.3	164.8	8.	1390.
		5	92.0	78.4	70.1	63.4	51.0	38.8	31.9	25.5	20.1	16.6	88.0	8.	1120.
11050	2	1	39.1	32.3	28.3	25.5	19.9	14.7	11.8	9.3	7.1	5.8	1439.0	-15.	1250.
		2	73.3	61.6	54.5	49.5	39.2	29.4	23.9	18.9	14.8	12.1	478.3	-36.	1251.
		3	69.5	58.7	52.1	47.3	37.7	28.5	23.2	18.4	14.4	11.8	257.1	-9.	1340.
		4	87.5	74.1	65.8	60.0	47.9	36.2	29.6	23.6	18.6	15.3	128.3	16.	1110.
		5	86.2	72.4	63.4	57.4	44.8	33.1	26.9	21.2	16.5	14.4	58.7	29.	768.
11075	2	1	61.7	51.5	45.8	41.5	33.0	24.9	20.3	16.1	12.6	10.4	521.6	-30.	655.
		2	62.3	52.5	46.9	42.6	34.2	26.0	20.8	17.0	13.5	11.1	217.5	-3.	819.
		3	80.0	67.8	60.8	55.2	44.5	34.1	28.0	22.4	17.8	14.8	103.8	-11.	780.
		4	79.3	66.1	58.5	52.7	42.1	31.9	26.1	21.0	16.8	14.1	45.2	53.	567.
		5	64.2	53.9	48.6	43.4	35.4	27.3	22.5	18.4	15.0	12.7	23.7	33.	446.
11100	2	1	71.3	59.2	51.3	45.9	35.4	25.7	20.5	15.9	12.3	9.9	201.0	6.	1050.
		2	86.5	72.7	63.4	57.2	44.6	32.9	26.5	20.7	16.0	13.0	70.2	-6.	1102.
		3	83.8	69.9	60.2	53.5	40.9	29.3	23.1	17.4	13.3	10.5	22.7	41.	710.
		4	66.2	56.2	47.1	41.3	31.5	21.8	16.7	11.5	8.5	6.2	10.5	42.	540.
		5	70.0	60.4	49.9	43.5	32.9	21.8	16.7	11.2	7.9	5.5	8.0	-7.	631.
11125	2	1	66.0	55.3	48.6	44.2	35.0	26.3	21.4	17.0	13.3	10.9	1098.0	-6.	1720.
		2	82.9	69.0	60.3	54.5	42.8	31.8	25.7	20.2	15.6	12.7	140.4	48.	661.
		3	63.5	53.4	46.9	42.4	33.6	24.4	20.0	15.7	11.5	9.4	53.0	27.	498.
		4	71.0	58.9	52.1	47.3	37.0	28.0	21.4	17.4	14.3	10.9	37.3	1.	586.
11150	2	1	78.2	65.7	58.1	52.8	41.8	31.5	25.7	20.4	16.1	13.1	226.3	47.	780.
		2	62.0	51.7	46.0	41.5	33.0	24.9	20.3	16.1	12.7	10.4	54.4	36.	569.
		3	67.2	56.5	49.8	44.7	35.6	26.7	21.7	17.2	13.5	11.0	33.5	-10.	690.
11175	2	1	73.4	61.7	54.5	49.5	39.3	29.5	24.1	19.0	14.9	12.2	149.9	40.	470.
		2	72.7	61.3	54.0	49.2	39.1	29.4	23.9	19.0	14.8	12.1	63.3	-12.	596.
11200	2	1	58.7	48.4	42.2	38.1	29.5	21.6	17.3	13.5	10.3	8.4	214.0	-12.	830.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 68W.IND
DATA FILE : 68W.DAT

LINE NO. : 684

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10675	2	1	9.6	7.8	7.0	6.5	5.1	3.4	3.0	2.3	1.7	1.3	421.0	-28.	293.
		2	10.2	8.6	7.8	7.3	5.7	5.2	3.4	2.6	2.0	1.6	132.6	2.	277.
		3	16.6	13.5	12.0	11.1	8.5	6.2	4.8	3.6	2.8	2.1	95.8	-4.	400.
		4	23.6	19.1	17.1	15.8	12.0	10.4	7.3	5.9	4.2	3.7	27.0	23.	188.
		5	24.8	21.0	19.5	18.2	14.6	13.5	9.2	7.5	6.0	5.0	14.9	-13.	156.
10700	2	1	9.3	7.4	6.3	5.6	4.3	3.0	2.4	1.9	1.4	1.1	1876.0	4.	650.
		2	16.8	13.6	11.7	10.5	8.0	5.7	4.5	3.4	2.6	2.0	790.1	3.	826.
		3	23.6	19.8	17.4	15.8	12.6	9.5	7.8	6.1	4.7	3.6	158.4	13.	330.
		4	27.0	23.0	20.3	18.5	15.0	11.4	9.5	7.4	5.5	5.4	70.2	-14.	244.
		5	20.5	17.2	15.1	13.5	11.0	8.2	6.9	5.2	4.1	3.3	50.2	-1.	262.
10725	2	1	22.6	17.8	15.3	13.5	10.1	7.0	5.5	4.2	3.2	2.5	2405.0	-4.	1880.
		2	29.1	24.4	21.6	19.5	15.2	11.1	8.9	7.0	5.4	4.4	339.1	8.	798.
		3	32.2	27.3	24.5	22.3	17.9	13.6	11.2	9.2	7.3	5.9	115.8	-25.	540.
		4	25.2	20.8	18.4	16.8	13.2	9.9	8.1	6.1	4.8	4.2	61.2	9.	480.
		5	21.9	17.4	15.4	13.8	10.7	8.0	6.4	5.0	3.9	3.2	23.9	9.	281.
10750	2	1	30.3	24.7	21.5	19.3	15.1	11.2	9.1	7.2	5.6	4.7	1819.0	4.	1260.
		2	34.9	29.8	26.5	24.2	19.5	14.9	12.2	9.9	7.8	6.5	546.0	-21.	1142.
		3	27.3	23.2	20.6	18.8	15.1	11.5	9.4	7.5	5.9	4.9	245.4	-1.	1020.
		4	24.9	21.0	18.4	16.6	13.1	9.9	8.1	6.4	5.1	4.2	84.3	16.	588.
		5	23.2	18.5	16.4	16.8	12.6	8.7	7.5	6.2	4.9	4.0	45.8	-28.	479.
10775	2	1	48.6	39.9	35.0	31.4	24.5	18.0	14.6	11.5	9.0	7.4	337.9	-24.	1170.
		2	41.0	33.7	29.5	26.3	20.4	14.9	11.9	9.4	7.3	5.9	124.8	8.	1300.
		3	38.4	31.5	27.5	24.5	19.0	13.9	11.1	8.7	6.2	4.2	39.3	8.	820.
		4	35.9	28.8	24.7	21.7	16.3	11.4	9.0	6.8	6.1	6.6	19.9	-25.	690.
		5	39.2	31.8	27.6	24.3	18.8	13.5	10.8	8.4	6.3	5.1	17.3	35.	900.
10800	2	1	36.4	30.0	26.1	23.6	18.4	13.7	11.0	8.7	6.8	5.5	561.9	16.	1102.

		2	36.4	29.9	25.9	23.3	18.1	13.2	10.7	8.4	6.5	5.3	137.4	8.	808.
		3	36.1	29.8	25.9	23.3	18.2	13.5	10.8	8.4	6.5	5.1	56.5	-26.	664.
		4	39.6	32.4	28.2	25.1	19.3	14.0	11.3	9.1	7.2	6.2	48.8	42.	958.
		5	43.6	36.1	31.6	28.2	21.8	16.1	12.3	9.5	7.4	5.2	27.2	-7.	800.
10825	2	1	37.2	30.7	26.9	24.5	19.2	14.3	11.6	9.2	7.2	5.9	793.6	14.	1245.
		2	40.3	33.4	29.2	26.5	20.7	15.4	12.4	9.8	7.6	6.2	192.9	-5.	908.
		3	43.4	35.8	31.3	28.4	22.1	16.4	13.1	10.2	8.0	6.6	150.9	15.	1410.
		4	48.6	40.4	35.5	32.4	25.6	19.2	15.6	12.5	9.5	7.5	71.1	-4.	1116.
		5	42.0	34.9	30.7	28.1	21.9	16.5	13.4	10.5	8.3	6.8	40.8	-27.	961.
10850	2	1	41.4	33.6	29.4	26.4	20.3	14.9	11.9	9.3	7.1	5.7	731.0	3.	1275.
		2	47.2	38.8	34.0	30.5	23.7	17.4	14.0	10.9	8.4	6.7	401.2	19.	2099.
		3	50.2	41.7	36.7	33.0	25.9	19.2	15.4	12.1	9.3	7.5	155.6	10.	1620.
		4	45.3	37.8	33.1	29.8	23.3	17.3	13.9	10.9	8.4	6.7	74.3	-47.	1295.
		5	38.9	32.7	28.5	25.5	19.9	14.6	11.7	9.3	7.0	5.7	52.2	22.	1364.
10875	2	1	39.8	32.4	28.2	25.1	19.3	14.0	11.2	8.6	6.6	5.2	840.7	16.	1649.
		2	45.8	37.6	32.9	29.4	22.9	16.7	13.4	10.4	7.9	6.4	225.6	-2.	1328.
		3	41.8	34.9	30.7	27.7	21.6	15.9	12.7	10.0	7.6	6.0	95.9	-28.	1127.
		4	38.3	31.4	27.5	24.5	19.1	14.0	11.1	8.7	6.6	5.3	61.2	25.	1200.
		5	25.6	20.5	17.6	15.5	11.9	8.4	6.5	5.1	3.8	3.0	28.0	10.	823.
10900	2	1	43.1	35.2	30.8	27.7	21.6	15.8	12.7	9.9	7.6	6.1	569.5	26.	1192.
		2	38.1	31.6	27.9	25.2	19.6	14.3	11.5	8.9	6.8	5.4	167.6	-66.	1052.
		3	35.6	29.2	25.6	23.2	17.9	13.0	10.5	8.1	6.2	4.9	110.5	25.	1380.
		4	22.6	17.6	14.9	13.5	9.7	6.5	5.0	4.2	3.3	2.6	39.0	14.	816.
		5	28.8	23.8	20.9	19.5	15.4	11.6	9.4	6.5	4.6	3.9	23.4	3.	733.
10925	2	1	35.5	35.2	25.4	22.7	17.5	12.7	10.2	7.9	6.1	4.9	442.1	-55.	991.
		2	37.6	30.9	27.3	24.4	19.0	13.9	11.0	8.6	6.6	5.2	200.3	27.	1347.
		3	25.5	20.6	18.1	16.1	12.3	9.0	7.1	5.5	4.2	3.3	61.8	2.	829.
		4	28.5	23.0	20.3	18.0	13.8	10.1	7.8	6.1	4.7	3.6	34.5	9.	772.
		5	32.5	25.5	22.7	20.5	16.2	12.2	9.3	7.3	5.4	4.2	28.4	-18.	953.
10950	2	1	39.6	32.3	28.1	25.1	19.3	13.9	11.1	8.5	6.5	5.5	385.2	33.	1209.
		2	29.3	23.8	20.5	18.2	13.6	9.6	7.6	5.9	4.4	3.5	76.8	-5.	724.
		3	31.2	25.9	22.6	20.2	15.3	11.0	8.7	6.6	5.0	4.0	43.4	11.	815.
		4	35.9	29.9	26.1	23.4	17.9	13.3	11.1	8.8	7.1	5.8	30.8	-13.	967.
		5	67.1	55.9	49.2	45.0	34.9	25.8	20.8	16.2	12.3	10.0	36.5	-26.	1721.
10975	2	1	30.7	25.1	22.1	19.8	15.4	11.3	9.1	7.1	5.5	4.4	299.7	21.	627.
		2	31.2	26.1	22.9	20.5	16.1	11.9	9.6	7.5	5.8	4.7	124.2	18.	779.
		3	33.6	27.8	24.8	22.5	17.5	13.1	10.6	8.3	6.4	5.2	76.1	-26.	953.
		4	67.7	56.5	50.8	45.7	36.5	27.5	22.4	17.8	13.9	11.3	83.8	-18.	1755.
		5	83.7	67.5	60.6	54.5	43.4	32.8	26.7	21.1	16.5	13.5	60.0	42.	1884.
11000	2	1	18.2	14.9	13.0	11.7	9.1	6.7	5.4	4.2	3.2	2.6	467.3	16.	666.
		2	24.7	20.6	18.0	16.3	12.9	9.6	7.7	6.1	4.7	3.7	219.3	-21.	939.
		3	60.6	51.4	45.8	41.7	33.4	25.3	20.6	16.4	12.8	10.4	213.3	-22.	1820.

		4	75.9	64.2	56.9	51.9	41.3	31.2	25.3	20.1	15.7	12.8	138.8	42.	1980.
		5	77.5	65.5	58.0	53.2	42.1	31.6	26.5	20.8	15.9	13.0	50.6	-11.	1083.
11025	2	1	15.1	12.4	10.7	9.5	7.4	5.4	4.3	3.4	2.6	2.0	437.4	-14.	624.
		2	55.9	47.0	41.6	37.7	30.0	22.6	18.4	14.6	11.4	9.3	335.6	-22.	1436.
		3	69.3	58.7	52.1	47.6	37.9	28.6	23.4	18.5	14.4	11.6	185.1	36.	1580.
		4	74.1	62.5	55.4	50.6	40.4	30.5	24.8	19.9	15.8	13.5	65.6	-5.	936.
		5	69.6	59.3	52.7	48.4	39.0	29.7	24.4	19.5	15.4	12.6	49.6	-14.	1062.
11050	2	1	50.1	41.8	36.5	33.1	26.1	19.4	15.7	12.4	9.6	7.8	448.9	-12.	829.
		2	66.4	56.2	49.4	45.2	35.8	26.8	21.8	17.2	13.3	10.8	202.4	36.	1121.
		3	70.6	59.9	52.8	48.4	38.5	29.0	23.8	18.8	14.8	12.1	64.6	-14.	713.
		4	66.7	56.8	50.1	46.3	36.8	28.0	23.0	18.2	14.3	11.6	46.5	-9.	858.
		5	83.7	70.9	62.1	57.6	45.1	33.8	27.7	22.0	17.5	14.2	22.6	38.	627.
11075	2	1	70.0	57.9	50.3	45.0	34.7	25.2	20.2	15.8	12.0	9.6	160.8	46.	840.
		2	74.0	62.0	53.8	49.2	38.6	28.4	22.7	17.9	14.8	12.2	38.2	-10.	599.
		3	66.9	57.1	49.3	45.0	35.3	26.2	21.1	16.6	13.2	10.6	25.4	-19.	790.
		4	84.9	72.1	61.6	56.3	43.9	32.4	25.9	20.4	16.1	13.1	11.9	45.	620.
		5	70.1	59.8	49.1	45.2	34.6	25.4	20.3	15.7	12.5	9.5	6.9	26.	539.
11100	2	1	75.9	63.8	56.5	51.6	41.2	31.3	25.6	20.5	16.1	13.2	324.6	-13.	536.
		2	60.1	50.8	45.3	41.5	33.2	25.3	20.7	16.5	13.0	10.6	153.3	-18.	760.
		3	76.2	64.0	56.9	52.0	41.4	31.3	25.5	20.4	16.0	13.1	63.2	35.	625.
		4	62.0	51.1	45.3	41.4	32.6	24.5	19.8	15.8	12.2	9.9	33.0	30.	545.
		5	54.3	44.1	39.5	36.3	28.2	21.4	17.2	13.8	10.6	8.6	19.9	-7.	493.
11125	2	1	68.8	57.5	50.9	46.0	36.3	27.1	22.0	17.2	13.6	11.1	310.1	-13.	973.
		2	87.6	73.6	65.3	59.1	46.7	35.0	28.4	23.0	17.7	14.5	86.5	42.	815.
		3	70.9	59.4	52.8	47.2	37.0	27.5	22.3	18.0	13.8	11.3	36.2	16.	679.
		4	63.1	52.8	46.9	41.7	32.6	24.0	19.6	16.1	12.0	9.8	19.4	0.	607.
11150	2	1	80.4	67.5	59.7	54.1	43.0	32.3	26.4	21.0	16.4	13.5	254.0	43.	1130.
		2	67.3	56.0	49.2	44.3	34.9	26.0	21.1	16.6	12.9	10.5	56.9	17.	766.
		3	58.0	48.1	42.2	37.3	29.1	20.7	16.6	12.7	9.9	9.5	26.6	-10.	710.
11175	2	1	68.1	56.6	50.4	46.1	36.4	27.6	22.6	18.0	14.3	11.8	186.1	25.	730.
		2	61.5	51.1	45.3	41.6	32.9	25.1	20.6	16.5	13.2	11.4	59.4	-8.	699.
11200	2	1	55.2	45.4	40.1	36.1	28.4	21.2	17.2	13.6	10.5	8.4	297.7	-9.	719.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 67W.IND
DATA FILE : 67W.DAT

LINE NO. : 674

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10675	2	1	12.4	10.1	8.7	7.5	5.8	4.2	3.3	2.5	1.9	1.5	72.1	17.	251.
		2	7.4	7.2	6.6	5.6	4.8	3.5	2.9	2.1	1.5	1.0	21.4	-3.	223.
		3	3.8	3.5	2.9	1.9	1.6	.8	.3	-.1	-.5	-.8	12.8	-2.	260.
		4	5.7	4.8	3.9	2.5	2.1	.7	.3	-.1	-.9	-1.4	7.6	-2.	263.
		5	11.2	9.4	8.1	5.3	4.5	2.0	1.0	-.1	-1.1	-1.8	3.8	6.	197.
10700	2	1	11.4	8.5	7.1	6.2	4.5	3.1	2.4	1.8	1.3	1.0	395.4	0.	191.
		2	7.8	6.1	5.2	4.6	3.4	2.3	1.7	1.2	.8	.6	179.5	4.	260.
		3	10.0	8.0	7.0	6.1	4.6	3.2	2.4	1.7	1.2	.7	89.1	-13.	257.
		4	16.7	13.4	11.7	10.3	7.7	5.4	4.1	3.1	2.0	1.7	39.9	9.	192.
		5	10.4	8.1	7.1	5.9	4.2	2.6	1.7	.9	.2	-.1	26.9	2.	195.
10725	2	1	9.9	7.6	6.0	5.0	3.6	2.4	1.8	1.4	1.0	.8	447.9	9.	327.
		2	13.4	10.7	8.9	7.8	5.8	4.1	3.2	2.5	1.8	1.5	150.0	-15.	328.
		3	21.3	17.5	14.9	13.3	10.3	7.5	6.0	4.7	3.6	2.9	54.6	5.	238.
		4	18.4	15.2	12.9	11.6	9.2	6.9	5.7	4.6	3.7	3.1	30.3	9.	221.
		5	25.6	21.2	18.3	16.6	13.3	10.0	8.1	6.5	5.1	4.2	17.8	-5.	194.
10750	2	1	15.8	12.3	10.5	9.3	7.1	5.1	4.0	3.1	2.4	1.9	1019.0	-3.	630.
		2	25.3	20.3	17.6	15.8	12.2	8.9	7.2	5.6	4.3	3.5	256.6	6.	483.
		3	25.6	20.8	18.2	16.5	12.9	9.5	7.7	6.1	4.7	3.8	109.1	-2.	410.
		4	31.4	25.6	22.3	20.3	15.9	11.7	9.5	7.5	5.8	4.7	54.4	4.	341.
		5	23.8	19.4	16.8	15.5	11.8	8.7	7.0	5.5	4.1	3.2	35.2	-8.	331.
10775	2	1	25.6	20.9	18.2	16.4	12.8	9.5	7.6	6.0	4.7	3.8	2265.0	-3.	940.
		2	29.8	24.7	21.7	19.6	15.5	11.7	9.5	7.5	5.9	4.8	623.7	0.	783.
		3	34.8	29.1	25.8	23.4	18.5	14.0	11.3	9.0	7.0	5.7	265.0	-8.	660.
		4	28.7	23.8	21.0	18.9	15.0	11.3	9.1	7.3	5.7	4.7	133.9	4.	560.
		5	22.5	18.2	16.1	14.3	11.4	8.5	6.9	5.5	4.3	3.5	80.4	19.	505.
10800	2	1	32.4	26.9	23.4	21.2	16.7	12.5	10.1	8.0	6.2	5.1	882.8	4.	815.

		2	39.1	32.6	28.5	25.8	20.3	15.2	12.3	9.7	7.5	6.1	315.4	-1.	873.
		3	33.1	28.0	24.5	22.2	17.6	13.2	10.7	8.4	6.5	5.3	132.0	-9.	720.
		4	27.5	23.1	20.0	18.1	14.3	10.6	8.4	6.6	5.0	4.0	70.7	26.	653.
		5	29.2	13.3	13.9	14.8	12.1	13.1	7.0	5.5	3.6	2.5	31.9	8.	442.
10825	2	1	43.8	35.8	31.3	28.1	22.1	16.4	13.3	10.5	8.1	6.6	1090.0	-1.	920.
		2	40.6	33.4	29.2	26.3	20.7	15.3	12.4	9.7	7.5	6.1	340.2	-6.	866.
		3	32.1	26.7	23.5	21.4	16.8	12.5	10.1	7.9	6.1	4.9	155.7	17.	790.
		4	30.9	25.3	21.8	19.6	15.3	11.5	9.2	7.2	5.6	4.5	65.3	13.	554.
		5	24.6	20.0	17.6	16.1	12.7	9.3	7.5	5.9	4.5	3.7	57.0	-16.	725.
10850	2	1	43.8	35.4	30.8	27.6	21.4	15.8	12.7	9.9	7.6	6.1	1531.0	-4.	1230.
		2	38.5	31.3	27.3	24.5	19.0	13.9	11.2	8.7	6.7	5.4	434.2	26.	1048.
		3	31.2	26.2	23.3	21.1	16.7	12.4	10.0	7.9	5.9	4.5	150.3	-3.	720.
		4	28.7	23.0	20.0	17.9	13.7	9.9	8.0	6.1	4.9	4.2	119.2	-6.	950.
		5	12.5	9.1	7.5	6.4	4.6	3.0	2.3	1.6	1.1	.7	25.6	-16.	309.
10875	2	1	36.3	29.0	25.3	22.6	17.5	12.7	10.2	7.9	6.0	4.9	1359.0	38.	1180.
		2	35.5	29.1	25.7	23.1	18.0	13.2	10.6	8.1	6.2	5.1	349.5	-2.	914.
		3	32.6	26.5	23.5	21.1	16.5	12.1	9.8	7.6	5.8	4.6	233.2	-19.	1210.
		4	18.0	13.6	11.8	10.4	7.5	5.3	4.1	3.1	2.3	1.8	44.7	-8.	389.
		5	9.1	6.7	5.7	5.4	3.4	1.8	1.6	.9	.9	-.5	32.2	-8.	421.
10900	2	1	33.4	26.9	23.0	20.6	15.9	11.7	9.3	7.3	5.6	4.5	1507.0	-2.	1150.
		2	35.9	29.7	25.9	23.3	18.2	13.4	10.8	8.4	6.5	5.2	750.9	-19.	1725.
		3	20.7	17.0	14.7	13.1	10.0	7.3	5.8	4.3	2.8	2.2	128.5	-32.	580.
		4	14.3	11.1	9.3	8.1	6.2	4.4	3.3	3.0	3.0	2.5	74.1	20.	567.
		5	25.2	19.8	17.3	15.1	11.9	8.8	6.9	5.6	4.0	3.2	61.9	-4.	710.
10925	2	1	33.1	26.5	22.7	20.3	15.7	11.5	9.2	7.2	5.5	4.5	2330.0	59.	1820.
		2	17.5	17.3	15.7	14.6	11.4	8.5	6.7	5.2	3.9	3.2	195.7	-37.	460.
		3	15.6	12.6	10.5	9.4	6.9	4.9	3.8	3.1	2.3	1.8	131.7	2.	610.
		4	26.7	21.8	18.8	17.0	13.2	9.8	7.9	5.8	4.5	3.7	86.3	6.	677.
		5	28.2	23.4	20.2	18.4	14.3	10.7	8.6	6.8	5.3	4.2	71.0	5.	836.
10947	2	1	22.8	16.9	14.3	12.4	9.2	6.5	5.1	3.9	3.0	2.4	74.0	-11.	232.
		2	20.4	15.1	12.8	11.2	8.2	5.8	4.5	3.4	2.6	2.0	51.0	7.	480.
		3	31.4	24.6	21.5	19.2	14.9	11.1	8.8	6.8	5.2	4.2	42.5	-4.	798.
		4	32.8	25.8	22.9	20.5	15.6	11.6	9.4	7.4	5.8	4.8	24.4	8.	766.
		5	40.1	32.0	28.4	25.4	20.0	15.1	12.2	9.5	7.4	6.0	23.1	-12.	1088.
10972	2	1	17.9	12.7	10.4	8.7	6.3	4.1	3.1	2.3	1.7	1.2	173.2	-5.	670.
		2	30.1	23.4	20.3	17.8	13.8	10.0	8.0	6.2	4.8	3.8	61.9	16.	728.
		3	31.9	24.9	21.7	19.1	14.9	10.7	8.6	6.6	5.0	4.0	34.9	6.	820.
		4	44.4	35.3	31.3	27.7	21.9	16.1	13.0	10.1	7.8	5.9	33.6	6.	1310.
		5	57.6	45.9	40.9	36.1	28.7	21.1	17.0	13.2	10.0	7.7	40.9	7.	2400.
10997	2	1	21.0	16.9	14.6	13.1	10.3	7.6	6.1	4.8	3.7	3.0	307.0	17.	481.
		2	27.5	22.8	20.0	18.0	14.3	10.7	8.7	6.9	5.4	4.4	120.6	13.	568.
		3	40.1	33.5	29.6	26.7	21.3	16.0	13.0	10.2	7.9	6.5	110.3	-13.	1030.

		4	52.8	44.0	38.9	35.2	28.0	21.0	17.1	13.5	10.6	8.6	111.5	19.	1750.
		5	55.8	46.6	41.4	37.3	29.8	22.5	18.3	14.5	11.4	9.3	47.8	12.	1124.
11023	2	1	22.0	17.5	15.2	13.6	10.6	7.8	6.3	5.0	3.8	3.0	241.6	1.	421.
		2	39.8	33.0	29.2	26.4	20.9	15.7	12.8	10.1	7.8	6.3	169.7	-7.	888.
		3	53.5	44.5	39.4	35.7	28.3	21.3	17.3	13.7	10.6	8.5	146.7	8.	1530.
		4	55.5	46.4	41.3	37.6	29.8	22.3	18.2	14.3	11.1	8.9	48.2	23.	840.
		5	66.8	55.8	49.7	45.2	36.1	27.3	22.4	17.8	13.9	11.2	50.5	-57.	1320.
11050	2	1	28.6	23.6	20.8	18.6	14.7	11.0	8.9	7.0	5.5	4.4	497.4	11.	743.
		2	48.1	39.9	35.2	31.8	25.2	18.9	15.4	12.2	9.5	7.8	318.1	12.	1426.
		3	52.2	44.2	39.3	35.7	28.6	21.8	17.9	14.3	11.2	9.3	97.6	-5.	873.
		4	65.3	54.7	48.0	44.3	35.5	27.2	22.4	18.0	14.3	11.9	75.0	-38.	1122.
		5	74.3	62.7	55.9	50.9	40.9	31.5	26.0	20.9	16.9	14.1	43.4	39.	972.
11075	2	1	37.1	30.9	27.0	24.2	19.1	14.3	11.6	9.1	7.0	5.7	827.8	16.	1083.
		2	44.8	37.9	33.5	30.3	24.2	18.2	14.8	11.7	9.1	7.4	169.9	-4.	666.
		3	61.1	51.7	45.7	41.4	33.3	25.0	20.5	16.2	12.6	10.3	126.2	-19.	980.
		4	66.2	55.8	49.2	44.2	35.4	26.8	22.0	17.4	13.8	11.3	55.9	19.	731.
		5	64.8	54.3	47.8	43.3	34.5	25.8	21.2	16.2	13.0	10.9	26.2	-4.	513.
11100	2	1	41.4	34.5	30.1	27.2	21.6	16.2	13.1	10.4	8.1	6.5	530.9	16.	757.
		2	60.6	51.0	44.9	40.8	32.5	24.6	20.0	16.0	12.5	10.2	253.3	-13.	1084.
		3	68.1	58.0	51.2	46.5	37.2	28.1	22.9	18.3	14.4	11.8	96.2	-6.	822.
		4	65.1	54.6	48.2	43.5	34.8	26.5	21.7	17.3	13.3	10.9	34.0	20.	484.
		5	57.3	48.5	42.9	38.5	30.9	23.6	19.3	15.6	12.4	10.1	26.6	4.	569.
11125	2	1	67.8	56.2	49.6	44.7	35.4	26.5	21.6	17.1	13.2	10.2	480.5	-9.	1508.
		2	81.9	68.6	60.7	55.0	43.8	33.0	27.0	21.5	16.8	13.8	121.7	-10.	1146.
		3	66.7	56.9	50.4	46.1	36.2	27.2	22.0	17.1	12.7	10.1	37.4	14.	703.
		4	68.7	58.1	52.0	47.8	38.0	29.2	24.0	19.6	17.0	14.2	23.3	-1.	730.
11150	2	1	69.8	58.5	51.6	46.9	37.3	28.1	23.1	18.4	14.4	11.8	426.6	-4.	956.
		2	67.7	56.3	50.1	45.6	36.2	27.0	21.8	17.2	13.3	10.7	100.0	17.	672.
		3	60.2	50.1	44.3	40.3	31.8	23.8	19.5	15.5	12.3	10.1	52.3	-11.	702.
11175	2	1	53.8	44.5	39.0	35.2	27.9	21.1	17.2	13.7	10.7	8.8	238.2	14.	747.
		2	52.0	43.1	37.3	34.0	27.0	20.3	16.5	13.2	10.3	8.5	94.3	-4.	889.
11200	2	1	52.5	42.4	37.1	33.2	25.9	19.1	15.4	12.1	9.4	7.6	137.6	-3.	860.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 66W.IND
DATA FILE : 66W.DAT

LINE NO. : 664

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10725	2	1	5.2	4.0	3.3	2.9	2.2	1.6	1.3	1.0	.7	.6	331.9	9.	208.
		2	5.1	4.0	3.4	3.0	2.3	1.6	1.3	.9	.7	.5	88.9	10.	168.
		3	6.6	5.2	4.5	4.1	3.1	2.2	1.7	1.3	.9	.7	43.1	0.	162.
		4	-2.2	-3.3	-3.7	-4.0	-3.5	-1.5	-1.3	******	-3.2	-1.7	23.1	0.	144.
		5	17.2	15.3	14.8	14.1	11.4	6.6	5.3	******	6.6	3.7	14.8	26.	139.
10750	2	1	7.0	5.2	4.3	3.6	2.6	1.8	1.4	1.1	.8	.6	336.4	18.	211.
		2	8.3	6.5	5.5	4.8	3.6	2.6	2.1	1.6	1.2	.9	83.3	4.	157.
		3	7.0	5.6	4.9	4.2	3.1	2.3	1.9	1.6	1.1	.8	38.2	-6.	143.
		4	6.5	5.0	4.4	3.8	2.9	1.9	1.1	.5	.4	.2	22.2	19.	139.
		5	5.9	4.6	4.1	3.8	2.7	1.7	1.0	.8	1.5	.4	30.8	-15.	290.
10775	2	1	7.7	5.9	5.0	4.5	3.4	2.5	2.0	1.5	1.1	.9	342.8	6.	149.
		2	8.3	6.6	5.6	5.0	3.8	2.7	2.2	1.7	1.2	1.0	108.4	-3.	141.
		3	7.2	5.7	4.9	4.5	3.5	2.6	2.2	1.7	1.4	1.2	53.8	15.	140.
		4	7.0	5.5	4.8	4.4	3.4	2.6	2.1	1.6	1.3	1.0	66.6	-14.	290.
		5	13.2	10.7	9.4	8.7	6.9	5.3	4.3	3.6	2.9	2.4	72.1	-5.	471.
10800	2	1	8.8	7.3	6.0	5.5	4.3	3.1	2.5	1.9	1.4	1.1	426.1	12.	196.
		2	8.6	7.0	5.9	5.3	4.2	3.1	2.5	1.9	1.4	1.2	123.1	19.	170.
		3	8.5	7.3	6.2	5.7	4.5	3.3	2.8	2.2	1.9	1.7	128.5	-2.	350.
		4	13.5	11.6	10.0	9.2	7.2	5.5	4.5	3.6	2.7	2.2	96.2	-28.	444.
		5	8.3	6.6	5.3	4.8	3.9	3.2	2.6	2.1	1.9	1.8	30.6	4.	212.
10825	2	1	10.5	8.3	7.3	6.6	5.1	3.7	2.9	2.2	1.7	1.3	443.4	24.	214.
		2	12.4	9.9	8.7	7.8	6.0	4.4	3.5	2.7	2.0	1.6	277.8	-5.	402.
		3	16.5	13.3	11.9	10.6	8.4	6.2	5.0	3.9	3.1	2.5	187.1	-16.	540.
		4	12.2	9.4	8.7	7.4	5.8	4.3	3.4	2.2	1.6	1.1	34.0	-5.	164.
		5	8.2	5.7	5.4	4.7	3.6	2.6	1.8	1.4	1.0	.8	17.9	-4.	129.
10850	2	1	12.0	9.4	8.2	7.4	5.7	4.2	3.3	2.5	1.9	1.5	967.5	-1.	482.

		2	18.9	15.3	13.5	12.2	9.5	7.0	5.6	4.4	3.3	2.6	431.9	-14.	645.
		3	13.0	10.4	9.1	7.9	6.0	4.5	3.6	2.6	1.8	1.2	67.8	-5.	202.
		4	11.5	9.1	7.9	6.8	5.4	3.2	2.3	1.8	1.3	1.1	30.5	-10.	152.
		5	9.7	7.4	6.1	5.0	3.8	2.4	1.7	1.1	.5	.2	21.6	-17.	161.
10875	2	1	17.0	13.4	11.9	10.5	8.2	6.0	4.8	3.7	2.8	2.3	1369.0	3.	720.
		2	14.0	11.1	9.8	8.5	6.6	4.7	3.7	2.8	2.1	1.6	148.2	-1.	236.
		3	11.6	8.9	7.9	6.6	5.1	3.6	2.8	2.0	1.5	1.1	59.8	-25.	190.
		4	11.9	9.0	8.0	6.6	5.2	3.6	2.8	2.1	1.5	1.0	37.3	-1.	198.
		5	7.2	5.1	4.7	3.2	2.6	1.9	1.2	.7	.3	.1	28.3	-1.	225.
10900	2	1	10.1	7.6	6.4	5.9	4.3	3.1	2.4	1.8	1.4	1.1	924.1	19.	446.
		2	11.1	8.4	7.2	6.6	4.9	3.4	2.7	2.1	1.5	1.2	255.8	-15.	370.
		3	12.3	9.4	8.1	7.3	5.5	3.9	3.1	2.4	1.8	1.4	140.8	-12.	400.
		4	9.5	7.2	6.2	5.6	4.2	3.0	2.4	1.8	1.4	1.1	90.4	1.	436.
		5	9.3	7.0	6.1	5.6	4.1	3.0	2.3	1.9	1.4	1.2	72.0	1.	521.
10925	2	1	9.2	6.8	5.9	5.1	3.8	2.7	2.1	1.6	1.2	1.0	1305.0	-4.	650.
		2	12.4	9.4	8.1	7.1	5.4	3.8	3.0	2.3	1.8	1.4	456.2	-5.	682.
		3	10.0	7.4	6.5	5.6	4.2	3.0	2.4	1.8	1.4	1.1	250.1	4.	740.
		4	9.4	7.2	6.3	5.5	4.1	2.9	2.3	1.8	1.4	1.2	168.9	-12.	840.
		5	19.7	15.8	14.1	12.6	9.8	7.4	6.0	4.7	3.7	3.0	117.7	-3.	870.
10950	2	1	10.2	7.8	6.6	5.6	4.3	3.0	2.4	1.8	1.3	1.0	926.6	0.	454.
		2	8.8	6.8	5.7	4.7	3.6	2.5	1.9	1.5	1.2	.9	389.3	-2.	573.
		3	8.9	7.1	5.9	5.0	3.8	2.6	2.0	1.5	1.2	.9	265.7	-11.	780.
		4	18.3	15.0	12.9	11.5	9.1	6.7	5.3	4.1	3.3	2.7	167.0	4.	810.
		5	19.6	16.3	14.1	12.6	10.0	7.5	6.1	4.9	3.7	2.8	131.3	4.	960.
10975	2	1	7.2	5.2	4.5	3.8	2.9	2.0	1.5	1.2	.9	.7	731.2	4.	353.
		2	8.3	6.2	5.3	4.5	3.3	2.3	1.8	1.3	1.0	.7	374.5	-8.	542.
		3	17.9	14.6	12.8	11.4	9.0	6.6	5.4	4.2	3.2	2.6	215.4	-5.	620.
		4	19.1	15.5	13.5	12.0	9.5	7.0	5.7	4.4	3.5	2.8	159.8	7.	770.
		5	26.2	21.5	19.0	16.9	13.5	10.0	8.1	6.4	5.0	4.1	126.0	14.	910.
11000	2	1	6.1	4.3	3.6	3.2	2.2	1.5	1.1	.9	.7	.5	927.7	-2.	434.
		2	17.8	14.4	12.6	11.3	8.8	6.6	5.3	4.1	3.2	2.6	366.0	-2.	514.
		3	19.6	15.9	14.0	12.6	9.7	7.2	5.8	4.5	3.5	2.8	238.0	1.	660.
		4	26.0	21.3	18.8	17.0	13.3	9.9	7.9	6.2	4.8	3.9	171.1	16.	800.
		5	29.5	24.2	21.5	19.4	15.2	11.5	9.2	7.3	5.6	4.4	133.9	-31.	940.
11025	2	1	18.1	13.9	12.2	10.6	8.1	5.9	4.7	3.6	2.8	2.2	154.9	1.	405.
		2	23.7	18.3	16.2	14.2	10.9	7.9	6.2	4.9	3.7	2.9	74.1	5.	581.
		3	27.6	21.4	19.3	16.8	12.8	9.3	7.2	5.6	4.2	3.3	44.8	11.	702.
		4	30.7	23.7	21.4	18.8	14.2	10.4	8.0	6.2	4.6	3.6	31.9	-32.	835.
		5	32.8	25.1	22.8	19.8	14.9	10.9	8.2	6.2	4.5	3.5	23.5	28.	923.
11050	2	1	21.3	17.7	15.1	13.8	10.7	8.0	6.4	5.0	3.9	3.1	363.4	7.	518.
		2	26.9	22.3	19.3	17.7	13.8	10.4	8.4	6.7	5.2	4.3	149.4	15.	639.
		3	29.2	24.4	21.3	19.5	15.3	11.5	9.2	7.2	6.1	5.2	90.8	-36.	775.

		4	33.0	27.6	24.2	22.2	17.4	13.1	10.9	8.7	6.2	4.7	62.4	23.	890.
		5	43.9	36.9	31.7	28.0	22.7	17.8	13.9	10.1	8.1	8.8	51.3	-1.	1097.
11075	2	1	18.3	14.8	12.6	11.3	8.8	6.4	5.1	4.0	3.0	2.5	359.4	20.	564.
		2	25.8	21.1	18.3	16.5	13.0	9.6	7.7	6.0	4.6	3.7	153.6	-35.	723.
		3	29.4	24.3	21.1	19.0	14.9	11.1	8.9	7.0	5.3	4.3	100.1	2.	940.
		4	40.5	33.7	29.4	26.6	21.0	15.7	12.6	10.0	7.7	6.2	63.6	17.	998.
		5	49.4	41.2	35.9	32.0	24.8	18.1	14.9	12.2	8.6	7.4	46.4	-27.	1092.
11100	2	1	20.1	15.9	13.9	12.6	9.6	7.1	5.6	4.4	3.4	2.6	435.8	-6.	594.
		2	25.2	20.3	17.8	16.2	12.5	9.3	7.4	5.8	4.5	3.5	221.7	7.	908.
		3	36.7	30.4	27.0	24.6	19.2	14.4	11.6	9.1	7.1	5.7	134.3	9.	1090.
		4	45.6	37.6	33.3	30.2	23.8	17.8	14.4	11.3	9.0	7.4	82.4	-21.	1125.
		5	51.2	42.4	37.7	34.2	27.0	20.3	16.5	12.9	10.1	8.0	70.4	29.	1441.
11125	2	1	19.6	15.4	13.2	11.9	9.0	6.5	5.2	4.0	2.9	2.2	402.7	-1.	665.
		2	33.8	27.4	23.9	21.6	16.7	12.3	9.9	7.6	5.9	4.7	200.8	25.	995.
		3	41.9	34.4	30.2	27.4	21.4	15.8	12.7	9.9	7.7	6.2	139.1	-16.	1370.
		4	50.4	41.6	36.5	33.1	25.8	19.3	15.5	12.0	8.8	6.8	78.3	16.	1294.
		5	60.6	50.3	44.5	40.0	31.3	23.4	18.7	14.6	11.3	9.1	57.3	29.	1420.
11150	2	1	23.4	19.0	16.1	14.4	11.2	8.2	6.6	5.2	3.9	3.2	468.8	24.	774.
		2	37.7	30.8	26.6	23.9	18.8	13.9	11.2	8.8	6.8	5.5	234.5	-19.	1162.
		3	43.3	36.4	31.9	29.0	22.9	17.1	13.9	11.0	8.5	6.9	158.8	7.	1570.
		4	57.8	47.9	42.1	38.2	30.2	22.7	18.4	14.6	11.4	9.2	92.0	27.	1520.
11175	2	1	26.7	22.1	19.0	17.2	13.2	9.7	7.7	6.0	4.6	3.6	219.8	3.	690.
		2	39.2	31.6	27.4	25.1	19.5	14.3	11.6	9.1	6.9	5.6	143.8	12.	1354.
		3	52.8	43.9	38.5	35.0	27.4	20.2	16.4	12.6	9.8	7.7	62.4	15.	1172.
11200	2	1	26.2	20.8	18.1	16.1	12.6	9.2	7.5	5.8	4.5	3.6	283.7	12.	809.
		2	44.2	36.1	31.7	28.5	22.5	16.8	13.6	10.8	8.4	6.8	124.5	20.	1066.
11225	2	1	34.4	27.3	23.7	21.0	16.2	11.9	9.4	7.4	5.8	4.5	108.7	21.	850.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 65W.IND
DATA FILE : 65W.DAT

LINE NO. : 654

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10725	2	1	8.9	6.5	5.4	4.8	3.6	2.5	2.0	1.5	1.1	.9	750.9	2.	336.
		2	6.3	4.8	4.2	3.6	2.8	2.0	1.6	1.2	.9	.7	121.8	20.	163.
		3	4.9	3.6	3.4	2.9	2.2	1.6	1.3	.8	.7	.2	57.4	1.	154.
		4	2.0	.9	1.2	.9	.4	.1	.0	.4	.0	.7	24.2	-6.	108.
		5	3.7	1.8	2.1	1.8	1.0	.5	.3	.2	.2	.2	17.4	-16.	117.
10750	2	1	7.4	5.7	4.9	4.3	3.3	2.4	1.9	1.4	1.1	.9	196.4	19.	154.
		2	6.2	5.0	4.4	3.9	3.1	2.3	1.8	1.4	1.1	.9	63.5	32.	150.
		3	2.9	2.1	1.8	1.5	1.1	.1	-.3	******	-.4	.0	23.1	-42.	108.
		4	1.1	.7	.7	.1	-.4	.3	.3	******	.8	-.7	13.9	-13.	109.
		5	-27.2	-26.2	-25.1	-25.6	-23.3	-22.8	-25.1	******	-25.8	-22.2	8.9	-13.	105.
10775	2	1	7.3	6.0	5.2	4.8	3.7	2.8	2.3	1.8	1.4	1.1	444.5	36.	136.
		2	3.0	2.4	2.0	1.9	1.3	.9	.8	.6	.5	.5	120.3	-35.	110.
		3	5.9	4.0	3.0	2.7	1.9	1.3	1.1	.8	.5	.3	62.1	21.	113.
		4	6.6	5.6	5.0	4.5	3.5	2.6	2.0	1.3	1.2	1.2	31.4	-50.	96.
		5	5.7	4.3	3.8	3.4	2.5	1.9	1.5	1.5	1.0	1.0	29.3	-24.	134.
10800	2	1	1.7	1.3	1.2	.8	.7	.4	.3	.2	.1	.0	297.2	-6.	89.
		2	7.7	5.6	4.8	3.9	3.0	2.1	1.6	1.2	.9	.8	123.1	-10.	110.
		3	4.4	3.0	2.5	1.8	1.1	.3	.1	.2	.2	.2	63.5	-23.	114.
		4	7.8	6.4	5.8	5.0	4.4	3.6	3.1	2.0	1.3	.9	37.8	-19.	113.
		5	4.8	3.6	3.1	2.5	1.9	1.2	.9	.5	.3	.2	37.5	33.	168.
10825	2	1	14.6	11.5	9.8	8.7	6.8	5.0	4.0	3.1	2.4	2.0	494.5	-52.	176.
		2	14.7	11.9	10.2	9.1	7.1	5.2	4.3	3.4	2.6	2.2	130.4	18.	139.
		3	11.7	9.5	8.2	7.4	5.8	4.3	3.5	2.8	2.2	1.9	77.7	2.	165.
		4	11.3	9.4	8.2	7.6	6.0	4.5	3.8	3.1	2.5	2.3	45.1	17.	161.
		5	9.9	8.3	7.2	6.9	5.4	4.2	3.6	3.0	2.5	2.3	36.5	-27.	195.
10850	2	1	13.5	10.0	8.4	7.4	5.7	4.1	3.3	2.5	1.9	1.5	54.6	-1.	171.

		2	14.1	11.4	10.0	8.9	7.1	5.3	4.3	3.3	2.5	2.0	23.3	-14.	219.
		3	14.9	12.7	11.7	10.9	9.6	8.3	7.5	4.4	2.4	1.1	13.1	26.	246.
		4	12.2	9.5	8.5	7.2	4.5	1.9	.3	2.6	3.2	4.0	8.0	-21.	252.
		5	15.2	12.7	12.3	11.1	9.2	7.1	5.9	4.5	3.5	2.8	4.9	-5.	232.
10875	2	1	6.6	4.8	4.3	3.6	2.8	1.9	1.5	1.2	.9	.7	1488.0	-14.	740.
		2	10.4	8.0	6.9	6.1	4.7	3.3	2.6	2.0	1.5	1.2	339.3	30.	507.
		3	12.1	9.4	8.2	7.3	5.6	4.0	3.2	2.4	1.8	1.5	149.5	-32.	440.
		4	12.8	10.1	8.7	7.8	6.0	4.3	3.4	2.7	2.0	1.6	78.1	5.	389.
		5	13.3	10.5	9.2	8.3	6.4	4.6	3.6	2.6	1.8	1.3	55.3	-13.	413.
10900	2	1	7.9	6.0	5.1	4.6	3.4	2.4	1.9	1.4	1.1	.9	491.3	14.	321.
		2	11.1	8.5	7.6	6.6	5.0	3.6	2.9	2.3	1.7	1.4	184.2	-28.	361.
		3	12.6	10.0	8.6	7.7	5.9	4.5	3.8	3.3	3.0	2.4	86.8	-1.	339.
		4	13.5	10.9	9.5	8.5	6.6	4.4	3.0	1.9	.8	.7	57.0	-10.	373.
		5	14.5	7.2	5.4	6.1	5.3	3.7	2.2	1.9	1.4	1.6	41.5	42.	407.
10925	2	1	8.1	6.3	5.4	4.5	3.5	2.4	1.9	1.5	1.1	.9	1067.0	-22.	360.
		2	11.2	9.1	7.9	6.7	5.3	3.9	3.1	2.4	1.8	1.5	318.8	3.	322.
		3	13.0	10.5	9.2	7.9	6.2	4.6	3.6	2.9	2.2	1.8	182.0	-20.	360.
		4	12.5	10.1	8.6	7.6	5.9	4.3	3.4	2.8	2.2	1.8	128.4	51.	430.
		5	16.2	13.5	11.6	11.2	8.7	7.1	5.5	4.5	4.2	3.9	123.0	22.	620.
10950	2	1	8.1	6.2	5.4	4.8	3.6	2.5	2.0	1.5	1.1	.9	614.9	5.	283.
		2	11.8	9.2	8.0	7.2	5.4	3.9	3.1	2.4	1.8	1.4	238.2	-17.	329.
		3	11.6	9.1	7.9	7.0	5.3	3.7	2.9	2.3	1.8	1.3	158.0	12.	430.
		4	14.9	11.8	10.5	9.4	7.3	5.5	4.3	3.2	2.4	2.0	128.9	55.	590.
		5	20.4	16.5	14.5	12.9	9.9	7.4	5.9	4.5	3.5	2.5	126.0	8.	870.
10975	2	1	8.0	6.2	5.3	4.8	3.5	2.5	2.0	1.5	1.1	.9	642.9	-4.	288.
		2	10.5	8.0	6.9	6.2	4.7	3.3	2.6	2.0	1.5	1.2	319.5	20.	429.
		3	13.9	11.1	9.7	8.7	6.6	4.8	3.8	2.9	2.3	1.9	244.8	42.	650.
		4	19.9	16.0	14.0	12.6	9.8	7.3	5.9	4.7	3.6	2.9	186.0	4.	830.
		5	20.7	16.8	14.9	13.5	10.5	7.9	6.4	5.1	4.0	3.3	128.5	-1.	860.
11000	2	1	6.8	5.0	4.2	3.6	2.7	1.9	1.5	1.1	.8	.7	786.5	27.	418.
		2	13.7	10.8	9.3	8.1	6.3	4.5	3.6	2.8	2.2	1.8	363.9	37.	581.
		3	18.0	14.4	12.5	11.2	8.6	6.2	4.9	3.8	2.8	2.2	272.4	-3.	860.
		4	19.8	16.1	14.1	12.6	9.8	7.2	5.9	4.6	3.6	2.9	158.3	7.	840.
		5	22.5	18.3	16.8	15.3	12.2	9.0	7.5	5.9	4.6	3.7	102.0	0.	810.
11025	2	1	8.8	6.9	5.8	5.2	3.9	2.8	2.2	1.7	1.3	1.0	594.4	42.	455.
		2	17.0	13.6	11.6	10.4	7.9	5.7	4.5	3.5	2.6	2.1	321.8	-5.	739.
		3	19.1	15.6	13.3	12.2	9.4	7.0	5.6	4.4	3.4	2.7	161.9	-2.	740.
		4	22.1	18.3	15.8	14.6	11.3	8.5	6.8	5.4	4.2	3.4	97.3	4.	744.
		5	24.1	19.2	18.5	16.3	13.2	9.2	7.0	5.8	4.7	3.9	53.2	34.	611.
11050	2	1	16.2	12.7	10.7	9.4	7.3	5.3	4.2	3.3	2.4	1.9	687.0	-7.	490.
		2	18.9	15.3	13.3	11.8	9.2	6.7	5.4	4.2	3.2	2.6	286.8	1.	614.
		3	21.9	18.1	15.8	14.1	11.2	8.3	6.7	5.3	4.0	3.2	162.1	-5.	690.

		4	23.7	19.5	16.9	14.9	12.0	8.8	7.2	5.5	4.3	3.3	72.5	44.	517.
		5	27.6	23.3	20.2	17.7	14.5	10.8	8.8	7.0	5.3	4.4	65.0	-32.	696.
11075	2	1	19.0	15.4	13.2	11.9	9.2	6.7	5.3	4.1	3.1	2.5	610.4	9.	467.
		2	20.9	17.0	14.8	13.4	10.4	7.7	6.1	4.8	3.6	2.9	243.9	3.	560.
		3	22.8	18.9	16.3	14.7	11.4	8.3	6.7	5.4	4.1	3.3	97.8	30.	448.
		4	27.2	22.6	19.9	17.9	13.7	10.3	8.1	5.9	4.4	3.5	83.2	-30.	636.
		5	32.6	26.7	23.3	20.4	17.1	13.7	8.9	7.0	4.4	4.3	42.2	5.	484.
11100	2	1	21.4	17.4	15.1	13.3	10.4	7.6	6.1	4.7	3.5	2.9	697.8	3.	486.
		2	24.1	19.5	17.0	15.1	11.8	8.5	6.8	5.2	3.9	3.0	191.5	34.	400.
		3	26.2	21.7	19.2	17.1	13.5	9.8	7.8	5.9	4.4	3.5	146.0	-41.	600.
		4	32.0	25.3	22.5	19.9	15.7	11.4	9.0	6.9	5.0	3.8	68.4	9.	477.
11125	2	1	20.3	16.7	14.3	12.7	9.9	7.3	5.8	4.6	3.6	2.8	398.9	39.	329.
		2	28.5	23.0	20.0	17.9	14.1	10.5	8.5	6.8	5.2	4.2	237.7	-34.	589.
		3	32.9	25.9	22.6	20.3	16.1	12.0	9.8	7.8	6.0	4.9	98.8	-3.	488.
11150	2	1	22.7	18.1	15.6	14.2	11.1	8.2	6.7	5.3	4.1	3.3	266.1	-2.	439.
		2	30.0	24.0	21.4	19.5	15.4	11.6	9.7	7.8	6.1	5.1	89.2	-1.	442.
11175	2	1	23.0	18.4	15.8	14.3	11.1	8.2	6.6	5.2	3.9	3.1	116.3	-1.	365.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 64W.IND
DATA FILE : 64W.DAT

LINE NO. : 644

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	12.4	9.5	8.0	7.0	5.4	3.9	3.1	2.4	1.8	1.5	1158.0	16.	400.
		2	14.3	11.7	10.2	9.1	7.2	5.3	4.3	3.3	2.6	2.1	360.7	13.	377.
		3	20.9	17.2	14.9	13.4	10.5	7.7	6.2	4.8	3.5	2.9	198.4	-22.	410.
		4	18.0	15.0	13.0	11.6	9.1	6.7	5.4	4.4	3.8	3.1	71.7	5.	249.
		5	14.7	12.4	10.9	9.4	7.8	5.8	4.7	3.9	3.0	2.6	32.2	0.	168.
10850	2	1	12.1	9.6	8.4	7.6	5.8	4.2	3.4	2.6	2.0	1.6	816.4	13.	337.
		2	20.8	16.7	14.6	13.1	10.1	7.4	5.9	4.6	3.6	2.9	324.7	-16.	402.
		3	18.7	15.0	13.2	11.9	9.0	6.4	4.9	3.8	2.9	2.6	100.0	-4.	240.
		4	16.3	13.3	12.0	11.0	8.6	6.7	5.9	4.8	3.7	2.5	41.0	-1.	169.
		5	12.0	9.5	8.7	8.0	6.0	4.5	3.6	2.8	2.3	1.9	24.7	-2.	152.
10875	2	1	20.0	16.2	14.0	12.6	9.8	7.2	5.8	4.5	3.5	2.8	1338.0	-17.	420.
		2	18.5	15.1	13.1	11.7	9.1	6.7	5.4	4.2	3.2	2.6	259.9	1.	245.
		3	16.0	13.1	11.5	10.3	8.0	5.9	4.8	3.7	2.7	2.3	92.7	-1.	174.
		4	11.5	9.5	8.3	7.5	5.6	4.0	3.1	2.3	1.9	1.4	38.3	-8.	120.
		5	14.2	15.4	17.9	10.2	4.8	2.1	2.0	2.0	.9	1.1	26.0	-19.	122.
10900	2	1	16.0	13.1	11.2	10.0	7.8	5.7	4.6	3.6	2.7	2.2	645.9	9.	203.
		2	16.5	13.8	11.7	10.4	8.3	6.1	4.9	3.8	2.9	2.4	182.6	-24.	172.
		3	11.6	10.0	8.5	7.5	6.0	4.3	3.5	2.7	2.0	1.6	67.7	-3.	127.
		4	8.4	7.1	5.9	4.9	4.4	3.3	2.7	2.0	1.2	1.1	31.6	-11.	99.
		5	4.9	4.2	3.3	2.6	2.5	1.6	1.3	1.0	.6	.4	36.8	26.	173.
10925	2	1	22.6	18.2	15.9	14.3	11.2	8.3	6.7	5.2	4.0	3.2	1013.0	-13.	302.
		2	16.7	13.7	12.1	10.8	8.5	6.2	5.0	3.8	2.9	2.4	197.6	8.	177.
		3	10.7	8.7	7.7	6.9	5.5	4.0	3.2	2.5	1.8	1.4	80.1	-21.	143.
		4	9.1	7.2	6.4	5.7	4.5	3.2	2.5	1.9	1.5	1.2	61.9	19.	185.
		5	5.0	2.9	2.9	3.1	2.5	.6	1.1	.9	.3	.6	58.5	9.	263.
10950	2	1	23.0	18.2	15.9	14.3	11.1	8.1	6.6	5.1	4.0	3.2	1004.0	-9.	315.

		2	16.4	13.1	11.6	10.6	8.2	6.0	4.9	3.7	2.9	2.3	205.7	-14.	194.
		3	13.6	10.9	9.7	8.7	6.7	4.9	3.9	2.9	2.1	1.6	133.1	15.	250.
		4	8.9	7.0	6.0	5.4	4.1	2.8	2.2	1.6	1.0	.5	95.8	8.	301.
		5	5.8	4.2	3.5	3.2	2.3	1.1	.8	.2	.1	.1	77.0	-4.	363.
10975	2	1	21.9	17.4	15.3	13.8	10.7	7.9	6.3	4.9	3.8	3.1	776.5	-11.	304.
		2	16.9	13.2	11.8	10.5	8.2	6.0	4.9	3.7	2.8	2.3	248.4	17.	292.
		3	11.1	8.9	8.1	7.2	5.7	4.1	3.2	2.4	1.8	1.5	155.0	-1.	360.
		4	8.9	6.7	6.2	5.2	4.1	2.9	2.5	1.9	1.4	1.1	108.8	8.	420.
		5	11.5	8.4	8.3	7.7	6.0	4.2	3.4	2.5	1.9	1.5	66.0	-10.	388.
11000	2	1	23.9	19.0	16.4	14.7	11.4	8.3	6.6	5.1	3.9	3.1	955.3	8.	389.
		2	11.6	9.4	8.2	7.3	5.7	4.2	3.3	2.5	1.9	1.5	315.5	3.	385.
		3	8.3	6.4	5.6	5.0	3.7	2.6	1.9	1.4	1.0	.7	213.9	-3.	520.
		4	12.1	9.6	8.3	7.4	5.7	4.0	3.0	2.2	1.6	1.1	93.3	-8.	380.
		5	17.5	14.2	12.4	11.1	8.7	6.3	4.8	3.6	2.6	2.0	72.5	16.	443.
11025	2	1	10.5	8.3	7.2	6.5	5.0	3.6	2.9	2.2	1.7	1.4	703.3	1.	210.
		2	8.6	6.6	5.7	5.1	3.8	2.7	2.1	1.6	1.3	1.0	483.1	2.	433.
		3	12.1	10.0	8.9	8.1	6.3	4.6	3.6	2.8	2.1	1.7	219.4	-5.	392.
		4	18.9	15.6	13.8	12.5	9.9	7.4	6.0	4.8	3.7	3.0	126.4	11.	377.
		5	21.3	17.6	15.6	14.0	11.1	8.3	6.6	5.2	4.0	3.2	138.4	5.	620.
11050	2	1	9.1	6.9	5.8	5.2	3.9	2.8	2.2	1.7	1.3	1.1	574.9	5.	429.
		2	12.5	10.5	9.2	8.4	6.4	4.7	3.7	2.8	2.1	1.7	165.2	-3.	370.
		3	17.6	14.8	13.0	12.1	9.5	7.1	5.7	4.5	3.5	2.8	100.6	-8.	450.
		4	21.9	18.1	15.8	14.5	11.4	8.6	7.0	5.5	4.2	3.4	74.7	19.	558.
		5	24.6	20.2	17.9	16.4	12.9	10.0	7.6	6.2	4.9	4.0	54.6	-27.	612.
11075	2	1	11.1	8.5	7.1	6.3	4.7	3.4	2.7	2.1	1.6	1.2	640.1	1.	275.
		2	18.2	15.1	13.4	12.2	9.5	7.1	5.7	4.5	3.5	2.8	323.8	-6.	417.
		3	21.5	18.1	15.9	14.3	11.4	8.5	6.9	5.4	4.2	3.4	240.2	-17.	610.
		4	25.6	21.3	18.8	17.0	13.5	10.1	8.2	6.4	5.0	4.1	128.4	5.	550.
		5	27.8	23.3	20.6	18.6	14.7	11.1	9.0	7.1	5.5	4.5	104.3	-37.	670.
11100	2	1	16.5	13.4	11.6	10.4	8.2	5.9	4.8	3.7	2.8	2.3	370.3	-11.	322.
		2	22.6	18.6	16.3	14.7	11.6	8.7	7.0	5.5	4.2	3.4	235.7	19.	616.
		3	27.1	22.5	19.9	18.0	14.2	10.6	8.6	6.8	5.2	4.3	126.3	-23.	650.
		4	31.1	25.0	22.1	19.7	15.8	11.7	9.5	7.6	5.8	4.8	67.3	3.	587.
11125	2	1	16.9	14.1	12.2	11.0	8.6	6.5	5.2	4.2	3.4	2.7	134.5	9.	422.
		2	25.2	20.8	18.3	16.6	13.2	10.1	8.3	6.6	5.4	4.5	58.1	0.	548.
		3	30.5	24.0	21.5	19.5	15.6	12.1	9.9	8.1	6.7	5.7	30.8	-42.	579.
11150	2	1	15.7	12.9	11.0	10.1	7.6	5.4	4.3	3.2	2.4	1.7	203.6	13.	376.
		2	24.8	19.3	16.1	14.8	11.5	8.5	6.9	5.5	4.3	3.5	91.0	-44.	504.
11175	2	1	14.2	11.0	9.6	8.4	6.4	4.7	3.7	2.7	2.3	1.8	165.0	-42.	370.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 59W.IND
DATA FILE : 59W.DAT

LINE NO. : 594

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	7.0	5.6	4.9	4.4	3.5	2.6	2.1	1.7	1.3	1.0	353.2	-5.	120.
		2	8.6	7.1	6.3	5.7	4.5	3.4	2.8	2.2	1.7	1.5	98.6	-10.	101.
		3	9.5	8.1	7.4	6.7	5.4	4.1	3.4	2.7	2.0	2.0	55.4	0.	113.
		4	12.6	10.7	9.9	9.1	7.8	6.4	5.5	4.9	4.2	3.3	33.3	4.	113.
		5	13.8	11.7	10.5	9.5	8.1	6.9	6.5	5.0	4.2	4.1	23.6	4.	120.
10850	2	1	5.9	4.9	4.0	3.8	2.8	2.1	1.5	1.1	.8	.6	248.2	-9.	173.
		2	7.7	6.5	5.5	5.1	4.0	3.1	2.8	2.4	1.9	1.8	81.8	4.	171.
		3	9.2	7.9	6.7	6.6	5.3	3.6	3.5	2.9	2.3	2.0	38.0	2.	158.
		4	10.5	9.6	8.9	8.6	7.0	5.2	4.5	3.7	3.1	2.8	22.9	10.	159.
		5	14.0	11.4	8.3	8.9	7.3	6.5	5.9	5.1	4.9	4.5	15.6	-18.	163.
10875	2	1	6.0	4.8	4.0	3.7	2.8	2.0	1.6	1.2	.9	.7	612.8	6.	260.
		2	8.8	7.2	6.1	5.6	4.4	3.3	2.7	2.1	1.6	1.3	194.3	2.	247.
		3	10.7	8.7	7.5	7.0	5.6	4.2	3.5	2.8	2.2	1.8	96.3	-2.	244.
		4	12.3	9.9	8.7	8.2	6.7	5.2	4.4	3.6	3.0	2.5	55.5	-1.	235.
		5	13.4	10.5	9.0	8.8	7.4	5.9	5.2	4.3	3.7	3.3	34.7	-4.	220.
10900	2	1	7.0	5.5	4.5	4.0	3.0	2.2	1.7	1.3	1.0	.7	628.9	25.	282.
		2	9.1	7.3	6.5	6.1	4.5	3.4	2.6	2.1	1.7	1.4	210.6	0.	283.
		3	11.3	9.4	8.2	7.6	5.9	4.4	3.6	2.9	2.2	1.8	104.7	-10.	280.
		4	11.9	10.0	8.7	8.2	6.4	4.8	3.9	3.2	2.4	2.0	51.3	4.	229.
		5	11.2	10.6	10.4	8.5	6.3	5.4	5.0	3.7	3.0	3.1	36.6	-18.	246.
10925	2	1	6.5	5.0	4.3	3.9	2.9	2.1	1.6	1.3	.9	.7	476.6	1.	277.
		2	10.2	8.2	7.1	6.5	5.0	3.6	2.9	2.2	1.6	1.3	179.1	-8.	312.
		3	11.3	9.3	8.1	7.5	5.7	4.2	3.3	2.6	1.9	1.4	80.3	-10.	279.
		4	11.2	9.2	8.1	7.6	5.9	4.6	3.7	3.1	2.4	1.8	40.8	0.	237.
		5	10.2	8.2	7.4	6.8	5.1	3.7	2.7	1.7	.8	.3	33.8	-8.	294.
10950	2	1	7.5	5.8	5.1	4.4	3.4	2.4	1.9	1.4	1.1	.8	576.5	-10.	377.

		2	10.1	8.1	7.2	6.3	4.9	3.6	2.8	2.1	1.5	1.2	158.5	4.	311.
		3	10.9	8.8	8.0	7.0	5.6	4.0	3.1	2.4	1.7	1.2	85.1	-13.	333.
		4	10.1	8.4	7.7	6.5	5.2	3.7	2.8	2.0	1.3	.8	53.6	-2.	350.
		5	8.7	7.3	6.7	5.4	4.4	3.1	2.2	1.5	.7	.2	29.2	-7.	286.
10975	2	1	8.0	6.3	5.4	4.7	3.6	2.7	2.0	1.5	1.2	.9	642.0	-10.	276.
		2	10.0	8.1	7.1	6.3	5.0	3.3	2.8	2.1	1.5	1.3	229.6	1.	296.
		3	9.8	7.8	6.2	6.1	4.8	3.4	2.5	1.9	1.3	1.0	116.5	-15.	300.
		4	9.0	6.9	6.1	5.4	4.2	2.9	2.2	1.6	1.1	.9	65.4	7.	281.
		5	9.1	6.7	5.8	5.1	4.1	2.7	2.0	1.3	.8	.6	59.7	-3.	385.
11000	2	1	6.9	5.4	4.6	4.2	3.1	2.2	1.7	1.3	1.0	.7	874.9	-3.	361.
		2	8.7	7.0	6.1	5.6	4.2	3.1	2.5	1.9	1.4	1.1	265.4	-10.	328.
		3	8.8	6.9	6.0	5.4	4.2	3.0	2.4	1.8	1.4	1.0	144.8	1.	350.
		4	8.8	6.9	6.1	5.5	4.2	3.1	2.3	1.9	1.3	1.0	86.7	9.	358.
		5	8.8	7.3	6.1	5.3	4.3	3.1	2.2	1.7	1.3	.9	66.1	20.	409.
11025	2	1	6.8	5.2	4.5	4.2	3.1	2.2	1.7	1.3	1.0	.8	819.6	-8.	279.
		2	8.5	6.6	5.7	5.3	3.9	2.8	2.2	1.7	1.3	1.0	306.7	1.	314.
		3	9.1	7.2	6.3	5.8	4.4	3.2	2.5	1.9	1.5	1.1	216.4	6.	440.
		4	9.3	7.2	6.2	5.9	4.2	2.9	2.3	1.7	1.2	.9	128.0	26.	430.
		5	11.8	9.4	8.2	7.7	5.7	4.2	3.2	2.5	1.8	1.4	113.3	-23.	580.
11050	2	1	6.3	5.1	4.1	3.7	3.0	2.2	1.7	1.1	.7	.5	624.5	4.	284.
		2	8.4	6.9	5.8	5.3	4.0	2.9	2.3	1.8	1.3	1.1	322.1	10.	439.
		3	9.2	7.4	6.2	5.7	4.3	3.2	2.4	1.9	1.4	1.1	166.9	19.	450.
		4	11.4	9.4	8.0	7.5	5.7	4.2	3.3	2.6	1.9	1.5	133.1	-14.	600.
		5	15.4	12.8	10.8	10.2	7.8	5.8	4.6	3.6	2.7	2.1	105.0	6.	710.
11075	2	1	6.9	5.3	4.6	4.2	3.1	2.2	1.7	1.4	1.0	.8	702.2	4.	306.
		2	8.9	6.8	5.9	5.5	4.0	2.9	2.3	1.7	1.3	1.0	324.2	21.	424.
		3	11.0	8.7	7.7	7.0	5.3	3.9	3.0	2.3	1.8	1.4	221.1	-19.	570.
		4	15.0	12.0	10.6	9.6	7.4	5.5	4.4	3.4	2.6	2.1	158.0	13.	680.
		5	15.7	12.6	11.3	10.3	7.8	5.8	4.6	3.6	2.7	2.2	111.7	-6.	730.
11100	2	1	7.9	6.2	5.2	4.6	3.5	2.5	2.0	1.5	1.1	.9	557.1	19.	349.
		2	10.8	8.4	7.2	6.4	5.0	3.6	2.8	2.1	1.5	1.2	280.3	-13.	528.
		3	14.5	11.7	10.0	9.0	7.1	5.1	4.1	3.1	2.2	1.8	173.8	16.	650.
		4	15.6	12.4	10.6	9.7	7.6	5.5	4.4	3.3	2.4	1.8	112.5	-3.	700.
11125	2	1	9.1	7.2	6.2	5.8	4.3	3.2	2.6	2.0	1.7	1.4	91.4	-19.	358.
		2	14.1	11.5	10.0	8.2	7.1	5.3	4.3	3.5	3.0	2.6	44.7	15.	526.
		3	14.7	12.6	10.7	10.1	7.8	5.9	5.0	4.1	3.7	3.4	26.1	-9.	610.
11150	2	1	13.7	10.9	9.5	8.4	6.7	5.0	4.1	3.3	2.8	2.4	124.7	21.	391.
		2	16.7	13.3	11.6	10.4	8.8	7.0	6.0	5.2	4.4	3.8	57.3	-8.	540.
11175	2	1	12.7	9.9	8.6	7.8	5.9	4.2	3.4	2.6	2.0	1.5	284.3	-10.	446.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 58W.IND
DATA FILE : 58W.DAT

LINE NO. : 584

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	8.1	6.4	5.4	4.9	3.8	2.7	2.2	1.7	1.3	1.0	622.8	19.	196.
		2	9.7	7.7	6.6	6.0	4.6	3.3	2.7	2.0	1.5	1.2	223.1	-13.	210.
		3	9.8	8.1	7.0	6.4	5.0	3.8	2.9	2.2	1.6	1.3	114.2	10.	214.
		4	12.0	10.0	8.8	8.0	6.2	4.4	3.7	2.8	2.0	1.7	53.0	-22.	167.
		5	12.2	10.0	8.9	8.6	6.8	5.2	3.8	2.9	2.0	1.5	35.4	-33.	167.
10850	2	1	7.7	6.5	5.3	4.8	3.6	2.7	2.1	1.7	1.2	1.0	750.4	-33.	248.
		2	9.7	8.4	7.3	6.6	5.1	3.9	3.1	2.2	1.9	1.4	245.3	19.	243.
		3	11.4	10.1	8.7	8.0	6.3	4.8	3.8	3.0	2.3	1.8	95.9	-42.	189.
		4	13.5	12.0	10.4	9.5	7.7	6.0	4.9	3.8	2.9	2.3	47.5	-7.	157.
		5	10.8	11.2	9.4	9.0	8.0	6.0	4.9	4.0	3.3	2.2	38.3	15.	189.
10875	2	1	6.4	5.1	4.3	3.7	2.9	2.1	1.7	1.3	1.0	.8	490.3	13.	296.
		2	9.8	8.2	7.0	6.4	5.0	3.6	2.9	2.2	1.6	1.3	133.4	-40.	241.
		3	12.1	10.4	9.0	8.2	6.5	4.8	3.8	2.8	2.1	1.7	58.7	0.	212.
		4	10.9	9.2	8.0	7.4	5.7	4.2	3.3	2.5	1.7	1.2	31.9	13.	192.
		5	8.5	7.0	5.9	5.5	3.9	2.9	2.0	1.3	.8	.4	22.9	-26.	207.
10900	2	1	7.6	6.1	5.3	4.8	3.6	2.7	2.1	1.6	1.2	.9	519.8	-39.	240.
		2	12.3	10.3	8.9	8.1	6.6	4.9	4.1	3.3	2.6	2.2	176.3	2.	244.
		3	13.0	11.1	9.8	9.0	7.3	5.6	4.6	3.7	2.9	2.4	79.3	3.	219.
		4	11.8	10.1	8.8	7.7	6.2	4.9	4.1	3.2	2.6	2.1	49.5	-12.	228.
		5	12.1	9.4	8.8	7.9	6.3	4.9	4.7	3.7	2.8	2.7	37.3	10.	258.
10925	2	1	8.2	6.7	5.7	5.4	4.0	2.9	2.3	1.7	1.1	1.0	812.5	-7.	349.
		2	11.6	9.7	8.5	7.9	6.2	4.7	3.8	2.9	2.3	1.8	228.0	9.	294.
		3	12.1	10.4	9.1	8.7	6.9	5.2	4.3	3.4	2.7	2.2	119.4	-16.	300.
		4	11.7	10.0	8.7	8.3	6.7	5.1	4.2	3.5	2.8	2.3	66.4	12.	285.
		5	11.8	12.4	9.7	7.5	6.7	5.1	4.8	3.4	2.7	2.6	54.8	2.	353.
10950	2	1	7.6	6.3	5.5	4.8	3.8	2.8	2.5	1.7	1.3	1.0	888.8	-1.	367.

		2	10.9	9.1	8.1	7.3	5.9	4.3	3.5	2.8	2.2	1.7	260.7	-18.	323.
		3	11.2	9.5	8.5	7.6	6.2	4.7	3.9	3.1	2.4	2.0	132.2	21.	320.
		4	11.8	10.0	9.0	8.0	6.6	5.0	4.3	3.5	2.8	2.4	93.4	8.	386.
		5	12.7	10.8	9.9	8.7	7.1	5.5	4.7	3.9	3.1	2.8	71.2	-20.	441.
10975	2	1	8.0	6.7	5.6	5.1	4.0	3.0	2.4	1.9	1.4	1.0	766.5	-19.	286.
		2	9.7	8.2	7.1	6.4	5.1	3.8	3.0	2.3	1.7	1.3	267.0	22.	299.
		3	9.8	8.6	7.3	6.6	5.3	3.9	3.1	2.4	1.7	1.4	163.2	-3.	360.
		4	10.9	9.2	7.9	7.1	5.7	4.2	3.4	2.6	1.9	1.4	118.1	-5.	440.
		5	15.2	13.1	11.5	10.2	8.1	6.0	4.8	3.8	2.8	2.2	86.0	-10.	482.
11000	2	1	7.5	6.0	5.2	4.6	3.6	2.6	2.0	1.5	1.1	.9	620.7	18.	249.
		2	8.8	7.1	6.1	5.4	4.3	3.1	2.4	1.8	1.3	1.0	308.5	-17.	372.
		3	10.4	8.5	7.3	6.6	5.2	3.7	2.9	2.2	1.6	1.2	168.2	-7.	400.
		4	14.0	11.5	9.9	9.0	7.1	5.1	4.0	3.0	2.2	1.6	109.2	4.	430.
		5	16.2	13.3	11.4	10.4	8.3	6.0	4.6	3.5	2.4	1.8	126.1	-7.	760.
11025	2	1	7.4	6.1	4.9	4.6	3.5	2.5	2.0	1.5	1.1	.8	431.5	16.	233.
		2	9.1	7.6	6.2	5.8	4.3	3.1	2.4	1.8	1.3	.9	211.0	-2.	342.
		3	12.9	10.8	9.0	8.4	6.4	4.6	3.6	2.7	1.9	1.4	135.3	-11.	430.
		4	14.9	12.5	10.5	9.8	7.3	5.2	4.2	2.9	2.1	1.5	126.4	11.	680.
		5	16.4	13.7	11.2	10.9	8.0	5.6	4.4	3.1	2.1	1.4	77.1	0.	626.
11050	2	1	7.1	5.5	4.8	4.1	3.1	2.2	1.7	1.3	1.0	.7	623.6	-16.	343.
		2	12.6	10.1	8.9	7.7	6.2	4.4	3.6	2.7	2.1	1.6	231.3	1.	382.
		3	15.1	12.3	10.9	9.6	7.6	5.5	4.4	3.4	2.5	2.0	225.7	-6.	740.
		4	17.1	14.0	12.4	10.9	8.6	6.2	5.0	3.8	2.9	2.2	117.9	10.	640.
		5	20.1	16.5	14.7	12.8	10.1	7.6	5.9	4.5	3.5	2.7	82.5	-2.	681.
11075	2	1	11.6	9.2	8.1	7.2	5.7	4.1	3.4	2.6	2.0	1.6	379.7	-1.	259.
		2	15.1	12.3	10.8	9.7	7.6	5.7	4.6	3.5	2.7	2.2	303.4	-1.	621.
		3	17.0	14.0	12.4	11.1	8.8	6.6	5.3	4.2	3.2	2.6	147.4	-4.	600.
		4	21.0	17.4	15.6	13.8	11.1	8.3	6.8	5.3	4.1	3.3	97.6	-1.	666.
		5	22.1	18.4	16.6	14.7	12.0	9.2	7.4	6.0	4.6	3.7	57.8	3.	591.
11100	2	1	14.0	11.1	10.0	8.9	6.9	5.1	4.1	3.2	2.4	1.9	502.9	-4.	607.
		2	16.8	13.3	12.0	10.7	8.3	6.2	4.9	3.9	3.0	2.4	175.3	9.	635.
		3	20.2	16.1	14.5	13.0	10.3	7.7	6.1	4.9	3.8	3.0	106.0	-13.	760.
		4	23.0	18.2	16.5	14.7	11.8	8.9	7.2	5.8	4.5	3.6	53.9	10.	651.
11125	2	1	13.7	11.3	9.9	8.7	7.0	5.1	4.2	3.3	2.6	2.1	206.4	7.	498.
		2	18.4	15.0	13.3	11.7	9.5	6.9	5.8	4.4	3.5	3.0	93.6	1.	678.
		3	21.3	17.2	15.5	13.5	10.9	8.6	6.8	5.9	4.4	3.7	50.5	-8.	731.
11150	2	1	16.1	13.1	11.5	10.3	8.0	5.9	4.7	3.6	2.8	2.2	308.2	-9.	744.
		2	19.3	15.6	13.6	12.2	9.5	7.0	5.6	4.3	3.3	2.5	111.0	1.	804.
11175	2	1	17.5	14.0	12.1	10.9	8.3	6.0	4.7	3.6	2.7	2.1	175.4	0.	680.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 57W.IND
DATA FILE : 57W.DAT

LINE NO. : 574

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	8.4	6.5	5.5	5.0	3.8	2.7	2.2	1.7	1.3	1.0	612.9	6.	356.
		2	10.5	8.5	7.5	6.9	5.4	4.0	3.3	2.6	2.0	1.6	130.7	-7.	227.
		3	13.1	11.0	9.7	9.1	7.3	5.6	4.6	3.7	3.0	2.5	50.5	-2.	175.
		4	14.5	12.4	11.2	10.6	8.6	6.9	5.7	4.9	3.8	3.1	28.2	1.	163.
		5	10.4	9.0	8.5	7.9	6.5	5.6	4.8	4.0	3.5	3.0	23.0	-4.	200.
10850	2	1	7.6	6.3	5.2	4.6	3.6	2.6	2.1	1.6	1.2	1.0	448.3	1.	213.
		2	12.2	10.4	9.0	8.1	6.5	4.9	4.0	3.1	2.4	1.9	113.8	-14.	162.
		3	13.9	12.0	10.7	9.9	8.1	6.1	5.1	4.0	3.1	2.5	63.0	-28.	179.
		4	11.2	9.5	8.4	7.9	6.5	5.2	4.5	3.6	2.8	2.3	37.1	28.	176.
		5	9.4	8.3	7.6	7.3	6.2	4.9	4.1	3.4	2.8	2.2	32.0	12.	228.
10875	2	1	9.0	7.6	6.2	5.4	4.3	3.0	2.3	1.8	1.3	1.0	381.3	-9.	202.
		2	13.0	11.3	9.8	8.6	6.8	5.0	3.8	3.0	2.1	1.6	126.4	7.	201.
		3	10.5	9.2	8.1	7.0	5.7	4.0	3.1	2.3	1.5	1.1	69.7	-13.	221.
		4	7.9	7.1	6.0	4.9	4.0	2.7	2.0	1.3	.6	.3	50.5	28.	268.
		5	5.6	4.9	4.4	3.4	2.7	1.6	1.1	.5	.0	-.1	36.1	-16.	288.
10900	2	1	9.6	7.9	6.8	6.0	4.7	3.4	2.7	2.0	1.6	1.4	468.4	13.	216.
		2	10.8	9.0	7.8	7.1	5.7	4.2	3.3	2.5	1.8	1.4	162.3	-10.	224.
		3	8.6	7.3	6.3	5.6	4.4	3.1	2.4	1.8	1.2	.9	98.3	18.	271.
		4	6.7	5.7	4.9	4.3	3.3	2.2	1.6	1.1	.7	.4	64.0	-3.	295.
		5	10.6	8.9	7.5	6.6	5.1	3.5	2.7	1.9	1.3	.9	54.9	-33.	380.
10925	2	1	8.1	6.6	5.6	5.2	4.0	3.0	2.4	1.9	1.4	1.1	435.7	15.	220.
		2	8.6	7.3	6.3	5.8	4.6	3.5	2.8	2.2	1.7	1.3	198.8	22.	302.
		3	8.1	7.0	6.1	5.7	4.6	3.6	2.9	2.3	1.9	1.4	116.5	-4.	350.
		4	12.8	10.8	9.5	8.9	7.2	5.6	4.7	3.8	3.0	2.5	84.9	-28.	430.
		5	18.2	15.2	13.5	12.6	10.0	8.0	6.6	5.4	4.2	3.5	63.6	-11.	483.
10950	2	1	6.0	4.7	4.0	3.5	2.7	1.9	1.5	1.1	.8	.7	635.4	29.	273.

		2	6.7	5.4	4.6	4.2	3.3	2.4	1.9	1.4	1.0	.7	253.6	-6.	327.
		3	11.3	9.3	8.2	7.4	5.9	4.3	3.5	2.6	1.9	1.4	171.9	-30.	440.
		4	16.6	13.7	11.9	10.9	8.7	6.5	5.3	4.1	3.1	2.4	110.4	4.	470.
		5	21.6	18.0	15.7	14.3	11.3	8.3	6.6	5.2	3.7	2.9	100.2	-4.	640.
10975	2	1	5.0	4.0	3.4	2.8	2.2	1.6	1.2	.9	.7	.5	513.8	-2.	268.
		2	9.8	8.2	7.1	6.3	4.9	3.7	2.9	2.3	1.8	1.4	259.2	-24.	406.
		3	15.3	12.8	11.2	9.9	7.9	5.9	4.8	3.7	2.9	2.3	147.0	-2.	460.
		4	21.0	17.4	15.8	13.1	11.5	8.7	7.0	5.4	4.0	3.4	122.2	2.	630.
		5	25.2	21.5	18.1	17.7	12.8	9.4	7.7	6.2	5.1	3.9	84.4	-11.	662.
11000	2	1	8.4	6.8	5.8	5.3	4.0	3.0	2.4	1.9	1.4	1.1	671.0	-39.	324.
		2	14.2	11.6	10.1	9.2	7.1	5.3	4.2	3.3	2.6	2.0	305.6	4.	442.
		3	21.4	17.8	15.7	14.3	11.2	8.4	6.7	5.3	4.0	3.2	242.5	20.	700.
		4	24.1	20.0	17.6	16.1	12.7	9.5	7.7	6.1	4.7	3.8	122.0	-26.	580.
		5	36.6	30.6	27.2	25.0	19.9	15.1	12.3	9.8	7.6	6.2	80.0	-19.	579.
11025	2	1	12.3	9.5	8.5	7.7	6.0	4.4	3.5	2.7	2.1	1.7	828.0	2.	388.
		2	23.7	19.1	16.9	15.4	12.0	8.9	7.2	5.6	4.4	3.5	455.3	24.	640.
		3	25.7	21.2	18.9	17.4	13.7	10.2	8.3	6.5	5.1	4.2	206.8	-45.	580.
		4	38.7	32.2	28.9	26.8	21.2	16.2	13.4	10.7	8.4	7.0	103.9	6.	480.
		5	27.2	22.4	19.9	18.3	14.9	11.4	9.3	7.6	6.1	5.1	61.0	-1.	428.
11050	2	1	24.6	20.1	17.5	15.9	12.4	9.1	7.3	5.7	4.4	3.5	1043.0	20.	530.
		2	27.7	23.0	20.3	18.6	14.5	10.7	8.6	6.7	5.1	4.1	339.0	-35.	523.
		3	36.9	31.9	28.4	26.1	20.8	15.7	12.7	10.0	7.8	6.2	174.1	-28.	530.
		4	26.1	21.7	19.4	17.9	13.9	10.3	8.3	6.4	4.9	3.8	74.5	31.	383.
		5	34.8	28.9	25.5	23.6	18.4	13.6	10.9	8.4	6.4	5.1	70.6	-7.	545.
11075	2	1	29.4	24.0	21.2	19.2	15.1	11.2	9.0	7.0	5.4	4.4	711.9	-43.	456.
		2	42.5	35.7	31.9	29.2	23.2	17.5	14.3	11.2	8.7	7.1	267.3	-21.	513.
		3	29.2	24.5	21.6	19.9	15.7	11.7	9.5	7.3	5.6	4.4	98.9	20.	379.
		4	37.5	31.3	27.6	25.4	19.9	14.8	12.0	9.2	7.0	5.6	86.1	6.	551.
		5	41.7	34.9	30.9	28.5	22.4	16.6	13.5	10.5	7.9	6.3	56.3	-9.	541.
11100	2	1	46.3	39.1	34.8	30.9	25.5	19.4	15.8	12.6	9.8	8.0	344.9	-18.	492.
		2	33.3	27.9	24.9	22.7	18.1	13.8	11.3	8.9	7.0	5.7	100.4	25.	429.
		3	39.2	32.9	29.3	26.6	21.3	16.1	13.3	10.5	8.3	6.7	75.3	-8.	643.
		4	43.9	36.9	32.9	29.8	24.0	18.4	15.2	11.9	9.4	7.8	46.0	10.	655.
11125	2	1	34.6	29.2	25.8	23.3	18.4	13.8	11.1	8.7	6.6	5.3	299.3	24.	494.
		2	39.8	32.6	28.7	25.8	20.4	15.1	12.1	9.4	7.1	5.6	153.9	0.	763.
		3	41.7	34.2	30.3	27.2	21.5	15.9	12.7	9.7	7.3	5.8	80.4	0.	795.
11150	2	1	36.3	30.2	26.6	24.0	19.0	14.2	11.5	9.1	7.0	5.7	272.3	0.	1060.
		2	40.9	34.1	30.3	27.4	22.0	16.6	13.6	10.9	8.6	7.0	91.3	2.	1074.
11175	2	1	40.6	33.7	29.7	26.8	21.0	15.5	12.5	9.8	7.5	6.0	165.8	1.	1300.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 56W.IND
DATA FILE : 56W.DAT

LINE NO. : 564

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	9.1	7.4	6.5	5.8	4.6	3.4	2.6	2.0	1.6	1.2	322.9	-17.	253.
		2	14.7	12.4	11.0	10.0	8.0	5.9	5.1	3.9	2.8	2.6	92.3	2.	217.
		3	11.5	9.8	8.7	8.1	6.5	5.0	4.2	3.3	2.5	2.1	48.7	31.	228.
		4	12.2	10.6	9.1	8.3	6.9	5.2	4.2	3.4	2.8	2.5	55.4	-15.	434.
		5	9.4	8.5	6.7	6.4	5.4	4.2	3.6	2.9	2.5	2.2	29.8	2.	350.
10850	2	1	10.9	8.9	7.6	7.1	5.5	4.0	3.2	2.4	1.8	1.4	305.8	-4.	160.
		2	11.0	9.2	8.0	7.5	5.8	4.3	3.4	2.6	1.9	1.4	134.4	27.	211.
		3	11.5	9.6	8.2	7.6	5.9	4.3	3.4	2.5	1.7	1.1	149.1	-11.	460.
		4	7.7	6.3	4.8	4.6	3.1	1.9	1.1	.4	.0	-.2	54.3	-19.	284.
		5	5.7	4.5	3.1	3.1	1.9	1.0	.4	.0	-.6	-1.0	42.0	23.	329.
10875	2	1	7.8	6.3	5.6	5.0	3.9	2.9	2.3	1.8	1.4	1.1	311.0	20.	195.
		2	11.3	9.3	8.4	7.5	5.9	4.3	3.4	2.7	2.0	1.6	259.3	-15.	488.
		3	7.9	6.5	6.0	5.3	4.2	3.2	2.4	1.9	1.4	1.1	76.9	-10.	289.
		4	6.4	5.2	4.8	4.1	3.2	2.5	1.8	1.4	1.0	.8	53.3	-1.	334.
		5	13.0	10.6	10.0	8.9	7.0	5.2	4.2	3.2	2.6	2.0	33.0	-20.	310.
10900	2	1	10.1	8.3	7.2	6.3	5.0	3.6	3.0	2.2	1.6	1.3	742.9	-14.	448.
		2	6.8	6.0	5.3	4.6	3.8	2.7	2.1	1.7	1.2	.9	151.1	-3.	273.
		3	4.6	4.1	3.4	2.8	1.7	.7	.7	.6	.8	.6	98.4	5.	355.
		4	11.5	10.0	8.5	7.3	7.1	6.0	4.4	3.1	1.5	1.2	52.7	-27.	318.
		5	12.1	10.7	9.1	8.0	6.5	4.8	3.6	2.8	1.9	1.5	40.1	7.	363.
10925	2	1	6.7	5.5	4.7	4.1	3.2	2.4	1.9	1.5	1.1	.9	830.1	-12.	221.
		2	4.8	4.0	3.3	2.8	2.2	1.6	1.2	.9	.7	.5	426.9	12.	341.
		3	12.1	10.4	9.0	8.1	6.5	4.8	3.9	3.1	2.3	1.9	206.2	-26.	328.
		4	13.6	11.5	10.2	9.0	7.3	5.5	4.4	3.5	2.7	2.2	138.1	-11.	367.
		5	16.9	14.2	12.4	11.1	8.8	6.6	5.3	4.3	3.3	2.8	94.2	17.	376.
10950	2	1	6.5	5.1	4.3	3.9	2.9	2.1	1.7	1.3	1.0	.7	2536.0	7.	773.

		2	14.5	12.1	10.6	9.7	7.6	5.7	4.6	3.6	2.8	2.3	756.1	-24.	692.
		3	17.4	14.5	12.9	11.8	9.3	7.1	5.8	4.7	3.7	3.1	366.8	-21.	669.
		4	20.6	17.2	15.2	14.0	11.0	8.3	6.8	5.4	4.3	3.6	201.9	6.	615.
		5	29.2	24.1	21.4	19.7	15.5	11.7	9.6	7.7	6.2	5.1	123.2	24.	563.
10975	2	1	12.9	10.3	9.1	8.0	6.3	4.7	3.8	2.9	2.3	1.8	1078.0	-25.	560.
		2	18.8	15.6	13.9	12.5	10.0	7.5	6.2	4.9	3.8	3.1	403.5	-10.	633.
		3	21.2	17.4	15.4	13.9	11.0	8.3	6.9	5.6	4.3	3.4	204.2	-1.	630.
		4	30.2	25.1	22.0	20.0	16.0	11.9	9.5	7.1	5.8	4.9	106.8	6.	550.
		5	32.9	27.1	24.2	22.0	17.3	13.0	10.7	8.4	6.5	5.4	72.8	-12.	571.
11000	2	1	20.0	16.4	14.6	13.4	10.5	7.9	6.5	5.1	4.0	3.3	887.4	-7.	506.
		2	23.0	18.9	16.8	15.2	11.9	8.9	7.3	5.8	4.4	3.6	315.8	-8.	540.
		3	30.2	25.2	22.3	20.3	16.3	12.2	9.9	7.7	6.1	5.0	185.1	19.	630.
		4	34.4	28.6	25.5	23.1	18.3	13.6	11.1	8.7	6.8	5.5	102.0	-23.	580.
		5	40.6	33.5	29.4	26.6	21.6	16.2	13.3	10.9	8.2	6.7	78.3	24.	670.
11025	2	1	16.8	13.7	11.9	10.8	8.5	6.2	5.1	3.9	3.0	2.5	987.1	-3.	387.
		2	27.7	22.9	20.1	18.4	14.4	10.7	8.6	6.7	5.1	4.2	482.8	16.	568.
		3	31.6	26.3	23.1	21.2	16.6	12.3	9.9	7.7	5.9	4.8	230.7	-15.	540.
		4	37.8	31.6	27.8	25.4	20.0	14.8	12.0	9.3	7.1	5.7	167.1	7.	650.
		5	47.7	39.3	34.6	31.8	25.1	18.6	14.9	11.7	8.7	7.2	132.0	26.	770.
11050	2	1	24.8	20.3	17.8	16.0	12.5	9.2	7.4	5.7	4.3	3.5	556.8	5.	406.
		2	28.9	23.9	21.0	19.0	14.9	11.0	8.8	6.8	5.0	4.0	225.1	-10.	493.
		3	34.2	28.5	25.1	22.7	18.0	13.2	10.6	8.2	6.0	4.7	142.7	11.	620.
		4	45.0	37.6	33.2	30.1	23.7	17.5	14.0	10.8	8.0	6.3	106.4	14.	770.
		5	51.2	42.7	37.8	34.2	26.9	19.8	15.8	12.1	8.8	6.8	78.6	-10.	861.
11075	2	1	28.4	22.9	20.0	17.7	13.9	10.1	8.0	6.2	4.7	3.7	139.1	-17.	436.
		2	33.4	27.4	24.3	21.4	16.7	12.1	9.3	7.1	5.2	4.1	63.9	11.	602.
		3	43.3	35.3	31.4	27.7	21.5	15.5	12.0	9.2	6.8	5.4	42.8	18.	805.
		4	49.8	40.6	36.2	31.7	24.8	17.8	13.6	10.2	7.5	5.9	27.2	-16.	853.
		5	56.5	45.6	40.6	35.4	27.4	19.4	14.6	11.0	7.8	6.2	17.6	-15.	827.
11100	2	1	22.8	18.9	16.7	15.1	11.9	8.9	7.3	5.7	4.5	3.6	216.1	14.	521.
		2	39.4	32.9	29.0	26.3	21.1	16.1	13.1	10.5	8.3	6.8	110.7	7.	802.
		3	48.7	42.8	37.0	33.9	27.2	20.7	17.1	13.8	11.1	9.3	76.7	-10.	1109.
		4	62.8	53.3	47.3	43.5	35.3	27.0	22.7	18.1	14.1	11.4	34.5	-15.	832.
11125	2	1	23.2	19.9	17.8	16.3	12.7	9.2	7.5	5.7	4.4	3.5	187.7	13.	535.
		2	42.8	32.5	28.8	26.3	20.5	15.4	12.3	9.6	7.5	6.0	101.1	7.	865.
		3	54.6	45.1	39.8	36.6	28.9	21.7	17.5	13.6	10.4	8.4	55.9	-38.	955.
11150	2	1	31.2	25.8	22.5	20.0	16.2	10.9	10.1	7.4	6.0	4.7	166.5	3.	650.
		2	54.0	45.0	39.9	36.3	29.2	22.2	18.3	14.5	11.3	9.0	77.6	-36.	913.
11175	2	1	42.3	35.1	30.9	27.8	21.9	16.3	13.2	10.3	7.9	6.4	198.8	-36.	690.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 55W.IND
DATA FILE : 55W.DAT

LINE NO. : 554

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	9.6	7.8	6.6	5.8	4.4	3.2	2.5	2.0	1.5	1.2	395.2	-1.	113.
		2	11.2	9.6	8.5	7.6	6.0	4.5	3.5	2.7	2.1	1.6	221.0	22.	189.
		3	8.7	7.5	6.7	5.9	4.7	3.6	2.7	2.1	1.6	1.2	124.6	-41.	212.
		4	7.8	6.4	5.7	5.0	3.9	2.9	2.2	1.8	1.3	1.0	88.7	-11.	253.
		5	5.9	4.8	4.3	3.7	3.0	2.2	1.6	1.3	1.0	.7	67.0	-2.	287.
10850	2	1	7.6	5.8	5.2	4.6	3.5	2.5	2.0	1.5	1.2	.9	620.4	23.	374.
		2	9.8	8.0	7.1	6.4	5.0	3.6	2.9	2.2	1.7	1.3	142.9	-46.	258.
		3	8.7	7.0	6.3	5.6	4.4	3.2	2.6	1.9	1.5	1.1	90.6	5.	327.
		4	7.1	6.0	5.3	4.5	3.6	2.5	2.1	1.5	1.2	.9	52.0	-12.	314.
		5	5.4	4.8	4.1	3.3	2.8	1.9	1.5	1.0	.9	.7	51.4	-3.	465.
10875	2	1	6.8	5.2	4.6	4.1	3.1	2.3	1.8	1.4	1.0	.8	592.1	-49.	199.
		2	8.1	6.5	5.9	5.1	4.0	2.9	2.3	1.8	1.4	1.1	272.2	-3.	275.
		3	6.7	5.2	5.0	4.2	3.3	2.4	1.9	1.5	1.1	.9	163.3	-14.	330.
		4	6.2	4.8	4.6	3.9	3.1	2.2	1.8	1.4	1.1	.8	124.1	11.	410.
		5	5.6	4.3	4.6	3.6	2.7	2.1	1.6	1.2	1.0	.7	104.6	6.	520.
10900	2	1	5.5	4.1	3.7	3.1	2.4	1.7	1.3	1.0	.8	.6	849.4	-3.	381.
		2	5.2	3.9	3.5	3.0	2.3	1.6	1.3	1.0	.7	.6	297.0	0.	399.
		3	4.0	2.9	2.7	2.3	1.8	1.3	1.0	.8	.3	.5	219.3	-11.	580.
		4	3.7	2.7	2.4	2.1	1.5	1.1	.8	.7	.6	.6	158.0	11.	700.
		5	13.2	10.7	9.6	8.8	7.0	5.4	4.3	3.5	2.8	2.4	94.9	4.	638.
10925	2	1	3.1	2.4	1.9	1.6	1.2	.8	.6	.4	.3	.2	681.4	1.	260.
		2	3.3	2.8	2.1	1.6	1.2	.8	.6	.4	.2	.1	416.9	-3.	478.
		3	2.2	2.0	1.4	1.0	.7	.4	.2	.1	.0	.0	288.9	-7.	660.
		4	12.5	10.7	9.2	8.1	6.5	4.9	4.0	3.1	2.3	1.8	155.2	12.	590.
		5	17.9	15.5	13.8	12.1	9.6	7.2	5.8	4.5	3.4	2.7	111.2	-10.	630.
10950	2	1	2.6	2.0	1.5	1.2	.9	.5	.4	.3	.2	.1	788.9	-4.	353.

		2	2.0	1.4	1.0	.8	.5	.3	.2	.1	.0	.0	426.4	0.	573.
		3	10.8	9.1	8.0	7.3	5.7	4.2	3.4	2.7	2.1	1.7	233.0	-1.	620.
		4	18.3	15.3	13.6	12.4	9.8	7.4	6.0	4.8	3.8	3.1	145.4	-13.	650.
		5	13.7	11.4	10.0	9.1	7.2	5.3	4.3	3.4	2.7	2.2	125.3	30.	840.
10975	2	1	1.7	.7	.6	.4	.2	.0	.0	.0	-.1	-.1	645.0	-1.	382.
		2	10.5	8.5	7.5	6.7	5.3	3.9	3.1	2.4	1.9	1.5	300.3	9.	533.
		3	18.7	15.2	13.7	12.3	9.8	7.3	6.0	4.6	3.5	2.8	173.6	-31.	610.
		4	14.0	11.2	10.1	9.0	7.0	5.1	4.1	3.1	2.4	1.8	146.2	24.	860.
		5	23.0	18.2	16.0	14.1	11.2	8.4	6.6	4.7	3.4	3.3	110.5	19.	980.
11000	2	1	9.5	7.9	6.8	6.1	4.7	3.5	2.7	2.2	1.6	1.3	592.6	6.	387.
		2	19.9	16.7	14.8	13.3	10.5	8.0	6.5	5.1	4.0	3.2	285.5	-25.	560.
		3	15.1	12.6	11.1	9.9	7.8	5.8	4.5	3.6	2.8	2.2	220.4	22.	860.
		4	23.9	19.7	17.4	15.6	12.2	9.1	7.2	5.7	4.3	3.5	161.3	21.	1050.
		5	49.6	41.8	37.0	33.3	26.7	20.3	16.3	13.1	10.1	8.2	103.3	-47.	1010.
11025	2	1	19.4	16.2	14.2	12.7	10.3	7.7	6.3	4.9	3.8	3.1	411.5	-25.	391.
		2	16.0	13.2	11.5	10.2	8.3	6.1	5.0	3.9	3.0	2.4	256.2	30.	731.
		3	23.8	19.7	17.3	15.3	12.2	9.0	7.3	5.8	4.5	3.7	173.6	9.	980.
		4	50.3	42.2	37.3	33.5	27.3	20.6	17.0	13.4	10.5	8.6	103.3	-39.	980.
		5	68.3	57.4	51.1	45.8	37.3	28.1	23.2	18.5	14.5	12.0	67.0	34.	956.
11050	2	1	11.3	9.0	7.9	7.0	5.5	4.0	3.2	2.5	2.0	1.6	587.7	31.	498.
		2	20.9	16.8	14.9	13.3	10.4	7.8	6.3	5.0	3.9	3.2	311.5	6.	793.
		3	48.7	40.6	36.2	32.7	26.3	20.0	16.4	13.2	10.4	8.6	176.8	-40.	890.
		4	68.7	57.7	51.6	46.9	37.7	28.7	23.7	19.1	15.2	12.5	99.8	23.	847.
		5	58.7	49.0	44.0	39.8	32.2	24.7	20.5	16.7	13.5	11.2	55.2	2.	702.
11075	2	1	14.0	11.0	9.6	8.5	6.5	4.7	3.7	2.9	2.2	1.7	604.5	-6.	593.
		2	46.4	38.6	34.2	31.0	24.7	18.6	15.2	12.0	9.4	7.7	250.5	-34.	737.
		3	67.4	56.7	50.4	45.8	36.8	27.9	22.9	18.2	14.3	11.8	132.0	33.	770.
		4	57.9	48.7	43.3	39.2	31.7	24.1	20.0	15.9	12.6	10.4	59.8	-10.	586.
		5	63.2	44.0	48.5	41.7	30.5	21.9	18.1	14.7	14.3	9.0	37.8	25.	557.
11100	2	1	49.0	41.0	36.1	32.7	26.0	19.6	15.9	12.6	9.8	8.0	596.5	-48.	535.
		2	69.2	58.5	51.6	46.9	37.6	28.4	23.1	18.3	14.2	11.6	254.9	32.	686.
		3	56.9	48.5	42.6	38.7	31.2	23.5	19.1	15.2	11.7	9.5	100.1	-14.	530.
		4	53.9	44.4	38.3	34.7	27.9	20.8	16.7	13.3	10.1	8.0	55.2	-8.	495.
11125	2	1	77.0	64.9	57.8	52.6	42.0	31.8	26.0	20.7	16.2	13.3	601.1	35.	699.
		2	69.4	57.8	51.8	47.2	38.0	29.0	23.8	19.0	15.1	12.4	139.5	-10.	486.
		3	66.1	48.6	43.3	39.1	31.3	24.0	19.6	15.6	12.4	10.2	66.4	28.	462.
11150	2	1	83.0	70.0	62.3	56.9	45.6	34.7	28.4	22.8	17.9	14.8	302.4	-14.	499.
		2	72.4	57.8	50.7	46.0	36.9	28.0	23.1	18.8	14.5	11.2	96.7	32.	480.
11175	2	1	84.3	70.9	62.6	57.2	45.8	34.7	28.4	22.6	17.7	14.6	243.3	33.	477.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 54W.IND
DATA FILE : 54W.DAT

LINE NO. : 544

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	4.3	3.2	2.5	2.5	1.7	1.2	.9	.7	.5	.4	398.2	-10.	250.
		2	6.2	5.0	4.1	4.0	2.8	2.5	1.6	1.3	1.1	.7	93.6	29.	176.
		3	7.3	6.2	5.3	5.3	4.1	3.4	2.8	2.3	1.8	1.9	51.8	-27.	194.
		4	7.9	6.5	5.6	5.6	4.6	3.7	3.1	2.7	2.4	2.2	37.7	-23.	237.
		5	7.0	6.6	6.3	5.6	4.3	4.3	3.5	3.5	3.0	3.0	35.1	-5.	330.
10850	2	1	4.3	3.6	2.8	2.5	1.9	1.3	1.0	.8	.6	.5	403.7	28.	239.
		2	7.4	6.2	5.2	4.7	3.7	2.7	2.2	1.7	1.3	1.1	133.1	-25.	236.
		3	6.7	5.6	4.9	4.4	3.6	2.8	2.5	2.0	1.7	1.6	76.6	-30.	271.
		4	5.3	4.5	4.0	3.6	3.1	2.5	2.3	2.0	1.8	1.8	66.6	13.	394.
		5	5.8	4.9	4.7	4.2	3.7	3.3	2.8	2.5	2.4	2.2	62.6	-2.	556.
10875	2	1	4.3	3.1	2.6	2.2	1.7	1.1	.8	.6	.5	.3	717.6	-16.	250.
		2	5.9	4.5	4.0	3.5	2.6	1.7	1.3	.9	.6	.4	283.0	-22.	296.
		3	4.5	3.3	3.0	2.5	1.8	1.1	.7	.4	.2	.0	219.1	-4.	450.
		4	4.0	3.0	2.5	2.1	1.4	.7	.4	.1	.0	-.1	172.3	9.	600.
		5	11.9	9.3	8.2	7.2	5.3	3.6	2.7	1.8	1.1	.7	88.0	-17.	460.
10900	2	1	4.1	3.0	2.5	2.1	1.6	1.1	.8	.6	.4	.3	543.9	-37.	328.
		2	5.0	3.8	3.3	2.8	2.2	1.5	1.1	.8	.6	.5	273.1	18.	494.
		3	4.3	3.3	2.9	2.5	1.9	1.3	1.0	.7	.6	.4	197.7	-12.	710.
		4	13.6	11.0	9.7	8.6	6.8	4.9	4.0	3.1	2.4	1.9	90.2	4.	544.
		5	17.6	14.2	12.7	11.5	9.0	6.6	5.2	4.1	3.3	2.6	58.3	24.	528.
10925	2	1	4.6	3.5	3.1	2.6	2.0	1.5	1.1	.9	.7	.5	1175.0	10.	380.
		2	5.5	4.2	3.9	3.2	2.7	1.9	1.5	1.2	.9	.8	688.8	-3.	682.
		3	15.1	12.4	11.1	9.9	7.9	6.0	4.9	3.9	3.1	2.5	303.2	-6.	600.
		4	20.6	17.0	15.4	13.9	11.1	8.5	7.0	5.7	4.5	3.7	180.9	7.	590.
		5	15.7	12.8	11.6	10.7	8.6	6.9	5.5	4.5	3.7	3.0	125.1	-10.	620.
10950	2	1	3.7	2.5	2.2	1.8	1.4	.9	.7	.5	.4	.3	1177.0	-9.	530.

		2	15.0	11.9	10.6	9.5	7.4	5.4	4.4	3.4	2.6	2.1	457.6	0.	624.
		3	21.1	17.3	15.4	13.9	11.0	8.1	6.6	5.1	3.9	3.2	248.5	-2.	670.
		4	16.5	13.4	11.8	10.6	8.3	6.1	4.8	3.7	2.8	2.2	160.8	-8.	730.
		5	37.4	30.7	27.1	24.4	19.2	14.2	11.4	8.9	6.8	5.5	167.5	4.	1140.
10975	2	1	12.7	10.5	9.0	8.1	6.3	4.6	3.7	2.9	2.2	1.7	797.5	-2.	481.
		2	22.2	18.5	16.1	14.6	11.4	8.4	6.7	5.2	4.0	3.2	363.3	6.	658.
		3	18.3	15.2	13.1	12.0	9.3	6.7	5.3	4.1	3.1	2.4	229.7	1.	830.
		4	37.9	31.5	27.6	24.9	19.5	14.4	11.6	9.0	6.9	5.5	196.8	-15.	1180.
		5	59.5	50.1	44.4	40.3	31.8	23.8	19.2	15.2	11.6	9.3	82.2	13.	744.
11000	2	1	20.6	16.9	14.9	13.4	10.5	7.8	6.3	4.9	3.8	3.0	739.8	3.	527.
		2	19.9	16.4	14.3	12.9	10.0	7.4	5.9	4.6	3.5	2.8	389.1	10.	833.
		3	39.1	32.3	28.6	25.9	20.3	15.1	12.2	9.6	7.4	6.0	300.6	-28.	1280.
		4	62.9	52.5	47.1	42.9	34.1	25.8	20.9	16.6	12.9	10.6	117.0	15.	830.
		5	64.2	52.5	47.2	43.4	33.6	25.7	21.1	16.3	12.7	10.4	54.1	1.	578.
11025	2	1	14.6	11.6	10.0	8.8	6.9	4.9	4.0	3.0	2.3	1.8	845.8	9.	663.
		2	36.3	29.8	26.2	23.5	18.6	13.7	11.1	8.7	6.7	5.4	521.9	-22.	1229.
		3	63.3	53.2	47.2	42.7	34.3	25.9	21.1	16.7	13.1	10.7	171.5	4.	800.
		4	64.8	54.1	47.8	43.1	34.6	26.0	21.1	16.7	13.1	10.7	76.2	-9.	597.
		5	61.1	50.8	46.4	41.3	34.3	26.3	21.4	17.0	13.3	11.2	40.2	21.	473.
11050	2	1	29.7	24.2	21.3	19.1	15.0	11.0	8.9	6.9	5.3	4.3	1438.0	-25.	1000.
		2	62.0	52.0	46.3	42.0	33.5	25.3	20.6	16.3	12.7	10.4	318.9	11.	667.
		3	64.7	53.9	47.8	43.3	34.4	25.8	21.0	16.5	12.8	10.5	128.0	-22.	530.
		4	62.3	52.5	47.1	43.0	34.5	26.1	21.3	16.8	13.0	10.7	62.3	23.	434.
		5	53.6	44.9	41.3	37.7	29.8	22.3	18.8	15.8	11.6	8.4	51.4	-20.	538.
11075	2	1	66.4	55.9	49.8	45.6	36.5	27.7	22.8	18.2	14.3	11.8	246.0	11.	514.
		2	70.5	58.8	52.2	47.6	38.0	28.7	23.6	18.8	14.7	12.2	75.1	-14.	471.
		3	67.8	57.1	50.8	46.9	37.9	29.0	24.1	19.3	15.2	12.8	31.3	13.	392.
		4	59.2	49.7	44.1	40.8	33.2	25.4	21.2	17.2	13.6	11.6	23.9	-20.	501.
		5	48.6	40.2	35.5	33.3	26.8	20.3	17.6	14.1	11.3	9.7	15.1	11.	475.
11100	2	1	83.9	70.2	62.3	56.5	44.9	33.8	27.6	21.8	17.0	13.9	297.0	-9.	621.
		2	88.1	74.7	67.2	61.3	49.3	37.9	31.1	24.8	19.5	16.0	73.3	16.	460.
		3	77.6	66.0	59.8	54.6	43.9	33.9	28.0	22.3	17.4	14.3	45.9	-29.	575.
		4	62.2	53.1	50.2	45.0	36.1	26.7	22.9	17.6	13.8	10.9	33.4	20.	698.
11125	2	1	88.3	74.3	65.9	60.3	48.1	36.6	29.7	23.6	18.6	15.3	264.9	15.	594.
		2	89.5	75.5	67.1	61.8	49.4	37.7	31.0	24.7	19.4	15.9	114.8	-24.	772.
		3	76.7	64.4	57.1	52.8	42.1	32.0	26.3	20.9	16.3	13.5	64.5	15.	865.
11150	2	1	74.8	62.6	56.4	51.0	41.0	31.2	25.5	20.5	16.1	13.3	190.8	-23.	660.
		2	77.9	64.5	58.3	52.6	42.3	32.3	26.3	21.2	16.9	14.0	72.9	15.	763.
11175	2	1	52.8	44.0	39.0	35.4	28.0	21.1	17.2	13.6	10.6	8.7	240.7	13.	830.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 53WA.IND
DATA FILE : 53WA.DAT

LINE NO. : 534

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	-3.6	-1.9	-1.1	-.5	-.6	.6	.1	.5	.3	.2	724.2	20.	349.
		2	11.8	8.8	6.4	5.3	4.2	1.9	1.8	.9	.7	.6	721.5	-27.	1045.
		3	12.6	10.6	9.0	8.1	6.2	4.4	3.4	2.5	1.8	1.4	70.3	2.	203.
		4	7.2	6.2	5.5	4.8	3.8	2.8	2.1	1.6	1.2	.9	68.2	21.	329.
		5	2.8	2.5	2.2	1.5	.9	.5	.2	.5	.4	.2	70.2	-5.	508.
10850	2	1	6.7	5.3	4.3	4.0	3.0	2.1	1.6	1.2	.9	.7	443.6	-11.	221.
		2	10.3	8.5	7.1	6.7	5.1	3.6	2.8	2.2	1.5	1.2	111.2	3.	166.
		3	7.2	6.2	5.2	5.1	3.8	2.7	2.0	1.5	1.1	.8	110.8	1.	330.
		4	7.8	6.7	5.6	5.6	4.0	2.9	2.1	1.6	1.0	.8	95.1	11.	474.
		5	6.6	5.3	4.1	4.0	2.8	1.8	1.3	.8	.2	.1	37.2	-26.	278.
10875	2	1	7.2	5.6	4.7	4.2	3.1	2.2	1.7	1.3	.9	.7	665.0	10.	245.
		2	8.4	7.0	6.1	5.5	4.2	3.1	2.4	1.8	1.3	1.0	342.2	6.	379.
		3	9.0	7.6	6.5	6.0	4.7	3.4	2.7	2.1	1.5	1.2	229.9	-42.	500.
		4	9.8	8.1	7.0	6.4	4.9	3.3	2.6	1.9	1.3	.8	72.7	16.	268.
		5	2.7	1.5	.1	1.2	.2	-.2	-.3	-.6	-.7	-1.0	30.0	-11.	166.
10900	2	1	6.6	5.4	4.6	4.3	3.3	2.4	1.9	1.5	1.1	.9	552.4	11.	299.
		2	9.5	7.8	6.7	6.2	4.8	3.6	2.8	2.2	1.6	1.4	222.4	-43.	361.
		3	11.2	9.6	8.3	7.6	6.2	4.7	3.7	3.0	2.3	1.9	90.8	20.	294.
		4	3.7	2.9	2.5	2.0	1.8	1.7	1.2	1.0	.6	.9	24.8	-10.	134.
		5	13.1	10.5	9.7	8.7	7.0	5.5	4.6	3.8	3.3	2.6	35.4	11.	287.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 53WB.IND
DATA FILE : 53WB.DAT

LINE NO. : 534

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
11000	2	1	28.9	23.9	21.1	19.1	15.0	11.3	9.1	7.2	5.5	4.5	2281.0	-20.	1370.
		2	33.8	28.1	24.9	22.5	17.6	13.2	10.6	8.3	6.5	5.2	439.2	-16.	795.
		3	59.7	50.4	44.8	40.7	32.4	24.4	19.8	15.6	12.2	9.9	132.0	3.	470.
		4	51.7	43.8	38.6	35.2	28.1	21.2	17.3	13.7	10.7	8.8	66.6	7.	401.
		5	77.3	63.4	58.8	53.8	42.9	32.6	26.8	21.2	16.7	13.8	33.4	0.	302.
11025	2	1	27.1	22.2	19.4	17.6	13.8	10.2	8.3	6.5	5.0	4.1	1811.0	-24.	810.
		2	58.2	49.0	43.5	39.7	31.6	23.9	19.4	15.4	12.0	9.9	332.0	5.	446.
		3	52.6	44.3	39.1	35.9	28.8	21.9	17.9	14.3	11.3	9.2	132.4	-6.	350.
		4	80.6	68.2	60.8	55.8	45.0	34.4	28.4	22.9	18.1	15.0	67.4	5.	302.
		5	62.1	52.5	46.9	43.1	34.9	26.7	21.9	17.6	14.0	11.5	54.2	-3.	364.
11050	2	1	67.9	56.5	50.1	45.5	36.2	27.3	22.2	17.6	13.8	11.3	1176.0	2.	690.
		2	60.9	51.1	45.5	41.4	33.2	25.2	20.8	16.6	12.8	10.3	286.0	-2.	508.
		3	90.6	76.6	68.7	62.7	50.8	38.9	32.1	25.9	20.5	17.0	122.1	-15.	430.
		4	71.2	59.8	53.5	48.7	39.5	30.0	24.6	19.5	15.2	12.4	83.7	10.	495.
		5	58.7	49.0	43.8	40.0	32.4	24.6	20.5	16.3	12.7	10.5	53.0	14.	470.
11075	2	1	74.5	62.7	55.3	50.5	40.2	30.3	24.8	19.7	15.3	12.6	1021.0	-12.	580.
		2	105.0	89.0	79.1	72.4	58.2	44.4	36.5	29.2	22.9	18.9	304.9	2.	522.
		3	80.8	68.8	61.1	56.0	45.1	34.4	28.3	22.6	17.8	14.7	186.7	-12.	630.
		4	66.2	56.1	49.6	45.4	36.6	27.8	22.9	18.3	14.3	11.8	93.9	7.	535.
		5	61.9	52.2	46.2	42.0	34.0	25.9	21.2	16.9	13.3	10.8	106.4	0.	910.
11100	2	1	97.8	81.9	72.2	65.8	52.2	39.3	32.0	25.3	19.8	16.1	1503.0	-12.	730.
		2	84.4	71.0	62.9	57.4	45.7	34.6	28.2	22.4	17.5	14.4	574.9	-11.	846.
		3	70.0	59.2	52.3	47.8	38.1	28.8	23.5	18.7	14.7	12.1	240.2	-1.	700.
		4	67.0	56.5	49.9	45.6	36.3	27.5	22.4	17.8	13.8	11.3	211.4	-11.	1030.
		5	67.9	57.4	50.8	46.3	37.0	28.0	22.8	18.2	14.3	11.7	139.3	22.	1020.
11125	2	1	59.6	49.6	43.9	39.8	31.7	23.8	19.4	15.4	12.0	9.8	1591.0	-18.	860.

		2	57.3	47.8	42.2	38.3	30.5	22.9	18.7	14.9	11.7	9.5	474.8	8.	771.
		3	57.5	47.9	42.4	38.5	30.8	23.2	18.9	14.8	11.5	9.5	366.4	-26.	1180.
		4	61.5	51.3	45.6	41.2	32.9	24.8	20.3	16.1	12.6	10.3	229.0	4.	1230.
		5	62.3	52.0	46.3	42.4	33.6	25.3	20.6	16.6	12.8	10.4	126.2	-8.	1020.
11150	2	1	29.1	24.0	21.4	18.9	14.9	11.1	9.0	7.1	5.5	4.4	1253.0	7.	670.
		2	36.6	30.3	26.7	24.0	18.9	14.1	11.4	9.1	7.1	5.8	784.0	-21.	1273.
		3	45.0	37.6	33.2	30.0	23.8	17.9	14.6	11.4	8.8	7.2	465.5	-8.	1500.
		4	49.8	41.7	37.0	33.4	26.7	20.0	16.2	12.9	10.0	8.2	207.8	0.	1120.
		5	48.4	40.6	36.0	32.6	26.0	19.5	15.9	12.8	9.8	8.0	219.6	-2.	1780.
11175	2	1	25.2	20.6	18.0	16.3	12.7	9.4	7.5	5.9	4.5	3.7	1503.0	-23.	900.
		2	35.7	29.5	25.9	23.5	18.4	13.8	11.0	8.6	6.7	5.4	771.3	-2.	1397.
		3	41.7	34.7	30.7	27.8	22.0	16.4	13.3	10.5	8.1	6.6	314.7	-10.	1130.
		4	41.9	34.9	30.9	28.0	22.2	16.6	13.4	10.6	8.2	6.6	314.5	-2.	1890.
		5	37.7	31.7	28.1	25.4	20.4	15.4	12.5	9.9	7.6	6.3	116.4	12.	1050.
11200	2	1	24.6	20.5	17.7	16.0	12.6	9.3	7.5	5.9	4.5	3.6	1923.0	-9.	1050.
		2	33.4	27.9	24.3	22.1	17.4	12.9	10.4	8.2	6.3	5.2	642.3	-15.	1061.
		3	34.8	29.2	25.5	23.2	18.4	13.8	11.2	8.8	6.8	5.5	614.0	-2.	2020.
		4	31.9	27.2	23.8	21.8	17.3	13.0	10.6	8.5	6.5	5.4	207.0	12.	1140.
		5	59.2	49.7	43.7	39.8	31.7	23.8	19.3	15.3	11.9	9.7	266.4	7.	2200.
11225	2	1	22.8	18.8	16.4	15.0	11.6	8.6	6.8	5.4	4.1	3.3	1657.0	-17.	960.
		2	27.8	22.8	20.1	18.2	14.2	10.6	8.6	6.7	5.2	4.2	1239.0	2.	2160.
		3	26.0	21.7	19.2	17.6	14.0	10.4	8.4	6.7	5.3	4.2	435.3	-11.	1510.
		4	54.8	45.9	40.6	36.9	29.2	21.9	17.7	14.0	10.8	8.8	446.3	10.	2590.
		5	60.2	50.3	44.7	40.9	33.0	24.8	19.9	15.6	12.6	10.2	212.3	2.	1850.
11250	2	1	21.0	17.2	15.1	13.5	10.5	7.8	6.2	4.8	3.7	3.0	2188.0	-3.	1710.
		2	20.1	16.7	14.8	13.3	10.6	7.9	6.5	5.0	3.9	3.2	569.2	7.	1340.
		3	48.9	40.7	36.1	32.6	25.9	19.3	15.7	12.4	9.6	7.8	610.8	-13.	2870.
		4	56.8	47.7	42.5	38.5	30.7	23.2	19.0	15.0	11.8	9.7	261.3	5.	2050.
		5	46.4	38.9	35.0	31.7	25.4	19.2	15.8	12.5	9.8	7.9	123.6	-2.	1450.
11275	2	1	16.1	13.3	11.7	10.7	8.3	6.2	5.0	3.9	3.0	2.4	1252.0	3.	1000.
		2	45.4	37.6	33.1	30.1	23.7	17.7	14.3	11.2	8.7	7.0	1071.0	-6.	2580.
		3	54.2	45.5	40.8	36.9	29.3	22.1	18.1	14.4	11.3	9.3	386.0	-13.	1860.
		4	42.9	36.1	32.1	29.4	23.4	17.7	14.4	11.4	8.9	7.3	178.0	-5.	1430.
		5	39.1	32.5	28.9	26.6	20.9	16.3	13.1	10.6	7.9	6.5	55.1	5.	665.
11300	2	1	45.9	32.8	27.6	24.9	19.5	14.7	11.9	9.4	7.4	6.0	2656.0	8.	1930.
		2	37.6	36.4	33.1	30.4	23.8	17.5	14.1	10.9	8.3	6.7	2655.0	-34.	5810.
		3	37.0	31.6	28.3	26.0	20.7	15.8	12.9	10.2	7.9	6.5	376.3	-17.	1640.
		4	30.2	25.5	22.8	21.1	19.0	13.0	10.6	8.5	6.6	5.5	104.4	4.	760.
		5	29.3	24.2	21.3	19.4	15.6	12.3	9.7	8.0	6.2	5.1	41.8	4.	457.
11325	2	1	46.7	38.8	34.3	31.0	24.6	18.4	14.9	11.8	9.1	7.5	2193.0	-21.	1530.
		2	31.4	26.6	23.9	21.7	17.5	13.3	10.9	8.6	6.7	5.5	552.3	-7.	1156.
		3	23.7	20.1	18.2	16.6	13.3	10.1	8.5	6.9	5.4	4.3	139.8	-9.	580.

		4	23.0	19.1	17.4	15.8	12.9	10.2	7.7	5.8	4.5	3.9	53.1	0.	370.
		5	26.9	21.1	18.4	16.4	13.5	10.2	8.0	6.6	5.1	4.3	30.8	-13.	322.
11350	2	1	45.0	37.3	32.9	29.6	23.4	17.4	14.1	11.1	8.6	7.0	1271.0	-10.	2850.
		2	28.9	24.8	21.9	19.8	15.9	11.8	9.6	7.5	5.8	4.7	96.3	-2.	648.
		3	22.1	18.9	16.6	15.0	12.1	9.0	7.3	5.8	4.5	3.6	29.1	-10.	391.
		4	24.7	20.9	18.2	16.5	13.4	9.8	8.0	6.3	4.9	3.7	17.5	-7.	392.
		5	20.8	17.0	14.6	13.6	11.3	8.4	6.7	5.5	4.1	3.4	13.6	-6.	458.
11375	2	1	20.3	17.0	14.9	13.4	10.5	7.9	6.4	5.1	4.0	3.2	982.4	-10.	670.
		2	20.1	16.8	14.7	13.1	10.3	7.7	6.2	4.8	3.7	3.0	223.8	4.	458.
		3	22.0	18.4	16.1	14.4	11.3	8.4	6.7	5.3	4.0	3.3	121.4	-19.	490.
		4	18.2	15.2	13.3	11.9	9.6	7.2	5.9	4.6	3.6	2.9	95.2	1.	649.
		5	16.9	14.1	12.2	10.9	8.7	6.6	5.2	4.2	3.2	2.7	118.6	15.	1210.
11400	2	1	15.0	12.5	10.7	9.5	7.5	5.5	4.4	3.4	2.6	2.1	187.7	1.	453.
		2	18.6	15.4	13.3	11.8	9.3	6.8	5.4	4.3	3.3	2.6	68.3	-13.	495.
		3	15.4	13.1	11.2	10.0	7.9	6.0	4.8	3.8	2.9	2.4	44.6	-10.	644.
		4	12.4	10.7	9.1	8.0	6.5	4.9	4.0	3.2	2.4	2.1	47.3	10.	1142.
		5	57.6	47.7	41.1	36.8	28.5	20.6	16.2	12.5	9.4	7.6	43.0	2.	1559.
11425	2	1	25.3	20.5	18.0	16.2	12.5	9.1	7.3	5.6	4.3	3.4	596.6	-16.	936.
		2	17.6	14.1	12.5	11.4	8.8	6.5	5.2	4.1	3.1	2.5	212.6	-16.	1001.
		3	13.0	10.4	9.2	8.2	6.4	4.7	3.8	3.0	2.4	1.9	159.6	0.	1500.
		4	56.2	45.6	39.7	35.5	27.2	19.6	15.4	11.7	8.7	6.8	119.4	15.	1870.
		5	28.7	22.4	19.5	17.4	13.5	9.7	7.5	5.8	4.5	3.1	59.0	27.	1390.
11450	2	1	28.6	23.4	20.5	18.3	14.3	10.4	8.4	6.4	4.9	3.9	591.3	-15.	1160.
		2	18.1	14.6	12.8	11.4	8.9	6.5	5.0	4.0	3.1	2.4	262.4	4.	1544.
		3	56.5	46.0	40.1	35.7	27.5	19.8	15.7	12.0	9.0	7.0	160.2	3.	1880.
		4	26.9	21.5	18.6	16.3	12.5	8.9	7.0	5.3	4.0	3.1	72.7	11.	1426.
		5	22.0	17.9	15.6	13.6	10.8	8.1	5.7	5.1	4.0	3.2	49.5	-2.	1455.
11475	2	1	36.7	30.1	26.3	23.6	18.3	13.4	10.7	8.2	6.2	4.9	1228.0	0.	2020.
		2	64.8	53.1	46.2	41.3	31.8	22.9	18.0	13.8	10.3	8.1	364.1	4.	1805.
		3	27.4	21.8	18.8	16.6	12.7	9.0	7.0	5.3	4.0	3.1	131.2	4.	1290.
		4	21.0	17.1	15.1	13.4	10.5	7.8	6.3	4.9	3.7	3.0	88.7	1.	1466.
		5	12.2	10.5	10.1	9.1	7.0	5.7	4.5	4.2	3.0	2.2	100.6	-4.	2490.
11500	2	1	83.7	68.9	60.3	54.3	42.0	30.4	24.1	18.4	13.8	11.0	1060.0	0.	2560.
		2	31.7	25.3	21.8	19.4	14.7	10.4	8.3	6.2	4.6	3.7	183.7	8.	1331.
		3	18.4	14.9	12.9	11.7	9.1	6.7	5.3	4.3	3.3	2.7	94.4	-9.	1365.
		4	10.5	8.6	7.6	6.7	6.0	4.8	4.0	3.3	2.6	2.5	96.5	-4.	2331.
11525	2	1	79.9	66.3	57.8	51.9	40.0	28.9	22.7	17.4	13.0	10.2	744.8	6.	2338.
		2	23.1	18.4	15.7	13.8	10.4	7.3	5.6	4.3	3.1	2.4	146.2	-4.	1377.
		3	8.4	6.9	6.0	5.1	4.0	3.1	2.2	1.8	1.3	1.0	118.3	-12.	2220.
11550	2	1	55.9	45.5	39.4	35.0	26.6	19.0	14.9	11.3	8.4	6.6	745.5	-6.	1560.
		2	31.5	25.4	21.9	19.5	14.9	10.7	8.4	6.4	4.8	3.7	365.2	-6.	2293.

11575	2	1	33.8	27.6	23.8	21.3	16.4	11.7	9.2	7.0	5.2	4.1	445.9	-11.	1750.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 52W.IND
DATA FILE : 52W.DAT

LINE NO. : 524

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	12.9	10.5	9.4	8.7	6.8	5.0	4.1	3.1	2.4	1.9	162.4	-9.	51.
		2	7.7	6.2	5.5	5.1	4.0	3.0	2.5	1.9	1.6	1.3	70.6	-58.	66.
		3	4.9	4.4	4.1	3.9	3.2	2.2	2.0	1.5	1.3	1.0	39.2	45.	74.
		4	1.0	.4	.3	1.0	.8	.7	.9	.8	.8	.8	37.8	-7.	119.
		5	1.0	1.7	2.2	1.1	1.5	1.1	1.2	1.1	1.6	1.1	38.3	-13.	181.
10850	2	1	9.7	8.2	7.2	6.3	5.1	3.7	2.9	2.2	1.7	1.3	239.6	-73.	60.
		2	9.7	8.2	7.3	6.5	5.1	3.8	2.9	2.1	1.5	1.2	105.7	60.	79.
		3	2.4	2.3	1.8	1.5	1.2	.8	.6	.4	.2	.1	84.6	-4.	126.
		4	2.6	2.4	1.9	1.6	1.3	.9	.7	.4	.2	.1	78.6	-21.	196.
		5	2.9	2.6	2.0	1.5	1.2	.8	.6	.3	.1	.0	69.6	-4.	260.
10875	2	1	8.3	6.5	5.7	5.2	3.9	2.9	2.3	1.7	1.3	1.0	200.3	62.	157.
		2	7.6	6.4	5.7	5.3	4.1	3.0	2.4	1.8	1.3	.9	106.4	-3.	250.
		3	6.4	5.8	5.1	4.6	3.6	2.7	2.1	1.5	1.0	.7	73.4	-21.	345.
		4	6.3	5.9	5.1	4.6	3.5	2.7	2.0	1.3	.8	.4	52.0	-24.	408.
		5	17.4	15.4	13.4	12.2	9.5	7.3	5.6	4.2	3.0	2.1	48.3	5.	568.
10900	2	1	5.7	4.5	4.0	3.6	2.7	2.0	1.6	1.2	.9	.7	489.3	-4.	320.
		2	6.8	5.4	4.9	4.5	3.5	2.6	2.1	1.6	1.2	1.0	229.8	-18.	450.
		3	7.9	6.3	5.7	5.3	4.1	3.1	2.5	2.0	1.5	1.3	136.0	-24.	530.
		4	19.9	16.3	14.8	13.5	10.6	8.0	6.5	5.2	4.0	3.4	112.6	1.	730.
		5	28.4	23.2	21.0	19.3	15.2	11.7	9.5	7.7	6.1	5.1	70.7	1.	693.
10925	2	1	5.7	3.8	3.8	3.5	2.6	1.9	1.5	1.1	.8	.7	1204.0	-17.	360.
		2	7.9	6.2	5.4	4.9	3.8	2.8	2.2	1.7	1.3	1.0	507.0	-15.	455.
		3	18.2	15.0	13.4	12.1	9.4	7.0	5.6	4.4	3.5	2.8	410.0	-5.	734.
		4	28.0	23.0	20.5	18.7	14.7	11.1	9.0	7.1	5.5	4.5	225.0	-15.	672.
		5	38.4	31.7	28.2	25.6	20.2	15.3	12.5	9.9	7.8	6.4	135.6	27.	608.
10950	2	1	7.7	6.6	5.6	4.8	3.8	2.8	2.2	1.7	1.2	1.1	958.9	-23.	430.

		2	18.8	15.8	13.6	12.1	9.6	7.0	5.7	4.4	3.3	2.5	494.7	4.	665.
		3	27.0	22.9	19.9	17.9	14.3	10.6	8.6	6.7	5.1	4.1	264.7	-11.	710.
		4	37.7	31.8	27.6	24.8	19.8	14.7	11.9	9.4	7.2	5.8	146.0	16.	650.
		5	47.5	40.2	34.8	31.4	25.1	18.6	15.0	11.9	8.8	7.2	117.8	-13.	790.
10975	2	1	17.6	14.1	12.5	11.3	8.8	6.5	5.3	4.1	3.1	2.5	859.4	6.	562.
		2	27.3	22.5	20.1	18.1	14.3	10.6	8.6	6.7	5.2	4.2	376.2	-13.	738.
		3	37.2	30.8	27.2	24.7	19.5	14.5	11.7	9.2	7.1	5.8	185.5	22.	720.
		4	48.3	40.1	35.4	32.2	25.5	19.0	15.4	12.2	9.4	7.7	137.8	-19.	900.
		5	46.7	39.1	35.2	31.6	24.9	19.1	15.1	12.6	9.4	7.6	51.7	-3.	507.
11000	2	1	25.0	20.4	18.3	16.4	13.1	10.0	8.2	6.6	5.4	4.5	266.3	-21.	760.
		2	37.7	31.2	28.0	25.3	20.5	15.9	13.4	11.0	9.1	7.8	98.0	20.	839.
		3	52.6	43.7	39.5	35.9	29.5	23.3	19.9	16.7	14.1	12.4	62.8	-19.	1073.
		4	56.0	46.9	42.8	39.2	32.8	26.6	23.3	19.9	17.2	15.6	21.4	-9.	611.
		5	72.9	61.3	56.1	51.5	43.4	35.6	31.4	27.1	23.7	21.6	17.9	4.	768.
11025	2	1	28.8	23.6	20.8	18.6	14.6	11.1	9.1	7.1	5.2	4.2	1332.0	15.	800.
		2	44.5	36.7	32.4	29.2	23.0	17.1	13.8	10.8	8.3	6.8	671.2	-21.	1215.
		3	46.3	38.5	34.2	30.8	24.6	18.4	15.0	11.9	9.3	7.4	205.9	-4.	740.
		4	60.8	50.7	45.1	40.8	32.7	24.5	20.0	15.8	12.3	10.1	158.5	-6.	950.
		5	60.2	50.2	44.7	40.4	32.3	24.3	19.9	15.8	12.3	10.0	68.8	18.	622.
11050	2	1	35.9	29.4	26.0	23.4	18.3	13.6	10.9	8.5	6.6	5.3	1733.0	-36.	1080.
		2	41.7	34.4	30.6	27.6	21.9	16.4	13.3	10.4	8.1	6.6	425.9	-1.	802.
		3	57.4	47.5	42.4	38.5	30.5	22.9	18.6	14.7	11.5	9.4	296.7	-5.	1110.
		4	59.7	49.5	44.1	39.9	31.7	23.9	19.5	15.4	12.0	9.8	120.0	12.	750.
		5	59.1	48.9	43.7	39.6	31.5	23.8	19.3	15.3	12.0	9.7	134.9	17.	1270.
11075	2	1	32.2	26.3	23.0	21.0	16.4	12.1	9.8	7.6	5.7	4.7	182.8	-8.	717.
		2	50.2	41.4	36.4	33.0	26.1	19.3	15.7	12.2	9.4	7.6	104.6	-5.	1232.
		3	53.9	44.8	39.2	35.6	28.2	20.8	16.9	13.1	10.1	8.2	38.0	18.	142.
		4	56.0	46.3	40.4	36.8	29.5	22.0	18.1	14.8	12.4	10.5	38.8	5.	243.
		5	55.7	46.9	40.4	35.6	28.2	19.9	15.8	10.9	6.0	4.1	21.0	9.	197.
11100	2	1	37.4	30.8	27.3	24.4	19.3	14.3	11.6	9.1	7.0	5.6	440.0	-5.	1256.
		2	44.6	36.8	32.7	29.3	23.3	17.3	14.0	11.1	8.6	7.0	130.4	17.	1116.
		3	48.1	39.9	35.4	31.7	25.3	18.9	15.3	12.1	9.4	7.7	116.6	2.	1990.
		4	53.2	44.4	39.3	35.1	28.3	21.2	17.3	13.6	10.5	8.4	53.4	0.	1524.
		5	52.9	44.2	38.9	34.6	28.4	21.3	17.5	14.0	11.3	9.5	26.0	-1.	1113.
11125	2	1	32.4	26.8	23.6	21.3	16.8	12.5	10.2	8.0	6.2	5.0	865.9	18.	679.
		2	39.3	32.7	28.9	26.1	20.7	15.4	12.5	9.8	7.6	6.2	629.1	1.	1481.
		3	45.6	38.1	33.6	30.5	24.1	18.1	14.7	11.6	9.0	7.4	256.3	-3.	1200.
		4	46.9	39.4	34.8	31.6	25.2	19.1	15.6	12.3	9.7	8.0	118.1	-10.	920.
		5	50.2	41.8	37.4	34.6	27.3	20.4	17.1	13.6	10.6	9.0	65.5	-21.	770.
11150	2	1	28.0	22.6	20.1	18.2	14.2	10.5	8.4	6.5	5.0	4.0	3211.0	-13.	2010.
		2	35.8	29.4	26.4	23.9	18.8	13.9	11.3	8.8	6.9	5.5	734.0	-4.	1382.
		3	37.8	31.3	27.9	25.4	20.2	15.2	12.4	9.8	7.7	6.3	263.9	-7.	990.

		4	43.2	35.9	32.2	29.2	23.3	17.6	14.4	11.5	9.0	7.4	122.7	-36.	770.
		5	42.9	35.4	32.4	29.2	22.9	17.2	14.2	11.2	8.9	7.4	91.4	26.	861.
11175	2	1	27.3	22.1	19.5	17.6	13.8	10.2	8.2	6.4	4.9	4.0	1091.0	-8.	1000.
		2	30.3	24.9	22.2	20.1	16.1	12.0	9.8	7.7	6.1	5.0	300.4	-8.	832.
		3	36.2	30.1	26.8	24.4	19.7	14.9	12.2	9.7	7.6	6.3	131.1	1.	720.
		4	37.7	31.3	27.8	25.3	20.5	15.5	12.9	10.3	8.1	6.7	78.5	-14.	724.
		5	43.7	38.0	32.4	32.5	25.1	18.6	15.2	11.9	10.0	7.8	68.4	-19.	947.
11200	2	1	26.8	22.1	19.4	17.6	13.7	10.2	8.1	6.4	4.9	4.0	1367.0	-15.	1100.
		2	27.6	23.0	20.5	18.6	14.7	11.1	9.1	7.2	5.6	4.6	342.8	1.	827.
		3	30.1	25.1	22.4	20.4	16.1	12.2	10.0	7.9	6.1	4.8	166.6	-12.	800.
		4	38.3	31.9	28.5	25.7	20.3	15.3	12.4	9.7	7.6	6.5	123.3	-34.	990.
		5	45.7	38.2	34.2	31.0	24.8	18.8	15.3	12.3	9.6	7.8	122.4	12.	1470.
11225	2	1	24.4	20.3	17.8	16.0	12.7	9.5	7.7	6.0	4.6	3.7	976.9	1.	829.
		2	26.2	21.7	19.1	17.0	13.5	10.1	8.2	6.4	5.0	4.1	350.8	-11.	893.
		3	33.0	27.8	24.7	22.1	17.6	13.1	10.6	8.4	6.5	5.3	194.9	-30.	990.
		4	41.4	34.6	30.8	27.7	22.2	16.7	13.6	10.7	8.4	6.8	160.8	3.	1360.
		5	50.8	42.5	37.8	34.1	27.3	20.5	16.7	13.2	10.8	9.1	132.9	-6.	1690.
11250	2	1	23.2	19.2	16.8	15.3	11.9	8.9	7.1	5.5	4.3	3.5	1922.0	-23.	1580.
		2	26.8	22.2	19.4	17.9	13.9	10.4	8.3	6.5	5.0	4.1	544.8	-30.	1350.
		3	32.5	27.3	24.0	22.3	17.5	13.2	10.7	8.5	6.6	5.3	309.3	8.	1530.
		4	44.7	37.6	33.1	30.8	24.1	18.1	14.7	11.7	9.1	7.4	204.6	-22.	1690.
		5	46.6	39.1	34.7	32.1	24.9	19.2	15.5	12.2	9.6	7.9	147.5	27.	1820.
11275	2	1	22.3	18.4	16.1	14.6	11.5	8.5	6.9	5.4	4.1	3.3	1276.0	-32.	1140.
		2	26.0	21.8	19.1	17.2	13.7	10.2	8.3	6.5	5.1	4.1	489.2	7.	1316.
		3	37.9	32.1	28.3	25.7	20.5	15.3	12.5	9.9	7.7	6.2	272.1	-20.	1460.
		4	42.8	36.3	32.1	29.0	23.2	17.4	14.1	11.2	8.8	7.1	169.4	21.	1510.
		5	44.6	37.5	32.0	28.8	23.4	18.4	11.9	12.0	9.0	7.4	83.9	23.	1129.
11300	2	1	23.6	19.4	17.1	15.5	12.2	9.0	7.3	5.8	4.5	3.6	2272.0	26.	1980.
		2	32.3	26.8	23.8	21.6	17.1	12.7	10.4	8.2	6.3	5.1	412.6	-33.	1079.
		3	35.7	30.2	27.0	24.5	19.6	14.7	12.0	9.5	7.4	6.1	303.4	18.	1580.
		4	37.8	32.0	28.7	25.9	20.5	15.6	12.9	10.1	8.1	6.6	110.2	14.	960.
		5	24.0	18.8	17.0	15.4	14.2	10.2	8.2	6.9	5.0	4.4	22.2	19.	290.
11325	2	1	31.6	26.0	23.1	20.7	16.4	12.1	9.8	7.6	5.8	4.7	365.1	-32.	1270.
		2	34.0	28.1	25.1	22.7	18.0	13.2	10.9	8.4	6.6	5.3	173.3	12.	1810.
		3	34.8	28.7	25.9	23.4	18.5	13.8	11.3	8.9	6.9	5.7	60.4	18.	1260.
		4	21.1	17.4	16.9	14.5	11.8	8.5	6.9	5.8	4.6	3.4	9.0	8.	313.
		5	30.0	23.7	21.5	20.6	15.9	11.8	10.8	7.7	6.2	5.6	10.4	-18.	540.
11350	2	1	32.0	26.4	23.2	21.0	16.4	12.2	9.7	7.5	5.8	4.6	1971.0	-19.	1620.
		2	31.9	26.4	23.2	21.0	16.4	12.2	9.7	7.5	5.8	4.7	1123.0	13.	2780.
		3	17.2	14.4	12.7	11.5	8.9	6.8	5.4	4.2	3.1	2.5	128.1	12.	630.
		4	22.7	18.9	16.6	15.1	11.7	9.3	7.3	5.7	4.4	3.7	111.9	-31.	920.
		5	27.3	22.8	20.1	18.3	14.1	11.2	9.0	7.0	5.5	4.3	68.6	10.	850.

11375	2	1	35.3	29.3	25.6	23.1	18.0	13.2	10.6	8.2	6.3	5.1	2469.0	8.	4300.
		2	15.7	13.6	11.9	10.8	8.4	6.1	4.8	3.7	2.8	2.2	179.6	12.	939.
		3	17.6	14.9	13.0	11.8	9.2	6.9	5.5	4.4	3.4	2.7	115.6	-31.	1200.
		4	22.0	18.1	15.6	14.2	11.3	8.2	6.8	5.1	3.9	3.3	60.4	2.	1053.
		5	19.6	16.4	14.1	12.8	10.5	8.1	6.5	5.2	4.2	3.2	44.8	-7.	1170.
11400	2	1	13.8	11.1	9.7	8.5	6.6	4.7	3.7	2.9	2.2	1.7	354.3	-5.	695.
		2	18.9	15.7	13.8	12.0	9.6	7.1	5.7	4.4	3.4	2.7	184.9	-26.	1088.
		3	20.9	17.4	15.5	13.6	10.9	8.2	6.6	5.2	4.0	3.2	84.3	1.	990.
		4	19.4	16.2	14.8	13.0	10.6	7.9	6.6	5.2	4.3	3.4	57.4	-17.	1127.
		5	31.8	26.2	22.9	19.7	15.9	11.9	9.6	7.9	6.0	4.8	53.3	-5.	1568.
11425	2	1	21.0	17.4	15.0	13.6	10.6	8.0	6.4	5.0	3.6	2.9	581.3	-42.	960.
		2	21.1	17.7	15.2	13.9	10.9	8.0	6.4	5.0	3.8	3.1	197.3	3.	978.
		3	18.0	15.2	13.1	12.0	9.5	7.2	5.8	4.5	3.5	2.8	117.2	-14.	1150.
		4	29.1	23.8	20.4	18.6	14.3	10.3	8.3	6.4	4.9	4.0	100.7	-16.	1660.
		5	37.7	29.9	26.4	23.9	18.1	12.9	10.9	7.8	6.0	5.0	66.5	4.	1648.
11450	2	1	20.4	16.8	14.6	13.0	10.2	7.4	5.8	4.5	3.4	2.7	267.6	2.	700.
		2	16.7	14.0	12.1	10.9	8.6	6.4	5.1	4.0	3.1	2.5	106.5	-7.	836.
		3	26.6	21.7	18.8	16.8	13.0	9.4	7.6	5.8	4.4	3.6	82.0	-17.	1284.
		4	35.5	28.8	24.6	21.9	16.7	12.0	9.5	7.2	5.4	4.4	50.8	-5.	1329.
		5	33.0	26.8	23.5	20.8	16.0	11.9	9.4	7.2	5.5	4.4	32.1	-1.	1260.
11475	2	1	20.5	16.6	14.4	12.8	9.9	7.2	5.7	4.3	3.3	2.6	446.7	-12.	876.
		2	26.7	21.5	18.6	16.5	12.7	9.1	7.2	5.5	4.1	3.2	219.4	-15.	1291.
		3	33.7	26.4	23.2	20.5	15.5	11.0	8.6	6.5	4.8	3.8	110.9	-3.	1300.
		4	30.9	25.2	22.0	19.7	15.0	10.8	8.6	6.4	4.8	3.7	63.1	-12.	1238.
		5	20.2	16.6	14.8	13.0	10.4	7.8	6.2	4.9	3.8	3.0	80.5	6.	2369.
11500	2	1	28.8	23.1	20.0	17.8	13.6	9.7	7.7	5.8	4.4	3.4	626.7	-14.	1035.
		2	34.9	27.7	23.9	21.1	16.0	11.3	8.8	6.6	4.9	3.8	241.0	2.	1194.
		3	31.5	25.6	22.3	19.8	15.2	11.0	8.6	6.6	4.9	3.8	122.2	-12.	1200.
		4	20.6	17.0	14.9	13.4	10.6	7.8	6.3	4.9	3.8	2.9	140.4	-4.	2320.
		5	19.0	15.8	14.0	12.6	10.0	7.2	5.8	4.5	3.5	2.7	107.0	-8.	2650.
11525	2	1	33.4	26.7	22.8	20.1	15.1	10.5	8.3	6.3	4.7	3.6	197.5	0.	1240.
		2	31.4	25.4	21.9	19.4	14.9	11.2	8.4	6.4	4.7	3.7	70.4	-11.	1326.
		3	20.3	17.1	14.7	13.0	10.2	7.4	5.9	4.5	3.3	2.6	66.5	-1.	2500.
		4	18.9	15.9	13.7	12.1	9.6	7.2	5.7	4.5	3.4	2.8	44.5	-16.	2790.
11550	2	1	40.7	32.8	28.2	25.2	19.0	13.4	10.5	8.0	5.9	4.6	322.1	-9.	1440.
		2	30.0	23.7	20.5	18.5	14.1	10.2	8.0	6.2	4.6	3.7	207.3	4.	2780.
		3	25.6	20.4	17.9	16.1	12.4	9.1	7.1	5.5	4.2	3.3	119.2	-19.	3200.
11575	2	1	34.5	28.0	24.0	21.4	16.4	11.8	9.3	7.2	5.4	4.2	156.2	1.	1630.
		2	31.5	25.3	21.5	19.3	14.9	10.8	8.4	6.6	5.0	3.9	66.8	-18.	2099.
11600	2	1	29.0	23.5	20.4	18.3	14.0	10.1	8.0	6.2	4.6	3.7	362.5	-19.	1260.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 51W.IND
DATA FILE : 51W.DAT

LINE NO. : 514

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	5.8	4.3	4.1	3.4	2.7	1.9	1.5	1.2	.9	.7	550.3	9.	191.
		2	7.4	6.0	5.5	4.8	3.8	2.8	2.2	1.7	1.3	1.0	157.3	-13.	164.
		3	9.4	7.8	7.3	6.4	5.1	3.8	3.0	2.3	1.7	1.3	53.3	7.	111.
		4	9.7	8.0	7.5	6.6	5.4	4.1	3.2	2.4	1.8	1.3	64.4	24.	224.
		5	3.8	3.2	3.8	3.2	2.2	1.8	1.4	.9	.8	.4	43.8	-21.	229.
10850	2	1	3.6	2.8	2.4	2.1	1.5	1.1	.9	.7	.5	.4	378.0	-15.	152.
		2	9.7	8.1	7.2	6.3	5.0	3.6	2.8	1.9	1.5	1.1	95.9	9.	116.
		3	9.7	8.1	7.3	6.5	5.1	3.7	2.9	2.2	1.6	1.1	94.8	21.	228.
		4	4.6	3.6	3.5	3.0	2.1	1.5	1.1	.7	.3	.2	57.6	-15.	231.
		5	-5.9	-5.6	-4.3	-3.9	-3.0	-2.6	-2.5	-2.0	-1.7	-1.7	25.4	14.	153.
10875	2	1	6.5	5.1	4.3	3.8	2.9	2.2	1.7	1.3	1.0	.8	296.0	4.	136.
		2	10.7	8.9	7.9	7.1	5.6	4.1	3.3	2.5	1.9	1.5	183.1	23.	253.
		3	6.7	5.8	5.3	4.8	3.8	2.8	2.3	1.8	1.4	1.1	89.3	-22.	246.
		4	-2.7	-1.9	-1.3	-1.4	-.9	-.6	-.4	-.3	-.1	.0	34.2	23.	157.
		5	7.0	6.0	5.6	4.7	3.7	2.7	2.3	1.8	1.5	1.3	63.5	-44.	439.
10898	2	1	7.9	6.3	5.5	5.0	3.9	2.9	2.3	1.8	1.3	1.1	713.3	23.	243.
		2	7.6	6.3	5.6	5.2	4.2	3.1	2.5	1.9	1.4	1.2	230.6	-18.	236.
		3	-1.3	-.9	-.8	-.4	-.3	-.2	-.1	.0	.0	.0	76.3	15.	155.
		4	8.4	6.5	5.6	5.5	4.4	3.1	2.6	2.0	1.5	1.1	129.5	-36.	440.
		5	26.6	22.2	19.5	18.0	14.3	10.7	8.6	6.9	5.3	4.3	100.9	-17.	510.
10922	2	1	7.0	5.7	5.0	4.4	3.8	2.6	2.1	1.6	1.2	1.0	470.6	0.	148.
		2	.0	.0	.1	.0	-.6	.0	.1	.0	.0	.0	142.7	12.	134.
		3	8.5	7.0	6.3	5.5	4.3	3.1	2.5	1.9	1.4	1.2	218.7	-37.	411.
		4	26.4	21.9	19.6	17.6	13.9	10.3	8.4	6.6	5.1	4.2	156.5	-2.	491.
		5	26.1	21.8	19.7	17.5	14.2	10.7	8.5	6.9	5.4	4.4	115.4	13.	543.
10947	2	1	10.0	8.3	7.4	6.8	5.3	3.8	3.2	2.5	1.9	1.5	634.6	18.	214.

		2	15.7	12.8	11.2	10.1	7.8	5.9	4.6	3.5	2.7	2.2	662.5	-37.	671.
		3	29.4	24.5	21.7	19.8	15.5	11.6	9.4	7.3	5.7	4.6	343.1	-9.	690.
		4	27.8	23.2	20.8	18.8	14.8	11.2	9.0	7.1	5.6	4.5	207.5	22.	700.
		5	39.9	32.8	30.0	27.6	21.4	16.1	12.9	10.3	8.0	6.7	105.2	-18.	530.
10972	2	1	18.6	15.2	13.3	12.0	9.3	6.8	5.4	4.2	3.2	2.6	2855.0	-49.	853.
		2	30.4	25.2	22.1	20.1	15.8	11.7	9.5	7.4	5.7	4.6	943.5	-9.	846.
		3	26.2	21.9	19.2	17.6	13.9	10.3	8.4	6.6	5.1	4.2	451.2	18.	807.
		4	38.6	32.0	28.1	25.5	20.0	14.8	12.0	9.4	7.2	5.8	202.6	-9.	605.
		5	37.7	31.3	27.5	25.0	19.7	14.6	11.9	9.4	7.3	6.0	134.4	-14.	602.
10997	2	1	49.1	40.8	35.6	32.2	25.2	18.7	15.0	11.8	9.1	7.4	2597.0	-9.	1530.
		2	31.5	26.1	23.2	21.2	16.7	12.5	10.1	7.9	6.1	5.0	515.5	20.	916.
		3	38.9	32.5	28.3	25.7	20.2	15.0	12.1	9.6	7.4	6.0	168.7	-13.	590.
		4	36.6	31.1	27.0	24.7	19.5	14.6	11.9	9.4	7.4	6.2	97.1	-5.	575.
		5	30.0	24.4	21.8	20.2	16.4	12.5	10.2	8.4	6.4	5.4	37.4	-19.	332.
11022	2	1	48.3	40.0	35.2	31.7	24.9	18.4	14.8	11.6	9.0	7.3	2877.0	-5.	1960.
		2	53.9	44.5	39.1	35.2	27.6	20.4	16.4	12.8	9.8	7.9	573.9	-17.	1175.
		3	46.7	38.6	33.8	30.6	24.0	17.7	14.3	11.2	8.6	7.0	240.5	-9.	980.
		4	36.9	30.8	26.9	24.3	19.1	14.2	11.3	9.0	6.8	5.5	74.1	-9.	505.
		5	43.1	35.9	31.6	28.7	23.0	17.1	13.7	10.9	8.3	6.8	92.2	-35.	943.
11046	2	1	74.1	61.5	54.4	49.2	38.7	28.7	23.1	18.1	14.0	11.3	1161.0	-22.	3310.
		2	67.8	56.1	49.7	44.9	35.3	26.2	21.2	16.6	12.8	10.4	247.5	-8.	2119.
		3	55.5	46.0	41.0	37.0	29.1	21.7	17.5	13.8	10.7	8.8	56.5	-12.	966.
		4	59.9	49.8	44.0	40.2	31.8	23.9	19.5	15.7	12.0	9.9	60.6	-26.	1729.
		5	52.3	43.3	40.0	33.5	28.0	21.9	17.5	13.3	11.5	9.5	17.3	36.	740.
11065	2	1	66.1	54.5	48.1	43.5	34.0	25.1	20.2	15.7	12.1	9.7	2308.0	-23.	3810.
		2	58.0	48.1	42.5	38.6	30.1	22.2	17.9	13.9	10.7	8.6	348.7	-17.	1728.
		3	61.1	50.6	44.9	40.8	32.0	23.8	19.3	15.0	11.6	9.4	318.8	-33.	3150.
		4	55.1	45.5	40.5	36.8	28.6	21.2	17.2	13.3	10.3	8.3	76.8	48.	1269.
		5	60.7	50.1	44.8	41.1	32.0	23.8	19.4	14.9	11.6	9.4	57.5	-30.	1424.
11096	2	1	41.0	33.5	29.4	26.5	20.7	15.2	12.2	9.5	7.3	5.9	826.0	-16.	1995.
		2	50.9	42.0	37.0	33.5	26.3	19.4	15.7	12.3	9.5	7.6	655.4	-33.	4749.
		3	47.3	39.1	34.4	31.1	24.5	18.1	14.6	11.4	8.8	7.1	133.8	43.	1930.
		4	55.6	46.0	40.5	36.9	29.1	21.7	17.6	13.8	10.8	8.8	90.7	-22.	2190.
		5	51.0	41.6	36.9	33.9	26.8	20.3	16.5	13.1	10.3	8.4	29.3	-6.	1059.
11120	2	1	34.6	28.4	25.1	22.6	17.7	13.0	10.5	8.2	6.2	5.0	2624.0	-30.	4110.
		2	32.6	26.9	24.0	21.5	16.8	12.3	9.9	7.5	5.9	4.7	397.1	42.	1870.
		3	40.9	33.9	30.0	27.0	21.3	15.8	12.7	9.9	7.6	6.2	246.4	-23.	2310.
		4	38.4	31.8	28.1	25.4	20.1	14.8	12.1	9.5	7.4	6.0	72.8	2.	1142.
		5	38.9	31.9	28.7	25.8	20.3	15.0	12.4	9.5	7.5	6.4	26.7	6.	628.
11146	2	1	20.0	15.8	14.1	12.5	9.8	7.1	5.7	4.4	3.3	2.7	879.1	43.	1200.
		2	31.7	26.5	23.2	20.6	16.3	12.0	9.7	7.5	5.8	4.7	468.5	-21.	1918.
		3	29.1	23.7	21.4	19.2	15.2	11.3	9.2	7.2	5.5	4.4	126.2	-3.	1030.

		4	31.7	25.9	23.6	20.9	16.6	12.3	9.9	7.9	6.3	5.2	43.1	12.	587.
		5	36.4	32.1	28.3	24.7	19.8	15.2	12.4	9.3	8.3	5.5	44.2	-9.	904.
11170	2	1	26.8	22.1	19.2	17.3	13.5	10.0	8.0	6.2	4.7	3.8	617.2	-19.	1938.
		2	23.3	19.6	17.2	15.5	12.3	9.0	7.3	5.7	4.3	3.4	123.6	-3.	1164.
		3	24.7	20.8	18.2	16.4	12.9	9.6	7.7	5.9	4.6	3.7	36.2	9.	679.
		4	30.8	25.7	22.8	20.6	16.3	12.3	9.9	7.9	6.0	4.8	32.8	0.	1030.
		5	40.0	31.2	26.6	25.0	19.0	15.1	11.4	9.0	7.6	6.6	22.7	2.	1068.
11195	2	1	16.4	13.5	11.7	10.6	8.3	6.2	4.9	3.7	2.7	2.1	294.7	-3.	462.
		2	19.6	16.2	14.2	12.8	10.0	7.4	5.9	4.6	3.5	2.8	70.2	10.	331.
		3	25.2	21.1	18.4	16.7	13.0	9.5	7.6	6.0	4.7	3.8	55.7	-4.	523.
		4	32.3	27.0	23.7	21.6	17.1	13.0	10.8	8.1	6.2	5.0	36.7	9.	575.
		5	37.3	30.7	26.8	24.2	18.9	14.0	11.3	9.0	6.9	5.6	39.8	-23.	936.
11220	2	1	18.5	15.3	13.2	11.8	9.1	6.7	5.3	4.2	3.1	2.4	449.1	11.	783.
		2	23.1	19.2	16.7	15.0	11.7	8.7	6.9	5.4	4.1	3.2	212.6	-3.	1112.
		3	29.1	24.5	21.4	19.4	15.2	11.3	9.0	7.1	5.4	4.3	112.1	4.	1170.
		4	32.8	27.4	24.0	21.6	16.9	12.6	10.0	7.9	5.9	4.6	108.7	-13.	1890.
		5	38.8	32.8	28.6	25.9	20.5	15.5	12.5	9.8	7.6	6.2	104.9	31.	2740.
11246	2	1	17.1	13.8	12.0	10.9	8.3	6.0	4.8	3.7	2.8	2.2	362.7	-2.	669.
		2	24.3	20.0	17.5	15.9	12.3	9.0	7.2	5.6	4.3	3.4	159.8	6.	885.
		3	28.0	23.1	20.2	18.4	14.3	10.5	8.5	6.6	5.0	4.0	144.0	-19.	1590.
		4	34.5	28.8	25.4	23.1	18.1	13.3	10.8	8.5	6.5	5.3	127.0	39.	2340.
		5	43.4	36.4	32.0	29.1	22.9	17.0	13.7	10.8	8.3	6.7	120.4	-29.	3330.
11270	2	1	18.7	15.5	13.5	12.1	9.4	6.9	5.4	4.2	3.3	2.6	256.5	8.	447.
		2	24.4	19.9	17.5	15.6	12.1	9.0	7.1	5.6	4.3	3.4	202.1	-16.	1057.
		3	31.2	26.1	23.1	20.5	16.3	12.2	9.7	7.7	6.0	4.7	165.0	36.	1720.
		4	41.2	34.6	30.4	27.1	21.8	16.3	13.1	10.3	8.2	6.7	141.2	-19.	2460.
		5	52.0	50.2	39.2	31.8	28.1	21.5	19.6	12.1	11.2	10.1	85.3	6.	2232.
11295	2	1	16.4	13.0	11.5	10.0	7.8	5.6	4.5	3.8	2.8	2.1	221.6	-13.	770.
		2	25.1	20.5	18.2	16.2	12.8	9.4	7.6	5.7	4.5	3.7	135.8	36.	1420.
		3	36.5	30.1	26.7	23.8	19.0	14.1	11.3	8.9	6.8	5.5	100.2	-22.	2000.
		4	41.8	34.6	30.9	27.7	22.3	16.6	13.7	11.2	8.7	7.0	55.1	16.	1920.
		5	44.2	36.1	31.5	28.8	23.2	17.6	14.2	11.4	8.7	7.4	28.3	22.	1470.
11320	2	1	19.3	15.8	13.7	12.4	9.5	7.0	5.5	4.3	3.2	2.6	588.0	35.	971.
		2	30.9	25.6	22.5	20.3	15.9	11.8	9.5	7.4	5.7	4.6	307.9	-21.	1526.
		3	38.0	31.8	28.2	25.6	20.3	15.3	12.3	9.7	7.5	6.1	143.8	6.	1420.
		4	41.1	34.4	30.5	27.7	22.0	16.6	13.4	10.6	8.2	6.7	68.7	36.	1135.
		5	41.9	34.9	30.8	27.9	22.1	16.6	13.5	10.7	8.3	6.7	23.8	-23.	589.
11342	2	1	24.6	20.3	17.8	16.0	12.4	9.1	7.3	5.6	4.3	3.3	559.6	-24.	1171.
		2	33.5	28.2	24.9	22.5	17.8	13.4	10.8	8.5	6.6	5.3	170.8	11.	1072.
		3	37.7	32.0	28.3	25.6	20.3	15.3	12.4	9.8	7.6	6.1	72.8	28.	912.
		4	39.1	33.0	29.5	26.5	20.9	15.9	12.7	10.2	8.0	6.3	24.1	-14.	504.
		5	36.1	31.1	26.7	24.0	19.3	14.6	11.9	9.2	7.1	5.8	16.9	-36.	530.

11365	2	1	23.8	19.7	17.4	15.5	12.3	9.1	7.4	5.8	4.4	3.6	527.8	15.	1104.
		2	31.7	26.6	23.6	21.1	16.8	12.5	10.2	8.0	6.1	5.0	124.4	27.	781.
		3	33.0	27.8	24.8	22.2	17.6	13.2	10.7	8.4	6.5	5.3	36.6	-16.	458.
		4	31.7	26.5	23.7	21.1	16.9	12.7	10.2	8.2	6.3	5.2	23.5	-30.	492.
		5	33.3	28.0	25.1	22.3	17.6	13.4	10.9	8.6	6.5	5.5	17.7	-26.	554.
11388	2	1	24.0	19.6	16.9	15.1	11.2	8.2	6.3	5.0	3.9	3.2	444.4	11.	930.
		2	26.8	22.2	19.3	17.6	13.8	8.9	8.2	6.4	4.9	3.9	90.3	-11.	567.
		3	24.8	20.5	17.6	16.1	12.6	8.7	7.5	5.8	4.5	3.6	49.1	-36.	615.
		4	27.9	23.1	19.8	18.3	14.4	9.9	8.6	6.5	4.9	3.9	32.8	-18.	687.
		5	32.4	26.8	23.1	21.3	16.1	12.7	9.5	7.2	5.5	4.7	34.6	-44.	1085.
11415	2	1	20.5	16.7	14.6	13.3	10.3	7.6	6.0	4.7	3.6	2.8	376.9	-21.	622.
		2	19.6	16.0	14.0	12.6	9.9	7.3	5.8	4.5	3.5	2.7	155.4	-38.	770.
		3	21.6	17.7	15.5	14.1	10.8	7.9	6.4	5.0	3.8	3.0	85.4	-19.	844.
		4	25.9	21.4	18.7	17.0	13.2	9.8	7.8	6.1	4.7	3.8	80.2	-33.	1325.
		5	21.1	17.5	15.2	13.8	10.9	8.4	7.3	5.8	4.6	3.6	40.9	29.	1013.
11435	2	1	16.7	13.6	11.9	10.5	8.3	6.1	4.9	3.8	2.9	2.3	434.1	-43.	681.
		2	18.0	14.8	13.1	11.4	9.0	6.5	5.3	4.1	3.1	2.4	176.6	-15.	831.
		3	21.5	17.8	15.7	13.9	11.0	8.1	6.5	5.1	3.9	3.1	141.2	-36.	1320.
		4	17.4	14.6	13.0	11.5	9.2	6.8	5.5	4.3	3.2	2.5	66.1	37.	1037.
		5	35.2	29.0	27.2	22.8	16.9	13.1	9.6	7.9	6.6	5.4	60.7	-3.	1428.
11460	2	1	17.8	14.4	12.7	11.3	8.8	6.6	5.4	4.3	3.3	2.3	281.5	-12.	589.
		2	19.4	15.5	13.6	12.1	9.3	6.6	5.2	3.8	2.8	2.3	170.1	19.	1068.
		3	17.9	14.7	13.3	11.9	9.1	7.0	5.7	4.5	3.4	2.6	91.0	-18.	1140.
		4	34.0	27.1	24.0	21.4	16.4	11.9	9.5	7.1	5.5	4.6	62.9	3.	1316.
		5	46.5	36.6	32.3	30.0	24.0	17.5	13.5	10.4	8.0	6.4	58.6	-37.	1840.
11480	2	1	20.0	16.1	13.8	12.4	9.5	6.8	5.4	4.1	3.1	2.4	483.5	-29.	2160.
		2	18.6	15.4	13.1	11.7	9.1	6.5	5.2	4.1	3.1	2.4	122.7	34.	1650.
		3	30.4	24.9	21.0	18.8	14.5	10.4	8.2	6.2	4.5	3.5	67.3	2.	1800.
		4	40.8	34.1	28.9	25.9	20.4	14.8	11.8	9.1	7.0	5.6	53.5	-24.	2400.
		5	28.2	24.4	20.5	18.5	14.8	11.1	9.2	7.7	6.0	4.6	28.3	20.	1900.
11505	2	1	20.9	16.6	14.4	12.7	9.9	7.1	5.6	4.3	3.2	2.5	624.6	-7.	1634.
		2	46.0	29.8	24.7	22.3	17.1	12.2	9.5	7.3	5.7	4.1	152.0	-18.	1193.
		3	22.2	24.7	22.2	19.4	15.1	10.9	8.8	6.6	4.8	4.1	152.6	-15.	2390.
		4	25.6	20.8	18.1	16.2	13.0	9.6	7.8	6.0	4.7	3.7	60.3	38.	1577.
11528	2	1	33.8	27.2	23.5	20.7	15.9	11.4	8.9	6.8	5.1	4.0	231.6	0.	1450.
		2	38.8	30.6	26.9	23.8	18.4	13.4	10.7	8.2	6.2	4.9	105.8	-30.	1990.
		3	24.1	19.1	17.3	15.2	12.1	9.2	7.4	5.9	4.6	3.7	46.3	26.	1740.
11551	2	1	29.8	224.3	20.5	18.5	13.9	9.8	7.7	5.8	4.3	3.3	194.1	-28.	2030.
		2	19.5	15.4	12.6	12.0	9.2	6.8	5.6	4.3	3.1	2.4	66.8	27.	2099.
11575	2	1	41.7	33.8	29.1	25.9	20.0	14.4	11.4	8.7	6.5	5.1	873.4	26.	2742.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 50W.IND
DATA FILE : 50W.DAT

LINE NO. : 504

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	14.3	11.6	10.4	9.5	7.6	5.7	4.6	3.6	2.8	2.3	591.1	-9.	232.
		2	10.8	8.8	8.0	7.2	5.7	4.2	3.4	2.7	2.1	1.6	144.6	15.	170.
		3	8.5	6.9	6.1	5.6	4.4	3.3	2.7	2.1	1.5	1.3	70.4	-1.	165.
		4	10.3	8.5	7.8	7.2	5.8	4.4	3.5	2.7	2.2	1.6	50.8	-8.	199.
		5	8.8	7.9	6.6	6.1	4.9	3.5	2.9	2.1	1.5	1.2	21.2	11.	125.
10850	2	1	8.0	6.3	5.8	5.2	4.1	3.0	2.5	1.9	1.5	1.2	282.9	25.	123.
		2	8.6	6.8	6.2	5.5	4.4	3.2	2.6	2.0	1.6	1.3	104.3	5.	136.
		3	10.7	8.8	8.1	7.4	5.9	4.5	3.6	2.9	2.2	1.9	65.7	-7.	171.
		4	9.7	7.8	7.2	6.7	5.2	3.7	3.1	2.4	1.8	1.5	23.6	-2.	102.
		5	5.1	4.1	4.2	4.0	2.7	2.4	2.0	1.3	1.2	1.2	42.5	4.	278.
10875	2	1	8.4	6.8	5.9	5.5	4.2	3.1	2.4	1.9	1.4	1.1	306.5	12.	137.
		2	11.8	10.0	8.9	8.3	6.5	5.0	4.0	3.2	2.5	2.1	124.8	-13.	167.
		3	11.2	9.6	8.8	8.1	6.5	4.9	4.0	3.2	2.5	2.1	37.4	0.	100.
		4	8.1	7.0	6.5	6.1	4.8	3.8	3.1	2.6	2.1	1.8	57.8	1.	259.
		5	3.7	4.0	2.6	1.9	1.4	1.0	.7	1.8	.8	.5	33.0	-14.	221.
10900	2	1	12.6	10.2	8.7	7.7	6.2	4.8	3.7	3.0	2.2	1.9	353.9	3.	146.
		2	12.9	10.6	9.6	8.7	7.0	5.2	4.2	3.2	2.4	1.9	73.4	4.	91.
		3	10.3	8.5	7.6	6.8	5.5	4.1	3.2	2.4	1.8	1.3	95.3	-6.	235.
		4	8.4	6.5	5.8	5.1	4.1	2.9	2.3	1.6	1.1	.8	50.5	-13.	208.
		5	-7.2	-8.5	-7.3	-5.1	-4.5	-5.1	-3.1	-2.7	-2.9	-2.2	57.0	-86.	353.
10925	2	1	13.1	11.1	9.8	9.0	7.1	5.4	4.3	3.4	2.6	2.1	147.1	7.	69.
		2	13.1	11.2	9.8	8.9	7.1	5.3	4.3	3.3	2.5	2.0	141.3	-2.	201.
		3	10.9	9.4	8.1	7.3	5.8	4.3	3.4	2.6	1.9	1.5	67.0	-7.	190.
		4	2.5	2.4	1.7	1.5	1.1	.7	.5	.3	.1	.0	67.4	-20.	320.
		5	10.0	8.8	7.4	6.6	5.2	3.8	3.0	2.3	1.7	1.3	50.2	22.	358.
10950	2	1	18.6	15.7	13.7	12.6	10.1	7.6	6.1	4.8	3.7	3.0	528.4	1.	276.

		2	18.2	15.4	13.3	12.3	9.7	7.2	5.8	4.5	3.4	2.7	160.2	-6.	251.
		3	7.1	6.6	5.5	5.1	4.0	2.9	2.3	2.0	1.3	1.0	122.1	-19.	380.
		4	12.9	11.0	9.3	8.7	6.9	5.1	4.0	3.1	2.2	1.7	71.4	4.	373.
		5	21.0	17.8	15.1	14.0	11.1	8.2	6.6	5.1	3.8	3.0	100.8	-3.	790.
10973	2	1	20.2	16.9	14.8	13.4	10.5	7.8	6.4	5.0	3.9	3.2	313.2	0.	196.
		2	11.2	9.6	8.1	7.4	5.8	4.3	3.4	2.7	2.1	1.6	175.2	-25.	330.
		3	13.5	11.8	10.2	9.3	7.2	5.5	4.4	3.5	2.8	2.2	89.8	12.	337.
		4	21.4	18.3	16.0	14.7	11.5	8.8	7.1	5.7	4.5	3.7	110.4	-14.	690.
		5	40.5	34.5	30.2	27.7	21.6	16.4	13.8	10.8	8.5	7.1	76.5	9.	720.
10996	2	1	14.9	12.0	10.6	9.7	7.5	5.5	4.5	3.5	2.6	2.1	931.0	-21.	487.
		2	15.9	12.8	11.2	10.3	8.0	5.9	4.7	3.7	2.8	2.2	291.3	13.	457.
		3	21.0	17.0	14.9	13.7	10.7	7.9	6.4	5.0	3.8	3.0	273.5	-16.	850.
		4	40.4	33.3	29.1	26.7	21.0	15.6	12.6	9.8	7.5	6.0	156.5	-4.	810.
		5	46.9	38.4	33.5	30.8	24.1	17.9	14.4	11.4	8.7	7.0	104.9	-9.	820.
11022	2	1	23.4	19.5	16.7	15.3	11.9	8.7	7.0	5.5	4.2	3.4	837.8	11.	453.
		2	21.7	18.1	15.7	14.4	11.3	8.4	6.7	5.2	4.0	3.2	494.1	-16.	802.
		3	39.1	32.9	28.8	26.3	20.8	15.6	12.5	9.8	7.6	6.1	228.5	5.	740.
		4	46.3	38.7	33.7	30.7	24.3	18.2	14.5	11.5	8.8	7.2	139.4	-30.	750.
		5	47.1	39.3	34.6	31.6	25.2	18.7	15.2	12.0	9.3	7.5	86.0	11.	698.
11047	2	1	54.6	44.8	39.2	35.2	27.6	20.2	16.3	12.7	9.7	7.9	2349.0	-28.	4090.
		2	58.8	49.7	43.4	39.0	31.3	23.2	18.8	14.7	11.4	9.3	290.5	9.	1520.
		3	53.9	46.3	39.2	34.8	29.0	21.5	17.6	13.9	10.8	8.9	93.9	-35.	980.
		4	52.0	45.5	37.1	32.0	28.0	20.9	17.2	13.7	10.8	9.0	44.6	3.	778.
		5	46.3	41.6	32.7	28.0	26.0	19.3	16.2	13.2	10.4	8.9	26.3	23.	689.
11072	2	1	57.7	47.8	42.3	38.1	30.0	22.2	17.9	14.1	10.9	8.8	4356.0	-16.	7590.
		2	67.1	56.4	50.2	45.2	35.8	26.6	21.5	16.9	13.0	10.6	556.3	-31.	2911.
		3	59.5	50.0	44.6	39.9	31.8	23.7	19.2	15.1	11.7	9.5	141.1	-2.	1470.
		4	52.8	44.1	39.4	35.0	28.1	20.9	17.1	13.5	10.5	8.6	71.3	15.	1242.
		5	47.1	39.7	35.9	31.2	25.6	19.1	15.8	12.6	9.8	8.2	22.8	-17.	596.
11096	2	1	74.3	61.7	54.2	49.2	38.3	28.4	22.8	17.9	13.7	11.1	1025.0	-34.	3500.
		2	67.0	56.3	49.5	45.1	35.2	26.3	21.1	16.5	12.7	10.2	195.0	0.	2040.
		3	56.8	47.7	41.9	38.4	29.9	22.4	18.0	14.1	10.9	8.8	87.1	8.	1810.
		4	49.9	42.3	37.3	34.3	26.6	20.3	16.3	12.9	10.1	8.2	23.3	-23.	810.
		5	53.5	45.0	39.5	35.5	28.1	19.1	17.6	13.0	10.0	8.2	9.4	47.	494.
11121	2	1	62.3	51.5	45.3	40.9	32.0	23.6	19.0	14.8	11.4	9.2	2229.0	-11.	4110.
		2	57.4	47.6	42.0	37.9	29.7	21.9	17.6	13.7	10.5	8.5	704.0	6.	3900.
		3	49.6	41.2	36.3	32.9	26.0	19.4	15.7	12.3	9.5	7.7	145.9	-23.	1610.
		4	50.5	41.6	36.7	33.3	26.5	19.8	16.2	12.6	9.9	8.1	50.5	33.	932.
		5	49.3	39.3	34.4	30.5	25.4	18.3	14.9	11.4	9.3	7.6	16.5	-22.	458.
11147	2	1	46.4	38.1	33.3	30.0	23.5	17.2	13.8	10.7	8.1	6.5	2256.0	-1.	5900.
		2	37.8	31.3	27.5	24.8	19.6	14.5	11.7	9.1	6.9	5.6	318.3	-20.	2498.
		3	37.2	31.1	27.4	24.7	19.7	14.6	11.9	9.4	7.2	5.8	94.9	37.	1487.

		4	37.3	30.5	26.9	24.5	19.1	14.1	11.6	9.0	7.1	5.9	29.3	-33.	766.
		5	45.0	38.5	33.8	30.3	24.6	18.4	15.0	11.9	9.1	7.5	42.7	14.	1674.
11171	2	1	31.3	25.7	22.7	20.3	15.9	11.8	9.4	7.3	5.6	4.5	1293.0	-22.	2380.
		2	30.3	25.0	22.2	19.7	15.5	11.6	9.3	7.3	5.6	4.5	328.2	37.	1818.
		3	26.8	22.3	19.9	17.7	13.9	10.4	8.5	6.7	5.1	4.1	94.9	-34.	1049.
		4	37.4	31.2	27.7	24.9	19.6	14.7	11.9	9.3	7.2	5.9	131.2	3.	2420.
		5	39.8	33.0	29.3	26.3	20.8	15.6	12.7	10.1	7.9	6.5	77.7	23.	2153.
11197	2	1	23.6	19.5	17.1	15.6	12.2	9.0	7.3	5.7	4.4	3.6	719.8	43.	1614.
		2	21.5	17.9	15.7	14.4	11.0	8.1	6.5	5.1	3.9	3.2	174.6	-28.	1174.
		3	30.1	25.2	22.1	20.2	16.0	11.9	9.6	7.5	5.8	4.7	228.1	-4.	3060.
		4	33.2	27.9	24.3	22.3	17.5	13.2	10.6	8.4	6.5	5.3	113.1	16.	2530.
		5	46.1	39.4	34.1	31.7	24.9	19.0	15.4	12.1	9.5	7.8	87.9	-14.	2958.
11222	2	1	20.4	16.9	14.8	13.4	10.4	7.6	6.1	4.8	3.6	2.9	840.8	-30.	1650.
		2	29.6	24.6	21.6	19.5	15.4	11.4	9.2	7.2	5.6	4.5	620.7	-3.	3654.
		3	28.4	23.7	20.9	18.9	14.9	11.1	9.0	7.1	5.5	4.5	264.8	14.	3110.
		4	40.3	34.1	30.1	27.3	21.8	16.5	13.6	11.0	8.8	7.4	153.1	-21.	3000.
		5	40.8	34.8	32.4	28.2	25.3	17.3	16.0	11.1	9.3	8.0	30.1	21.	886.
11248	2	1	31.1	25.7	22.3	20.2	15.7	11.6	9.3	7.3	5.5	4.4	1956.0	-5.	4380.
		2	26.8	22.4	19.5	17.9	14.0	10.4	8.4	6.6	5.1	4.1	478.2	17.	3217.
		3	35.2	29.9	26.2	24.4	19.3	14.5	11.8	9.4	7.2	5.9	206.0	-29.	2760.
		4	38.6	32.7	28.8	27.2	21.5	16.4	13.6	11.0	8.4	7.1	35.0	12.	784.
		5	46.4	38.0	32.9	30.8	24.3	19.2	15.6	13.0	10.6	8.0	22.3	9.	750.
11273	2	1	22.6	18.7	16.4	14.8	11.6	8.6	6.9	5.4	4.2	3.4	887.9	18.	1742.
		2	31.1	26.1	23.1	21.0	16.6	12.4	10.0	7.8	6.1	4.9	294.8	-32.	1735.
		3	33.3	28.2	25.1	22.6	18.0	13.5	11.0	8.6	6.8	5.6	45.7	14.	536.
		4	40.3	34.0	30.0	27.3	21.9	15.7	13.1	9.8	7.8	6.5	28.2	2.	554.
		5	46.3	38.2	33.3	30.9	24.2	17.9	14.6	11.3	9.0	7.1	43.3	-17.	1273.
11297	2	1	33.0	27.3	24.3	22.1	17.4	12.9	10.4	8.2	6.3	5.1	1120.0	-32.	2190.
		2	32.1	27.1	24.1	22.4	17.7	13.0	10.6	8.3	6.2	5.0	89.1	16.	525.
		3	34.9	28.8	24.7	23.3	18.0	12.8	10.2	7.5	5.3	4.0	38.8	1.	456.
		4	42.2	34.5	29.4	27.8	21.5	15.1	11.8	8.7	6.1	4.4	57.0	-31.	1118.
		5	46.3	37.9	31.9	31.4	23.7	16.5	13.2	9.6	6.9	6.8	51.2	25.	1506.
11322	2	1	32.3	26.7	23.6	21.5	16.7	12.4	10.1	8.0	6.2	5.1	894.3	1.	1404.
		2	27.7	22.8	20.4	18.7	14.5	10.9	8.8	6.9	5.3	4.2	98.8	4.	465.
		3	37.6	31.0	27.9	25.4	19.8	15.0	12.1	9.5	7.3	5.8	99.2	-32.	932.
		4	44.4	36.5	32.9	30.1	23.5	17.7	14.3	11.2	8.6	6.9	80.8	17.	1268.
		5	49.3	40.2	36.2	33.0	25.7	19.6	16.0	12.5	9.6	7.6	41.9	22.	986.
11346	2	1	30.7	25.1	21.9	19.8	15.4	11.2	9.0	7.0	5.3	4.2	482.1	2.	1376.
		2	32.4	26.5	23.1	21.2	16.3	11.8	9.3	7.1	5.2	4.0	164.9	-23.	1412.
		3	36.6	30.0	26.1	24.3	18.7	13.5	10.6	8.0	5.7	4.1	98.4	7.	1681.
		4	41.1	33.5	29.9	27.7	21.0	15.6	11.2	9.1	5.8	4.3	41.6	11.	1188.
		5	47.5	37.1	32.1	31.5	23.6	16.6	13.8	8.7	6.8	4.4	31.0	8.	1327.

11372	2	1	26.4	22.0	19.3	17.3	13.5	10.0	8.0	6.3	4.8	3.8	854.5	-26.	1412.
		2	32.5	27.2	24.0	21.7	17.0	12.6	10.1	7.9	6.0	4.7	271.1	7.	1344.
		3	38.2	32.1	28.5	25.8	20.3	15.2	12.1	9.5	7.2	5.7	99.8	8.	987.
		4	44.1	36.7	32.7	29.5	23.1	17.5	14.1	10.9	8.5	6.5	69.6	3.	1149.
		5	45.2	37.7	33.0	27.8	23.1	20.0	13.6	11.6	7.6	7.4	19.0	10.	470.
11397	2	1	22.2	18.4	16.0	14.6	11.4	8.4	6.8	5.3	4.1	3.3	514.4	9.	950.
		2	32.0	26.6	23.2	21.3	16.6	12.4	10.0	7.8	6.0	4.8	135.6	15.	751.
		3	38.5	32.0	28.0	25.7	20.0	14.8	11.9	9.3	7.2	5.7	86.6	-4.	957.
		4	38.3	32.4	28.7	27.0	20.6	15.3	12.6	9.7	7.7	6.4	21.9	-1.	405.
		5	41.8	33.9	28.6	27.7	21.1	16.7	13.4	10.1	8.2	6.7	18.2	15.	503.
11422	2	1	23.9	19.7	17.2	15.7	12.3	9.1	7.3	5.8	4.4	3.6	262.3	17.	686.
		2	31.2	25.9	22.6	20.5	15.9	11.9	9.6	7.6	5.8	4.7	112.9	-8.	886.
		3	32.9	27.3	24.2	22.1	17.5	13.1	10.4	8.4	6.6	5.4	38.4	5.	601.
		4	36.6	28.6	26.3	22.7	18.0	13.8	10.7	9.1	6.9	5.7	21.2	5.	554.
		5	36.7	32.9	27.9	28.7	19.3	15.7	12.0	9.9	7.7	6.6	13.4	-3.	525.
11447	2	1	23.9	19.3	16.8	15.3	11.9	8.8	7.0	5.5	4.2	3.4	569.6	-4.	894.
		2	25.4	21.0	18.4	16.8	13.1	9.8	7.9	6.2	4.8	3.9	145.3	9.	684.
		3	26.9	22.1	19.3	17.6	13.8	10.3	8.4	6.7	5.2	4.3	67.7	5.	636.
		4	32.5	26.8	23.3	21.4	17.0	13.0	10.7	8.4	6.7	5.6	37.7	-18.	591.
		5	37.6	31.4	27.5	25.0	19.6	14.6	12.2	9.8	7.9	6.2	58.8	3.	1385.
11472	2	1	21.6	17.6	15.7	13.9	10.9	8.0	6.5	5.0	3.8	3.0	380.7	9.	747.
		2	21.4	17.2	15.2	13.6	10.6	7.7	6.2	4.8	3.6	2.8	109.2	6.	642.
		3	25.7	21.0	18.4	16.7	13.0	9.4	7.6	5.9	4.4	3.4	49.9	-21.	586.
		4	30.8	25.4	21.9	20.2	15.6	11.2	9.0	7.0	5.2	4.3	72.0	-2.	1412.
		5	36.4	29.4	32.0	31.3	18.4	15.4	10.3	9.0	5.7	4.1	48.2	-13.	1418.
11497	2	1	19.6	15.7	13.9	12.4	9.7	7.0	5.6	4.3	3.3	2.6	444.3	6.	871.
		2	22.0	17.6	15.6	13.9	10.6	8.0	6.3	4.9	3.8	3.0	111.8	-17.	658.
		3	25.9	21.1	18.5	16.5	13.0	9.5	7.6	6.0	4.6	3.7	130.4	-8.	1530.
		4	30.4	24.4	21.5	18.7	15.3	11.4	8.5	7.2	5.3	4.4	76.8	-11.	1506.
11520	2	1	17.9	14.8	12.9	11.4	9.2	6.7	5.0	4.2	3.2	2.6	135.1	-15.	424.
		2	23.6	19.0	16.6	15.1	11.7	8.6	6.9	5.4	4.2	3.3	118.2	-7.	1113.
		3	27.1	21.4	18.9	17.3	13.5	9.9	7.9	6.3	4.8	3.8	62.2	-11.	1168.
11542	2	1	18.0	14.8	12.9	11.7	9.0	6.5	5.2	4.0	3.0	2.4	283.1	-9.	980.
		2	24.4	18.7	15.5	14.4	11.0	8.2	6.5	5.1	3.9	3.1	102.7	-9.	1070.
11571	2	1	16.7	12.9	11.0	10.1	7.8	5.5	4.5	3.4	2.6	2.0	155.5	-10.	810.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA - LARA PROJECT

INDEX FILE : 49W.IND
DATA FILE : 49W.DAT

LINE NO. : 494

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10825	2	1	13.2	10.9	9.7	9.0	7.0	5.3	4.3	3.4	2.6	2.1	358.9	-24.	154.
		2	13.2	10.9	9.7	8.9	7.0	5.3	4.3	3.4	2.7	2.2	100.0	20.	129.
		3	8.7	7.1	6.3	5.8	4.5	3.4	2.7	2.2	1.6	1.3	72.8	15.	187.
		4	8.1	6.8	6.2	5.8	4.4	3.5	2.9	2.3	2.0	1.6	18.5	-4.	79.
		5	9.8	7.9	7.2	6.9	6.2	4.5	3.5	3.3	2.3	2.2	19.7	-10.	127.
10850	2	1	12.9	10.3	9.4	8.6	6.8	5.1	4.1	3.2	2.4	1.8	217.6	22.	113.
		2	8.9	6.8	6.3	5.7	4.4	3.2	2.6	2.0	1.7	1.5	113.2	-5.	177.
		3	7.9	6.1	5.8	5.2	4.1	2.9	2.2	1.7	1.2	.9	29.2	10.	91.
		4	9.7	7.5	7.3	6.6	5.1	3.7	3.1	2.2	1.9	1.3	24.6	4.	128.
		5	12.7	9.9	8.7	8.4	7.1	3.8	2.5	3.5	1.2	.7	11.6	-24.	90.
10875	2	1	14.1	11.7	10.3	9.5	7.5	5.7	4.6	3.7	2.8	2.3	355.1	-8.	174.
		2	10.7	9.0	7.9	7.4	5.7	4.3	3.4	2.7	2.0	1.6	62.7	11.	92.
		3	11.4	9.8	8.7	8.5	6.4	4.8	3.9	3.1	2.4	1.9	43.9	0.	129.
		4	12.7	11.2	10.7	10.7	7.6	6.4	5.6	3.2	2.9	4.3	18.3	-5.	89.
		5	10.0	9.4	7.6	7.7	5.5	4.3	3.2	3.2	2.2	.3	26.4	-10.	194.
10900	2	1	12.6	10.7	9.5	8.6	6.9	5.2	4.1	3.3	2.5	2.1	183.3	13.	72.
		2	13.3	11.5	10.2	9.2	7.3	5.5	4.5	3.5	2.6	2.1	98.7	-21.	118.
		3	15.0	13.3	12.1	11.0	9.0	6.9	5.6	4.4	3.4	2.7	37.5	11.	89.
		4	12.4	11.2	9.9	8.9	7.1	5.6	4.3	3.4	2.6	1.9	45.8	2.	182.
		5	5.7	6.6	5.2	4.3	3.7	2.9	2.2	1.7	1.1	.8	61.5	-4.	366.
10925	2	1	12.6	10.7	9.4	8.6	6.9	5.1	4.2	3.3	2.5	2.0	489.9	-23.	140.
		2	16.2	14.0	12.4	11.4	9.3	7.0	5.7	4.5	3.5	2.8	122.3	20.	105.
		3	16.5	14.1	12.3	11.4	9.1	6.8	5.5	4.3	3.3	2.6	113.2	-14.	193.
		4	10.4	8.8	7.5	7.4	5.8	4.2	3.4	2.7	2.0	1.6	127.0	5.	362.
		5	3.3	3.3	2.8	2.4	2.0	1.4	1.5	.7	.7	.6	63.1	10.	270.
10950	2	1	15.8	13.8	12.0	11.2	9.1	7.0	5.7	4.5	3.4	2.7	292.2	17.	96.

		2	19.7	16.8	14.8	13.6	10.7	8.0	6.5	5.1	3.9	3.3	187.8	-15.	186.
		3	13.5	11.7	10.1	9.5	7.6	5.7	4.6	3.8	2.8	2.3	170.4	1.	330.
		4	6.3	5.7	4.9	4.8	3.8	3.3	2.3	1.6	1.2	.9	78.4	22.	259.
		5	4.1	4.0	3.3	3.4	2.6	1.6	1.7	1.2	.9	.8	52.2	-28.	258.
10975	2	1	26.4	21.2	18.5	16.4	12.7	9.4	7.5	5.8	4.4	3.6	347.5	20.	218.
		2	21.2	17.4	15.4	13.7	10.8	7.9	6.3	4.9	3.7	3.0	177.9	-36.	335.
		3	13.7	11.2	9.9	8.8	6.9	5.1	4.1	3.2	2.4	1.9	83.6	46.	314.
		4	10.1	8.0	7.1	6.2	4.9	3.4	2.5	1.9	1.4	1.0	44.6	-46.	279.
		5	6.1	4.7	4.2	3.4	2.8	1.7	1.2	.9	.5	.7	22.9	7.	215.
11000	2	1	24.5	19.6	17.1	15.4	11.9	8.5	6.5	5.4	4.7	4.2	332.6	6.	237.
		2	18.5	15.1	13.1	11.6	9.0	6.4	5.1	3.9	3.0	2.3	124.4	52.	266.
		3	12.2	9.5	8.1	7.1	5.4	3.8	3.1	2.5	1.7	1.4	53.8	-42.	229.
		4	13.3	10.7	10.0	9.0	7.2	5.4	4.7	4.1	3.7	2.7	24.0	-12.	171.
		5	22.9	18.5	16.4	14.8	11.6	9.2	7.7	6.1	5.0	4.2	68.6	4.	734.
11025	2	1	24.4	19.8	16.9	15.3	11.6	8.4	6.7	5.2	4.0	3.2	1022.0	26.	660.
		2	15.9	12.5	10.5	9.5	7.0	5.0	3.8	2.9	2.1	1.7	171.2	-25.	335.
		3	8.4	5.9	4.4	3.9	2.3	1.3	.5	-.4	-1.4	-.7	60.1	-18.	235.
		4	21.4	17.4	14.9	13.8	10.4	7.7	6.1	5.3	4.5	3.4	122.0	-7.	790.
		5	32.3	26.5	22.8	21.2	16.1	11.9	9.5	7.5	5.6	4.4	101.2	17.	990.
11050	2	1	14.8	11.5	10.0	8.9	6.7	4.8	3.7	2.9	2.2	1.8	667.6	-27.	381.
		2	10.8	8.2	6.9	6.1	4.3	3.0	2.2	1.7	1.2	.9	165.8	-13.	283.
		3	18.8	14.7	12.7	11.5	8.5	6.1	4.8	3.7	2.8	2.1	273.0	-11.	930.
		4	30.9	25.0	22.0	20.0	15.5	11.6	9.3	7.3	5.6	4.6	201.2	11.	1140.
		5	47.5	39.2	34.4	31.5	24.5	18.3	14.7	11.5	8.9	7.2	91.6	-13.	784.
11075	2	1	12.9	9.4	7.9	7.0	4.8	3.1	2.4	1.7	1.3	1.0	279.9	12.	219.
		2	20.2	15.1	12.9	11.4	8.3	5.8	4.5	3.4	2.6	2.1	360.3	-9.	848.
		3	33.9	26.8	23.3	21.0	16.0	11.7	9.4	7.2	5.6	4.5	221.8	-23.	1040.
		4	50.9	41.0	36.1	32.6	25.2	18.4	14.8	11.5	8.9	7.2	87.9	6.	690.
		5	57.2	46.3	40.9	37.0	28.8	21.2	17.2	13.3	10.4	8.4	92.8	25.	1093.
11100	2	1	19.5	15.0	12.8	11.3	8.4	5.9	4.6	3.6	2.7	2.1	1658.0	1.	1150.
		2	34.4	28.0	24.3	21.8	16.7	12.1	9.7	7.5	5.7	4.6	506.8	-11.	1060.
		3	51.0	41.0	35.6	32.0	24.8	18.2	14.7	11.6	9.0	7.3	158.2	-11.	660.
		4	59.6	49.1	43.1	38.9	30.2	22.3	18.0	14.1	10.8	8.8	147.7	23.	1030.
		5	63.9	52.6	46.2	41.7	32.9	24.6	19.9	15.7	12.3	9.8	76.4	-122.	799.
11125	2	1	38.4	30.9	27.0	24.0	18.4	13.3	10.7	8.3	6.5	5.2	1128.0	-18.	800.
		2	59.4	48.2	42.4	38.1	29.5	21.8	17.5	13.8	10.6	8.6	239.8	-4.	513.
		3	62.0	50.0	43.9	39.5	30.8	22.7	18.3	14.4	11.2	9.1	195.6	9.	830.
		4	67.7	55.6	49.0	44.4	34.8	25.9	21.1	16.6	12.9	10.5	89.5	0.	638.
		5	62.4	51.4	45.4	41.3	32.4	24.1	19.6	15.5	12.0	9.8	39.4	0.	421.
11150	2	1	79.8	65.0	56.4	50.7	39.0	28.5	22.7	17.7	13.6	11.0	1097.0	10.	3130.
		2	91.2	74.1	64.5	57.9	44.8	32.8	26.2	20.5	15.7	12.7	364.7	19.	3123.
		3	93.9	76.5	66.7	60.0	46.6	34.3	27.5	21.7	17.0	13.8	108.1	-16.	1840.

		4	86.7	71.3	62.5	55.9	43.7	32.6	27.1	20.8	15.4	12.3	33.1	-2.	945.
		5	73.2	60.9	53.8	47.5	37.7	28.8	22.9	18.7	14.7	12.0	15.0	-7.	640.
11175	2	1	72.4	58.6	51.1	45.8	35.2	25.7	20.5	16.0	12.3	9.8	3454.0	-7.	7740.
		2	86.5	70.5	61.7	55.5	43.1	31.7	25.4	19.8	15.3	12.3	648.0	-24.	4360.
		3	83.2	66.4	57.6	51.6	39.6	28.8	22.9	17.8	13.8	11.1	196.5	-1.	2630.
		4	74.3	61.5	54.2	48.7	38.3	28.7	23.3	18.5	14.5	11.8	49.1	-13.	1100.
		5	74.5	58.9	51.4	45.4	36.1	27.2	22.1	17.7	13.8	11.3	12.0	0.	404.
11200	2	1	60.0	48.8	42.2	37.7	29.0	21.1	16.8	13.1	10.1	8.1	3543.0	-31.	7940.
		2	66.8	54.5	47.3	42.3	32.6	23.8	19.0	14.8	11.4	9.2	797.0	-20.	5362.
		3	55.8	44.8	38.9	34.8	26.9	19.5	15.5	11.9	9.1	7.3	131.3	-19.	1760.
		4	60.9	49.9	43.7	39.4	31.2	23.8	20.2	17.8	14.7	12.4	29.9	-5.	670.
		5	56.8	47.3	41.2	36.6	28.6	21.1	16.5	11.7	8.3	5.9	16.4	11.	551.
11225	2	1	65.8	51.3	43.5	38.1	28.2	19.6	15.3	11.7	8.8	6.9	3944.0	-57.	15400.
		2	55.7	43.3	36.9	32.3	24.1	16.9	13.3	10.2	7.7	6.2	354.4	-15.	4170.
		3	40.0	28.8	23.9	20.4	14.4	9.7	7.5	7.5	5.6	4.2	48.9	-15.	1140.
		4	63.6	49.9	42.8	37.5	27.5	18.9	14.5	7.7	5.8	4.9	28.4	10.	1110.
		5	64.8	51.1	45.3	39.9	30.4	22.2	17.9	13.9	11.1	9.5	13.5	8.	790.
11250	2	1	38.3	30.2	25.7	22.8	17.1	12.2	9.6	7.4	5.6	4.5	1838.0	-6.	4800.
		2	36.9	30.1	25.9	23.1	17.6	12.8	10.1	7.9	6.0	4.8	183.9	-7.	1443.
		3	34.9	25.7	21.5	18.7	13.6	9.4	7.3	5.6	4.0	3.0	83.3	0.	1304.
		4	46.2	37.1	32.0	28.6	21.8	15.8	12.6	10.0	8.0	6.9	45.3	4.	1184.
		5	56.0	45.3	39.3	35.5	27.5	20.4	16.5	13.2	10.5	8.2	20.3	13.	796.
11275	2	1	27.7	21.3	18.2	16.1	12.0	8.4	6.8	5.0	4.0	3.4	365.8	-4.	1044.
		2	41.0	30.6	25.6	22.4	15.7	10.6	7.8	6.5	4.4	3.1	135.0	-8.	1156.
		3	41.7	32.7	28.0	25.0	19.0	13.7	10.9	8.5	6.5	5.3	71.5	8.	1222.
		4	50.0	39.9	34.3	30.6	23.3	16.8	13.5	10.6	8.3	6.8	30.2	8.	862.
		5	51.2	41.1	35.1	31.5	24.2	17.4	14.0	11.0	8.5	7.0	36.9	-11.	1581.
11300	2	1	29.2	22.4	19.2	17.0	12.9	9.3	7.4	5.8	4.5	3.7	571.9	-18.	1197.
		2	31.7	25.0	21.7	19.4	14.8	10.1	8.1	6.1	4.7	3.7	218.9	13.	1374.
		3	37.3	29.0	25.1	22.4	17.0	12.2	9.8	7.5	5.8	4.6	82.1	2.	1028.
		4	38.9	31.0	26.9	24.4	18.6	13.5	10.8	8.3	6.4	5.2	86.9	-16.	1819.
		5	50.3	40.6	35.4	32.4	24.9	18.4	15.0	11.6	9.0	7.3	88.6	1.	2782.
11325	2	1	26.1	20.5	17.3	15.2	11.4	8.1	6.4	5.0	3.8	3.0	467.4	10.	1128.
		2	36.7	28.9	24.5	21.7	16.3	11.7	9.2	7.1	5.4	4.3	128.3	5.	929.
		3	35.0	27.2	22.9	20.4	15.4	11.3	8.9	6.9	5.4	4.5	111.0	-23.	1600.
		4	46.4	37.3	32.0	28.7	21.7	15.5	12.3	9.6	7.1	5.5	104.0	1.	2510.
		5	55.9	45.0	39.0	35.3	27.1	20.0	16.0	12.5	9.7	7.8	72.1	17.	2610.
11350	2	1	39.4	31.1	26.6	23.8	18.2	13.7	9.9	7.0	4.5	1.6	328.5	2.	937.
		2	35.3	27.2	22.9	20.2	15.0	10.4	8.2	6.2	4.7	3.6	163.6	-10.	1401.
		3	44.3	34.7	29.6	26.4	20.0	14.3	11.4	8.8	6.7	5.3	128.4	7.	2190.
		4	53.7	43.0	37.0	33.0	25.3	18.4	14.8	11.8	9.1	7.5	86.2	19.	2461.
		5	57.4	46.1	39.8	35.6	27.6	19.5	15.4	11.2	8.2	6.1	37.1	-22.	1587.

11375	2	1	27.2	21.1	18.0	15.8	11.9	8.5	6.8	5.6	4.1	3.0	597.2	-12.	1250.
		2	37.9	30.2	26.1	23.2	17.8	12.9	10.2	7.9	6.1	4.9	278.2	0.	1747.
		3	44.6	35.6	30.8	27.4	21.0	15.2	12.1	9.4	7.2	5.8	171.2	10.	2140.
		4	49.5	40.6	35.6	31.7	24.5	18.1	14.4	11.3	8.7	7.0	68.6	-22.	1436.
		5	61.8	51.1	45.0	40.3	31.8	24.0	19.5	15.7	13.9	12.5	49.6	27.	1557.
11397	2	1	42.8	32.6	27.4	23.7	17.3	11.9	9.1	7.0	5.3	4.2	262.2	-3.	1020.
		2	54.2	42.2	36.0	31.6	23.5	16.6	13.0	10.0	7.6	6.1	136.4	-2.	1600.
		3	54.0	41.6	35.4	31.1	23.0	16.2	12.7	9.7	7.5	6.2	48.6	-17.	1140.
		4	65.6	51.9	44.7	39.6	29.9	21.5	17.0	13.4	10.6	8.4	34.1	43.	1330.
		5	69.3	55.2	47.7	42.4	32.1	23.4	18.6	14.2	10.7	9.5	15.6	-29.	910.
11421	2	1	32.6	25.4	21.9	19.1	14.4	10.1	8.0	6.1	4.6	3.7	666.0	-4.	1608.
		2	42.4	33.0	28.3	24.8	18.8	13.4	10.6	8.1	6.2	4.9	154.5	-10.	1119.
		3	53.1	42.4	37.0	32.8	24.5	17.6	14.0	10.8	8.4	6.1	89.1	32.	1287.
		4	53.5	43.0	37.6	32.9	26.9	20.2	16.2	12.8	9.4	9.1	37.7	-32.	910.
		5	70.3	57.1	50.8	45.0	35.5	26.5	21.6	17.2	13.4	11.3	14.8	30.	536.
11447	2	1	42.1	32.7	27.3	24.0	17.7	12.3	9.6	7.4	5.5	4.4	493.4	-20.	1549.
		2	50.5	39.5	33.3	29.4	21.9	15.5	12.2	9.4	7.1	5.7	160.5	37.	1511.
		3	52.2	41.0	34.6	30.5	23.3	16.9	13.5	10.6	8.3	6.7	53.6	-38.	1008.
		4	64.4	52.3	44.8	40.0	29.0	20.1	15.5	11.8	8.4	6.5	20.6	26.	648.
		5	66.4	54.4	47.1	42.2	32.9	24.5	19.6	16.1	12.6	10.5	17.4	12.	821.
11472	2	1	39.6	31.6	27.3	24.0	18.5	13.2	10.5	8.1	6.1	4.9	726.0	40.	1424.
		2	41.0	32.7	28.0	24.6	18.8	13.4	10.7	8.2	6.2	5.0	188.7	-30.	1110.
		3	59.6	48.4	42.5	38.3	30.4	22.5	18.3	14.3	10.7	8.6	64.4	41.	756.
		4	55.3	45.6	39.9	35.7	28.3	21.0	17.1	13.1	10.5	8.9	45.7	-24.	897.
		5	49.6	40.4	35.1	31.2	24.6	18.1	15.1	12.9	10.0	8.1	22.0	0.	648.
11497	2	1	38.6	30.0	25.6	22.7	17.0	11.9	9.5	7.7	6.2	5.0	379.7	-30.	917.
		2	55.5	44.9	38.7	34.6	26.6	19.4	15.1	9.9	6.0	4.7	87.1	17.	631.
		3	58.6	46.9	40.2	36.4	28.7	21.5	17.4	13.5	10.3	8.5	57.7	-5.	834.
		4	48.6	38.0	31.4	28.2	20.9	14.2	11.6	9.6	8.2	6.5	24.3	-6.	586.
11523	2	1	50.0	40.1	34.6	30.8	23.5	16.9	13.5	10.5	8.1	6.5	173.3	21.	770.
		2	55.6	44.2	38.1	34.0	26.0	18.7	15.0	11.7	8.8	7.0	78.9	-1.	1061.
		3	43.8	33.8	28.6	25.2	18.3	12.2	9.1	6.3	4.9	4.4	24.8	-11.	660.
11548	2	1	41.7	32.4	28.2	24.2	14.4	9.1	8.6	7.0	6.6	7.6	179.9	-30.	800.
		2	44.8	35.3	30.0	26.8	20.1	14.4	11.5	8.8	6.8	5.5	43.8	1.	589.
11575	2	1	36.3	28.8	24.2	21.0	15.9	11.1	8.7	6.8	5.2	4.1	102.9	15.	460.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA-LARA PROJECT

INDEX FILE : 4800W.IND
DATA FILE : 4800W.DAT

LINE NO. : 484

Station	Receive Dipole : Mode		M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
0825	2	1	14.2	11.6	10.0	9.0	7.0	5.1	4.0	3.1	2.3	1.9	174.3	16.	103.
		2	17.1	14.2	12.3	11.0	8.6	6.3	5.1	3.9	3.0	2.4	99.1	-7.	176.
		3	12.0	10.1	8.9	8.0	6.0	4.4	3.4	2.5	1.2	.9	34.1	12.	120.
		4	13.0	11.0	9.8	8.8	6.9	5.2	4.2	3.3	4.2	3.2	17.1	-9.	101.
		5	15.1	12.4	11.4	10.7	8.6	6.1	5.8	4.2	3.1	2.9	17.5	-9.	155.
850	2	1	17.9	14.5	12.7	11.5	8.1	6.6	5.4	4.2	3.2	2.6	486.2	-4.	212.
		2	12.5	10.3	8.9	8.1	6.4	4.7	3.8	2.9	2.2	1.8	98.3	-4.	129.
		3	13.1	10.9	9.7	8.7	6.9	5.0	3.9	3.1	2.3	1.8	42.5	4.	111.
		4	15.5	13.1	11.7	10.7	8.7	6.5	5.5	4.1	3.2	2.6	39.3	-10.	171.
		5	24.0	20.5	18.7	17.1	14.0	10.7	8.9	7.0	5.4	4.3	18.3	-10.	119.
875	2	1	10.9	8.8	7.5	6.7	5.1	3.8	3.0	2.3	1.8	1.4	171.7	-5.	86.
		2	12.7	10.4	9.0	8.1	6.3	4.4	3.6	2.8	2.0	1.6	67.5	10.	103.
		3	15.3	12.9	11.3	10.4	8.3	6.2	4.9	3.8	2.8	2.0	43.9	-20.	133.
		4	24.3	20.8	18.4	17.2	13.8	10.7	8.9	7.2	5.8	5.2	21.0	-5.	106.
		5	24.1	20.8	18.4	17.4	14.0	10.9	8.5	6.7	5.1	4.0	22.1	28.	167.
900	2	1	14.7	11.8	10.2	9.1	7.1	5.1	4.0	3.1	2.3	1.9	170.8	8.	107.
		2	17.4	14.5	12.8	11.6	9.2	6.9	5.6	4.4	3.3	2.6	105.5	-8.	198.
		3	25.9	22.0	19.7	18.0	14.6	11.1	8.8	7.0	5.4	4.0	34.6	-10.	130.
		4	27.6	23.5	20.9	19.3	15.7	11.8	10.1	7.9	6.3	5.7	30.5	27.	191.
		5	17.2	14.4	12.5	11.3	9.2	6.6	4.9	3.5	1.8	.5	11.3	-26.	106.
925	2	1	15.7	12.9	11.3	10.2	8.0	5.9	4.8	3.7	2.8	2.3	447.2	-12.	260.
		2	24.9	21.0	18.8	17.1	13.7	10.5	8.6	6.8	5.3	4.3	89.2	-11.	156.
		3	28.0	23.9	21.4	19.7	15.7	11.8	9.6	7.5	5.7	4.6	61.2	29.	212.
		4	18.6	15.8	14.2	13.0	10.2	7.5	5.9	4.6	3.5	3.3	19.3	-24.	112.
		5	10.7	8.1	6.7	5.5	4.6	3.0	3.6	2.3	1.8	.4	10.3	5.	89.
947	2	1	25.0	20.8	18.6	17.2	13.7	10.4	8.5	6.7	5.2	4.2	212.3	-6.	114.

		2	29.2	24.8	22.1	20.5	16.4	12.4	10.1	7.9	6.1	4.9	108.1	26.	175.
		3	20.6	17.6	15.7	14.5	11.7	8.9	7.1	5.5	4.1	3.1	33.7	-29.	109.
		4	15.0	11.1	9.2	8.8	8.2	5.4	5.2	3.4	2.8	2.0	15.9	13.	86.
		5	9.7	8.2	7.3	6.6	4.5	3.6	2.3	1.7	1.4	1.2	43.6	28.	353.
971	2	1	29.3	24.9	22.5	20.7	16.8	12.9	10.6	8.3	6.5	5.3	501.8	25.	225.
		2	24.8	21.4	19.6	18.0	14.6	10.9	9.0	7.0	5.3	4.1	96.6	-33.	130.
		3	16.1	14.0	12.8	11.4	9.6	7.4	5.9	4.5	3.8	3.5	37.0	12.	99.
		4	15.2	12.6	11.5	10.4	8.6	6.5	5.2	4.1	3.0	2.2	91.3	31.	409.
		5	12.7	10.5	9.4	8.2	6.9	5.2	4.2	3.2	2.4	1.9	96.4	-14.	648.
995	2	1	27.7	23.7	21.4	19.6	16.0	12.2	10.0	7.9	6.1	4.9	223.7	-28.	106.
		2	22.4	19.6	18.0	16.0	13.3	10.0	8.3	6.4	4.9	4.0	63.8	7.	91.
		3	19.4	16.4	14.7	13.5	10.8	8.1	6.6	5.1	3.8	3.0	132.7	32.	370.
		4	17.4	14.7	13.5	12.1	10.0	7.7	6.3	4.9	3.8	3.1	127.0	-14.	600.
		5	14.8	12.4	11.4	9.8	7.4	5.1	4.0	2.9	2.2	1.8	46.6	-10.	332.
1020	2	1	19.8	16.8	14.9	13.7	11.0	8.3	6.7	5.2	4.0	3.2	176.9	-3.	99.
		2	22.8	19.2	17.0	15.5	12.4	9.4	7.7	6.0	4.5	3.6	286.0	27.	481.
		3	19.9	16.9	15.0	13.8	11.1	8.2	6.6	5.2	4.0	3.2	210.8	-13.	700.
		4	19.0	15.9	14.1	12.8	10.3	7.9	6.3	4.5	2.7	2.1	63.6	-10.	356.
		5	22.7	18.8	16.6	15.2	12.5	9.4	7.6	6.1	5.0	4.1	87.9	-34.	739.
1045	2	1	19.7	16.1	14.1	12.8	10.0	7.4	5.9	4.6	3.5	2.8	1018.0	29.	580.
		2	17.8	14.9	13.2	12.1	9.5	7.1	5.7	4.4	3.3	2.6	361.5	-19.	619.
		3	15.1	12.9	11.5	10.6	8.3	6.1	4.9	3.7	2.8	2.1	106.3	3.	360.
		4	21.5	18.0	16.1	14.8	11.7	8.8	7.1	5.5	4.2	3.4	109.8	-5.	620.
		5	23.5	19.7	17.3	15.8	12.6	9.4	7.0	5.8	4.7	3.7	64.9	-11.	556.
1069	2	1	13.9	11.1	9.9	8.9	7.0	5.2	4.2	3.3	2.5	2.0	410.4	2.	234.
		2	13.3	10.8	9.9	8.9	7.0	5.1	4.0	2.9	2.1	1.6	135.3	-16.	231.
		3	18.9	15.1	13.7	12.7	9.9	7.3	5.9	4.5	3.4	2.7	128.4	24.	430.
		4	24.0	19.3	15.9	16.2	12.6	9.6	8.1	6.0	4.6	3.9	62.5	-26.	356.
		5	28.8	25.1	22.5	21.0	16.6	11.9	9.8	7.7	6.0	4.9	57.9	16.	495.
1094	2	1	9.1	7.1	6.1	5.4	4.1	2.9	2.2	1.6	1.2	.9	603.9	-16.	316.
		2	14.0	11.4	10.0	8.9	6.9	5.0	4.0	3.0	2.3	1.8	347.0	20.	544.
		3	20.2	16.9	15.1	13.5	10.8	8.1	6.6	5.1	3.9	3.2	142.9	-4.	440.
		4	27.3	22.9	20.4	18.2	14.5	10.8	8.8	6.8	5.2	4.1	87.4	-3.	457.
		5	38.5	32.4	28.5	25.7	20.6	15.2	12.4	9.7	7.5	6.1	94.8	27.	744.
1119	2	1	22.3	17.8	15.2	13.7	10.6	7.7	6.2	4.8	3.7	3.0	974.4	20.	826.
		2	25.4	21.2	18.4	16.5	13.1	9.7	7.9	6.1	4.7	3.9	261.6	-8.	666.
		3	30.5	25.3	22.1	19.8	15.9	11.8	9.6	7.5	5.7	4.7	125.3	-13.	630.
		4	40.5	33.6	29.4	26.4	21.0	15.5	12.6	9.8	7.6	6.2	110.2	29.	930.
		5	52.9	43.3	38.6	34.6	27.0	20.1	16.6	12.8	9.7	7.9	56.9	-42.	724.
1140	2	1	29.9	24.8	21.7	19.8	15.7	11.7	9.5	7.5	5.8	4.7	1635.0	-13.	850.
		2	34.8	29.1	25.6	23.3	18.5	13.9	11.2	8.9	6.9	5.6	516.9	6.	811.
		3	44.1	36.7	32.3	29.4	23.3	17.4	14.1	11.1	8.5	6.9	407.7	10.	1270.

		4	60.9	51.2	45.2	41.0	32.5	24.3	19.7	15.6	11.9	9.6	112.8	-23.	590.
		5	65.6	54.9	48.4	44.0	35.3	26.7	21.6	17.1	13.4	11.1	126.9	21.	990.
1160	2	1	31.4	25.7	22.5	20.3	15.9	11.7	9.5	7.4	5.7	4.6	3037.0	-20.	1640.
		2	39.5	32.3	28.3	25.5	20.1	14.9	12.0	9.4	7.3	5.9	1345.0	17.	2180.
		3	53.8	46.1	41.2	37.5	29.8	22.4	18.2	14.4	11.2	9.1	321.8	-24.	1040.
		4	68.3	57.2	50.6	46.1	36.9	27.8	22.8	18.0	14.0	11.5	231.7	4.	1250.
		5	66.1	55.5	49.2	44.8	35.9	27.1	22.2	17.7	13.9	11.4	153.8	21.	1240.
1185	2	1	36.9	30.3	26.3	23.5	18.5	13.6	10.9	8.5	6.5	5.3	4070.0	2.	3540.
		2	51.3	44.3	39.3	35.8	28.4	21.3	17.4	13.5	10.5	8.6	638.2	-18.	1669.
		3	67.7	57.6	51.2	46.4	37.0	27.8	22.6	17.9	13.9	11.4	267.0	-8.	1390.
		4	66.4	56.0	49.5	45.0	35.7	26.9	21.8	17.3	13.8	11.2	168.0	21.	1460.
		5	70.4	58.4	51.1	45.9	37.5	29.2	24.5	20.2	14.6	12.6	87.2	-10.	1140.
1210	2	1	58.9	48.4	42.5	38.5	30.1	22.3	18.0	14.1	10.9	8.8	1647.0	-27.	2870.
		2	72.1	60.3	53.4	48.5	38.3	28.6	23.1	18.2	14.1	11.5	469.0	-12.	2454.
		3	70.9	59.3	52.7	47.8	37.9	28.4	23.1	18.2	14.2	11.5	210.5	22.	2190.
		4	74.9	62.6	55.8	50.9	40.5	30.1	25.1	19.6	15.4	12.4	86.2	-15.	1503.
		5	62.8	52.8	46.1	42.0	32.8	27.8	20.9	17.5	13.2	11.7	26.8	15.	701.
1230	2	1	66.1	54.0	47.1	42.5	33.0	24.2	19.4	15.1	11.6	9.3	2555.0	-47.	5340.
		2	69.1	57.0	50.0	45.2	35.3	26.1	21.0	16.4	12.6	10.2	677.9	23.	4257.
		3	75.3	62.7	55.3	50.1	39.4	29.4	23.9	18.7	14.5	11.8	186.2	-20.	2330.
		4	64.8	54.6	48.8	44.5	35.8	26.5	21.7	17.4	13.4	11.0	38.8	17.	812.
		5	64.8	51.3	44.7	40.5	31.7	23.7	19.6	15.4	12.2	10.0	11.2	-21.	350.
1256	2	1	57.6	46.8	40.8	36.6	28.4	20.8	16.6	12.9	9.9	8.0	1997.0	13.	5700.
		2	67.1	55.2	48.5	43.7	34.1	25.1	20.2	15.8	12.2	9.8	400.4	-26.	3428.
		3	57.3	48.8	43.4	39.2	31.1	23.4	18.8	14.9	11.7	9.3	53.4	25.	912.
		4	55.3	46.2	40.7	36.8	29.4	21.9	18.2	14.1	10.8	9.6	11.7	-26.	334.
		5	69.1	57.2	50.4	44.9	36.2	27.0	22.1	17.7	13.6	11.1	17.5	5.	748.
1280	2	1	54.8	44.3	38.6	34.6	26.7	19.4	15.5	12.0	9.1	7.3	2389.0	-40.	12500.
		2	45.6	38.6	34.3	31.1	24.3	17.9	14.4	11.3	8.7	7.0	177.8	20.	2790.
		3	32.3	28.0	25.1	23.1	18.3	13.8	11.2	9.0	7.2	5.9	19.3	-23.	600.
		4	57.4	48.4	42.0	38.8	30.7	24.0	18.8	15.3	12.1	10.4	18.6	-2.	970.
		5	59.6	49.0	44.1	41.4	31.9	23.4	19.4	15.4	12.6	9.9	15.3	-15.	1200.
1305	2	1	43.1	34.9	30.3	27.4	21.0	15.3	12.2	9.5	7.3	5.8	1558.0	12.	6900.
		2	26.5	21.5	18.8	16.9	13.1	9.8	7.8	6.1	4.7	3.8	101.4	-25.	1360.
		3	41.3	35.1	30.9	28.1	22.5	17.8	14.3	10.8	8.2	7.0	55.0	-1.	1470.
		4	48.5	40.5	36.0	32.4	26.2	18.5	15.5	12.6	10.5	8.4	36.3	-23.	1620.
		5	59.9	49.6	44.3	39.7	32.6	18.4	14.5	17.0	11.4	6.9	42.5	13.	2860.
1330	2	1	23.8	19.1	16.5	14.7	11.3	8.2	6.6	5.1	3.9	3.1	321.4	-21.	1440.
		2	38.1	31.0	27.1	24.2	18.8	13.8	11.0	8.6	6.6	5.3	115.6	-3.	1550.
		3	42.4	35.8	31.9	28.6	22.6	16.7	13.8	10.9	8.4	6.7	63.4	-20.	1700.
		4	54.4	45.4	40.9	37.4	28.9	21.8	17.3	13.4	10.5	8.5	63.2	6.	2830.
		5	63.5	53.1	46.2	40.9	33.1	24.7	19.8	16.0	11.7	9.6	27.4	-12.	1840.

1355	2	1	28.9	23.3	20.1	18.1	13.9	10.3	8.2	6.5	5.1	4.0	348.6	4.	1360.
		2	36.6	30.7	27.0	24.6	19.2	14.2	11.3	8.7	6.5	5.3	145.1	-30.	1700.
		3	47.5	40.1	35.4	31.9	24.8	18.9	15.1	11.8	9.1	7.4	117.1	13.	2700.
		4	57.4	47.8	42.3	38.7	30.6	22.2	18.0	14.3	10.9	8.6	46.0	-15.	1800.
		5	64.4	53.8	46.7	42.5	32.9	24.2	19.6	15.0	11.4	9.1	26.1	25.	1530.
1380	2	1	31.8	25.4	22.0	19.8	15.4	11.3	9.1	7.1	5.5	4.4	329.5	-26.	1290.
		2	42.2	34.7	30.2	27.3	21.4	15.9	12.8	10.1	7.8	6.2	185.0	20.	2170.
		3	51.2	43.9	38.1	34.5	27.1	20.1	16.4	13.0	9.9	8.1	60.2	-22.	1410.
		4	61.4	50.5	44.6	41.1	32.7	24.5	19.4	15.1	11.9	9.2	32.5	22.	1270.
		5	52.5	43.0	37.0	34.5	27.3	19.8	16.0	12.5	10.2	7.4	11.8	-4.	690.
1405	2	1	36.7	29.0	24.9	22.3	17.2	12.6	10.1	7.9	6.1	4.9	623.0	16.	2790.
		2	43.4	37.2	32.8	29.8	23.4	17.5	14.2	11.3	8.9	7.3	118.5	-26.	1590.
		3	54.1	45.1	39.4	35.9	28.5	21.4	17.4	13.9	10.9	9.0	49.6	25.	1330.
		4	49.0	40.0	34.8	31.8	25.4	19.2	15.8	13.0	10.8	9.2	16.4	-8.	730.
		5	54.7	45.5	40.6	36.8	30.1	23.0	19.0	16.1	12.6	11.0	13.5	5.	900.
1430	2	1	40.3	32.9	28.8	26.0	20.2	14.9	12.0	9.4	7.3	5.9	1270.0	-35.	3320.
		2	43.4	35.9	31.4	28.6	22.4	16.6	13.4	10.5	8.1	6.5	246.8	25.	1937.
		3	32.0	28.3	25.2	23.3	18.8	14.4	11.6	9.3	7.2	6.0	65.4	-26.	1025.
		4	44.0	36.6	32.3	29.5	22.8	16.7	13.5	10.4	8.1	6.3	41.7	20.	1091.
		5	60.2	50.2	44.1	40.3	31.8	24.0	19.4	15.4	12.0	9.8	38.1	-5.	1496.
1455	2	1	45.9	37.0	32.1	28.7	22.2	16.2	12.9	10.0	7.7	6.1	714.1	6.	2880.
		2	38.5	32.4	28.5	25.7	20.1	14.6	11.6	9.0	6.9	5.4	148.7	-23.	1750.
		3	42.4	35.2	30.6	27.9	21.8	16.2	13.1	10.3	8.0	6.4	83.2	18.	1950.
		4	57.9	47.7	40.9	37.6	29.4	21.6	17.4	13.5	10.3	8.1	51.6	-10.	2020.
		5	87.1	72.7	63.3	58.6	45.8	35.0	28.1	22.6	17.3	14.5	21.7	6.	1270.
1480	2	1	33.9	27.6	23.8	21.2	16.4	12.0	9.6	7.4	5.6	4.6	592.2	-47.	1690.
		2	40.3	33.2	28.8	25.8	20.3	14.8	11.9	9.4	7.2	5.7	210.1	9.	1799.
		3	56.6	47.1	41.3	37.2	29.3	21.8	17.6	13.8	10.7	8.7	143.1	31.	2440.
		4	84.0	70.1	61.7	55.6	43.9	32.9	26.5	20.8	16.3	13.3	45.2	-8.	1289.
		5	66.2	55.9	49.4	44.6	36.4	27.2	22.8	18.1	14.0	11.3	17.2	7.	738.
1505	2	1	38.8	30.8	26.9	24.0	18.3	13.3	10.6	8.2	6.2	5.0	388.3	-9.	2030.
		2	55.3	44.8	39.3	35.4	27.4	20.1	16.1	12.5	9.6	7.8	168.6	24.	2640.
		3	82.0	68.1	60.5	54.9	43.1	32.1	26.6	21.1	16.8	13.9	46.1	0.	1440.
		4	61.5	48.8	43.1	38.4	30.7	23.3	15.6	11.8	8.3	6.5	15.4	1.	800.
1530	2	1	50.0	40.7	35.3	31.4	24.3	17.8	14.2	11.1	8.5	6.8	206.2	1.	1610.
		2	76.4	63.1	55.8	49.9	39.3	29.1	23.5	18.4	14.2	11.5	43.7	0.	1028.
		3	55.7	47.0	41.9	37.5	29.5	22.2	17.8	14.3	12.3	10.2	12.7	6.	590.
1555	2	1	68.2	56.2	49.4	44.4	35.0	25.9	20.9	16.4	12.6	10.2	282.0	7.	804.
		2	50.9	42.2	37.8	34.3	27.5	20.6	17.0	13.5	10.3	8.2	71.4	3.	611.
1580	2	1	41.9	33.8	29.7	26.9	21.1	15.6	12.6	9.9	7.7	6.1	265.2	3.	1380.

IPR-11 DATA SUMMARY

SURVEY : MINNOVA-LARA PROJECT

INDEX FILE : 4700W.IND
DATA FILE : 4700W.DAT

LINE NO. : 474

Station	Receive Mode	Dipole :	M0	M1	M2	M3	M4	M5 mV/V	M6	M7	M8	M9	Vp mV	SP mV	Apparent Resist.
10 825	2	1	12.5	10.3	9.1	8.2	6.5	4.8	3.9	3.0	2.3	1.8	292.2	-28.	176.
		2	20.4	17.2	15.2	13.9	11.1	8.3	6.7	5.3	4.1	3.3	213.1	33.	386.
		3	14.1	12.4	11.2	10.3	8.3	6.3	5.2	4.1	3.3	2.7	40.5	-12.	146.
		4	14.1	11.7	10.2	9.3	7.2	5.2	4.1	3.0	2.1	1.7	39.0	12.	235.
		5	14.4	11.9	10.5	9.6	7.3	5.3	4.3	3.4	2.5	2.0	22.4	-4.	202.
850	2	1	16.6	13.3	11.9	10.7	8.4	6.3	5.1	4.0	3.1	2.5	490.6	11.	296.
		2	12.1	10.1	9.2	8.4	6.7	5.0	4.1	3.3	2.6	2.2	64.9	-22.	118.
		3	12.5	10.1	9.2	8.3	6.4	4.7	3.6	2.8	2.1	1.7	53.8	21.	194.
		4	14.5	11.6	10.7	9.5	7.6	5.7	4.8	3.8	2.9	2.3	28.0	-1.	169.
		5	16.0	13.1	12.2	10.8	8.8	5.8	4.9	3.2	2.4	1.8	14.4	10.	130.
875	2	1	10.6	8.6	7.5	6.8	5.3	3.9	3.1	2.4	1.8	1.4	149.4	-13.	78.
		2	12.9	10.7	9.3	8.5	6.5	4.7	3.8	2.9	2.2	1.8	113.2	21.	177.
		3	14.1	11.8	10.4	9.6	7.3	5.3	4.2	3.2	2.6	2.1	50.3	-7.	157.
		4	17.3	14.5	12.6	11.6	9.2	6.7	5.1	4.0	2.8	2.0	22.6	12.	118.
		5	23.2	19.5	17.6	16.2	13.2	10.7	8.5	6.8	5.3	4.0	20.2	-9.	158.
900	2	1	17.0	14.2	12.4	11.3	8.9	6.6	5.3	4.2	3.2	2.5	504.4	15.	239.
		2	18.6	15.6	13.7	12.5	10.0	7.4	5.9	4.6	3.5	2.8	163.6	-13.	233.
		3	19.6	16.9	15.0	13.7	10.8	8.1	6.6	5.1	4.0	3.1	55.6	19.	158.
		4	26.2	22.6	20.2	18.6	15.0	11.4	9.2	7.1	5.3	4.4	41.0	-10.	194.
		5	25.1	21.7	19.4	18.0	14.6	11.2	9.1	7.0	5.3	4.3	33.8	9.	241.
925	2	1	16.8	13.9	12.4	11.2	8.9	6.6	5.3	4.2	3.2	2.5	409.4	-13.	178.
		2	19.5	16.3	14.7	13.4	10.6	7.9	6.3	4.9	3.6	3.1	102.1	9.	133.
		3	24.7	21.4	19.3	17.9	14.4	11.0	9.1	7.1	5.4	4.3	64.7	-5.	168.
		4	24.9	21.3	19.3	17.7	14.2	10.7	8.7	6.8	5.1	4.1	47.8	9.	208.
		5	23.8	20.4	18.6	17.2	12.9	11.2	7.8	6.8	4.7	4.1	33.3	0.	217.
950	2	1	15.5	12.9	11.2	10.1	8.0	5.9	4.8	3.7	2.8	2.2	281.5	24.	117.

		2	22.8	19.4	17.3	15.8	12.8	9.7	7.9	6.2	4.7	3.9	126.1	-18.	158.
		3	24.1	20.8	18.5	16.9	13.8	10.4	8.5	6.6	5.0	4.0	78.0	11.	195.
		4	25.3	21.7	19.2	17.4	14.0	10.4	8.5	6.6	5.0	4.1	49.3	3.	206.
		5	18.8	16.0	13.9	12.5	10.2	7.4	6.0	4.5	3.3	2.6	43.8	11.	275.
975	2	1	20.7	17.6	15.6	14.3	11.4	8.6	6.9	5.5	4.2	3.3	328.5	2.	187.
		2	24.6	20.9	18.6	17.1	13.7	10.3	8.3	6.6	4.9	3.9	128.8	7.	220.
		3	25.8	21.9	19.4	17.7	14.1	10.6	8.5	6.6	5.0	3.9	68.5	2.	234.
		4	20.7	17.2	15.1	13.7	10.9	8.1	6.3	4.8	3.6	2.8	55.4	9.	316.
		5	15.6	12.4	11.7	12.0	8.0	5.8	4.7	3.8	2.6	1.9	36.5	-34.	312.
1000	2	1	25.5	21.7	19.3	17.4	14.1	10.6	8.5	6.7	5.1	4.1	387.6	8.	196.
		2	27.8	23.5	21.0	19.0	15.2	11.4	9.3	7.2	5.2	4.0	154.3	-1.	234.
		3	21.8	18.4	16.2	14.6	11.6	8.5	6.6	5.1	4.3	3.6	107.4	9.	320.
		4	17.4	14.8	13.1	11.6	9.3	7.0	5.6	4.2	3.2	2.5	63.8	-35.	323.
		5	11.1	10.0	9.0	8.4	6.7	5.0	3.8	3.2	2.4	1.8	43.9	26.	333.
1025	2	1	28.1	22.2	21.2	19.1	15.2	11.5	9.3	7.3	5.6	4.4	722.6	1.	302.
		2	24.8	20.9	18.6	17.0	13.5	10.1	8.2	6.4	4.8	3.9	359.8	6.	451.
		3	20.6	17.6	15.7	14.3	11.5	8.7	7.0	5.5	4.2	3.3	176.0	-32.	440.
		4	15.0	13.1	11.8	10.9	8.8	6.6	5.4	4.2	3.2	2.5	105.9	20.	440.
		5	18.1	15.5	13.9	12.9	10.2	7.7	6.3	4.9	3.8	3.0	78.4	6.	492.
1047	2	1	22.7	18.1	16.0	14.4	11.2	8.2	6.6	5.1	3.9	3.1	1135.0	13.	640.
		2	18.4	15.1	13.4	12.3	9.8	7.3	5.9	4.6	3.5	2.8	387.5	-35.	663.
		3	13.8	11.7	10.6	9.7	7.8	5.9	4.8	3.8	2.9	2.3	190.0	26.	640.
		4	17.3	14.4	13.1	12.0	9.7	7.3	6.0	4.7	3.7	3.0	102.0	7.	580.
		5	20.8	17.3	15.7	14.3	11.6	8.9	7.1	5.6	4.5	3.6	63.9	-17.	547.
1072	2	1	21.4	16.8	14.7	13.3	10.3	7.4	5.9	4.6	3.5	2.8	1436.0	-41.	800.
		2	14.1	11.4	10.2	9.2	7.3	5.3	4.3	3.3	2.6	2.0	539.1	26.	906.
		3	15.7	12.8	11.5	10.5	8.3	6.1	4.9	3.8	3.0	2.4	224.5	-6.	750.
		4	17.2	13.9	12.6	11.6	9.2	6.7	5.5	4.2	3.0	2.4	80.3	-6.	449.
		5	16.4	13.2	12.2	11.3	8.9	6.6	5.2	4.1	3.1	2.7	43.2	-27.	363.
1097	2	1	11.5	9.1	8.0	7.3	5.6	4.1	3.3	2.5	1.9	1.5	923.8	-1.	402.
		2	14.4	11.8	10.3	9.5	7.3	5.4	4.3	3.3	2.5	2.0	532.3	-10.	696.
		3	13.2	10.9	9.6	8.9	6.9	5.1	4.1	3.2	2.5	2.0	154.9	2.	400.
		4	17.7	15.0	13.5	12.5	9.0	7.2	5.3	4.1	3.0	2.3	54.9	-29.	239.
		5	32.5	27.4	24.3	22.3	18.1	13.5	11.2	8.8	6.8	5.5	159.2	35.	1040.
1122	2	1	10.8	8.6	7.4	6.7	5.1	3.7	2.9	2.2	1.7	1.3	1525.0	4.	920.
		2	9.6	7.8	6.6	6.0	4.6	3.3	2.5	1.9	1.5	1.1	305.1	2.	552.
		3	14.8	12.4	10.8	9.8	7.8	5.8	4.6	3.5	2.7	2.2	112.3	-35.	400.
		4	35.0	29.5	26.1	23.9	19.0	14.4	11.7	9.3	7.2	5.8	197.2	36.	1190.
		5	29.5	24.9	21.9	20.2	16.3	12.4	10.2	8.1	6.3	5.1	93.4	1.	846.
1150	2	1	7.4	5.7	4.9	4.4	3.3	2.3	1.8	1.3	1.0	.8	616.9	-2.	345.
		2	16.5	13.5	11.9	10.9	8.5	6.3	5.1	4.1	3.1	2.4	191.1	-37.	321.
		3	36.9	31.1	27.8	25.4	20.4	15.4	12.6	9.9	7.8	6.4	298.6	35.	1000.

		4	31.9	26.9	24.0	22.3	17.9	13.7	11.3	8.5	6.9	5.6	129.4	-2.	720.
		5	25.7	21.4	19.2	17.6	13.8	10.4	8.6	6.4	5.2	4.2	97.4	-2.	819.
1175	2	1	32.0	25.4	22.3	20.0	15.8	11.7	9.4	7.3	5.6	4.6	1275.0	-39.	810.
		2	58.1	48.9	43.5	39.5	31.6	23.9	19.5	15.5	12.0	9.8	841.7	26.	1618.
		3	53.3	45.7	41.0	37.5	30.4	23.3	19.2	15.3	11.9	9.8	247.4	-16.	940.
		4	43.5	36.7	32.5	29.7	23.9	18.1	15.0	11.9	9.3	7.5	154.5	0.	990.
		5	46.7	39.5	34.5	31.3	25.3	18.9	15.9	13.1	9.5	7.8	133.0	-3.	1270.
1200	2	1	56.6	47.2	42.0	38.3	30.4	22.9	18.7	14.7	11.5	9.3	1802.0	-11.	1250.
		2	60.4	51.4	46.1	42.4	34.2	26.1	21.5	17.1	13.4	11.0	462.5	-29.	968.
		3	49.3	41.8	37.5	34.4	27.6	21.1	17.3	13.8	10.8	8.8	221.3	2.	920.
		4	53.4	45.1	40.2	36.4	29.3	22.2	18.2	14.5	11.4	9.3	198.0	0.	1380.
		5	68.1	57.4	51.3	46.1	37.1	27.8	22.9	18.1	14.0	11.4	164.6	9.	1720.
1225	2	1	51.4	43.6	38.9	35.4	28.5	21.8	17.9	14.2	11.2	9.2	791.0	-19.	577.
		2	45.3	38.3	34.0	31.0	25.1	19.1	15.7	12.5	9.8	8.1	315.3	13.	690.
		3	50.8	43.1	38.4	35.0	27.8	21.1	17.3	13.7	10.7	8.8	252.3	-16.	1100.
		4	66.4	55.8	49.6	45.1	35.8	27.1	22.1	17.5	13.7	11.2	207.1	6.	1510.
		5	67.0	56.7	50.5	46.0	36.7	27.8	22.7	18.1	14.2	11.7	101.2	46.	1100.
1250	2	1	28.9	23.9	21.3	19.1	15.2	11.5	9.4	7.4	5.7	4.7	1001.0	13.	780.
		2	41.4	34.5	30.6	27.6	22.0	16.4	13.4	10.6	8.3	6.8	531.9	-20.	1252.
		3	58.9	49.3	43.9	39.5	31.6	23.7	19.4	15.3	11.9	9.8	375.9	34.	1760.
		4	68.0	57.1	50.9	46.1	36.8	27.7	22.6	18.0	14.0	11.4	150.5	14.	1180.
		5	67.8	56.8	50.9	46.4	37.2	28.2	23.0	18.2	13.9	11.3	91.3	-17.	1075.
1275	2	1	35.9	29.6	26.1	23.4	18.5	13.8	11.1	8.8	6.8	5.5	2602.0	-19.	2150.
		2	54.9	45.7	40.5	36.4	29.0	21.7	17.6	13.9	10.8	8.8	627.5	7.	1555.
		3	62.4	52.5	46.9	42.2	33.8	25.4	20.8	16.5	12.8	10.5	241.7	40.	1190.
		4	65.8	55.4	49.6	44.7	36.1	27.3	22.5	18.0	14.3	11.8	130.4	-21.	1070.
		5	68.0	57.6	51.9	46.9	38.1	29.1	24.0	19.1	14.9	12.2	94.3	-1.	1169.
1297	2	1	56.7	47.3	41.3	37.4	29.5	22.0	17.8	14.0	10.8	8.8	3114.0	-19.	2320.
		2	62.5	53.1	46.8	42.7	33.9	25.5	20.8	16.4	12.8	10.5	439.8	5.	986.
		3	64.8	55.2	48.9	44.7	35.8	27.2	22.2	17.7	13.9	11.4	203.6	11.	910.
		4	67.7	57.6	51.2	46.9	37.7	28.8	23.6	18.8	14.8	12.2	139.5	0.	1040.
		5	61.8	52.7	46.9	42.8	34.6	26.6	21.9	17.6	13.8	11.4	38.7	0.	433.
1325	2	1	65.0	53.7	47.2	42.5	33.3	24.9	20.1	15.8	12.3	10.0	266.6	2.	1040.
		2	72.7	60.9	53.9	48.7	38.7	29.2	23.8	18.9	14.7	12.1	70.9	15.	834.
		3	74.0	62.7	55.8	50.3	40.4	30.7	25.0	20.0	15.6	12.8	44.0	6.	1030.
		4	68.6	58.1	52.4	46.8	38.2	29.0	23.9	19.4	15.1	13.0	10.5	-8.	410.
		5	79.8	67.6	60.5	52.8	42.7	33.4	26.9	21.7	16.7	13.9	12.5	11.	730.
1350	2	1	68.0	56.3	49.6	44.9	35.3	26.3	21.2	16.7	12.9	10.5	530.9	-17.	1111.
		2	72.9	61.0	54.0	49.2	39.1	29.4	24.0	19.0	14.9	12.1	197.8	2.	1242.
		3	69.2	58.4	51.9	47.4	37.9	28.6	23.4	18.5	14.5	11.9	35.2	-5.	440.
		4	83.1	70.2	62.5	57.2	45.7	34.5	28.3	22.5	17.5	14.3	37.3	9.	780.
		5	93.3	79.1	70.3	64.5	51.5	38.9	31.9	25.2	19.7	16.2	42.9	-23.	1346.

1372	2	1	39.0	32.5	28.3	25.6	20.1	15.0	12.0	9.5	7.3	5.9	1874.0	-10.	3090.
		2	47.3	40.0	35.3	32.1	25.5	19.2	15.6	12.4	9.6	7.9	151.5	-5.	751.
		3	67.3	57.8	51.3	46.7	37.4	28.2	23.2	18.4	14.5	11.8	122.1	7.	1200.
		4	89.9	76.2	67.9	61.9	49.7	38.0	31.0	24.9	19.5	16.1	118.3	-21.	1950.
		5	63.2	54.3	48.6	44.3	35.7	27.6	22.9	18.4	14.6	12.1	40.3	-12.	998.
1397	2	1	34.6	28.1	24.8	22.3	17.4	12.9	10.3	8.1	6.3	5.1	327.8	-4.	735.
		2	53.2	44.2	39.3	35.5	28.2	21.1	17.1	13.5	10.6	8.6	158.0	10.	1063.
		3	82.4	69.2	61.9	56.1	44.9	33.9	27.6	21.9	17.2	13.9	121.7	-31.	1630.
		4	62.4	52.8	47.2	42.6	34.4	26.6	21.9	17.2	13.6	11.5	34.6	-7.	775.
		5	51.4	43.6	39.1	35.4	28.6	21.9	18.0	14.5	11.2	9.1	39.8	-7.	1339.
1422	2	1	32.7	27.0	23.7	21.3	16.7	12.4	10.0	7.9	6.1	4.9	1145.0	6.	2390.
		2	67.7	56.8	50.2	45.6	36.1	27.2	22.0	17.4	13.6	11.1	385.9	-34.	2423.
		3	56.2	48.2	43.1	39.3	31.6	24.3	19.9	15.7	12.3	10.2	70.2	-1.	880.
		4	49.7	42.1	37.4	34.0	27.1	20.8	17.0	13.5	10.6	8.7	70.3	-11.	1471.
		5	77.2	65.3	58.2	52.7	42.3	32.3	26.6	21.3	16.8	14.1	51.7	3.	1622.
1447	2	1	54.6	45.4	39.8	36.0	28.4	21.1	17.0	13.4	10.3	8.4	1029.0	-32.	2010.
		2	50.9	43.1	38.6	35.1	28.3	21.5	17.4	14.1	11.0	9.2	116.7	-17.	687.
		3	45.1	38.9	35.1	31.9	25.8	19.9	16.3	13.1	10.2	8.4	100.6	0.	1180.
		4	73.7	62.2	55.7	50.3	40.3	30.4	24.6	19.8	15.6	12.8	69.4	3.	1361.
		5	76.3	64.7	58.6	53.3	42.6	32.4	26.2	21.3	16.6	13.6	47.6	3.	1401.
1472	2	1	37.7	30.7	27.1	24.5	19.2	14.2	11.5	9.0	7.0	5.7	501.1	-14.	1740.
		2	39.3	32.2	28.5	25.6	20.2	15.0	12.2	9.5	7.4	6.0	196.7	-7.	2050.
		3	68.2	57.1	50.7	45.8	36.4	27.2	22.1	17.4	13.5	11.0	95.2	9.	1980.
		4	75.6	62.9	56.0	50.5	40.5	30.8	24.8	19.6	15.3	12.5	55.7	0.	1940.
		5	71.1	61.9	53.4	48.0	37.9	28.7	24.7	18.2	14.7	11.6	14.8	9.	770.
1497	2	1	31.3	25.2	21.8	19.7	15.4	11.3	9.1	7.1	5.5	4.4	1048.0	-10.	2740.
		2	62.1	51.6	45.5	41.3	32.6	24.2	19.6	15.4	11.9	9.7	374.2	2.	2937.
		3	71.4	59.6	52.8	48.1	38.2	28.5	23.3	18.4	14.4	11.7	181.1	4.	2830.
		4	69.2	57.8	51.0	46.7	37.2	28.6	23.0	18.2	14.2	11.6	43.3	8.	1132.
1525	2	1	49.6	40.5	35.4	32.1	25.0	18.4	14.9	11.6	9.0	7.2	1454.0	-8.	5000.
		2	67.3	55.6	49.0	44.4	34.9	26.0	21.0	16.5	12.8	10.4	291.0	5.	3040.
		3	59.0	49.9	44.8	41.2	32.9	25.0	20.4	16.2	12.6	10.2	54.7	4.	1140.
1550	2	1	73.7	61.3	53.9	48.6	38.4	28.4	22.9	18.0	13.9	11.3	1637.0	-10.	3420.
		2	61.4	51.8	45.9	41.7	33.4	25.0	20.3	16.0	12.4	10.0	203.6	4.	1278.
1575	2	1	73.7	60.6	52.7	47.6	36.9	27.0	21.8	17.0	13.0	10.5	713.1	1.	3730.