

1710- 609 GRANVILLE ST
 PO BOX 10363
 VANCOUVER BC
 CANADA V7Y 1G5
 (604) 683-7265 FAX 683-5306

George Cross News Letter

"Reliable Reporting"
 WESTERN CANADIAN INVESTMENTS

COPYRIGHT
 ALL REPRODUCTION
 RIGHT RESERVED
 PUBLISHED DAILY
 SUBSCRIPTION RATE
 \$315.00 PER YEAR

NO. 159 (1993)
 AUGUST 19, 1993

NO. 159 (1993)
 AUGUST 19, 1993

LIBRARY
 AUG 27 1993
 DEPARTMENT OF ENERGY, MINES
 AND TECHNICAL RESOURCES

NEWHAWK GOLD MINES LTD. [NHG-V]

HOLE NO.	STRUCTURE	INTERVAL METRES	LENGTH METRES	AU OZ/T	AG OZ/T
93-411 (171.6m)	G-5	32.3-35.3	3.0	0.145	4.58
	G-7	80.0-83.0	3.0	.123	.44
	-	94.5-95.5	1.0	.483	1.02
	*G-8	148.8-150.8	2.0	.756	18.67
93-412 (141.7m)	G-5	1.4-1.9	.5	.429	12.83
	*G-8	133.2-136.2	3.0	1.652	1.25
	or	133.2-139.2	6.0	.867	.83
93-413 (102.1m)	G-5	21.0-21.9	.9	.510	3.70
	G-6	37.2-40.2	3.0	.241	-
93-414 (163.7m)	G-4	13.5-16.5	3.0	.102	1.32
	G-1	133.1-135.3	2.2	.162	2.00
93-415 (124.4m)	G-3	33.2-36.2	3.0	.227	.44
	-	41.2-42.2	1.0	.204	.20
	-	55.9-60.1	4.2	.124	.33

MORE SULPHURETS DRILL RESULTS - Newhawk Gold Mines Ltd. has reported further results from

the current surface diamond drilling program in progress at the Sulphurets property, located 60 km north of Stewart in northwestern B.C. On the 60%-owned Bruce side portion of the property, drilling has continued to test the SG and Galena Hill Zones with 16 holes totalling 2,178 metres to date. **GRANDUC MINES LTD.** [GDC-V.T] owns the other 40% interest. Additional results are in table above. The Galena Hill zone is composed of a series of parallel structures referred to as G-1 to G-8. Holes 93-411 and 412 were drilled to test the G-8 structure, at the northern end of Galena Hill and 500 metres southeast of the West Zone. Holes 93-413, 414 and 415 were drilled along the zone and were designed to test other structures southerly and parallel to G-8.

The above holes tested various structures within the Galena Hill zone over a strike length of 300 metres, and a vertical distance of 100 metres. The G-8 structure appears to be developing as a distinct higher grade vein and two additional holes have been drilled to define its continuity and grade. As well, two holes have been drilled on other structures within the zone. Results are forthcoming.

One additional hole (93-417) was drilled to a depth of 188.4 metres to provide a deeper test of the SG zone. No significant results were obtained. The SG zone appears to be a strong continuous structure with gold values in the 0.25 oz/ton range and further geological interpretation is needed to define its potential. Prospecting and field mapping are continuing on other zones on the property to define possible drill targets. Drilling is planned shortly on the high grade

104B 193

PM-4 and Tommyknocker zones on Gossan Hill.

At the Snowfield property, two holes totalling 768 metres have been completed to test the potential for higher grade at depth and to examine the zone to the southeast. No assay results have been received to date. A third deep hole has just begun and three holes totalling 275 metres have been laid out to test the high grade Josephie Zone at the southern edge of Snowfield. Work on both properties is expected to continue until late September. (SEE GCNL NO.152, 10Aug93, P.4 FOR PREVIOUS PROJECT INFORMATION)